

[illegible]

11/29/2000 8:08:29 AM

```
1: <cfparam name="lFormat" default="False">
2:
3:
4: <cfif lFormat is True>
5:   <cfoutput>#qryFormat.sideCode#</cfoutput>
6: <cfelse>
7:   &nbsp;
8: </cfif>
```



```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3: <!-- If a Type ID is not passed, then exit -->
4: <cfif not isdefined("URL.agency_id")>
5:   <cflocation url="index.cfm" addtoken="no">
6: </cfelse>
7:   <cfset nTypeID = URL.agency_id>
8: </cfif>
9:
10:  <cfif not isdefined("URL.Region")>
11:    <cfset URL.Region="*">
12:  </cfif>
13:
14:  <cfquery name="qryAgency" datasource="#SourceName#">
15:    SELECT *
16:    FROM Agency
17:    WHERE Agency.agency_id = #nTypeID#
18:  </cfquery>
19:
20:  <!-- Set these for the page counter -->
21:  <cfset nTargetID=#nTypeID#>
22:  <cfset cPageType="Agency">
23:  <cfinclude template="..\common\srvPageCounter.cfm">
24:
25:  <!-- Parameter names for the fields -->
26:  <CFQUERY NAME="qryParamNames" DATASOURCE="#SourceName#">
27:    SELECT
28:      DISTINCT id, name, description, label, displayorder, restrictions, type, selectOptions
29:    FROM param_defs
30:    WHERE securityLevel=1
31:    AND dataGroup = 10
32:    ORDER BY displayorder
33:  </CFQUERY>
34:
35:  <CFQUERY NAME="qryParamCntrs" DATASOURCE="#SourceName#">
36:    SELECT DISTINCT agency_param_param_cntr
37:    FROM agency_param
38:    WHERE agency_param.dataGroup=10
39:    AND agency_param.agency_id=#nTypeID#
40:    ORDER BY agency_param_param_cntr
41:  </CFQUERY>
42:
43:  <CFSET listParamCntrs = ValueList(qryParamCntrs.param_cntr)>
44:
45:  <!-- Delimited lists for various uses -->
46:  <CFSET listFieldNames = ValueList(qryParamNames.name)>  <!-- "HTML" -->
47:
48:  <html>
49:  <head>

```

```

50: <title>Realty Objects</title>
51: <link rel="stylesheet" href="style1.css" type="text/css">
52: </head>
53:
54: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
55:
56: <cfset nEntityType = 6> <!-- Agency Page = 6 -->
57: <cfset nEntityID = nTypeID> <!-- Agency ID = nTypeID -->
58: <cfinclude template="include\pageFormat.cfm">
59:
60: <cfinclude template="header_bannerad.cfm">
61:
62: <table width="760" border="0" cellpadding="0" cellspacing="0">
63:   <tr>
64:     <td align="right" valign="top" bgcolor="#cNavColor"</cfoutput>" width="135">
65:       <cfinclude template="navigation.cfm">
66:     </td>
67:     <td width="500" valign="top" align="center">
68:       <cfoutput>
69:         <table border="0" width="480" cellspacing="2">
70:           <tr>
71:             <td bgcolor="#cMenuColor" c:ass="heading">Find an Office/Agent - #qryAgency.Name# Profile</td>
72:           </tr>
73:           <tr>
74:             <td>
75:               <cfif len(trim(qryAgency.headerfilename)) gt 0>
76:                 <p align="center"></div>
78:                 </cfif>
79:                 <cfif len(trim(qryAgency.mainImage)) gt 0>
80:                   <p align="center"></div>
82:                   </cfif>
83:                   <cfif qryParamCntrs.recordCount eq 0>
84:                     <paragraphFormat(qryAgency.description)#
85:                   </cfif>
86:                   <CFLOOP FROM=1 TO=#listlen(listParamCntrs)# INDEX=nParamIndex>
87:                     <!-- Title -->
88:                     <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
89:                       SELECT param_value FROM agency_param
90:                       WHERE agency_id=#nTypeID# AND dataGroup=10
91:                       AND param_cntr=#listGetAt(listParamCntrs,nParamIndex)#
92:                       AND param_name='imgTitle'
93:                     </CFQUERY>
94:                     <CFSET cTitle = qryFindInfo.param_value>
95:                     <CFIF len(trim(cTitle)) gt 0>
96:                       <CFSET cSetTitle = "YES">

```

```

97: <CFSET cSetTitle = "No">
98: </CFIF>
99:
100: <!-- Image Align -->
101: <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
102:   SELECT param_value FROM agency_param
103:   WHERE agency_id=#ntypeID# AND dataGroup=10
104:   AND param_ctr=#listGetAt(listParamCntirs,nParamIndex)#
105:   AND param_name='imgAlign'
106: </CFQUERY>
107: <CFSET cImageAlign = ucase(qryFindInfo.param_value)>
108:
109: <!-- Image Name -->
110: <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
111:   SELECT param_value FROM agency_param
112:   WHERE agency_id=#ntypeID# AND dataGroup=10
113:   AND param_ctr=#listGetAt(listParamCntirs,nParamIndex)#
114:   AND param_name='imgFile'
115: </CFQUERY>
116: <CFSET cImageName = qryFindInfo.param_value>
117:
118: <!-- Text -->
119: <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
120:   SELECT param_value FROM agency_param
121:   WHERE agency_id=#ntypeID# AND dataGroup=10
122:   AND param_ctr=#listGetAt(listParamCntirs,nParamIndex)#
123:   AND param_name='imgText'
124: </CFQUERY>
125: <CFIF len(trim(cImageName)) gt 0>
126:   <p>
127:     <CFIF cImageAlign is "MIDDLE">
128:       <p align="center"><IMG SRC=Images\#cImageName# BORDER=0 ALIGN=#cImageAlign# HSPACE=4></p>
129:     <CFELSE>
130:       <IMG SRC=Images\#cImageName# BORDER=0 ALIGN=#cImageAlign# HSPACE=4>
131:     </CFIF>
132:   </CFELSE>
133:   <p>
134:     </CFIF>
135:
136:   <CFIF cSetTitle is "YES">
137:     <h3>#cTitle#</h3>
138:   </CFIF>
139:
140:   <CFIF qryFindInfo.recordCount gt 0 and len(trim(qryFindInfo.param_value)) gt 0>
141:     #qryFindInfo.param_value#</p>
142:   <CFELSE>
143:     </p>
144:   </CFIF>
145: </CFLOOP>

```

```
146:         </td>
147:     </tr>
148: <tr>
149:     <td>
150:         <table border="0" align="center" width="480">
151:         <tr>
152:             <td valign="top" width="240">
153:                 <p><a href="FindProperty_Result.cfm?agencyID=#URL.agency_id#">View Agency's Properties</a></p>
154:                 <p><a href="FindAgent_Result.cfm?agencyID=#URL.agency_id#">View Agents in this Agency</a></p>
155:             </td>
156:             <td valign="top" width="240">
157:                 <p><b>#qryAgency.name#</b><br>
158:                 #qryAgency.address#<br>
159:                 #qryAgency.city#, #qryAgency.state# #qryAgency.zip#</p>
160:                 <p>Specialty: #qryAgency.specialty#<br>
161:                 Phone: #qryAgency.phone#<br>
162:                 Fax: #qryAgency.fax#<br>
163:                 Email: <a href="mailto:#qryAgency.email#">#qryAgency.email#</a></p>
164:             </td>
165:         </tr>
166:     </tr>
167: <td>
168:         <cfset nDisplayType="6">
169:         <cfset nDisplayID="#qryAgency.agency_id#">
170:         <cfset lVerbose = False>
171:         <cfinclude template="resources.cfm">
172:     </td>
173: </tr>
174: </table>
175: </td>
176: </tr>
177: <tr>
178:     <td>
179:         <cfif len(trim(qryAgency.footerfilename)) gt 0>
180:             <p align="center"></p>
181:             </cfif>
182:         </td>
183:     </tr>
184: </table>
185: </cfoutput>
186: </td>
187: </tr>
188: <td valign="top" width="1" bgcolor="#6666ff"></td>
189: <td valign="top" width="4" bgcolor="#ffffff"></td>
190: </tr>
191: <td width="120" valign="top">
192:     <cfinclude template="120x65ads.cfm">
193: </td>
```

```
194:      </tr>
195:    </table>
196:    <cfinclude template="footer.cfm">
197:
198:  </body>
199: </html>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2: <!-- agentdel.cfm -->
3: <!-- Change Tracker Yakalo, Inc. Beta -->
4: <!-- Name Date Description -->
5: <!-- SPE * 02/10/00 * Added a check for properties listed by agent. If -->
6: <!-- there are any then reassign to another agent and -->
7: <!-- prompt to confirm deletion. Then update table -->
8: <!-- -->
9: <!-- -->
10: <!-- -->
11: <!-- -->
12: <!-- -->
13:
14: <cfif isDefined("URL.ReturnURL") and isDefined("URL.ReturnAgency_id")>
15:   <cfset cReturnURL="?ReturnURL=#URL.ReturnURL#&ReturnAgency_id=#URL.ReturnAgency_ID#&displayPage=Agents">
16: <cfelse>
17:   <cfset cReturnURL="">
18: </cfif>
19:
20:
21: <cfif IsDefined("agent_id") IS "No">
22:   <h2><font face="Verdana, Arial" color="Red">Error! No Agent ID was specified!</font></h2>
23:   <cflocation url="agentForm.cfm">
24: <cfelse>
25:   <cfif IsDefined("updateAgent") is "NO">
26:     <cfset updateAgent = "NO">
27:   </cfif>
28:   <cfif IsDefined("delConfirmed") is "NO">
29:     <cfset delConfirmed = "NO">
30:   </cfif>
31:   <cfset delAgent = #agent_id#>
32:   <!-- check to see if agent has any properties -->
33:   <cfquery datasource="#sourceName#" name="checkProperty">
34:     SELECT prop_id, agent_id from prop_main, agency
35:     where (prop_main.agency_id=agency.agency_id or prop_main.agency_id=0)
36:     and agency.distributorID = #ap_distributorID#
37:     AND agent_id = #agent_id#
38:   </cfquery>
39:   <cfif checkProperty.RecordCount gt 0 and #updateAgent# is "NO">
40:     <!-- If agent has properties then find a display a list of agents in this office to take over those properties -->
41:     The agent has <cfoutput>#checkProperty.RecordCount#</cfoutput> properties that are still listed in their name. <br><br>
42:     <cfquery name="qAgentsList" datasource="#sourceName#">
43:       SELECT lastName+', ' + firstName AS wholeName, agent_id
44:       FROM agents,agency
45:       where agents.agency_id=agency.agency_id
46:       and agency.distributorID = #ap_distributorID#
47:       AND agent_id < #agent_id#
48:     </cfquery>
49:     <cfoutput>

```

```

50: <cfform action="agentdel.cfm#cReturnURL#" name="firmAgentId"><select replacement agent:
51: <cfselect display="wholeName" value="agent_id" query="qAgentsList" name="selAgentId">
52: </cfselect>
53: <input type="hidden" name="updateAgent" value="YES">
54: <input type="hidden" value="#delAgent#" name="agent_id">
55: <INPUT TYPE="submit" VALUE="Delete">
56: <INPUT TYPE="reset" VALUE="Clear">
57: </cfform>
58: </cfoutput>
59: <cfelse>
60: <cfif delConfirmed is "NO">
61: <!-- Confirm deletion -->
62: <cfquery name="qDeldAgent" datasource="#sourcename#">
63: SELECT LastName, firstName, agent_id
64: FROM agents
65: WHERE agent_id = #agent_id#
66: </cfquery>
67: </cfoutput>
68: <form action="agentdel.cfm#cReturnURL#" method="post">
69: <font face="Verdana, Arial" size="1">Did you really want to delete #qDeldAgent.firstName# #qDeldAgent.lastName#
    from the database?</font>
70: <input type="hidden" name="delConfirmed" value="YES">
71: <input type="hidden" name="agent_id" value="#qDeldAgent.agent_id#">
72: <cfif IsDefined("selAgentId")>
73: <input type="Hidden" name="selAgentId" value="#selAgentId#">
74: </cfif>
75: <input type="Hidden" name="updateAgent" value="YES">
76: <input type="submit" value="Delete">
77: </form>
78: </cfoutput>
79: <cfelse>
80: <!-- Update properties with new listing agent -->
81: <cfif checkProperty.RecordCount gt 0 and #updateAgent# is "YES">
82: <!--
83: <cfquery name="qUpdateAgent" datasource="#sourcename#">
84: UPDATE prop_main, Agency
85: SET agent_id = #selAgentId#
86: where agents.agency_id=agency.agency_id
87: and agency.distributorID = #ap_distributorID#
88: AND agent_id = #agent_id#
89: </cfquery>
90: -->
91: <cfquery name="qUpdateAgent" datasource="#sourcename#">
92: UPDATE prop_main
93: SET prop_main.agent_id = #selAgentId#
94: where prop_main.distributorID = #ap_distributorID#
95: AND prop_main.agent_id = #agent_id#
96: </cfquery>
97:

```

[illegible]



400 500 600 700 800 900 1000  
 11/29/2000 8:08:30 AM  
 MNT/bennington/agentview.cfm

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfif isDefined("agent_id") is "NO">
4:    <cfquery datasource="#sourceName#" name="agentView">
5:      select *
6:      from agents where
7:        agents.distributorID is #ap_distributorID#
8:    </cfquery>
9:    <cfif agentView.recordCount neq 1>
10:      <cflocation url="errPage.cfm?err=agt101">
11:    </cfif>
12:  <cfelse>
13:    <CFQUERY DATASOURCE="#sourceName#" NAME="agentView">
14:      SELECT *
15:      FROM agents
16:      WHERE agent_id = #agent_id#
17:    </CFQUERY>
18:  </cfif>
19:
20:  <!-- Set these for the page counter -->
21:  <cfset nTargetID=#agent_id#>
22:  <cfset cPageType="Agent">
23:  <cfinclude template=".\\common\\srvPageCounter.cfm">
24:
25:  <CFQUERY NAME="qAgency" DATASOURCE="#sourceName#">
26:    SELECT name
27:    FROM agency
28:    WHERE
29:      agency.distributorID = #ap_distributorID#
30:
31:  </CFQUERY>
32:  <CFQUERY NAME="qPropImage" DATASOURCE="#sourceName#">
33:    SELECT DISTINCT photo_name
34:    FROM prop_main
35:    WHERE
36:      prop_main.distributorID = #ap_distributorID#
37:      AND agent_id = #agent_id#
38:      AND showPiece > 0
39:  </CFQUERY>
40:
41:  <html>
42:  <head>
43:    <title>Realty Objects</title>
44:    <link rel="stylesheet" href="style1.css" type="text/css">
45:    <script language="JavaScript" src="window.js"></script>
46:  </head>
47:
48:  <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
49:

```

```

50: <cfset nEntityType = 7>
51: <cfset nEntityID = #agent_id#> <!-- Agent ID -->
52: <cfinclude template="include\pageFormat.cfm">
53:
54: <cfinclude template="header_bannerad.cfm">
55:
56: <table width="760" border="0" cellpadding="0" cellspacing="0">
57:   <tr><td align="right" valign="top" bgcolor="#cNavColor#"><cfoutput><#cNavColor#" width="135">
58:     <cfinclude template="navigation.cfm">
59:   </td>
60:   <td width="500" valign="top" align="center">
61:     <cfoutput query="agentView">
62:       <table border="0" width="480" cellspacing="2">
63:         <tr>
64:           <td bgcolor="#cMenuColor#" class="heading">Find an Office/Agent - #firstName# #lastName#, #title#</td>
65:         </tr>
66:         <tr>
67:           <td>
68:             <table border="0" width="480">
69:               <tr>
70:                 <td valign="top">
71:                   <CFIF isDefined("agentview.image_name") AND len(agentview.image_name) GT 3>
72:                     <p align="center"><br>
73:                     <b>#firstName#<br>#lastName#</b></p>
74:                   <CFELSE>
75:                     <p align="center">Photo<br>not<br>available.</p>
76:                   </cfif>
77:                 </td>
78:                 <td valign="top">
79:                   <cfif isDefined("bio")>
80:                     <p>#bio#</p>
81:                   </cfif>
82:                   <CFIF isDefined("specialty")>
83:                     <b>Specialty:</b> #specialty#<br>
84:                   </CFIF>
85:                   <CFIF #len(trim(website))# GT 3 AND #participation# LT #notParticipating#>
86:                     </b>More Info</b>: <a href="http://#website#" target="_blank">#website#</a><br>
87:                   </CFIF>
88:                   <CFIF isDefined("workphone")>
89:                     <b>Office Phone:</b> #workphone#
90:                   <CFIF isDefined("extension") AND len("extension") gt 0 AND extension neq "">
91:                     ext. #extension#
92:                   </CFIF><br>
93:                   </cfif>
94:                   <CFIF isDefined("cellphone") AND len(trim(cellphone)) GT 1>
95:                     <b>Cell Phone</b>: #cellphone#<br>
96:                   </cfif>
97:                   <cfif isDefined("faxphone") AND len(trim(faxphone)) gt 1>
98:                     <b>Fax</b>: #faxphone#<br>

```

```

99: </cfif>
100: <cfif isDefined("otherphone") AND len(trim(otherphone)) gt 1>
101:   <b>Other Phone</b>: #otherphone#<br>
102: </cfif>
103: <CFIF isDefined("homephone") AND len(trim(homephone)) gt 1 AND #pub_home# eq "y">
104:   <b>Residence Phone:</b> #homephone#<br>
105: </CFIF>
106: <CFIF #len(trim(email))# GT 4>
107:   <b>Email</b>: <a href="mailto:#email#">#email#</a><br>
108: </CFIF>
109: <CFIF #len(trim(agencyEmail))# GT 1>
110:   <b>Agency Email</b>: <a href="mailto:#agencyEmail#">#agencyEmail#</a><br>
111: </CFIF>
112: <p><a href="FindProperty_Result.cfm?agent_id=#agent_id#">#firstName#'s Listings</a></p>
113: </td>
114: </tr>
115: <tr>
116:   <td>
117:     <cfset nDisplayType="7">
118:     <cfset nDisplayID="#agentView.agent_id#">
119:     <cfset lVerbose = False>
120:     <cfinclude template="resources.cfm">
121:   </td>
122: </tr>
123: </table>
124: <p align="center"><a href="JavaScript: newWindow = openWin('agentview_print.cfm?agent_id=#agent_id', 'open',
'width=550,height=600,toolbar=1,location=0,directories=0,status=0,scrollBars=1,resizable=1');
newWindow.focus()">Printable Page</a></p>
</td>
</tr>
</table>
</cfoutput>
</td>
<td valign="top" width="1" bgcolor="#6666ff"></td>
<td valign="top" width="4" bgcolor="#ffffff"></td>
<td width="120" valign="top">
  <cfinclude template="120x65ads.cfm">
</td>
</tr>
</table>
<cfinclude template="footer.cfm">
</body>
</html>

```



```
50: <td valign="top">
51: <CFIF isDefined("agentview.image_name") AND len(agentview.image_name) GT 3>
52: <p align="center"><br>
53: <b>#firstName#<br>#lastName#</b></p>
54: <CFELSE>
55: <p align="center">Photo<br>not<br>available.</p>
56: </cfif>
57: </td>
58: <td valign="top">
59: <p><b>#firstName# #lastName#, #title#</b></p>
60: <cfif isDefined("bio")>
61: <p>#bio#</p>
62: </cfif>
63: <CFIF isDefined("specialty")>
64: <b>Specialty:</b> #specialty#<br>
65: </CFIF>
66: <CFIF #len(trim(website))# GT 3 AND #participation# LT #notParticipating#>
67: <b>More Info</b>: <a href="http://#website#" target="_blank">#website#</a><br>
68: </CFIF>
69: <CFIF isDefined("workphone")>
70: <b>Office Phone:</b> #workphone#
71: <CFIF isDefined("extension") AND len("extension") gt 0 AND extension neq "">
72: ext. #extension#
73: </CFIF><br>
74: </cfif>
75: <CFIF isDefined("cellphone") AND len(trim(cellphone)) GT 1>
76: <b>Cell Phone</b>: #cellphone#<br>
77: </cfif>
78: <cfif isDefined("faxphone") AND len(trim(faxphone)) gt 1>
79: <b>Fax</b>: #faxphone#<br>
80: </cfif>
81: <cfif isDefined("otherphone") AND len(trim(otherphone)) gt 1>
82: <b>Other Phone</b>: #otherphone#<br>
83: </cfif>
84: <CFIF isDefined("homephone") AND len(trim(homephone)) gt 1 AND #pub_home# eq "Y">
85: <b>Residence Phone:</b> #homephone#<br>
86: </CFIF>
87: <CFIF #len(trim(email))# GT 4>
88: <b>Email</b>: <a href="mailto:#email#">#email#</a><br>
89: </CFIF>
90: <CFIF #len(trim(agencyEmail))# GT 1>
91: <b>Agency Email</b>: <a href="mailto:#agencyEmail#">#agencyEmail#</a><br>
92: </CFIF>
93: </td>
94: </tr>
95: </table>
96: </cfoutput>
97:
98:
```

99: </body>  
100: </html>

-----

```
1: <cfapplication
2: name="Bennington"
3: clientmanagement="yes"
4: sessionmanagement="yes">
5:
6: <CFSET sourceName = "realestate">
7: <CFSET ap_agency = "agency_id = 43">
8: <cfparam name="ap_agencyName" default="Bennington">
9: <cfparam name="ap_agencyURL" default="http://www.tekchange.com/bennington">
10: <CFSET ap_agency_number = "18">
11: <CFSET ap_docs_path = "D:\wwwroot\MNT\Bennington\admin\docs\docFiles">
12: <cfparam name="ap_reportsPath" default="http://www.yakalo.com/bennington/admin/reports">
13: <CFSET ap_propview = "propview.cfm">
14: <CFSET ap_contract_duration = "180">
15: <CFPARAM NAME="ap_true" DEFAULT="1">
16: <CFPARAM NAME="ap_false" DEFAULT="0">
17: <CFPARAM NAME="ap_yes" DEFAULT="1">
18: <CFPARAM NAME="ap_no" DEFAULT="0">
19: <CFPARAM NAME="ap_MLS" DEFAULT="1">
20: <CFPARAM NAME="siteRoot" DEFAULT="Bennington">
21: <CFPARAM NAME="ap_siteRoot" DEFAULT="Bennington">
22: <CFPARAM NAME="ap_default_state" DEFAULT="CO">
23: <CFPARAM NAME="ap_new_duration" DEFAULT="15">
24: <CFPARAM NAME="ap_sold_duration" DEFAULT="15">
25: <CFPARAM NAME="ap_baseColor" DEFAULT="##000099">
26: <CFPARAM NAME="ap_textColor" DEFAULT="white">
27: <CFPARAM NAME="ap_notListed" DEFAULT="0">
28: <!-- Images Related Parameters -->
29: <CFSET ap_image_path = "D:\wwwroot\MNT\Bennington\images\">
30: <CFPARAM NAME="dgBamboo" DEFAULT="2">
31: <CFPARAM NAME="ap_BambooPath" DEFAULT="http://tours.bamboo.com/usa/co/">
32: <CFPARAM NAME="dgStill" DEFAULT="1">
33:
34: <!-- Online Home Tour Parameters -->
35: <CFSET ap_OHT_path = "D:\wwwroot\MNT\Bennington\OHT\images\">
36:
37: <!-- Communities Parameters -->
38: <CFSET ap_Communities_path = "D:\wwwroot\MNT\Bennington\Communities\">
39:
40: <!-- Community Type Parameters -->
41: <CFSET ap_CommType_path = "D:\wwwroot\MNT\Bennington\CommType\">
42:
43: <!-- Property Type Parameters -->
44: <CFSET ap_PropType_path = "D:\wwwroot\MNT\Bennington\PropType\">
45:
46: <!-- Status Parameters -->
47:
48: <!-- Resource Page Related -->
49: <CFPARAM NAME="AP_NLISTINGCOLUMNS" DEFAULT="2">
```

```
50: <CFPARAM NAME="ap_links_sort" DEFAULT="linksgroup.sortOrder, link.sortOrder,">
51: <CFPARAM NAME="ap_res_links" DEFAULT="L">
52: <CFPARAM NAME="ap_res_docs" DEFAULT="D">
53:
54: <!-- Security Related Information -->
55: <CFPARAM NAME="admin_forceLogin" DEFAULT="True"> <!-- Force users to login to back office -->
56:
57: <!-- distributor newspaper related information -->
58: <cfset ap_distributorID = 4>
59:
60: <cfset ap_maxCommunities = 1> <!-- Maximum communities allowed -->
61: <cfset ap_maxSpecialties = 5> <!-- Maximum specialty pages allowed -->
62:
63: <cfset ap_backofficeName = 'Bennington'> <!-- The name/title of each page -->
64:
65: <cfset ap_useFormats = True> <!-- Use page formats -->
66: <cfset ap_defaultNavColor = "#330099"> <!-- Default navigation background color -->
67: <cfset ap_defaultMenuColor = "#990000"> <!-- Default menu background color -->
68:
```



```
1: <cfapplication
2:   name="SmallDemo"
3:   clientmanagement="yes"
4:   sessionmanagement="yes">
5:
6:   <CFSET sourceName = "realestatedev">
7:   <CFSET ap_agency = "agency_id = 43">
8:   <cfparam name="ap_agencyName" default="SmallDemo">
9:   <CFSET ap_agency_number = "18">
10:  <CFSET ap_docs_path = "C:\inetpub\wwwroot\yakalo\staging\smalldemo\admin\docs\docFiles">
11:  <CFSET ap_propview = "propview.cfm">
12:  <CFSET ap_contract_duration = "180">
13:  <CFPARAM NAME="ap_true" DEFAULT="1">
14:  <CFPARAM NAME="ap_false" DEFAULT="0">
15:  <CFPARAM NAME="ap_yes" DEFAULT="1">
16:  <CFPARAM NAME="ap_no" DEFAULT="0">
17:  <CFPARAM NAME="ap_MLS" DEFAULT="1">
18:  <CFPARAM NAME="siteroot" DEFAULT="smalldemo">
19:  <CFPARAM NAME="ap_siteroot" DEFAULT="smalldemo">
20:  <CFPARAM NAME="ap_default_state" DEFAULT="CO">
21:  <CFPARAM NAME="ap_new_duration" DEFAULT="15">
22:  <CFPARAM NAME="ap_sold_duration" DEFAULT="15">
23:  <CFPARAM NAME="ap_baseColor" DEFAULT="##000099">
24:  <CFPARAM NAME="ap_textColor" DEFAULT="white">
25:  <CFPARAM NAME="ap_notlisted" DEFAULT="0">
26:  <!--- Images Related Parameters --->
27:  <CFSET ap_image_path = "C:\inetpub\wwwroot\yakalo\staging\smalldemo\images">
28:  <CFPARAM NAME="dgBamboo" DEFAULT="2">
29:  <CFPARAM NAME="ap_BambooPath" DEFAULT="http://tours.bamboo.com/usa/co/">
30:  <CFPARAM NAME="dgStill" DEFAULT="1">
31:
32:  <!--- Online Home Tour Parameters --->
33:  <CFSET ap_OHT_path = "C:\inetpub\wwwroot\yakalo\staging\smalldemo\OHT\images">
34:
35:  <!--- Communities Parameters --->
36:  <CFSET ap_Communities_path = "C:\inetpub\wwwroot\yakalo\staging\smalldemo\Communities">
37:
38:  <!--- Community Type Parameters --->
39:  <CFSET ap_CommType_path = "C:\inetpub\wwwroot\yakalo\staging\smalldemo\CommType">
40:
41:  <!--- Property Type Parameters --->
42:  <CFSET ap_PropType_path = "C:\inetpub\wwwroot\yakalo\staging\smalldemo\PropType">
43:
44:  <!--- Status Parameters - - ->
45:
46:  <!--- Resource Page Related --->
47:  <CFPARAM NAME="AP_NLISTINGCOLUMNS" DEFAULT="2">
48:  <CFPARAM NAME="ap_links_sort" DEFAULT="linksGroup.sortOrder, link.sortOrder,">
49:  <CFPARAM NAME="ap_res_links" DEFAULT="L">
```

```
50: <CFPARAM NAME="ap_res_docs" DEFAULT="D">
51:
52: <!-- Security Related Information -->
53: <CFPARAM NAME="admin_forceLogin" DEFAULT="True" > <!-- Force users to login to back office -->
54:
55: <!-- distributor newspaper related information -->
56: <cfset ap_distributorID = 4> <!-- Small Market Demo -->
57:
58: <cfset ap_maxCommunities = 1> <!-- Maximum communities allowed -->
59: <cfset ap_maxSpecialties = 5> <!-- Maximum specialty pages allowed -->
60:
61: <cfset ap_backofficeName = 'Small Market Demo'> <!-- The name/title of each page -->
62:
63: <cfset ap_useFormats = True> <!-- Use page formats -->
64: <cfset ap_defaultNavColor = "##330099"> <!-- Default navigation background color -->
65:
```

```
1: <cfapplication
2:   name="Berkshire"
3:   clientmanagement="yes"
4:   sessionmanagement="yes">
5:
6:   <CFSET sourceName = "realestatedev">
7:   <CFSET ap_agency = "agency_id = 43">
8:   <cfparam name="ap_agencyName" default="Berkshire">
9:   <CFSET ap_agency_number = "18">
10:  <CFSET ap_docs_path = "C:\inetpub\wwwroot\yakalo\staging\berkshire\admin\docs\docFiles">
11:  <CFSET ap_propview = "propview.cfm">
12:  <CFSET ap_contract_duration = "180">
13:  <CFPARAM NAME="ap_true" DEFAULT="1">
14:  <CFPARAM NAME="ap_false" DEFAULT="0">
15:  <CFPARAM NAME="ap_yes" DEFAULT="1">
16:  <CFPARAM NAME="ap_no" DEFAULT="0">
17:  <CFPARAM NAME="ap_MLS" DEFAULT="1">
18:  <CFPARAM NAME="siteRoot" DEFAULT="berkshire">
19:  <CFPARAM NAME="ap_siteRoot" DEFAULT="berkshire">
20:  <CFPARAM NAME="ap_default_state" DEFAULT="CO">
21:  <CFPARAM NAME="ap_new_duration" DEFAULT="15">
22:  <CFPARAM NAME="ap_sold_duration" DEFAULT="15">
23:  <CFPARAM NAME="ap_baseColor" DEFAULT="##000099">
24:  <CFPARAM NAME="ap_textColor" DEFAULT="white">
25:  <CFPARAM NAME="ap_notListed" DEFAULT="0">
26:  <!-- Images Related Parameters -->
27:  <CFSET ap_image_path = "C:\inetpub\wwwroot\yakalo\staging\berkshire\images">
28:  <CFPARAM NAME="dgBamboo" DEFAULT="2">
29:  <CFPARAM NAME="ap_BambooPath" DEFAULT="http://tours.bamboo.com/usa/co/">
30:  <CFPARAM NAME="dgStill" DEFAULT="1">
31:
32:  <!-- Online Home Tour Parameters -->
33:  <CFSET ap_OHT_path = "C:\inetpub\wwwroot\yakalo\staging\berkshire\OHT\images">
34:
35:  <!-- Communities Parameters -->
36:  <CFSET ap_Communities_path = "C:\inetpub\wwwroot\yakalo\staging\berkshire\Communities">
37:
38:  <!-- Community Type Parameters -->
39:  <CFSET ap_CommType_path = "C:\inetpub\wwwroot\yakalo\staging\berkshire\CommType">
40:
41:  <!-- Property Type Parameters -->
42:  <CFSET ap_PropType_path = "C:\inetpub\wwwroot\yakalo\staging\berkshire\PropType">
43:
44:  <!-- Status Parameters -->
45:
46:  <!-- Resource Page Related -->
47:  <CFPARAM NAME="AP_NLISTINGCOLUMNS" DEFAULT="2">
48:  <CFPARAM NAME="ap_links_sort" DEFAULT="linksGroup.sortOrder, link.sortOrder,">
49:  <CFPARAM NAME="ap_res_links" DEFAULT="L">
```

```
50: <CFPARAM NAME="ap_res_docs" DEFAULT="D">
51:
52: <!-- Security Related Information -->
53: <CFPARAM NAME="admin_forceLogin" DEFAULT="True"> <!-- Force users to login to back office -->
54:
55: <!-- distributor newspaper related information -->
56: <cfset ap_distributorID = 3> <!-- Berkshire Eagle -->
57:
58: <cfset ap_maxCommunities = 1> <!-- Maximum communities allowed -->
59: <cfset ap_backofficeName = 'Berkshire'> <!-- The name/title of each page -->
60:
61: <cfset ap_useFormats = True> <!-- Use page formats -->
62: <cfset ap_defaultNavColor = "##330099"> <!-- Default navigation background color -->
```

```
1: <cfoutput query="prop_main"><!-- Mortgage Calculator Table -->
2: <form name="analyzer">
3: <table border="0" width="230" cellpadding="1" cellspacing="1" bgcolor="#000000">
4: <tr><td colspan="2" bgcolor="#666666" class="tdtitle"><b>Mortgage Calculator</b></td></tr>
5: <tr><td bgcolor="#000000" colspan="2" align="center">
6: <table align="center">
7: <tr><td align="right">Price $</td>
8: <td><input type="text" name="loan" size="7" value="#int(price)#"></td></tr>
9: <tr><td align="right">Down Payment %</td>
10: <td><input type="text" name="downp" size="3"></td></tr>
11: <tr><td align="right">Number of Years</td><td><input type="text" name="term" size="3"></td></tr>
12: <tr><td align="right">Interest Rate %</td><td><input type="text" name="rate" size="3"></td></tr>
13: <tr><td align="center" colspan="2"><input type="button" name="calculate" value="Calculate" onClick="calculate_Click
14: ()" language="JavaScript">
15: <script language="JavaScript">var pointer;</script><input type="button" name="clear" value="Clear"
onClick="clear_Click()"></td></tr>
16: <tr><td align="right">Down Payment</td><td><input type="text" name="thedown" size="7"></td></tr>
17: <tr><td align="right">Monthly Payment</td><td><input type="text" name="payment" size="7"></td></tr>
18: </table>
19: </td></tr>
20: </table>
21: </form>
22: <!-- End Calc Table --></cfoutput>
```

```
1:  <!-- begin calc table -->
2:  <CFQUERY DATASOURCE="#sourceName#" NAME="qPropPrice">
3:    SELECT price
4:    FROM prop_main
5:    WHERE prop_id = #prop_id#
6:  </CFQUERY>
7:  <cfoutput query="qPropPrice">
8:
9:    <table border="0" cellpadding="1" cellspacing="1" bgcolor="#000000" align="center">
10:     <tr><td colspan="2" bgcolor="#666666" class="tdtitle"><b>Mortgage Calculator</b></td></tr>
12:     <tr><td align="right" bgcolor="#eeeeee"><form name="analyzer">
13:       <table border="0">
14:         <tr><td>Price: $</td><td><input type="Text" name="loan" size="7" value="#int(price)#"></td></tr>
15:         <tr><td>Down Payment:</td><td><input type="Text" name="downp" size="3"></td></tr>
16:         <tr><td>Number of Years:</td><td><input type="Text" name="term" size="3"></td></tr>
17:         <tr><td>Interest Rate:</td><td><input type="Text" name="rate" size="3"></td></tr>
18:         <tr><td>&nbsp;</td><td><input type="button" name="calculate" value="Calculate" onClick="calculate_Click()"
19:         language="JavaScript">
20:           <script language="JavaScript">var pointer;</script>
21:           <input type="button" name="Clear" value="Clear" onClick="clear_Click()"></td></tr>
22:         </table>
23:       </td>
24:     <td align="left" bgcolor="#eeeeee">
25:       Down Payment: $<input type="text" name="thedown" size="7"><br>
26:       Monthly Payment: $<input type="Text" name="payment" size="7">
27:     </form></td></tr>
28:   </table>
29: </cfoutput>
30: <!-- end calc table -->
```

```

1:  <!-- If a is not passed, then exit -->
2:  <cfif not isDefined("URL.Region")>
3:    <cfset nRegion = 0>
4:  <cfelse>
5:    <cfset nRegion = URL.Region>
6:  </cfif>
7:
8:  <!-- If a is not passed, then exit -->
9:  <cfif not isDefined("URL.propType")>
10:    <cfset nPropType = 0>
11:  <cfelse>
12:    <cfset nPropType = URL.PropType>
13:  </cfif>
14:
15:  <!--
16:  <CFQUERY NAME="qLink" DATASOURCE="#sourceName#">
17:  SELECT LinksGroup.name AS grpName,
18:         link.grpid,
19:         link.linkid,
20:         link.Name,
21:         link.URL,
22:         link.SortOrder
23:  FROM link, LinksGroup
24:  WHERE link.agency_id = #ap_agency_number#
25:        AND link.grpid = LinksGroup.grpid
26:        AND link.linkType = '#ap_ies_links#'
27:        AND LinksGroup.linkType = link.linkType
28:        AND LinksGroup.name = 'Home Improvement'
29:  ORDER BY LinksGroup.name, link.name
30:  </CFQUERY>
31:  -->
32:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
33:
34:  <html>
35:  <head>
36:    <title>DPO Homes</title>
37:    <link rel="stylesheet" href="style1.css" type="text/css">
38:    <script language="JavaScript" src="menu.js"></script>
39:    <script language="JavaScript1.2" src="menu2.js"></script>
40:    <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
41:  </head>
42:
43:  <body bgcolor="#ffffff" marginheight="0" marginwidth="0" leftmargin="0" topmargin="0" onLoad="Sniff();LoadImgs();">
44:
45:  <!-- ..... begin outer table : left strip -->
46:  <table border="0" cellpadding="0" cellspacing="0">
47:  <tr><td bgcolor="#6666cc" width="5">&nbsp;</td>
48:  <!-- ..... end left strip -->
49:

```

```

50: <td valign="top">
51: <!-- ~~~~~~ begin page header : nested table -->
52: <table border="0" cellpadding="0" cellspacing="0" width="777">
53: <tr><td width="299" height="76">
54: <a href="index.cfm"></a>
55: </td><td valign="middle">
56: <cfinclude template="banner_ad.cfm">
57: </td></tr>
58: </table>
59: <!-- ~~~~~~ end page header -->
60:
61: <!-- ~~~~~~ begin page body : nested table -->
62: <table border="0" cellpadding="0" cellspacing="0" width="777">
63: <tr><td valign="top" width="653" height="34">
64: <cfinclude template="menu.cfm">
65: </td><td valign="top" width="124" align="center" rowspan="3">
66: <cfinclude template="small_ad.cfm">
67: </td></tr>
68: <tr><td align="center" valign="bottom" width="653" height="34">
69: <table width="630" border="0">
70: <tr><td class="nav" valign="bottom">Find a Home</td></tr>
71: </table>
72: </td></tr>
73: <!-- ~~~~~~ BEGIN CONTENT -->
74: <tr><td valign="top"><form name="frmSrchClass" method="post" action="classView.cfm">
75: <table border="0" align="center" width="630" bgcolor="#000000" cellpadding="1" cellspacing="1">
76: <tr><td bgcolor="#6666cc" class="tdtitle"><b>Classifieds Search Criteria</b></td></tr>
77:
78: <tr><td bgcolor="#eeeeee" align="center">
79: <table border="0">
80: <tr><td valign="top"></td>
81: <td valign="top">
82: <table border="0" cellpadding="3" cellspacing="1">
83: <tr><td colspan="2">Search the most current listings of homes and building sites for sale in the Denver Post
    Classifieds.</td></tr>
84: <tr><td align="right">Region:</td><td>
85: <select name="edtRegion">
86: <option value="0"><cfif 0 is #nRegion#> selected</cfif> >All Regions
87: <option value="1"><cfif 1 is #nRegion#> selected</cfif>>Metro Denver
88: <option value="2"><cfif 2 is #nRegion#> selected</cfif>>North East
89: <option value="3"><cfif 3 is #nRegion#> selected</cfif>>North West
90: <option value="4"><cfif 4 is #nRegion#> selected</cfif>>South East
91: <option value="5"><cfif 5 is #nRegion#> selected</cfif>>South West
92: <option value="6"><cfif 6 is #nRegion#> selected</cfif>>Mountain
93: <option value="7"><cfif 7 is #nRegion#> selected</cfif>>Other
94: </select>
95: </td></tr>

```



```
96: <tr><td align="right">Property Type:</td><td>
97: <select name="edPropertyType">
98: <option value="0"<cfif 0 is #nProperty#> selected</cfif>>All Types
99: <option value="1"<cfif 1 is #nProperty#> selected</cfif>>Residential
100: <option value="2"<cfif 2 is #nProperty#> selected</cfif>>Condo
101: <option value="3"<cfif 3 is #nProperty#> selected</cfif>>Land
102: <option value="4"<cfif 4 is #nProperty#> selected</cfif>>Commercial
103: <option value="5"<cfif 5 is #nProperty#> selected</cfif>>Income
104: </select>
105:
106: </td></tr>
107:
108:
109: <tr><td align="right">Text to Search:</td><td>
110: <input type="text" name="edtFullText" size="10">
111: </td></tr>
112:
113: <tr><td align="right">Show</td><td>
114: <select name="edtAdsToShow">
115: <option value="10" selected>10
116: <option value="25">25
117: <option value="50">50
118: <option value="100">100
119: </select> ads per page
120: <!-- <input type="submit" name="btnSearch" value="Search"> -->
121: </td></tr>
122: <tr><td colspan="2" align="center"><input type="submit" name="btnSearch" value="Search"> <input type="reset"
value="Reset Form"></td></tr>
123: </table>
124: </td></tr>
125: </table>
126: </td></tr>
127: </table>
128:
129:
130: </form>
131: </td></tr>
132: <!-- ~~~~~~ END CONTENT ~~~~>
133: </table>
134: <!-- ~~~~~~ end page body -->
135: </td></tr></table>
136: <cfinclude template="footer.cfm">
137: </body>
138: </html>
```

-----  
4.0 Transitional/ENUS

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/ENUS"
2:
3: <CFQUERY NAME="qLink" DATASOURCE="#sourceName#"
4: SELECT linksGroup.name AS grpName,
5: link.grpId,
6: link.LinkId,
7: link.Name,
8: link.URL,
9: link.SortOrder
10: FROM link, linksGroup
11: WHERE link.agency_id = #ap_agency_number#
12: AND link.grpId = linksGroup.grpId
13: AND link.linkType = '#ap_res_links#'
14: AND linksGroup.linkType = link.linkType
15: AND linksGroup.name = 'Home Improvement'
16: ORDER BY linksGroup.name, link.name
17: </CFQUERY>
18:
19: <html>
20: <head>
21: <title>DPO Homes</title>
22: <link rel="stylesheet" href="style1.css" type="text/css">
23: <script language="JavaScript" src="menu.js"></script>
24: <script language="JavaScript1.2" src="menu2.js"></script>
25: </head>
26:
27: <body bgcolor="#ffffff" marginheight="0" marginwidth="0" leftmargin="0" topmargin="0"
28:
29: <!-- ~~~~~~ begin outer table : left strip ~-->
30: <table border="0" cellpadding="0" cellspacing="0">
31: <tr><td bgcolor="#6666cc" width="5">&nbsp;</td>
32: <!-- ~~~~~~ end left strip ~-->
33:
34: <td valign="top">
35: <!-- ~~~~~~ begin page header : nested table -->
36: <table border="0" cellpadding="0" cellspacing="0" width="777">
37: <tr><td width="299" height="76">
38: <a href="index.cfm"></a>
40: </td><td valign="middle">
41: <cfinclude template="banner_ad.cfm">
42: </td></tr>
43: </table>
44: <!-- ~~~~~~ end page header -->
45:
46: <!-- ~~~~~~ begin page body : nested table -->
47: <table border="0" cellpadding="0" cellspacing="0" width="777">
48: <tr><td valign="top" width="653" height="34">
49: <cfinclude template="menu.cfm">
```

```

49: </td><td valign="top" width="124" height="653" style="border: 1px solid black; text-align: center; vertical-align: top;">
50:   <cfinclude template="small_ad.cfm">
51: </td></tr>
52: <tr><td valign="top" width="124" height="653" style="border: 1px solid black; text-align: center; vertical-align: top;">
53:   <cfinclude template="small_ad.cfm">
54: </td></tr>
55: </tr></table>
56: <tr><td colspan="2" style="text-align: center; vertical-align: top;">
57:   <table border="0" style="width: 100%; border-collapse: collapse;">
58:     <tr><td colspan="2" style="text-align: center; vertical-align: top;">
59:       <table border="0" style="width: 100%; border-collapse: collapse;">
60:         <tr><td colspan="2" style="text-align: center; vertical-align: top;">
61:           <table border="0" style="width: 100%; border-collapse: collapse;">
62:             <tr><td colspan="2" style="text-align: center; vertical-align: top;">
63:               <table border="0" style="width: 100%; border-collapse: collapse;">
64:                 <tr><td colspan="2" style="text-align: center; vertical-align: top;">
65:                   <table border="0" style="width: 100%; border-collapse: collapse;">
66:                     <tr><td colspan="2" style="text-align: center; vertical-align: top;">
67:                       <table border="0" style="width: 100%; border-collapse: collapse;">
68:                         <tr><td colspan="2" style="text-align: center; vertical-align: top;">
69:                           <table border="0" style="width: 100%; border-collapse: collapse;">
70:                             <tr><td colspan="2" style="text-align: center; vertical-align: top;">
71:                               <table border="0" style="width: 100%; border-collapse: collapse;">
72:                                 <tr><td colspan="2" style="text-align: center; vertical-align: top;">
73:                                   <table border="0" style="width: 100%; border-collapse: collapse;">
74:                                     <tr><td colspan="2" style="text-align: center; vertical-align: top;">
75:                                       <table border="0" style="width: 100%; border-collapse: collapse;">
76:                                         <tr><td colspan="2" style="text-align: center; vertical-align: top;">
77:                                           <table border="0" style="width: 100%; border-collapse: collapse;">
78:                                             <tr><td colspan="2" style="text-align: center; vertical-align: top;">
79:                                               <table border="0" style="width: 100%; border-collapse: collapse;">
80:                                                 <tr><td colspan="2" style="text-align: center; vertical-align: top;">
81:                                                   <table border="0" style="width: 100%; border-collapse: collapse;">
82:                                                     <tr><td colspan="2" style="text-align: center; vertical-align: top;">
83:                                                       <table border="0" style="width: 100%; border-collapse: collapse;">
84:                                                         <tr><td colspan="2" style="text-align: center; vertical-align: top;">
85:                                                           <table border="0" style="width: 100%; border-collapse: collapse;">
86:                                                             <tr><td colspan="2" style="text-align: center; vertical-align: top;">
87:                                                               <table border="0" style="width: 100%; border-collapse: collapse;">
88:                                                                 <tr><td colspan="2" style="text-align: center; vertical-align: top;">
89:                                                                   <table border="0" style="width: 100%; border-collapse: collapse;">
90:                                                                     <tr><td colspan="2" style="text-align: center; vertical-align: top;">
91:                                                                       <table border="0" style="width: 100%; border-collapse: collapse;">
92:                                                                         <tr><td colspan="2" style="text-align: center; vertical-align: top;">
93:                                                                           <table border="0" style="width: 100%; border-collapse: collapse;">
94:                                                                             <tr><td colspan="2" style="text-align: center; vertical-align: top;">
95:                                                                               <table border="0" style="width: 100%; border-collapse: collapse;">

```

```
96:         <option value="<=">or fewer
97:         <option value="=">only
98:     </select>
99: </td></tr>
100: <tr><td>Bathrooms</td><td>
101:     <cfoutput>
102:     <select name="edtBedCount">
103:     <option value="0">Any Number
104:     <cfloop from="1" to="10" index="nIndex">
105:         <option value="#nIndex#">#nIndex#
106:     </cfloop>
107:     </select>
108:     </cfoutput>
109:     <select name="edtBedOperator">
110:     <option value=">=">selected>or more
111:     <option value="<=">or fewer
112:     <option value="=">only
113:     </select>
114: </td></tr>
115: <tr><td>City</td><td>
116:     <input type="text" name="edtCity" size="20">
117: </td></tr>
118: <tr><td>Text to Search</td><td>
119:     <input type="text" name="edtFullText" size="30">
120: </td></tr>
121: <tr><td colspan="2"><input type="submit" name="btnSearch" value="Search"> <input type="reset" value="Reset
Form"></td></tr>
122: </table>
123: </td></tr>
124: </table>
125: </td></tr>
126: </table>
127:
128:
129: </form> </td></tr>
130: </table>
131: </table>
132: </td></tr></table>
133: <cfinclude template="footer.cfm">
134: </body>
135: </html>
136:
137:
```

```


1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
2:
3:  <cfparam name="nStartFrom" default="1">
4:  <cfparam name="ntoDisplay" default="10">
5:  <cfparam name="nEnd" default="10">
6:  <cfparam name="cCriteria" default="">
7:  <cfparam name="cPropType" default="">
8:  <cfparam name="cRegion" default="">
9:
10:
11:  <!-- This returns all matches from the Varsity collection -->
12:  <cfif isDefined("FORM.edtFullText")>
13:    <cfsearch collection="RealEstate" name="SearchResults" criteria="#FORM.edtFullText#">
14:      <cfset cCriteria = #FORM.edtFullText#>
15:    <cfelse>
16:      <cfsearch collection="RealEstate" name="SearchResults" criteria="#cCriteria#">
17:    </cfif>
18:
19:    <cfif isDefined("FORM.edtPropType")>
20:      <cfif #FORM.edtPropType# EQ 0>
21:        <cfset cPropType = 'AllTypes'>
22:      </cfif>
23:      <cfif #FORM.edtPropType# EQ 1>
24:        <cfset cPropType = 'Residential'>
25:      </cfif>
26:      <cfif #FORM.edtPropType# EQ 2>
27:        <cfset cPropType = 'Condo'>
28:      </cfif>
29:      <cfif #FORM.edtPropType# EQ 3>
30:        <cfset cPropType = 'Land'>
31:      </cfif>
32:      <cfif #FORM.edtPropType# EQ 4>
33:        <cfset cPropType = 'Commercial'>
34:      </cfif>
35:      <cfif #FORM.edtPropType# EQ 5>
36:        <cfset cPropType = 'Income'>
37:      </cfif>
38:    </cfif>
39:    <cfif isDefined("Form.edtRegion")>
40:      <cfif #FORM.edtRegion# EQ 0>
41:        <cfset cRegion = 'AllRegions'>
42:      </cfif>
43:      <cfif #FORM.edtRegion# EQ 1>
44:        <cfset cRegion = 'Metro'>
45:      </cfif>
46:      <cfif #FORM.edtRegion# EQ 2>
47:        <cfset cRegion = 'North East'>
48:      </cfif>
49:      <cfif #FORM.edtRegion# EQ 3>

```

```

50:         <cfset cRegion = 'North West'>
51:     </cfif>
52:     <cfif #FORM.edtRegion# EQ 4>
53:         <cfset cRegion = 'South East'>
54:     </cfif>
55:     <cfif #FORM.edtRegion# EQ 5>
56:         <cfset cRegion = 'South West'>
57:     </cfif>
58:     <cfif #FORM.edtRegion# EQ 6>
59:         <cfset cRegion = 'Mountain'>
60:     </cfif>
61:     <cfif #FORM.edtRegion# EQ 7>
62:         <cfset cRegion = 'Other'>
63:     </cfif>
64: </cfif>
65: <cfif isDefined("Form.edtAdstoShow")>
66:     <cfset nToDisplay = Form.edtAdstoShow>
67: </cfif>
68:
69: <!--- Now create a subquery based on the returned results -->
70: <cfquery name="qryResults" datasource="#sourcename#">
71:     select pap_cl_ad.ad_id,pap_cl_ad.ad_content, pap_cl_classes.ad_class_desc from
72:     pap_cl_ad, pap_cl_classes
73:     where pap_cl_ad.ad_id in (-1<cfif searchResults.Key is not ">,</cfif>#ValueList(SearchResults.Key)#</cfif>
74:     <cfif #cPropType# is not 'AllTypes'>
75:         and pap_cl_classes.ad_class_sort1 = '#cPropType#'
76:     </cfif>
77:     <cfif #cRegion# is not 'AllRegions'>
78:         and pap_cl_classes.ad_class_region = '#cRegion#'
79:         and pap_cl_classes.ad_class = pap_cl_ad.ad_class
80:     </cfif>
81:     and pap_cl_classes.ad_class = pap_cl_ad.ad_class
82:     order by pap_cl_ad.ad_id
83: </cfquery>
84:
85: <!--- checks to see how many results to display -->
86:
87: <CFSET nViewTo = #nStartFrom#+#nToDisplay#-1>
88: <CFIF nViewTo GT #qryResults.recordCount#>
89:     <CFSET nViewTo = #qryResults.recordCount#>
90: </CFIF>
91:
92: <html>
93: <head>
94:     <title>DPO Homes</title>
95:     <link rel="stylesheet" href="style1.css" type="text/css">
96:     <script language="JavaScript" src="menu.js"></script>
97:     <script language="JavaScript1.2" src="menu2.js"></script>
98: </head>

```



```

99: <body bgcolor="#ffffff" marginheight="0" marginwidth="0" leftmargin="0" topmargin="0" onload="Sniff();Loadimgs();">
100:
101: <!-- ~~~~~~ begin outer table : left strip -->
102: <table border="0" cellpadding="0" cellspacing="0">
103: <tr><td bgcolor="#6666cc" width="5">&nbsp;</td>
104: <!-- ~~~~~~ end left strip -->
105:
106: <td valign="top">
107:
108: <!-- ~~~~~~ begin page header : nested table -->
109: <table border="0" cellpadding="0" cellspacing="0" width="777">
110: <tr><td width="299" height="76">
111: <a href="index.cfm"></a>
113: </td><td valign="middle">
114: <cfinclude template="banner_ad.cfm">
115: </td></tr>
116: </table>
117: <!-- ~~~~~~ end page header -->
118:
119: <!-- ~~~~~~ begin page body : nested table -->
120: <table border="0" cellpadding="0" cellspacing="0" width="777">
121: <tr><td valign="top" width="653" height="34">
122: <cfinclude template="menu.cfm">
123: </td><td valign="top" width="124" align="center" rowspan="3">
124: <cfinclude template="small_ad.cfm">
125: </td></tr>
126: <tr><td align="center" valign="bottom" width="653" height="34">
127: <table width="630" border="0">
128: <tr><td class="nav" valign="bottom">Find a Home</td></tr>
129: </table>
130: </td></tr>
131: <!-- ~~~~~~ BEGIN CONTENT -->
132:
133: <tr><td valign="top">
134:
135: <table border="0" cellpadding="1" cellspacing="1" align="center" width="630" bgcolor="#000000">
136: <tr><td bgcolor="#6666cc" class="tdtitle">
137: <cfif #ntoDisplay# GTE qryResults.recordCount>
138: <cfset ctoDisplay = min(qryResults.recordCount, #ntoDisplay#)>
139: </cfif>
140: <cfif qryResults.recordCount GTE #ntoDisplay#>
141: <cfset ctoDisplay = min(qryResults.recordCount, #nEnd#)>
142: </cfif>
143: <cfset cStartFrom = min(qryResults.recordCount, #nStartFrom#)>
144: <cfoutput>
145:
146: <b>Classified Search Results Detail</b>

```

[illegible]



```
196: <INPUT TYPE="hidden" NAME="nstartFrom" VALUE="#nNextStart#">
197: <INPUT TYPE="hidden" NAME="nToDisplay" VALUE="#nToDisplay#">
198: <INPUT TYPE="hidden" NAME="nEnd" VALUE="#nNextEnd#">
199: <INPUT TYPE="hidden" NAME="cCriteria" VALUE="#cCriteria#">
200: <INPUT TYPE="hidden" NAME="cPropType" VALUE="#cPropType#">
201: <INPUT TYPE="hidden" NAME="cRegion" VALUE="#cRegion#">
202: <INPUT TYPE="submit" VALUE="Next #nToDisplay#">
203: </FORM>
204: </CFOUTPUT>
205: </TD>
206: </CFIF>
207: <TD>
208: <CFOUTPUT>
209: <FORM ACTION="classView.cfm" METHOD="POST">
210: <INPUT TYPE="Button" VALUE="Back To Search" OnClick="location.href='classSearch.cfm'">
211: </FORM>
212: </CFOUTPUT>
213: </TD>
214: </TR>
215:
216:
217: <!-- ~~~~~~ END CONTENT ~~~~>
218: </table>
219: <!-- ~~~~~~ end page body ~~~~>
220: </td></tr></table>
221: </td></tr></table>
222: <cfinclude template="footer.cfm">
223: </body>
224: </html>
```

```
1:  <!-- Lists, Arrays, and other Structures for community information demo -->
2:
3:  <!-- Region information for property location ---->
4:  <!-- DO NOT FORGET TO CHANGE THE MENU JAVASCRIPT TO REFLECT ANY CHANGES ---->
5:
6:  <!-- <CFSET lstRegions = "Denver,Metro,Northeast,NorthWest,Southeast,SouthWest,Mountain"> ---->
7:
8:  <CFSET lstRegions = "Small Demo">
9:  <cfset lstRegionValues="0">
10:
```

```

1: <script language="JavaScript">
2: <!-- hide from JavaScript-challenged browsers
3: function openWindow1() { popupWin = window.open('apticker.htm', 'remote',
4: 'toolbar=no,width=368,height=95,resizeable=no,location=no,directories=no,left=10,top=95')
5: } // done hiding -->
6: </script>
7:
8: <!-- Get the region list -->
9: <cfinclude template="commdefines.cfm">
10: <cfparam name="URL.Region" Default="">
11:
12: <cfquery name="qryCommunities" datasource="#SourceName#">
13: SELECT communityID, name, region
14: FROM Communities
15: and communities.distributorID = #ap_distributorID#
16: <CFIF URL.Region IS NOT "">
17: and Communities.Region = '#URL.Region#'
18: </cfif>
19: ORDER BY Communities.Region, Communities.name
20: <!-- !!! Don't forget StartDate and StopDate !!! -->
21: </cfquery>
22:
23: <form method="post"><select name="url" onChange="window.open(this.options[this.selectedIndex].value,'_top')">
24: <!-- <option value="Community Menu">-Communities- -->
25: <option value="commsrch.cfm">-Communities-
26: <cfset coldRegion = ""NONE"">
27: <cfloop query="qryCommunities">
28: <cfoutput>
29: <cfif URL.Region is "" and coldRegion is not trim(qryCommunities.Region)>
30: <option value="commsrch.cfm?Region=#qryCommunities.Region#">#qryCommunities.Region#
31: <cfset coldRegion = trim(qryCommunities.Region)>
32: <option value="commview3.cfm?communityID=#qryCommunities.communityID#<cfif URL.Region is not
33: "">&Region=#URL.Region#</cfif>">&nbsp;#&nbsp;#qryCommunities.name#
34: <cfelse>
35: <option value="commview3.cfm?communityID=#qryCommunities.communityID#<cfif URL.Region is not
36: "">&Region=#URL.Region#</cfif>"><cfif URL.Region is "">&nbsp;#&nbsp;#qryCommunities.name#
37: </cfif>
38: </cfoutput>
39: <!--
40: <option value="castlepines.cfm">Castle Pines
41: <option value="cherryhills.cfm">Cherry Hills
42: <option value="greenvill.cfm">Greenwood Village
43: <option value="washpark.cfm">Washington Park
44: </select></form>

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" . . . . .>
2:
3: <cfparam name="URL.Region" Default=""*>
4:
5: <cfif not isDefined("URL.CommunityID")>
6:   <cflocation url="commsrch.cfm">
7: </cfelse>
8:   <cfset nCommunityID = URL.communityID>
9: </cfif>
10:
11: <cfquery name="qryCommunity" datasource="#SourceName#">
12:   select *
13:   from communities
14:   where communityID = #URL.CommunityID#
15: </cfquery>
16:
17: <cfif qryCommunity.recordCount is 0>
18:   <cflocation url="commsrch.cfm">
19: </cfif>
20:
21: <html>
22: <head>
23:   <title>DPO Homes</title>
24:   <link rel="stylesheet" href="style1.css" type="text/css">
25:   <script language="JavaScript" src="menu.js"></script>
26:   <script language="JavaScript1.2" src="menu2.js"></script>
27: </head>
28:
29: <body bgcolor="#ffffff" marginheight="0" marginwidth="0" leftmargin="0" topmargin="0"
30:   <!-- ..... begin outer table : left strip -->
31:   <table border="0" cellpadding="0" cellspacing="0">
32:     <tr><td bgcolor="##6666cc" width="5">&nbsp;</td>
33:     <!-- ..... end left strip -->
34:
35:     <td valign="top">
36:     <!-- ..... begin page header : nested table -->
37:     <table border="0" cellpadding="0" cellspacing="0" width="777">
38:       <tr><td width="299" height="76">
39:         <a href="index.cfm"></a>
40:       </td><td valign="middle">
41:         <cfinclude template="commbanner_ad.cfm">
42:       </td></tr>
43:     </table>
44:     <!-- ..... and page header -->
45:
46:     <!-- ..... begin page body : nested table -->
47:     <table border="0" cellpadding="0" cellspacing="0" width="777">
48:       <tr><td valign="top" width="653" height="34">
49:         <cfinclude template="menu.cfm">

```

```
50: </td><td valign="top" width="124" align="center" rowspan="3">
51: <cfinclude template="commsmall_ad.cfm">
52: </td></tr>
53: <tr><td align="center" valign="bottom" width="653" height="34">
54: <table width="630" border="0">
55: <tr><td class="nav" valign="bottom">DPO Homes : Community Profiles</td></tr>
56: </table>
57: </td></tr>
58: <!-- BEGIN CONTENT -->
59: <cfoutput>
60: <tr><td valign="top">
61: <table border="0" align="center" width="630" cellpadding="1" cellspacing="1" bgcolor="#000000">
62: <tr><td bgcolor="#6666cc" class="tdtitle"><b>#qryCommunity.Name# Community Resources</b></td></tr>
64: <tr>
65: <td bgcolor="#ffffff">
66: <p align="center"><a href="commview3.cfm?communityID=#nCommunityID#">Community Home</a> |
67: <a href="myPortfolio/savedList.cfm">My Portfolio</a> |
68: <a href="OHTListings.cfm?communityID=#nCommunityID#">Online Home Tours</a></p>
69: <p><cfset nDisplayType="2">
70: <cfset nDisplayID="#qryCommunity.communityID#"
71: <cfinclude template="resources.cfm"></p>
72: </td>
73: </tr>
74: </table>
75: <br>
76: <table border="0" cellpadding="1" cellspacing="1" width="630" align="center">
77: <tr>
78: <td colspan="2"><!-- Make a community Search -->
79: <td bgcolor="#ffffff" align="left" valign="top" width="315">
80: <cfinclude template="include\commPropSearch.cfm">
81: </td>
82: <td colspan="2"><!-- Make an Agent Search -->
83: <td bgcolor="#ffffff" align="right" valign="top" width="315">
84: <cfinclude template="include\commAgentSearch.cfm">
85: </td>
86: </tr>
87: </table>
88:
89: <br>
90: <table border="0" cellpadding="1" cellspacing="1" bgcolor="#000000" align="center" width="630">
91: <tr>
92: <td colspan="2"><td colspan="2">
93: <td bgcolor="#6666cc" class="tdtitle">
94: <b>Select Another <cfif
95: URL.Region is not ""> #URL.Region# </cfif>Community</b>
96: </td></tr>
97: <tr><td align="center" bgcolor="#ffffff"><cfinclude template="commlist.cfm">
```

```
97:         </td></tr>
98:         </table>
99:         </td></tr>
100:     </cfoutput>
101:     <!-- ~~~~~~ END CONTENT ~-->
102: </table>
103: <!-- ~~~~~~ end page body ~-->
104: </td></tr></table>
105: <cfinclude template="footer.cfm">
106: </body>
107: </html>
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html40/loose.dtd">
2:
3: <cfquery name="qryFindComm" datasource="#sourceName#">
4:   select * from communities
5:   where communities.distributorID = #ap_distributorID#
6: </cfquery>
7:
8: <cfif qryFindComm.recordCount gt 0>
9:   <cfif qryFindComm.alternateURL is "">
10:     <cflocation url="commview.cfm?communityID=#qryFindComm.communityID#" addtoken="no">
11:   </cfif>
12:   <cflocation url="#qryFindComm.alternateURL#" addtoken="no">
13:   </cfif>
14: </cfif>
15:
16: <html>
17: <head>
18:   <title>Realty Objects</title>
19:   <link rel="stylesheet" href="style1.css" type="text/css">
20: </head>
21:
22: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
23:
24: <cfset nEntityType = 2> <!-- Community Page = 1 -->
25: <cfset nEntityID = 0> <!-- Main community Page -->
26: <cfinclude template="include\pageFormat.cfm">
27:
28: <cfinclude template="header_bannerad.cfm">
29:
30: <table width="760" border="0" cellpadding="0" cellspacing="0">
31:   <tr><td align="right" valign="top" bgcolor="#cfcfcfcf"><cfoutput>#cNavColor#</cfoutput> width="135">
32:     <cfinclude template="navigation.cfm">
33:   </td>
34:   <td width="500" valign="top" align="center">
35:     <table border="0" width="480" cellspacing="2">
36:       <tr>
37:         <td bgcolor="#cfcfcfcf"><cfoutput>#cMenuColor#</cfoutput> class="heading">Community Information</td>
38:       </tr>
39:       <tr>
40:         <td>
41:           <p>text</p>
42:         </td>
43:       </tr>
44:     </table>
45:   </td>
46:   <td valign="top" width="1" bgcolor="#6666ff"></td>
47:   <td valign="top" width="4" bgcolor="#ffffff"></td>
48:   <td width="120" valign="top">
49:     <cfinclude template="120x65ads.cfm">
```

```
50:      </td>
51:      </tr>
52:    </table>
53:    <cfinclude template="footer.cfm">
54:  </body>
55: </html>
```



```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html40/strict.dtd">
2:
3: <!-- If a community ID is not passed, then exit -->
4: <cfif not isDefined("URL.communityID")>
5:   <cflocation url="commsrch.cfm" addtoken="no">
6: <cfelse>
7:   <cfset nCommunityID = URL.communityID>
8: </cfif>
9:
10: <cfif not isDefined("URL.Region")>
11:   <cfset URL.Region="">
12: </cfif>
13:
14: <cfquery name="qryCommunity" datasource="#SourceName#">
15:   SELECT *
16:   FROM Communities
17:   WHERE Communities.communityID = #nCommunityID#
18: </cfquery>
19:
20: <!-- Parameter names for the fields -->
21: <CFQUERY NAME="qryParamNames" DATASOURCE="#sourceName#">
22:   SELECT
23:     DISTINCT id, name, description, label, displayOrder, restrictions, type, selectOptions
24:   FROM param_defs
25:   WHERE securityLevel=1
26:   AND dataGroup = 6
27:   ORDER BY displayOrder
28: </CFQUERY>
29:
30: <CFQUERY NAME="qryParamCntrs" DATASOURCE="#sourceName#">
31:   SELECT DISTINCT comm_param.param_cntr
32:   FROM comm_param
33:   WHERE comm_param.dataGroup=6
34:   AND comm_param.communityID=#nCommunityID#
35:   ORDER BY comm_param.param_cntr
36: </CFQUERY>
37:
38: <CFSET listParamCntrs = ValueList(qryParamCntrs.param_cntr)>
39:
40: <!-- Delimited lists for various uses -->
41: <CFSET listfieldNames = ValueList(qryParamNames.name)> <!-- "OHTTitle" -->
42:
43:
44: <html>
45: <head>
46:   <title>Realty Objects</title>
47:   <link rel="stylesheet" href="style1.css" type="text/css">
48: </head>
49:

```

```

50: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
51:
52: <cfset nEntityType = 2> <!-- Community Page = 2 -->
53: <cfset nEntityID = #nCommunityID#> <!-- Community ID -->
54: <cfinclude template="include\pageFormat.cfm">
55:
56: <cfinclude template="header_bannerad.cfm">
57:
58: <table width="760" border="0" cellpadding="0" cellspacing="0">
59: <tr><td align="right" valign="top" bgcolor="#<cfoutput>#navColor#</cfoutput>" width="135">
60: <cfinclude template="navigation.cfm">
61: </td>
62: <td width="500" valign="top" align="center">
63: <table border="0" width="480" cellspacing="2">
64: <cfoutput>
65: <tr>
66: <td bgcolor="#MenuColor#" class="heading"><b>#qryCommunity.Name# Community Profile</b></td>
67: </tr>
68: <tr>
69: <td>
70: <cfif len(trim(qryCommunity.primarypic)) gt 0>
71: <p align="center"></p>
72: </cfif>
73: <paragraphFormat(qryCommunity.description)#</p>
74: <cfif len(trim(qryCommunity.headerfilename)) gt 0>
75: <p align="center"></p>
76: </cfif>
77:
78: <CFLOOP FROM=1 TO=#listlen(listParamCntrs) # INDEX=nParamIndex>
79:
80: <!-- Title -->
81: <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
82: SELECT param_value FROM comm_param
83: WHERE communityID=#nCommunityID# AND dataGroup=6
84: AND param_cntr=#listGetAt(listParamCntrs,nParamIndex)#
85: AND param_name='CommTitle'
86: </CFQUERY>
87: <CFSET cTitle = qryFindInfo.param_value>
88: <CFIF len(trim(cTitle)) gt 0>
89: <CFSET cUseTitle = "YES">
90: <CFELSE>
91: <CFSET cUseTitle = "NO">
92: </CFIF>
93:
94: <!-- Image Align -->
95: <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
96: SELECT param_value FROM comm_param

```

```

97: WHERE communityID=#nCommunityID# AND dataGroup=#nDataGroup#
98: AND param_cnr=#listGetAt(listParamCntrs,nParamIndex) #
99: AND param_name='CommImgAln'
100: </CFQUERY>
101: <CFSET cImageAlign = ucase(qryFindInfo.param_value)>
102:
103: <!-- Image Name -->
104: <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
105: SELECT param_value FROM comm_param
106: WHERE communityID=#nCommunityID# AND dataGroup=6
107: AND param_cnr=#listGetAt(listParamCntrs,nParamIndex) #
108: AND param_name='CommImage'
109: </CFQUERY>
110: <CFSET cImageName = qryFindInfo.param_value>
111:
112: <!-- Text -->
113: <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
114: SELECT param_value FROM comm_param
115: WHERE communityID=#nCommunityID# AND dataGroup=6
116: AND param_cnr=#listGetAt(listParamCntrs,nParamIndex) #
117: AND param_name='CommText'
118: </CFQUERY>
119: <CFIF len(trim(cImageName)) gt 0>
120: <p>
121: <CFIF cImageAlign is "MIDDLE">
122: <DIV ALIGN=center><IMG SRC=#cImageName# BORDER=0 ALIGN=#cImageAlign# HSPACE=4></DIV>
123: <CFELSE>
124: <IMG SRC=#cImageName# BORDER=0 ALIGN=#cImageAlign# HSPACE=4>
125: </CFIF>
126: <CFELSE>
127: <p>
128: </CFIF>
129:
130: <CFIF cUseTitle is "YES">
131: <H3>#cTitle#</H3>
132: </CFIF>
133:
134: <CFIF qryFindInfo.recordCount GT 0 and len(trim(qryFindInfo.param_value)) gt 0>
135: #paragraphFormat(qryFindInfo.param_value)#</p>
136: <CFELSE>
137: </p>
138: </CFIF>
139:
140: </CFLOOP>
141: </td>
142: <tr>
143: <td>
144: <p><cfset nDisplayType="2">
145: <cfset nDisplayID="#qrycommunity.communityid#">

```

```
146: <cfset lVerbose = False>
147: <cfinclude template="resources.cfm"></p>
148: </td></tr>
149: <tr><td>
150: <cfif len(trim(qryCommunity.footerfilename)) gt 0>
151: <div align="center"></div>
152: </cfif>
153: </td></tr>
154: </cfoutput>
155: </table>
156: </td>
157: <td valign="top" width="1" bgcolor="#6666ff"></td>
158: <td valign="top" width="4" bgcolor="#ffffff"></td>
159: <td width="120" valign="top">
160: <cfinclude template="120x65ads.cfm">
161: </td>
162: </tr>
163: </table>
164: <cfinclude template="footer.cfm">
165: </body>
166: </html>
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <!-- These are for displaying x through y return results -->
4: <cfparam name="nStartFrom" default="1">
5: <cfparam name="nDisplay" default="10">
6: <cfparam name="nEnd" default="10">
7:
8:
9: <cfparam name="FORM.agentName" default="">
10: <cfparam name="FORM.agentFullName" default="">
11: <cfparam name="FORM.agencyName" default="">
12: <cfparam name="FORM.specialty" default="">
13:
14: <cfparam name="edtCommunity" default="None, None">
15:
16: <cfif listGetAt(edtCommunity,1) is "Region">
17:   <cfset FORM.Region = listGetAt(edtCommunity,2)>
18: <cfelseif listGetAt(edtCommunity,1) is "Community">
19:   <cfset FORM.communityID = listGetAt(edtCommunity,2)>
20: </cfif>
21:
22: <cfparam name="FORM.Region" default="">
23: <cfparam name="FORM.communityID" default="-1">
24: <!-- Community takes precedence over region -->
25:
26: <cfset FORM.agentName = preserveSingleQuotes(FORM.agentName)>
27: <cfset FORM.agentFullName = preserveSingleQuotes(FORM.agentFullName)>
28: <cfset FORM.agencyName = preserveSingleQuotes(FORM.agencyName)>
29: <cfset FORM.specialty = preserveSingleQuotes(FORM.specialty)>
30:
31: <cfif isDefined("sortagent.x")>
32:   <cfset csortorder = "fullname">
33: <cfelseif isDefined("sortspecialty.x")>
34:   <cfset csortorder = "entitySpecialty,fullname">
35: <cfelseif isDefined("sortphone.x")>
36:   <cfset csortorder = "workphone">
37: <cfelseif isDefined("sortemail.x")>
38:   <cfset csortorder = "entityEmail">
39: <cfelse>
40:   <cfset csortorder = "fullname">
41: </cfif>
42:
43:
44:
45: <cfif isDefined("URL.agencyID")>
46:   <cfif not isnumeric(URL.agencyID)>
47:     <cfset URL.agencyID = -1>
48:   </cfif>
49:   <cfset cLookedFor = "">
```

```

50:
51: <cfquery name="qrySearchResults" datasource="#sourceName#">
52:   select agents.agent_id as idNumber, agents.firstname+ 'agents.lastname as fullname,
53:   agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
54:   agents.email as entityEmail, agents.email,website,'agent' as rowType
55:   from agents
56:   where agents.distributorID = #ap_distributorID#
57:   and agents.agency_id = #URL.agencyid#
58:   order by #cSortOrder# <!-- fullname -->
59: </cfquery>
60:
61: <cftry>
62: <cfquery name="qryAgency" datasource="#sourceName#">
63:   select name from agency
64:   where agency.agency_id = #URL.agencyID#
65: </cfquery>
66: <cfif qryAgency.recordCount gt 0>
67:   <cfset cAgencyName = qryAgency.name>
68:   <cfelse>
69:     <cfset cAgencyName = "">
70:   </cfif>
71:   <cfcatch type="any">
72:     <cfset cAgencyName = "">
73:   </cfcatch>
74:   </cftry>
75:   <cfelse>
76:
77:   <!---
78:   This search is pretty ugly. If the actual informatio to search for was not found
79:   the paper wants to look for the first character. If that is not found, then
80:   everything is returned
81:   -->
82:
83:   <!--- Specially only entered -->
84:   <cfif form.agentfullname is "" and form.agencyname is "">
85:     <!--- This means return everything in the database -->
86:     <cfset clookedFor = "">
87:     <cfquery name="qrySearchResults" datasource="#sourceName#">
88:       SELECT agents.agent_id as idNumber,agents.firstname+ 'agents.lastname as fullname,
89:       agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
90:       agents.email as entityEmail, agents.email,website,'agent' as rowType
91:       from agents
92:       where agents.distributorID = #ap_distributorID#
93:       <cfif form.specialty is not "">
94:         and agents.specialty like '#form.specialty#%'
95:       </cfif>
96:       union select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
97:       agency.phone as workphone, agency.specialty as entitySpecialty,
98:       agency.email as entityEmail, agency.email, agency.URL_name as website,'agency' as rowType

```

```

99:      from agency
100:      where agency.distributorID = #ap_distributorID#
101:      <cfif form.specialty is not "">
102:      and agency.specialty like '#form.specialty#%'
103:      </cfif>
104:      order by #cSortOrder#
105:      </cfquery>
106:
107:      <!--- Agency name, not agent selected -->
108:      <cfelseif form.agentfullname is "" and form.agencyname is not "">
109:      <cfset cLookedFor = "">
110:      <cfquery name="qrySearchResults" datasource="#sourceName#">
111:      select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
112:      agency.phone as workphone, agency.specialty as entitySpecialty,
113:      agency.email as entityEmail, agency.email, agency.URL_name as website,'agency' as rowType
114:      from agency
115:      where agency.distributorID = #ap_distributorID#
116:      <cfif form.specialty is not "">
117:      and agency.specialty like '#form.specialty#%'
118:      </cfif>
119:      and agency.name like '#form.agencyName#%'
120:      order by #cSortOrder#
121:      </cfquery>
122:      <cfif qrySearchResults.recordCount is 0>
123:      <cfset cFirstLetter = ucase(left(form.agencyName,1))>
124:      <cfset cLookedFor = "The specific agency could not be found. Here are the results for all agencies starting with
      '#cFirstLetter#'.">
125:      <cfquery name="qrySearchResults" datasource="#sourceName#">
126:      select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
127:      agency.phone as workphone, agency.specialty as entitySpecialty,
128:      agency.email as entityEmail, agency.email, agency.URL_name as website,'agency' as rowType
129:      from agency
130:      where agency.distributorID = #ap_distributorID#
131:      <cfif form.specialty is not "">
132:      and agency.specialty like '#form.specialty#%'
133:      </cfif>
134:      and agency.name like '#cFirstLetter#%'
135:      order by #cSortOrder#
136:      </cfquery>
137:      <cfif qrySearchResults.recordCount is 0>
138:      <cfset cLookedFor = "The specific agency could not be found. Here are all the agencies available.">
139:      <cfquery name="qrySearchResults" datasource="#sourceName#">
140:      select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
141:      agency.phone as workphone, agency.specialty as entitySpecialty,
142:      agency.email as entityEmail, agency.email, agency.URL_name as website,'agency' as rowType
143:      from agency
144:      where agency.distributorID = #ap_distributorID#
145:      <cfif form.specialty is not "">
146:      and agency.specialty like '#form.specialty#%'

```

```

147:         </cfif>
148:         and agency.name like '#cFirstLetter#',
149:         order by #cSortOrder#
150:     </cfquery>
151: </cfif>
152: </cfif>
153:
154: <!-- Agent name entered, no agency entered -->
155: <cfelseif form.agentfullname is not "" and form.agencyname is "">
156:     <cfset clookedFor = "">
157:     <cfquery name="qrySearchResults" datasource="#sourceName#">
158:         SELECT agents.agent_id as idNumber,agents.firstname+' '+agents.lastname as fullname,
159:         agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
160:         agents.email as entityEmail, agents.email,website,'agent' as rowType
161:     from agents
162:     where agents.distributorID = #ap_distributorID#
163:     <cfif form.specialty is not "">
164:         and agents.specialty like '#form.specialty#%'
165:     </cfif>
166:     and (agents.firstname like '#form.agentfullname#%' or agents.lastname like '#form.agentfullname#%'
167:     or agents.firstname + ' ' + agents.lastname like '#form.agentfullname#%')
168: </cfquery>
169: <cfif qrySearchResults.recordCount is 0>
170:     <cfset cFirstLetter = ucase(left(form.agentfullname,1))>
171:     <cfset clookedFor = "The specific agent could not be found. Here are the results for all agents starting with
'#cFirstLetter#'. ">
172:     <cfquery name="qrySearchResults" datasource="#sourceName#">
173:         SELECT agents.agent_id as idNumber,agents.firstname+' '+agents.lastname as fullname,
174:         agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
175:         agents.email as entityEmail, agents.email,website,'agent' as rowType
176:     from agents
177:     where agents.distributorID = #ap_distributorID#
178:     <cfif form.specialty is not "">
179:         and agents.specialty like '#form.specialty#%'
180:     </cfif>
181:     and (agents.firstname like '#cFirstLetter#%' or agents.lastname like '#cFirstLetter#%')
182: </cfquery>
183: <cfif qrySearchResults.recordCount is 0>
184:     <cfset clookedFor = "The specific agent could not be found. Here are all the agents available<cfif form.specialty
is not ""> specializing in #form.specialty#</cfif>.">
185:     <cfquery name="qrySearchResults" datasource="#sourceName#">
186:         SELECT agents.agent_id as idNumber,agents.firstname+' '+agents.lastname as fullname,
187:         agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
188:         agents.email as entityEmail, agents.email,website,'agent' as rowType
189:     from agents
190:     where agents.distributorID = #ap_distributorID#
191:     <cfif form.specialty is not "">
192:         and agents.specialty like '#form.specialty#%'
193:     </cfif>

```



```

194:         </cfquery>
195:     </cfif>
196: </cfif>
197: <!-- agent and agency info entered -->
198: <cfelse>
199:     <cfset cLookedFor = "">
200:     <cfquery name="qrySearchResults" datasource="#sourceName#">
201:         SELECT agents.agent_id as idNumber,agents.firstname+' '+agents.lastname as fullname,
202:             agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
203:             agents.email as entityEmail, agents.email,website,'agent' as rowType
204:         from agents
205:         where agents.distributorID = #ap_distributorID#
206:         <cfif form.specialty is not "">
207:             and agents.specialty like '#form.specialty#%'
208:         </cfif>
209:         and (agents.firstname like '#form.agentfullname#%' or agents.lastname like '#form.agentfullname#%',
210:             or agents.firstname + ' ' + agents.lastname like '#form.agentfullname#%')
211:         union select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
212:             agency.phone as workphone, agency.specialty as entitySpecialty,
213:             agency.email as entityEmail, agency.email, agency.URL_name as website,'agency' as rowType
214:         from agency
215:         where agency.distributorID = #ap_distributorID#
216:         <cfif form.specialty is not "">
217:             and agency.specialty like '#form.specialty#%'
218:         </cfif>
219:         and agency.name like '#form.agencyName#%'
220:         order by #cSortOrder#
221:     </cfquery>
222:
223:     <cfif qrySearchResults.recordCount is 0>
224:         <!-- no agent name AND no agency found -->
225:         <cfset cFirstAgent = ucase(left(form.agentFullname,1))>
226:         <cfset cFirstAgency = ucase(left(form.agencyName,1))>
227:         <cfset cLookedFor = "The specific agent and agency could not be found. Here are the results for all agents starting
            with '#cFirstAgent#' and agencies starting with '#cFirstAgency#'.">
228:         <cfquery name="qrySearchResults" datasource="#sourceName#">
229:             SELECT agents.agent_id as idNumber,agents.firstname+' '+agents.lastname as fullname,
230:                 agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
231:                 agents.email as entityEmail, agents.email,website,'agent' as rowType
232:             from agents
233:             where agents.distributorID = #ap_distributorID#
234:             <cfif form.specialty is not "">
235:                 and agents.specialty like '#form.specialty#%'
236:             </cfif>
237:             and (agents.firstname like '#cFirstAgent#%' or agents.lastname like '#cFirstAgent#%')
238:             union select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
239:                 agency.phone as workphone, agency.specialty as entitySpecialty,
240:                 agency.email as entityEmail, agency.email, agency.URL_name as website,'agency' as rowType
241:             from agency

```

```

242: where agency.distributorID = #ap_distributorID#
243: <cfif form.specialty is not "">
244:   and agency.specialty like '#form.specialty#%'
245: </cfif>
246: and agency.name like '#cFirstAgency#%'
247: order by #cSortOrder#
248: </cfquery>
249:
250: <cfif qrySerachResults.recordCount is 0>
251:   <cfset cLookedFor = "The specific agent and agency could not be found. Here are all the agents and agencies
available">
252:   <cfif form.specialty is not ""> specializing in #form.specialty#</cfif>.">
253:   <cfquery name="qrySearchResults" datasource="#sourceName#">
254:     SELECT agents.agent_id as idNumber,agents.firstname+' '+agents.lastname as fullname,
255:     agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
256:     agents.email as entityEmail, agents.email,website,'agent' as rowType
257:   from agents
258:   where agents.distributorID = #ap_distributorID#
259:   <cfif form.specialty is not "">
260:     and agents.specialty like '#form.specialty#%'
261:   </cfif>
262:   union select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
263:   agency.phone as workphone, agency.specialty as entitySpecialty,
264:   agency.email as entityEmail, agency.email, agency.URL_name as website,'agency' as rowType
265:   from agency
266:   where agency.distributorID = #ap_distributorID#
267:   <cfif form.specialty is not "">
268:     and agency.specialty like '#form.specialty#%'
269:   </cfif>
270:   order by #cSortOrder#
271: </cfquery>
272: </cfif>
273: </cfif>
274:
275: <cfif qrySearchResults.recordCount is 0>
276:   <!--- Nothing has been found, so return absolutely everything in the database --->
277:   <cfset cLookedFor = "The specific agent and agency could not be found. Here are all the agents and agencies
available.">
278:   <cfquery name="qrySearchResults" datasource="#sourceName#">
279:     SELECT agents.agent_id as idNumber,agents.firstname+' '+agents.lastname as fullname,
280:     agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
281:     agents.email as entityEmail, agents.email,website,'agent' as rowType
282:   from agents
283:   where agents.distributorID = #ap_distributorID#
284:   union select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
285:   agency.phone as workphone, agency.specialty as entitySpecialty,
286:   agency.email as entityEmail, agency.email, agency.URL_name as website,'agency' as rowType
287:   from agency
288:   where agency.distributorID = #ap_distributorID#

```

```

289:         order by #csortOrder#
290:     </cfquery>
291: </cfif>
292:
293: <!--
294: <!-- Need to test for various kinds of agent finds --->
295: <cfif form.agentfullname is not "">
296:     <cfset cFirstLetter = left(form.agentfullname,1)>
297:     <cfquery name="qryFindAgent" datasource="#sourceName#">
298:         select agents.agent_id from agents
299:         where agents.firstname like '#form.agentfullname#%' or
300:             agents.lastname like '#form.agentfullname#%' or
301:             agents.firstname + ' ' + agents.lastname like '#form.agentfullname#%'
302:     </cfquery>
303:     <cfif qryFindAgent.recordCount gt 0>
304:         <cfset nAgentQuery = 1>
305:         <cfset cFoundAgent = 'Found the agent you were searching for.'>
306:         <cfelse>
307:             <cfquery name="qryFindAgent" datasource="#sourceName#">
308:                 select agents.agent_id from agents
309:                 where agents.firstname like '#cFirstLetter#%' or
310:                     agents.lastname like '#cFirstLetter#%'
311:             </cfquery>
312:             <cfif qryFindAgent.recordCount gt 0>
313:                 <cfset nAgentQuery = 2>
314:                 <cfset cFoundAgent = "There was no matches for the agent. Here are all matches for the first letter of your search.">
315:                 <cfelse>
316:                     <cfset nAgentQuery = 3>
317:                     <cfset cFoundAgent = "There were no matches of the agent. Here is a list of all agents.">
318:                     </cfif>
319:                 </cfif>
320:             <cfelse>
321:                 <cfset nAgentQuery = -1>
322:                 <cfset cFoundAgent = "">
323:             </cfif>
324:
325:             <cfquery name="qrySearchResults" datasource="#sourceName#">
326:                 <cfif nAgentQuery gt 0>
327:                     SELECT agents.agent_id as idNumber,agents.firstname+' '+agents.lastname as fullname,
328:                         agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
329:                         agents.email as entityEmail, agents.email,website,'agent' as rowType
330:                     from agents <!-- <cfif form.agencyName is not "">,agency</cfif> --->
331:                     where 1=1
332:                     and (agents.distributorID = #ap_dist_idbutorID#)
333:                 <cfif form.agentfullname is not "">
334:                     <cfif nAgentQuery is 1>
335:                         and (agents.firstname like '#form.agentfullname#%' or
336:                             agents.lastname like '#form.agentfullname#%' or
337:                             agents.firstname + ' ' + agents.lastname like '#form.agentfullname#%')

```

```

338: <cfelseif nAgentQuery is 2>
339:   and (agents.firstname like '#cFirstLetter#' or
340:     agents.lastname like '#cFirstLetter#')
341: </cfif>
342:
343: <!-- and (agents.lastname = #FORM.agentFullName# or agents.firstname = #FORM.agentFullName#
344:   or fullname = #FORM.agentFullName#) -->
345:
346: <!-- and (agents.lastname, ' + agents.firstname = #FORM.agentFullName#) -->
347: </cfif>
348: <!-- <cfif form.agentName is not ""> -->
349: <!-- and (agents.firstname like '#FORM.agentName#' or agents.lastname like '#FORM.agentName#') -->
350: <!-- </cfif> -->
351: <cfif form.specialty is not "">
352:   and (agents.specialty like '#FORM.specialty#')
353: </cfif>
354: <cfif FORM.communityID gt 1>
355:   and ((agents.agent_id in (select prop_main.agent_ID from prop_main where prop_main.communityID=#FORM.communityID#)
356:     or (( in LOCATE('*2|#FORM.communityID#', agents.communities) ) > 0))
357: </cfif>
358: <cfif FORM.Region is not "">
359:   and (agents.agent_id in (select prop_main.agent_id from prop_main,communities where prop_main.agent_id=agents.agent_id
    and
    communities.communityID=prop_main.communityID and communities.Region = '#FORM.Region#'))
360: </cfif>
361: </cfif>
362: </cfif>
363: <cfif form.agencyName is not "">
364:   <cfif nAgentQuery gt 0>union</cfif> select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
365:     agency.phone as workphone, agency.specialty as entitySpecialty,
366:     agency.email as entityEmail, agency.email, agency.URL_name as website, 'agency' as rowType
367:   from agency
368:   where agency.distributorID=#ap_distributorID#
369:   and agency.name like '#FORM.agencyName#'
370:   <cfif trim(form.specialty) is not "">
371:     and agency.specialty like '#FORM.specialty#'
372:   </cfif>
373: </cfif>
374: <!--
375:   <cfif FORM.agencyName is not "">
376:     and (agents.agency_id=agency.agency_id)
377:     and agency.name like '#FORM.agencyName#'
378:   union select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
379:     agency.phone as workphone, agency.specialty as entitySpecialty,
380:     agency.email as entityEmail, agency.email, agency.URL_name as website, 'agency' as rowType
381:   from agency
382:   where 1=1
383:   and (agency.distributorID=#ap_distributorID#
384:     and agency.name like '#FORM.agencyName#'
385:     <cfif trim(form.specialty) is not "">

```

```

386:         and agency.specialty like '#FORM,selected' and agency.id = #id#
387:         </cfif>
388:         </cfif>
389:         --->
390:         order by #cSortOrder# <!--- fullname --->
391:         </cfquery>
392:         -->
393:         </cfif>
394:         <!--
395:         select agent_id as idNumber,firstname+ ' ' +lastname as name,workphone,email,'1' as rowType from agents
396:         where agents.lastname like 'Shier%'
397:         union select agent_id as idNumber,name,phone,email,'2' as rowType from agency
398:         where agency.name like 'Cold%'
399:         order by name
400:         ---->
401:
402:         <!-- If there are absolutely no results, then show everything --->
403:         <!---
404:         <cfif qrySearchResults.recordCount is 0>
405:         <cfset cFoundAgent = "There were no matches to your query. Here is everything...">
406:         <cfquery name="qrySearchResults" datasource="#sourceName#"
407:             SELECT agents.agent_id as idNumber,agents.firstname+ 'agents.lastname as fullname,
408:             agents.specialty,agents.workphone, agents.specialty as entitySpecialty,
409:             agents.email as entityEmail, agents.email,website,'agent' as rowType
410:             from agents <!--- <cfif form.agencyName is not "">,agency</cfif> -->
411:             where agents.distributorID = #ap_distributorID#
412:             union select agency.agency_id as idNumber,agency.name as fullname, agency.specialty,
413:             agency.phone as workphone, agency.specialty as entitySpecialty,
414:             agency.email as entityEmail, agency.email, agency.url_name as website,'agency' as rowType
415:             from agency
416:             where agency.distributorID=#ap_distributorID#
417:             order by #cSortOrder#
418:         </cfquery>
419:         </cfif>
420:         --->
421:
422:         <!-- checks to see how many results to display --->
423:         <CFSET nViewTo = #nStartFrom#+#nToDisplay#-1>
424:         <CFIF nViewTo GT #qrySearchResults.recordCount#>
425:             <CFSET nViewTo = #qrySearchResults.recordCount#>
426:         </CFIF>
427:
428:         <html>
429:         <head>
430:             <title>Realty Objects</title>
431:             <link rel="stylesheet" href="style1.css" type="text/css">
432:         </head>
433:
434:         <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">

```

- 10 -

```
482: <input type="hidden" name="specialty" value="#FORM.Specialty#">
483: </cfoutput>
484:
485: <td><input type="image" name="sortagent" src="images/sortby_name.gif" width="76" height="14" border="0"
      alt="Sort by Agent/Agency"></td>
486: <td><input type="image" name="sortspecialty" src="images/sortby_specialty.gif" width="90" height="14"
      alt="Sort by Specialty" border="0"></td>
487: <td><input type="image" name="sortphone" src="images/sortby_phone.gif" width="78" height="14" alt="Sort by
      Phone" border="0"></td>
488: <td><input type="image" name="sortemail" src="images/sortby_email.gif" width="76" height="14" alt="Sort by
      Email" border="0"></td>
489: </tr>
490: </form>
491: </cfif>
492: <cfoutput query="qrySearchResults" startrow="#instartFrom#" maxrows="#ntoDisplay#">
493: <tr bgcolor="#If(Currentrow Mod 2, DE('fffff'), DE('eeeeee'))#">
494: <cfif qrySearchResults.rowType is "agent">
495: <cfquery name="qryFindOHT" datasource="#SourceName#">
496:   select id,startdate,stopdate,htfilename, otherURL
497:   from adData
498:   where callingId=#qrySearchResults.idNumber#
499:   and callingtype=1
500: </cfquery>
501: <cfif trim(qrySearchResults.website) is not "">
502: <td><a href="#qrySearchResults.website#" target="_blank">Website</a></td>
503: <cfelse>
504: <td><a href="agtntview.cfm?agent_id=#qrySearchResults.idNumber#">View</a></td>
505: </cfif>
506: <cfif qryFindOHT.recordcount gt 0>
507: <cfif trim(qryFindOHT.otherURL) is not "">
508: <td><a href="#qryFindOHT.otherURL#" target="_blank">Website</a></td>
509: <cfelseif trim(qryFindOHT.htfilename) is not "">
510: <td><a href="#qryFindOHT.htfilename#" target="_blank">Bio</a></td>
511: <cfelse>
512: <td>&nbsp;</td>
513: </cfif>
514: <cfelse>
515: <td>&nbsp;</td>
516: </cfif>
517: <cfelse>
518: <cfif trim(qrySearchResults.website) is not "">
519: <td><a href="#qrySearchResults.website#">View</a></td>
520: <cfelse>
521: <td><a href="agencyview.cfm?agency_id=#qrySearchResults.idNumber#">View</a></td>
522: </cfif>
523: <td>&nbsp;</td>
524: </cfif>
525: <td>&nbsp;</td>
526: <!-- <td>#trim(qrySearchResults.firstname) # #trim(qrySearchResults.lastname) #</td> -->
```

```

527: <td>#qrySearchResults.fullname#4/<td>#qrySearchResults.specialty#</td>
528: <td>#qrySearchResults.specialty#</td>
529: <td nowrap>#qrySearchResults.workphone#</td>
530: <td><a href="mailto:#qrySearchResults.email#">#qrySearchResults.email#</a></td>
531: </tr>
532: </cfoutput>
533: <cfif qrySearchResults.recordCount is 0>
534: <tr><td colspan="6" align="center"><em>There were no matches to your search criteria.</em></td></tr>
535: </cfif>
536: </table>
537: <CFSET nPrevStart = nStartFrom-nToDisplay>
538: <CFSET nNextStart = nStartFrom+nToDisplay>
539: <CFSET nPrevEnd = #nPrevStart#+nToDisplay-1>
540: <CFSET nNextEnd = #nNextStart#+nToDisplay-1>
541:
542: <table border="0" align="center">
543: <tr>
544: <CFIF nPrevStart GTE 1>
545: <td>
546: <CFOUTPUT>
547: <FORM ACTION="#findAgent_result.cfm<cfif isDefined("URL.agencyID")>?agencyID=#URL.agencyID#</cfif>"
METHOD="POST">
548: <input type="hidden" name="agentName" value="#FORM.agentName#">
549: <input type="hidden" name="agentFullName" value="#FORM.agentFullName#">
550: <input type="hidden" name="agencyName" value="#FORM.agencyName#">
551: <input type="hidden" name="specialty" value="#FORM.specialty#">
552: <cfif isDefined("sortagent.x")>
553: <input type="hidden" name="sortagent.x">
554: <cfelseif isDefined("sortspecialty.x")>
555: <input type="hidden" name="sortspecialty.x">
556: <cfelseif isDefined("sortphone.x")>
557: <input type="hidden" name="sortphone.x">
558: <cfelseif isDefined("sortemail.x")>
559: <input type="hidden" name="sortemail.x">
560: </cfif>
561:
562: <INPUT TYPE="hidden" NAME="nStartFrom" VALUE="#nPrevStart#">
563: <INPUT TYPE="hidden" NAME="nToDisplay" VALUE="#nToDisplay#">
564: <INPUT TYPE="hidden" NAME="nEnd" VALUE="#nPrevEnd#">
565: <INPUT TYPE="submit" VALUE="Previous #nToDisplay#">
566: </FORM>
567: </CFOUTPUT>
568: </td>
569: </CFIF>
570: <CFIF nNextStart LTE qrySearchResults.recordCount>
571: <td>
572: <CFOUTPUT>
573: <FORM ACTION="#findAgent_result.cfm<cfif isDefined("URL.agencyID")>?agencyID=#URL.agencyID#</cfif>"
METHOD="POST">

```



```
574: <input type="hidden" name="agentName" value="#FORM.agentName#">
575: <input type="hidden" name="agentFullName" value="#FORM.agentFullName#">
576: <input type="hidden" name="agencyName" value="#FORM.agencyName#">
577: <input type="hidden" name="specialty" value="#FORM.specialty#">
578: <cfif isDefined("sortagent.x")>
579: <input type="hidden" name="sortagent.x">
580: <cfelseif isDefined("sortspecialty.x")>
581: <input type="hidden" name="sortspecialty.x">
582: <cfelseif isDefined("sortphone.x")>
583: <input type="hidden" name="sortphone.x">
584: <cfelseif isDefined("sortemail.x")>
585: <input type="hidden" name="sortemail.x">
586: </cfif>
587:
588: <INPUT TYPE="hidden" NAME="nStartFrom" VALUE="#nNextStart#">
589: <INPUT TYPE="hidden" NAME="nToDisplay" VALUE="#nToDisplay#">
590: <INPUT TYPE="hidden" NAME="nEnd" VALUE="#nNextEnd#">
591: <cfset nLeftToShow = min(nToDisplay, (qrySearchResults.recordcount - cToDisplay))>
592: <INPUT TYPE="submit" VALUE="Next #nLeftToShow#">
593: </FORM>
594: </CFOUTPUT>
595: </td>
596: </CFIF>
597: </tr>
598: </table>
599: </td>
600: </tr>
601: </table>
602: </td>
603: <td valign="top" width="1" bgcolor="#6666ff"></td>
604: <td valign="top" width="4" bgcolor="#ffffff"></td>
605: <td width="120" valign="top">
606: <cfinclude template="120x65ads.cfm">
607: </td>
608: </tr>
609: </table>
610: <cfinclude template="footer.cfm">
611: </body>
612: </html>
```

11/29/2000 8:08:36 AM  
Transitional/FEN

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfparam name="nStartFrom" default="1">
4: <cfparam name="ntoDisplay" default="10">
5: <cfparam name="nEnd" default="10">
6:
7: <cftry>
8:   <cfset minPrice = #val(minValue)#>
9:   <cfcatch type="any">
10:     <cfset minPrice=0>
11:   </cfcatch>
12: </cftry>
13:
14: <cftry>
15:   <cfset maxPrice = #val(maxValue)#>
16:   <cfcatch type="any">
17:     <cfset maxPrice=999999999>
18:   </cfcatch>
19: </cftry>
20:
21: <cftry>
22:   <cfset minbedrooms = #val(minbedrooms)#>
23:   <cfcatch type="any">
24:     <cfset minbedrooms=0>
25:   </cfcatch>
26: </cftry>
27:
28:
29: <cftry>
30:   <cfset minBathrooms = #val(minBathrooms)#>
31:   <cfcatch type="any">
32:     <cfset minBathrooms=0>
33:   </cfcatch>
34: </cftry>
35:
36: <cfparam name="edtCommunity" default="None,None">
37:
38: <cfif listGetAt(edtCommunity,1) is "Region">
39:   <cfset FORM.Region = listGetAt(edtCommunity,2)>
40:   <cfelseif listGetAt(edtCommunity,1) is "Community">
41:     <cfset FORM.communityID = listGetAt(edtCommunity,2)>
42:   </cfif>
43:
44:
45: <cfparam name="county" default="All">
46:
47: <cfparam name="FORM.Region" default="*">
48: <cfparam name="FORM.communityID" default="-1">
49: <cfparam name="FORM.propertyTypeID" default="-1">
```

```
50: <cfif isDefined("URL.agent_id")>
51:   <cfset FORM.agent_id = URL.agent_id>
52: </cfif>
53: <cfparam name="FORM.agent_id" default="-1">
54:
55: <!--- Community takes precedence over region --->
56:
57: <cfinclude template="proplists.cfm">
58: <!--- BWS 5/8 --->
59: <cfset nLotLen = listlen(ls_LotType)>
60:
61: <!--- BWS 5/8 --->
62:
63: <cfset cStatus = "">
64: <cfloop from="1" to="#listlen(ls_SearchStatus)#" index="nIndex">
65:   <cfif listGetAt(ls_SearchStatus,nIndex) is 1>
66:     <cfif cStatus is not "">
67:       <cfset cStatus = cStatus & ", ">
68:     </cfif>
69:     <cfset cStatus = cStatus & nIndex>
70:   </cfif>
71: </cfloop>
72:
73: <!--- JH 5/8 --->
74: <cfparam name="edtLotType" default="0">
75: <!--- BWS 5/8 --->
76: <cfset cLotType = "">
77: <cfif #edtLotType# EQ 0>
78:   <cfset cLotType = "ALL">
79: </cfelse>
80:   <cfloop from="1" to="#listlen(ls_LotType)#" index="nIndex">
81:     <cfif listGetAt(ls_LotType, edtLotType) GTE 1>
82:       <cfset cLotType = listGetAt(#ls_LotType#,edtLotType)>
83:     </cfif>
84:   </cfloop>
85: </cfif>
86:
87: <cfparam name="edtPropType" default="0">
88: <cfset cPropType = "">
89: <cfif #edtPropType# EQ 0>
90:   <cfset cPropType = "ALL">
91: </cfif>
92:
93: <cfparam name="edtHomeType" default="0">
94: <cfset cHomeType = "">
95: <cfif #edtHomeType# EQ 0>
96:   <cfset cHomeType = "ALL">
97: </cfelse>
98:   <cfloop from="1" to="#listlen(ls_HomeType)#" index="nIndex">
```

```

99:  <cfif listGetAt(ls_HomeType, edtHomeType, edtHomeType) # "" >
100:    <cfset cHomeType = listGetAt(ls_HomeType, edtHomeType) >
101:    </cfif>
102:    </cfloop>
103:    </cfif>
104:
105:    <!-- BWS 5/8 --->
106:
107:    <!-- JHJ 6/1 Image submit only passed name.x and name.y, no values; so check for existence of each button --->
108:    <cfif isDefined("sortname.x") >
109:      <cfset sortorder = "prop_main.name">
110:      <cfelseif isDefined("sortprice.x") >
111:        <cfset sortorder = "prop_main.price">
112:        <cfelseif isDefined("sortbedroom.x") >
113:          <cfset sortorder = "prop_main.bedroom,prop_main.price">
114:          <cfelseif isDefined("sortbath.x") >
115:            <cfset sortorder = "prop_main.bath,prop_main.price">
116:            <cfelse>
117:              <cfset sortorder = "prop_main.price">
118:            </cfif>
119:
120:            <cfif isDefined("URL.agencyID") >
121:              <cfif not isnumeric(URL.agencyID) >
122:                <cfset URL.agencyID = -1>
123:              </cfif>
124:
125:              <cfquery name="qSearchResults" datasource="#sourcename#">
126:                select prop_main.prop_id, prop_main.name,prop_main.price,prop_main.bedroom,prop_main.bath, prop_main.communityID,
127:                  prop_main.status
128:                from prop_main
129:                where prop_main.agency_id = #URL.agencyid#
130:                order by #sortorder#
131:              </cfquery>
132:
133:            <cftry>
134:              <cfquery name="qryAgency" datasource="#sourcename#">
135:                select name from agency
136:                where agency.agency_id = #URL.agencyID#
137:              </cfquery>
138:              <cfif qryAgency.recordCount gt 0>
139:                <cfset cAgencyName = qryAgency.name>
140:              <cfelse>
141:                <cfset cAgencyName = "">
142:              </cfif>
143:              <cfcatch type="any">
144:                <cfset cAgencyName = "">
145:              </cfcatch>
146:            </cftry>
147:            <cfelse>

```

```

148: <cfquery name="qSearchResults" datasource="#source#"#sourceName#">
149: SELECT prop_main.prop_id,prop_main.name, prop_main.price, prop_main.bath, prop_main.bedroom, prop_main.communityID,
150: prop_main.status, prop_main.seeItBuyIt
151: <cfif #FORM.communityID# gt -1>,communities.name as commName
152: <cfelseif #FORM.Region# is not "">,communities.region
153: <cfelseif #FORM.PropertyTypeID# gt -1>,prop_main.findPropType
154: </cfif>
155: FROM prop_main<cfif #FORM.communityID# gt -1>,communities<cfelseif #FORM.Region# is not "">,communities</cfif>
156: WHERE (prop_main.price >= #minPrice#) AND
157: (prop_main.price <= #maxPrice#) AND
158: (prop_main.bath >= #minBathrooms#) AND
159: (prop_main.bedroom >= #minBedrooms#)
160: AND (prop_main.status IN (#cStatus#))
161: AND (prop_main.distributorID = #ap_distributorID#)
162: <cfif #FORM.agent_id# gt -1>
163: AND (prop_main.agent_id = #FORM.agent_id#)
164: </cfif>
165: <cfif #county# IS NOT "All">
166: AND (prop_main.county = '#county#')
167: </cfif>
168: <cfif #edtHomeType# IS NOT 0>
169: AND (prop_main.hometype = '#edtHomeType#')
170: </cfif>
171: <cfif #edtPropType# IS NOT 0>
172: AND (prop_main.propdscrip = '#edtPropType#')
173: </cfif>
174: <cfif #edtLotType# IS NOT 0>
175: AND (prop_main.lotttype = '#edtLotType#')
176: </cfif>
177: <cfif #FORM.communityID# gt -1>
178: AND (communities.communityID = prop_main.communityID)
179: AND (prop_main.communityID = #FORM.communityID#)
180: <cfelseif #FORM.Region# is not "">
181: AND (communities.communityID = prop_main.communityID)
182: AND (communities.region = '#FORM.Region#')
183: <cfelseif #FORM.PropertyTypeID# gt -1>
184: <!--- AND ('#FORM.propertyTypeID#' IN (prop_main.findPropType)) --->
185: AND ({ fn LOCATE('#FORM.propertyTypeID', prop_main.findPropType) } > 0)
186: </cfif>
187: AND prop_main.distributorID = #ap_distributorID#
188: ORDER BY #sortOrder#
189: </cfquery>
190: </cfif>
191:
192: <cfif qSearchResults.recordCount is 0>
193: <cfquery name="qCommName" datasource="#sourceName#">
194: SELECT communities.name as commName
195: FROM communities
196: WHERE communities.communityID = #FORM.communityID#

```

```

197:     </cfquery>
198:   </cfif>
199:
200:   <!--- <cfif #FORM.communityID# gt -1>,communities.name as commName --->
201:   <!--- AND (prop_main.communityID = #FORM.communityID#) --->
202:
203:
204:   <!--- checks to see how many results to display --->
205:   <CFSET nViewTo = #nStartFrom+#nToDisplay#-1>
206:   <CFIF nViewTo GT #qSearchResults.recordCount#>
207:     <CFSET nViewTo = #qSearchResults.recordCount#>
208:   </CFIF>
209:
210:   <CFSET thisPath= ExpandPath("*.")>
211:   <CFSET thisDirectory= GetDirectoryFromPath(thisPath)>
212:
213:   <html>
214:   <head>
215:     <title><cfoutput>#ap_agencyName# - Find a Home - Search Results</cfoutput></title>
216:     <link rel="stylesheet" href="style1.css" type="text/css">
217:   </head>
218:
219:   <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
220:
221:   <cfset nEntityType = 5> <!--- Property Pages = 5 --->
222:   <cfset nEntityID = 0> <!--- All property pages = 0 --->
223:   <cfinclude template="include\pageFormat.cfm">
224:
225:   <cfinclude template="header_bannerad.cfm">
226:
227:   <cfif isDefined("url.agencyID")>
228:     <cfset cOtherURL = "?agencyID=#url.agencyID#">
229:   <cfelseif isDefined("url.agent_id")>
230:     <cfset cOtherURL = "?agent_id=#url.agent_id#">
231:   <cfelse>
232:     <cfset cOtherURL = "">
233:   </cfif>
234:
235:
236:   <table width="760" border="0" cellpadding="0" cellspacing="0">
237:     <tr><td align="right" valign="top" bgcolor="#<cfoutput>#cNavColor#</cfoutput>" width="135">
238:       <cfinclude template="navigation.cfm">
239:     </td>
240:     <td width="500" valign="top" align="center">
241:       <table border="0" width="480" cellspacing="2">
242:         <tr>
243:           <td bgcolor="#<cfoutput>#cMenuColor#</cfoutput>" class="heading">Find a Home - Search Results</td>
244:         </tr>
245:         <tr>

```

```
246: <cfoutput>
247: <td>
248: <blockquote>
249: <cfif #ntoDisplay# GTE qSearchResults.recordCount>
250: <cfset cToDisplay = min(qSearchResults.recordCount, #ntoDisplay#)>
251: </cfif>
252: <cfif qSearchResults.recordCount GTE #ntoDisplay#>
253: <cfset cToDisplay = min(qSearchResults.recordCount, #nEnd#)>
254: </cfif>
255: <cfset cStartFrom = min(qSearchResults.recordCount, #nStartFrom#)>
256: <p align="center">(Viewing records #cstartFrom# to #cToDisplay# out of #qSearchResults.recordCount#) <a
href="propTypeSrch.cfm"><b>New Search</b></a></p>
</blockquote>
257: <cfif not isDefined("URL.agencyID") AND qSearchResults.recordCount gt 0>
258: <table border="0" align="center" width="350">
259: <tr>
260: <td valign="top"><b>Price:</b>
261: <em>#numberFormat(minprice)#</em> to <em>#numberFormat(maxprice)#</em><br>
262: <b>Property Type:</b>
263: <cfif edtPropType is 0>
264: <em>All</em><br>
265: <cfelse>
266: <em>#listGetAt(ls_propDscpt, edtPropType)#</em><br>
267: </cfif>
268: </td>
269: <td valign="top">
270: <cfif edtPropType is "5">
271: <b>Bathrooms:</b> <em>#minBathrooms#</em><br>
272: <b>Bedrooms:</b> <em>#minBedrooms#</em>
273: </cfif>
274: </td>
275: </tr>
276: </table>
277: </cfif>
278: <form action="FindProperty_Result.cfm#otherURL#" method="post">
279: <input type="hidden" name="minvalue" value="#minprice#">
280: <input type="hidden" name="maxvalue" value="#maxprice#">
281: <input type="hidden" name="minbedrooms" value="#minbedrooms#">
282: <input type="hidden" name="minbathrooms" value="#minbathrooms#">
283: <input type="hidden" name="sortorder" value="#sortorder#">
284: <cfif not isDefined("agentID")>
285: <input type="hidden" name="agentID" value="-1">
286: <cfelse>
287: <input type="hidden" name="agentID" value="#agentID#">
288: </cfif>
289: <input type="hidden" name="county" value="#county#">
290: <input type="hidden" name="edtHomeType" value="#edtHomeType#">
291:
292:
293:
```





```
339: <td align="center">
340: <cfif #int (bedroom) # eq bedroom>
341: #int (bedroom) #
342: <cfelse>
343: #numberFormat (bedroom, 99.9) #
344: </cfif>
345: </td>
346: <td align="center">
347: <cfif #int (bath) # eq bath>
348: #int (bath) #
349: <cfelse>
350: #numberFormat (bath, 99.9) #
351: </cfif>
352: </td>
353: </cfif>
354: </tr>
355: </cfoutput>
356: </table>
357: </form>
358: <cfif qSearchResults.recordCount is 0>
359: <em>There were no matches to your search criteria.</em>
360: </cfif>
361: <CFSET nPrevStart = nStartFrom-nToDisplay>
362: <CFSET nNextStart = nStartFrom+nToDisplay>
363: <CFSET nPrevEnd = #nPrevStart#+nToDisplay-1>
364: <CFSET nNextEnd = #nNextStart#+nToDisplay-1>
365: <table border="0" align="center">
366: <tr>
367: <CFIF nPrevStart GTE 1>
368: <td>
369: <CFOUTPUT>
370: <form action="findProperty_result.cfm#cOtherURL#" METHOD="POST">
371: <input type="hidden" name="minvalue" value="#minprice#">
372: <input type="hidden" name="maxvalue" value="#maxprice#">
373: <input type="hidden" name="minbedrooms" value="#minbedrooms#">
374: <input type="hidden" name="minbathrooms" value="#minbathrooms#">
375: <input type="hidden" name="sortorder" value="#sortorder#">
376: <cfif not isDefined("agentID")>
377: <input type="hidden" name="agentID" value="-1">
378: <cfelse>
379: <input type="hidden" name="agentID" value="#agentID#">
380: </cfif>
381: <input type="hidden" name="county" value="#county#">
382: <input type="hidden" name="edHomeType" value="#edHomeType#">
383: <input type="hidden" name="edPropType" value="#edPropType#">
384: <input type="hidden" name="edLotType" value="#edLotType#">
385: <cfif isDefined("communityID")>
386: <input type="hidden" name="communityID" value="#communityID#">
387: </cfif>
```

```
388: <cfif isDefined("region")><input type="hidden" name="region" value="#region#">
389: </cfif>
390: <cfif isDefined("sortname.x")>
391: <input type="hidden" name="sortname.x">
392: <cfelseif isDefined("sortprice.x")>
393: <input type="hidden" name="sortprice.x">
394: <cfelseif isDefined("sortbedroom.x")>
395: <input type="hidden" name="sortbedroom.x">
396: <cfelseif isDefined("sortbath.x")>
397: <input type="hidden" name="sortbath.x">
398: </cfif>
399: <INPUT TYPE="hidden" NAME="nStartFrom" VALUE="#nPrevStart#">
400: <INPUT TYPE="hidden" NAME="nToDisplay" VALUE="#nToDisplay#">
401: <INPUT TYPE="hidden" NAME="nEnd" VALUE="#nPrevEnd#">
402: <INPUT TYPE="submit" VALUE="Previous #nToDisplay#">
403: </FORM>
404: </CFOUTPUT>
405: </TD>
406: </CFIF>
407: <CFIF nNextStart LTE qSearchResults.recordCount>
408: <TD>
409: <CFOUTPUT>
410: <FORM ACTION="findProperty_result.cfm#cOtherURL#" METHOD="POST">
411: <input type="hidden" name="minvalue" value="#minprice#">
412: <input type="hidden" name="maxvalue" value="#maxprice#">
413: <input type="hidden" name="minbedrooms" value="#minbedrooms#">
414: <input type="hidden" name="minbathrooms" value="#minbathrooms#">
415: <input type="hidden" name="sortorder" value="#sortorder#">
416: <cfif not isDefined("agentID")>
417: <input type="hidden" name="agentID" value="-1">
418: <cfelse>
419: <input type="hidden" name="agentID" value="#agentID#">
420: </cfif>
421: <input type="hidden" name="county" value="#county#">
422: <input type="hidden" name="edtHomeType" value="#edtHomeType#">
423: <input type="hidden" name="edtPropType" value="#edtPropType#">
424: <input type="hidden" name="edtLotType" value="#edtLotType#">
425: <cfif isDefined("communityID")>
426: <input type="hidden" name="communityID" value="#communityID#">
427: </cfif>
428: <cfif isDefined("region")>
429: <input type="hidden" name="region" value="#region#">
430: </cfif>
431: <cfif isDefined("sortname.x")>
432: <input type="hidden" name="sortname.x">
433: <cfelseif isDefined("sortprice.x")>
434: <input type="hidden" name="sortprice.x">
435: <cfelseif isDefined("sortbedroom.x")>
```

```
437: <input type="hidden" name="sortbath.x">
438: <cfelseif isdefined("sortbath.x")>
439: <input type="hidden" name="sortbath.x">
440: </cfif>
441: <INPUT TYPE="hidden" NAME="nStartFrom" VALUE="#nNextStart#">
442: <INPUT TYPE="hidden" NAME="nToDisplay" VALUE="#nToDisplay#">
443: <INPUT TYPE="hidden" NAME="nEnd" VALUE="#nNextEnd#">
444: <cfset nLeftToShow = min(nToDisplay, (qSearchResults.recordcount - cToDisplay))>
445: <INPUT TYPE="submit" VALUE="Next #nLeftToShow#">
446: </FORM>
447: </CFOUTPUT>
448: </td>
449: </CFIF>
450: </tr>
451: </table>
452: </td>
453: </tr>
454: </table>
455: </td>
456: <td valign="top" width="1" bgcolor="#666666ff"></td>
457: <td valign="top" width="4" bgcolor="#ffffff"></td>
458: <td width="120" valign="top">
459: <cfinclude template="120x65ads.cfm">
460: </td>
461: </tr>
462: </table>
463: <cfinclude template="footer.cfm">
464: </body>
465: </html>
```

```
1: <cfparam name="lFormat" default="False">
2:
3: <cfif lFormat is True>
4:   <table width="760" border="0" cellpadding="0" cellspacing="0">
5:     <tr><td>
6:       <cfoutput>#qryFormat.footerCode#</cfoutput>
7:     </td></tr>
8:   </table>
9: </cfif>
```

```
1: <cfparam name="lFormat" default="False">
2:
3: <cfif lFormat is True>
4:   <table width="760" border="0" cellpadding="0" cellspacing="0">
5:     <tr>
6:       <td>
7:         <cfoutput>#qryFormat.headerCode#</cfoutput>
8:       </td>
9:     </tr>
10:   </table>
11: </cfelse>
12:   &nbsp;
13: </cfif>
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3: <html>
4: <head>
5:   <title>DPO Homes</title>
6:   <link rel="stylesheet" href="style1.css" type="text/css">
7:   <script language="JavaScript" src="menu.js"></script>
8:   <script language="JavaScript1.2" src="menu2.js"></script>
9: </head>
10:
11: <body bgcolor="#ffffff" marginheight="0" marginwidth="0" leftmargin="0" topmargin="0" onLoad="Sniff();LoadImgs();">
12:
13:   <!-- ~~~~~~ begin outer table : left strip ~-->
14:   <table border="0" cellpadding="0" cellspacing="0">
15:     <tr><td bgcolor="#6666cc" width="5">&nbsp;</td>
16:     <!-- ~~~~~~ end left strip -->
17:
18:     <td valign="top">
19:       <!-- ~~~~~~ begin page header : nested table ~-->
20:       <table border="0" cellpadding="0" cellspacing="0" width="777">
21:         <tr><td width="299" height="76">
22:           <a href="index.cfm"></a>
23:         </td><td valign="middle">
24:           <cfinclude template="banner_ad.cfm">
25:         </td></tr>
26:       </table>
27:       <!-- ~~~~~~ end page header ~-->
28:
29:       <!-- ~~~~~~ begin page body : nested table ~-->
30:       <table border="0" cellpadding="0" cellspacing="0" width="777">
31:         <tr><td valign="top" width="653" height="34">
32:           <cfinclude template="menu.cfm">
33:         </td><td valign="top" width="124" align="center" rowspan="3">
34:           <cfinclude template="small_ad.cfm">
35:         </td></tr>
36:         <tr><td valign="top" width="653" height="34">
37:           &nbsp;</td></tr>
38:       </table>
39:       <!-- ~~~~~~ BEGIN CONTENT ~-->
40:       <tr><td valign="top">
41:         <table border="0" align="center" width="630" bgcolor="#000000" cellpadding="1" cellspacing="1">
42:           <tr><td class="tdtitle" bgcolor="#6666cc"><b>DPO Home Improvement</b></td></tr>
43:           <tr><td bgcolor="#ffffff">
44:             <table border="0" cellpadding="1" cellspacing="1" bgcolor="#ffffff">
45:               <tr><td valign="top"><a href="http://www.servicemagic.com" target="_blank"></a></td>
46:               <td valign="top">Make your house a home, find the right resources from contractors to the latest in decorating,
```

```
47: remodeling and furnishing.</td>
48:     </tr>
49:     </table>
50: </td></tr>
51: </table>
52: 
53: <table border="0" align="center" width="630" bgcolor="#000000" cellpadding="1" cellspacing="1">
54:   <tr><td class="tdtitle" bgcolor="#6666cc"><b>DPO Gardening</b></td></tr>
56:   <tr><td bgcolor="#ffffff">
57:     <table border="0" cellpadding="1" cellspacing="1" bgcolor="#ffffff">
58:       <tr><td valign="top"><a href="http://www.garden.com" target="_blank"></a></td>
60:       <td valign="top">Visit <a href="http://www.garden.com">garden.com</a>, a multi-dimensional garden resource.
61:       garden.com is interactive, innovative, and informative...the perfect site for home gardeners! You can ask gardening
62:       questions of our garden doctor (this doctor is always in!), design your own garden with our on-site LandscapePlanner, buy
63:       seeds, plants, and tools in our online shopping area, and read about current gardening trends in garden.com magazine. You
64:       can even chat with other gardeners 24 hours a day. And a lot more! garden.com brings together the best of what the gardening
65:       world has to offer, from all around the world.</td>
66:     </tr>
67:   </table>
68:   </td></tr></table>
69:   <!-- ~~~~~ END CONTENT ~-->
70:   <!-- ~~~~~ and page body ~-->
71:   <cfinclude template="footer.cfm">
  </body>
</html>
```





```
45:         <cfset cDesc1 = qrySpecialty.description>
46:     <cfelse>
47:         <cfset cDesc2 = qrySpecialty.description>
48:     </cfif>
49:     <td class="click_heading" bgcolor="#cMenuColor#" width="50%"><a
href="propertyView.cfm?propertyTypeID=#qrySpecialty.propertyTypeID#" class="nav">#qrySpecialty.menuTitle#</a></td>
50:     <cfif nColumn is 2>
51:     </tr>
52:     <tr>
53:         <td width="50%" valign="top"><p>#cDesc1#</p><p>&nbsp;</p></td>
54:         <td width="50%" valign="top"><p>#cDesc2#</p><p>&nbsp;</p></td>
55:     </tr>
56:     </cfif>
57:     <cfif nColumn is 1>
58:         <cfset nColumn = 2>
59:     <cfelse>
60:         <cfset nColumn = 1>
61:     </cfif>
62:     </cfoutput>
63:     <cfif nColumn is 2>
64:         <td width="50%">&nbsp;</td>
65:     </tr>
66:     <tr>
67:         <td width="50%" valign="top"><p><cfoutput>#cDesc1#</cfoutput></p></td>
68:         <td width="50%" valign="top">&nbsp;</td>
69:     </tr>
70:     </cfif>
71: </table>
72: </td>
73: <td valign="top" width="1" bgcolor="#6666ff"></td>
74: <td valign="top" width="4" bgcolor="#ffffff"></td>
75: <td width="120" valign="top">
76:     <cfinclude template="120x65ads.cfm">
77: </td>
78: </tr>
79: </table>
80: <cfinclude template="footer.cfm">
81: </body>
82: </html>
```

```
var t=document.getElementById("t");
var l=document.getElementById("l");
var i=document.getElementById("i");
var r=document.getElementById("r");
var d=document.getElementById("d");
var n=document.getElementById("n");
var p=document.getElementById("p");
var ia=document.getElementById("ia");
var ip=document.getElementById("ip");
var pp=document.getElementById("pp");
var xpt=document.getElementById("xpt");
var dn=document.getElementById("dn");
var l=document.getElementById("l");
var t=document.getElementById("t");
var i=document.getElementById("i");
var r=document.getElementById("r");
var d=document.getElementById("d");
var n=document.getElementById("n");
var p=document.getElementById("p");
var ia=document.getElementById("ia");
var ip=document.getElementById("ip");
var pp=document.getElementById("pp");
var xpt=document.getElementById("xpt");
var dn=document.getElementById("dn");
```

```
1: function clear_Click() {
2:   document.analyzer.loan.value = "";
3:   document.analyzer.downp.value="";
4:   document.analyzer.term.value = "";
5:   document.analyzer.rate.value = "";
6:   document.analyzer.thedown.value="";
7:   document.analyzer.payment.value = "";
8:
9:
10: }
11:
12: function calculate_Click() {
13:   var t1=0.0;
14:   var t=0.0;
15:   var i=0.0;
16:   var l=0.0;
17:   var x=0.0;
18:   var b=0.0;
19:   var t2=0.0;
20:   var im=0.0;
21:   var d=0.0;
22:   var n=0.0
23:   var p=0.0;
24:   var ia=0.0;
25:   var ip=0.0;
26:   var pp=0.0;
27:   var xpt=0.0;
28:   var dn=0.0;
29:   l = document.analyzer.loan.value;
30:   if (l=="") {
31:     alert ("A loan amount must be entered.");
32:     document.analyzer.loan.focus()
33:   }
34:
35:   t = document.analyzer.term.value;
36:   if (t=="") {
37:     alert ("The loan's term in years must be entered.");
38:     document.analyzer.term.focus()
39:   }
40:   i = document.analyzer.rate.value;
41:   if (i=="") {
42:     alert ("The interest rate must be entered.");
43:     document.analyzer.rate.focus()
44:   }
45:
46:   dn = document.analyzer.downp.value;
47:   if (dn=="") {
48:     dn = 0
49:   }
```

```
/*  
 * Copyright (c) 1999 Netscape Communications Corporation  
 * All rights reserved.  
 */
```

```
50:  
51:  if (dn > 0) {  
52:      dn = dn/100;  
53:      dn = l*dn;  
54:  }  
55:  document.analyzer.thedown.value = dn;  
56:  b = l-dn;  
57:  i = i/100;  
58:  im = i/12;  
59:  m = t*12;  
60:  t2 = l+im;  
61:  t1 = Math.pow(t2, m);  
62:  n = im*t1;  
63:  d = t1-l;  
64:  p = b*(n/d);  
65:  t1 = p*100;  
66:  t1 = Math.round(t1);  
67:  p = t1/100;  
68:  
69:  document.analyzer.payment.value = p;  
70:  
71:  
72:  
73:  
74:  
75:  x = x*100;  
76:  x = Math.round(x);  
77:  x = x/100;  
78:  
79:  
80:  
81:  if (x < 0){  
82:      alert( "Extra payment must be a positive value")  
83:  }  
84:  
85:  if (x > 0) {  
86:      var j  
87:      j = 0;  
88:      ip = 0;  
89:      pp = 0;  
90:  
91:  
92:      ll = m+1;  
93:  
94:      while (b > 0) {  
95:          ia = im*b;  
96:          ip = ip+ia;  
97:          pp = p-ia;  
98:          b = b-pp;
```

```

99:
100:
101:
102:
103:
104:

```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <html>
4: <head>
5:   <title>Realty Objects</title>
6:   <link rel="stylesheet" href="style1.css" type="text/css">
7: </head>
8:
9: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
10:
11:
12: <cfset nEntityType = -1> <!-- Default Page -->
13: <cfset nEntityID = -1> <!-- Default Page -->
14: <cfinclude template="include\pageFormat.cfm">
15:
16: <cfinclude template="header_bannerad.cfm">
17:
18: <table width="760" border="0" cellpadding="0" cellspacing="0">
19:   <tr><td align="right" valign="top" bgcolor="#ffffff" width="135">
20:     <cfinclude template="navigation.cfm">
21:   </td>
22:   <td width="500" valign="top" align="center">
23:     <table border="0" width="480" cellspacing="2">
24:       <tr>
25:         <td bgcolor="#ffffff" width="100%">
26:           <div class="heading">Mortgage Information</div>
27:         </td>
28:       </tr>
29:       <tr>
30:         <td align="center"><a href="http://www.mortgageratewatch.com/" target="_blank"></a></td>
31:         <td align="center"><p>There's no longer any need to track down individual lenders or to study days-old mortgage rate charts. We make it simple to compare rates from the top lenders in your area with constantly updated online rates.<br>Whether you're a first time buyer, a veteran real estate player, or a homeowner with plans to refinance, you now have the power of <a href="http://www.mortgageratewatch.com" target="_blank">Mortgage Rate Watch</a> at your fingertips.</p></td>
32:       </tr>
33:     </table>
34:   </td>
35:   <td valign="top" width="1" bgcolor="#6666ff"></td>
36:   <td valign="top" width="4" bgcolor="#ffffff"></td>
37:   <td width="120" valign="top">
38:     <cfinclude template="120x65ads.cfm">
39:   </td>
40: </tr>
41: </table>
42: <cfinclude template="footer.cfm">
43: </body>
44: </html>
```

171

```
business relationships, and interactivity together to provide new tools and services to job seekers and employers.</p>
42: <p><a href="http://www.employmentwizard.com/class_search.cfm" target="_blank"><b>Job Finder</b></a><br>Our
database of jobs from newspapers and employers around the U.S. is updated daily. Search now for your perfect job!</p>
43: <p><a href="http://www.employmentwizard.com/route_jobseeker.cfm?r=20" target="_blank"><b>My Wizard</b></a><br>My
Wizard is a free service that can help you with your job search. Create an online resume and cover letter that you can send
or update at any time.</p>
44: <p><a href="http://www.employmentwizard.com/resources.cfm" target="_blank"><b>News and
Resources</b></a><br>Information, tips and advice on starting or managing your career.</p>
45: </td>
46: </tr>
47: <tr>
48: <td align="center">
49: 
50: </td>
51: </tr>
52: <tr>
53: <td>
54: <p><a href="http://www.mapquest.com" target="_blank"></a><br>MapQuest is the most highly-rated and popular interactive mapping service on
the World Wide Web. MapQuest offers consumers the ability to find over three million locations worldwide, obtain driving
directions, overlay places of interest, and create and save personalized maps. We also offer business, leisure and local
information, plus live traffic updates.
</td>
55: </tr>
56: </table>
57: </table>
58: </td>
59: <td valign="top" width="1" bgcolor="#6666ff"></td>
60: <td valign="top" width="4" bgcolor="#ffffff"></td>
61: <td width="120" valign="top">
62: <cfinclude template="120x65ads.cfm">
63: </td>
64: </tr>
65: </table>
66: <cfinclude template="footer.cfm">
67: </body>
68: </html>
69:
```

```

1: <cfquery name="qrySpecialty" datasource="#sourceName#">
2:   select propTypeID, name, menuTitle, sortOrder, description
3:   from propTypes
4:   where propTypes.distributorID = #ap_distributorID#
5:   order by sortOrder, menuTitle
6: </cfquery>
7:
8: <br>
9: <br>
10: <a href="propTypeSrch.cfm" class="nav">FIND A HOME<img alt=""></a><br>
11: <br>
12: <a href="realtors.cfm" class="nav">FIND AN OFFICE<img alt=""></a><br>
13: <br>
14: <a href="commsrch.cfm" class="nav">COMMUNITY INFO<img alt=""></a><br>
15: <br>
16: <a href="hotListings.cfm" class="nav">ENHANCED LISTINGS<img alt=""></a><br>
17: <br>
18: <cfoutput query="qrySpecialty">
19:   <a href="propTypeView.cfm?propTypeID=#qrySpecialty.propTypeID#"
     class="nav">#ucase(qrySpecialty.menuTitle)<img alt=""></a><br>
     <br>
     </cfoutput>
20:   <a href="index.cfm" class="nav">HOME<img alt=""></a><br>
21:   <a href="images/nav_rule.gif" width="135" height="2" border="0" alt=""><br>
22:   <br>
23:   <img alt=""><br>
24:   <br>
25:   <img alt=""><br>
26:   <cfoutput>
27:     <a href="#ap_agencyURL#" class="nav">#ap_agencyName<img alt=""></a><br>
28:   </cfoutput>
29:   <br>
30:   <p><img alt=""></p>
31:   <p align="center"><a href="http://www.yakalo.net"></a></p>
32:   <p><img alt=""></p>

```



```
99: <cfinclude template="banner_ad.cfm"><!-- BEGIN CONTENT -->
100: </td></tr>
101: </table>
102: <!-- ~~~~~~ end page header ~~~~~~ -->
103:
104: <!-- ~~~~~~ begin page body : nested table ~~~~~~ -->
105: <table border="0" cellpadding="0" cellspacing="0" width="777">
106: <tr><td valign="top" width="653" height="34">
107: <cfinclude template="menu.cfm">
108: </td><td valign="top" width="124" align="center" rowspan="3">
109: <cfinclude template="small_ad.cfm">
110: </td></tr>
111: <tr><td valign="top" width="653" height="34">
112: <b><br></td></tr>
113: <!-- ~~~~~~ BEGIN CONTENT ~~~~~~ -->
114: <tr><td valign="top" width="653" height="400">
115: <table border="0" align="center">
116: <tr><td bgcolor="#cccc99"><b>New Homes Search Result</b></td></tr>
117: <tr><td bgcolor="#ffffff">
118: <table border="0" width="495" align="center">
119:
120: <tr><td><b></td><td><b>Property</b></td><td><b>Bedrooms</b></td><td><b>Bathrooms</b></td></tr>
121: <td colspan="4"><cfoutput query="qSearchResults">
122: <cfquery name="qryFindOHT" datasource="#SourceName#">
123: select id, startdate, stopdate, ohtfilename
124: from adData
125: where callingId=#qsearchResults.prop_id#
126: and callingtype=0
127: </cfquery>
128: <tr>
129: <td><a href="propview.cfm?prop_id=#qsearchResults.prop_id#">View</a></td>
130: <td colspan="3"><cfif qryFindOHT.recordcount gt 0>
131: <td><a href="#qryFindOHT.ohtfilename#">Tour</a></td>
132: <td><b></td>
133: </td>
134: </td>
135: <td>#name#</td><td>#numberFormat(price)#</td><td align="center">#bath#
136: </td></tr>
137: <td colspan="4"><cfoutput>
138: </td></tr>
139: <td colspan="4"></table>
140: </td></tr>
141: <td colspan="4"></table>
142: <td colspan="4"></td>
143: <td colspan="4"></table>
144: <td colspan="4"></td>
145: </td></tr></table>
```

```
146: <cfinclude template="footer.cfm">
147: </body>
148: </html>
```

```
<!--#include virtual="/includes/footer.cfm" -->
</body>
</html>
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
2:
3: <html>
4: <head>
5:   <title>DPO Homes</title>
6:   <link rel="stylesheet" href="style1.css" type="text/css">
7:   <script language="JavaScript" src="menu.js"></script>
8:   <script language="JavaScript1.2" src="menu2.js"></script>
9: </head>
10:
11: <body bgcolor="#ffffff" marginheight="0" marginwidth="0" leftmargin="0" topmargin="0" onLoad="Sniff();LoadImgs();">
12:
13:   <!-- ~~~~~~ begin outer table : left strip -->
14:   <table border="0" cellpadding="0" cellspacing="0">
15:     <tr><td bgcolor="#6666cc" width="5">&nbsp;</td>
16:     <!-- ~~~~~~ end left strip -->
17:
18:     <td valign="top">
19:       <!-- ~~~~~~ begin page header : nested table -->
20:       <table border="0" cellpadding="0" cellspacing="0" width="777">
21:         <tr><td width="299" height="76">
22:           <a href="index.cfm"></a>
23:         </td><td valign="middle">
24:           <cfinclude template="banner_ad.cfm">
25:         </td></tr>
26:       </table>
27:       <!-- ~~~~~~ end page header -->
28:
29:       <!-- ~~~~~~ begin page body : nested table -->
30:       <table border="0" cellpadding="0" cellspacing="0" width="777">
31:         <tr><td valign="top" width="653" height="34">
32:           <cfinclude template="menu.cfm">
33:         </td><td valign="top" width="124" align="center" rowspan="3">
34:           <cfinclude template="small_ad.cfm">
35:         </td></tr>
36:         <tr><td valign="top" width="653" height="34">
37:           &nbsp;</td></tr>
38:       </table>
39:       <!-- ~~~~~~ BEGIN CONTENT -->
40:       <tr><td valign="top">
41:         <table border="0" align="center" width="630">
42:           <tr><td align="center"><p></p>
43:             <h3>Custom Tour &quot;Sites&quot; of Homes Throughout the Denver Metro Area</h3>
44:             <p align="left">These new web &quot;sites&quot; are unique, highly detailed, multi-photograph, full color tours of
the individual properties. Please review them online at your leisure and then contact the listing agent identified with any
questions and for your private in-person showing.</p>
45:             <p><a href="ohrListings.cfm">View Our Listings of Online Home Tours</a></p>
46:             <table border="0" align="center"><tr><td>
```

```
47: <cfset nDisplayType="8">
48: <cfset nDisplayID="0">
49: <cfset lVerbose = False>
50: <cfinclude template="resources.cfm">
51: </td></tr></table>
52: </td></tr>
53: </table>
54: </td></tr>
55: <!-- ~~~~~ ENH CONTENT ~-->
56: </table>
57: <!-- ~~~~~ end page body ~-->
58: </td></tr></table>
59: <cfinclude template="footer.cfm">
60: </body>
61: </html>
62:
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3: <!-- <cfinclude template="include\security.cfm"> -->
4:
5:
6: <cfparam Name="URL.communityID" Default="-1">
7: <cfparam Name="URL.Region" default="">
8: <cfparam Name="displayFrom" Default="1">
9: <cfparam Name="displayTo" Default="12">
10: <cfparam Name="displayAmount" Default="12">
11:
12:
13: <cfquery name="qryCommunity" datasource="#SourceName#">
14: select *
15: from Communities
16: where communities.distributorID = #ap_distributorID#
17: <cfif URL.communityID gt -1>
18: and communities.communityID = #URL.CommunityID#
19: </cfif>
20: </cfquery>
21:
22: <CFQUERY NAME="qryGetActive" DATASOURCE="#SourceName#" >
23: SELECT adData.callingID,adData.startDate,adData.stopDate,adData.ohfileName,adData.primaryPic,
24: prop_main.prop_id,prop_main.dscreptn_s,prop_main.price,agents.email,agents.lastname,agents.firstname,agents.workphone
25: <cfif URL.region is not "">
26: ,communities.region
27: </cfif>
28: FROM AdData,prop_main,agents<cfif URL.region is not "">,communities</cfif>
29: WHERE adData.startDate <= #createODBCDate(now())#
30: AND adData.StopDate >= #createODBCDate(now())#
31: AND adData.callingType=0
32: AND adData.ohfileName <> ''
33: AND prop_main.prop_id = adData.callingID
34: AND prop_main.agent_id = agents.agent_id
35: <cfif URL.communityID gt -1>
36: AND prop_main.communityID = #URL.communityID#
37: </cfif>
38: <cfif URL.region is not "">
39: AND prop_main.communityID = communities.communityID
40: AND communities.region = '#URL.region#'
41: </cfif>
42: and prop_main.distributorID = #ap_distributorID#
43: ORDER BY prop_main.price DESC
44: </CFQUERY>
45:
46: <cfset displayTo = min(displayTo, qryGetActive.recordCount)>
47: <cfset displayFrom = min(displayFrom, qryGetActive.recordCount)>
48:
49: <html>

```

```
50: <head>
51: <title>Realty Objects</title>
52: <link rel="stylesheet" href="style1.css" type="text/css">
53: </head>
54:
55: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
56:
57: <cfset nEntityType = 8> <!-- OHT Pages -->
58: <cfset nEntityID = 0> <!-- OHT Main Page -->
59: <cfinclude template="include\pageFormat.cfm">
60:
61: <cfinclude template="header_bannerad.cfm">
62:
63: <table width="760" border="0" cellpadding="0" cellspacing="0">
64: <tr><td align="right" valign="top" bgcolor="#cfcfcfcf"><cfoutput>#cNavColor#</cfoutput> width="135">
65: <cfinclude template="navigation.cfm">
66: </td>
67: <td width="500" valign="top" align="center">
68: <table border="0" width="480" cellspacing="2">
69: <tr>
70: <td bgcolor="#cfcfcfcf"><cfoutput>#cMenuColor#</cfoutput> class="heading">Enhanced Listings</td>
71: </tr>
72: <cfoutput>
73: <tr>
74: <td>
75: <cfif qryGetActive.recordCount gt 0>
76: <p align="center">Showing tours #displayFrom# through #displayTo# out of #qryGetActive.recordCount#</p>
77: <cfelse>
78: <p>There are no virtual tours available.</p>
79: </cfif>
80: </td>
81: </tr>
82: </cfoutput>
83: <cfif qryGetActive.recordCount gt 0>
84: <tr>
85: <td>
86: <table border="0" width="480">
87: <cfset placeRule = "off">
88: <cfoutput QUERY="qryGetActive" startrow="#displayFrom#" maxrows="#displayAmount#">
89: <cfif placeRule IS "on">
90: <tr>
91: <td colspan="2" align="center">
92: 
93: </td>
94: </tr>
95: </cfif>
96: <cfset placeRule = "on">
97: <tr>
98: <td valign="top" align="center">
```

```
99: <cfset cDataPath = getDirectoryFromPath(trim(qryGetActive.primaryPic#))>
100: <CFSET cImageProp = "#cDataPath#qryGetActive.primaryPic#">
101: <cfset cImageProp = trim(cImageProp)>
102: <cfif trim(cImageProp) is not "#cDataPath#">
103:   
104: <cfelse>
105:   No Image
106: </cfif>
107: </td>
108: <td valign="top">
109:   <p><b>#dollarFormat(qryGetActive.price)#</b><br>#qryGetActive.dscrptn_s#<br>
110:   <a href="#qryGetActive.ohffilename#" target="_blank"><br>View Tour</a></p>
111: </td>
112: </tr>
113: </cfoutput>
114: </table>
115: </td>
116: </tr>
117: </cfif>
118: </table>
119: </td>
120: <td valign="top" width="1" bgcolor="#6666ff"></td>
121: <td valign="top" width="4" bgcolor="#ffffff"></td>
122: <td width="120" valign="top">
123:   <cfinclude template="120x65ads.cfm">
124: </td>
125: </tr>
126: </table>
127: <cfinclude template="footer.cfm">
128: </body>
129: </html>
```

```
1: <CFSET staStatus=ArrayNew(1)>
2: <CFSET staStatus[1]="Deleted">
3: <CFSET staStatus[2]="New">
4: <CFSET staStatus[3]="On Market">
5: <CFSET staStatus[4]="Contract Pending">
6: <CFSET staStatus[5]="Under Contract">
7: <CFSET staStatus[6]="Sold">
8: <CFSET staStatus[7]="Off Market">
9:
10: <CFSET ar_lotttype=ArrayNew(1)>
11: <CFSET ar_lotttype[1]="None">
12: <CFSET ar_lotttype[2]="City/Town">
13: <CFSET ar_lotttype[3]="Land 0 - 34 acres">
14: <CFSET ar_lotttype[4]="Land 35+ acres">
15: <CFSET ar_lotttype[5]="Leased">
16:
17: <CFSET ar_proptype=ArrayNew(1)>
18: <CFSET ar_proptype[1]="Other">
19: <CFSET ar_proptype[2]="Residential">
20: <CFSET ar_proptype[3]="Farm/Ranch">
21: <CFSET ar_proptype[4]="Mountain Property">
22: <CFSET ar_proptype[5]="Commercial">
23: <CFSET ar_proptype[6]="Rentals">
24: <CFSET ar_proptype[7]="Vacation Rentals">
25:
26: <CFSET ls_Status = "Deleted,Inactive,Off Market,Sold,New,Active,Contract Pending,Under Contract">
27: <CFSET ls_SearchStatus = "0,0,0,0,1,1,1">
28:
29: <CFSET ls_lotttype ="Other,City/Town,Land 0-34 acres,Land 35+ acres,leased">
30: <CFSET ls_hometype ="None,Single Family,Townhome/Condo,Mobile Home,Cabin">
31: <!-- SPE 2/9/99 -->
32: <CFSET ls_propDscript = "Other,Residential,Ranch/Farm,Mountain Property,Commercial,Rentals,Vacation Rentals">
33: <cfset lstSearchPropType = ls_propDscript>
34: <cfset lstPropTypeValues = "1,2,3,4,5,6,7">
35: <CFSET ls_showPiece = "None,Realtors Photo,Online_INPrint,MLS,Feature">
```



```

1: <table border="0" bgcolor="#ffffff">
2: <cfinclude template="propLists.cfm">
3: <form action="FindProperty_Result.cfm" method="post">
4: <!-- Field: prop_main.propdscrip=CHAR;30;FALSE -->
5: <input type="hidden" name="Crit5_FieldName" value="prop_main.propdscrip">
6: <input type="hidden" name="Crit5_FieldType" value="CHAR">
7: <tr><td colspan="2" bgcolor="#cccc99"><div align="center"><b>Property Search</b></div></td></tr>
8: <tr>
9: <td align="right" class="td">Property Type:</td>
10: <td>
11: <input type="hidden" name="Crit5_Operator" value="EQUAL">
12: <select name="Crit5_Value">
13: <cfset ls_propdscrip=listAppend(ls_propdscrip, "All")>
14: <cf_optionsList ls_list="#ls_propdscrip#" defValue="#listLen(ls_propdscrip)#">
15: </select>
16: </td>
17: </tr>
18: <tr><!-- Field: prop_main.price=float;21;FALSE -->
19: <input type="hidden" name="Crit6_FieldName" value="prop_main.price">
20: <input type="hidden" name="Crit6_Value_integer">
21: <input type="hidden" name="Crit6_FieldType" value="FLOAT">
22:
23: <td align="right" class="td">Price
24: Range: </td>
25: <td>
26: <input type="hidden" name="Crit6_Operator" value="GREATER_THAN">
27: <input type="text" name="Crit6_Value" value="0"></td></tr>
28:
29: <tr><td align="right" class="td">
30: To:
31: </td><td>
32: <input type="hidden" name="Crit7_FieldName" value="prop_main.price">
33: <input type="hidden" name="Crit7_Value_integer">
34: <input type="hidden" name="Crit7_FieldType" value="FLOAT">
35: <input type="hidden" name="Crit7_Operator" value="SMALLER_THAN">
36: <input type="text" name="Crit7_Value" value="10,000,000">
37: </td>
38: </tr>
39: <!-- Field: prop_main.lotType=CHAR;25;FALSE -->
40: <input type="hidden" name="Crit4_FieldName" value="prop_main.lotType">
41: <input type="hidden" name="Crit4_FieldType" value="CHAR">
42: <tr>
43: <td align="right" class="td">Lot
44: Type:</td>
45: <td>
46: <input type="hidden" name="Crit4_Operator" value="EQUAL">
47: <select name="Crit4_Value">
48: <cfset ls_lotType=listAppend(ls_lotType, "All")>
49: <cf_optionsList ls_list="#ls_lotType#" defValue="#listLen(ls_lotType)#">

```

```
50:      </select>
51:    </td>
52:  </tr>
53:  <!-- Field: prop_main.hometype=CHAR;25;FALSE -->
54:  <input type="hidden" name="Crit1_FieldName" value="prop_main.hometype">
55:  <input type="hidden" name="Crit1_FieldType" value="CHAR">
56:
57:  <td align="right" class="td">Home
58:    Type:</td>
59:
60:  <input type="hidden" name="Crit1_Operator" value="EQUAL">
61:  <select name="Crit1_Value">
62:    <cfset ls_hometype=listAppend(ls_hometype, "All")>
63:    <cf_optionsList ls_list="#ls_hometype#" defValue="#listLen(ls_hometype)#">
64:  </select>
65:
66:  </td>
67: </tr>
68:
69:
70:
71:  <!-- Field: prop_main.bedrooms=INT;4;FALSE -->
72:  <input type="hidden" name="Crit2_FieldName" value="prop_main.bedroom">
73:  <input type="hidden" name="Crit2_Value_integer">
74:  <input type="hidden" name="Crit2_FieldType" value="CHAR">
75:
76:  <td align="right" class="td">Min.
77:    Bedrooms:</td>
78:
79:
80:  <input type="hidden" name="Crit2_Operator" value="GREATER_EQUAL">
81:  <input type="text" name="Crit2_Value" size="2">
82:
83:  </td>
84: </tr>
85:
86:  <!-- Field: prop_main.bath=INT;4;FALSE -->
87:  <input type="hidden" name="Crit3_FieldName" value="prop_main.bath">
88:  <input type="hidden" name="Crit3_Value_integer">
89:  <input type="hidden" name="Crit3_FieldType" value="CHAR">
90:
91:  <td align="right" class="td">Min. Baths:</td>
92:
93:  <input type="hidden" name="Crit3_Operator" value="GREATER_EQUAL">
94:  <input type="text" name="Crit3_Value" size="2">
95:
96:  </td>
97: </tr>
98:
99:  <td colspan="2">
100:  <div align="center">
101:  <input type="submit" value="Find" name="submit">
102:  <input type="reset" value="Clear" name="reset">
103:  </div>
104: </td>
```

1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html40/strict.dtd">
2:
3: <cfparam name="URL.PropertyType" DEFAULT="">
4:
5: <cfquery name="qryPropTypes" datasource="#SourceName#">
6:   select * from propTypes
7:   where propTypes.distributorID = #ap_distributorID#
8: </cfquery>
9:
10: <html>
11: <head>
12:   <title>Realty Objects</title>
13:   <link rel="stylesheet" href="style1.css" type="text/css">
14: </head>
15:
16: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
17:
18: <cfset nEntityType = 5> <!-- Property Main Page -->
19: <cfset nEntityID = 0> <!-- Property Pages -->
20: <cfinclude template="include\pageFormat.cfm">
21:
22: <cfinclude template="header_bannerad.cfm">
23:
24: <table width="760" border="0" cellpadding="0" cellspacing="0">
25:   <tr><td align="right" valign="top" bgcolor="#cfcfcd" width="135">
26:     <cfinclude template="navigation.cfm">
27:   </td>
28:   <td width="500" valign="top" align="center">
29:     <table border="0" width="480" cellspacing="2">
30:       <tr>
31:         <td bgcolor="#cfcfcd"><cfoutput>#cMenuColor#</cfoutput> Find a Home</td>
32:       </tr>
33:       <tr>
34:         <td>
35:           <blockquote><p>Search our database of homes for sale in the area.</p></blockquote>
36:           <p><cfinclude template="include/mlsPropsSrchForm.cfm"></p>
37:         </td>
38:       </tr>
39:     </table>
40:   </td>
41:   <td valign="top" width="1" bgcolor="#6666ff"></td>
42:   <td valign="top" width="4" bgcolor="#ffffff"></td>
43:   <td width="120" valign="top">
44:     <cfinclude template="120x65ads.cfm">
45:   </td>
46: </tr>
47: </table>
48: <cfinclude template="footer.cfm">
49: </body>
```

50: </html>

-----  
The following information was retrieved from the database:  
-----



```

50: <html>
51: <head>
52: <title><cfoutput>#ap_agencyName# - #qryPropType.menuTitle#</cfoutput></title>
53: <link rel="stylesheet" href="style1.css" type="text/css">
54: </head>
55:
56: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
57: <cfset nEntityType = 4> <!--- Specialty Page = 1 -->
58: <cfset nEntityID = URL.PropertyTypeID> <!--- Specialty Page ID -->
59: <cfinclude template="include\pageFormat.cfm">
60:
61: <cfinclude template="header_bannerad.cfm">
62:
63: <cfoutput>
64:
65: <table width="760" border="0" cellpadding="0" cellspacing="0">
66: <tr>
67: <td align="right" valign="top" bgcolor="#cNavColor#" width="135">
68: <cfinclude template="navigation.cfm">
69: </td>
70: <td width="500" valign="top" align="center">
71: <table border="0" width="480" cellspacing="2">
72: <tr>
73: <td bgcolor="#cMenuColor#" class="heading">#qryPropType.Name#</td>
74: </tr>
75: <!--- <cfif len(trim(qryPropType.headerFilename)) gt 0>
76: <p align="center"></p>
border="0" hspace="4"></p>
</cfif>
</cfif>
<cfif len(trim(qryPropType.primarypic)) gt 0>
<p align="center"></p>
</cfif>
<p>#paragraphFormat(qryPropType.description) #</p> -->
<!--- Display other paragraph information about this community -->
<CFLOOP FROM=1 TO=#listlen(listParamCtrs) # INDEX=nParamIndex>
<tr><td>
<!--- Title -->
<CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
SELECT param_value FROM propType_param
WHERE propTypeID=#nPropTypeID# AND dataGroup=8
AND param_ctr=#listGetAt(listParamCtrs,nParamIndex) #
AND param_name='imgTitle'
</CFQUERY>
<CFSET cTitle = qryFindInfo.param_value>
<CFIF len(trim(cTitle)) gt 0>
<CFSET cUseTitle = "YES">
<CFELSE>

```

```

97:      <CFSET cUseTitle = "NO">
98:    </CFIF>
99:
100:    <!-- Image Align -->
101:    <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
102:      SELECT param_value FROM propType_param
103:      WHERE propTypeID=#nPropTypeID# AND dataGroup=8
104:      AND param_cnr=#listGetAt(listParamCntrs,nParamIndex)#
105:      AND param_name='PTYPEImgAl'
106:    </CFQUERY>
107:    <CFSET cImageAlign = ucase(qryFindInfo.param_value)>
108:
109:    <!-- Image Name -->
110:    <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
111:      SELECT param_value FROM propType_param
112:      WHERE propTypeID=#nPropTypeID# AND dataGroup=8
113:      AND param_cnr=#listGetAt(listParamCntrs,nParamIndex)#
114:      AND param_name='PTYPEImage'
115:    </CFQUERY>
116:    <CFSET cImageName = qryFindInfo.param_value>
117:
118:    <!-- Text -->
119:    <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
120:      SELECT param_value FROM propType_param
121:      WHERE propTypeID=#nPropTypeID# AND dataGroup=8
122:      AND param_cnr=#listGetAt(listParamCntrs,nParamIndex)#
123:      AND param_name='PTYPEText'
124:    </CFQUERY>
125:
126:    <CFIF len(trim(cImageName)) gt 0>
127:      <CFIF cImageAlign is "MIDDLE">
128:        <p align="center"></p>
129:      <CFELSE>
130:        
131:      </CFIF>
132:    </CFIF>
133:
134:    <CFIF cUseTitle is "YES">
135:      <h3>#cTitle#</h3>
136:    </CFIF>
137:
138:    <CFIF qryFindInfo.recordCount GT 0 and len(trim(qryFindInfo.param_value)) gt 0>
139:      #paragraphFormat(qryFindInfo.param_value)#
140:    </CFIF>
141:    </td></tr>
142:  </CFLOOP>
143: <tr>
144:   <td>
145:     <cfset nDisplayType="4">

```



```
146: <cfset nDisplayID="#qryPropType.propTypeID#">
147: <cfset lVerbose = False>
148: <cfinclude template="resources.cfm"></p>
149: <div align="center"><cfinclude template="include\specpropsearch.cfm"></div>
150:
151: <cfif len(trim(qryPropType.footerfilename)) gt 0>
152:   <p align="center"></p>
153:   </cfif>
154:   </td>
155: </tr>
156: </table>
157: </td>
158: <td valign="top" width="1" bgcolor="#6666ff"></td>
159: <td valign="top" width="4" bgcolor="#ffffff"></td>
160: <td width="120" valign="top">
161:   <cfinclude template="120x65ads.cfm">
162: </td>
163: </tr>
164: <!-- ~~~~~~ END CONTENT ~~~~>
165: </table>
166: </cfoutput>
167: <cfinclude template="footer.cfm">
168: </body>
169: </html>
```

-----  
 4.0 Transitional//EN" style="display: block; margin: 0 auto; text-align: center;">
 -----

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" style="display: block; margin: 0 auto; text-align: center;">
2: <cfif not isDefined("URL.prop_id")>
3:   <cflocation url="propTypesrch.cfm">
4: </cfif>
5:
6: <CFQUERY DATASOURCE="#sourceName#" NAME="prop_main">
7:   SELECT prop_main.prop_id,prop_main.name,prop_main.address,prop_main.city,prop_main.county,prop_main.state,prop_main.price,
8:     prop_main.size,prop_main.size_unit,prop_main.bedroom,prop_main.bath,prop_main.dscrptn_s,prop_main.dscrptn_l,
9:     prop_main.photo_name,prop_main.communityID,prop_main.propdscrpt,prop_main.seeitbuyit,agents.firstname,
10:    agents.lastname,agents.workphone,agents.homephone,agents.pub_home,agents.email,agents.agent_id,showpiece
11:  FROM prop_main, agents
12:  WHERE prop_main.prop_id = #prop_id#
13:  AND prop_main.agent_id=agents.agent_id
14: </CFQUERY>
15:
16: <cfif len(trim(prop_main.communityID)) gt 0>
17:   <cfset nCommunityID = prop_main.communityID>
18:   <cfquery name="qryCommunity" datasource="#SourceName#">
19:     select communityID,Name from communities where communities.communityID = #nCommunityID#
20:   </cfquery>
21: <cfelse>
22:   <cfset nCommunityID = -1>
23: </cfif>
24:
25: <!-- Set these for the page counter -->
26: <cfset nTargetID=#prop_id#>
27: <cfset cPageType="Property">
28: <cfinclude template=".\\common\\srvPageCounter.cfm">
29:
30: <!-- Check for a Bamboo virtual tour -->
31: <CFQUERY NAME="qBambooParam" DATASOURCE="#sourceName#">
32:   SELECT
33:     DISTINCT id, name, description, label, displayOrder, restrictions, type
34:   FROM param defs
35:   WHERE securityLevel=1
36:     AND #ap_agency#
37:     AND datagroup = #dgBamboo#
38:   ORDER BY displayOrder
39:
40: </CFQUERY>
41:
42: <CFSET totalNames = qBambooParam.recordCount>
43:
44: <CFSET ls_id = ValueList(qBambooParam.id)>
45: <CFSET ls_name = ValueList(qBambooParam.name)>
46: <CFSET ls_description = ValueList(qBambooParam.description)>
47: <CFSET ls_label = ValueList(qBambooParam.label)>
48:
49: <!-- Get actual Bamboo data for labels-->

```

```

50: <CFSET bcount = 0>
51: <CFQUERY NAME="qBambooData" DATASOURCE="#sourceName#">
52:   SELECT param_value, param_cntr
53:   FROM p_param
54:   WHERE prop_id = #prop_id#
55:   AND #ap_agency#
56:   AND dataGroup = #dgBamboo#
57:   AND param_Name = 'imgLabel'
58:   ORDER BY param_cntr
59: </CFQUERY>
60: <CFSET bcount = #qBambooData.RecordCount#>
61: <CFIF #bcount# NEQ 0>
62:   <CFSET isBamboo = "1">
63:   <CFELSE>
64:     <CFSET isBamboo = "0">
65:   </CFIF>
66:
67:   <!-- Get the actual Bamboo to view -->
68:
69:   <CFIF NOT isDefined("viewId")>
70:     <CFset viewId = "1">
71:   </CFIF>
72:   <CFQUERY NAME="qBambooView" DATASOURCE="#sourceName#">
73:     SELECT *
74:     FROM p_param
75:     WHERE prop_id = #prop_id#
76:     AND #ap_agency#
77:     AND dataGroup = #dgBamboo#
78:     AND param_cntr = #viewId#
79:   </CFQUERY>
80:   <!-- <CFIF #qBambooData.RecordCount# LE #totalNames#> -->
81:   <CFLOOP QUERY="qBambooView">
82:     <CFIF #trim(param_name)# EQ "imgName">
83:       <CFSET imageTitle = #trim(param_value)#>
84:       <CFELSEIF #trim(param_name)# EQ "imgCapti">
85:         <CFSET imageCaption = #trim(param_value)#>
86:       <CFELSEIF #trim(param_name)# EQ "imgURL">
87:         <CFSET imageURL = #trim(param_value)#>
88:       <CFELSEIF #trim(param_name)# EQ "imgLabel">
89:         <CFSET imgLabel = #trim(param_value)#>
90:       <CFELSE>
91:         <CFSET imageError = #trim(param_name)#>
92:       </CFIF>
93:     </CFLOOP>
94:     <!-- <CFELSE>
95:       <CFSET imageError = "Too many Bamboos">
96:     </CFIF> -->
97:     <CFSET ls_values = valueList(qBambooData.param_value)>
98:     <CFSET ls_order = valueList(qBambooData.param_cntr)>

```

11/29/2000 8:08:43 AM

```

99:
100: <CFQUERY NAME="qagency" DATASOURCE="#sourceName#">
101: SELECT name, address, city, state, zip, phone, fax, num800, email, URL_name
102: FROM agency
103: WHERE #ap_agency#
104:
105: </CFQUERY>
106:
107: <html>
108: <head>
109: <title><cfoutput>#ap_agencyName# - Find a Home - Property Details</cfoutput></title>
110: <link rel="stylesheet" href="style1.css" type="text/css">
111: <script language="JavaScript" src="window.js"></script>
112: </head>
113:
114: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
115:
116:
117: <cfset nEntityType = 5> <!-- Property Pages -->
118: <cfset nEntityID = 0> <!-- Property Pages -->
119: <cfinclude template="include\pageFormat.cfm">
120:
121: <cfinclude template="header_bannerad.cfm">
122:
123: <table width="760" border="0" cellpadding="0" cellspacing="0">
124: <tr><td align="right" valign="top" bgcolor="#cNavColor#"><cfoutput>#cNavColor#</cfoutput> width="135">
125: <cfinclude template="navigation.cfm">
126: </td>
127: <td width="500" valign="top" align="center">
128: <table border="0" width="480" cellspacing="2">
129: <tr>
130: <td bgcolor="#cMenuColor#"><cfoutput>#cMenuColor#</cfoutput> class="heading">Find a Home - Property Detail</td>
131: </tr>
132: <tr>
133: <td>
134: <CFOUTPUT QUERY="prop_main">
135: <table border="0" width="480">
136: <tr>
137: <td colspan="2" align="center">
138: <CFIF #len(Photo_name)# GT 1>
139: <br>
140: <CFELSE>
141: <p>Photo of this property is<br>unavailable at this time.</p>
142: </CFIF>
143: <p><b>#name#</b></p>
144: </td>
145: </tr>
146: <cfif trim(#seelbuyit#) is not "">
147: <tr>

```

```
148: <td colspan="2" align="center">
149:   <a href="#seeitbuyit#">View A "See It Buy It" Virtual Tour</a><br><br>
150: </td>
151: </tr>
152: </cfif>
153: <tr>
154:   <td valign="top" width="50%">
155:     <b>Priced At:</b> #NumberFormat(int(price),"$,9999999999")#<br>
156:     <b>Location:</b> #trim(address)#, #trim(city)#, #trim(state)#<br>
157:     <!-- <cfif #qryCommunity.recordCount# gt 0>
158:       <b>Community:</b> <a
href="community2.cfm?communityID=#qryCommunity.communityID#",#qryCommunity.name#</a><br>
159:       </cfif> ---->
160:     <CFIF (#size# neq "") and (#size# neq 0)>
161:       <b>Lot Acreage:</b> #size#<br>
162:     </CFIF>
163:     <CFIF (#size_unit# neq "") and (#size_unit# neq 0)>
164:       <b>Bldg. Size:</b> #size_unit# Sq Ft<br>
165:     </CFIF>
166:     <cfif propdscrip is not "5">
167:       <cfif #int(bedroom)# eq #bedroom#>
168:         <b>Bedrooms:</b> #int(bedroom)#<br>
169:       <cfelse>
170:         <b>Bedrooms:</b> #numberFormat(bedroom, 99.9)#<br>
171:       </cfif>
172:       <cfif #int(bath)# eq bath>
173:         <b>Baths:</b> #int(bath)#<br>
174:       <cfelse>
175:         <b>Baths:</b> #numberFormat(bath, 99.9)#<br>
176:       </cfif>
177:       </cfif>
178:     </td>
179:     <td valign="top" width="50%">
180:       <CFIF #prop.main.agent.id# gt 0><!-- was url.agent_id---bws--->
181:         <b>Agent:</b> #firstName# #lastName#<br>
182:         <b>Work Phone:</b> #workPhone#<br>
183:         <CFIF (#pub_home# eq "Y") and isDefined("homePhone") and len(trim(homePhone)) gt 0>
184:           <b>Home Phone: </b> #homePhone#<br>
185:         </CFIF>
186:         <b>E-Mail:</b> <a href="mailto:#email#">#email#</a><br>
187:         <!-- Mapquest link added 5/8/00 --->
188:       </CFIF>
189:     </td>
190:   </tr>
191:   <cfif trim(dscrip1) is not "">
192:     <tr>
193:       <td colspan="2">
194:         <b>Features:</b> #dscrip1#
195:       </td>
```

```
196:         </tr>
197:     </cfif>
198: </table>
199: <cfset cURL =
200:     "MQConnect/mqinterconnect.exe?POI1city=#trim(prop_main.city)&POI1state=#trim(prop_main.state)&POI1streetaddress=#trim(prop
       _main.address)&POI1iconid=201&level=9">
201:         <p align="center"><a href="#cURL#" target="_blank">Show Map</a> | <a href="JavaScript: newWindow =
       openWin('propview.print.cfm?prop_id=#prop_id#','open',
       'width=550,height=600,toolbar=1,location=0,directories=0,status=0,menuBar=0,scrollBars=1,resizable=1');
       newWindow.focus()">Printable Page</a> | <a href="Keepers\addsaved.cfm?prop_id=#prop_main.prop_id#">Add this to
       Keepers</a></p>
202:     </cfoutput>
203: </tr>
204: </table>
205: </td>
206: <td valign="top" width="1" bgcolor="#6666ff"></td>
207: <td valign="top" width="4" bgcolor="#ffffff"></td>
208: <td width="120" valign="top">
209:     <cfinclude template="120x65ads.cfm">
210: </td>
211: </tr>
212: </table>
213:
214: <cfinclude template="footer.cfm">
215:
216: </body>
217: </html>
```



```

50: <CFSET bcount = 0>
51: <CFQUERY NAME="qBambooData" DATASOURCE="#sourceName#">
52:   SELECT param_value, param_cntr
53:   FROM p_param
54:   WHERE prop_id = #prop_id#
55:   AND #ap_agency#
56:   AND dataGroup = #dgBamboo#
57:   AND param_Name = 'imgLabel'
58:   ORDER BY param_cntr
59: </CFQUERY>
60: <CFSET bcount = qBambooData.RecordCount#>
61: <CFIF #bcount# NEQ 0>
62:   <CFSET isBamboo = "1">
63: <CFELSE>
64:   <CFSET isBamboo = "0">
65: </CFIF>
66:
67: <!-- Get the actual Bamboo to view -->
68:
69: <CFIF NOT isDefined("viewId")>
70:   <CFset viewId = "1">
71: </CFIF>
72: <CFQUERY NAME="qBambooView" DATASOURCE="#sourceName#">
73:   SELECT *
74:   FROM p_param
75:   WHERE prop_id = #prop_id#
76:   AND #ap_agency#
77:   AND dataGroup = #dgBamboo#
78:   AND param_cntr = #viewId#
79: </CFQUERY>
80: <!-- <CFIF #qBambooData.recordCount# LE #totalNames# -->
81: <CFLOOP QUERY="qBambooView">
82:   <CFIF #trim(param_name)# EQ "imgName">
83:     <CFSET imageTitle = #trim(param_value)#>
84:     <CFELSEIF #trim(param_name)# EQ "imgCapti">
85:       <CFSET imageCaption = #trim(param_value)#>
86:       <CFELSEIF #trim(param_name)# EQ "imgURL">
87:         <CFSET imageURL = #trim(param_value)#>
88:         <CFELSEIF #trim(param_name)# EQ "imgLabel">
89:           <CFSET imageLabel = #trim(param_value)#>
90:         <CFELSE>
91:           <CFSET imageError = #trim(param_name)#>
92:         </CFIF>
93:       </CFLOOP>
94:     <!-- <CFELSE>
95:       <CFSET imageError = "Too many Bamboos">
96:     </CFIF -->
97:     <CFSET ls_Values = valueList(qBambooData.param_value)>
98:     <CFSET ls_Order = valueList(qBambooData.param_cntr)>

```



```

99:
100: <CFQUERY NAME="qagency" DATASOURCE="#sourceName#">
101: SELECT name, address, city, state, zip, phone, fax, num800, email, URL_name
102: FROM agency
103: WHERE #ap_agency#
104:
105: </CFQUERY>
106:
107: <html>
108: <head>
109: <title><cfoutput>#ap_agencyName# - Find a Home - Printable Property Details</cfoutput></title>
110: <link rel="stylesheet" href="style1.css" type="text/css">
111: <script language="JavaScript" src="window.js"></script>
112: </head>
113:
114: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
115:
116: <table width="480" border="0" cellpadding="0" cellspacing="0" align="center">
117: <tr>
118: <td>
119: <CFOUTPUT QUERY="prop_main">
120: <table border="0" width="480">
121: <tr>
122: <td colspan="2" align="center">
123: <p><b>#name#</b></p>
124: <CFIF #len(Photo_name)# GT 1>
125: <br>
126: <CFELSE>
127: <p>Photo of this property is<br>unavailable at this time.</p>
128: </CFIF>
129: </td>
130: </tr>
131: <tr>
132: <td valign="top" width="50%">
133: <b>Priced At:</b> #NumberFormat(int(price),"$,99999999999")#<br>
134: <b>Location:</b> #trim(address)#, #trim(city)#, #trim(state)#<br>
135: <CFIF (#size# neq "") and (#size# neq 0)>
136: <b>Lot Acreage:</b> #size#<br>
137: </CFIF>
138: <CFIF (#size_unit# neq "") and (#size_unit# neq 0)>
139: <b>Bldg. Size:</b> #size_unit# Sq Ft<br>
140: </CFIF>
141: <cfif propdscrip is not "5">
142: <cfif #int(bedroom)# eq #bedroom#>
143: <b>Bedrooms:</b> #int(bedroom)#<br>
144: <cfelse>
145: <b>Bedrooms:</b> n#numberFormat(bedroom, 99.9)#<br>
146: <cfif>
147: <cfif #int(bath)# eq bath>

```

```

148:         <b>Baths:</b>#int(bath)#<br>
149:     <cfelse>
150:         <b>Baths:</b>#numberFormat(bath, 99.9)#<br>
151:     </cfif>
152: </cfif>
153: </td>
154: <td valign="top" width="50%">
155:     <CFIF #agent_id# gt 0>
156:         <b>Agent:</b>#firstName# #lastName#<br>
157:         <b>Work Phone:</b>#workPhone#<br>
158:         <CFIF (#pub_home# eq "Y") and isDefined("homePhone") and len(trim(homePhone)) gt 0>
159:             <b>Home Phone: </b>#homePhone#<br>
160:         </CFIF>
161:         <b>E-Mail:</b> <a href="mailto:#email#">#email#</a><br>
162:         <!-- Mapquest link added 5/8/00 -->
163:     </CFIF>
164: </td>
165: </tr>
166: <cfif trim(dscrptn_1) is not "">
167: <tr>
168:     <td colspan="2">
169:         <b>Features:</b>#dscrptn_1#
170:     </td>
171: </tr>
172: </cfif>
173: </table>
174: </cfoutput>
175: </td>
176: </tr>
177: </table>
178: </body>
179: </html>
180:

```

— 17 —

```
50: <tr>
51: <td><blockquote><p>Search for the right real estate agent by either Company, Name, or Specialty.</p></blockquote>
52: <form action="FindAgent_Result.cfm" method="post">
53: <table border="0" bgcolor="#ccccff" cellpadding="0" cellspacing="2" align="center">
54: <!--
55: <tr><td>Agent Name: </td><td><select name="agentFullName">
56: <option value="">-Agent Name-</option>
57: <cfoutput query="agentList">
58: <option value="#lastName#, #firstName#">#lastName#, #firstName#</option>
59: </cfoutput>
60: </select>
61: </td></tr>
62: <!--
63: <tr><td>Agent Name: </td>
64: <td><input type="text" value="" name="agentFullName" size="15"></td></tr>
65: <tr><td>Agency Name: </td><td><input type="text" value="" name="agencyName" size="15"></td></tr>
66: <tr><td>Specialty: </td><td><select name="specialty">
67: <option value="">-Any Specialty-</option>
68: <cfoutput query="specialtyList">
69: <option value="#specialty#">#specialty#</option>
70: </cfoutput></select>
71: </td></tr>
72: <tr><td><input type="submit" value="Search"> <input type="reset"
value="Reset"></td></tr>
73: </table>
74: </form>
75: </td>
76: </tr>
77: </table>
78: </td>
79: <td valign="top" width="1" bgcolor="#6666ff"></td>
80: <td valign="top" width="4" bgcolor="#ffffff"></td>
81: <td width="120" valign="top">
82: <cfinclude template="120x65ads.cfm">
83: </td>
84: </tr>
85: </table>
86:
87: <cfinclude template="footer.cfm">
88:
89: </body>
90: </html>
```

```

1: <cfparam name="nDisplayType" default="-1">
2: <cfparam name="nDisplayID" default="0">
3: <cfparam name="lVerbose" default="True">
4: <cfset cDisplayFind = "*" & nDisplayType & "|" & nDisplayID & "*">
5: <cfset cFindAll = "*" & nDisplayType & "|0*">
6:
7: <!--
8: <CFQUERY NAME="qAgency" DATASOURCE="#sourceName#">
9:   SELECT agency_id, name
10:   FROM agency
11:   WHERE #ap_Agency#
12: </CFQUERY>
13: ---
14:
15: <CFQUERY NAME="qLink" DATASOURCE="#sourceName#">
16:   SELECT linksGroup.name AS grpName,
17:   link.grpid,
18:   link.LinkId,
19:   link.Name,
20:   link.URL,
21:   link.SortOrder,
22:   link.displayPages,
23:   link.image
24: FROM link, linksGroup
25: WHERE linksGroup.distributorID = #ap_distributorID#
26: AND link.grpid = linksGroup.grpid
27: AND link.linkType = '#ap_res_links#'
28: AND linksGroup.linkType = link.linkType
29: AND ({ fn LOCATE('#preservesingleQuotes(cDisplayFind)#',link.displayPages)} > 0
30: OR { fn LOCATE('#preservesingleQuotes(cFindAll)#',link.displayPages)} > 0)
31: ORDER BY link.grpid,link.SortOrder, link.name<!-- ; sortlinksGroup.name, link.name --->
32: <!-- ABOVE LINE HAS BEEN COMMENTED OUT BY MIKE ON 5/10/00. REM-ED OUT TO SORT BY SORT ORDER AND NAME --->
33: </CFQUERY>
34:
35: <p>
36:
37: <cfif isDefined("ap_nListingColumns")>
38:   <cfset nMaxColumns = ap_nListingColumns>
39: <cfelse>
40:   <cfset nMaxColumns = 1>
41: </cfif>
42:
43: <cfif qLink.recordCount gt 0>
44:   <table width="100%" border="0" cellspacing="0" cellpadding="4">
45:     <cfset nLastGroup = -1>
46:     <cfset nColumn = 1>
47:     <CFSET nColWidth = int(100/nMaxColumns)> <!-- Set the column width --->
48:
49:     <cfoutput query="qLink">

```

1  
2  
1

```
1: a { font-family: verdana, arial, helvetica,sans-serif; color:#003399; font-size: 9pt; }
2: a.nav { font-family: arial, verdana, helvetica,sans-serif; color:#ffffff; font-size: 9pt; font-weight: bold; }
3: a.nav:hover { text-decoration: underline; font-family: arial, verdana, helvetica,sans-serif; color:#ffff00; font-size: 9pt;
  font-weight: bold; }
4: .heading { font-family: verdana, arial, helvetica,sans-serif; font-size: 10pt; font-weight: bold; color: #ffffff; }
5: a:hover { text-decoration: underline; font-family: verdana, arial, helvetica,sans-serif; color:#990000; }
6: p, body, th, ul, td { font-family: verdana, arial, helvetica,sans-serif; font-size: 9pt; }
7: .click_heading { font-family: verdana, arial, helvetica,sans-serif; font-size: 10pt; font-weight: bold; color: #ffffff; }
8: .td { font-family: verdana, arial, helvetica,sans-serif; font-size: 9pt; }
```

```
1: <!--
2: function openWin( windowURL, windowName, windowFeatures ) {
3:     return window.open( windowURL, windowName, windowFeatures ) ;
4: }
5: // -->
6:
```



```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
2: <cfinclude template="include\security.cfm">
3:
4:
5: <cfparam name="URL.SortBy" default="name,address">
6:
7: <cfquery name="qryAgency" datasource="#sourceName#">
8:   select * from agency
9:   where agency.distributorID = #ap_distributorID#
10:  and '14-' + convert(varchar,agency.agency_id) + '|' in (#listQualify(client.lstSecurity,"")#)
11:  order by #URL.SortBy#
12: </cfquery>
13:
14: <html>
15: <head>
16:   <cfoutput>
17:     <title>#ap_backofficeName# Backoffice</title>
18:   </cfoutput>
19:   <link rel="stylesheet" href="style1.css" type="text/css">
20: </head>
21:
22: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
23:
24: <p><cfinclude template="header.cfm"></p>
25:
26: <cfif client.securityLevel eq 0> <!-- Administrator Access -->
27:   <!-- Does not really have access to this page -->
28:   <cflocation url="index.cfm" addtoken="no">
29: </cfif>
30:
31: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
32:   <tr bgcolor="#cccc99">
33:     <td colspan="4">
34:       <span class="h2"><b>Agency Administration</b></span><span><b><span><b>Add an Agency</a>
35:     </td>
36:   </tr>
37:
38:   <tr bgcolor="#cccccc">
39:     <td>Sort by <a href="agencyAdm.cfm?sortBy=name,address"><b>Agency Name</b></a></td>
40:     <td>Sort by <a href="agencyAdm.cfm?sortBy=address"><b>Agency Address</b></a></td>
41:     <td>Sort by <a href="agencyAdm.cfm?sortBy=phone"><b>Agency Phone</b></a></td>
42:     <td><b></td>
43:   </tr>
44:
45:
46:   <CFIF qryAgency.recordCount is 0>
47:     <TR><TD COLSPAN="4"><I>There are no agencies defined</I></TD></TR>
48:   </CFIF>
49:   <cfset lColor = True>

```

```
50: <cfloop query="qryAgency">
51:   <cfset lColor = not lColor>
52:   <tr <cfif lColor is TRUE>bgcolor="#eeeeee"</cfif>>
53:     <cfoutput>
54:       <CFQUERY NAME="qryFindBio" DATASOURCE="#SourceName#">
55:         SELECT agency_id
56:         FROM agency_param
57:         WHERE agency_param.agency_id=#qryAgency.agency_id#
58:       </CFQUERY>
59:
60:       <td>#qryAgency.name#</td>
61:       <td>#qryAgency.address#</td>
62:       <td>#qryAgency.phone#</td>
63:       <td>
64:         <a href="agencyMaint.cfm?agency_id=#qryAgency.agency_id#">Edit</a> | <a
href="agencyMaint.cfm?agency_id=#qryAgency.agency_id#displayPage=Template"><cfif qryFindBio.recordCount is
0>Add<cfelse>Edit</cfif> Enhanced Agency Profile</a>
65:       </td>
66:     </cfoutput>
67:   </tr>
68: </cfloop>
69: </table></p>
70:
71: </body>
72: </html>
```

```

1: <CFPARAM NAME="ACTION" DEFAULT="Cancel"><!-- Cancel -->
2:
3: <CFIF isDefined("agency_id")>
4:   <cfset nTypeID = agency_id>
5: </cfif>
6:
7:
8: <HTML>
9: <TITLE>Online Agency Upload Results</TITLE>
10:
11: <CFIF #Action# is "Cancel">
12:   <CFLOCATION URL="agencyMaint.cfm?agency_id=#nTypeID#&displayPage=Template" ADDTOKEN="NO">
13: </CFIF>
14:
15: <BODY BGCOLOR="WHITE">
16:   <!-- <CFINCLUDE TEMPLATE="adminlinks.cfm" --> -->
17:   <CFAPPLICATION NAME="RealStuff" CLIENTMANAGEMENT="Yes">
18:
19:   <CFIF #Action# is "Add">
20:     Field Values:<BR>
21:     <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
22:       <CFSET cNewField = "FORM.Field" & nIndex>
23:       <CFOUTPUT>#cNewField# = #evaluate(cNewField)#<BR></CFOUTPUT>
24:     </CFLOOP>
25:     <BR>
26:     <HR>
27:
28:
29:   <!-- First try to find out what kind of image is being uploaded -->
30:   <CFSET nImageTypeLoc = listFindNoCase(FORM.Field_Names,'imgType')>
31:   <CFIF nImageTypeLoc GT 0>
32:     <CFSET cImageField = 'FORM.FIELD' & nImageTypeLoc>
33:     <CFSET nImageType = #evaluate(cImageField)#>
34:     <CFOUTPUT>Image Type : #nImageType#<BR></CFOUTPUT>
35:   <CFELSE>
36:     <CFSET nImageType = -1>
37:   </CFIF>
38:
39:   <!-- !!!!! -->
40:   <!-- <CFSET nImageType = 0> -->
41:
42:   <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
43:     <CFSET nParamID = -1>
44:
45:     <CFQUERY NAME="qryFindParamID" DATASOURCE="#SourceName#">
46:       SELECT * FROM param_defs
47:       WHERE dataGroup=10
48:       AND agency_id in (10, #ap_agency number#)
49:       AND name='#listGetAt(FORM.Field_Names,nIndex) #'

```

```

50: </CFQUERY>
51:
52: <CFIF qryFindParamID.recordCount GT 0>
53:   <CFSET nParamID = qryFindParamID.id>
54: </CFIF>
55:
56: <CFSET cFieldType = ucase(trim(listGetAt(FORM.FieldTypes, nIndex)))>
57: <CFSET cNewField = "FORM.FIELD" & nIndex>
58:
59: <CFIF cFieldType is "TEXT">
60:   <cfoutput>Inserting data:
61:     #nTypeID#,#nParamID#,#ap_agency_number#,#param_counter#,'#qryFindParamID.name#','#Evaluate(cNewField)','#,10</cfoutput> <br>
62:     <CFSET cTextToSend = evaluate(cNewField)>
63:     <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
64:     <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
65:       INSERT INTO agency_param(agency_id,param_id,param_cntr,param_name,param_value,dataGroup)
66:       VALUES (#nTypeID#,#nParamID#,#param_counter#,'#qryFindParamID.name#','#cTextToSend#',10)
67:     </CFQUERY>
68:     <CFELSEIF cFieldType is "TEXTAREA">
69:       <cfoutput>Inserting Text Area data:
70:         #nTypeID#,#nParamID#,#ap_agency_number#,#param_counter#,'#qryFindParamID.name#','#Evaluate(cNewField)','#,10</cfoutput> <br>
71:         <CFSET cTextToSend = evaluate(cNewField)>
72:         <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
73:         <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
74:           INSERT INTO agency_param(agency_id,param_id,param_cntr,param_name,param_value,dataGroup)
75:           VALUES (#nTypeID#,#nParamID#,#param_counter#,'#qryFindParamID.name#','#cTextToSend#',10)
76:         </CFQUERY>
77:         <CFELSEIF cFieldType is "CHECKBOX">
78:           <cfoutput>Inserting checkbox data:
79:             #nTypeID#,#nParamID#,#ap_agency_number#,#param_counter#,'#qryFindParamID.name#','#Evaluate(cNewField)','#,10</cfoutput> <br>
80:             <CFSET cTextToSend = evaluate(cNewField)>
81:             <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
82:             <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
83:               INSERT INTO agency_param(agency_id,param_id,param_cntr,param_name,param_value,dataGroup)
84:               VALUES (#nTypeID#,#nParamID#,#ap_agency_number#,#param_counter#,'#qryFindParamID.name#','#cTextToSend#',10)
85:             </CFQUERY>
86:             <CFELSEIF cFieldType is "SELECT">
87:               <cfoutput>Inserting select data:
88:                 #nTypeID#,#nParamID#,#ap_agency_number#,#param_counter#,'#qryFindParamID.name#','#Evaluate(cNewField)','#,10</cfoutput> <br>
89:                 <CFSET cTextToSend = evaluate(cNewField)>
90:                 <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
91:                 <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
92:                   INSERT INTO agency_param(agency_id,param_id,param_cntr,param_name,param_value,dataGroup)
93:                   VALUES (#nTypeID#,#nParamID#,#param_counter#,'#qryFindParamID.name#','#cTextToSend#',10)
94:                 </CFQUERY>
95:                 <CFELSEIF cFieldType is "FILE">
96:                   <HR>
97:                   <CFSET cNewField = "FORM.FIELD" & nIndex>

```

```

95: <CFSET cFilePath = trim("Field" & nIndex)>
96:
97: <CFSET cFilePath = #ap_image_path# & "Agency#FORM.agency_id#\ ">
98:
99: <CFOUTPUT>File Name is: #cFilePath#</CFOUTPUT><BR>
100: <CFOUTPUT>New Field : #cNewField# (#evaluate(cNewField)#)</CFOUTPUT><BR>
101: <CFOUTPUT>Field Name: #listGetAt(FORM.Field Names,nIndex)#</CFOUTPUT><BR>
102: <CFIF listGetAt(FORM.Field Names, nIndex) is "imgFile">
103:   <CFSET nImageField = #FORM.imageField#>
104:   <CFSET cImageType = "FORM.FIELD" & nImageField>
105:   <CFIF nImageType is "0"> <!-- This is a still image --> <!-- </CFIF> nImageField GT 0 AND
      #evaluate(cImageType) is "0" -->
106:   <CFOUTPUT>#ap_image_path# : #cNewField#</CFOUTPUT>
107:   <CFOUTPUT>[#evaluate(cNewField)#]</CFOUTPUT>
108:
109:   <CFTRY>
110:     <CFDIRECTORY>
111:       DIRECTORY="#cFilePath#"
112:       ACTION="CREATE"
113:     >
114:     <CFOUTPUT>Creating New Directory #cFilePath#</CFOUTPUT><BR>
115:     <CFATCH TYPE="ANY">
116:       <B>Directory already exists!</B><BR>
117:     </CFATCH>
118:   </CFTRY>
119:
120:   <!-- If an image name is not sent, then the user only wanted to add a text entry -->
121:   <!-- If the field is blank, don't try to send anything -->
122:
123:   <CFSET cEvaluate = evaluate(cNewField)>
124:   <CFIF len(trim(cEvaluate)) gt 0>
125:     <CFFILE>
126:       DESTINATION=#cFilePath#
127:       ACTION="UPLOAD"
128:       NAMECONFLICT="OVERWRITE"
129:       FILEFIELD="#cImageField#"
130:
131:   <CFIF #FILE.fileWasSaved#>
132:     <BR><B>File was Saved</B><BR>
133:     <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
134:       INSERT INTO agency_param(agency_id,param_id,param_name,param_value,param_cntr,param_name,param_value,dataGroup)
135:       VALUES
        (#ntypeID#,#nParamID#,#param_counter#,'#qryFindParamID.name#','Agency#FORM.agency_id#\#FILE.ServerFile#',10)
        </CFQUERY>
136:     <CFELSE>
137:       <BR><B>File was NOT saved</B>
138:     </CFABORT>
139:   </CFIF>
140:   <CFELSE>
141:

```

```

142: <!-- Save the database info -->
143: <BR><B>File was Saved (No image)</B><BR>
144: <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
145: INSERT INTO agency_param(agency_id,param_id,param_ctr,param_name,param_value,dataGroup)
146: VALUES (#ntypeID#,#nParamID#,#param_counter#,'#qryFindParamID.name#','',10)
147: </CFQUERY>
148: </CFIF>
149: </CFELSE>
150: <CFOUTPUT>Saving other image information:#cNewField# [#evaluate(cNewField)] #evaluate('FORM.Field1')# *
#cFileField# * #evaluate(cFileField)<BR></CFOUTPUT>
151: <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
152: INSERT INTO agency_param(agency_id,param_id,param_ctr,param_name,param_value,dataGroup)
153: VALUES (#ntypeID#,#nParamID#,#param_counter#,'#qryFindParamID.name#','',10)
154: </CFQUERY>
155: </CFIF>
156: </CFIF>
157: </CFIF>
158: </CFLOOP>
159:
160: <!-- New takes us back to the view mode, informing the user that information has been updated -->
161: <CFLOCATION URL="agencyMaint.cfm?agency_id=#ntypeID#&Action=Updated&displayPage=Template" ADDTOKEN="NO">
162:
163: <CFELSEIF #Action# is "Edit">
164: <!-- First try to find out what kind of image is being uploaded -->
165: <CFSET nImageTypeLoc = listFindNoCase(FORM.Field_Names,'imgType')>
166: <CFIF nImageTypeLoc GT 0>
167: <CFSET cImageField = 'FORM.FIELD' & nImageTypeLoc>
168: <CFSET nImageType = #evaluate(cImageField)#>
169: <CFOUTPUT>Image Type : #nImageType#</CFOUTPUT>
170: </CFELSE>
171: <CFSET nImageType = -1>
172: </CFIF>
173:
174: <!-- !!!!! -->
175: <!-- <CFSET nImageType = 0> -->
176:
177:
178: <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
179: <CFSET cFieldType = ucase(trim(listGetAt(FORM.FieldTypes, nIndex)))>
180: <CFSET cNewField = "FORM.FIELD" & nIndex>
181:
182: <CFIF cFieldType is "FILE">
183: <CFSET cNewField = "FORM.FIELD" & nIndex>
184: <CFSET cFileField = trim("Field" & nIndex)>
185:
186: <CFOUTPUT>New Field : #cNewField# (#evaluate(cNewField))</CFOUTPUT><BR>
187: <CFOUTPUT>Field Name: #listGetAt(FORM.Field_Names,nIndex)#</CFOUTPUT><BR>
188:
189: <CFIF listGetAt(FORM.Field_Names, nIndex) is "imgFile" AND #Evaluate(cNewField) is not "">

```

```

190: <CFSET nimageField = #FORM.imageField#>
191: <CFSET cimageType = "FORM.FIELD" & nimageField>
192: <CFIF nimageType is "0"> <!--- This is a still image ---> <!--- </CFIF>nimageType GT -1 AND #evaluate(cimageType)#
    is "0"> --->
193: <CFOUTPUT>#ap_image_path# : #cNewField#</CFOUTPUT>
194: <CFOUTPUT>[#evaluate(cNewField)#]</CFOUTPUT>
195:
196: <CFSET cFilePath = #ap_image_path# & "Agency#nTypeID#\ ">
197:
198: <CFIF
199:     DESTINATION=#cFilePath#
200:     ACTION="UPLOAD"
201:     NAMECONFLICT="OVERWRITE"
202:     FILEFIELD="#cFileField#">
203:
204: <CFIF #FILE.fileWasSaved#>
205:     <B>File was Saved</B><BR>
206:     <CFOUTPUT>#Evaluate(cNewField)# / #nTypeID# / #param_counter# /
#listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
207:     <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
        UPDATE agency_param
        SET param_value = 'Agency#nTypeID#\#FILE.ServerFile#'
        WHERE agency_id=#nTypeID#
        AND param_cntr=#param_counter#
        AND param_name='#listGetAt(FORM.Field_Names,nIndex) #'
208:     </CFQUERY>
209: <CFELSE>
210:     <B>File was NOT saved</B>
211:     <CFABORT>
212: </CFIF>
213: <CFELSE>
214:
215: <!--- Just insert the name, since this is not a still image --->
216:
217:
218:
219:
220:
221: <CFOUTPUT>Insert Other Image<BR>#Evaluate(cNewField)# / #nTypeID# / #param_counter# /
#listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
222: <CFSET cTextToSend = evaluate(cNewField)>
223: <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
224: <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
        UPDATE agency_param
        SET param_value = 'cTextToSend#'
        WHERE agency_id=#nTypeID#
        AND param_cntr=#param_counter#
        AND param_name='#listGetAt(FORM.Field_Names,nIndex) #'
225: </CFQUERY>
226: </CFIF>
227: </CFIF>
228: <CFELSE>
229: <CFOUTPUT>#Evaluate(cNewField)# / #nTypeID# / #param_counter# / #listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
230: <CFSET cTextToSend = evaluate(cNewField)>
231:
232:
233:
234:
235:

```

```
236: <CFSET cTextToSend = preservesingleQuotes(cTextToSend)>
237: <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
238:     UPDATE agency_param
239:     SET param_value = '#cTextToSend#'
240:     WHERE agency_id=#ntypeID#
241:     AND param_cntr=#param_counter#
242:     AND param_name='#listGetAt(FORM.Field_Names,nIndex)#'
243: </CFQUERY>
244: </CFIF>
245: </CFLOOP>
246: <!-- Now take us back to the view mode, informing the user that information has been updated -->
247: <CFLOCATION URL="agencyMaint.cfm?agency_id=#ntypeID#&Action=Updated&displayPage=Template" ADDTOKEN="NO">
248:
249: <CFELSEIF #Action# is "Delete">
250: <CFIF NOT IsDefined("param_counter")> <!-- To delete the information -->
251: <CFLOCATION URL="agencyMaint.cfm?agency_id=#ntypeID#&displayPage=Template" ADDTOKEN="NO">
252: </CFIF>
253:
254: <!-- Delete the selected paragraph -->
255: <CFQUERY NAME="qryDeleteAd" DATASOURCE="#SourceName#">
256:     DELETE FROM agency_param
257:     WHERE agency_id=#ntypeID# AND
258:     param_cntr=#param_counter# AND
259:     dataGroup=10
260: </CFQUERY>
261:
262: <!-- Now take us back to the view mode, informing the user that information has been updated -->
263: <CFLOCATION URL="agencyMaint.cfm?agency_id=#ntypeID#&Action=Deleted&displayPage=Template" ADDTOKEN="NO">
264: </CFIF>
265:
266: </BODY>
267: </HTML>
268:
```



```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfinclude template="include\securityTest.cfm">
4:
5: <cfparam name="URL.agency_id" default="-1">
6: <cfparam name="URL.userName" default="">
7: <cfparam name="URL.displayPage" Default="Info">
8:
9: <cfset nAgencyID = URL.agency_id>
10: <cfset cReturnURL = "returnURL=agencyMaint.cfm&ReturnAgency_id=#nAgencyID&displayPage=#URL.displayPage#">
11:
12: <cfquery name="qryFindAgency" datasource="#sourceName#">
13:   select * from agency
14:   where agency.agency_id=#nAgencyID#
15: </cfquery>
16:
17: <cfquery name="qryFindAgents" datasource="#sourceName#">
18:   select agents.agent_id
19:   from agents
20:   where agents.agency_id = #nAgencyID#
21: </cfquery>
22:
23: <html>
24: <head>
25:   <cfoutput>
26:     <title#ap_backofficeName# Backoffice</title>
27:   </cfoutput>
28:   <link rel="stylesheet" href="style1.css" type="text/css">
29:   <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
30: </head>
31:
32: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
33:
34: <p><cfinclude template="header.cfm"></p>
35:
36: <cfoutput>
37:
38: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
39:   <tr bgcolor="#cccc99"><td colspan="5">
40:     <span class="h2">
41:       <b>Agency Maintenance
42:     <cfif agency_id gt -1>
43:       - #qryFindAgency.name#
44:     </cfif>
45:     <cfif URL.displayPage is "Agents"> Agents
46:     <cfelseif URL.displayPage is "Template"> Enhanced Agency Profile
47:     <cfelseif URL.displayPage is "Properties"> Properties
48:     </cfif>
49:   </b></span>
```

```
50: <cfif isDefined("URL.displayPage")><div display="flex; justify-content: space-between; align-items: center; padding: 10px 0;">
51:   <div><div display="flex; align-items: center; gap: 10px;">
52:     <div><div display="flex; align-items: center; gap: 5px;">
53:       <div><div display="flex; align-items: center; gap: 5px;">
54:         <div><div display="flex; align-items: center; gap: 5px;">
55:           <div><div display="flex; align-items: center; gap: 5px;">
56:             <div><div display="flex; align-items: center; gap: 5px;">
57:               <div><div display="flex; align-items: center; gap: 5px;">
58:                 <div><div display="flex; align-items: center; gap: 5px;">
59:                   <div><div display="flex; align-items: center; gap: 5px;">
60:                     <div><div display="flex; align-items: center; gap: 5px;">
61:                       <div><div display="flex; align-items: center; gap: 5px;">
62:                         <div><div display="flex; align-items: center; gap: 5px;">
63:                           <div><div display="flex; align-items: center; gap: 5px;">
64:                             <div><div display="flex; align-items: center; gap: 5px;">
65:                               <div><div display="flex; align-items: center; gap: 5px;">
66:                                 <div><div display="flex; align-items: center; gap: 5px;">
67:                                   <div><div display="flex; align-items: center; gap: 5px;">
68:                                     <div><div display="flex; align-items: center; gap: 5px;">
69:                                       <div><div display="flex; align-items: center; gap: 5px;">
70:                                         <div><div display="flex; align-items: center; gap: 5px;">
71:                                           <div><div display="flex; align-items: center; gap: 5px;">
72:                                             <div><div display="flex; align-items: center; gap: 5px;">
73:                                               <div><div display="flex; align-items: center; gap: 5px;">
74:                                                 <div><div display="flex; align-items: center; gap: 5px;">
75:                                                   <div><div display="flex; align-items: center; gap: 5px;">
76:                                                     <div><div display="flex; align-items: center; gap: 5px;">
77:                                                       <div><div display="flex; align-items: center; gap: 5px;">
78:                                                         <div><div display="flex; align-items: center; gap: 5px;">
79:                                                           <div><div display="flex; align-items: center; gap: 5px;">
80:                                                             <div><div display="flex; align-items: center; gap: 5px;">
81:                                                               <div><div display="flex; align-items: center; gap: 5px;">
82:                                                                 <div><div display="flex; align-items: center; gap: 5px;">
83:                                                                   <div><div display="flex; align-items: center; gap: 5px;">
84:                                                                     <div><div display="flex; align-items: center; gap: 5px;">
85:                                                                       <div><div display="flex; align-items: center; gap: 5px;">
86:                                                                         <div><div display="flex; align-items: center; gap: 5px;">
87:                                                                           <div><div display="flex; align-items: center; gap: 5px;">
88:                                                                             <div><div display="flex; align-items: center; gap: 5px;">
89:                                                                               <div><div display="flex; align-items: center; gap: 5px;">
90:                                                                                 <div><div display="flex; align-items: center; gap: 5px;">
91:                                                                                   <div><div display="flex; align-items: center; gap: 5px;">
92:                                                                                     <div><div display="flex; align-items: center; gap: 5px;">
93:                                                                                       <div><div display="flex; align-items: center; gap: 5px;">
94:                                                                                         <div><div display="flex; align-items: center; gap: 5px;">
95:                                                                                           <div><div display="flex; align-items: center; gap: 5px;">
96:                                                                                             <div><div display="flex; align-items: center; gap: 5px;">
97:                                                                                               <div><div display="flex; align-items: center; gap: 5px;">
```

98: </body>  
99: </html>  
100:

-----

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfinclude template="include\securityTest.cfm">
4:
5: <cfparam name="URL.agency_id" default="-1">
6: <cfparam name="URL.userName" default="">
7:
8: <cfset nAgencyID = URL.agency_id>
9:
10: <cfquery name="qryFindAgency" datasource="#sourceName#">
11:   select * from agency
12:   where agency.agency_id=#nAgencyID#
13: </cfquery>
14:
15: <html>
16: <head>
17:   <cfoutput>
18:     <title>#ap_backofficeName# Backoffice</title>
19:   </cfoutput>
20:   <link rel="stylesheet" href="style1.css" type="text/css">
21:   <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
22: </head>
23:
24: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
25:
26: <p><cfinclude template="header.cfm"></p>
27:
28: <cfoutput>
29:
30: <form name="frmAgency" enctype="multipart/form-data" action="agencyUpdate.cfm" method="post">
31:   <input type="hidden" name="agency_id" value="#nAgencyID#">
32:   <input type="hidden" name="edtDistributorID" value="#ap_distributorID#">
33:   <input type="hidden" name="edtCountry" value="USA">
34:
35:   <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
36:     <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Agency Maintenance</b></span></td></tr>
37:
38:     <CFIF URL.UserName is not "">
39:       <tr bgcolor="eeeeee">
40:         <td colspan="5"><p><font color="red">#URL.UserName#</font></p></td>
41:       </tr>
42:       <tr bgcolor="eeeeee"><td colspan="5"><nbsp;</td></tr>
43:     </CFIF>
44:
45:     <tr bgcolor="eeeeee">
46:       <td width="15%">Agency Name:</td>
47:       <td width="34%"><input type="text" name="edtAgencyName" value="#qryFindAgency.name#"></td>
48:       <td width="2%"><nbsp;</td>
49:       <td width="15%">Phone:</td>
```

```

50: <td width="34%"><input type="text" name="editPhone" value="#qryFindAgency.phone#"></td>
51: </tr>
52:
53: <tr bgcolor="eeeeee">
54: <td width="15%">Address:</td>
55: <td width="34%"><input type="text" name="editAddress" value="#qryFindAgency.address#"></td>
56: <td colspan="3">&nbsp;</td>
57: </tr>
58: <tr bgcolor="eeeeee">
59: <td width="15%">City:</td>
60: <td width="34%"><input type="text" name="editCity" value="#qryFindAgency.city#"></td>
61: <td colspan="3">&nbsp;</td>
62: </tr>
63: <tr bgcolor="eeeeee">
64: <td width="15%">State:</td>
65: <td width="34%"><input type="text" name="editState" value="#qryFindAgency.state#" maxlength="2"></td>
66: <td colspan="3">&nbsp;</td>
67: </tr>
68: <tr bgcolor="eeeeee">
69: <td width="15%">Zipcode:</td>
70: <td width="34%"><input type="text" name="editzipcode" value="#qryFindAgency.zip#"></td>
71: <td colspan="3">&nbsp;</td>
72: </tr>
73:
74: <tr bgcolor="eeeeee">
75: <td width="15%">Fax:</td>
76: <td width="34%"><input type="text" name="editFax" value="#qryFindAgency.fax#"></td>
77: <td width="2%">&nbsp;</td>
78: <td width="15%">Email:</td>
79: <td width="34%"><input type="text" name="editEmail" value="#qryFindAgency.email#"></td>
80: </tr>
81:
82: <tr bgcolor="eeeeee">
83: <td width="15%">Specialty:</td>
84: <td width="34%"><input type="text" name="editSpecialty" value="#qryFindAgency.specialty#"></td>
85: <td width="2%">&nbsp;</td>
86: <td width="15%">Master Agency:</td>
87: <td width="34%">
88: <select name="editMasterAgency">
89: <option value="0">--None--
90: </select>
91: <cfif qrySecurity.entityTypeID is 4 and qrySecurity.entityID is not qryFindAgency.agency_id>
92: <option value="#qrySecurity.entityID#">cfif qryFindAgency.parentAgency is qrySecurity.entityID
selected</cfif></select>
93: </cfif>
94: </td>
95: </td>
96: </td>
97: </tr>

```

```

98: <tr bgcolor="eeeeee">
99:   <td width="15%">Sold Life:</td>
100:   <td width="34%"><input type="text" name="edtSoldLife" value="#qryFindAgency.soldLife#"></td>
101:   <td width="2%">&nbsp;</td>
102:   <td width="15%">New Life:</td>
103:   <td width="34%"><input type="text" name="edtNewLife" value="#qryFindAgency.newLife#"></td>
104: </tr>
105:
106:
107: <tr bgcolor="eeeeee">
108:   <td width="15%">Main Image:</td>
109:   <td width="34%"><input type="file" name="edtmainImage"></td>
110:   <td colspan="3" align="left">
111:     <cfif qryFindAgency.mainImage is "">&nbsp;</cfif>
112:     <cfelse>
113:       <cfset cCurrentImage = getFileFromPath(qryFindAgency.mainImage)>
114:       <cfset nAt = findNoCase("-", cCurrentImage)>
115:       <cfif nAt gt 0>
116:         <cfset cCurrentImage = mid(cCurrentImage, nAt+1, len(cCurrentImage)-nAt)>
117:       </cfif>
118:       <em>Currently: #cCurrentImage#</em>
119:     </cfif>
120:   </td>
121: </tr>
122:
123: <tr bgcolor="eeeeee">
124:   <td width="15%">Header Image:</td>
125:   <td width="34%"><input type="file" name="edtheadfilename"></td>
126:   <td colspan="3" align="left">
127:     <cfif qryFindAgency.headerfilename is "">&nbsp;</cfif>
128:     <cfelse>
129:       <cfset cCurrentImage = getFileFromPath(qryFindAgency.headerfilename)>
130:       <cfset nAt = findNoCase("-", cCurrentImage)>
131:       <cfif nAt gt 0>
132:         <cfset cCurrentImage = mid(cCurrentImage, nAt+1, len(cCurrentImage)-nAt)>
133:       </cfif>
134:       <em>Currently: #cCurrentImage#</em>
135:     </cfif>
136:   </td>
137: </tr>
138:
139: <tr bgcolor="eeeeee">
140:   <td width="15%">Footer Image:</td>
141:   <td width="34%"><input type="file" name="edtfooterfilename"></td>
142:   <td colspan="3" align="left">
143:     <cfif qryFindAgency.footerfilename is "">&nbsp;</cfif>
144:     <cfelse>
145:       <cfset cCurrentImage = getFileFromPath(qryFindAgency.footerfilename)>
146:       <cfset nAt = findNoCase("-", cCurrentImage)>
147:       <cfif nAt gt 0>
148:         <cfset cCurrentImage = mid(cCurrentImage, nAt+1, len(cCurrentImage)-nAt)>

```

```

147:         </cfif>
148:         <em>Currently: #cCurrentImage#</em>
149:         </cfif>
150:     </td>
151: </tr>
152:
153: <tr bgcolor="eeeeee">
154:     <td width="15%">Description:</td>
155:     <td colspan="4">
156:         <textarea name="edtDesc" rows="5" cols="80" wrap="virtual">#qryFindAgency.Description#</textarea>
157:     </td>
158: </tr>
159:
160: <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
161:
162: <tr bgcolor="eeeeee">
163:     <td colspan="5">
164:         <cfif qryFindAgency.recordCount is 0>
165:             <input type="submit" name="btnUpdate" value="Add Agency">
166:             <input type="reset" value="Reset Info">
167:         <cfelse>
168:             <input type="submit" name="btnUpdate" value="Update Agency">
169:             <input type="reset" value="Reset Info">
170:             <input type="submit" name="btnDelete" value="Delete Agency">
171:         </cfif>
172:     </td>
173: </tr>
174:
175: </table>
176: </FORM>
177: </cfoutput>
178:
179: <cfif nAgencyID gt 0>
180:     <cfparam name="URL.SortBy" Default="lastname,firstname">
181:     <cfparam name="URL.displayPage" Default="Agents">
182:
183:     <cfif URL.displayPage is "Agents">
184:         <cfquery name="qryAgents" datasource="#sourcename#">
185:             select agent_id, firstname, lastname, email, workphone, specialty from Agents
186:             where agents.agency_id=#nAgencyID#
187:             order by #URL.SortBy#
188:         </cfquery>
189:
190:         <cfset cReturnURL = "returnURL=agencyMaint.cfm&ReturnAgency_id=#nAgencyID#">
191:         <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
192:             <cfoutput>
193:                 <tr bgcolor="#cccc99"><td colspan="6"><b>Agents under this agency</b></span>&nbsp;</tr>

```

```

194: <tr bgcolor="#cccccc">
195: <td><b><a href="agencyMaint.cfm?agency_id=#nAgencyID&SortBy=lastname,firstname">Name</a></b></td>
196: <td><b><a href="agencyMaint.cfm?agency_id=#nAgencyID&SortBy=workphone">Work Phone</a></b></td>
197: <td><b><a href="agencyMaint.cfm?agency_id=#nAgencyID&SortBy=email">Email</a></b></td>
198: <td><b><a href="agencyMaint.cfm?agency_id=#nAgencyID&SortBy=specialty">Specialty</a></b></td>
199: <td colspan="2">&nbsp;</td>
200: </tr>
201: </cfoutput>
202:
203: <cfoutput query="qryAgents">
204: <CFQUERY NAME="qryFindBio" DATASOURCE="#SourceName#">
205: SELECT callingID
206: FROM adData
207: WHERE adData.callingID=#qryAgents.agent_id#
208: AND callingType=1
209: </CFQUERY>
210: <tr bgcolor="#f0f0f0" Mod 2, DE('fffff'), DE('eeeeee'))#>
211: <td>#firstname# #lastname#</td>
212: <td>#workphone#</td>
213: <td>#email#</td>
214: <td>#specialty#</td>
215: <td><a href="agentForm.cfm?agent_id=#agent_id&#cReturnURL#">Edit</a> | <a
href="agentdel.cfm?agent_id=#agent_id&#cReturnURL#">Delete</a></td>
</td>
216: <td>
217: <CFIF qryFindBio.recordCount is 0>
218: <a href="OHTMaint.cfm?agent_id=#agent_id&#cReturnURL#">Create Enhanced Bio</a>
219: <CFELSE>
220: <a href="OHTMaint.cfm?agent_id=#agent_id&#cReturnURL#">Edit Enhanced Bio</a>
221: </CFIF>
222: </td>
223: </tr>
224: </cfoutput>
225: <cfif qryAgents.recordCount is 0>
226: <td colspan="6">#eeeeee"><i>There are no agents assigned to this agency.</i></td>
227: </cfif>
228: <tr bgcolor="#cccc99"><td colspan="6">&nbsp;</td></tr>
229: </table></p>
230: <cfelseif URL.displayPage is "Template">
231: <CFPARAM NAME="URL.TypeID" DEFAULT="-1">
232: <CFPARAM NAME="URL.Action" DEFAULT="View">
233: <cfparam name="URL.param.counter" default="-1"> <!-- If editing, this will have a number -->
234: <cfparam name="URL.ImageType" default="0"> <!-- the image type -->
235:
236: <CFSET nTypeID = URL.agency_id>
237:
238: <cfquery name="qryParameters" datasource="#SourceName#">
239: SELECT agency_param.agency_id, agency_param.param_name, agency_param.param_value, agency_param.param_cntr,
240: param_defs.description, param_defs.label, param_defs.displayOrder, param_defs.restrictions, param_defs.type
241: FROM param_defs, agency_param

```



```

242: WHERE agency_param.agency_id=#ntypeid#
243: AND agency_param.param_id = param_defs.id
244: ORDER BY agency_param.param_cntr,param_defs.displayOrder
245: </cfquery>
246:
247: <!-- Parameter names for the image fields -->
248: <cfquery name="qryParamNames" datasource="#sourceName#">
249: SELECT
250:     DISTINCT id, name, description, label, displayOrder, restrictions, type, selectOptions
251: FROM param_defs
252: WHERE securityLevel=1
253: AND dataGroup = 10 <!-- 10 - Agencies -->
254: ORDER BY displayOrder
255: </cfquery>
256:
257: <!-- qryImageTypes will load the image types for the pull down while
258:      adding or editing a photo -->
259: <cfquery name="qryImageTypes" datasource="#sourceName#">
260: SELECT label,counter,value,agency_id
261: FROM param_allowed
262: WHERE param_allowed.id = 9
263: ORDER BY param_allowed.counter
264: </cfquery>
265:
266:
267: <!-- Delimited lists for various uses -->
268: <cfset listLabels = ValueList(qryParamNames.label)> <!-- "Use Name" -->
269: <cfset listFieldNames = ValueList(qryParamNames.name)> <!-- "CommTitle" -->
270: <cfset listFieldTypes = ValueList(qryParamNames.type)> <!-- TEXT, Field, etc. -->
271: <cfset listFieldOptions = QuotedValueList(qryParamNames.selectOptions,"|")>
272:
273: <cfoutput>
274:
275: <CFSET nTotalCols = qryParamNames.recordCount+2>
276: <CFSET aFieldValues = ArrayNew(1)>
277:
278: <CFIF URL.Action is "View">
279:     <!-- Set default values for the edit fields -->
280:     <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
281:         <CFSET aFieldValues[nIndex] = "">
282:     </CFLOOP>
283:
284: <CFELSEIF URL.Action is "Add">
285:     <CFSET URL.Action = "View">
286: <CFELSEIF URL.Action is "Edit">
287:     <!-- A Paragraph has been selected for editing -->
288:     <CFELSEIF URL.Action is "Deleted">
289:         <!-- Delete the selected image -->
290:         <!-- Set default values for the edit fields -->

```

```

291: <CFLOOP FROM="1" TO="#listlen(listLabels)"# INDEX="nIndex">
292:   <CFSET aFieldValues[nIndex] = "">
293: </CFLOOP>
294:
295:   <CFSET URL.Action = "View">
296:   <CFELSEIF URL.Action is "Updated">
297:     <!-- Set default values for the edit fields -->
298:     <CFLOOP FROM="1" TO="#listlen(listLabels)"# INDEX="nIndex">
299:       <CFSET aFieldValues[nIndex] = "">
300:     </CFLOOP>
301:   <CFSET URL.Action = "View">
302:   </CFIF>
303:
304:
305:   <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
306:     <tr bgcolor="##cccc99"><td colspan="6"><span class="h2"><b>Agency Features</b></span><span><b>Agency Agents</b></span></td></tr>
307:   </table>
308:
309:   <p><table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
310:     <!-- First see if there are any images to display -->
311:     <cfif #qryParameters.recordCount# is 0>
312:       <tr bgcolor="cccccc">
313:         <td><b class="h2">No paragraphs are associated with this community type</b></td>
314:       </td></tr>
315:     <cfelse>
316:       <!-- there are paragraphs, so display the labels first -->
317:       <tr bgcolor="cccccc">
318:         <cfloop from="1" TO="#listlen(listLabels)"# index="nIndex">
319:           <td align="center"><b>#listGetAt(listLabels, nIndex)#</b></td>
320:         </cfloop>
321:       <td><b></td></tr>
322:     </cfif>
323:
324:     <!-- Now for the actual data -->
325:     <CFSET lEditrow = False>
326:     <CFSET cImageName = "">
327:     <CFSET nRow = 0>
328:     <CFSET nOldParamCounter = -1>
329:     <CFSET nParamCounter = -1>
330:     <CFSET nMaxParamCounter = -1>
331:     <CFSET nColumn = 0>
332:
333:     <CFLOOP QUERY="qryParameters">
334:       <CFSET nRow = nRow + 1>
335:       <CFIF qryParameters.param_name IS listGetAt(listFieldNames, 1)>
336:         <CFSET nColumn = 0>
337:         <CFSET nMaxParamCounter = max(nMaxParamCounter, qryParameters.param_cntr)>
338:         <CFSET nParamCounter = qryParameters.param_cntr>

```

```

339: <CFIF nParamCounter is URL.param_counter>
340: <CFSET leditrow = TRUE>
341: <CFELSE>
342: <CFSET leditrow = FALSE>
343: </CFIF>
344: <tr bgcolor="eeeeee">
345: </CFIF>
346: <CFSET nColumn = nColumn + 1>
347: <CFIF leditrow>
348: <CFSET aFieldValues[nColumn] = qryParameters.param_value>
349: </CFIF>
350: <CFIF listGetAt(listFieldNames,nColumn) is "imgType">
351: <td <CFIF leditrow IS true>bgcolor="ffffff"</CFIF> valign="top">
352: <CFIF qryParameters.param_value is "0">
353: Standard Photo
354: <CFIF leditrow is true><CFSET URL.ImageType = "0"></CFIF>
355: <CFELSEIF qryParameters.param_value is "1">
356: Bamboo Image
357: <CFIF leditrow is true><CFSET URL.ImageType = "1"></CFIF>
358: <CFELSEIF qryParameters.param_value is "2">
359: IPIX Image
360: <CFIF leditrow is true><CFSET URL.ImageType = "2"></CFIF>
361: <CFELSE>
362: #qryParameters.param_value#
363: <CFIF leditrow is true><CFSET URL.ImageType = "-1"></CFIF>
364: </CFIF>
365: </td>
366: <CFELSE>
367: <td <CFIF leditrow IS true>bgcolor="ffffff"</CFIF> valign="top">#qryParameters.param_value#</td>
368: </CFIF>
369:
370: <CFIF nColumn is nTotalCols-2> <!-- the last column with info was displayed -->
371: <td <CFIF leditrow is true>bgcolor="ffffff"</CFIF> colspan="2" valign="top">
372: <a
href="agencyMaint.cfm?Action=Edit&agency_id=#URL.agency_id#&param_counter=#qryParameters.param_cntr#&displayPage=Template">E
dit</a><hr>
373: <a
href="agencyDataUpdate.cfm?Action=Delete&agency_id=#URL.agency_id#&param_counter=#qryParameters.param_cntr#">Delete</a></td>
</td>
374: </tr>
375: </tr>
376: <CFSET nColumn = 0>
377: </CFIF>
378: </CFLOOP>
379:
380: </table></p>
381:
382:
383: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
384: <!-- Now allow the user to add or edit an image -->

```

```

385: <tr bgcolor="cccccc">
386: <td colspan="#nTotalCols#">
387: <CFIF #URL.Action# is "Add">
388: <b>Add A Paragraph</b>:
389: <input type="hidden" name="Action" VALUE="Add">
390: <CFELSEIF #URL.Action# is "Edit">
391: <b>Edit Selected Paragraph:</b>
392: <input type="hidden" name="Action" VALUE="Edit">
393: <CFELSEIF #URL.Action# is "View">
394: <b>Add A Paragraph:</b>
395: <input type="hidden" name="Action" VALUE="Add">
396: </CFIF>
397: </td>
398: </tr>
399:
400: <tr>
401: <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
402: <td bgcolor="eeeeee" valign="bottom">
403: <!-- Moved the text area (paragraph) to a row immediately under the other input data --SFF (404900--->
404: <cfif findNocase("Text", #listGetAt(listLabels, nIndex)#) neq 0>
405: <cfset labelId = #nIndex#>
406: <cfelse>
407: <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, nIndex)#</b></font>
408: </cfif>
409: </td>
410: </CFLOOP>
411: </tr>
412:
413: <form name="frmValues" enctype="multipart/form-data" action="agencyDataUpdate.cfm" method="post">
414: <tr valign="top" bgcolor="eeeeee">
415: <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
416: <CFSET cFieldType = ucase(trim(listGetAt(listFieldTypes, nIndex)))>
417: <CFIF cFieldType is "TEXT">
418: <CFIF listGetAt(listFieldNames, nIndex) is "imgType">
419: <td>
420: <CFIF #URL.Action# is "Edit">
421: <CFIF aFieldValues[nIndex] is "0">
422: <I>Standard Photo</I><br>
423: <CFELSEIF aFieldValues[nIndex] is "1">
424: <I>Bamboo Image</I><br>
425: <CFELSEIF aFieldValues[nIndex] is "2">
426: <I>IPIX Image</I><br>
427: <CFELSE>
428: <I>#aFieldValues[nIndex]#</I><br>
429: </CFIF>
430: </CFIF>
431: <SELECT NAME="FIELD#nIndex#">
432: <CFLOOP QUERY="qryImageTypes">
433: <CFIF URL.ImageType is "0" and qryImageTypes.value is "0">

```

```

434: <CFSET lshowOption = true>
435: <CFELSEIF URL.ImageType is not "0" and qryImageTypes.value is not "0">
436: <CFSET lshowOption = true>
437: <CFELSE>
438: <CFSET lshowOption = False>
439: </CFIF>
440: <CFIF lshowOption is true>
441: <OPTION value=#qryImageTypes.value# <CFIF #trim(aFieldValues[nIndex])# is
#trim(qryImageTypes.value)#>SELECTED</CFIF>>#trim(label)#</OPTION>
442: </CFIF>
443: </CFLOOP>
444: </SELECT>
445: <br>
446: <CFIF URL.Action is not "Edit">
447: <!-- If they want to change the image type, they will need to delete the image and reenter it -->
448: <CFIF URL.ImageType is "0">
449: <font face="Verdana, Arial" size="1"><a
href="agencyMaint.cfm?Action=#URL.Action#&agency_id=#URL.agency_id#&imageType=1&param_counter=#URL.param_counter#&displayPag
e=Template">To Add Bamboo or IPIX<br>images, Click Here</a></font>
<CFELSE>
450: <font face="Verdana, Arial" size="1"><a
href="agencyMaint.cfm?Action=#URL.Action#&agency_id=#URL.agency_id#&imageType=0&param_counter=#URL.param_counter#&displayPag
e=Template">To Add a standard photo, Click Here</a></font>
451: </CFIF>
452: </CFIF>
453: </td>
454: <CFELSE>
455: <td>
456: <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
457: </td>
458: </CFIF>
459: <CFELSEIF cFieldType is "FILE">
460: <td>
461: <CFIF #URL.Action# is "Edit">
462: <CFIF URL.ImageType is "0">
463: <I>#getFileFromPath(aFieldValues[nIndex])#</I><br>
464: <CFELSE>
465: #aFieldValues[nIndex]#<br>
466: </CFIF>
467: </CFIF>
468: <CFIF URL.ImageType is "0">
469: <INPUT TYPE="FILE" NAME="Field#nIndex#" SIZE="20">
470: <CFELSE>
471: <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
472: </td>
473: </CFIF>
474: </td>
475: <CFELSEIF cFieldType is "TEXTAREA">
476: <td>
477: <!-- Moved the text area to a row immediately under the other input data --SPE 0404800-->

```

```

478: <cfset textId = #nIndex#>
479: </td>
480: <CFELSEIF cfieldType is "CHECKBOX">
481: <td ALIGN="CENTER">
482: <INPUT TYPE="CHECKBOX" NAME="Field#nIndex#" SIZE="70" <CFIF #aFieldValues[nIndex] is "ON">CHECKED</CFIF>>
483: </td>
484: <CFELSEIF cfieldType is "SELECT">
485: <td>
486: <CFSET listColOptions = replace(listGetAt(listFieldOptions, nIndex, "|"), "", "All")>
487: <CFIF listlen(listColOptions) gt 0>
488: <SELECT NAME="Field#nIndex#">
489: <CFLOOP FROM="1" TO="#listlen(listColOptions)#" INDEX="nListInd">
490: <CFSET coption = listGetAt(listColOptions, nListInd, ",")>
491: <OPTION <CFIF #aFieldValues[nIndex] is #coption#>SELECTED</CFIF>>#coption#
492: </CFLOOP>
493: </SELECT>
494: </CFIF>
495: </td>
496: </CFIF>
497: </CFLOOP>
498: </tr>
499: <tr valign="top" bgcolor="eeeeee">
500: <!-- Moved the text area to a row immediately under the other input data --SFE 0404800-->
501: <td colspan="#listlen(listLabels)#">
502: <cfif isDefined("textId")>
503: <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, labelId)#</b></font><br>
504: <TEXTAREA ROWS="8" COLS="80" WRAP="VIRTUAL" NAME="Field#textId#">#aFieldValues[textId]#</TEXTAREA>
505: </cfif>
506: </td>
507: </tr>
508: <tr bgcolor="eeeeee">
509: <td colspan="#nTotalCols#">
510: <CFIF nMaxParamCounter is -1>
511: <CFSET nMaxParamCounter = 1>
512: <CFELSE>
513: <CFSET nMaxParamCounter = nMaxParamCounter + 1>
514: </CFIF>
515: <CFIF #URL.Action# is "View">
516: <input type="hidden" name="Action" VALUE="ADD">
517: <INPUT TYPE="SUBMIT" VALUE="Add New Paragraph" NAME="btnSubmit">
518:
519: <input type="hidden" name="param_counter" VALUE="#nMaxParamCounter#">
520: <CFELSEIF #URL.Action# is "Edit">
521: <input type="hidden" name="Action" VALUE="EDIT">
522: <INPUT TYPE="SUBMIT" VALUE="Update Paragraph">
523: <INPUT TYPE="RESET" VALUE="Reset Information">
524: <INPUT TYPE="BUTTON" VALUE="Cancel" NAME="btnSubmit"
ONCLICK="location.href='agencyMaint.cfm?agency_id=#URL.agency_id#&displayPage=Template'">
525: <input type="hidden" name="param_counter" VALUE="#URL.Param_Counter#">

```

```
526:         </CFIF>
527:     </td>
528: </tr>
529:
530: <CFSET nImageTypeField = listFindNoCase(listFieldNames,"imgType")>
531:
532: <input type="hidden" name="imageField" VALUE="#nImageTypeField#">
533: <input type="hidden" name="agency_id" VALUE="#URL.agency_id#">
534: <input type="hidden" name="FieldLabels" VALUE="#listLabels#">
535: <input type="hidden" name="FieldTypes" VALUE="#listFieldTypes#">
536: <input type="hidden" name="Field_Names" VALUE="#listFieldNames#">
537: </form>
538: </table></p>
539:
540: </cfoutput>
541: </cfif>
542: </cfif>
543: </body>
544: </html>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfif not isdefined("FORM.agency_id")>
4:   <cflocation url="agencyAdm.cfm" addtoken="no">
5: </cfif>
6:
7: <cfquery name="qryFindAgency" datasource="#sourcename#">
8:   select agency_id, mainImage,headerfilename,footerfilename from agency
9:   where agency.agency_id = #FORM.agency_id#
10: </cfquery>
11:
12:
13: <cfif isdefined("FORM.btnUpdate")>
14:   <cfif FORM.edtAgencyName is "" or FORM.edtAddress is "" or FORM.edtState is "" or
15:     FORM.edtZipcode is "" or FORM.edtPhone is "" or FORM.edtCountry is "" or FORM.edtFax is "">
16:     <cflocation url="agencyMaint.cfm?agency_id=#form.agency_id#&userMessage=All required fields were not filled in"
17:       addtoken="no">
18:   </cfif>
19:   <!-- <cfif form.edtSoldLife is "">-->
20:   <cfset form.edtSoldLife = 10>
21:   <!--</cfif>-->
22:   <!--<cfif form.edtNewLife is "">-->
23:   <cfset form.edtNewLife = 10>
24:   <!--</cfif>-->
25:   <cfset cAgencyName = preserveSingleQuotes(FORM.edtAgencyName)>
26:   <cfset cAddress = preserveSingleQuotes(FORM.edtAddress)>
27:   <cfset cCity = preserveSingleQuotes(FORM.edtCity)>
28:   <cfset cSpecialty = preserveSingleQuotes(FORM.edtSpecialty)>
29:   <cfset cDescription = preserveSingleQuotes(FORM.edtDesc)>
30:   <cfset cURL = trim(FORM.edtURL)>
31:   <cfset cURL = preserveSingleQuotes(cURL)>
32:
33:   <cfif qryFindAgency.recordCount is 0 <!-- Add this agency -->
34:     <cftransaction>
35:       <cfquery name="qryInsert" datasource="#sourcename#">
36:         insert into Agency
37:         (name, address, city, state, zip, country, phone, fax, email, url_name, type, soldLife, newLife, specialty,
38:           distributorID,description,parentAgency)
39:         values ('#cAgencyName#', '#cAddress#', '#cCity#', '#FORM.edtState#',
40:           '#FORM.edtZipcode#', '#FORM.edtCountry#', '#FORM.edtPhone#', '#FORM.edtFax#',
41:           '#FORM.edtEmail#', '#FORM.edtURL#', '#FORM.edtSoldLife#', '#FORM.edtNewLife#', '#cSpecialty#',
42:           '#FORM.edtdistributorID#', '#cDescription#', '#edtMasterAgency#')
43:       </cfquery>
44:       <CFQUERY NAME="qryGetID" DATASOURCE="#SourceName#">
45:         SELECT max(agency_id) as newAgencyID
46:         FROM Agency
47:       </CFQUERY>

```



```
47: <CFSET nAgencyID = qryGetID.newAgencyID>
48:
49:
50: <CFSET cFilePath = #ap_image_path# & "Agency#nAgencyID#\ ">
51:
52: <CFTRY> <!--- Create the directory and catch exception if directory already exists --->
53: <CFDIRECTORY
54:   DIRECTORY="#cFilePath#"
55:   ACTION="CREATE"
56: >
57: <CFCATCH TYPE="ANY">
58: </CFCATCH>
59: </CFTRY>
60:
61: <CFIF len(FORM.edtMainImage) gt 0>
62:   <CFFILE
63:     DESTINATION=#cFilePath#
64:     ACTION="UPLOAD"
65:     NAMECONFLICT="OVERWRITE"
66:     FILEFIELD="edtMainImage">
67:
68:   <CFSET cMainImage = "#FILE.ServerFile#">
69:   <CFELSE>
70:   <CFSET cMainImage="">
71:   </CFIF>
72:
73: <CFIF len(FORM.edtheaderfilename) gt 0>
74:   <CFFILE
75:     DESTINATION=#cFilePath#
76:     ACTION="UPLOAD"
77:     NAMECONFLICT="OVERWRITE"
78:     FILEFIELD="edtheaderfilename">
79:
80:   <CFSET cHeaderImage = "#FILE.ServerFile#">
81:   <CFELSE>
82:   <CFSET cHeaderImage="">
83:   </CFIF>
84:
85: <CFIF len(FORM.edtfooterfilename) gt 0>
86:   <CFFILE
87:     DESTINATION=#cFilePath#
88:     ACTION="UPLOAD"
89:     NAMECONFLICT="OVERWRITE"
90:     FILEFIELD="edtfooterfilename">
91:
92:   <CFSET cFooterImage = "#FILE.ServerFile#">
93:   <CFELSE>
94:   <CFSET cFooterImage="">
95:   </CFIF>
```

```

96:
97:
98:
99:
100:
101:
102:
103:
104:
105:
106:
107:
108:
109:
110:
111:
112:
113:
114:
115:
116:
117:
118:
119:
120:
121:
122:
123:
124:
125:
126:
127:
128:
129:
130:
131:
132:
133:
134:
135:
136:
137:
138:
139:
140:
141:
142:
143:
144:

<cfquery name="qryFinish" datasource="#sourceName#">
  update Agency
  set mainImage='cMainImage#', headerfileName='cHeaderImage#',
  footerfileName='cFooterImage#', dataPath='Agency#nAgencyID#\
  where Agency.agency_id = #nAgencyID#
</cfquery>
</cftransaction>
<cfelse>
  <cftransaction>

    <cfquery name="qryUpdate" datasource="#sourceName#">
      update Agency
      set name='cAgencyName#', address='cAddress#', city='cCity#',
      state='cFORM.edtState#', zip='cFORM.edtZipcode#', country='cFORM.edtCountry#',
      phone='cFORM.edtPhone#', fax='cFORM.edtFax#', email='cFORM.edtEmail#', url_name='cFORM.edtURL#',
      soldLife='cFORM.edtSoldLife#', newLife='cFORM.edtNewLife#',
      description='cDescription#', specialty='cSpecialty#',
      distributorID='cFORM.edtDistributorID#',
      parentAgency='cFORM.edtMasterAgency#
      where agency.agency_id = #FORM.agency_id#
    </cfquery>

    <CFSET nAgencyID = #FORM.agency_id#>

    <CFSET cFilePath = #ap_image_path# & "Agency#nAgencyID#\">

    <CFTRY> <!--- Create the directory and catch exception if directory already exists ---->
      <CFDIRECTORY
        DIRECTORY="#cFilePath#"
        ACTION="CREATE"
      >
      <CFCATCH TYPE="ANY">
        </CFCATCH>
      </CFTRY>

    <CFIF len(FORM.edtMainImage) gt 0 and not isdefined("form.edtDeleteMainImage")>
      <CFFILE
        DESTINATION="#cFilePath#
        ACTION="UPLOAD"
        NAMECONFLICT="OVERWRITE"
        FILEFIELD="edtMainImage">

    <CFSET cMainImage = "#FILE.ServerFile#">
    <cfelseif isdefined("form.edtDeleteMainImage")>
      <cfset cMainImage = "">
    <CFELSE>
      <CFSET cMainImage=qryFindAgency.mainImage>
    </CFIF>

```

```

145:
146: <CFIF len(FORM.edtheadfilename) gt 0 and not isDefined("form.edtDeleteHeaderFilename")>
147:   <CFFILE
148:     DESTINATION=#cFilePath#
149:     ACTION="UPLOAD"
150:     NAMECONFLICT="OVERWRITE"
151:     FILEFIELD="edtheadfilename">
152:
153:   <CFSET cHeaderImage = "#FILE.ServerFile#">
154:   <cfelseif isDefined("form.edtDeleteHeaderFilename")>
155:     <cfset cHeaderImage = "">
156:   <CFELSE>
157:     <CFSET cHeaderImage=qryFindAgency.headerfilename>
158:   </CFIF>
159:
160: <CFIF len(FORM.edtfootfilename) gt 0 and not isDefined("form.edtDeleteFooterFilename")>
161:   <CFFILE
162:     DESTINATION=#cFilePath#
163:     ACTION="UPLOAD"
164:     NAMECONFLICT="OVERWRITE"
165:     FILEFIELD="edtfootfilename">
166:
167:   <CFSET cFooterImage = "#FILE.ServerFile#">
168:   <cfelseif isDefined("form.edtDeleteFooterFilename")>
169:     <cfset cFooterImage = "">
170:   <CFELSE>
171:     <CFSET cFooterImage=qryFindAgency.footerfilename>
172:   </CFIF>
173:
174:
175:
176: <cfquery name="qryFinish" datasource="#sourceName#">
177:   update Agency
178:   set mainImage='#cMainImage#', dataPath='Agency#nAgencyID#\',
179:   headerfilename='#cHeaderImage#', footerfilename='#cFooterImage#',
180:   where Agency.agency_id = #nAgencyID#
181: </cfquery>
182: </cftransaction>
183: </cfif>
184: <cflocation url="agencyMaint.cfm?agency_id=#nAgencyID#" addtoken="no">
185:
186: <cfelseif isDefined("FORM.btnDelete")>
187:
188:   <cfquery name="qryDelete" datasource="#sourcename#">
189:     delete from agency
190:     where agency.agency_id = #FORM.agency_id#
191:     and agency.agency_id <> #ap_agency_number#
192:   </cfquery>
193:

```

```
194:      <cflocation url="agencyAdm.cfm" addtoken="#H01#" />
195:    </cfif>
```

```
1: <CFQUERY DATASOURCE="#sourceName#" NAME="Agent">
2: SELECT agents.firstName,
3: agents.lastName,
4: agents.agent_id,
5: agents.lastName + ' ' + agents.firstName AS fullName
6: FROM agents, agency
7: where agents.agent_id=agency.agent_id
8: and agency.distributorID = #ap_distributorID#
9: ORDER BY agents.lastName, agents.agent_id
10: </CFQUERY>
11: <HTML>
12: <HEAD>
13: <TITLE>Agent Photos</TITLE>
14: </HEAD>
15: <body bgcolor="white">
16: <CFINCLUDE TEMPLATE="admlinks.cfm">
17: <div align="center"><H1><font face="Verdana, Arial" color="Teal">Agent Photos Administration</font></H1>
18: <font face="Verdana, Arial" size="4">Click on Agent's Name or ID Number to Add An Agent Photo</font><p>
19: <TABLE BORDER>
20: <TR>
21: <TH bgcolor="#FFCC33">
22: <font face="Verdana, Arial, sans-serif">Agent Name</font></TH>
23: <TH bgcolor="#FFCC33">
24: <font face="Verdana, Arial, sans-serif">ID Number</font></TH>
25: </TR>
26: <CFOUTPUT QUERY="Agent">
27: <TR>
28: <td><A
29: HREF="agent_pics.cfm?agent_id=#agent_id#">#fullName#</A></td>
30: <td><div align="center"><A
31: HREF="agent_pics.cfm?agent_id=#agent_id#">#NumberFormat(agent_id,'0000')#</A></div></td>
32: </TR></CFOUTPUT>
33:
34: </TABLE></div><p>
35:
36: </BODY>
37: </HTML>
38:
39:
40:
41:
42:
```

```
1: <cffile destination="#ap_image_path#"
2: action="UPLOAD"
3: nameconflict="OVERWRITE"
4: filefield="PhotoFile"
5: accept="image/gif, image/pjpeg, image/jpeg">
6:
7: <cftransaction>
8:   <cfquery name="image_name" datasource="#sourceName#">
9:     UPDATE agents
10:    SET image_name = 'images\#FILE.ServerFile#'
11:    WHERE agent_id=#FORM.agent_id#
12:  </cfquery>
13: </cftransaction>
14:
15: <cflocation url="agentadm.cfm">
```

```
1: <cfquery name="Agent" datasource="#sourceName#">
2: SELECT
3: agents.agent_id,
4: agents.firstName,
5: agents.lastName,
6: agents.agency_id,
7: agents.lastname + ', ' + agents.firstname AS fullName
8: FROM agents
9: where agent_id = #URL.agent_id#
10: and agents.distributorID = #ap_distributorID#
11: </cfquery>
12:
13: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
14:
15: <html>
16: <head>
17: <cfoutput>
18: <title>#ap_backofficeName# Backoffice</title>
19: </cfoutput>
20: <link rel="stylesheet" href="style1.css" type="text/css">
21: </head>
22:
23: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
24:
25: <p><cfinclude template="header.cfm"></p>
26:
27: <form action="agent_pickup.cfm" enctype="multipart/form-data" method="post">
28: <cfoutput query="Agent">
29: <input type="hidden" name="agent_id" value=#Agent.agent_id#>
30:
31: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="75%">
32: <tr bgcolor="cccc99"><td colspan="2"><b>Agent Photo Form</b></span> Agent: #Agent.fullName#</td></tr>
33: <tr><td>Agent Photo to Upload:</td><td><input name="PhotoFile" size="25" type="file"> <input type="submit"
value="Upload"></td></tr>
34: </table></p>
35: </cfoutput>
36: </form>
37:
38: </body>
39: </html>
```

```

1: <cfinclude template="include\security.cfm">
2:
3: <!---
4: <CFQUERY DATASOURCE="#sourceName#" NAME="qAgents">
5: SELECT
6:     first_name,
7:     last_name,
8:     agent_id
9: FROM agents, agency
10: WHERE (agents.agent_id = agency.agent_id or agents.agent_id = 0)
11: and agency.distributorID = #ap_distributorID#
12: and '16-' + convert(varchar,agents.agent_id) < '1' in (#listQualify(client.lstSecurity,"")#)
13: ORDER BY last_name
14: </CFQUERY>
15: --->
16:
17: <cf
18:
19: <CFQUERY DATASOURCE="#sourceName#" NAME="qAgents">
20: SELECT
21:     first_name,
22:     last_name,
23:     agent_id
24: FROM agents
25: WHERE agents.distributorID = #ap_distributorID#
26: and '16-' + convert(varchar,agents.agent_id) + '|' in (#listQualify(client.lstSecurity,"")#)
27: ORDER BY last_name
28: </CFQUERY>
29:
30: <!--- WHERE #ap_agency# --->
31:
32:
33: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
34:
35: <html>
36: <head>
37: <cfoutput>
38: <title>#ap_backofficeName# Backoffice</title>
39: </cfoutput>
40: <link rel="stylesheet" href="style1.css" type="text/css">
41: <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
42: </head>
43:
44: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
45:
46: <p><cfinclude template="header.cfm"></p>
47:
48: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
49: <tr bgcolor="#cccc99"><td colspan="3"><b>Agents</b></td></tr></table></p>

```



```
an Agent</a></td></tr>
<tr bgcolor="#cccccc"><td><b>Name</b></td></tr>
<td><b>Agent ID</b></td>
<td>&nbsp;</td>
</tr>

<cfoutput query="qAgents">
<CFQUERY NAME="qryFindBio" DATASOURCE="#SourceName#">
  SELECT callingID
  FROM adData
  WHERE adData.callingID=#agent_id#
  AND callingType=1
</CFQUERY>
<tr bgcolor="#If(CurrentRow Mod 2, DE('ffffff'), DE('eeeeee'))">
<td>#firstname# #lastname#</td>
<td>#agent_id#</td>
<td><a href="#agentForm.cfm?agent_id=#agent_id#">Edit</a> | <a href="#agentdel.cfm?agent_id=#agent_id#">Delete</a> |
  <CFIF qryFindBio.recordCount is 0>
    <a href="#OHTMaint.cfm?agent_id=#agent_id#">Create Enhanced Bio</a>
  <CFELSE>
    <a href="#OHTMaint.cfm?agent_id=#agent_id#">Edit Enhanced Bio</a>
  </CFIF>
</td>
</tr>
</cfoutput>
</table></p>
</body>
</html>
```

```
1: <CFPARAM NAME="URL.CallingType" DEFAULT="1">
2:
3: <CFIF URL.CallingType is 0>
4:   <CFSET nCallingType = 0>
5: <CFELSEIF URL.CallingType is 1>
6:   <CFSET nCallingType = 1>
7: <CFELSE>
8:   <CFLOCATION URL="AgentBioAdm.cfm" ADDTOKEN="NO">
9: </CFIF>
10:
11: <cfoutput>
12: <CFIF nCallingType is 0>
13:   <cfparam name="URL.SortBy" default="callingID">
14:   <cfquery name="qryAds" datasource="#SourceName#">
15:     SELECT callingID, startdate, stopdate
16:     FROM AdData
17:     WHERE AdData.CallingType=#URL.CallingType#
18:     ORDER BY #URL.SortBy#
19:   </cfquery>
20: <CFELSEIF nCallingType is 1>
21:   <cfparam name="URL.SortBy" default="LastName">
22:   <cfquery name="qryAds" datasource="#SourceName#">
23:     SELECT adData.callingID, adData.startdate, adData.stopdate, agents.name, agents.firstname, agents.lastname
24:     FROM AdData, Agents
25:     WHERE AdData.CallingType=#URL.CallingType#
26:     AND AdData.callingID = Agents.agent_id
27:     and '[6-' + convert(varchar,adData.callingid) + '|' in (#listQualify(client.lstSecurity,"")#)
28:     ORDER BY #URL.SortBy#
29:   </cfquery>
30: </CFIF>
31:
32:
33: </cfoutput>
34:
35: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
36:
37: <html>
38: <head>
39:   <cfoutput>
40:     <title>#ap_backofficeName# Backoffice</title>
41:   </cfoutput>
42:   <link rel="stylesheet" href="style1.css" type="text/css">
43: </head>
44:
45: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
46:
47: <p><cfinclude template="header.cfm"></p>
48:
49: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
```

```
50: <tr bgcolor="#cccc99">
51: <CFIF nCallingType is 0>
52: <td colspan="4"><b class="h2">Online Home Tours</b></td>
53: <CFELSEIF nCallingType is 1>
54: <td colspan="4"><b class="h2">Online Agent Bios</b></td>
55: </CFIF>
56: </tr>
57:
58: <tr bgcolor="#cccccc">
59: <CFIF nCallingType is 0>
60: <td>Sort by <a href="ohtadm.cfm?SortBy=callingID"><b>Property ID</b></a></td>
61: <td>Sort by <a href="ohtadm.cfm?SortBy=startDate"><b>Start Date</b></a></td>
62: <td>Sort by <a href="ohtadm.cfm?SortBy=stopDate"><b>End Date</b></a></td>
63: <td><b>nbsp;</td>
64: <CFELSEIF nCallingType is 1>
65: <td>Sort by <a href="AgentBioadm.cfm?CallingType=1&SortBy=lastname"><b>Agent Name</b></a></td>
66: <td>Sort by <a href="AgentBioadm.cfm?CallingType=1&SortBy=startDate"><b>Start Date</b></a></td>
67: <td>Sort by <a href="AgentBioadm.cfm?CallingType=1&SortBy=stopDate"><b>End Date</b></a></td>
68: <td><b>nbsp;</td>
69: </CFIF>
70: </tr>
71:
72: <cfset lColor = True>
73: <cfloop query="qryAds">
74: <cfset lColor = not lColor>
75: <tr <cfif lColor is TRUE>bgcolor="eeeeee"</cfif>>
76: <cfoutput>
77: <CFIF nCallingType is 0>
78: <td>#qryAds.callingID#</td>
79: <td>#dateFormat(qryAds.startDate,"mm/dd/yyyy")#</td>
80: <td>#dateFormat(qryAds.stopDate,"mm/dd/yyyy")#</td>
81: <td><a href="OHTMaint.cfm?prop_id=#qryAds.callingID#">Edit</a></td>
82: <CFELSEIF nCallingType is 1>
83: <td>#qryAds.lastname#, #qryAds.firstname#</td>
84: <td>#dateFormat(qryAds.startDate,"mm/dd/yyyy")#</td>
85: <td>#dateFormat(qryAds.stopDate,"mm/dd/yyyy")#</td>
86: <td><a href="OHTMaint.cfm?Agent_id=#qryAds.callingID#">Edit</a></td>
87: </CFIF>
88: </cfoutput>
89: </tr>
90: </cfloop>
91: </table></p>
92:
93: </body>
94: </html>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2: <!-- agentdel.cfm -->
3: <!-- Change Tracker Yakalo, Inc. Beta -->
4: <!-- Name Date Description -->
5: <!-- SPE * 02/10/00* Added a check for properties listed by agent. If there are any then reassign to another agent and then prompt to confirm deletion. Then update table -->
6: <!-- * * * -->
7: <!-- * * * -->
8: <!-- * * * -->
9: <!-- * * * -->
10: <!-- * * * -->
11: <!-- * * * -->
12: <!-- * * * -->
13:
14: <cfif isDefined("URL.ReturnURL") and isDefined("URL.ReturnAgency_id") >
15: <cfset cReturnURL="?ReturnURL=#URL.ReturnURL#&ReturnAgency_id=#URL.ReturnAgency_ID#&displayPage=Agents">
16: <cfelse>
17: <cfset cReturnURL="">
18: </cfif>
19:
20:
21: <cfif IsDefined("agent_id") IS "No">
22: <h2><font face="Verdana, Arial" color="Red">Error! No Agent ID was specified!</font></h2>
23: <cflocation url="agentForm.cfm">
24: <cfelse>
25: <cfif IsDefined("updateAgent") is "NO">
26: <cfset updateAgent = "NO">
27: </cfif>
28: <cfif IsDefined("delConfirmed") is "NO">
29: <cfset delConfirmed = "NO">
30: </cfif>
31: <cfset delAgent = #agent_id#>
32: <!-- Check to see if agent has any properties -->
33: <cfquery datasource="#sourceName#" name="checkProperty">
34: SELECT prop_id, agent_id from prop_main, agency
35: where (prop_main.agency_id=agency.agency_id or prop_main.agency_id=0)
36: and agency.distributorID = #ap_distributorID#
37: AND agent_id = #agent_id#
38: </cfquery>
39: <cfif checkProperty.RecordCount gt 0 and #updateAgent# is "NO">
40: <!-- If agent has properties then find a display a list of agents in this office to take over those properties -->
41: The agent has <cfoutput>#checkProperty.RecordCount#</cfoutput> properties that are still listed in their name. <br><br>
42: <cfquery name="qAgentsList" datasource="#sourceName#">
43: SELECT lastName+', ' + firstName AS wholeName, agent_id
44: FROM agents,agency
45: where agents.agency_id=agency.agency_id
46: and agency.distributorID = #ap_distributorID#
47: AND agent_id <> #agent_id#
48: </cfquery>
49: <cfoutput>

```

```

50: <cfm action="agentdel.cfm#cReturnURL#" name="firmAgentId">select * replace agent:
51: <cfselect display="wholeName" value="agent_id" query="qAgentsList" name="selAgentId">
52: </cfselect>
53: <input type="hidden" name="updateAgent" value="YES">
54: <input type="hidden" value="#delAgent#" name="agent_id">
55: <INPUT TYPE="submit" VALUE="Delete">
56: <INPUT TYPE="reset" VALUE="Clear">
57: </cform>
58: </cfoutput>
59: <cfelse>
60: <cfif delConfirmed is "NO">
61: <!-- Confirm deletion -->
62: <cfquery name="qDeldAgent" datasource="#sourcename#">
63: SELECT lastName, firstName, agent_id
64: FROM agents
65: WHERE agent_id = #agent_id#
66: </cfquery>
67: </cfoutput>
68: <form action="agentdel.cfm#cReturnURL#" method="post">
69: <font face="Verdana, Arial" size="1">Did you really want to delete #qDeldAgent.firstName# #qDeldAgent.lastName#
    from the database?</font>
70: <input type="hidden" name="delConfirmed" value="YES">
71: <input type="hidden" name="agent_id" value="#qDeldAgent.agent_id#">
72: <cfif IsDefined("selAgentId")>
73: <input type="Hidden" name="selAgentId" value="#selAgentId#">
74: </cfif>
75: <input type="Hidden" name="updateAgent" value="YES">
76: <input type="submit" value="Delete">
77: </form>
78: </cfoutput>
79: <cfelse>
80: <!-- Update properties with new listing agent -->
81: <cfif checkProperty.RecordCount gt 0 and #updateAgent# is "YES">
82: <!--
83: <cfquery name="qUpdateAgent" datasource="#sourcename#">
84: UPDATE prop_main,Agency
85: SET agent_id = #selAgentId#
86: where agents.agency_id=agency.agency_id
87: and agency.distributorID = #ap_distributorID#
88: AND agent_id = #agent_id#
89: </cfquery>
90: <!-->
91: <cfquery name="qUpdateAgent" datasource="#sourcename#">
92: UPDATE prop_main
93: SET prop_main.agent_id = #selAgentId#
94: where prop_main.distributorID = #ap_distributorID#
95: AND prop_main.agent_id = #agent_id#
96: </cfquery>
97:

```

```
98: </cfif>
99: <!--- Finally delete agent --->
100: <cfquery datasource="#sourceName#">
101: delete from agents
102: where agent_id = #agent_id#
103: </cfquery>
104: <cfif isDefined("URL.ReturnURL") and isDefined("URL.ReturnAgency_id")>
105: <cfset cReturnURL="#URL.ReturnURL?agency_id=#URL.ReturnAgency_ID#&displayPage=Agents">
106: <cfelse>
107: <cfset cReturnURL="agentadm.cfm">
108: </cfif>
109:
110: <cfoutput><cflocation url="#cReturnURL#" addtoken="no"></cfoutput>
111: </cfif>
112: </cfif>
113: </cfif>
```

----->

```
1: <cfparam name="URL.agency_id" default="">
2: <cfparam name="URL.userName" default="">
3:
4: <cfif IsDefined("agent_id")>
5:   <cfset NewRecord="No">
6: <cfelse>
7:   <cfset NewRecord="Yes">
8: </cfif>
9:
10: <cfif NewRecord>
11:   <cfset PageTitle = "Add an Agent">
12:   <cfset ButtonText = "Add Agent">
13:   <cfset name = "?">
14:   <cfif isDefined("URL.ReturnAgency_id")>
15:     <cfset agency_id="#URL.ReturnAgency_ID#">
16:   <cfelse>
17:     <cfset agency_id = "#ap_agency_number#">
18:   </cfif>
19:   <cfset agent_id="">
20:   <cfset title="">
21:   <!-- <cfset description=""> -->
22:   <cfset email="">
23:   <cfset workphone="">
24:   <cfset homophone="">
25:   <cfset cellphone="">
26:   <cfset faxphone="">
27:   <cfset extension="">
28:   <cfset pub_home="Y">
29:   <cfset otherphone="">
30:   <cfset bio="">
31:   <cfset specialty="">
32:   <cfset lastname="">
33:   <cfset firstname="">
34:   <cfset agencyEmail="">
35:   <cfset website="">
36:   <cfset communities="">
37: <cfelse>
38:   <cfquery datasource="#sourceName#" name="agents">
39:     SELECT
40:       agents.title,
41:       <!-- agents.description, -->
42:       agents.agency_id,
43:       agent_id,
44:       agents.email,
45:       agents.workphone,
46:       agents.homophone,
47:       agents.cellphone,
48:       agents.faxphone,
49:       agents.extension,
```

```

<!-- Agent Form -->
<!-- Agent Form -->

```

```

50: agents.pub_home,
51: agents.otherphone,
52: agents.bio,
53: agents.image_name,
54: agents.specialty,
55: agents.lastname,
56: agents.firstname,
57: agents.agencyEmail,
58: agents.website,
59: agents.communities,
60: agents.firstname + ' ' + agents.lastname as fullname,
61: agents.distributorID
62: FROM agents
63: where agent_id = #agent_id#
64: and agents.distributorID = #ap_distributorID#
65: <!-- WHERE #ap_agency# AND agent_id = #agent_id# -->
66: </cfquery>
67: <cfset PageTitle = "Update Agent Profile - " & Agents.fullname>
68: <cfset ButtonText = "Update Agent">
69: <cfset agent_id = Trim(Agents.agent_id)>
70: <cfset agent_id = Trim(Agents.agent_id)>
71: <cfset title = Trim(Agents.title)>
72: <!-- <cfset description = Trim(Agents.description) -->
73: <cfset email = Trim(Agents.email)>
74: <cfset workphone = Trim(Agents.workphone)>
75: <cfset homephone = Trim(Agents.homephone)>
76: <cfset cellphone = Trim(Agents.cellphone)>
77: <cfset faxphone = Trim(Agents.faxphone)>
78: <cfset extension = Trim(Agents.extension)>
79: <cfset pub_home = Trim(Agents.pub_home)>
80: <cfset otherphone = Trim(Agents.otherphone)>
81: <cfset bio = Trim(Agents.bio)>
82: <cfset image_name = Trim(Agents.image_name)>
83: <cfset specialty = Trim(Agents.specialty)>
84: <cfset lastname = Trim(Agents.lastname)>
85: <cfset firstname = Trim(Agents.firstname)>
86: <cfset agencyEmail = Trim(Agents.agencyEmail)>
87: <cfset website = trim(agents.website)>
88: <cfset distributorID = #ap_distributorID#>
89: <cfset communities = trim(agents.communities)>
90:
91: </cfif>
92:
93: <cfquery name="qryAgencies" datasource="#sourceName#">
94: select agency_id as agencyID, name
95: from agency
96: where agency.distributorID = #ap_distributorID#
97: and '14-' + convert(varchar,agency.agency_id) + '|' in (#listQualify(client.lstSecurity,"")#)
98:

```

<!-- Added 5/8/00 SPE -->



```

99: </cfquery>
100:
101: <cfset lstDisplayNames="">
102: <cfset lstDisplayValues="">
103: <!-- Communities -->
104: <cfquery name="qryGetCommunities" datasource="#sourcename#">
105:   select communityID,name from communities
106:   where communities.distributorID = #ap_distributorID#
107: </cfquery>
108: <cfloop query="qryGetCommunities">
109:   <cfset lstDisplayNames=listappend(lstDisplayNames,"#qryGetCommunities.name#")>
110:   <cfset lstDisplayValues=listappend(lstDisplayValues,"2|#qryGetCommunities.communityID#">
111:   <cfset lstDisplayValues=listQualify(lstDisplayValues,"**")>
112: </cfloop>
113: <cfset lstDisplayValues=listQualify(lstDisplayValues,"**")>
114:
115:
116: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
117:
118: <html>
119: <head>
120:   <cfoutput>
121:     <title>#ap_backofficeName# Backoffice</title>
122:   </cfoutput>
123:   <link rel="stylesheet" href="style1.css" type="text/css">
124:   <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
125: </head>
126:
127: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
128:
129: <p><cfinclude template="header.cfm"></p>
130:
131: <cfoutput>
132: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
133:   <tr bgcolor="cccc99"><td colspan="2"><b>#pageTitle#</b><b>#pageTitle#</b><b>#pageTitle#</b></td></tr>
134:   <tr><td colspan="2"><div>
135:     <div>
136:       <div>
137:         <div>
138:           <div>
139:             <div>
140:               <div>
141:                 <div>
142:                   <div>
143:                     <div>
144:                       <div>
145:                         <div>
146:                           <div>

```

```

147: <cfform action="agentPost.cfm#cReturnURL#">
148: <!--- <cfform action="showform.cfm#cReturnURL#"> ---
149: <cfif NewRecord IS "No">
150:   <input type="hidden" name="agent_id" value="#agent_id#">
151: </cfif>
152: <!--- <input type="hidden" name="agency_id" value="#ap_agency_number#"> ---
153: <!--- <input type="hidden" name="name" value="?"> ---
154: <input type="hidden" name="distributorID" value="#ap_distributorID#"> <!--- Added 5/8/00 SPE ---
155: <tr bgcolor="eeeeee">
156:   <td><cfinput type="text" name="first_name" size="20" maxlength="30" value="#first_name#" required="yes" message="Please
157:   enter a first name.">
158:   </td>
159:   <input type="hidden" name="first_name_required" value="Please enter a first name.">
160:   </td>
161: </tr>
162: <tr bgcolor="eeeeee">
163:   <td><cfinput type="text" name="last_name" size="20" maxlength="30" value="#last_name#" required="yes" message="Please
164:   enter a last name.">
165:   <input type="hidden" name="last_name_required" value="Please enter a last name.">
166:   </td>
167:   </tr>
168: <tr bgcolor="eeeeee">
169:   <td><cfinput type="text" name="title" size="20" maxlength="50" value="#title#" required="yes" message="Please enter a
170:   title.">
171:   <input type="hidden" name="title_required" value="Please enter a title.">
172:   </td>
173:   </tr>
174:   <tr>
175:     <td>Specialty:</td>
176:     <td><cfinput type="text" name="specialty" size="20" maxlength="64" value="#specialty#"></td>
177:   </tr>
178:   <!--- <tr bgcolor="eeeeee">
179:     <td><cfinput type="text" name="description" size="50" maxlength="100" value="#description#" required="yes" message="Please
180:     enter a short description.">
181:     <input type="hidden" name="description_required" value="Please enter a short description.">
182:   </tr> ---
183:   <tr bgcolor="eeeeee">
184:     <td>E-Mail:</td>
185:     <td><cfinput type="text" name="email" size="20" maxlength="138" value="#email#" required="yes" message="Please enter an
186:     email address.">
187:     <input type="hidden" name="email_required" value="Please enter an email address.">
188:   </td>
189:   </tr>
190:   <tr>

```

```

191:         <td>Web Site:</td>
192:         <td><input type="text" name="website" size="20" maxlength="120" value="#website#"></td>
193:     </tr>
194: <tr>
195:     <td>Agency E-Mail:</td>
196:     <td><input type="text" name="agencyEmail" size="20" maxlength="138" value="#agencyEmail#"></td>
197: </tr>
198: <tr bgcolor="#eeeeee">
199:     <td>Work Phone:</td>
200:     <td><input type="text" name="workphone" size="20" maxlength="15" value="#trim(workphone)#" required="yes"
201:     message="Please enter a work phone number in the format #####-#####" validate="telephone">
202:     <input type="hidden" name="workphone_required" value="Please enter a work phone number in the format
203:     #####-#####">
204:     </td>
205: <td>Extension:</td>
206:     <td><input type="text" name="extension" size="20" maxlength="7" value="#extension#"></td>
207: </tr>
208: <tr>
209:     <td>Home Phone:</td>
210:     <td><input type="text" name="homephone" size="20" maxlength="15" value="#homephone#"> Publish? <input type="radio"
211:     name="pub_home" title="Yes" value="Y"><cfif #pub_home# is "Y"> checked</cfif> Yes <input type="radio" name="pub_home"
212:     title="No" value="N"><cfif #pub_home# is "N"> checked</cfif> No</td>
213: </tr>
214: <td>Cell Phone:</td>
215:     <td><input type="text" name="cellphone" size="20" maxlength="15" value="#cellphone#"></td>
216: </tr>
217: <tr bgcolor="#eeeeee">
218:     <td>Fax:</td>
219:     <td><input type="text" name="faxphone" size="20" maxlength="15" value="#trim(faxphone)#" required="yes"
220:     message="Please enter a fax number in the format #####-#####" validate="telephone">
221:     <input type="hidden" name="faxphone_required" value="Please enter a fax number in the format #####-#####">
222:     </td>
223: <td>Other Phone:</td>
224:     <td><input type="text" name="otherphone" size="20" maxlength="15" value="#otherphone#"></td>
225: </tr>
226: <tr>
227:     <td>Agency:</td>
228:     <td>
229:         <select name="agency_id">
230:             <option value="0"><cfif agency_id is 0> selected</cfif><-None-
231:             <cfloop query="qryAgencies">
232:                 <option value="#qryAgencies.agencyID#"><cfif agency_id is #qryAgencies.agencyID#>
233:                     selected</cfif>#qryAgencies.name#

```

```
234:         </cfloop>
235:     </select>
236: </td>
237: </tr>
238:
239: <tr>
240:     <td>Communities:</td>
241:     <td>
242:         <input type="hidden" name="communities" value=""> <!-- in case nothing is selected -->
243:         <select name="communities" size="5" multiple>
244:             <cfloop from="1" to="#listlen(listDisplayNames)#" index="nIndex">
245:                 <option value="#listGetAt(listDisplayValues,nIndex)#"><cfif
listFind(#communities#,listGetAt(listDisplayValues,nIndex)#) gt 0> selected</cfif>>#listGetAt(listDisplayNames,nIndex)#
246:             </cfloop>
247:         </select>
248:     </td>
249: </tr>
250:
251: <tr>
252:     <td valign="top">Bio:</td>
253:     <td><textarea name="bio" rows="5" cols="50" wrap="virtual" title="">#bio#</textarea></td>
254: </tr>
255: <tr bgcolor="cccc99">
256:     <td colspan="2"><input type="submit" value="#ButtonText#"> <input type="reset" value="Clear"></td></tr>
257: </cfloop>
258: </table></p>
259: </cfoutput>
260:
261: </body>
262: </html>
```

```

1: <cfinclude template="include\security.cfm">
2:
3: <cfquery datasource="#sourceName#" name="Agent2">
4:   SELECT image_name, agent_id, lastName+, 'firstName as fullName
5:   FROM agents<cfif isDefined("URL.ReturnAgency_id")>,agency</cfif>
6:   WHERE agents.distributorID = #ap_distributorID#
7:   and '16-' + convert(varchar,agents.agent_id) + '|' in (#listQualify(client.lstSecurity,'"")#)
8:   <cfif isDefined("URL.ReturnAgency_id")> <!-- Filter for agency selected -->
9:     and agents.agent_id = agency.agent_id
10:    and agents.agent_id=#URL.ReturnAgency_id#
11:   </cfif>
12: ORDER BY fullName
13: <!-- ORDER BY agent_id DESC -->
14: </cfquery>
15:
16: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
17:
18: <html>
19: <head>
20:   <cfoutput>
21:     <title>#ap_backofficeName# Backoffice</title>
22:   </cfoutput>
23:   <link rel="stylesheet" href="style1.css" type="text/css">
24: </head>
25:
26: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
27:
28: <p><cfinclude template="header.cfm"></p>
29:
30: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
31:   <tr bgcolor="#cccc99"><td width="50%" valign="top"><b>Agent </b></span><cfoutput>#URL.name#
32:   #URL.Operation#</cfoutput></td>
33:     <td align="right" width="50%">To add or replace agent's photo, select agent below. Otherwise, <a
34:     href="agentadm.cfm">return to agents</a>
35:     <cfif isDefined("URL.ReturnURL") and isDefined("URL.ReturnAgency_id")>
36:       <cfquery name="qryFindAgency" datasource="#sourceName#">
37:         select name
38:         from agency
39:         where agency.agent_id=#URL.ReturnAgency_id#
40:       </cfquery>
41:     <cfset cReturnURL="#URL.ReturnURL#?agency_id=#URL.ReturnAgency_ID#&displayPage=Agents">
42:     <cfoutput>
43:       or <a href="#cReturnURL#">return to #qryFindAgency.name# agency</a>
44:     </cfoutput>
45:   </td></tr>
46:   <tr bgcolor="#cccccc"><td><b>Name</b></td><b>Agent ID</b></td></tr>
47:   <cfoutput query="Agent2">

```

```
48: <tr><td><a href="agent_pics.cfm?agent_id=#agent_id#">#agent2's Full Name</a></td>
49: <td><a href="agent_pics.cfm?agent_id=#agent_id#">#NumberFormat(agent_id,'0000')#</a></td>
50: </tr></cfoutput>
51: </table></p>
52: </body>
53: </html>
54:
```

```

1: <cfinclude template="include\security.cfm">
2:
3: <cfif IsDefined("agent_id")>
4:   <cfset Operation="Updated">
5:   <cfupdate datasource="#sourceName#" tablename="agents">
6:   <cfelseif IsDefined('Form.lastName') and IsDefined('Form.firstName') and IsDefined('Form.workphone') and
   IsDefined('Form.title')>
7:     <cfset Operation="Inserted">
8:     <cfset agent_id="0">
9:     <cfinsert datasource="#sourceName#" tablename="agents">
10:   <cfelse>
11:     <cflocation url="agentForm.cfm?usermessage=all required fields were not included" addtoken="no">
12:   <!--- <cflocation url="errPage.cfm?error=agt102">--->
13:   </cfif>
14:
15: <cfif IsDefined("URL.ReturnURL") and IsDefined("URL.ReturnAgency_id")>
16:   <cfset cReturnURL="#URL.ReturnURL#"&ReturnAgency_id=#URL.ReturnAgency_ID#">
17: <cfelse>
18:   <cfset cReturnURL = "">
19: </cfif>
20:
21: <cfset cURL = "agentImages.cfm?Operation=#Operation#&Name=#form.firstName#%20#form.lastName#cReturnURL#">
22: <!--- <cfset cURL = URLEncodeFormat(cURL) > --->
23: <cflocation url="#cURL#" addtoken="no">
24:
25: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
26:
27: <html>
28: <head>
29:   <cfoutput>
30:     <title>#ap_backofficeName# Backoffice</title>
31:   </cfoutput>
32:   <link rel="stylesheet" href="style1.css" type="text/css">
33: </head>
34:
35: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
36: </body>
37: </html>

```

```
1: <cfif not isdefined("attributes.fuseaction")>
2:   <cf_formURL2attributes>
3: </cfif>
4:
5: <cfparam name="attributes.fuseaction" default="">
6: <cfparam name="attributes.calendarDSN" default="dpo">
7: <cfparam name="attributes.FuseBox_ID" default="999">
8:
9: <!--- Logic Related Global Parameters -->
10: <cfparam name="gYes" default="1">
11: <cfparam name="gNo" default="0">
12:
```





```
50: <td>sort by <a href="commAdm.cfm?sortBy=Region"><b>Region</b></a></td>
51: <td>sort by <a href="commAdm.cfm?sortBy=startDate"><b>start Date</b></a></td>
52: <td>sort by <a href="commAdm.cfm?sortBy=stopDate"><b>End Date</b></a></td>
53: <td>&nbsp;</td>
54: </tr>
55:
56:
57: <CFIF qryCommunities.recordCount is 0>
58: <TR><TD COLSPAN="5"><I>There are no Online Communities defined</I></TD></TR>
59: </CFIF>
60: <cfset lColor = True>
61: <cfloop query="qryCommunities">
62: <cfset lColor = not lColor>
63: <tr <cfif lColor is TRUE>bgcolor="eeeeee"</cfif>>
64: <cfoutput>
65: <td>#qryCommunities.Name#</td>
66: <td>#qryCommunities.Region#</td>
67: <td>#dateFormat(qryCommunities.startDate,"mm/dd/yyyy")#</td>
68: <td>#dateFormat(qryCommunities.stopDate,"mm/dd/yyyy")#</td>
69: <td><a href="CommMaint.cfm?communityID=#qryCommunities.communityID#">Edit</a></td>
70: </cfoutput>
71: </tr>
72: </cfloop>
73: </table></p>
74:
75: </body>
76: </html>
```

```

1: <CFPARAM NAME="ACTION" DEFAULT="Cancel">
2:
3: <CFIF isDefined("communityID")>
4:   <cfset nCommunityID = communityID>
5: </cfif>
6:
7:
8: <HTML>
9: <TITLE>Online Community Upload Results</TITLE>
10:
11: <CFIF #Action# is "Cancel">
12:   <CFLOCATION URL="commMaint.cfm?communityID=#nCommunityID#" ADDTOKEN="NO">
13: </CFIF>
14:
15: <BODY BGCOLOR="WHITE">
16: <!-- <CFINCLUDE TEMPLATE="admlinks.cfm" ><p>-->
17: <CFAPPLICATION NAME="Realstuff" CLIENTMANAGEMENT="Yes">
18:
19: <CFIF #Action# is "Add">
20:   Field Values:<BR>
21:   <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
22:     <CFSET cNewField = "FORM.Field" & nIndex>
23:     <CFOUTPUT>#cNewField# = #evaluate(cNewField)#<BR></CFOUTPUT>
24:   </CFLOOP>
25:   <BR>
26:   <HR>
27:
28:
29: <!-- First try to find out what kind of image is being uploaded -->
30: <CFSET nImageTypeLoc = listFindNoCase(FORM.Field_Names,'imgType')>
31: <CFIF nImageTypeLoc GT 0>
32:   <CFSET cImageField = 'FORM.FIELD' & nImageTypeLoc>
33:   <CFSET nImageType = #evaluate(cImageField)#>
34:   <CFOUTPUT>Image Type : #nImageType#<BR></CFOUTPUT>
35: <CFELSE>
36:   <CFSET nImageType = -1>
37: </CFIF>
38:
39: <!--- !!!!! -->
40: <!--- <CFSET nImageType = 0> -->
41:
42: <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
43:   <CFSET nParamID = -1>
44:
45:   <CFQUERY NAME="qryFindParamID" DATASOURCE="#SourceName#">
46:     SELECT * FROM param_defs
47:     WHERE dataGroup=6
48:     AND agency_id in (10, #ap_agency_number#)
49:     AND name='#listGetAt(FORM.Field_Names,nIndex) #'

```

```

50: </CFQUERY>
51:
52: <CFIF qryFindParamID.recordCount GT 0>
53:   <CFSET nParamID = qryFindParamID.id>
54: </CFIF>
55:
56: <CFSET cFieldType = ucase(trim(listGetAt(FORM.FieldTypes, nIndex)))>
57: <CFSET cNewField = "FORM.FIELD" & nIndex>
58:
59: <CFIF cFieldType is "TEXT">
60:   <cfoutput>Inserting data:
        #nCommunityID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, #Evaluate(cNewField)#, 6</cfoutput>
        <br>
        <CFSET cTextToSend = evaluate(cNewField)>
        <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
        <CFQUERY NAME="qryAddParameter" DATASOURCE="#DataSource#">
          INSERT INTO comm_param (communityID, param_id, agency_id, param_cntr, param_name, param_value, dataGroup)
          VALUES (#communityID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, #cTextToSend#, 6)
        </CFQUERY>
        <CFELSEIF cFieldType is "TEXTAREA">
          <cfoutput>Inserting Text Area data:
        #nCommunityID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, #Evaluate(cNewField)#, 6</cfoutput>
        <br>
        <CFSET cTextToSend = evaluate(cNewField)>
        <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
        <CFQUERY NAME="qryAddParameter" DATASOURCE="#DataSource#">
          INSERT INTO comm_param (communityID, param_id, agency_id, param_cntr, param_name, param_value, dataGroup)
          VALUES (#communityID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, #cTextToSend#, 6)
        </CFQUERY>
        <CFELSEIF cFieldType is "CHECKBOX">
          <cfoutput>Inserting checkbox data:
        #nCommunityID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, #Evaluate(cNewField)#, 6</cfoutput>
        <br>
        <CFSET cTextToSend = evaluate(cNewField)>
        <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
        <CFQUERY NAME="qryAddParameter" DATASOURCE="#DataSource#">
          INSERT INTO comm_param (communityID, param_id, agency_id, param_cntr, param_name, param_value, dataGroup)
          VALUES (#communityID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, #cTextToSend#, 6)
        </CFQUERY>
        <CFELSEIF cFieldType is "SELECT">
          <cfoutput>Inserting select data:
        #nCommunityID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, #Evaluate(cNewField)#, 6</cfoutput>
        <br>
        <CFSET cTextToSend = evaluate(cNewField)>
        <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
        <CFQUERY NAME="qryAddParameter" DATASOURCE="#DataSource#">
          INSERT INTO comm_param (communityID, param_id, agency_id, param_cntr, param_name, param_value, dataGroup)
          VALUES (#communityID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, #cTextToSend#, 6)
        </CFQUERY>

```

```

91:      </CFQUERY>
92:      <CFELSEIF cFieldType is "FILE">
93:      <HR>
94:      <CFSET cNewField = "FORM.FIELD" & nIndex>
95:      <CFSET cFileField = trim("Field" & nIndex)>
96:
97:      <CFSET cFilePath = #ap_communities_path# & #FORM.communityID# & "\">
98:
99:      <CFOUTPUT>File Name is: #cFilePath#</CFOUTPUT><BR>
100:      <CFOUTPUT>New Field : #cNewField# (#evaluate(cNewField))</CFOUTPUT><BR>
101:      <CFOUTPUT>Field Name: #listGetAt(FORM.Field_Names,nIndex)#</CFOUTPUT><BR>
102:      <CFIF listGetAt(FORM.Field_Names,nIndex) is "commImage">
103:      <CFSET nImageField = #FORM.imageField#>
104:      <CFSET cImageType = "FORM.FIELD" & nImageField>
105:      <CFIF nImageType is "0"> <!-- This is a still image --> <!-- </CFIF>nImageField GT 0 AND
      /evaluate(cImageType)# is "<"> --->
106:      <CFOUTPUT>#ap_communities_path# : #cNewField#</CFOUTPUT>
107:      <CFOUTPUT>[#evaluate(cNewField)]</CFOUTPUT>
108:
109:      <CFTRY>
110:      <CFDIRECTORY
111:      DIRECTORY="#cFilePath#"
112:      ACTION="CREATE"
113:      >
114:      <CFOUTPUT>Creating New Directory #cFilePath#</CFOUTPUT><BR>
115:      <CFCATCH TYPE="ANY">
116:      <B>Directory already exists!</B><BR>
117:      </CFCATCH>
118:      </CFTRY>
119:
120:      <!-- If an image name is not sent, then the user only wanted to add a text entry --->
121:      <!-- If the field is blank, don't try to send anything --->
122:
123:      <CFSET cEvaluate = evaluate(cNewField)>
124:      <CFIF len(trim(cEvaluate)) gt 0>
125:      <CFFILE
126:      DESTINATION=#cFilePath#
127:      ACTION="UPLOAD"
128:      NAMECONFLICT="OVERWRITE"
129:      FILEFIELD="#cFileField#">
130:
131:      <CFIF #FILE.fileWasSaved#>
132:      <BR><B>File was Saved</B><BR>
133:      <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
134:      INSERT INTO comm_param(communityID,param_id,agency_id,param_cntr,param_value,param_dataGroup)
135:      VALUES
      (#communityID#,nParamID#,ap_agency_number#,param_counter#, 'qryFindParamID.name#', 'Communities\#FORM.communityID#\#FILE.S
      erverFile#',6)
      </CFQUERY>
136:

```

```

137: <CFELSE>
138:   <BR><B>File was NOT saved</B>
139:   <CFABORT>
140:   </CFIF>
141: <CFELSE>
142:   <!-- Save the database info so the other programs don't get confused --->
143:   <BR><B>File was Saved (No image)</B><BR>
144:   <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
145:     INSERT INTO comm_param (communityID,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
146:     VALUES (#communityID#, #nParamID#, #ap_agency_number#, #param_counter#, '#qryFindParamID.name#',' ',6)
147:   </CFQUERY>
148:   </CFIF>
149: <CFELSE>
150:   <CFOUTPUT>Saving other image information: #cNewField# [ #evaluate(cNewField)# ] #evaluate('FORM.Field1')# *
    #cFileField# * #evaluate(cFileField)#<BR></CFOUTPUT>
151:   <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
152:     INSERT INTO comm_param (communityID,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
153:     VALUES
    (#communityID#, #nParamID#, #ap_agency_number#, #param_counter#, '#qryFindParamID.name#', '#Evaluate(cNewField)#', 6)
    </CFQUERY>
154:   </CFIF>
155:   </CFIF>
156:   </CFIF>
157:   </CFIF>
158:   </CFOLOOP>
159:
160: <!-- Now take us back to the view mode, informing the user that information has been updated --->
161: <CFLOCATION URL="commMaint.cfm?communityID=#nCommunityID#&Action=Updated" ADDTOKEN="NO">
162:
163: <CFELSEIF #Action# is "Edit">
164:   <!-- First try to find out what kind of image is being uploaded ---->
165:   <CFSET nImageTypeLoc = listFindNoCase(FORM.Field_Names,'imgType')>
166:   <CFIF nImageTypeLoc GT 0>
167:     <CFSET cImageField = 'FORM.FIELD' & nImageTypeLoc>
168:     <CFSET nImageType = #evaluate(cImageField)#>
169:     <CFOUTPUT>Image Type : #nImageType#</CFOUTPUT>
170:   <CFELSE>
171:     <CFSET nImageType = -1>
172:   </CFIF>
173:
174:   <!-- !!!!!!! --->
175:   <!-- <CFSET nImageType = 0> --->
176:
177:
178:   <CFOLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
179:     <CFSET cFieldType = ucase(trim(listGetAt(FORM.FieldTypes, nIndex)))>
180:     <CFSET cNewField = "FORM.FIELD" & nIndex>
181:
182:     <CFIF cFieldType is "FILE">
183:       <CFSET cNewField = "FORM.FIELD" & nIndex>

```

```

184: <CFSET cFilePath = trim("Field" & nIndex)>
185:
186: <CFOUTPUT>New Field : #NewField# (#evaluate(cNewField)#)</CFOUTPUT><BR>
187: <CFOUTPUT>Field Name: #listGetAt(FORM.Field_Names,nIndex)#</CFOUTPUT><BR>
188:
189: <CFIF listGetAt(FORM.Field_Names,nIndex) is "commImage" AND #Evaluate(cNewField)# is not "">
190:   <CFSET nImageField = #FORM.imageField#>
191:   <CFSET cImageType = "FORM.FIELD" & nImageField>
192:   <CFIF nImageType is "0"> <!-- This is a still image --> <!-- </CFIF>nImageType GT -1 AND #evaluate(cImageType)#
      is "0">
193:     <CFOUTPUT>#ap_communities_path# : #cNewField#</CFOUTPUT>
194:     <CFOUTPUT>[#evaluate(cNewField)#]</CFOUTPUT>
195:
196:     <CFSET cFilePath = #ap_communities_path# & #nCommunityID# & "\">
197:
198:     <CFIF #FILE.fileWasSaved#>
199:       DESTINATION=#cFilePath#
200:       ACTION="UPLOAD"
201:       NAMECONFLICT="OVERWRITE"
202:       FILEFIELD="#cFileField#">
203:
204:     <CFIF #FILE.fileWasSaved#>
205:       <B>File was Saved</B><BR>
206:       <CFOUTPUT>#Evaluate(cNewField)# / #nCommunityID# / #param_counter# /
      #listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
      <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
        UPDATE comm_param
        SET param_value = 'communities\#nCommunityID#\#FILE.ServerFile#'
        WHERE communityID=#communityID#
        AND param_cntr=#param_counter#
        AND param_name='#listGetAt(FORM.Field_Names,nIndex) #'
      </CFQUERY>
207:
208:     </CFELSE>
209:     <B>File was NOT saved</B>
210:     <CFABORT>
211:   </CFIF>
212:
213:   <CFELSE>
214:     <B>File was NOT saved</B>
215:     <CFABORT>
216:   </CFIF>
217:
218:   <CFELSE>
219:     <!-- Just insert the name, since this is not a still image -->
220:
221:     <CFOUTPUT>Insert Other Image<BR>#Evaluate(cNewField)# / #communityID# / #param_counter# /
      #listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
      <CFSET cTextToSend = evaluate(cNewField)>
      <CFSET cTextToSend = preservesSingleQuotes(cTextToSend)>
      <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
        UPDATE comm_param
        SET param_value = '#cTextToSend#'
        WHERE communityID=#nCommunityID#
        AND param_cntr=#param_counter#
        AND param_name='#listGetAt(FORM.Field_Names,nIndex) #'
      </CFQUERY>
222:
223:
224:
225:
226:
227:
228:
229:

```

```

230:         </CFQUERY>
231:         </CFIF>
232:         </CFIF>
233:         <CFELSE>
234:             <CFOUTPUT>#Evaluate(cNewField)# / #nCommunityID# / #param_counter# /
                #listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
235:             <CFSET cTextToSend = evaluate(cNewField)>
236:             <CFSET cTextToSend = preservesingleQuotes(cTextToSend)>
237:             <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
238:                 UPDATE comm_param
239:                 SET param_value = '#cTextToSend#'
240:                 WHERE communityID=#nCommunityID#
241:                 AND param_cntr=#param_counter#
242:                 AND param_name='#listGetAt(FORM.Field_Names,nIndex) #'
243:             </CFQUERY>
244:             </CFIF>
245:         </CFLOOP>
246:         <!-- Now take us back to the view mode, informing the user that information has been updated -->
247:         <CFLOCATION URL="commMaint.cfm?communityID=#nCommunityID#&Action=Updated" ADDTOKEN="NO">
248:
249:         <CFELSEIF #Action# is "Delete">
250:             <CFIF NOT IsDefined("param_counter")> <!-- To delete the information -->
251:                 <CFLOCATION URL="commMaint.cfm?communityID=#nCommunityID#" ADDTOKEN="NO">
252:             </CFIF>
253:
254:             <!-- Delete the selected paragraph -->
255:             <CFQUERY NAME="qryDeleteAd" DATASOURCE="#SourceName#">
256:                 DELETE FROM comm_param
257:                 WHERE communityID=#nCommunityID# AND
258:                 param_cntr=#param_counter# AND
259:                 agency_id=#ap_agency_number# AND
260:                 dataGroup=6
261:             </CFQUERY>
262:
263:             <!-- Now take us back to the view mode, informing the user that information has been updated -->
264:             <CFLOCATION URL="commMaint.cfm?communityID=#nCommunityID#&Action=Deleted" ADDTOKEN="NO">
265:         </CFIF>
266:
267:         </BODY>
268:         </HTML>
269:

```



```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3: <!-- Include file holding lists and other community related information -->
4: <CFINCLUDE TEMPLATE="..\commDefines.cfm">
5:
6: <!-- -1 = add a new community -->
7: <CFPARAM NAME="URL.communityID" DEFAULT="-1">
8: <CFPARAM NAME="URL.Action" DEFAULT="View">
9: <cfparam name="URL.param_counter" default="-1"> <!-- If editing, this will have a number -->
10: <cfparam name="URL.ImageType" default="0"> <!-- the image type -->
11:
12:
13: <CFSET nCommunityID = URL.communityID>
14:
15:
16: <!-- Find the community based on the passed communityID -->
17: <cfquery name="qryFindComm" datasource="#sourceName#">
18:   SELECT *
19:   FROM Communities
20:   WHERE CommunityID = #nCommunityID#
21: </cfquery>
22:
23:
24: <cfquery name="qryCommTypes" datasource="#SourceName#">
25:   select TypeID, Name
26:   from CommTypes
27: </cfquery>
28:
29: <cfquery name="qryParameters" datasource="#sourceName#">
30:   SELECT comm_param.communityID, comm_param.agency_id, comm_param.param_name, comm_param.param_value, comm_param.param_cntr,
31:     param_defs.description, param_defs.label, param_defs.displayOrder, param_defs.restrictions, param_defs.type
32:   FROM param_defs, comm_param
33:   WHERE comm_param.communityID=#nCommunityID#
34:   AND comm_param.param_id = param_defs.id
35:   ORDER BY comm_param.param_cntr,param_defs.displayOrder
36: </cfquery>
37:
38: <!-- Parameter names for the image fields -->
39: <cfquery name="qryParamNames" datasource="#sourceName#">
40:   SELECT
41:     DISTINCT id, name, description, label, displayOrder, restrictions, type, selectOptions
42:   FROM param_defs
43:   WHERE securityLevel=1
44:   AND dataGroup = 6
45:   ORDER BY displayOrder
46: </cfquery>
47:
48: <!-- qryImageTypes will load the image types for the pull down while
49:   adding or editing a photo -->

```

```

50: <cfquery name="qryImageTypes" datasource="#source#">
51:   SELECT label,counter,value,agency_id
52:   FROM param_allowed
53:   WHERE param_allowed.id = 9
54:   ORDER BY param_allowed.counter
55: </cfquery>
56:
57:
58: <!--- Delimited lists for various uses --->
59: <cfset listLabels = ValueList(qryParamNames.label)> <!--- "Use Name" --->
60: <cfset listFieldNames = ValueList(qryParamNames.name)> <!--- "Comantitie" --->
61: <cfset listFieldTypes = ValueList(qryParamNames.type)> <!--- "FFXT, Field, etc. --->
62: <cfset listFieldOptions = QuotedValueList(qryParamNames.selectOptions,"|")>
63:
64:
65: <html>
66: <head>
67:   <cfoutput>
68:     <title>#ap_backofficeName# Backoffice</title>
69:   </cfoutput>
70:   <link rel="stylesheet" href="style1.css" type="text/css">
71:   <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
72: </head>
73:
74: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
75:
76: <p><cfinclude template="header.cfm"></p>
77:
78: <cfoutput>
79:
80: <CFSET nTotalCols = qryParamNames.recordCount+2>
81: <CFSET aFieldValues = ArrayNew(1)>
82:
83: <CFIF URL.Action is "View">
84:   <!--- Set default values for the edit fields --->
85:   <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
86:     <CFSET aFieldValues[nIndex] = "">
87:   </CFLOOP>
88:
89: <CFELSEIF URL.Action is "Add">
90:   <CFSET URL.Action = "View">
91:   <CFELSEIF URL.Action is "Edit">
92:     <!--- A Paragraph has been selected for editing --->
93:   <CFELSEIF URL.Action is "Deleted">
94:     <!--- Delete the selected image --->
95:     <!--- Set default values for the edit fields --->
96:     <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
97:       <CFSET aFieldValues[nIndex] = "">
98:     </CFLOOP>

```

```

99:      <CFSET URL.Action = "View">
100:      <CFELSEIF URL.Action is "Updated">
101:      <!-- Set default values for the edit fields -->
102:      <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nindex">
103:      <CFSET afieldValues[nindex] = "">
104:      </CFLOOP>
105:      <CFSET URL.Action = "View">
106:      </CFIF>
107:
108:
109:
110:      <p>
111:      <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
112:      <tr bgcolor="cccc99"><td colspan="2"><span class="h2"><b>Online Communities</b></span></td></tr>
113:      <tr bgcolor="cccccc"><td colspan="2"><b>General Online Community Information</b></td></tr>
114:      <tr bgcolor="eeeeee">
115:      <td width="20%">Community Name:</td>
116:      <td>
117:      <form name="frmCommInfo" enctype="multipart/form-data" action="commUpdate.cfm?communityID=#nCommunityID#"
118:      method="post">
119:      <input type="text" name="edtCommName" value="#qryFindComm.Name#"></td>
120:      </tr>
121:      <tr bgcolor="eeeeee">
122:      <td width="20%">Region:</td>
123:      <td>
124:      <select name="edtRegion">
125:      <cfloop index="cindex" list="#listRegions#">
126:      <option<cfif cindex is #trim(qryFindComm.Region)#> selected</cfif>>#cindex#
127:      </cfloop>
128:      </select>
129:      </td>
130:      </tr>
131:      <!-- Moved to property type for individual properties 4/25/00 -->
132:      <tr bgcolor="eeeeee">
133:      <td width="20%">Community Type:</td>
134:      <td>
135:      <select name="edtCommType" multiple>
136:      <cfloop query="qryCommTypes">
137:      <option<cfif #listfindnocase(qryFindComm.CommunityType,qryCommTypes.Name)# gt. 0>
138:      selected</cfif>>#qryCommTypes.name#
139:      </cfloop>
140:      </select>
141:      </td>
142:      </tr>
143:      <tr bgcolor="eeeeee">
144:      <td width="20%">Header Image:</td>
145:      <td>
146:      <input type="FILE" name="edtHeader">

```

```

146:         <cfif qryFindComm.recordCount gt 0><em>Currently: #getFileFromPath(qryFindComm.headerFilename)#</em></cfif></td>
147:     </tr>
148:     <tr bgcolor="eeeeee">
149:         <td width="20%">Footer Image:</td>
150:     </tr>
151:     <input type="FILE" name="edtFooter">
152:     <cfif qryFindComm.recordCount gt 0><em>Currently: #getFileFromPath(qryFindComm.footerFilename)#</em></cfif></td>
153: </tr>
154: <tr bgcolor="eeeeee">
155:     <td width="20%">Available Dates:</td>
156:     <td>From <input type="TEXT" size="10" name="edtStartDate" value="#DateFormat(qryFindComm.startDate,"mm/dd/yyyy")#"> To
157:     <input type="TEXT" size="10" name="edtStopDate" VALUE="#dateformat(qryFindComm.stopDate,"mm/dd/yyyy")#"></td>
158: </tr>
159: <tr bgcolor="eeeeee">
160:     <td width="20%">Primary Picture:</td>
161:     <input type="FILE" name="edtprimaryPic">
162:     <cfif qryFindComm.recordCount gt 0><em>Currently: #getFileFromPath(qryFindComm.primaryPic)#</em></cfif></td>
163: </tr>
164:
165:     <tr bgcolor="eeeeee">
166:         <td width="20%">Alternate URL:</td>
167:     </tr>
168:     <input type="text" name="edtAltURL" value="#qryFindComm.AlternateURL#">
169:     </td>
170: </tr>
171:
172:     <tr bgcolor="eeeeee">
173:         <td width="20%">Description:</td>
174:     </tr>
175:     <textarea name="edtDesc" rows="5" cols="80" wrap="virtual">#qryFindComm.Description#</textarea>
176:     </td>
177: </tr>
178:
179:
180:     <tr bgcolor="eeeeee">
181:         <td colspan="2">
182:             <cfif qryFindComm.recordCount is 0>
183:                 <input type="submit" name="btnUpdate" value="Add Community Info">
184:                 <input type="reset" value="Reset Info">
185:             <cfelse>
186:                 <input type="submit" name="btnUpdate" value="Update Community Info">
187:                 <input type="reset" value="Reset Info">
188:                 <input type="submit" name="btnDelete" value="Delete Community">
189:             </cfif>
190:         </td>
191:     </tr>
192:     </FORM>
193:

```

```

194: </table>
195: </p>
196:
197:
198:
199: <!-- Here is the paragraph information already entered -->
200:
201: <cfif qryFindComm.recordcount gt 0>
202: <p><table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
203: <!-- First see if there are any images to display -->
204: <cfif #qryParameters.recordcount# is 0>
205: <tr bgcolor="cccccc">
206: <td><b class="h2">No paragraphs are associated with this community</b></td>
207: </td></tr>
208: </cfelse>
209: <!-- there are paragraphs, so display the labels first -->
210: <tr bgcolor="cccccc">
211: <cfloop from="1" to="#listlen(listLabels)#" index="nindex">
212: <td align="center"><b>#listGetAt(listLabels, nindex)#</b></td>
213: </cfloop>
214: <td>&nbsp;</td></tr>
215: </cfif>
216:
217: <!-- Now for the actual data -->
218: <CFSET lEditrow = False>
219: <CFSET cImageName = "">
220: <CFSET nRow = 0>
221: <CFSET nOldParamCounter = -1>
222: <CFSET nParamCounter = -1>
223: <CFSET nMaxParamCounter = -1>
224: <CFSET nColumn = 0>
225:
226: <CFLOOP QUERY="qryParameters">
227: <CFSET nRow = nRow + 1>
228: <CFIF qryParameters.param_name IS listGetAt(listFieldNames, 1)>
229: <CFSET nColumn = 0>
230: <CFSET nMaxParamCounter = max(nMaxParamCounter, qryParameters.param_cntr)>
231: <CFSET nParamCounter = qryParameters.param_cntr>
232: <CFIF nParamCounter is URL.param_counter>
233: <CFSET lEditrow = TRUE>
234: </CFELSE>
235: <CFSET lEditrow = FALSE>
236: </CFIF>
237: <tr bgcolor="eeeeee">
238: </CFIF>
239: <CFSET nColumn = nColumn + 1>
240: <CFIF lEditrow>
241: <CFSET aFieldValue[nColumn] = qryParameters.param_value>
242: </CFIF>

```

```

243: <CFIF listGetAt(listFieldNames,nColumn) is "imgType">
244:   <td <CFIF leditrow IS true>bgcolor="ffffff"</CFIF> valign="top">
245:     <CFIF qryParameters.param_value is "0">
246:       Standard Photo
247:     <CFIF leditrow is true><CFSET URL.ImageType = "0"></CFIF>
248:     <CFELSEIF qryParameters.param_value is "1">
249:       Bamboo Image
250:     <CFIF leditrow is true><CFSET URL.ImageType = "1"></CFIF>
251:     <CFELSEIF qryParameters.param_value is "2">
252:       IPIX Image
253:     <CFIF leditrow is true><CFSET URL.ImageType = "2"></CFIF>
254:     <CFELSE>
255:       #qryParameters.param_value#
256:     <CFIF leditrow is true><CFSET URL.ImageType = "-1"></CFIF>
257:   </CFIF>
258: </td>
259: <CFELSE>
260:   <td <CFIF leditrow IS true>bgcolor="ffffff"</CFIF> valign="top">#qryParameters.param_value#</td>
261: </CFIF>
262:
263: <CFIF nColumn is nTotalCols-2> <!-- the last column with info was displayed -->
264:   <td <CFIF leditrow is true>bgcolor="ffffff"</CFIF> colspan="2" valign="top">
265:     <a
266:       href="commMaint.cfm?Action=Edit&communityID=#URL.communityID#&param_counter=#qryParameters.param_cntr#>Edit</a><hr>
267:     <a
268:       href="commDataUpdate.cfm?Action=Delete&communityID=#URL.communityID#&param_counter=#qryParameters.param_cntr#>Delete</a></td>
269:   </tr>
270:   <CFSET nColumn = 0>
271:   </CFIF>
272: </CFLOOP>
273: </table></p>
274:
275:
276: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
277:   <!-- Now allow the user to add or edit an image -->
278:   <tr bgcolor="cccccc">
279:     <td colspan="#nTotalCols#"
280:       <CFIF #URL.Action# is "Add">
281:         <b>Add A Paragraph</b>:
282:         <input type="hidden" name="Action" VALUE="Add">
283:         <CFELSEIF #URL.Action# is "Edit">
284:         <b>Edit Selected Paragraph:</b>
285:         <input type="hidden" name="Action" VALUE="Edit">
286:         <CFELSEIF #URL.Action# is "View">
287:         <b>Add A Paragraph:</b>
288:         <input type="hidden" name="Action" VALUE="Add">

```

```

289:         </CFIF>
290:     </td>
291: </tr>
292:
293: <tr>
294:     <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
295:         <td bgcolor="eeeeee" valign="bottom">
296:             <!-- Moved the text area (paragraph) to a row immediately under the other input data --SFE 0404800-->
297:             <cfif findNoCase("Text", #listGetAt(listLabels, nIndex)#) neq 0>
298:                 <cfset labelId = #nIndex#>
299:                 <cfelse>
300:                     <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, nIndex)#</b></font>
301:                 </cfif>
302:             </td>
303:         </CFLOOP>
304:     </tr>
305:
306:     <form name="frmValues" enctype="multipart/form-data" action="commDataUpdate.cfm" method="post">
307:         <tr valign="top" bgcolor="eeeeee">
308:             <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
309:                 <CFSET cFieldType = ucase(trim(listGetAt(listFieldTypes, nIndex)))>
310:                 <CFIF cFieldType is "TEXT">
311:                     <CFIF listGetAt(listFieldNames, nIndex) is "imgType">
312:                         <td>
313:                             <CFIF #URL.Action# is "Edit">
314:                                 <CFIF aFieldValues[nIndex] is "0">
315:                                     <I>Standard Photo</I><br>
316:                                 <CFELSEIF aFieldValues[nIndex] is "1">
317:                                     <I>Bamboo Image</I><br>
318:                                 <CFELSEIF aFieldValues[nIndex] is "2">
319:                                     <I>IPIX Image</I><br>
320:                                 <CFELSE>
321:                                     <I>#aFieldValues[nIndex]#</I><br>
322:                                 </CFIF>
323:                             </CFIF>
324:                         <SELECT NAME="FIELD#nIndex#">
325:                             <CFLOOP QUERY="qryImageTypes">
326:                                 <CFIF URL.ImageType is "0" and qryImageTypes.value is "0">
327:                                     <CFSET lShowOption = true>
328:                                 <CFELSEIF URL.ImageType is not "0" and qryImageTypes.value is not "0">
329:                                     <CFSET lShowOption = true>
330:                                 <CFELSE>
331:                                     <CFSET lShowOption = False>
332:                                 </CFIF>
333:                                 <CFIF lShowOption is true>
334:                                     <OPTION value="#qryImageTypes.value#>#listGetAt(listFieldNames, nIndex)# is
                                     #trim(qryImageTypes.value)#>SELECTED</CFIF><#trim(label)#</OPTION>
                                     </CFIF>
335:                                 </CFLOOP>
336:

```

```

337: </SELECT>
338: <br>
339: <CFIF URL.Action is not "Edit">
340: <!-- If they want to change the image type, they will need to delete the image and reenter it -->
341: <CFIF URL.ImageType is "0">
342:   <font face="Verdana, Arial" size="1"><a
href="commMaint.cfm?Action=#URL.Action#&communityID=#URL.communityID#&ImageType=1&param_counter=#URL.param_counter#">To Add
Bamboo or IPIX<br>images, Click Here</a></font>
   <CFELSE>
343:     <font face="Verdana, Arial" size="1"><a
344: href="commMaint.cfm?Action=#URL.Action#&communityID=#URL.communityID#&ImageType=0&param_counter=#URL.param_counter#">To Add
a standard photo, Click Here</a></font>
   </CFIF>
345: </CFIF>
346: </td>
347: </td>
348: <CFELSE>
349: <td>
350:   <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
351: </td>
352: </CFIF>
353: <CFELSEIF cFieldType is "FILE">
354: <td>
355:   <CFIF #URL.Action# is "Edit">
356:     <CFIF URL.ImageType is "0">
357:       <I>#getFileFromPath(aFieldValues[nIndex])#</I><br>
358:     <CFELSE>
359:       #aFieldValues[nIndex]#<br>
360:     </CFIF>
361:   </CFIF>
362:   <CFIF URL.ImageType is "0">
363:     <INPUT TYPE="FILE" NAME="Field#nIndex#" SIZE="20">
364:   <CFELSE>
365:     <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
366:   </CFIF>
367: </td>
368: <CFELSEIF cFieldType is "TEXTAREA">
369: <td>
370:   <!-- Moved the text area to a row immediately under the other input data --SPE 0404800-->
371:   <cfset textId = #nIndex#>
372: </td>
373: <CFELSEIF cFieldType is "CHECKBOX">
374:   <td ALIGN="CENTER">
375:     <INPUT TYPE="CHECKBOX" NAME="Field#nIndex#" SIZE="70" <CFIF #aFieldValues[nIndex]# is "ON">CHECKED</CFIF>>
376:   </td>
377: <CFELSEIF cFieldType is "SELECT">
378:   <td>
379:     <CFSET listColOptions = replace(ListGetAt(listFieldOptions, nIndex,"|"), "','',"All")>
380:     <CFIF listlen(listColOptions) gt 0>
381:       <SELECT NAME="Field#nIndex#">

```



```

382: <CFLOOP FROM="1" TO="#listlen(listColOptions)" INDEX="nlistInd">
383:   <CFSET Option = listGetAt(listColOptions, nlistInd, ",")>
384:   <OPTION <CFIF #aFieldValues[nIndex]# is #cOption#>SELECT</CFIF>>#cOption#
385: </CFLOOP>
386: </SELECT>
387: </CFIF>
388: </td>
389: </CFIF>
390: </CFLOOP>
391: </tr>
392: <tr valign="top" bgcolor="eeeeee">
393: <!-- Moved the text area to a row immediately under the other input data -- SPE 6104800 -->
394: <td colspan="#listlen(listLabels)#">
395:   <cfif isDefined("textid")>
396:     <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, labelId)#</b></font><br>
397:     <TEXTAREA ROWS="8" COLS="80" WRAP="VIRTUAL" NAME="Field#textid#">#aFieldValues[textid]#</TEXTAREA>
398:   </cfif>
399: </td>
400: </tr>
401: <tr bgcolor="eeeeee">
402: <td colspan="#nTotalCols#">
403:   <CFIF nMaxParamCounter is -1>
404:     <CFSET nMaxParamCounter = 1>
405:   <CFELSE>
406:     <CFSET nMaxParamCounter = nMaxParamCounter + 1>
407:   </CFIF>
408:   <CFIF #URL.Action# is "View">
409:     <input type="hidden" name="Action" VALUE="ADD">
410:     <INPUT TYPE="SUBMIT" VALUE="Add New Paragraph" NAME="btnSubmit">
411:
412:     <input type="hidden" name="param_counter" VALUE="#nMaxParamCounter#">
413:     <CFELSEIF #URL.Action# is "Edit">
414:       <input type="hidden" name="Action" VALUE="EDIT">
415:       <INPUT TYPE="SUBMIT" VALUE="Update Paragraph">
416:       <INPUT TYPE="RESET" VALUE="Reset Information">
417:       <INPUT TYPE="BUTTON" VALUE="Cancel" NAME="btnSubmit"
ONCLICK="location.href='commMaint.cfm?communityID=#URL.communityID#&Action=View'">
418:       <input type="hidden" name="param_counter" VALUE="#URL.Param_Counter#">
419:     </CFIF>
420:   </td>
421: </tr>
422:
423: <CFSET nImageTypeField = listFindNoCase(listFieldNames, "imgType")>
424:
425: <input type="hidden" name="imageField" VALUE="#nImageTypeField#">
426: <input type="hidden" name="communityID" VALUE="#URL.communityID#">
427: <input type="hidden" name="FieldLabels" VALUE="#listLabels#">
428: <input type="hidden" name="FieldTypes" VALUE="#listFieldTypes#">
429: <input type="hidden" name="Field_Names" VALUE="#listFieldNames#">

```

```
430:      </form>
431:      </table></p>
432:
433:
434:
435:
436:      </cfif>
437:      </cfoutput>
438:
439:      </body>
440:      </html>
```

4.0 transitional / EN 3

```
49:         <td><a href="#CommTypeMaint.cfm?typeID=#tryCommTypes.typeID#>Edit</a></td>
50:       </cfoutput>
51:     </tr>
52:   </cfloop>
53: </table></p>
54:
55: </body>
56: </html>
```

```

1: <CFPARAM NAME="ACTION" DEFAULT="Cancel">
2:
3: <CFIF isDefined("TypeID")>
4:   <cfset nTypeID = TypeID>
5: </cfif>
6:
7:
8: <HTML>
9: <TITLE>Online Community Type Upload Results</TITLE>
10:
11: <CFIF #Action# is "Cancel">
12:   <CFLOCATION URL="commTypeMaint.cfm?typeID=#nTypeID#" ADDTOKEN="NO">
13: </CFIF>
14:
15: <BODY BGCOLOR="WHITE">
16:   <!-- <CFINCLUDE TEMPLATE="acmlinks.cfm" --> -->
17:   <CFAPPLICATION NAME="RealStuff" CLIENTMANAGEMENT="Yes">
18:
19:   <CFIF #Action# is "Add">
20:     Field Values:<BR>
21:     <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
22:       <CFSET cNewField = "FORM.Field" & nIndex>
23:       <CFOUTPUT>#cNewField# = #evaluate(cNewField)#<BR></CFOUTPUT>
24:     </CFLOOP>
25:   <BR>
26:   <HR>
27:
28:
29:   <!-- First try to find out what kind of image is being uploaded --->
30:   <CFSET nImageTypeLoc = listFindNoCase(FORM.Field_Names,'imgType')>
31:   <CFIF nImageTypeLoc GT 0>
32:     <CFSET cImageField = 'FORM.FIELD' & nImageTypeLoc>
33:     <CFSET nImageType = #evaluate(cImageField)#>
34:     <CFOUTPUT>Image Type : #nImageType#<BR></CFOUTPUT>
35:   <CFELSE>
36:     <CFSET nImageType = -1>
37:   </CFIF>
38:
39:   <!-- !!!!! -->
40:   <!-- <CFSET nImageType = 0> --->
41:
42:   <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
43:     <CFSET nParamID = -1>
44:
45:     <CFQUERY NAME="qryFindParamID" DATASOURCE="#SourceName#">
46:       SELECT * FROM param_defs
47:       WHERE dataGroup=7
48:       AND agency_id in (10, #ap_agency_number#)
49:       AND name='#listGetAt(FORM.Field_Names,nIndex) #'

```

```
50: </CFQUERY>
51:
52: <CFIF qryFindParamID.recordCount GT 0>
53:   <CFSET nParamID = qryFindParamID.id>
54: </CFIF>
55:
56: <CFSET cFieldType = ucase(trim(listGetAt(FORM.FieldTypes, nIndex)))>
57: <CFSET cNewField = "FORM.FIELD" & nIndex>
58:
59: <CFIF cFieldType is "TEXT">
60:   <cfoutput>Inserting data:
61:     #nTypeID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, '#Evaluate(cNewField)','#,7</cfoutput> <br>
62:     <CFSET cTextToSend = evaluate(cNewField)>
63:     <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
64:     <CFQUERY NAME="qryAddParameter" DATASOURCE="#DataSource#">
65:       INSERT INTO commtype_param (TypeID, param_id, agency_id, param_cntr, param_name, param_value, dataGroup)
66:       VALUES (#TypeID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, '#cTextToSend','#,7)
67:     </CFQUERY>
68:     <CFELSEIF cFieldType is "TEXTAREA">
69:       <cfoutput>Inserting Text Area data:
70:         #nTypeID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, '#Evaluate(cNewField)','#,7</cfoutput> <br>
71:         <CFSET cTextToSend = evaluate(cNewField)>
72:         <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
73:         <CFQUERY NAME="qryAddParameter" DATASOURCE="#DataSource#">
74:           INSERT INTO commtype_param (TypeID, param_id, agency_id, param_cntr, param_name, param_value, dataGroup)
75:           VALUES (#TypeID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, '#cTextToSend','#,7)
76:         </CFQUERY>
77:         <CFELSEIF cFieldType is "CHECKBOX">
78:           <cfoutput>Inserting checkbox data:
79:             #nTypeID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, '#Evaluate(cNewField)','#,7</cfoutput> <br>
80:             <CFSET cTextToSend = evaluate(cNewField)>
81:             <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
82:             <CFQUERY NAME="qryAddParameter" DATASOURCE="#DataSource#">
83:               INSERT INTO commtype_param (TypeID, param_id, agency_id, param_cntr, param_name, param_value, dataGroup)
84:               VALUES (#TypeID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, '#cTextToSend','#,7)
85:             </CFQUERY>
86:             <CFELSEIF cFieldType is "SELECT">
87:               <cfoutput>Inserting select data:
88:                 #nTypeID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, '#Evaluate(cNewField)','#,7</cfoutput> <br>
89:                 <CFSET cTextToSend = evaluate(cNewField)>
90:                 <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
91:                 <CFQUERY NAME="qryAddParameter" DATASOURCE="#DataSource#">
92:                   INSERT INTO commtype_param (TypeID, param_id, agency_id, param_cntr, param_name, param_value, dataGroup)
93:                   VALUES (#TypeID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, '#cTextToSend','#,7)
94:                 </CFQUERY>
95:                 <CFELSEIF cFieldType is "FILE">
96:                   <HR>
97:                   <CFSET cNewField = "FORM.FIELD" & nIndex>
```

```

95: <CFSET cFilePath = trim("Field" & nIndex)>
96:
97: <CFSET cFilePath = #ap_commttype_path# & #FORM.typeID# & "\">
98:
99: <CFOUTPUT>File Name is: #cFilePath#</CFOUTPUT><BR>
100: <CFOUTPUT>New Field : #cNewField# (#evaluate(cNewField))</CFOUTPUT><BR>
101: <CFOUTPUT>Field Name: #listGetAt(FORM.Field_Names,nIndex)#</CFOUTPUT><BR>
102: <CFIF listGetAt(FORM.Field_Names, nIndex) is "CTypeImage">
103:   <CFSET nIndexField = #FORM.imageField#>
104:   <CFSET cImageType = "FORM.FIELD" & nIndexField>
105:   <CFIF nIndexField is "0"> <!-- This is a still image --> <!-- </CFIF>#imageField GT 0 AND
      #evaluate(cImageType) is "C"> <!--
106:   <CFOUTPUT>#ap_commttype_path# : #cNewField#</CFOUTPUT>
107:   <CFOUTPUT>[#evaluate(cNewField)]</CFOUTPUT>
108:
109:   <CFTRY>
110:     <CFDIRECTORY
111:       DIRECTORY="#cFilePath#"
112:       ACTION="CREATE"
113:     >
114:     <CFOUTPUT>Creating New Directory #cFilePath#</CFOUTPUT><BR>
115:     <CFCATCH TYPE="ANY">
116:       <B>Directory already exists!</B><BR>
117:     </CFCATCH>
118:   </CFTRY>
119:
120:   <!-- If an image name is not sent, then the user only wanted to add a text entry -->
121:   <!-- If the field is blank, don't try to send anything -->
122:
123:   <CFSET cEvaluate = evaluate(cNewField)>
124:   <CFIF len(trim(cEvaluate)) gt 0>
125:     <CFFILE
126:       DESTINATION=#cFilePath#
127:       ACTION="UPLOAD"
128:       NAMECONFLICT="OVERWRITE"
129:       FILEFIELD="#cField#">
130:
131:   <CFIF #FILE.fileWasSaved#>
132:     <BR><B>File was Saved</B><BR>
133:     <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
134:       INSERT INTO commtype_param(typeID,param_id,param_cntr,param_value,param_group)
135:       VALUES
136:       (#typeID#, #nParamID#, #ap_agency_number#, #param_counter#, 'qryFindParamID.name#', 'Commttype\#FORM.typeID#\#FILE.ServerFile#', 7
137:     )
138:     </CFQUERY>
139:   <CFELSE>
140:     <BR><B>File was NOT saved</B>
141:   </CFIF>

```

```

141: <CFELSE>
142: <!-- Save the database info so the other programs don't get confused -->
143: <BR><B>File was Saved (No image)</B><BR>
144: <CFOURPUT NAME="qryAddParameter" DATASOURCE="#SourceName#">
145: INSERT INTO commtype_param (typeID,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
146: VALUES (#typeID#, #nParamID#, #ap_agency_number#, #param_counter#, '','',7)
147: </CFL="com
148: </CFIF>
149: <CFELSE>
150: <CFOUTPUT>Saving other image information: #cNewField# [#evaluate(cNewField)] #evaluate('FORM.Field1')# *
    #cFileField# * #evaluate(cFileField)<BR></CFOUTPUT>
151: <CFOURPUT NAME="qryAddParameter" DATASOURCE="#SourceName#">
152: INSERT INTO commtype_param (typeID,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
153: VALUES
    (#typeID#, #nParamID#, #ap_agency_number#, #param_counter#, 'qryFindParamID.name', '#Evaluate(cNewField)','#',7)
154: </CFOURPUT>
155: </CFIF>
156: </CFIF>
157: </CFIF>
158: </CFOURPUT>
159:
160: <!-- New take us back to the view mode, informing the user that information has been updated -->
161: <CFLOCATION URL="commTypeMaint.cfm?typeID=#nTypeID#&Action=Updated" ADDTOKEN="NO">
162:
163: <CFELSEIF #Action# is "Edit">
164: <!-- First try to find out what kind of image is being uploaded ---->
165: <CFSET nImageTypeLoc = listFindNoCase(FORM.Field_Names, 'imgType')>
166: <CFIF nImageTypeLoc GT 0>
167: <CFSET cImageField = 'FORM.FIELD' & nImageTypeLoc>
168: <CFSET nImageType = #evaluate(cImageField)>
169: <CFOUTPUT>Image Type : #nImageType#</CFOUTPUT>
170: <CFELSE>
171: <CFSET nImageType = -1>
172: </CFIF>
173:
174: <!-- !!!!! -->
175: <!-- <CFSET nImageType = 0> -->
176:
177:
178: <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)" INDEX="nIndex">
179: <CFSET cFieldType = ucase(trim(listGetAt(FORM.FieldTypes, nIndex)))>
180: <CFSET cNewField = "FORM.FIELD" & nIndex>
181:
182: <CFIF cFieldType is "FILE">
183: <CFSET cNewField = "FORM.FIELD" & nIndex>
184: <CFSET cFileField = trim("Field" & nIndex)>
185:
186: <CFOUTPUT>New Field : #cNewField# (#evaluate(cNewField))</CFOUTPUT><BR>
187: <CFOUTPUT>Field Name: #listGetAt(FORM.Field_Names, nIndex)#</CFOUTPUT><BR>

```



```

188:
189:
190:
191:
192:
193:
194:
195:
196:
197:
198:
199:
200:
201:
202:
203:
204:
205:
206:
207:
208:
209:
210:
211:
212:
213:
214:
215:
216:
217:
218:
219:
220:
221:
222:
223:
224:
225:
226:
227:
228:
229:
230:
231:
232:
233:

    <CFIF listGetAt(FORM.Field_Names, nIndex) is "commImage" AND #Evaluate(cNewField)# is not "">
    <CFSET nImageField = #FORM.imageField#>
    <CFSET cImageType = "FORM.FIELD" & nImageField>
    <CFIF nImageType is "0"> <!--- This is a still image ---> <!--- </CFIF>nImageType GT -1 AND #evaluate(cImageType)#
    is "0"> --->
    <CFOUTPUT>#ap_commttype_path# : #cNewField#</CFOUTPUT>
    <CFOUTPUT>[#evaluate(cNewField)#]</CFOUTPUT>

    <CFSET cFilePath = #ap_commttype_path# & #nTypeID# & "\">
    <CFFILE
    DESTINATION=#cFilePath#
    ACTION="UPLOAD"
    NAMECONFLICT="OVERWRITE"
    FILEFIELD="#cFileField#">

    <CFIF #FILE.fileWasSaved#>
    <B>File was Saved</B><BR>
    <CFOUTPUT>#Evaluate(cNewField)# / #nTypeID# / #param_counter# /
    #listGetAt(FORM.Field_Names, nIndex)#<BR></CFOUTPUT>
    <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
    UPDATE commtype_param
    SET param_value = 'commtype\#nTypeID#\#FILE.ServerFile#'
    WHERE typeID=#nTypeID#
    AND param_cntr=#param_counter#
    AND param_name='#listGetAt(FORM.Field_Names, nIndex)#'
    </CFQUERY>
    <CFELSE>
    <B>File was NOT saved</B>
    <CFABORT>
    </CFIF>
    <CFELSE>
    <!--- Just insert the name, since this is not a still image --->

    <CFOUTPUT>Insert Other Image<BR>#Evaluate(cNewField)# / #nTypeID# / #param_counter# /
    #listGetAt(FORM.Field_Names, nIndex)#<BR></CFOUTPUT>
    <CFSET cTextToSend = evaluate(cNewField)>
    <CFSET cTextToSend = preservesingleQuotes(cTextToSend)>
    <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
    UPDATE commtype_param
    SET param_value = 'cTextToSend#'
    WHERE typeID=#nTypeID#
    AND param_cntr=#param_counter#
    AND param_name='#listGetAt(FORM.Field_Names, nIndex)#'
    </CFQUERY>
    </CFIF>
    </CFIF>
    <CFELSE>

```

```

234: <CFOUTPUT>#Evaluate(cNewField)# / #ntypeID# / #param_counter# / #listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
235: <CFSET cTextToSend = evaluate(cNewField)>
236: <CFSET cTextToSend = preservesSingleQuotes(cTextToSend)>
237: <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
238:     UPDATE commtype_param
239:     SET param_value = '#cTextToSend#'
240:     WHERE typeID=#ntypeID#
241:     AND param_cntr=#param_counter#
242:     AND param_name='#listGetAt(FORM.Field_Names,nIndex) #'
243: </CFQUERY>
244: </CFIF>
245: </CFLOOP>
246: <!-- Now take us back to the view mode, informing the user that information has been updated -->
247: <CFLOCATION URL="commTypeMaint.cfm?typeID=#ntypeID#&Action=Updated" ADDTOKEN="NO">
248:
249: <CFELSEIF #Action# is "Delete">
250: <CFIF NOT IsDefined("param_counter")> <!-- To delete the information -->
251: <CFLOCATION URL="commTypeMaint.cfm?typeID=#ntypeID#" ADDTOKEN="NO">
252: </CFIF>
253:
254: <!-- Delete the selected paragraph -->
255: <CFQUERY NAME="qryDeleteAd" DATASOURCE="#SourceName#">
256:     DELETE FROM commtype_param
257:     WHERE typeID=#ntypeID# AND
258:     param_cntr=#param_counter# AND
259:     agency_id=#ap_agency_number# AND
260:     dataGroup=7
261: </CFQUERY>
262:
263: <!-- Now take us back to the view mode, informing the user that information has been updated -->
264: <CFLOCATION URL="commTypeMaint.cfm?typeID=#ntypeID#&Action=Deleted" ADDTOKEN="NO">
265: </CFIF>
266:
267: </BODY>
268: </HTML>
269:

```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3:  <!-- -1 = add a new community type -->
4:  <CFPARAM NAME="URL.TypeID" DEFAULT="-1">
5:  <CFPARAM NAME="URL.Action" DEFAULT="View">
6:  <cfparam name="URL.param_counter" default="-1"> <!-- If editing, this will have a number -->
7:  <cfparam name="URL.ImageType" default="0"> <!-- the image type -->
8:
9:
10:  <CFSET nTypeID = URL.TypeID>
11:
12:
13:  <!-- Find the community type based on the passed TypeID -->
14:  <cfquery name="qryFindComm" datasource="#sourceName#">
15:    SELECT *
16:    FROM CommTypes
17:    WHERE TypeID = #nTypeID#
18:  </cfquery>
19:
20:
21:  <cfquery name="qryParameters" datasource="#sourceName#">
22:    SELECT commtype_param.TypeID, commtype_param.agency_id, commtype_param.param_name, commtype_param.param_value,
23:           commtype_param.param_cntr,
24:           param_defs.description, param_defs.label, param_defs.displayOrder, param_defs.restrictions, param_defs.type
25:    FROM param_defs, commtype_param
26:    WHERE commtype_param.TypeID=#nTypeID#
27:    AND commtype_param.param_id = param_defs.id
28:    ORDER BY commtype_param.param_cntr,param_defs.displayOrder
29:  </cfquery>
30:
31:  <!-- Parameter names for the image fields -->
32:  <cfquery name="qryParamNames" datasource="#sourceName#">
33:    SELECT
34:      DISTINCT id, name, description, label, displayOrder, restrictions, type, selectOptions
35:    FROM param_defs
36:    WHERE securityLevel=1
37:    AND dataGroup = 7
38:    ORDER BY displayOrder
39:  </cfquery>
40:
41:  <!-- qryImageTypes will load the image types for the pull down while
42:       adding or editing a photo -->
43:  <cfquery name="qryImageTypes" datasource="#sourceName#">
44:    SELECT label,counter,value,agency_id
45:    FROM param_allowed
46:    WHERE param_allowed.id = 9
47:    ORDER BY param_allowed.counter
48:  </cfquery>

```

```

49:      <!-- Delimited lists for various uses -->
50:      <cfset listLabels = ValueList(qryParamNames.label)> <!-- "Use Name" -->
51:      <cfset listFieldNames = ValueList(qryParamNames.name)> <!-- "CommTitle" -->
52:      <cfset listFieldTypes = ValueList(qryParamNames.type)> <!-- TEXT, Field, etc. -->
53:      <cfset listFieldOptions = QuotedValueList(qryParamNames.selectOptions,"|")>
54:
55:
56:
57:      <html>
58:      <head>
59:          <cfoutput>
60:              <title>#ap_backofficeName# Backoffice</title>
61:          </cfoutput>
62:          <link rel="stylesheet" href="style1.css" type="text/css">
63:          <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
64:      </head>
65:
66:      <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
67:
68:      <p><cfinclude template="header.cfm"></p>
69:
70:      <cfoutput>
71:
72:      <CFSET nTotalCols = qryParamNames.recordCount+2>
73:      <CFSET aFieldValues = ArrayNew(1)>
74:
75:      <CFIF URL.Action is "View">
76:          <!-- Set default values for the edit fields -->
77:          <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
78:              <CFSET aFieldValues[nIndex] = "">
79:          </CFLOOP>
80:
81:      <CFELSEIF URL.Action is "Add">
82:          <CFSET URL.Action = "View">
83:      <CFELSEIF URL.Action is "Edit">
84:          <!-- A Paragraph has been selected for editing -->
85:      <CFELSEIF URL.Action is "Deleted">
86:          <!-- Delete the selected image -->
87:          <!-- Set default values for the edit fields -->
88:          <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
89:              <CFSET aFieldValues[nIndex] = "">
90:          </CFLOOP>
91:
92:      <CFSET URL.Action = "View">
93:      <CFELSEIF URL.Action is "Updated">
94:          <!-- Set default values for the edit fields -->
95:          <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
96:              <CFSET aFieldValues[nIndex] = "">
97:          </CFLOOP>

```

```
98: <CFSET URL.Action = "View">
99: </CFIF>
100:
101: <p>
102: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
103: <tr bgcolor="cccc99"><td colspan="2"><span class="h2"><b>Online Community Types</b></span></td></tr>
104: <tr bgcolor="cccccc"><td colspan="2"><b>General Online Community Type Information</b></td>
105: <tr bgcolor="eeeeee">
106: <td width="20%">Community Type:</td>
107: <td>
108: <form name="frmCommInfo" enctype="multipart/form-data" action="commTypeUpdate.cfm?TypeID=#TypeID#" method="post">
109: <input type="text" name="edtCommName" value="#qryFindComm.Name#"></td>
110: </tr>
111: <tr bgcolor="eeeeee">
112: <td width="20%">
113: Header Image:</td>
114: <td>
115: <input type="FILE" name="edtHeader">
116: <cfif qryFindComm.recordCount gt 0><em>Currently: #getFileFromPath(qryFindComm.headerFilename)#</em></cfif></td>
117: </tr>
118: <tr bgcolor="eeeeee">
119: <td width="20%">Footer Image:</td>
120: <td>
121: <input type="FILE" name="edtFooter">
122: <cfif qryFindComm.recordCount gt 0><em>Currently: #getFileFromPath(qryFindComm.footerFilename)#</em></cfif></td>
123: </tr>
124: <tr bgcolor="eeeeee">
125: <td width="20%">Available Dates:</td>
126: <td>From <input type="TEXT" size="10" name="edtStartDate" value="#DateFormat(qryFindComm.startdate,"mm/dd/yyyy")#"> To
127: <input type="TEXT" size="10" name="edtStopDate" value="#dateformat(qryFindComm.stopDate,"mm/dd/yyyy")#"></td>
128: </tr>
129: <tr bgcolor="eeeeee">
130: <td width="20%">Primary Picture:</td>
131: <td>
132: <input type="FILE" name="edtPrimaryPic">
133: <cfif qryFindComm.recordCount gt 0><em>Currently: #getFileFromPath(qryFindComm.primaryPic)#</em></cfif></td>
134: </tr>
135: <tr bgcolor="eeeeee">
136: <td width="20%">Description:</td>
137: <td>
138: <textarea name="edtDesc" rows="5" cols="80" wrap="virtual">#qryFindComm.Description#</textarea>
139: </td>
140: </tr>
141:
142: <tr bgcolor="eeeeee">
143: <td colspan="2">
144: <cfif qryFindComm.recordCount is 0>
145: <input type="submit" name="btnUpdate" value="Add Type Info">
```

```

146:         <input type="reset" value="Reset Info">
147:     <cfelse>
148:         <input type="submit" name="btnUpdate" value="Update Type Info">
149:         <input type="reset" value="Reset Info">
150:         <input type="submit" name="btnDelete" value="Delete Type">
151:     </cfif>
152: </td>
153: </tr>
154: </FORM>
155:
156: </table>
157: </p>
158:
159:
160:
161: <!-- Here is the paragraph information already entered -->
162:
163: <cfif qryFindComm.recordcount gt 0>
164: <p><table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
165: <!-- First see if there are any images to display -->
166: <cfif #qryParameters.recordcount# is 0>
167: <tr bgcolor="cccccc">
168: <td><b class="h2">No paragraphs are associated with this community type</b></td>
169: </td></tr>
170: <cfelse>
171: <!-- there are paragraphs, so display the labels first -->
172: <tr bgcolor="cccccc">
173: <cfloop from="1" TO="#listlen(listLabels)#" index="nIndex">
174: <td align="center"><b>#listGetAt(listLabels, nIndex)#</b></td>
175: </cfloop>
176: <td><b></td></tr>
177: </cfif>
178:
179: <!-- Now for the actual data -->
180: <CFSET lEditrow = False>
181: <CFSET cImageName = "">
182: <CFSET nRow = 0>
183: <CFSET nOldParamCounter = -1>
184: <CFSET nParamCounter = -1>
185: <CFSET nMaxParamCounter = -1>
186: <CFSET nColumn = 0>
187:
188: <CFLOOP QUERY="qryParameters">
189: <CFSET nRow = nRow + 1>
190: <CFIF qryParameters.param_name IS listGetAt(listFieldNames, 1)>
191: <CFSET nColumn = 0>
192: <CFSET nMaxParamCounter = max(nMaxParamCounter, qryParameters.param_cntr)>
193: <CFSET nParamCounter = qryParameters.param_cntr>
194: <CFIF nParamCounter is URL.param_counter>

```

```

195:         <CFSET lEditrow = TRUE>
196:     <CFELSE>
197:         <CFSET lEditrow = FALSE>
198:     </CFIF>
199:     <tr bgcolor="eeeeee">
200:     </CFIF>
201:     <CFSET nColumn = nColumn + 1>
202:     <CFIF lEditrow>
203:         <CFSET aFieldValues[nColumn] = qryParameters.param_value>
204:     </CFIF>
205:     <CFIF listGetAt(listFieldNames,nColumn) is "imgType">
206:         <td <CFIF lEditrow IS true>bgcolor="ffffff"</CFIF> valign="top">
207:         <CFIF qryParameters.param_value is "0">
208:             Standard Photo
209:         <CFIF lEditrow is true><CFSET URL.ImageType = "0"></CFIF>
210:         <CFELSEIF qryParameters.param_value is "1">
211:             Bamboo Image
212:         <CFIF lEditrow is true><CFSET URL.ImageType = "1"></CFIF>
213:         <CFELSEIF qryParameters.param_value is "2">
214:             IPIX Image
215:         <CFIF lEditrow is true><CFSET URL.ImageType = "2"></CFIF>
216:     <CFELSE>
217:         #qryParameters.param_value#
218:         <CFIF lEditrow is true><CFSET URL.ImageType = "-1"></CFIF>
219:     </CFIF>
220:     </td>
221: <CFELSE>
222:     <td <CFIF lEditrow IS true>bgcolor="ffffff"</CFIF> valign="top">#qryParameters.param_value#</td>
223: </CFIF>
224:
225: <CFIF nColumn is nTotalCols-2> <!-- the last column with info was displayed -->
226:     <td <CFIF lEditrow is true>bgcolor="ffffff"</CFIF> colspan="2" valign="top">
227:     <a href="commTypeMaint.cfm?Action=Edit&TypeID=#URL.TypeID&param_counter=#qryParameters.param_cntr#">Edit</a><hr>
228:     <a
229:         href="commTypeDataUpdate.cfm?Action=Delete&TypeID=#URL.TypeID&param_counter=#qryParameters.param_cntr#">Delete</a></td>
230:     </td>
231:     </tr>
232:     <CFSET nColumn = 0>
233:     </CFIF>
234: </CFLOOP>
235: </table></p>
236:
237:
238: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
239: <!-- Now allow the user to add or edit an image -->
240: <tr bgcolor="cccccc">
241: <td colspan="#nTotalCols#">
242:     <CFIF #URL.Action# is "Add">

```

```

243: <b>Add A Paragraph</b>:
244: <input type="hidden" name="Action" VALUE="Add">
245: <CFELSEIF #URL.Action# is "Edit">
246: <b>Edit Selected Paragraph:</b>
247: <input type="hidden" name="Action" VALUE="Edit">
248: <CFELSEIF #URL.Action# is "View">
249: <b>Add A Paragraph:</b>
250: <input type="hidden" name="Action" VALUE="Add">
251: </CFIF>
252: </td>
253: </tr>
254:
255: <tr>
256: <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
257: <td bgcolor="eeeeee" valign="bottom">
258: <!-- Moved the text area (Paragraph) to a row immediately under the other input data --SIF 0408CC-->
259: <cfif findNCase("Text", #listGetAt(listLabels, nIndex)#) neq 0>
260: <cfset labelId = #nIndex#>
261: <cfelse>
262: <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, nIndex)#</b></font>
263: </cfif>
264: </td>
265: </CFLOOP>
266: </tr>
267:
268: <form name="frmValues" enctype="multipart/form-data" action="commTypeDataUpdate.cfm" method="post">
269: <tr valign="top" bgcolor="eeeeee">
270: <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
271: <CFSET cFieldType = ucase(trim(listGetAt(listFieldTypes, nIndex)))>
272: <CFIF cFieldType is "TEXT">
273: <CFIF listGetAt(listFieldNames, nIndex) is "imgType">
274: <td>
275: <CFIF #URL.Action# is "Edit">
276: <CFIF aFieldValues[nIndex] is "0">
277: <I>Standard Photo</I><br>
278: <CFELSEIF aFieldValues[nIndex] is "1">
279: <I>Bamboo Image</I><br>
280: <CFELSEIF aFieldValues[nIndex] is "2">
281: <I>PIX Image</I><br>
282: <CFELSE>
283: <I>#aFieldValues[nIndex]#</I><br>
284: </CFIF>
285: </CFIF>
286: <SELECT NAME="FIELD#nIndex#">
287: <CFLOOP QUERY="qryImageTypes">
288: <CFIF URL.ImageType is "0" and qryImageTypes.value is "0">
289: <CFSET lShowOption = true>
290: <CFELSEIF URL.ImageType is not "0" and qryImageTypes.value is not "0">
291: <CFSET lShowOption = true>

```



```

292: <CFELSE>
293: <CFSET lShowOption = False>
294: </CFIF>
295: <CFIF lShowOption is true>
296: <OPTION value=#qryImageTypes.value# <CFIF #trim(aFieldValues[nIndex])# is
#trim(qryImageTypes.value)#>SELECTED</CFIF>>#trim(label)#</OPTION>
297: </CFIF>
298: </CFLOOP>
299: </SELECT>
300: <br>
301: <CFIF URL.Action is not "Edit">
302: <!-- If they want to change the image type, they will need to delete the image and reenter it -->
303: <CFIF URL.ImageType is "0">
304: <font face="Verdana, Arial" size="1"><a
href="commTypeMaint.cfm?Action=#URL.Action#&TypeID=#URL.TypeID#&ImageType=1&param_counter=#URL.param_counter#">To Add Bamboo
or IPIX<br>images, Click Here</a></font>
<CFELSE>
305: <font face="Verdana, Arial" size="1"><a
href="commTypeMaint.cfm?Action=#URL.Action#&TypeID=#URL.TypeID#&ImageType=0&param_counter=#URL.param_counter#">To Add a
standard photo, Click Here</a></font>
</CFIF>
307: </CFIF>
308: </td>
309: </td>
310: <CFELSE>
311: <td>
312: <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
313: </td>
314: </CFIF>
315: <CFELSEIF cFieldType is "FILE">
316: <td>
317: <CFIF #URL.Action# is "Edit">
318: <CFIF URL.ImageType is "0">
319: <I>#getFileFromPath(aFieldValues[nIndex])#</I><br>
320: <CFELSE>
#FieldValues[nIndex]#<br>
321: </CFIF>
322: </td>
323: </CFIF>
324: <CFIF URL.ImageType is "0">
325: <INPUT TYPE="FILE" NAME="Field#nIndex#" SIZE="20">
326: <CFELSE>
327: <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
328: </CFIF>
329: </td>
330: <CFELSEIF cFieldType is "TEXTAREA">
331: <td>
332: <!-- Moved the text area to a row immediately under the other input data --SPE 0404300-->
333: <cfset textId = #nIndex#>
334: </td>
335: <CFELSEIF cFieldType is "CHECKBOX">

```

```

336: <td align="center">
337: <input type="checkbox" name="Field#nIndex#" size="70" <CFIF #aFieldValues[nIndex]# is "ON">CHECKED</CFIF>>
338: </td>
339: <CFELSEIF cFieldType is "SELECT">
340: <td>
341: <CFSET listColOptions = replace(ListGetAt(listFieldOptions, nIndex, "|"), ",", "All")>
342: <CFIF listlen(listColOptions) gt 0>
343: <SELECT NAME="Field#nIndex#">
344: <CFLOOP FROM="1" TO="#listlen(listColOptions)#" INDEX="nListInd">
345: <CFSET cOption = listGetAt(listColOptions, nListInd, ", ")>
346: <OPTION <CFIF #aFieldValues[nIndex]# is #cOption#>SELECTED</CFIF>>#cOption#
347: </CFLOOP>
348: </SELECT>
349: </CFIF>
350: </td>
351: </CFIF>
352: </CFLOOP>
353: </tr>
354: <tr valign="top" bgcolor="eeeeee">
355: <!-- Moved the text area to a row immediately under the other input data --SFE 0404800-->
356: <td colspan="#listlen(listLabels)#">
357: <cfif isDefined("textId")>
358: <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, labelId)</b></font><br>
359: <TEXTAREA ROWS="8" COLS="80" WRAP="VIRTUAL" NAME="Field#textId#">#aFieldValues[textId]#</TEXTAREA>
360: </cfif>
361: </td>
362: </tr>
363: <tr bgcolor="eeeeee">
364: <td colspan="#nTotalCols#">
365: <CFIF nMaxParamCounter is -1>
366: <CFSET nMaxParamCounter = 1>
367: <CFELSE>
368: <CFSET nMaxParamCounter = nMaxParamCounter + 1>
369: </CFIF>
370: <CFIF #URL.Action# is "View">
371: <input type="hidden" name="Action" value="ADD">
372: <input type="submit" value="Add New Paragraph" name="btnSubmit">
373:
374: <input type="hidden" name="param_counter" value="#nMaxParamCounter#">
375: <CFELSEIF #URL.Action# is "Edit">
376: <input type="hidden" name="Action" value="EDIT">
377: <input type="submit" value="Update Paragraph">
378: <input type="reset" value="Reset Information">
379: <input type="button" value="Cancel" name="btnSubmit">
380: <ONCLICK="location.href='commTypeMaint.cfm?TypeID=#URL.TypeID#&Action=View'">
381: <input type="hidden" name="param_counter" value="#URL.Param_Counter#">
382: </td>
383: </tr>

```

```
384:      <CFSET nImageTypeField = listFindNoCase(listFieldNames,"imgType")>
385:
386:
387:      <input type="hidden" name="imageField" VALUE="#nImageTypeField#">
388:      <input type="hidden" name="TypeID" VALUE="#URL.TypeID#">
389:      <input type="hidden" name="FieldLabels" VALUE="#listLabels#">
390:      <input type="hidden" name="FieldTypes" VALUE="#listFieldTypes#">
391:      <input type="hidden" name="Field_Names" VALUE="#listFieldNames#">
392:      </form>
393:      </table></p>
394:
395:      </cfif>
396:      </cfoutput>
397:
398:      </body>
399:      </html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <CFPARAM NAME="URL.TypeID" DEFAULT="-1">
4:
5:  <CFSET nTypeID = URL.TypeID>
6:
7:  <html>
8:  <head>
9:    <title>Update Community Type Information</title>
10:  </head>
11:
12:
13:  <body>
14:
15:    <CFIF isDefined("FORM.btnUpdate")>
16:      <CFQUERY NAME="qryFindComm" DATASOURCE="#SourceName#">
17:        SELECT * FROM CommTypes
18:        WHERE TypeID=#nTypeID#
19:      </CFQUERY>
20:
21:      <CFIF qryFindComm.recordCount is 0> <!--- This is a new community --->
22:        <CFSET nTypeID=-1>
23:        <CFTRANSACTION>
24:          <CFSET cDesc = trim(preserveSingleQuotes(FORM.edtDesc))>
25:
26:          <CFIF len(trim(FORM.edtStartDate)) is 0>
27:            <CFSET cStartDate = now()>
28:          <cfelse>
29:            <cftry>
30:              <cfset cStartDate = createODBCDate(FORM.edtStartDate)>
31:            <cfcatch type="any">
32:              <cfset cStartDate = now()>
33:            </cfcatch>
34:          </cftry>
35:        </cfif>
36:
37:        <CFIF len(trim(FORM.edtStopDate)) is 0>
38:          <CFSET cStopDate = createDate(2999,12,31)>
39:        <cfelse>
40:          <cftry>
41:            <cfset cStopDate = createODBCDate(FORM.edtStopDate)>
42:          <cfcatch type="any">
43:            <cfset cStopDate = createDate(2999,12,31)>
44:          </cfcatch>
45:        </cftry>
46:      </cfif>
47:
48:      <CFQUERY NAME="qryAddComm" DATASOURCE="#SourceName#">
49:        INSERT INTO CommTypes(Name, Description, StartDate, StopDate)

```

```
50: VALUES ('#FORM.edtCommName', '#desc', '#startdate', '#stopdate')
51: </CFQUERY>
52:
53: <CFQUERY NAME="qryGetID" DATASOURCE="#SourceName#">
54:   SELECT max(TypeID) as newCommunityID
55:   FROM CommTypes
56: </CFQUERY>
57:
58: <CFSET nTypeID = qryGetID.newCommunityID>
59: </CFTRANSACTION>
60: <CFIF nTypeID is -1> <!-- Insertion failed -->
61:
62: <CFELSE> <!-- Insertion successful -->
63:
64:   <!-- Now create the directory and upload the files -->
65:
66:   <CFSET cFilePath = #ap_CommType_path# & #nTypeID# & "\">
67:
68:   <CFTRY> <!-- Create the directory and catch exception if directory already exists -->
69:     <CFDIRECTORY
70:       DIRECTORY="#cFilePath#"
71:       ACTION="CREATE"
72:     >
73:     <CFCATCH TYPE="ANY">
74:       </CFCATCH>
75:     </CFTRY>
76:
77:     <CFIF len(FORM.edtHeader) gt 0>
78:       <CFFILE
79:         DESTINATION=#cFilePath#
80:         ACTION="UPLOAD"
81:         NAMECONFLICT="OVERWRITE"
82:         FILEFIELD="edtHeader">
83:
84:       <CFSET cHeaderName = FILE.ServerFile>
85:     <CFELSE>
86:       <CFSET cHeaderName="">
87:     </CFIF>
88:
89:     <CFIF len(FORM.edtFooter) gt 0>
90:       <CFFILE
91:         DESTINATION=#cFilePath#
92:         ACTION="UPLOAD"
93:         NAMECONFLICT="OVERWRITE"
94:         FILEFIELD="edtFooter">
95:       <CFSET cFooterName = FILE.ServerFile>
96:     <CFELSE>
97:       <CFSET cFooterName = "">
98:     </CFIF>
```

```
99:
100: <CFIF len(FORM.edtprimaryPic) gt 0>
101: <CFFILE
102:     DESTINATION=#cFilePath#
103:     ACTION="UPLOAD"
104:     NAMECONFLICT="OVERWRITE"
105:     FILEFIELD="edtPrimaryPic">
106: <CFSET cPrimaryPic = FILE.ServerFile>
107: <CFELSE>
108: <CFSET cPrimaryPic = "">
109: </CFIF>
110:
111: <cftransaction>
112: <CFQUERY NAME="qryEditComm" DATASOURCE="#SourceName#">
113:     UPDATE CommTypes
114:     SET headerFileName=#cHeaderName#, footerFileName=#cFooterName#, primaryPic=#cPrimaryPic#,
115:     DataPath='\CommType\#nTypeID#
116:     WHERE TypeID = #nTypeID#
117: </cfquery>
118: </cftransaction>
119:
120: </CFIF>
121: <CFLOCATION url="commTypeMaint.cfm?TypeID=#nTypeID#" addtoken="no">
122:
123: <CFELSE> <!-- Editing an existing community -->
124:
125: <CFTRANSACTION>
126: <CFSET cDesc = trim(preserveSingleQuotes(FORM.edtDesc))>
127:
128: <CFIF len(trim(FORM.edtStartDate)) is 0>
129: <CFSET cStartDate = now()>
130: <cfelse>
131: <cftry>
132: <cfset cStartDate = createODBCDate(FORM.edtStartDate)>
133: <cfcatch type="any">
134: <cfset cStartDate = now()>
135: </cfcatch>
136: </cftry>
137: </cfif>
138:
139: <CFIF len(trim(FORM.edtStopDate)) is 0>
140: <CFSET cStopDate = createDate(2999,12,31)>
141: <cfelse>
142: <cftry>
143: <cfset cStopDate = createODBCDate(FORM.edtStopDate)>
144: <cfcatch type="any">
145: <cfset cStopDate = createDate(2999,12,31)>
146: </cfcatch>
147: </cftry>
```

```

148: </cfif>
149:
150: <CFQUERY NAME="qryEditComm" DATASOURCE="#SourceName#">
151:   UPDATE CommTypes
152:   SET Name='#FORM.edtCommName#', Description='#cDesc#',
153:       StartDate=#cStartDate#, StopDate=#cStopDate#
154:   WHERE TypeID = #nTypeID#
155: </cfquery>
156: </cftransaction>
157:
158: <CFSET cFilePath = #ap_Commtype_path# & #nTypeID# & "\">
159: <!-- The directory should already exist, but just in case... -->
160: <CFTRY> <!-- Create the directory and catch exception if already exists -->
161:   <CFDIRECTORY
162:     DIRECTORY="#cFilePath#"
163:     ACTION="CREATE"
164:   >
165:   <CFCATCH TYPE="ANY">
166:     </CFCATCH>
167:   </CFTRY>
168:
169: <CFIF len(FORM.edtHeader) gt 0>
170:   <CFFILE
171:     DESTINATION=#cFilePath#
172:     ACTION="UPLOAD"
173:     NAMECONFLICT="OVERWRITE"
174:     FILEFIELD="edtHeader">
175:     <CFSET cHeaderName = FILE.ServerFile>
176:   <CFELSE>
177:     <CFSET cHeaderName=qryFindComm.headerFilename>
178:   </CFIF>
179:
180: <CFIF len(FORM.edtFooter) gt 0>
181:   <CFFILE
182:     DESTINATION=#cFilePath#
183:     ACTION="UPLOAD"
184:     NAMECONFLICT="OVERWRITE"
185:     FILEFIELD="edtFooter">
186:     <CFSET cFooterName = FILE.ServerFile>
187:   <CFELSE>
188:     <CFSET cFooterName = qryFindComm.footerFilename>
189:   </CFIF>
190:
191: <CFIF len(FORM.edtPrimaryPic) gt 0>
192:   <CFFILE
193:     DESTINATION=#cFilePath#
194:     ACTION="UPLOAD"
195:     NAMECONFLICT="OVERWRITE"
196:     FILEFIELD="edtPrimaryPic">

```

```

197:      <CFSET cPrimaryPic = FILE.ServerFiles>
198:    <CFELSE>
199:      <CFSET cPrimaryPic = qryFindComm.primaryPic>
200:    </CFIF>
201:
202:    <cftransaction>
203:      <CFQUERY NAME="qryEditComm" DATASOURCE="#SourceName#">
204:        UPDATE CommTypes
205:        SET headerFileName= '#cHeaderName#', footerFileName= '#cFooterName#', primaryPic= '#cPrimaryPic#',
206:          DataPath= '\CommType\#nTypeID#'
207:        WHERE TypeID = #nTypeID#
208:      </cfquery>
209:    </cftransaction>
210:
211:    <CFLOCATION url="commTypeMaint.cfm?TypeID=#nTypeID#" addtoken="no">
212:  </CFIF>
213:
214:  <CFELSEIF IsDefined("FORM.btnDelete")>  <!-- Delete the selected community -->
215:    <cftransaction>
216:      <cfquery name="qryDeleteComm" datasource="#SourceName#">
217:        DELETE commtype_param
218:        WHERE TypeID=#nTypeID#
219:      </cfquery>
220:
221:      <cfquery name="qryDeleteComm" datasource="#SourceName#">
222:        DELETE CommTypes
223:        WHERE TypeID=#nTypeID#
224:      </cfquery>
225:    </cftransaction>
226:
227:    <!-- First delete the directory files -->
228:    <CFSET cFilePath = #ap_CommType_path# & #nTypeID# & "\">
229:
230:    <CFDIRECTORY ACTION="LIST"
231:      DIRECTORY="#cFilePath#"
232:      NAME="qryDirList"
233:    >
234:
235:    <CFLOOP QUERY="qryDirList">
236:      <CFIF qryDirList.name IS NOT "." AND qryDirList.name IS NOT "..">
237:        <CFSET cFilename = cFilePath & qryDirList.name>
238:        <CFFILE ACTION="DELETE"
239:          FILE="#cFilename#"
240:        >
241:      </CFIF>
242:    </CFLOOP>
243:
244:    <!-- Now delete the whole directory -->
245:    <CFSET cFilePath = #ap_CommType_path# & #nTypeID# & "\">

```



```
246:
247: <CFDIRECTORY ACTION="DELETE"
248:   DIRECTORY="#cfilePath#"
249: >
250:
251:   <cflocation url="commTypeAdm.cfm" addtoken="no">
252:   </CFIF>
253:
254: </body>
255: </html>
256:
```

```

50: prop_main.status,prop_main.findPropType
51: <cfif #FORM.communityID# gt -1>
52: <cfelseif #FORM.Region# is not "*">,communities.region
53: </cfif>
54: FROM prop_main<cfif #FORM.communityID# gt -1><cfelseif #FORM.Region# is not "*">,communities</cfif>
55: WHERE (price >= #minPrice#) AND
56: (price <= #maxPrice#) AND
57: (bedroom >= '#minBedrooms#') AND
58: (bath >= '#minBathrooms#')
59: AND (status IN (#cStatus#))
60: <cfif #county# IS NOT "All">
61: AND (county = '#county#')
62: </cfif>
63: <cfif #FORM.communityID# gt -1>
64: AND (prop_main.communityID = #FORM.communityID#)
65: <cfelseif #FORM.Region# is not "*">
66: AND (communities.communityID = prop_main.communityID)
67: <cfelseif #FORM.PropertyTypeID# gt -1>
68: AND ('#FORM.PropertyTypeID#' IN (prop_main.findPropType))
69: </cfif>
70: </cfquery>
71:
72:
73: <html>
74: <head>
75: <title>DPO Homes</title>
76: <link rel="stylesheet" href="style1.css" type="text/css">
77: <script language="JavaScript" src="menu.js"></script>
78: <script language="JavaScript1.2" src="menu2.js"></script>
79: </head>
80:
81: <body bgcolor="#ffffff" marginheight="0" marginwidth="0" leftmargin="0" topmargin="0" onLoad="Sniff();LoadImgs();">
82: <!-- Token List --><cfoutput>#ls_numberTokens# <br>
83: #find(ls_numberTokens, minValue)#<br>
84: #replace(minValue, "$", "")#<br>
85: #minValue#<br>
86: </cfoutput> -->
87: <!-- ~~~~~~ begin outer table : left strip ~~~~
88:
89: <table border="0" cellpadding="0" cellspacing="0">
90: <tr><td bgcolor="#6666cc" width="5"><b><td>
91: <!-- ~~~~~~ end left strip ~~~~
92:
93: <td valign="top">
94: <!-- ~~~~~~ begin page header : nested table -->
95: <table border="0" cellpadding="0" cellspacing="0" width="777">
96: <tr><td width="299" height="76">
97: <a href="index.cfm"></a>
98: </td><td valign="middle">

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2: <!-- <cfset ls_numberTokens = "$,." -->
3: <cfif findOneOf("ls_numberTokens", minValue, 1) neq 0>
4:   <cfset minValue = replace(minValue, ls_numberTokens, "")>
5: </cfif>
6: <cfif findOneOf("ls_numberTokens", maxValue, 1)>
7:   <cfset maxValue = replace(maxValue, ls_numberTokens, "")>
8: </cfif>
9: <cftry>
10:   <cfset minPrice = #val(minValue)#>
11:   <cfcatch type="any">
12:     <cfset minPrice=0>
13:   </cfcatch>
14: </cftry>
15:
16:   <cftry>
17:     <cfset maxPrice = #val(maxValue)#>
18:     <cfcatch type="any">
19:       <cfset maxPrice=999999999>
20:     </cfcatch>
21:   </cftry>
22:
23:   <cftry>
24:     <cfset minBedrooms = #val(minBedrooms)#>
25:     <cfcatch type="any">
26:       <cfset minBedrooms=0>
27:     </cfcatch>
28:   </cftry>
29:
30:   <cftry>
31:     <cfset minBathrooms = #val(minBathrooms)#>
32:     <cfcatch type="any">
33:       <cfset minBathrooms=0>
34:     </cfcatch>
35:   </cftry>
36:
37:   <cfparam name="county" default="All">
38:
39:   <cfparam name="FORM.Region" default="*">
40:   <cfparam name="FORM.communityID" default="-1">
41:   <cfparam name="FORM.propertyTypeID" default="-1">
42:   <!-- Community takes precedence over region -->
43:
44:   <cfinclude template="proplists.cfm">
45:
46:   <cfset cStatus = listFindNoCase(ls_SearchStatus, "New")>
47:
48:   <cfquery name="qSearchResults" datasource="RealEstateDev">
49:     SELECT prop_main.prop_id, prop_main.name, prop_main.price, prop_main.bedroom, prop_main.bath, prop_main.communityID,

```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN"
2:
3:  <CFPARAM NAME="URL.CommunityID" DEFAULT="-1">
4:
5:  <CFSET nCommunityID = URL.CommunityID>
6:
7:  <html>
8:  <head>
9:    <title>Update Community Information</title>
10:  </head>
11:
12:
13:  <body>
14:
15:  <CFIF isDefined("FORM.btnUpdate")>
16:    <CFQUERY NAME="qryFindComm" DATASOURCE="#SourceName#">
17:      SELECT * FROM Communities
18:      WHERE communityID=#nCommunityID#
19:    </CFQUERY>
20:
21:    <CFIF qryFindComm.recordCount is 0> <!-- This is a new community -->
22:      <CFSET nCommunityID=-1>
23:      <CFTRANSACTION>
24:        <CFSET cDesc = trim(preserveSingleQuotes(FORM.edtDesc))>
25:        <CFSET cAltURL = trim(preserveSingleQuotes(FORM.edtAltURL))>
26:
27:        <CFIF len(trim(FORM.edtStartDate)) is 0>
28:          <CFSET cStartDate = now()>
29:        </cfelse>
30:        <cftry>
31:          <cfset cStartDate = createODBCDate(FORM.edtStartDate)>
32:          <cfcatch type="any">
33:            <cfset cStartDate = now()>
34:          </cfcatch>
35:        </cftry>
36:      </cfif>
37:
38:      <CFIF len(trim(FORM.edtStopDate)) is 0>
39:        <CFSET cStopDate = createDate(2999,12,31)>
40:      </cfelse>
41:      <cftry>
42:        <cfset cStopDate = createODBCDate(FORM.edtStopDate)>
43:        <cfcatch type="any">
44:          <cfset cStopDate = createDate(2999,12,31)>
45:        </cfcatch>
46:      </cftry>
47:    </cfif>
48:
49:    <cfif NOT isDefined("FORM.edtCommType")>

```

```

50:      <cfset cCommType = "">
51:    <cfelse>
52:      <cfset cCommType = FORM.edtCommType>
53:    </cfif>
54:
55:    <CFQUERY NAME="qryAddComm" DATASOURCE="#SourceName#">
56:      INSERT INTO Communities (Name, Description, Region, CommunityType, StartDate, StopDate, distributorID, AlternateURL)
57:      VALUES ('#FORM.edtCommName#', '#cDesc#', '#FORM.edtRegion#', '#cCommType#', #cStartDate#, #cStopDate#,
58:      #ap_distributorID#, '#cAltURL#')
59:    </CFQUERY>
60:
61:    <CFQUERY NAME="qryGetID" DATASOURCE="#SourceName#">
62:      SELECT max(CommunityID) as newCommunityID
63:      FROM Communities
64:    </CFQUERY>
65:
66:    <CFSET nCommunityID = qryGetID.newCommunityID>
67:    </CFTRANSACTION>
68:    <CFIF nCommunityID is -1> <!-- Insertion failed -->
69:
70:    <CFELSE> <!-- Insertion successful -->
71:
72:    <!-- Now create the directory and upload the files -->
73:
74:    <CFSET cFilePath = #ap_Communities_path# & #nCommunityID# & "\">
75:
76:    <CFTRY> <!-- Create the directory and catch exception if directory already exists -->
77:      <CFDIRECTORY
78:        DIRECTORY="#cFilePath#"
79:        ACTION="CREATE"
80:      >
81:      <CFCATCH TYPE="ANY">
82:        </CFCATCH>
83:      </CFTRY>
84:
85:      <CFIF len(FORM.edtHeader) gt 0>
86:        <CFFILE
87:          DESTINATION="#cFilePath#
88:          ACTION="UPLOAD"
89:          NAMECONFLICT="OVERWRITE"
90:          FILEFIELD="edtHeader">
91:
92:        <CFSET cHeaderName = FILE.ServerFile>
93:      <CFELSE>
94:        <CFSET cHeaderName="">
95:      </CFIF>
96:
97:      <CFIF len(FORM.edtFooter) gt 0>
98:        <CFFILE

```

```

98:  DESTINATION=#cFilePath#
99:  ACTION="UPLOAD"
100:  NAMECONFLICT="OVERWRITE"
101:  FILEFIELD="edtFooter">
102:  <CFSET cFooterName = FILE.ServerFile>
103:  <CFELSE>
104:  <CFSET cFooterName = "">
105:  </CFIF>
106:
107:  <CFIF len(FORM.edtprimaryPic) gt 0>
108:  <CFFILE
109:  DESTINATION=#cFilePath#
110:  ACTION="UPLOAD"
111:  NAMECONFLICT="OVERWRITE"
112:  FILEFIELD="edtPrimaryPic">
113:  <CFSET cPrimaryPic = FILE.ServerFile>
114:  <CFELSE>
115:  <CFSET cPrimaryPic = "">
116:  </CFIF>
117:
118:  <cfttransaction>
119:  <CFQUERY NAME="qryEditComm" DATASOURCE="#SourceName#">
120:  UPDATE Communities
121:  SET headerFileName=#cHeaderName#, footerFileName=#cFooterName#, primaryPic=#cPrimaryPic#,
122:  DataPath='\Communities\#nCommunityID#
123:  WHERE CommunityID = #nCommunityID#
124:  </cfquery>
125:  </cfttransaction>
126:
127:  </CFIF>
128:  <CFLOCATION url="commMaint.cfm?CommunityID=#nCommunityID#" addtoken="no">
129:
130:  <CFELSE> <!-- Editing an existing community --->
131:
132:  <CFTRANSACTION>
133:  <CFSET cDesc = trim(preserveSingleQuotes(FORM.edtDesc))>
134:  <CFSET cAltURL = trim(preserveSingleQuotes(FORM.edtAltURL))>
135:
136:  <CFIF len(trim(FORM.edtStartDate)) is 0>
137:  <CFSET cStartDate = now()>
138:  <cfelse>
139:  <cftry>
140:  <cfset cStartDate = createODBCDate(FORM.edtStartDate)>
141:  <cfcatch type="any">
142:  <cfset cStartDate = now()>
143:  </cfcatch>
144:  </cftry>
145:  </cfif>
146:

```

```

147: <CFIF len(trim(FORM.edtStopDate)) > 0 >
148: <CFSET cStopDate = createDate(2000,12,31)>
149: <cfelse>
150: <cftry>
151: <cfset cStopDate = createODBCDate(FORM.edtStopDate)>
152: <cfcatch type="any">
153: <cfset cStopDate = createDate(2000,12,31)>
154: </cfcatch>
155: </cftry>
156: </cfif>
157:
158: <cfif NOT isdefined("FORM.edtCommType")>
159: <cfset cCommType = "">
160: <cfelse>
161: <cfset cCommType = FORM.edtCommType>
162: </cfif>
163:
164: <CFQUERY NAME="qryEditComm" DATASOURCE="#SourceName#">
165: UPDATE Communities
166: SET Name='#FORM.edtCommName#', Description='#cDesc#', Region='#FORM.edtRegion#', CommunityType='#cCommType#',
167: StartDate=#cStartDate#, StopDate=#cStopDate#, distributorID=#ap_distributorID#,
168: alternateURL='#cAltURL#'
169: WHERE CommunityID = #nCommunityID#
170: </cfquery>
171: </cftransaction>
172:
173:
174: <CFSET cFilePath = #ap_Communities_path# & #nCommunityID# & "\">
175: <!-- The directory should already exist, but just in case... -->
176: <CFTRY> <!-- Create the directory and catch exception if directory already exists -->
177: <CFDIRECTORY
178: DIRECTORY="#cFilePath#"
179: ACTION="CREATE"
180: >
181: <CFCATCH TYPE="ANY">
182: </CFCATCH>
183: </CFTRY>
184:
185: <CFIF len(FORM.edtHeader) gt 0>
186: <CFFILE
187: DESTINATION=#cFilePath#
188: ACTION="UPLOAD"
189: NAMECONFLICT="OVERWRITE"
190: FILEFIELD="edtHeader">
191: <CFSET cHeaderName = FILE.ServerFile>
192: <CFELSE>
193: <CFSET cHeaderName=qryFindComm.headerFilename>
194: </CFIF>
195: <CFIF len(FORM.edtFooter) gt 0>

```

```

196: <CFFILE
197:   DESTINATION=#cFilePath#
198:   ACTION="UPLOAD"
199:   NAMECONFLICT="OVERWRITE"
200:   FILEFIELD="edtFooter">
201:   <CFSET cFooterName = FILE.ServerFile>
202: <CFELSE>
203:   <CFSET cFooterName = qryFindComm.footerFilename>
204: </CFIF>
205:
206: <CFIF len(FORM.edtPrimaryPic) gt 0>
207:   <CFFILE
208:     DESTINATION=#cFilePath#
209:     ACTION="UPLOAD"
210:     NAMECONFLICT="OVERWRITE"
211:     FILEFIELD="edtPrimaryPic">
212:   <CFSET cPrimaryPic = FILE.ServerFile>
213: <CFELSE>
214:   <CFSET cPrimaryPic = qryFindComm.primaryPic>
215: </CFIF>
216:
217: <cftransaction>
218:   <CFQUERY NAME="qryEditComm" DATASOURCE="#SourceName#">
219:     UPDATE Communities
220:     SET headerFileName='#cHeaderName#', footerFilename='#cFooterName#', primaryPic='#cPrimaryPic#',
221:       DataPath='\Communities\#nCommunityID#',
222:       WHERE CommunityID = #nCommunityID#
223:   </cfquery>
224: </cftransaction>
225:
226:   <CFLOCATION url="commMaint.cfm?CommunityID=#nCommunityID#" addtoken="no">
227: </CFIF>
228:
229: <CFELSEIF IsDefined("FORM.btnDelete")>   <!-- Delete the selected community --->
230: <cftransaction>
231:   <cfquery name="qryDeleteComm" datasource="#SourceName#">
232:     DELETE comm_param
233:     WHERE communityID=#nCommunityID#
234:   </cfquery>
235:
236:   <cfquery name="qryDeleteComm" datasource="#SourceName#">
237:     DELETE Communities
238:     WHERE CommunityID=#nCommunityID#
239:   </cfquery>
240: </cftransaction>
241:
242:   <!-- First delete the directory files --->
243:   <CFSET cFilePath = #ap_Communities_path# & #nCommunityID# & "\">
244:

```



```

      <!-- Now delete the whole directory --->
      <CFSET cFilePath = #ap_Communities_path# & #CommunityID# & "\">

```

```

245: <CFDIRECTORY ACTION="LIST"
246:   DIRECTORY="#cFilePath#"
247:   NAME="qryDirList"
248: >
249:
250: <CFLOOP QUERY="qryDirList">
251:   <CFIF qryDirList.name IS NOT "." AND qryDirList.name IS NOT "..">
252:     <CFSET cFilename = cFilePath & qryDirList.name>
253:     <CFFILE ACTION="DELETE"
254:       FILE="#cFilename#"
255:     >
256:   </CFIF>
257: </CFLOOP>
258:
259: <!-- Now delete the whole directory --->
260: <CFSET cFilePath = #ap_Communities_path# & #CommunityID# & "\">
261:
262: <CFDIRECTORY ACTION="DELETE"
263:   DIRECTORY="#cFilePath#"
264: >
265:
266: <cflocation url="commAdm.cfm" addtoken="no">
267: </CFIF>
268:
269:
270: </body>
271: </html>

```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2: <cfinclude template="include\security.cfm">
3:
4:
5: <cfparam name="URL.SortBy" default="Name">
6:
7: <cfquery name="qryDistributors" datasource="#SourceName#">
8:   SELECT distributorID, Name
9:   FROM distributors
10:  where '12-' + convert(varchar,distributors.distributorID) + '|' in (#listQualify(client.lstSecurity, "'")#)
11:  ORDER BY #URL.SortBy#
12: </cfquery>
13:
14: <html>
15: <head>
16:   <cfoutput>
17:     <title>#ap_backofficeName# Backoffice</title>
18:   </cfoutput>
19:   <link rel="stylesheet" href="style1.css" type="text/css">
20: </head>
21:
22: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
23:
24: <p><cfinclude template="header.cfm"></p>
25:
26: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
27:   <tr bgcolor="#cccc99">
28:     <td colspan="5">
29:       <span class="h2"><b>Distributor Maintenance</b></span>
30:       <cfif client.securityGroup is 1 and client.securityLevel is 1>
31:         &nbsp; <b>Add a distributor</b>
32:       </cfif>
33:     </td>
34:   </tr>
35:
36:   <tr bgcolor="#cccccc">
37:     <td>Sort by <a href="distAdm.cfm?SortBy=Name"><b>Name</b></a></td>
38:     <td>&nbsp;</td>
39:   </tr>
40:
41:
42: <CFIF qryDistributors.recordCount is 0>
43:   <TR><TD COLSPAN="5"><I>There are no distributors defined</I></TD></TR>
44: </CFIF>
45: <cfset lColor = True>
46: <cfloop query="qryDistributors">
47:   <cfset lColor = not lColor>
48:   <tr <cfif lColor is TRUE>bgcolor="eeeeee"</cfif>>
49:     <cfoutput>
```

```
50:         <td>#qryDistributors.Name#</td>
51:         <td><a href="#formatAdm.cfm?distributorID=#qryDistributors.distributorID#">Edit</a></td>
52:     </tr>
53: </cfoutput>
54: </cfloop>
55: </table></p>
56:
57: </body>
58: </html>
```

*Syntherisma*

```

50: <tr bgcolor="eeeeee">
51:   <td width="20%">Description:</td>
52: </tr>
53:   <input type="text" name="edtDescription" value="#edtDescription#">
54: </td>
55: </tr>
56:
57: <tr bgcolor="eeeeee">
58:   <td width="20%">Navigation Color:</td>
59: </td>
60:   <input type="text" name="edtNavColor" value="#edtNavColor#">
61: </td>
62: </tr>
63:
64: <tr bgcolor="eeeeee">
65:   <td width="20%">Menu Color:</td>
66: </td>
67:   <input type="text" name="edtMenuColor" value="#edtMenuColor#">
68: </td>
69: </tr>
70:
71:
72: <tr bgcolor="eeeeee">
73:   <td width="20%">Header Content:</td>
74: </td>
75:   <textarea name="edtHeader" rows="5" cols="80" wrap="virtual">#qryDistributor.headerCode#</textarea>
76: </td>
77: </tr>
78:
79: <tr bgcolor="eeeeee">
80:   <td width="20%">Side Content:</td>
81: </td>
82:   <textarea name="edtSide" rows="5" cols="80" wrap="virtual">#qryDistributor.sideCode#</textarea>
83: </td>
84: </tr>
85:
86: <tr bgcolor="eeeeee">
87:   <td width="20%">Footer Content:</td>
88: </td>
89:   <textarea name="edtFooter" rows="5" cols="80" wrap="virtual">#qryDistributor.footerCode#</textarea>
90: </td>
91: </tr>
92:
93: <tr bgcolor="eeeeee">
94:   <td colspan="2">
95:     <cfif qryDistributor.recordCount is 0>
96:       <input type="submit" name="btnUpdate" value="Add Distributor Info">
97:       <input type="button" name="btnShowme" value="View Layout">
98:       <input type="reset" value="Reset Info">

```

```
99: <cfelse>
100: <input type="submit" name="btnUpdate" value="Update Distributor Info">
101: <input type="button" name="btnShowme" value="View Layout">
102: <input type="reset" value="Reset Info">
103: <!-- <input type="submit" name="btnDelete" value="Delete Type" -->
104: </cfif>
105: </td>
106: </tr>
107: </FORM>
108:
109: </table>
110: </cfoutput>
111:
112: </body>
113: </html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3:
4:  <html>
5:  <head>
6:    <title>Update Distributor Information</title>
7:  </head>
8:
9:
10: <body>
11:
12: <CFIF isDefined("FORM.btnUpdate")>
13:   <CFQUERY NAME="qryFindDist" DATASOURCE="#SourceName#">
14:     SELECT distributorID FROM distributors
15:     WHERE distributorID=#FORM.distributorID#
16:   </CFQUERY>
17:
18: <CFIF qryFindDist.recordCount is 0>
19:   <cflocation URL="distAdm.cfm" addtoken="no"> <!-- no adding of distributors yet -->
20: <!--
21: <CFSET URL=distributorIP-->
22: <CFTRANSACT>
23:   <cfset cHeader = trim(preservesingleQuotes(LOGM.edtHeader))>
24:   <cfset cSide = trim(preservesingleQuotes(FORM.edtSide))~
25:   <cfset cFooter = trim(preservesingleQuotes(FORM.edtFooter))>
26:
27:   <CFQUERY NAME="qryAddComm" DATASOURCE="#SourceName#">
28:     INSERT INTO Communities (Name, Description, StartDate, StopDate)
29:     VALUES ('#FORM.edtCommunity#', '#cDesc#', #StartDate#, #cStopDate#)
30:   </CFQUERY>
31:
32:   <CFQUERY NAME="qryGetID" DATASOURCE="#SourceName#">
33:     SELECT max(TypeID) as newCommunityID
34:     FROM Communities
35:   </CFQUERY>
36:
37:   <CFSET nTypeID = qryGetID.newCommunityID>
38: </CFTRANSACT>
39:   <CFIF nTypeID is -1> <!-- Insertion failed -->
40:
41:   <CFELSE> <!-- Insertion successful -->
42:
43:   <!-- Now create the directory and upload the files -->
44:
45:   <CFSET cFilePath = #ap_CommTypePath# & #nTypeID# & "\">
46:
47:   <CFTRY> <!-- Create the directory and catch exception if directory already exists -->
48:     <CFDIRECTORY
49:       DIRECTORY="#cFilePath#"

```

```

50:     ACTION="CREATE"
51: >
52: <CFCATCH TYPE="ANY">
53: </CFCATCH>
54: </CFTRY>
55:
56: <CFIF len(FORM.edtHeader) gt 0>
57: <CFFILE
58:     DESTINATION=#filePath#
59:     ACTION="UPLOAD"
60:     NAMECONFLICT="OVERWRITE"
61:     FILEFIELD="edtHeader">
62:
63:     <CFSET cHeaderName = FILE.ServerFile>
64: <CFELSE>
65:     <CFSET cHeaderName="">
66: </CFIF>
67:
68: <CFIF len(FORM.edtFooter) gt 0>
69: <CFFILE
70:     DESTINATION=#filePath#
71:     ACTION="UPLOAD"
72:     NAMECONFLICT="OVERWRITE"
73:     FILEFIELD="edtFooter">
74:     <CFSET cFooterName = FILE.ServerFile>
75: <CFELSE>
76:     <CFSET cFooterName="">
77: </CFIF>
78:
79: <CFIF len(FORM.edtPrimaryPic) gt 0>
80: <CFFILE
81:     DESTINATION=#filePath#
82:     ACTION="UPLOAD"
83:     NAMECONFLICT="OVERWRITE"
84:     FILEFIELD="edtPrimaryPic">
85:     <CFSET cPrimaryPic = FILE.ServerFile>
86: <CFELSE>
87:     <CFSET cPrimaryPic="">
88: </CFIF>
89:
90: <cftransaction>
91:     <CFCOPY NAME="qryEdtComm" DATASOURCE="#SourceName#">
92:     UPDATE CountTypes
93:     SET headerFileName=#cHeaderName#, footerFileName=#cFooterName#, primaryPic=#cPrimaryPic#,
94:     DataPath=#\Community\#nTypeID#
95:     WHERE TypeID = #nTypeID#
96: </cfquery>
97: </cftransaction>
98:

```



```

99:      </CFIF>
100:      <CFLOCATION url="communityMaint.cfm?TypeID=#nTypeID#" addtoken="no">
101:      --->
102:      <CFELSE> <!--- Editing an existing distributor --->
103:
104:      <CFTRANSACT>
105:      <cfset cHeader = trim(preservesSingleQuotes(FORM.edtHeader))>
106:      <cfset cSide = trim(preservesSingleQuotes(FORM.edtSide))>
107:      <cfset cFooter = trim(preservesSingleQuotes(FORM.edtFooter))>
108:      <cfset cNavColor = trim(replace(FORM.edtNavColor,"##",""))>
109:      <cfset cMenuColor = trim(replace(FORM.edtNavColor,"##",""))>
110:
111:      <cfquery name="qryEditDist" datasource="#sourceName#"
112:      update distributors
113:      set headerCode='#cHeader#', sideCode='#cSide#', footerCode='#cFooter#',
114:      navColor = '##cNavColor#', menuColor = '##cMenuColor#',
115:      where distributorID = #FORM.distributorID#
116:      </cfquery>
117:
118:      </cftransaction>
119:
120:      <CFLOCATION url="distMaint.cfm?distributorID=#FORM.distributorID#" addtoken="no">
121:      </CFIF>
122:
123:      <CFELSEIF IsDefined("FORM.btnDelete")> <!--- Delete the selected community --->
124:      <cftransaction>
125:      <cfquery name="qryDeleteComm" datasource="#SourceName#">
126:      DELETE commtype_param
127:      WHERE TypeID=#nTypeID#
128:      </cfquery>
129:
130:      <cfquery name="qryDeleteComm" datasource="#SourceName#">
131:      DELETE CommTypes
132:      WHERE TypeID=#nTypeID#
133:      </cfquery>
134:      </cftransaction>
135:
136:      <!--- First delete the directory files --->
137:      <CFSET cFilePath = #ap_CommType_path# & #nTypeID# & "\">
138:
139:      <CFDIRECTORY ACTION="LIST"
140:      DIRECTORY="#cFilePath#"
141:      NAME="qryDirList"
142:      >
143:
144:      <CFLOOP QUERY="qryDirList">
145:      <CFIF qryDirList.name IS NOT "." AND qryDirList.name IS NOT "..">
146:      <CFSET cFilename = cFilePath & qryDirList.name>
147:      <CFFILE ACTION="DELETE"

```

```
148:         FILE="#cFilename#"
149:     >
150:     </CFIF>
151:     </CFLOOP>
152:
153:     <!-- Now delete the whole directory -->
154:     <CFSET cFilePath = #ap_CommType_path# & #ntypeID# & "\">
155:
156:     <CFDIRECTORY ACTION="DELETE"
157:         DIRECTORY="#cFilePath#"
158:     >
159:
160:     <cflocation url="commTypeAdm.cfm" addtoken="no">
161:     </CFIF>
162:
163:
164: </body>
165: </html>
```

```
1:
2: <!DOCTYPE HTML PUBLIC "-//W3C//Dtd HTML 3.2 Final//EN">
3: <HTML>
4: <BODY bgcolor="white">
5: <!-- The form variable selectedDocs is a comma-delimited list of the documents that should be given permission. Any other
   docs should be excluded. In order to do this, we will (a) delete all records and (b) add in the new ones. This whole thing
   will be wrapped in a transaction so that it can be committed or rolled back. -->
6: <cfTRANSACTION>
7: <cfQUERY
8:   name="deleteAssignedDocs"
9:   datasource="realestate">
10:  DELETE
11:  FROM Permissions
12:  WHERE Permissions.secureUserID = #URL.userID#
13: </cfquery>
14: <cfLOOP
15:   Index="listElement"
16:   list="#form.selectedDocs#">
17: <cfQUERY
18:   name="insertPermissions"
19:   datasource="realestate">
20:  INSERT INTO Permissions (secureUserID, docID)
21:  VALUES (#URL.userID#, #listElement#)
22: </cfquery>
23: </cfloop>
24: </cfTRANSACTION>
25: <font face="Verdana,Arial,Helvetica,sans-serif"><h3>Thank you.</h3></font>
26: </BODY>
27: </HTML>
```

```

1:
2: <!DOCTYPE HTML PUBLIC "-//W3C//Dtd HTML 3.2 Final//EN">
3: <HTML>
4: <BODY bgcolor="white">
5: <!-- Run query to get values if in edit mode -->
6: <cfif IsDefined("URL.docID")>
7: <cfquery
8:   datasource="realestate"
9:   name="getExistingValues">
10:  SELECT *
11:  FROM Documents
12:  WHERE docID = #URL.docID#
13: </cfquery>
14: <!-- Put query variables in common variables -->
15: <cfset #docName# = "#getExistingValues.docName#">
16: <cfset #docScope# = "#getExistingValues.docScope#">
17: <b>Editing Info for <cfoutput>#getExistingValues.docName#</cfoutput><b>
18: <cfelse>
19: <!-- Initialize variables to empty string -->
20: <font face="Verdana,Arial,Helvetica,sans-serif" color="navy"><b>Adding a New Document</b></font>
21: <cfset #docName# = "">
22: <cfset #docScope# = "Private">
23: </cfif>
24: <!-- Create form for data entry. -->
25: <form
26:   action="doDocEntry.cfm"
27:   enctype="multipart/form-data"
28:   method="post">
29: <cfoutput>
30: <!-- Add hidden field to pass primary key if editing an existing entry -->
31: <cfif IsDefined("URL.docID")>
32: <input
33:   type="hidden"
34:   name="docID"
35:   value="#URL.docID#">
36: </cfif>
37: <table
38:   border="0"
39:   cellpadding="4">
40: <tr>
41: <td align="right">
42: <font face="Verdana,Arial,Helvetica,sans-serif"><b>Document Name</b></font>
43: </td>
44: <td>
45: <input
46:   type="text"
47:   size="20"
48:   name="docName"
49:   value="#docName#">

```

```

50:      </td>
51:    </tr>
52:    <!-- Show this only if adding a new doc -->
53:    <cfif #docName# IS "">
54:      <tr>
55:        <td align="right">
56:          <font face="Verdana,Arial,Helvetica,sans-serif">Document File</font>
57:        </td>
58:      <td>
59:        <input
60:          name="fileContents"
61:          type="file">
62:        </td>
63:      </tr>
64:    </cfif>
65:  </tr>
66:  <td align="right">
67:    <font face="Verdana,Arial,Helvetica,sans-serif"><b>Scope</b></font>
68:  </td>
69:  <td>
70:    <input
71:      type="radio"
72:      name ="docScope"
73:      value="Private"
74:    <cfif #docScope# IS "Private">checked</cfif>
75:    <font face="Verdana,Arial,Helvetica,sans-serif">Private</font>
76:    &nbsp;
77:    <input
78:      type="radio"
79:      name="docScope"
80:      value="Public"
81:    <cfif #docScope# IS "Public">checked</cfif>
82:    <font face="Verdana,Arial,Helvetica,sans-serif">Public</font>
83:  </td>
84: </tr>
85: <tr>
86:   <td colspan="2">
87:     <center>
88:       <input
89:         type="Submit"
90:         value="      OK      ">
91:       </center>
92:     </td>
93:   </tr>
94: </table>
95: <cfif IsDefined("url.docID")>
96:   <p>&nbsp;</p>
97:   <font face="Verdana,Arial,Helvetica,sans-serif">You may DELETE this record by clicking <a
href="doDeleteFile.cfm?docID=#URL.docID#">here</a>. WARNING: If you choose to delete this file, you will not be able to undo

```

```
98:      this delete.</font>
99:      </cfif>
100:    </cfoutput>
101:  </BODY>
102: </HTML>
```

-----

```
1:
2: <!DOCTYPE HTML PUBLIC "-//W3C//Dtd HTML 3.2 Final//EN">
3: <!-- Get all docs -->
4: <cfquery
5:   datasource="realestate"
6:   name="getdocs">
7:   SELECT *
8:   FROM Documents
9:   ORDER BY Documents.docName
10: </cfquery>
11: <HTML>
12: <BODY bgcolor="white">
13: <a href="docEntry.cfm">
14:   <font face="Verdana,Arial,Helvetica,sans-serif">[Click to add new document]</font>
15: </a>
16: <p>
17: <cfoutput query="getdocs">
18:   <a href="docEntry.cfm?docID=#docID#">
19:     <font face="Verdana,Arial,Helvetica,sans-serif">#docName#</font>
20:   </a>
21:   <br>
22: </cfoutput>
23: </BODY>
24: </HTML>
```

```
1: <CFIF IsDefined("Form.listid")>
2:   <CFSET Operation="Updated">
3:   <CFUPDATE DATASOURCE="#sourceName#" TABLENAME="list">
4:   <CFELSE>
5:   <CFSET Operation="Inserted">
6:   <CFINSERT DATASOURCE="#sourceName#" TABLENAME="list">
7:   </CFIF>
8:
9:
10: <CFOUTPUT>
11: <HTML>
12: <HEAD>
13: <TITLE>Resource has been #Operation#</TITLE>
14: </HEAD>
15: <body bgcolor="ffffff">
16: <CFINCLUDE TEMPLATE="admlinks.cfm"><p>
17: <H2><font face="Verdana,Arial" color="Teal">Property:</font> <font color="Maroon"><b>#name# is linked to the resource
   #URL#</b></font></H2>
18: </CFOUTPUT>
19: </BODY>
20: </HTML>
21:
```



```
1: <CFIF IsDefined("linkId")>
2:   <CFQUERY DATASOURCE="#sourceName#">
3:     DELETE link
4:     WHERE linkId = #linkId#
5:   </CFQUERY>
6:
7: <CFELSE>
8:   <h2><font face="Verdana, Arial" color="Red">Error! No Property ID was specified!</font></h2>
9:   <CFABORT>
10:  </CFIF>
11:
12: <CFLOCATION URL="docsForm.cfm">
13:
14:
15:
16:
```

```
1: <CFSET recType = "D">
2: <cfif isDefined("action")>
3: <CFIF isDefined("linkid")>
4: <CFSET NewRecord="No">
5: <cfquery name="qlink" datasource="#sourcename#">
6: SELECT *
7: FROM link
8: WHERE agency_id in (0, #ap_agency_number#)
9: AND linkId = #URL.linkId#
10: AND linkType = '#recType#'
11:
12: </cfquery>
13: <cfset pageTitle = "Edit a Document Listing">
14: <cfset localGrpId = "#Trim(qlink.grpId)#">
15: <cfset localName = "#Trim(qlink.name)#">
16: <cfset localURL = "#Trim(qlink.url)#">
17: <cfset localOrder = "#Trim(qlink.sortOrder)#">
18: <CFSET doUpDef = "">
19: <CFSET doUpload = "No">
20:
21: <CFELSE>
22: <CFSET NewRecord="Yes">
23: <cfset pageTitle = "Add a Document Listing">
24: <cfset localGrpId = "">
25: <cfset localName = "">
26: <cfset localURL = "http://">
27: <CFSET localOrder = "0">
28: <CFSET doUpDef = "CHECKED">
29:
30: </CFIF>
31: <CFELSE>
32: <CFSET action = "view">
33: <cfset pageTitle = "View Document Listings">
34:
35: </CFIF>
36:
37: <cfquery name="qLinksGroup" datasource="#sourcename#">
38: SELECT grpId, name
39: FROM linksGroup
40: WHERE agency_id in (0, #ap_agency_number#)
41: AND linkType = '#recType#'
42: ORDER BY grpId
43:
44: </cfquery>
45:
46: <cfquery name="qlinkAll" datasource="#sourcename#">
47: SELECT linksGroup.name AS grpName,
48: link.grpId,
49: link.LinkId,
```

[illegible]

```
98: <CFIF #action# NEQ "view">
99: <!-- This is where the add -- edit action takes place -->
100: <CFFORM ACTION="docsPost.cfm" ENCTYPE="multipart/form-data">
101:   <TR BGCOLOR="Silver">
102:     <td COLSPAN="4"><CFIF NewRecord IS "No">
103:       <INPUT TYPE="hidden" NAME="linkid" VALUE="#linkid#">
104:       <B>Edit Record #linkid# </B>
105:     <CFELSE>
106:       <B>Add a New Record</B>
107:     </CFIF>
108:     <input type="hidden" NAME="agency_id" VALUE="#ap_agency_number#">
109:     <input type="hidden" NAME="linkType" VALUE="#rectype#">
110:   </td>
111: </TR><font face="Verdana, Arial" size=1>
112:   <TR valign="top" BGCOLOR="Silver">
113:     <td><cfselect display="name" query="qLinksGroup" name="grpId" value="GrpId"
selected="#localGrpId#"></cfselect><BR><INPUT type="submit" value="Submit"> </td>
114:     <td><INPUT TYPE="text" NAME="name" SIZE="20" MAXLENGTH="128" VALUE="#localName#"><BR><INPUT type="reset"></td>
115:     <td><INPUT TYPE="FILE" NAME="name" SIZE="30" MAXLENGTH="128"><BR>
116:       <input TYPE="checkbox" NAME="doUpload" VALUE="Yes" #doUpDef# Upload file</td>
117:     <td><INPUT TYPE="text" NAME="sortOrder" VALUE="#localOrder#" SIZE="3"></td>
118:   </TR></font>
119: </CFFORM>
120: </CFIF>
121: </CFOUTPUT>
122:
123: <CFOUTPUT QUERY="qLinkAll">
124:   <TR BGCOLOR="#If (CurrentRow Mod 2, DE('fffff'), DE('ffffff'))#" valign="top">
125:     <td>
126:       <font face="Verdana, Arial, sans-serif" size="1"><b>#qLinkAll.grpName#<BR><A
HREF="docsform.cfm?linkid=#qLinkAll.linkid#&action=update">Edit</A><b>#qLinkAll.grpName#<BR><A
HREF="docsdel.cfm?linkid=#qLinkAll.linkid#&action=delete">Delete</A></font> </b></font>
127:     </td>
128:     <td align="LEFT">
129:       <font face="Verdana, Arial, sans-serif" size="1">#qLinkAll.linkName#
130:     </td>
131:   </tr>
132:   <font face="Verdana, Arial, sans-serif" size="1">#qLinkAll.URL#</font>
133:   </td>
134:   <font face="Verdana, Arial, sans-serif" size="1">#qLinkAll.linkSort#</font>
135:   </td>
136: </tr>
137: </CFOUTPUT>
138: </TABLE>
139: </CENTER>
140:
141: </BODY>
142: </HTML>
143:
```

```
1: <CFSET rectype = "D">
2: <CFIF isDefined("grpId")>
3:   <cfset new_Record = "No">
4:   <cfset localGrpId = "grpId">
5:   <cfelse>
6:     <cfset new_Record = "Yes">
7:     <cfset localGrpId = "">
8:   </cfif>
9:
10: <cfquery name="qAgency" datasource="#sourceName#">
11:   SELECT name FROM agency
12:   WHERE agency_id in (0, #ap_agency_number#)
13: </cfquery>
14:
15: <cfquery name="qlinksGroup" datasource="#sourcenamename#">
16:   SELECT name, grpId, sortOrder
17:   FROM linksGroup
18:   WHERE agency_id in (0, #ap_agency_number#)
19:   AND linkType = '#rectype#'
20:   ORDER BY Name
21: </cfquery>
22:
23: <HTML><HEAD>
24: <cfoutput>
25: <TITLE>Document Groupings List and Administration</TITLE>
26: </cfoutput>
27: </HEAD>
28:
29: <body bgcolor="white">
30: <CFINCLUDE TEMPLATE="admlinks.cfm"><p>
31: <CENTER>
32: <CFFORM action="docsGroupPost.cfm">
33: <CFOUTPUT>
34:   <CFIF new_Record eq "No">
35:     <input type="hidden" name="grpId" value="#qlinksGroup.grpId#"
36:   </cfif>
37:   <input type="hidden" name="agency_id" value="#ap_agency_number#">
38:   <input type="hidden" NAME="linkType" VALUE="#rectype#">
39: </cfoutput>
40: <TABLE BORDER="0" width=550 cellpadding="0">
41:   <TR>
42:     <TH COLSPAN=4 bgcolor="#FFFFFF">
43:     <font face="Verdana, Arial, sans-serif" font size="4" color="Teal"><b>Document Groups</b></font>
44:   </TH>
45:   </TR>
46:   <TR>
47:     <TH bgcolor="cc9999">
48:     <div align="left"><font face="Verdana, Arial, sans-serif" size="2">Group Name</font></div>
49:   </TH>
```

```
50: <TH bgcolor="cc9999"><div align="left"><div align="left">
51: <font face="Verdana, Arial, sans-serif" size="2">
52: Sort Order</font>
53: </div></TH>
54: <TH bgcolor="cc9999"><div align="left">
55: <font face="Verdana, Arial, sans-serif" size="2">
56: Delete
57: </font>
58: </div></TH>
59: </TR>
60: <CFOUTPUT QUERY="qLinksGroup">
61: <TR BGCOLOR="#IIf(CurrentRow Mod 2, DE('ffffff'), DE('ffffcf'))#">
62: <td>
63: <font face="Verdana, Arial, sans-serif" size="1"><b>#qLinksGroup.Name#</b></font>
64: </td>
65: <td align="LEFT">
66: <font face="Verdana, Arial, sans-serif" size="1">#qLinksGroup.sortOrder#</font>
67: </td>
68: <td><A HREF="docsGroupDel.cfm?grpId=#qLinksGroup.grpId#&groupName=#qLinksGroup.Name#">Delete</A></td>
69: </TR>
70: </CFOUTPUT>
71: <TR>
72: <td colspan="3" align="left" bgcolor="cc9999"><B> Define a Document Group </b></td>
73: </tr>
74: <tr>
75: <td> <input type="text" name="name" maxlength="30" ></td>
76: <td> <input type="text" name="sortOrder" maxlength="3" value="0"> </td>
77: <td></td>
78: </tr>
79: <TR>
80: <td><INPUT type="submit" value="Submit"> <INPUT type="reset"></td>
81: <td align="right"></td>
82: </TR>
83: </TABLE>
84:
85: </CFform>
86: </CENTER>
87:
88: </body>
89: </html>
90:
91:
92:
93:
94:
95:
96:
97:
98:
```

99:  
100:  
101:  
102:

-----

```

1: <CFSET recType = "D">
2: <!-- CFIF IsDefined("GrpId") -->
3: <CFQUERY DATASOURCE="#sourceName#" name="qLinkNewGroup">
4:   SELECT *
5:   FROM linksGroup
6:   WHERE #ap_agency#
7:   AND agency_id = 0
8:   AND linkType = '#recType#'
9: </CFQUERY>
10: <cfquery datasource="#sourceName#" name="qLinks">
11:   SELECT *
12:   FROM link
13:   WHERE agency_id in (0, #ap_agency_number#)
14:   AND grpId = #URL.grpId#
15:   AND linkType = '#recType#'
16: </cfquery>
17: <CFSET mxRecs = "#qLinks.RecordCount#">
18: <html><HTML><HEAD>
19: <TITLE> Confirm Document Group Deletion </TITLE>
20: </HEAD>
21:
22: <body bgcolor="white">
23: <CFINCLUDE TEMPLATE="admlinks.cfm"><p>
24: <cfoutput>
25:   <cfif #mxRecs# gt 0>
26:     <b>There are #mxRecs# in that group. Which group do you want to use in place of #groupName#</b><BR>
27:     <cfselect display="name" query="qLinkNewGroup" value="grpId" name="newGrpId">
28:       <input TYPE="Hidden" VALUE="Yes" NAME="replaceGrpId">
29:       </cfselect>
30:     <a HREF="docsGroupAdm.cfm">Cancel</A>
31:   <cfelse>
32:     To delete the resource group #groupName# click on the submit button.
33:     <input TYPE="Hidden" VALUE="No" NAME="replaceGrpId">
34:   </cfif>
35:   <input type="hidden" value="#grpId#" name="oldGrpId">
36:   <input type="submit" value="submit">
37: </cfoutput>
38: </body></html>
40:

```



```
1: <CFSET recType = "D">
2: <CFIF isDefined("replaceGrpId")>
3:   <CFIF #replaceGrpId# eq "Yes" and #newGrpId# neq #oldGrpId#>
4:     Replace Grp Id is Defined and Positive
5:   </cftransaction>
6:   <cfquery datasource="#sourceName#" name="qLinkUpdate">
7:     UPDATE link
8:     SET grpId = #newGrpId#
9:     WHERE agency_id in (0, #ap_agency_number#)
10:    AND grpId = #oldGrpId#
11:    AND linkType = '#recType#'
12:  </cfquery>
13:
14:
15: <CFQUERY DATASOURCE="#sourceName#" NAME="qLinksGroupDelete">
16:   DELETE linksGroup
17:   WHERE grpId = #oldGrpId#
18:   AND agency_id in (0, #ap_agency_number#)
19:   AND linkType = '#recType#'
20: </CFQUERY>
21: </cftransaction> <BR>
22:
23:
24: <CFELSEIF #replaceGrpId# eq "Yes" and #newGrpId# eq #oldGrpId#>
25:   <P><B><I>Need to select a group that is different from the group to be deleted!</I></B>
26: </CFELSE>
27:   Replace Grp Id is Defined and Negative
28: <CFQUERY DATASOURCE="#sourceName#">
29:   DELETE linksGroup
30:   WHERE grpId = #oldGrpId#
31:   AND agency_id in (0, #ap_agency_number#)
32:   AND linkType = '#recType#'
33: </CFQUERY>
34: </CFIF>
35: </CFIF>
36: <CFLOCATION URL="docsGroup.cfm">
```

```

    <!-- CFIF IsDefined("Form.grpid") -->
    <!-- CFSET Operation="Updated" -->
    <!-- CFUPDATE DATASOURCE="#sourceName#" TABLENAME="linksGroup" -->
    <!-- CFELSE -->
    <!-- CFSET Operation="Inserted" -->
    <!-- CFINSERT DATASOURCE="#sourceName#" TABLENAME="linksGroup" -->
    <!-- CFIF -->

```

```

1:  <CFIF IsDefined("Form.grpid")>
2:  <CFSET Operation="Updated">
3:  <CFUPDATE DATASOURCE="#sourceName#" TABLENAME="linksGroup">
4:  <CFELSE>
5:  <CFSET Operation="Inserted">
6:  <CFINSERT DATASOURCE="#sourceName#" TABLENAME="linksGroup">
7:  </CFIF>
8:
9:  <CFOUTPUT>
10:  <HTML>
11:  <HEAD>
12:  <TITLE>Resource has been #Operation#</TITLE>
13:  </HEAD>
14:  <body bgcolor="ffffff">
15:  <cflocation url="docsGroup.cfm">
16:  </CFOUTPUT>
17:  </BODY>
18:  </HTML>
19:
20:
```

```
1: <CFIF IsDefined("linkid")>
2: <CFSET Operation="Updated">
3: <CFELSE>
4: <CFSET Operation="Inserted">
5: </CFIF>
6:
7:
8: <HTML>
9: <HEAD>
10: <CFOUTPUT>
11: <TITLE>The document, #FORM.URL#, has been #Operation#</TITLE>
12: </CFOUTPUT>
13: </HEAD>
14: <body bgcolor="ffffff"><CFINCLUDE TEMPLATE="admlinks.cfm"><p>
15: <CFOUTPUT>
16: <CFIF Not isDefined("doUpload")>
17: <CFSET doUpload = "No">
18: </CFIF>
19: <CFIF #doUpload# EQ "Yes">
20: <CFIF>
21: <CFIF #doUpload# EQ "Yes">
22: <CFIF #doUpload# EQ "Yes">
23: <CFIF #doUpload# EQ "Yes">
24: <CFIF #doUpload# EQ "Yes">
25: <CFIF #doUpload# EQ "Yes">
26: <CFIF #doUpload# EQ "Yes">
27: <CFIF #doUpload# EQ "Yes">
28: <CFIF #doUpload# EQ "Yes">
29: <CFIF #doUpload# EQ "Yes">
30: <CFIF #doUpload# EQ "Yes">
31: <CFIF #doUpload# EQ "Yes">
32: <CFIF #doUpload# EQ "Yes">
33: <CFIF #doUpload# EQ "Yes">
34: <CFIF #doUpload# EQ "Yes">
35: <CFIF #doUpload# EQ "Yes">
36: <CFIF #doUpload# EQ "Yes">
37: <CFIF #doUpload# EQ "Yes">
38: <CFIF #doUpload# EQ "Yes">
39: <CFIF #doUpload# EQ "Yes">
40: <CFIF #doUpload# EQ "Yes">
41: <CFIF #doUpload# EQ "Yes">
42: <CFIF #doUpload# EQ "Yes">
43: <CFIF #doUpload# EQ "Yes">
44: <CFIF #doUpload# EQ "Yes">
45: <CFIF #doUpload# EQ "Yes">
46: <CFIF #doUpload# EQ "Yes">
47: <CFIF #doUpload# EQ "Yes">
48: <CFIF #doUpload# EQ "Yes">
49: <CFIF #doUpload# EQ "Yes">
```

1  
1  
1

```

48: <table WIDTH="90%" border="0" cellspacing="0" cellpadding="0" style="width: 100%; border-collapse: collapse;">
49: <tr valign="top" ><td WIDTH="#colWidth%">
50: <CFLOOP FROM="1" TO="#nRecs#" INDEX="counter">
51: <CFIF #GroupIdOld# NEQ #ListGetAt(lsGroup, counter, dlm) #>
52: <CFIF #counter# gt 0>
53: </UL>
54: <CFIF #nLines# gte #colLines#>
55: <!-- Start a new column -->
56: </td><td WIDTH="#colWidth%">
57: <CFSET nLines = 0>
58: </CFIF>
59: </CFIF>
60: <!-- Put in the group heading -->
61: <CFSET GroupIdOld = #ListGetAt(lsGroup, counter, dlm) #>
62: <BR><b>#GroupIdOld#</B><BR><UL TYPE="disc">
63:
64: </CFIF>
65: <!-- Put in the resource listing -->
66: <li><A HREF="#docs/#ListGetAt(lsURL, counter, dlm)#" TARGET="new">#Trim(ListGetAt(lsName, counter, dlm))#</A><BR>
67: <CFSET nLines = nLines + 1>
68: </CFLOOP><p><div align="center">If you don't already have Acrobat,<br>get it free here<br><a href="http://www.adobe.com/products/acrobat/readstep.html" target="_blank"></a></div><p>
69: </td></TR>
70: </table>
71: </CFOUTPUT>
72: </table>
73: </body>
74: </html>
75:

```

4.0 Transitional/EN

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN"
2:
3: <html>
4: <head>
5:   <title>Update Page Format Information</title>
6: </head>
7:
8: <body>
9:
10:  <CFIF isDefined("FORM.btnUpdate")>
11:    <CFQUERY NAME="qryFindFormat" DATASOURCE="#SourceName#">
12:      SELECT pageFormatID FROM pageFormat
13:      WHERE pageFormatID=#FORM.pageFormatID#
14:    </CFQUERY>
15:
16:    <CFIF qryFindFormat.recordCount is 0>
17:
18:      <cfset cDescription = trim(preservesingleQuotes(FORM.edtDescription))>
19:      <cfset cHeader = trim(preservesingleQuotes(FORM.edtHeader))>
20:      <cfset cSide = trim(preservesingleQuotes(FORM.edtSide))>
21:      <cfset cFooter = trim(preservesingleQuotes(FORM.edtFooter))>
22:      <cfset cNavColor = trim(replace(FORM.edtNavColor,"##",""))>
23:      <cfset cMenuColor = trim(replace(FORM.edtMenuColor,"##",""))>
24:
25:      <cftransaction>
26:        <cfquery name="qryAddFormat" datasource="#sourceName#">
27:          insert into pageFormat
28:            (distributorID, description, navcolor, menuColor, headerCode, sideCode, footerCode)
29:            values (#FORM.distributorID#, 'cDescription', '##cNavColor', '##cMenuColor', 'cHeader',
30:              'cSide', 'cFooter#')
31:        </cfquery>
32:
33:        <CFQUERY NAME="qryGetID" DATASOURCE="#SourceName#">
34:          SELECT max(pageFormatID) as newPageFormatID
35:          FROM pageFormat
36:        </CFQUERY>
37:
38:        <CFSET nPageFormatID = qryGetID.newPageFormatID>
39:
40:        <!--- Remove old references to this page format --->
41:        <cfquery name="qryDeleteFormat" datasource="#sourceName#">
42:          delete from formatAssignment
43:          where formatAssignment.pageFormatID = #FORM.pageFormatID#
44:        </cfquery>
45:
46:        <cfloop list="#FORM.lstDisplayPages#" index="cValue" delimiters=",">
47:          <cfset nEntityType = replace(listGetAt(cValue, 1, "|"),"","")>
48:          <cfset nEntityID = replace(listGetAt(cValue, 2, "|"),"","")>
49:          <cfquery name="qryAddFormat" datasource="#sourceName#">

```

```

50:         insert into formatAssignment
51:         (pageFormatID, distributorID, entityType, entityID)
52:         values (#nPageFormatID#, #FORM.distributorID#, #nEntityType#, #nEntityID#)
53:     </cfquery>
54: </cfloop>
55:
56: </cftransaction>
57:
58:
59: <CFLOCATION url="formatMaint.cfm?pageFormatID=#nPageFormatID#&distributorID=#FORM.distributorID#" addtoken="no">
60:
61: <CFELSE> <!--- Editing an existing distributor ---->
62:
63: <CFTRANSACTION>
64:     <cfset cDescription = trim(preservesSingleQuotes(FORM.edtDescription))>
65:     <cfset cHeader = trim(preservesSingleQuotes(FORM.edtHeader))>
66:     <cfset cSide = trim(preservesSingleQuotes(FORM.edtSide))>
67:     <cfset cFooter = trim(preservesSingleQuotes(FORM.edtFooter))>
68:     <cfset cNavColor = trim(replace(#FORM.edtNavColor#, "##", ""))>
69:     <cfset cMenuColor = trim(replace(#FORM.edtMenuColor#, "##", ""))>
70:
71:     <cfquery name="qryEditDist" datasource="#sourceName#">
72:         update pageFormat
73:         set description='#cDescription', headerCode='#cHeader', sideCode='#cSide', footerCode='#cFooter',
74:         navColor = '##cNavColor', menuColor = '##cMenuColor#',
75:         where pageFormatID = #FORM.pageFormatID#
76:     </cfquery>
77:
78: <!--- Remove old references to this page format ---->
79: <cfquery name="qryDeleteFormat" datasource="#sourceName#">
80:     delete from formatAssignment
81:     where formatAssignment.pageFormatID = #FORM.pageFormatID#
82: </cfquery>
83:
84: <cfloop list="#FORM.lstDisplayPages#" index="cValue" delimiters=", ">
85:     <cfset nEntityType = replace(listGetAt(cValue, 1, "|"), "**", "")>
86:     <cfset nEntityID = replace(listGetAt(cValue, 2, "|"), "**", "")>
87:     <cfquery name="qryAddFormat" datasource="#sourceName#">
88:         insert into formatAssignment
89:         (pageFormatID, distributorID, entityType, entityID)
90:         values (#FORM.pageFormatID#, #FORM.distributorID#, #nEntityType#, #nEntityID#)
91:     </cfquery>
92: </cfloop>
93:
94: </cftransaction>
95:
96: <CFLOCATION url="formatMaint.cfm?pageFormatID=#FORM.pageFormatID#&distributorID=#FORM.distributorID#" addtoken="no">
97: </CFIF>
98:

```

```
99: <CFELSEIF IsDefined("FORM.btnDelete")>
100: <cftransaction>
101: <cfquery name="qryDeleteFormat" datasource="#DataSource#">
102: DELETE formatAssignment
103: WHERE formatAssignment.pageFormatID=#FORM.pageFormatID#
104: </cfquery>
105:
106: <cfquery name="qryDeleteComm" datasource="#DataSource#">
107: DELETE pageFormat
108: WHERE pageFormat.pageFormatID=#FORM.pageFormatID#
109: </cfquery>
110: </cftransaction>
111:
112: <cflocation url="formatAdm.cfm" addtoken="no">
113: </CFIF>
114:
115: </body>
116: </html>
117:
```



```

1: <cfif isdefined("cgi.query_string")>
2:   <cfif cgi.query_string is not "">
3:     <cfparam name="thefieldnames" default="">
4:     <cfparam name="loopcounter" default="1">
5:     <cfloop list="#cgi.query_string#" delimiters="&" index="Item">
6:       <cfset findequal = "#find( "=", "#item#", 1)#">
7:       <cfset URLName = "#removechars("#item#", "#findequal#", "#len(item)#")#">
8:       <cfif loopcounter is 1>
9:         <cfset thefieldnames = "#thefieldnames#" & "URLNAME#">
10:        <cfelse>
11:          <cfset thefieldnames = "#thefieldnames#" & "URLNAME#">
12:        </cfif>
13:        <cfset loopcounter = loopcounter+1>
14:      </cfloop>
15:      <cfloop list="#thefieldnames#" index="thefield">
16:        <CFIF NOT ISDEFINED( 'ATTRIBUTES.' & thefield )>
17:          <cfset SetVariable("caller.attributes.thefield#", "#evaluate("url."&"#thefield#")#")>
18:        <cfelse>
19:          </CFIF>
20:
21:        </cfloop>
22:      </cfif>
23:    </cfif>
24:
25:    <cfif isdefined("form.fieldnames")>
26:      <cfloop list="#form.fieldnames#" index="field">
27:        <CFIF NOT ISDEFINED( 'ATTRIBUTES.' & field )>
28:          <cfset SetVariable("caller.attributes.#field#", "#evaluate("form."&"#field#")#")>
29:        </cfif>
30:      </cfloop>
31:    </cfif>
32:

```

```
1: <cfif not isDefined("securityTested")>
2:   <cfinclude template="include\security.cfm">
3: </cfif>
4:
5: <table border="0" width="100%" cellpadding="2" cellspacing="0">
6: <tr><td bgcolor="#cccc99" class="h1" align="center"><cfoutput>#ap_agencyname#</cfoutput> Back Office<br></td></tr>
7: <tr><td bgcolor="#cccc99" align="center"><cfif client.securityGroup le 6><b>&middot;</b><a href="index.cfm">Back Office
   Home</a>&nbsp;</cfif>
8:   <cfif client.securityGroup le 6><b>&middot;</b><a href="index.cfm" target="_blank">WWW Home</a>&nbsp;</cfif>
9:
10:   <!-- Yakelo Administrator Links -->
11:   <cfif client.securityGroup is 1 and client.securityLevel is 1>
12:     <cfif client.securityLevel is 1>
13:       <b>&middot;</b><a href="custadm.cfm">Maintain Customers&nbsp;</a>&nbsp;</cfif>
14:     </cfif>
15:   <cfelseif client.securityGroup is 2>
16:   <cfelseif client.securityGroup is 3>
17:   <cfelseif client.securityGroup is 4>
18:   <cfelseif client.securityGroup is 5>
19:   </cfif>
20:
21:   <cfif client.securityLevel is 1> <!-- Administrator Access can edit logins -->
22:     <b>&middot;</b><a href="loginAdm.cfm">Maintain Logins</a>&nbsp;</cfif>
23:   </cfif>
24:   <cfif client.securityLevel is 1> <!-- Administrator Access can edit logins -->
25:     <b>&middot;</b><a href="stats.cfm">Stats</a>&nbsp;</cfif>
26:   </cfif>
27:
28:   <cfif (admin_forceLogin is True and client.userID gt -1) or (admin_forceLogin is False and client.userID gt 1)>
29:     <b>&middot;</b><a href="login.cfm">Logout <cfoutput>(<client.userName#></cfoutput></a>&nbsp;</cfif>
30:   </cfif>
31: </td></tr>
32: <cfif client.securityLevel is 1 and client.securityGroup is 1 and client.userID gt -1>
33:   <tr><td bgcolor="#cccccc" align="center"><font color="red">(Warning: You are in superYak mode)</font></td></tr>
34: </cfif>
35: <tr><td bgcolor="#cccccc" align="center">
36:   <!--
37:   <cfif client.securityGroup le 2><a href="distadm.cfm">Distributors</a> | </cfif>
38:   <!--
39:   <table border="0">
40:   <tr><td align="right"><b>Agent/Property Pages:</b></td>
41:   <td><cfif client.securityGroup le 4><b>&middot;</b><a href="agencyadm.cfm">Agencies</a>&nbsp;</cfif>
42:   <cfif client.securityGroup le 5><b>&middot;</b><a href="agentadm.cfm">Agents</a>&nbsp;</cfif>
43:   <cfif client.securityGroup le 6><b>&middot;</b><a href="agentbioadm.cfm">Enhanced Agent Bio</a>&nbsp;</cfif>
44:   <cfif client.securityGroup le 6><b>&middot;</b><a href="propadm.cfm">Properties</a>&nbsp;</cfif>
45:   <cfif client.securityGroup le 6><b>&middot;</b><a href="onlineTours.cfm">Online Tours</a>&nbsp;</cfif></td></tr>
46:   <tr><td align="right"><b>Newspaper:</b></td>
47:   <td>
48:     <cfif client.securityGroup le 3><b>&middot;</b><a href="distAdm.cfm">Distributors</a>&nbsp;</cfif>
```

```

<cfif client.securityGroup le 6><b>emiiddot</b><a href="linkAdm.cfm">Resources</a>enbsp</cfif>
<cfif client.securityGroup le 3><b>emiiddot</b><a href="commAdm.cfm">Communities</a>enbsp</cfif>
<cfif client.securityGroup le 3><b>emiiddot</b><a href="propTypeAdm.cfm">Specialty Pages</a>enbsp</cfif>
<!-- <cfif client.securityGroup le 3><b>emiiddot</b><a href="classAdm.cfm">Classifieds</a>enbsp</cfif> -->

```

```
1: <CFQUERY DATASOURCE="#sourceName#" NAME="prop_main">
2: SELECT name, city, state, prop_id
3: FROM prop_main
4: WHERE #ap_agency# AND status > #ap_NotListed#
5: ORDER BY name, city, state, prop_id
6: </CFQUERY>
7:
8: <HTML>
9:
10: <HEAD>
11: <TITLE>Maintain Property Images</TITLE>
12: </HEAD>
13:
14: <body bgcolor="white">
15: <CFINCLUDE TEMPLATE="admlinks.cfm">
16: <div align="center"><H1><font face="Verdana, Arial" color="Teal">Property Images</font></H1>
17: <font face="Verdana, Arial" size="4">Click on Property's Name or ID Number to Add Property Image</font><p>
18: <TABLE BORDER=0>
19: <TR>
20: <TH bgcolor="cc9999">
21: <font face="Verdana, Arial, sans-serif" size="2"><b>Property Name</b></font></TH>
22: <TH bgcolor="cc9999">
23: <font face="Verdana, Arial, sans-serif" size="2"><b>City, State</b></font></TH>
24: <TH bgcolor="cc9999">
25: <font face="Verdana, Arial, sans-serif" size="2"><b>ID Number</b></font></TH>
26: </TR>
27: <CFOUTPUT QUERY="prop_main">
28: <TR bgcolor="#If(CurrentRow Mod 2, DE('cccccc'), DE('ffffcf'))#">
29: <td><font face="Verdana, Arial, sans-serif" size="2"><A
30: HREF="imagadm.cfm?prop_id=#prop_id#"><b>#name</b></A></font></td>
31: <td><font face="Verdana, Arial, sans-serif" size="2"> #city#, #state#</font></td>
32: <td><div align="center"><font face="Verdana, Arial, sans-serif" size="2"><A
33: HREF="imagadm.cfm?prop_id=#prop_id#">#NumberFormat(prop_id, '0000') #</A></font></div></td>
34: </TR></CFOUTPUT>
35: </TABLE></div><p>
36: </BODY>
37: </HTML>
38:
39:
40:
41:
42:
```

```
1: <cffile
2: destination="#ap_image_path#"
3: action="UPLOAD"
4: nameconflict="OVERWRITE"
5: filefield="PhotoFile"
6: accept="image/gif, image/jpeg, image/jpeg">
7: <cftransaction>
8:   <cfquery name="photo_file_1" datasource="#sourceName#">
9:     UPDATE prop_main
10:    SET photo_file_1 = 'FILE.ServerDirectory#\FILE.ServerFile#',
11:    photo_name = 'images\#FILE.ServerFile#'
12:    WHERE prop_id=#FORM.prop_id#
13:   </cfquery>
14: </cftransaction>
15:
16: <cflocation url="propadmn.cfm">
```

```

1:
2:
3: <HTML>
4: <TITLE>Big Pine Property Image Upload Results</TITLE>
5:
6: <body bgcolor="white">
7: <CFINCLUDE TEMPLATE="admlinks.cfm" ><p>
8: <CFAPPLICATION NAME="RealStuff" CLIENTMANAGEMENT="Yes">
9: <!-- Get characteristics ready to store -->
10: <CFSET pid = #prop_id#>
11: <CFFILE
12: DESTINATION="C:\inetpub\wwwroot\yakalo\mintown\images\"
13: ACTION="UPLOAD"
14: NAMECONFLICT="OVERWRITE"
15: FILEFIELD="imgVar1"
16: <!-- ACCEPT="image/gif,image/jpeg" -->>
17:
18: <cfoutput>
19: Field Names: #Form.FieldNames#<BR>
20: "----"<br>
21: #form.imagefile#<br>
22: #form.imagecapti#<br>
23: #form.imglabel#<br>
24:
25: "----"<br>
26: Next Test:<br>
27: <CFLOOP INDEX="FormField" LIST="#FORM.ls_value#">
28:
29: <CFSET QualifiedFormField = "FORM." & FormField>
30:
31: #QualifiedFormField#: #Evaluate(QualifiedFormField)#<br>
32:
33: </CFLOOP>
34:
35: /cfoutput>
36: <!--
37: <CFTRANSACTION>
38: <CFLOOP INDEX="input" FROM="1" TO="#totalName#" >
39:
40: <CFQUERY DATASOURCE="Realestate" QUERY="qParamInput">
41: Insert p_param VALUES (prop_id, listGetAt(ls_id,input), #sn_agency_id#, listGetAt(ls_param_cncr, input),
42: listGetAt(ls_name, input),
43: </CFQUERY>
44: </CFLOOP>
45: </CFTRANSACTION>
46: ---
47: <CFOUTPUT>
48: <font face="Verdana, Arial" color="Teal"><h2><b>Property Image File Upload was Successful!</b></h2></font><br>

```

-----

49:  
50:       <p>  
51:       </CFOUTPUT>  
52:       </BODY>  
53:       </HTML>  
54:  
55:  
56:  
57:  
58:  
59:  
60:  
61:  
62:  
63:  
64:  
65:

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3: <html>
4: <head>
5:   <cfoutput>
6:     <title>#ap_backofficeName# Backoffice</title>
7:   </cfoutput>
8:   <link rel="stylesheet" href="style1.css" type="text/css">
9: </head>
10:
11: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
12:
13:   <cfinclude template="header.cfm">
14:
15: </body>
16: </html>
```



4.0 Transitional HTML 4.0

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfquery name="qryClassifieds" datasource="#SourceName#">
4:   select ad_id, ad_class, ad_content
5:   from pap_cl_ad
6: </cfquery>
7:
8: <cfindex action="refresh"
9:   collection="RealEstate"
10:  Key="ad_id"
11:  Type="Custom"
12:  Title="ad_class"
13:  query="qryClassifieds"
14:  body="ad_content"
15: >
16:
17: <html>
18: <head>
19:   <title>Verity RealEstate Collection Indexing</title>
20: </head>
21:
22: <body>
23: <H2>Indexing Complete</h2>
24:
25: </body>
26: </html>
```

```
1: <CFIF IsDefined("Form.listid")>
2:   <CFSET Operation="Updated">
3:   <CFUPDATE DATASOURCE="#sourceName#" TABLENAME="list">
4:   <CFELSE>
5:   <CFSET Operation="Inserted">
6:   <CFINSERT DATASOURCE="#sourceName#" TABLENAME="list">
7:   </CFIF>
8:
9:
10: <CFOUTPUT>
11: <HTML>
12: <HEAD>
13: <TITLE>Resource has been #Operation#</TITLE>
14: </HEAD>
15: <body bgcolor="ffffff">
16: <CFINCLUDE TEMPLATE="admlinks.cfm"><p>
17: <H2><font face="Verdana,Arial" color="Teal">Property:</font> <font color="Maroon"><b>#name# is linked to the resource
   #URL#</b></font></H2>
18: </CFOUTPUT>
19: </BODY>
20: </HTML>
21:
```

```

1: <cfinclude template="include\security.cfm" default="grpName,linkname">
2:
3: <cfparam name="URL.sortBy" default="grpName,linkname">
4:
5: <!--- Removed 6/5/00 JHJ Why was this here? To suck up processor cycles?
6: <cfquery name="qAgency" datasource="#sourceName#">
7:   SELECT name FROM agency
8:   WHERE distributorID = #ap_distributorID#
9: </cfquery>
10: -- >
11:
12: <cfquery name="qlink" datasource="#sourceName#">
13:   SELECT linksGroup.name AS grpName, link.grpid, link.LinkId, link.Name AS linkName, link.URL, link.SortOrder AS linkSort
14:   FROM link, linksGroup
15:   WHERE linksGroup.distributorID = #ap_distributorID#
16:   AND link.grpid = linksGroup.grpid
17: <!--- and '!' is convert(varchar,link.agency_id) + ';' in (#listQualify(client.IsSecurity,"")#) -->
18:   ORDER BY #URL.sortBy#
19: </cfquery>
20:
21: <!--- WHERE link.agency_id = #ap_agency_number# removed 6/5/00 JHJ -->
22:
23: <!--- ORDER BY link.grpid, link.Name -->
24:
25:
26: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
27:
28: <html>
29: <head>
30:   <cfoutput>
31:     <title>#ap_backofficeName# Backoffice</title>
32:   </cfoutput>
33:   <link rel="stylesheet" href="style1.css" type="text/css">
34: </head>
35:
36: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
37:
38: <p><cfinclude template="header.cfm"></p>
39:
40: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
41:   <tr bgcolor="#cccc99"><td colspan="5"><b>Resources</b></span><b> <a href="linksForm.cfm?Action=Add">Add a
42:   Resource</a></td></tr>
43:   <tr bgcolor="#cccccc">
44:     <td valign="bottom"><b>Sort by <a href="linksadm.cfm?sortBy=grpName,linkname">Group</a></b></td>
45:     <td valign="bottom"><b>Sort by <a href="linksadm.cfm?sortBy=linkname,grpName">Resource</a></b></td>
46:     <td valign="bottom"><b>Sort by <a href="linksadm.cfm?sortBy=URL">URL</a></b></td>
47:     <td valign="bottom"><b>Sort by <a href="linksadm.cfm?sortBy=linkSort">Sort Order</a></b></td>
48:   <td><b> </td>

```

```
48: </tr>
49: <CFOUTPUT QUERY="qLink">
50: <tr bgcolor="#IIf(CurrentRow Mod 2, DE('fffff'), DE('eeeeee'))#">
51: <td><cfif trim(qLink.grpName) IS "" OR ISDefined("qLink.grpName") IS "No">&nbsp; </cfif></td>
52: <td><cfif trim(qLink.linkName) IS "" OR ISDefined("qLink.linkName") IS "No">&nbsp; </cfif></td>
53: <td><cfif trim(qLink.URL) IS "http://" OR ISDefined("qLink.URL") IS "No">&nbsp; </cfif></td>
54: <td>#qLink.linkSort#</td>
55: <td><a href="Linksform.cfm?linkid=#qLink.linkid#&Action=Edit">Edit</a> | <a
    href="linksdel.cfm?linkid=#qLink.linkid#">Delete</a></td>
56: </tr>
57: </cfoutput>
58: </table></p>
59:
60: </body>
61: </html>
```

```
1: <CFIF IsDefined("linkId")>
2: <CFQUERY DATASOURCE="#sourceName#">
3: DELETE link
4: WHERE linkId = #linkId#
5: </CFQUERY>
6:
7: <CFELSE>
8: <h2><font face="Verdana, Arial" color="Red">Error! No Property ID was specified!</font></h2>
9: <CFABORT>
10: </CFIF>
11:
12: <CFLOCATION URL="linksform.cfm?action=Add" addtoken="no">
13:
14:
15:
16:
```

```

1: <cfif j
2: </CFIF j
3: <CFSE
4: <cfql
5: SEI
6: FRC
7: whe
8: anc
9: ANI
10: ANI
11: </cfql
12: <cfse
13: <cfse
14: <cfse
15: <cfse
16: <cfse
17: <cfse
18: <cfse
19: <CFELSE
20: <CFSE
21: <cfse
22: <cfse
23: <cfse
24: <cfse
25: <CFSE
26: <cfse
27: <cfse
28: </CFIF>
29: <CFELSE
30: <CFSE
31: <cfse
32: </CFIF>
33:
34: <cfquer
35: SELE
36: FROM
37: WHERE
38: ANI
39: ORDE
40: </cfque
41:
42: <cfquer
43: SELE
44: li
45: FROM
46: WHERE
47: AND J
48: ORDE
49: </cfque

1: <cfif isdefined("action")>
2: <CFIF isdefined("linkid")>
3: <CFSET NewRecord="No">
4: <cfquery name="qlink" datasource="#sourcename#">
5: SELECT *
6: FROM link
7: WHERE agency_id = #ap_agency_number#
8: AND linkid = #URL.linkid#
9: AND linkType = 'L'
10:
11: </cfquery>
12: <cfset pageTitle = "Edit a Resource Link">
13: <cfset localGrpId = "#Trim(qlink.grpid)#">
14: <cfset localName = "#Trim(qlink.name)#">
15: <cfset localURL = "#Trim(qlink.url)#">
16: <cfset localOrder = "#Trim(qlink.sortOrder)#">
17:
18: <CFELSE>
19: <CFSET NewRecord="Yes">
20: <cfset pageTitle = "Add a Resource Link">
21: <cfset localGrpId = "">
22: <cfset localName = "">
23: <cfset localURL = "http://">
24: <CFSET localOrder = "0">
25:
26: </CFIF>
27: <CFELSE>
28: <CFSET action = "view">
29: <cfset pageTitle = "View Resource Links">
30:
31: </CFIF>
32:
33: <cfquery name="qLinksGroup" datasource="#sourcename#">
34: SELECT grpid, name
35: FROM linksGroup
36: WHERE agency_id = #ap_agency_number#
37: AND linkType = 'L'
38: ORDER BY grpid
39:
40: </cfquery>
41:
42: <cfquery name="qlinkAll" datasource="#sourcename#">
43: SELECT linksGroup.name AS grpName,
44: link.grpid,
45: link.LinkId,
46: link.Name AS linkName,
47: link.URL,
48: link.SortOrder AS linkSort
49: FROM link, linksGroup

```



```

98:  <INPUT TYPE="hidden" NAME="linkid" VALUE="#linkid#">
99:  <B>Edit Record #linkid# </B>
100:  <CFELSE>
101:  <B>Add a New Record</B>
102:  </CFIF>
103:  <input type="hidden" NAME="agency_id" VALUE="#ap_agency_number#">
104:  <input type="hidden" NAME="linkType" VALUE="L">
105:  </td>
106:  </TR><font face="Arial" size="2">
107:  <TR valign="top" BGCOLOR="Silver">
108:    <td><cfselect display="name" query="qLinksGroup" name="grpId" value="GrpId"
selected="#localGrpId#"></cfselect><BR><INPUT type="submit" value="Submit"> <INPUT type="reset"></td>
109:    <td><INPUT TYPE="text" NAME="name" SIZE="20" MAXLENGTH="128" VALUE="#localName#"></td>
110:    <td><INPUT TYPE="text" NAME="URL" SIZE="30" MAXLENGTH="128" VALUE="#localURL#"></td>
111:    <td><INPUT TYPE="text" NAME="sortOrder" VALUE="#localOrder#" SIZE="3"></td>
112:  </TR></font>
113:  </CFFORM>
114:  </CFIF>
115:  </CFOUTPUT>
116:
117:  <CFOUTPUT QUERY="qLinkAll">
118:  <TR BGCOLOR="#IIf(CurrentRow Mod 2, DE('fffff'), DE('eeeeee'))#" valign="top">
119:    <td>
120:      <font face="Arial, sans-serif" size="2"><b>#qLinkAll.grpName#<BR><A
HREF="Linksform.cfm?linkid=#qLinkAll.linkid#&action=update">Edit</A> <b>#qLinkAll.grpName#<BR><A
HREF="linksdel.cfm?linkid=#qLinkAll.linkid#&action=delete">Delete</A></b></font> </td>
121:    </td>
122:    <td align="LEFT">
123:      <font face="Arial, sans-serif" size="2">#qLinkAll.linkName#
124:    </td>
125:    <td>
126:      <font face="Arial, sans-serif" size="2">#qLinkAll.URL#</font>
127:    </td>
128:    <td>
129:      <font face="Arial, sans-serif" size="2">#qLinkAll.linkSort#</font>
130:    </td>
131:  </tr>
132:  </cfoutput>
133:  </taoale>
134:  </center>
135:
136:  </body>
137:  </html>
138:

```



```
1:
2: <!DOCTYPE HTML PUBLIC "-//W3C//Dtd HTML 3.2 Final//EN">
3: <cfquery
4:   datasource="realestate"
5:   name="deleteFile">
6:   DELETE
7:   FROM Documents
8:   WHERE Documents.docID = #URL.docID#
9: </cfquery>
10: <HTML>
11: <BODY bgcolor="white">
12:   <font face="Verdana,Arial,Helvetica,sans-serif"><h3>Thank you. The file was deleted. If you wish to bring it back, you need
      to ADD a new document and upload it again.</h3></font>
13: </BODY>
14: </HTML>
15:
```

```
1:
2: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
3: <!-- Is this an existing update or a new upload? -->
4: <cfif IsDefined("form.docID")>
5:   <cfset process = "update">
6:   <cfelse>
7:     <cfset process = "upload">
8:   </cfif>
9:   <HTML>
10:     <BODY bgcolor="white">
11:       <cfif process is "update">
12:         <cfupdate
13:           datasource="realestate"
14:           tablename="Documents">
15:         <font face="Verdana,Arial,Helvetica,sans-serif"><h2>Thank you.</h2> This record has been updated.</font>
16:       <cfelse>
17:         <!-- We must be uploading a new file -->
18:         <!-- Actual file upload. -->
19:         <cfif
20:           action="upload"
21:           filefield="form.fileContents"
22:           destination="C:\inetpub\wwwroot\yakalo\development\generic\admin\"
23:           nameconflict="makeUnique">
24:
25:         <!-- New create an entry into the Documents database -->
26:         <cfquery name="addDocument" datasource="realestate">
27:           <cfif docScope is "Public">
28:             INSERT INTO Documents (docName, docLocation, docScope)
29:             VALUES ('#form.docName#', '#file.ServerFile#', 'Public')
30:           <cfelse>
31:             INSERT INTO Documents (docName, docLocation, docScope)
32:             VALUES ('#form.docName#', '#file.ServerFile#', 'Private')
33:           </cfif>
34:         </cfquery>
35:         <font face="Verdana,Arial,Helvetica,sans-serif"><h2>Thank you.</h2> This record has been added to the database.</font>
36:       </cfif>
37:     </BODY>
38:   </HTML>
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//Dtd HTML 3.2 Final//EN">
2: <HTML>
3: <BODY bgcolor="white">
4: <cfif IsDefined("form.secureUserID")>
5: <cfupdate
6:   datasource="realestate"
7:   tablename="Users">
8:   <font face="Verdana,Arial,Helvetica,sans-serif"><b>Thank you.</b> This record has been updated.</font>
9: <cfelse>
10: <cfinsert
11:   datasource="realestate"
12:   tablename="Users">
13:   <font face="Verdana,Arial,Helvetica,sans-serif"><b>Thank you.</b> This record has been added to the database.</font>
14: </cfif>
15: </BODY>
16: </HTML>
```

```
1: <HTML>
2: <HEAD>
3:   <TITLE>Calendar Administration</TITLE>
4: </HEAD>
5:
6: <BODY BGCOLOR="#FFFFFF">
7:
8:
9:   <A HREF="index.cfm?FuseAction=AddEvent"><font face="Verdana,Arial" size="2">Add An Event</font></A> |
10:  <A HREF="index.cfm?FuseAction=EditEvent"><font face="Verdana,Arial" size="2">Edit/Remove Events</font></A> |
11:  <A Href="index.cfm?FuseAction=ShowCalendar"><font face="Verdana,Arial" size="2">View The Calendar</font></a><br>
12: </BODY>
13: </HTML>
14:
```

```

1: <CFSET FIELDLIST =
2: "FuseCalendar_ID,CalendarDate,EventDescription,Location,Cost,Email,Website,EventName,Contact,Phone,ShowTime,FuseBox_ID">
3:
4:
5: <CFIF attributes.fuseaction IS "AddEvent">
6: <!-- If adding a new event, this code is run, setting each form field to empty. -->
7: <CFLOOP LIST="#fieldlist#" INDEX="counter">
8: <CFSET TEMP = SETVARIABLE("#counter#", "")>
9: </CFLOOP>
10: <cfset time = "10:00 AM">
11: <CFELSEIF attributes.fuseaction IS "EditEventID">
12: <!-- If the user is creating a record -->
13: <CFQUERY NAME="getEvent" DATASOURCE="#attributes.calendarDSN#">
14: select *
15: from Event
16: where FuseCalendar_ID = #attributes.FuseCalendar_ID#
17: </CFQUERY>
18:
19: <!-- We will now set the form field variables to the event to be edited based on the record taken from the query above.
    -->
20: <CFLOOP LIST="#fieldlist#" INDEX="counter">
21: <CFSET TEMP = SETVARIABLE("#counter#", "evaluate("GetEvent." & "#COUNTER#"#)">
22: </CFLOOP>
23: <cfset Time = "#TimeFormat(CalendarDate)#">
24:
25: <CFELSEIF attributes.fuseaction IS "RemoveEventID">
26: <!-- This code is similar to the editing of an event, but will just display the data that is about to be deleted. -->
27: <CFQUERY NAME="getEvent" DATASOURCE="#attributes.calendarDSN#">
28: select *
29: from Event
30: where FuseCalendar_ID = #attributes.FuseCalendar_ID#
31: </CFQUERY>
32:
33: <CFLOOP LIST="#fieldlist#" INDEX="counter">
34: <CFSET TEMP = SETVARIABLE("#counter#", "evaluate("GetEvent." & "#COUNTER#"#)">
35: </CFLOOP>
36:
37: <cfset Time = "#TimeFormat(CalendarDate)#">
38: </CFIF>
39:
40: <html>
41: <head>
42: <title>Alter the Event Data for the Calendar.</title>
43: </head>
44:
45: <Body bgcolor="#FFFFFF">
46: <p>
47: <font face="Verdana,Arial" size="2">You are about to <cfif attributes.fuseaction is "AddEvent"><B>add</B> a new event

```

```
to<cfelseif attributes.fuseaction is "EditEventID"><B>modify</B> an event on<cfelseif attributes.fuseaction is  
"RemoveEventID">remove an event on</CFIF> the Calendar.<br> Fill out the form below. All fields in <FONT  
COLOR="Red">red</FONT> are required.<p></font>  
  
<FORM ACTION="index.cfm" METHOD="post">  
  <INPUT Type="Hidden" Name="fuseaction" Value="<cfoutput>#attributes.fuseaction#Process</cfoutput>">  
  
  <INPUT TYPE="HIDDEN" NAME="FuseCalendar_ID" value="<CFOUTPUT>#FuseCalendar_ID#</CFOUTPUT>">  
  <TABLE border="0">  
  
    <TR>  
      <td valign="top"><FONT COLOR="Red">Event Name:</FONT> </td>  
      <td>  
        <INPUT TYPE="text" NAME="EventName" SIZE="20" MaxSize="100"><CFOUTPUT>value="#EventName#"</CFOUTPUT>>  
      </td>  
    </TR>  
  
    <TR>  
      <td valign="top"><FONT COLOR="Red">Location:</FONT> </td>  
      <td>  
        <INPUT TYPE="text" NAME="Location" SIZE="20" MaxSize="100"><CFOUTPUT>value="#Location#"</CFOUTPUT>>  
      </td>  
    </TR>  
  
    <TR>  
      <td valign="top"><FONT COLOR="Red">Date:</FONT> </td>  
      <td>  
        <INPUT TYPE="text" NAME="CalendarDate" SIZE="20" MaxSize="100"><CFOUTPUT>value="<cfif CalendarDate NEQ  
        "">#DateFormat(CalendarDate)#<cfelse>#DateFormat(NOW())#</CFIF>"</CFOUTPUT>>  
        <input type="hidden" Name="CalendarDate_Date" Value="The Date must be in a valid format, such as 4/27/1999">  
      </td>  
    </TR>  
  
    <TR>  
      <td valign="top">Cost:</td>  
      <td>  
        $<INPUT TYPE="text" NAME="Cost" SIZE="09" MaxSize="10" ><CFOUTPUT>value="#Cost#"</CFOUTPUT>>  
      </td>  
    </TR>  
  
    <TR>  
      <td valign="top">Time:</td>  
      <td>  
        Show? No <INPUT TYPE="Radio" NAME="ShowTime" VALUE="0" <cfif ShowTime is "NO">CHECKED</CFIF>>  
        Yes <INPUT TYPE="Radio" NAME="ShowTime" VALUE="1" <cfif ShowTime NEQ "No">CHECKED</CFIF>> Time:  
        <INPUT TYPE="text" NAME="Time" SIZE="20" MaxSize="100"><CFOUTPUT>value="#Time#"</CFOUTPUT>>  
      </td>  
    </TR>  
  </TABLE>  
  <TR>  
    <td colspan="2"></td>  
  </TR>
```

```
93: <TR>
94: <td valign="top">Contact Name:</td>
95: <td>
96: <INPUT TYPE="text" NAME="Contact" SIZE="20" MaxSize="50"><CFOUTPUT>value="#Contact#"</CFOUTPUT>>
97: </td>
98: </TR>
99:
100: <TR>
101: <td valign="top">Phone Number:</td>
102: <td>
103: <INPUT TYPE="text" NAME="phone" SIZE="20" MaxSize="50"><CFOUTPUT>value="#phone#"</CFOUTPUT>>
104: </td>
105: </TR>
106:
107: <TR>
108: <td valign="top">Email:</td>
109: <td>
110: <INPUT TYPE="text" NAME="Email" SIZE="20" MaxSize="50"><CFOUTPUT>value="#Email#"</CFOUTPUT>>
111: </td>
112: </TR>
113:
114: <TR>
115: <td valign="top">Web Site Address:</td>
116: <td>
117: http://<INPUT TYPE="text" NAME="Website" SIZE="20" MaxSize="50"><CFOUTPUT>value="#Website#"</CFOUTPUT>>
118: </td>
119: </TR>
120:
121: <TR>
122: <td valign="top"><FONT COLOR="Red">Event Description:</FONT> </td>
123: <td>
124: <TextArea NAME="Eventdescription" Cols="45" ROWS="20"
Wrap=Virtual><CFOUTPUT>#Eventdescription#</CFOUTPUT></textarea>
125: </td>
126: </TR>
127:
128: <tr>
129: <td></td>
130: <td>
131: <input type="hidden" name="FuseBox ID" Value="999">
132: <input type="hidden" name="Eventdescription_required" Value="You must provide a description for your event.">
133: <input type="hidden" name="EventName_required" Value="You must provide a name for your event.">
134: <input type="hidden" name="Location_required" Value="You must provide a location for your event.">
135: <input type="hidden" name="CalendarDate_required" Value="You must provide a description for your event.">
136: <INPUT TYPE="submit" VALUE="Just Do It!">
137: </td>
138: </TR>
139:
140: </FORM>
```

141:       </TABLE>  
142:       </body>  
143:       </html>

-----  
141:       </TABLE>  
142:       </body>  
143:       </html>



```

1:  <cfparam Name="Curntdate" default="#now()"#>
2:
3:  <cfparam name="YearSet" default="#year(Curntdate)"#>
4:  <cfparam NAME="MonthSet" Default="#month(Curntdate)"#>
5:
6:
7:  <cfset MonthStart = CreateDateTime(#YearSet#, #MonthSet#, 1, 0, 0, 0)>
8:  <cfset MonthEnd = CreateDateTime(#YearSet#, #MonthSet#, #DaysInMonth(MonthStart)#, 23, 59, 59)>
9:
10:
11:  <CFQUERY Datasource="#attributes.calendarDSN#" NAME="SearchResults">
12:    Select EventName, FuseCalendar_ID, CalendarDate
13:    From Event
14:    Where CalendarDate Between #MonthStart# and #MonthEnd#
15:  </CFQUERY>
16:
17:
18:  <HTML>
19:  <HEAD>
20:    <TITLE>Select Event to <cfif attributes.fuseaction is "RemoveEvent">Delete<cfelseif attributes.fuseaction is
      "EditEvent">Modify</CFIF>.</TITLE>
21:  </HEAD>
22:
23:
24:  <script language="javascript">
25:    function ConfirmDelete() {
26:      return confirm("Do you really want to delete this Event?")
27:    }
28:  </script>
29:
30:
31:  <BODY BGCOLOR="#FFFFFF">
32:  <cfif attributes.fuseaction is "RemoveEvent">Delete<cfelseif attributes.fuseaction is "EditEvent">Modify</CFIF>.<br><p> <font
      face="sans-serif"><b> To display an event from a different date, enter the date in the form.</b></font></p>
33:
34:  <FORM METHOD="post" ACTION="index.cfm">
35:    <B>Date:</B> <INPUT TYPE="text" NAME="Curntdate" <cfoutput>VALUE=#DateFormat(Curntdate, "mm/dd/yyyy")#</cfoutput>
      SIZE="10" MAXLENGTH="10"><br>
36:    <INPUT TYPE="Hidden" NAME="fuseaction" VALUE="EditEvent">
37:    <INPUT TYPE="hidden" NAME="Curntdate_date" VALUE="You must enter a valid date.">
38:    <INPUT TYPE="submit" NAME="GoToUserData" Value="Go To Date"></FORM>
39:  <p>
40:  <cfoutput query="SearchResults">
41:    <A HREF="index.cfm?fuseaction=EditEventID&FuseCalendar_ID=#FuseCalendar_ID#[edit]></a> <A
      HREF="index.cfm?fuseaction=RemoveEventID&Process&FuseCalendar_ID=#FuseCalendar_ID#" onclick="return
      ConfirmDelete()">[remove]</a> #EventName#</A> #DateFormat(CalendarDate)#<p>
42:  </cfoutput>
43:
44:

```

45:                   </BODY>  
46:                   </HTML>  
47:

45:                   </BODY>  
46:                   </HTML>  
47:

```
1:
2:  <a href="index.cfm?fuseaction=showcalendar"><font face="Verdana,Arial">View the Calendar</font></a> | <a
3:  href="index.cfm?fuseaction=adminmenu"><font face="Verdana,Arial">Administer the Calendar</font></a>
```

```
1:
2: <font face="verdana, arial, helvetica" size="2">
3: <a href=<cfoutput>#cgi.script_name#</cfoutput>?FUSEACTION=ADDevent>Add Event</a>
4: |
5: <a href=<cfoutput>#cgi.script_name#</cfoutput>?FUSEACTION=Editevent>Edit/Remove Event</a>
6: |
7: <a href=<cfoutput>#cgi.script_name#</cfoutput>?FUSEACTION=showcalendar>Show Calendar</a>
8:
9: </font>
10:
```

```

1: <cfparam Name="Currtdate" default="#now()#">
2: <cfif isdefined("attributes.MonthChange")>
3:   <cfif attributes.MonthChange is 'Forward'>
4:     <cfset Currtdate = CreateODBCDate(DateAdd("m", 1, attributes.Lastdate))>
5:   <cfelse>
6:     <cfset Currtdate = CreateODBCDate(DateAdd("m", -1, attributes.Lastdate))>
7:   </CFIF>
8: </CFIF>
9:
10: <cfparam name="YearSet" default="#year(Currtdate)#">
11: <cfparam NAME="MonthSet" Default="#month(Currtdate)#">
12:
13: <!-- Create the date variables to search the Database by. -->
14: <cfset MonthStart = Createdatetime(#YearSet#, #MonthSet#, 1, 0, 0, 0)>
15: <cfset MonthEnd = Createdatetime(#YearSet#, #MonthSet#, #DaysInMonth(MonthStart)#, 23, 59, 59)>
16:
17:
18:
19: <CFQUERY Datasource="#attributes.calendarDSN#" NAME="SearchResults">
20:   Select EventName, FuseCalendar_ID, CalendarDate
21:   From Event
22:   Where CalendarDate Between #MonthStart# and #MonthEnd#
23: </CFQUERY>
24:
25:
26: <CFSET Offset = #DayOfWeek(MonthStart)#>
27: <CFSET LastSlot = #Offset# + #DaysInMonth(MonthStart)#-1>
28: <CFSET CalDays = (#Ceiling(LastSlot/7)*7)>
29: <CFSET Day = 1>
30:
31:
32: <HTML>
33: <HEAD>
34:   <TITLE>DPO Calendar for <cfoutput>#DateFormat(Currtdate,"mm/dd/yyyy")#</cfoutput></TITLE>
35: </HEAD>
36:
37: <BODY BGCOLOR="#FFFFFF" LINK="#6666633" vlink="#6666633">
38:
39: <TABLE BORDER="1">
40:   <TR ALIGN="center" >
41:     <CFOUTPUT>
42:       <td BGCOLOR="ffff0" COLSPAN="2" align="center">
43:         <A HREF="index.cfm?MonthChange=Forward&Lastdate=#DateFormat(Currtdate, "mm/dd/yyyy")#&FuseAction=ShowCalendar"><font
         face="Verdana, Arial, Helvetica" size="2">Forward to #MonthAsString(Month(DateAdd("m", 1, Currtdate)))#</FONT></A><br>
         <A HREF="index.cfm?MonthChange=Backward&Lastdate=#DateFormat(Currtdate,
         "mm/dd/yyyy")#&FuseAction=ShowCalendar"><font face="Verdana, Arial, Helvetica" size="2">Back to
         #MonthAsString(Month(DateAdd("m", -1, Currtdate)))#</FONT></A></td>
44:       <td BGCOLOR="ffff0" COLSPAN="2" align="center"><FONT FACE="Verdana, Arial, Helvetica" SIZE="5"
         color="##333366">#DateFormat(Currtdate, "MMMM yyyy")#</FONT></td>
45:

```

```

46: <td bgcolor="ffffff" colspan="3" action="index.cfm">
47: <form method="post" action="index.cfm">
48: <input type="hidden" name="FuseAction" value="ShowCalendar">
49: <input type="hidden" name="Currtdate_date" value="You must enter a valid date.">
50: <font face="Verdana, Arial, Helvetica" size="2"><B>Date:</B></font>
51: <input type="text" name="Currtdate" value="#DateFormat(Currtdate, "mm/dd/yyyy")#" size="10" maxlength="10"><br>
52: <input type="submit" name="GoToUserData" value="Go To Date">
53: </form>
54: </td>
55: </cfoutput>
56: </tr>
57:
58: <tr>
59: <td align="center" width="77"><font color="#990033">SUN</font></td>
60: <td align="center" width="77"><font color="#990033">MON</font></td>
61: <td align="center" width="77"><font color="#990033">TUE</font></td>
62: <td align="center" width="77"><font color="#990033">WED</font></td>
63: <td align="center" width="77"><font color="#990033">THU</font></td>
64: <td align="center" width="77"><font color="#990033">FRI</font></td>
65: <td align="center" width="77"><font color="#990033">SAT</font></td>
66: </tr>
67:
68: <tr>
69: <cfloop index="i" from="1" to="#CalDays#">
70: <cfif #i# gte #offset# and #i# lte #LastSlot# >
71: <td valign=top width="77" height="60">
72: <cfoutput><font face="Verdana,Arial,sans-serif" size="1" color="#000080">#Day#</font><br></cfoutput>
73: <cfoutput query="SearchResults">
74: <cfif #Day# is #day(CalendarDate)#>
75: &##183: <A href="index.cfm?FuseCalendar_ID=#FuseCalendar_ID#&Currtdate=#DateFormat(Currtdate,
"mm/dd/yyyy")#&FuseAction=ShowEvent"><font face="Verdana,Arial,sans-serif" size="1">#EventName#</font></A><p>
</cfif>
</cfoutput>
</td>
78: </tr>
79: <cfset Day = #Day# + 1>
80: <cfelse>
81: <td width="77"></td>
82: </cfif>
83:
84: <cfif (#i# mod 7 is 0)>
85: </tr>
86: <tr>
87: </cfif>
88: </cfloop>
89:
90: <!-- The last TR is created in the loop above -->
91: <td colspan="7"></td>
92: </tr>
93: </table>

```

94: </BODY>  
95: </HTML>

-----

```
1:
2:
3:
4:
5:
6:
7:
8:
9:
10:
11:
12:
13:
14:
15:
16:
17:
18:
19:
20:
21:
22:
23:
24:
25:
26:
27:
28:
29:
30:
31:
32:
33:
34:
35:
36:
37:
38:
39:
40:
41:
42:
43:
44:
45:
46:
47:

<!-- Get the details for the event -->
<CFQUERY NAME="details" DataSource="#attributes.calendarDSN#">
  SELECT *
  From Event
  Where FuseCalendar_ID = #attributes.FuseCalendar_ID#
</CFQUERY>

<HTML>
<HEAD>
<TITLE>Calendar Event Information for <cfoutput>#details.EventName#</cfoutput></TITLE>
</HEAD>

<BODY BGCOLOR="#FFFFFF" vlink="#3333399" link="#3333399" alink="#3333399">
<table border="0" width="580">
<tr>
<td><br><br><p>
<center>

<CFOUTPUT query="details">
  <table cellpadding=0 cellspacing=0 width="475" border="0" BGCOLOR="##eeeeee">
<TR><td width="20"><b>sp</td>
  <td width="400">
    <!-- Show basic info about Event Here -->

    <font face="Verdana,Arial,sans-serif" size="2"><B>#EventName#</B>
<br><b>Date:</b>
    #DateFormat(CalendarDate, "mmmm d, yyyy")#<br>
    <B>Location:</B> #Location#</font>
    <cfif #ShowTime# is "yes"><br>
      <font face="Verdana,Arial,sans-serif" size="2"><B>Time:</B> #TimeFormat(CalendarDate, "h:mm tt")#</font>
</cfif>
    <CFIF #cost# is not "">
      <br><font face="Verdana,Arial,sans-serif" size="2"><B>Cost:</B> $#cost#</font>
</CFIF><br>
    <CFIF #email# is not "">
      <font face="Verdana,Arial,sans-serif" size="2"><B>Email:</B> <A HREF="mailto:#email#">#email#</A></font>
</CFIF>
<br>
    <CFIF #website# is not "">
      <font face="Verdana,Arial,sans-serif" size="2"><B>WWW:</B> <A HREF="http://#website#">#website#</A></font>
</CFIF>
<br><br><p></p>
<div align="center"><A HREF="#index.cfm?Currtdate=#urlencodedformat(DateFormat(attributes.Currtdate, "mm/dd/yyyy"))#&FuseAction=ShowCalendar"><font face="Verdana,Arial,sans-serif" size="2"><b>back to
calendar</b></A></div>
  </td>
</TR>
```



```
48: </TABLE>
49: <P>
50: <TABLE cellpadding="0" cellspacing="0" width="455" border="0" ALIGN="CENTER" valign="CENTER">
51: <TR valign="CENTER">
52: <td>
53: <CENTER>
54: <cfif #contact# NEQ "">
55: <font face="Verdana,Arial,sans-serif" size="2"><B>Contact Name:</B> #contact# </font>
56: </cfif>
57: <cfif #phone# NEQ "">
58: <font face="Verdana,Arial,sans-serif" size="2"><B>Phone:</B> #phone#</font></CENTER>
59: </cfif>
60: <p>
61: <!-- Show the text for the Event -->
62: <font face="Verdana,Arial,sans-serif" size="2">#Eventdescription#</font>
63: </td>
64: </TR>
65: </TABLE>
66: <p>
67: <A HREF="index.cfm?Curntdate=#urlencodedformat(DateFormat(attributes.Curntdate,
"mm/dd/yyyy"))#&FuseAction=ShowCalendar"><font face="Verdana,Arial,sans-serif" size="2">back to calendar</font></A>
68: </CFOUTPUT>
69: </center>
70: </td>
71: </tr>
72: </table>
73:
74: </BODY>
75: </HTML>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN"
2:
3: <cfparam name="URL.SortBy" default="Name">
4:
5: <cfquery name="qryUsers" datasource="#SourceName#">
6:   select * from Entities
7:   order by entities.parentID, entities.name
8: </cfquery>
9:
10: <cfif qryUsers.recordCount is 0>
11:   <cftransaction>
12:     <cfquery name="qryGetID" datasource="#SourceName#">
13:       select userGroup from securityGroups
14:       where securityGroups.description = 'Yakalo Administrator'
15:     </cfquery>
16:
17:     <cfquery name="qryAddDefault" datasource="#SourceName#">
18:       insert into Entities
19:       (Name, entityType, parentID, URL)
20:       values ('Yakalo Solutions', #qryGetID.userGroup#, 0, 'www.yakalo.net')
21:     </cfquery>
22:   </cftransaction>
23:
24:   <cflocation url="loginMaint.cfm" addtoken="no">
25:   </cfif>
26:
27:
28: <html>
29: <head>
30:   <cfoutput>
31:     <title>#ap_backofficeName# Backoffice</title>
32:   </cfoutput>
33:   <link rel="stylesheet" href="style1.css" type="text/css">
34: </head>
35:
36: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
37:
38: <p><cfinclude template="header.cfm"></p>
39:
40: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
41:   <tr bgcolor="#cccc99">
42:     <td colspan="5">
43:       <span class="h2"><b>User Login Administration</b></span><nbsp;<b> <a href="#CommTypeMaint.cfm">Add a user
login</a>
44:     </td>
45:   </tr>
46:
47:   <tr bgcolor="#cccccc">
48:     <td>Sort by <a href="commTypeAdm.cfm?SortBy=Name"><b>Name</b></a></td>

```

```
49:         <td>&nbsp;</td>
50:     </tr>
51:
52:
53:     <CFIF qryCommTypes.recordCount is 0>
54:         <TR><TD COLSPAN="5"><I>There are no Online Community Types defined</I></TD></TR>
55:     </CFIF>
56:     <cfset lColor = True>
57:     <cfloop query="qryCommTypes">
58:         <cfset lColor = not lColor>
59:         <tr <cfif lColor is TRUE>bgcolor="eeeeee"</cfif>>
60:             <cfoutput>
61:                 <td>#qryCommTypes.Name#</td>
62:                 <td><a href="#CommTypeMaint.cfm?TypeID=#qryCommTypes.TypeID#">Edit</a></td>
63:             </cfoutput>
64:         </tr>
65:     </cfloop>
66: </table></p>
67:
68:
69:
70: <cfquery name="qryTest" datasource="#SourceName#">
71:     select entityID as itemID, parentID as parentItemID, name from entities
72: </cfquery>
73:
74: <cfx_make_tree query="qryTest">
75:
76: <cfoutput>
77: <cfloop query="qryTest">
78:     #itemID# | #parentItemID# | #Name#<br>
79: </cfloop>
80: </cfoutput>
81:
82:
83: </body>
84: </html>
```

```
1: <p><div align="center"><div><p>
2: <CENTER><font face="Verdana, Arial" size="1"><A HREF="/">Home Page</A> | <A HREF="..agents.htm">Agents</A> | <A
3: HREF="..Propsrch.cfm">Properties</A> | <A HREF=
4: " ../SearchForm.cfm">Search</A></font></CENTER>
5: <P><CENTER>
6: <table width="353" border="0" cellspacing="0" cellpadding="0"
7: height="67">
8: <tr>
9: <td width="17%" height="51"><p></td>
10: <td width="83%" align="left"><font face="verdana, arial" size="1"><b>copy; 1999 Coldwell Banker Big Pine Realty<BR>
11: </B>227 North Commercial Street<BR> Trinidad, Colorado
12: 81082<BR>
13: Phone: (719) 846-2291 - Fax: (719) 846-1595<BR>
14: E-Mail: <A HREF="mailto:dshier@mtntown.com">dshier@mtntown.com</A></font></td></tr>
15: </table>
16: </center>
17:
18:
19:
20:
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN">
2:
3: <html>
4: <head>
5:   <title>Berkshire Eagle</title>
6:   <link rel="stylesheet" href="style1.css" type="text/css">
7: </head>
8:
9: <body bgcolor="#ffffff">
10: <CFPARAM NAME="form.Action" DEFAULT="None">
11:
12: <CFIF form.action is "SendEmail">
13:   <CFQUERY Name="qryFindUser" DATASOURCE="#SourceName#" DBTYPE="ODBC">
14:     SELECT * FROM Security
15:     WHERE Security.Email='#form.edtEmail#'
16:   </CFQUERY>
17:   <CFIF qryFindUser.recordCount is 1>
18:     <CFMAIL TO=#form.edtEmail# FROM="Yakalo Backoffice Admin"
19:     SUBJECT="Your Security Information">
20:       Hello #trim(qryFindUser.fullName)#.
21:
22:   Here is the information you requested regarding your backoffice administrator account:
23:
24:   Username: #qryFindUser.LoginName#
25:   <cfset cPassword = decrypt("#qryFindUser.password#", "#qryFindUser.loginName#(YakPass)")>
26:   Password: #cPassword#
27:
28:   If you have additional problems, please contact Yakalo Technical Support at 303-772-2212.
29:
30:   Thank you.
31:   </CFMAIL>
32:   <CFLOCATION URL="login.cfm?UserMessage=<B>Your information has been forwarded to your email address.</B>"
33:   ADDTOKEN="NO">
34:   <CFELSE>
35:     <CFLOCATION URL="login.cfm?UserMessage=<B>The email address you entered is not on file.</B>" ADDTOKEN="NO">
36:   </CFIF>
37: </CFIF>
38:
39:
40: <!-- ~~~~~~ begin content ~~~~~~ -->
41: <td valign="top">
42:   <table border="0" width="700" align="center">
43:     <CFORM NAME="frmPassword" ACTION="forgotpass.cfm?Action=SendPass">
44:       <tr><td colspan="2" align="center"><b class="bighead">Forgotten Password</b></td></tr>
45:       <tr><td><p>If you have forgotten your password, we can send it to your registered email address. Please enter your
46:       email address and we will send your registered information to you.</p>
47:       <p>After you click the 'Lookup Information' button, you should receive your registration information via
47:       email in a few minutes.</p>
```

```
48: <table border="0">
49: <tr><td>Email:</td>
50: <td><CFINPUT MESSAGE="Please enter your email address" REQUIRED="YES" TYPE="Text" Name="edtEmail"></td></tr>
51: </table></p>
52: <input type="Hidden" name="Action" value="SendEmail">
53: <input type="Submit" value="Lookup Information">
54: <input type="Button" value="Cancel" onclick="location.href='login.cfm'">
55: </td></tr>
56: </CFFORM>
57: </table>
58: </td>
59: <!-- ~~~~~ end content ~~~~~ -->
60:
61: </body>
62: </html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:  <cfinclude template="include\security.cfm">
3:
4:  <cfif not isDefined("URL.distributorID")>
5:    <cflocation url="distadm.cfm" addtoken="no">
6:  </cfif>
7:
8:  <cfparam name="URL.SortBy" default="Description">
9:
10:  <cfquery name="qryFormats" datasource="#SourceName#">
11:    SELECT pageFormatID, Description
12:    FROM pageFormat
13:    where pageFormat.distributorID = #URL.distributorID#
14:    ORDER BY #URL.SortBy#
15:  </cfquery>
16:
17:  <html>
18:  <head>
19:    <cfoutput>
20:      <title>#ap_backofficeName# Backoffice</title>
21:    </cfoutput>
22:    <link rel="stylesheet" href="style1.css" type="text/css">
23:  </head>
24:
25:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
26:
27:  <p><cfinclude template="header.cfm"></p>
28:
29:  <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
30:    <tr bgcolor="#cccc99">
31:      <cfoutput>
32:        <td colspan="5">
33:          <span class="h2"><b>Distributor Page Format Maintenance</b></span>
34:          <b><cfoutput>
35:            <td><b><a href="formatMaint.cfm?distributorID=#URL.distributorID#">Add a page format</a>
36:          </td>
37:        </cfoutput>
38:      </tr>
39:      <tr bgcolor="#cccccc">
40:        <cfoutput>
41:          <td>Sort by <a href="formatAdm.cfm?SortBy=Description&distributorID=#URL.distributorID#"><b>Description</b></a></td>
42:          <td><b></td>
43:        </cfoutput>
44:      </tr>
45:
46:
47:  <CFIF qryFormats.recordCount is 0>
48:    <TR><TD COLSPAN="5"><I>There are no page formats defined</I></TD></TR>
49:  </CFIF>

```

```
50: <cfset lColor = True>
51: <cfloop query="qryFormats">
52:   <cfset lColor = not lColor>
53:   <tr <cfif lColor is TRUE>bgcolor="eeeeee"</cfif>>
54:     <cfoutput>
55:       <td>
56:         #qryFormats.description#
57:         <cfquery name="qryFindDefault" datasource="#sourceName#">
58:           select entityType, entityID
59:             from formatAssignment
60:           where formatAssignment.pageFormatID = #qryFormats.pageFormatID#
61:         and formatAssignment.entityType = -1
62:         and formatAssignment.entityID = -1
63:         </cfquery>
64:         <cfif qryFindDefault.recordCount gt 0> (Default For All Pages)</cfif>
65:         </td>
66:         <td><a href="formatMaint.cfm?pageFormatID=#qryFormats.pageFormatID#&distributorID=#URL.distributorID#">Edit</a></td>
67:       </cfoutput>
68:     </tr>
69:   </cfloop>
70: </table></p>
71:
72: </body>
73: </html>
```



```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2: <cfinclude template="include\security.cfm">
3:
4: <CFPARAM NAME="URL.pageFormatID" DEFAULT="-1">
5:
6: <!-- Lock for the distributor passed -->
7: <cfquery name="qryFormat" datasource="#sourceName#">
8:   select *
9:   from pageFormat
10:   where pageFormat.pageFormatID = #URL.pageFormatID#
11: </cfquery>
12:
13: <cfquery name="qryPages" datasource="#sourceName#">
14:   select *
15:   from formatAssignment
16:   where formatAssignment.pageFormatID = #URL.pageFormatID#
17: </cfquery>
18:
19: <cfif qryFormat.recordCount gt 0>
20:   <cfset edtDescription = trim(qryFormat.description)>
21:   <cfset edtNavColor = trim(qryFormat.navColor)>
22:   <cfset edtMenuColor = trim(qryFormat.menuColor)>
23:   <cfset edtHeader = qryFormat.headerCode>
24:   <cfset edtSide = qryFormat.sideCode>
25:   <cfset edtFooter = qryFormat.footerCode>
26:   <cfset lstDisplayPages = "">
27:   <cfloop query="qryPages">
28:     <cfset lstDisplayPages = listAppend(lstDisplayPages, "#qryPages.entityType#|#qryPages.entityID#", ",")>
29:   </cfloop>
30: <cfelse>
31:   <cfset URL.pageFormatID = -1>
32:   <cfset edtDescription = "">
33:   <cfset edtNavColor = "#330099">
34:   <cfset edtMenuColor = "#990000">
35:   <cfset edtHeader = "">
36:   <cfset edtSide = "">
37:   <cfset edtFooter = "">
38:   <cfset lstDisplayPages = "">
39: </cfif>
40:
41: <html>
42: <head>
43:   <cfoutput>
44:     <title>#ap_backofficeName# Backoffice</title>
45:   </cfoutput>
46:   <link rel="stylesheet" href="style1.css" type="text/css">
47:   <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
48: </head>
49:

```

```
50: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" leftmarginheight="0" leftmarginwidth="0">
51:
52: <p><cfinclude template="header.cfm"></p>
53:
54: <cfoutput>
55:
56: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
57:   <form name="frmFormat" action="formatUpdate.cfm" method="post">
58:
59:     <input type="hidden" name="distributorID" value="#URL.distributorID#">
60:     <input type="hidden" name="pageFormatID" value="#URL.pageFormatID#">
61:
62:     <tr bgcolor="cccc99"><td colspan="2"><span class="h2"><b>Page Format Maintenance</b></span></td></tr>
63:
64:     <tr bgcolor="eeeeee">
65:       <td width="20%">Description:</td>
66:       <td>
67:         <input type="text" name="edtDescription" value="#edtDescription#" size="80">
68:       </td>
69:     </tr>
70:
71:     <cfset AllPages = True>
72:     <cfinclude template="..\include\linksDefines.cfm">
73:     <tr bgcolor="eeeeee">
74:       <td width="20%">Page Assignment:</td>
75:       <td>
76:         <input type="hidden" name="lstDisplayPages" value="">
77:         <select name="lstDisplayPages" size="5" multiple>
78:           <cfloop from="1" to="#listlen(listDisplayNames)#" index="nIndex">
79:             <option value="#listGetAt(listDisplayValues,nIndex)#"><cfif
listFind(listDisplayPages,#listGetAt(listDisplayValues,nIndex)#) gt 0> selected</cfif>>#listGetAt(listDisplayNames,nIndex)#
             </cfloop>
80:           </select>
81:         </td>
82:       </tr>
83:
84:     <tr bgcolor="eeeeee">
85:       <td width="20%">Navigation Color:</td>
86:       <td>
87:         <input type="text" name="edtNavColor" value="#edtNavColor#" size="10">
88:       </td>
89:     </tr>
90:
91:     <tr bgcolor="eeeeee">
92:       <td width="20%">Menu Color:</td>
93:       <td>
94:         <input type="text" name="edtMenuColor" value="#edtMenuColor#" size="10">
95:       </td>
96:     </tr>
97:   </form>
```

```
98: <tr bgcolor="eeeeee">
99: <td width="20%">Header Content:</td>
100: <td>
101: <textarea name="edtHeader" rows="5" cols="80" wrap="virtual">#HTMLEditFormat(qryFormat.headerCode)#</textarea>
102: </td>
103: </tr>
104:
105:
106: <tr bgcolor="eeeeee">
107: <td width="20%">Side Content:</td>
108: <td>
109: <textarea name="edtSide" rows="5" cols="80" wrap="virtual">#HTMLEditFormat(qryFormat.sideCode)#</textarea>
110: </td>
111: </tr>
112:
113: <tr bgcolor="eeeeee">
114: <td width="20%">Footer Content:</td>
115: <td>
116: <textarea name="edtFooter" rows="5" cols="80" wrap="virtual">#HTMLEditFormat(qryFormat.footerCode)#</textarea>
117: </td>
118: </tr>
119:
120: <tr bgcolor="eeeeee">
121: <td colspan="2">
122: <cfif qryFormat.recordCount is 0>
123: <input type="submit" name="btnUpdate" value="Add Page Format">
124: <input type="button" name="btnShowme" value="View Layout"> <!-->
125: <input type="reset" value="Reset Info">
126: </td>
127: <input type="submit" name="btnUpdate" value="Update Page Format">
128: <input type="button" name="btnShowme" value="View Layout"> <!-->
129: <input type="reset" value="Reset Info">
130: <input type="submit" name="btnDelete" value="Delete Page Format">
131: </td>
132: </tr>
133: </FORM>
134:
135: </table>
136: </cfoutput>
137:
138: </body>
139: </html>
140:
```

```
1: <cfset oldMonth = 0>
2: <cfset firstTable = "TRUE">
3:
4: <table><tr><cfoutput query="qryGetProperties">
5:   <cfset currentMonth = datePart("m",hitDate)>
6:   <cfif oldMonth neq currentMonth>
7:     <cfif not firstTable>
8:       </table></td>
9:       <cfset firstTable = "False">
10:      </cfif>
11:      <td><table border="2" bordercolor="Olive">
12:        <tr><td><b>Date</b></td><td><b>Standard<br/>Views</b></td></tr>
13:        <cfset oldMonth = currentMonth>
14:      </cfif>
15:      <tr><td>#dateFormat(hitDate,"mm/dd")#</td><td align="center">#tHits#</td></tr>
16:    </cfoutput>
17:    </table></td>
18:  </tr></table>
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2: <cfparam name="pageType" default="Agency">
3: <cfparam name="pageID" default="0">
4:
5: <cfif pageID le 0>
6:   <cflocation url="stats.cfm">
7: </cfif>
8:
9: <cfquery name="qryGetProperties" datasource="#sourceName#">
10:   SELECT c.name,a.hits AS thits, a.hitDate
11:   FROM pgCountDaily a,agency c
12:   WHERE a.distID = #ap_distributorID#
13:   AND a.pageType = '#pageType#'
14:   AND a.pageTarget = #pageID#
15:   AND a.pageTarget = c.agency_id
16:   and dateDiff(mm,a.hitDate,current_Timestamp) <= 4
17:   ORDER BY hitDate DESC
18: </cfquery>
19:
20: <cfquery name="qryGetSum" datasource="#sourceName#">
21:   SELECT sum(hits) AS sumOfHits
22:   FROM pgCountDaily
23:   WHERE distID = #ap_distributorID#
24:   AND pageType = '#pageType#'
25:   and pageTarget = #pageID#
26:   and dateDiff(mm,hitDate,current_Timestamp) <= 4
27: </cfquery>
28:
29: <html><head><title>History of Page Views</title>
30:   <link rel="stylesheet" href="style1.css" type="text/css">
31: </head>
32:
33: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
34:   <p><cfinclude template="header.cfm"></p>
35:   <cfoutput>
36:     <p align="center"><b><font color="Olive" size="+1"> History of #qryGetProperties.name# </font><br/>
37:       Viewed a total of #qryGetProperties.recordcount# days for a total of #qryGetSum.sumOfHits# page views<br/><br/>
38:   </cfoutput>
39:   <cfinclude template="pgMonthlyTables.cfm">
40: </p></body></html>
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"us
2:
3: <cfquery name="qryGetProperties" datasource="#sourceName#">
4:   SELECT d.name AS propAddress,b.firstName+' '+b.lastName AS agentName,a.hits AS tHits, a.hitDate
5:   FROM (pgPropCountDaily a
6:     LEFT OUTER JOIN prop_main d ON a.pagetarget = d.prop_id)
7:   LEFT OUTER JOIN agents b ON a.agentID = b.agent_id
8:   WHERE a.distID = #ap_distributorID#
9:     AND pagetype = 'Property'
10:    and pagetarget = #pageID#
11:   ORDER BY a.hitDate DESC
12: </cfquery>
13:
14: <cfquery name="qryGetSum" datasource="#sourceName#">
15:   SELECT sum(hits) AS sumOfHits
16:   FROM pgPropCountDaily
17:   WHERE distID = #ap_distributorID#
18:     AND pagetype = 'Property'
19:     and pagetarget = #pageID#
20: </cfquery>
21:
22: <html><head><title>History of Property Page Views</title>
23: <link rel="stylesheet" href="style1.css" type="text/css">
24: </head>
25:
26: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
27: <p><cfinclude template="header.cfm"></p>
28: <cfoutput>
29:   <p align="center"><b><font color="Olive" size="+1"> History of #qryGetProperties.propAddress# </font><br/>
30:   <font color="Olive">listed by #qryGetProperties.agentName#<br/></font> </b>
31:   Viewed a total of #qryGetProperties.recordcount# days for a total of #qryGetSum.sumOfHits# page views<br/><br/>
32: </cfoutput>
33: <cfinclude template="pgMonthlyTables.cfm">
34: </p></body></html>
```

Transitional

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <cfquery name="qryGetProperties" datasource="#sourceName#">
4:   SELECT d.prop_id,d.name AS propAddress,c.name,
5:     b.firstName+ 'b.lastName AS agentName,sum(a.hits) AS thits
6:   FROM (pgPropCountDaily a
7:     LEFT OUTER JOIN prop_main d ON a.pagetarget = d.prop_id)
8:     LEFT OUTER JOIN agents b ON a.agentID = b.agent_id
9:     LEFT OUTER JOIN agency c ON b.agency_id = c.agency_id
10:  WHERE a.distID = #ap_distributorID#
11:  AND pagetype = 'Property'
12:  GROUP BY c.name,b.firstName+ 'b.lastName,d.name,d.prop_id
13:  ORDER BY c.name,b.firstName+ 'b.lastName,sum(a.hits) DESC
14: </cfquery>
15:
16: <cfquery name="qryLastPost" datasource="#sourceName#">
17:   SELECT max(lastRun) AS dLastPost
18: FROM def_pgCountDaily
19: </cfquery>
20:
21: <html><head><title>Property Page Views</title>
22:   <link rel="stylesheet" href="style1.css" type="text/css">
23: </head>
24:
25: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
26:   <p><cfinclude template="header.cfm"></p>
27:
28:   <p align="center"><b><font color="Olive" size="+1"> Number of Page Views By Property </font><br/>
29:   <font color="Olive"><cfoutput>through #dateFormat(qryLastPost.dLastPost-1,"mmmm-dd-yyyy")#<br/></cfoutput></font> </b>
30:   <cfoutput>Total of #qryGetProperties.recordcount# properties</cfoutput>
31: </p>
32: <table>
33:   <cfoutput query="qryGetProperties" group="name">
34:     <tr><td colspan="2">
35:       <cfif isDefined("agentName") and len(agentName) gt 0>
36:         <b><font color="Green" size="+1">#name#</font></b>
37:       <cfelse>
38:         <b><font color="Green" size="+1">Unknown Agency</font></b>
39:       </cfif>
40:     </td></tr>
41:     <cfoutput group="agentName">
42:       <tr>
43:         <td colspan="2">
44:           <cfif isDefined("agentName") and len(agentName) gt 0>
45:             &nbsp;<b><cfif isDefined("agentName") and len(agentName) gt 0>
46:               &nbsp;<b><cfif isDefined("agentName") and len(agentName) gt 0>
47:                 &nbsp;<b><cfif isDefined("agentName") and len(agentName) gt 0>
48:                   &nbsp;<b><cfif isDefined("agentName") and len(agentName) gt 0>
49:                     &nbsp;<b><cfif isDefined("agentName") and len(agentName) gt 0>
```

[illegible]



```
1: <CFIF IsDefined("Form.prop_id")>
2: <CFSET Operation="Updated">
3:
4: <CFUPDATE DATASOURCE="#sourceName#" TABLENAME="prop_main">
5: <CFELSE>
6: <CFSET Operation="Inserted">
7: <CFINSERT DATASOURCE="#sourceName#" TABLENAME="prop_main">
8: </CFIF>
9: <CFQUERY DATASOURCE="#sourceName#" NAME="PropImage">
10: SELECT name, prop_id
11: FROM prop_main
12: ORDER BY prop_id DESC
13:
14: </CFQUERY>
15: <CFOUTPUT>
16:
17: <HTML>
18: <HEAD>
19: <TITLE>Property: #name#, #Operation#</TITLE>
20:
21: </HEAD>
22: <body bgcolor="white">
23: <CFINCLUDE TEMPLATE="admlinks.cfm"><p>
24: <H2><font face="Verdana,Arial" color="teal">Property:</font> <font color="Maroon"><b>#name# #PropImage.prop_id#</b></font>,
    <i>#Operation#</i> </H2>
25: <font face="Verdana, Arial"><h3>Do you want to add an image for this property?</h3></font><p>
26: <font face="Verdana, Arial" size="2">
27: If yes, Click on Property's Name/ID Number to Add Property Image:
28: <A HREF="imagadm.cfm?prop_id=#PropImage.prop_id#>#name# / #PropImage.prop_id#</A><p>
29: If no, <a href="propadm.cfm">click here to go back to Property Admin</a></font>
30: </CFOUTPUT>
31:
32: <p>
33: </BODY>
34: </HTML>
```

```

1: <cfinclude template="../propLists.cfm">
2: <cfif not isDefined("srchOrder")>
3:   <cfset srchOrder="name">
4: </cfif>
5:
6: <cfquery datasource="#sourceName#" name="qPropMain">
7:   SELECT
8:     name,
9:     price,
10:    address,
11:    city,
12:    state,
13:    prop_id,
14:    prop_type,
15:    mls_no,
16:    agent_id,
17:    status
18:  FROM prop_main
19:  <!-- WHERE #ap_agency# -->
20:  <!-- WHERE #ap_agency# = 1 Deleted 6/5/00 JHJ -->
21:  where distributorID = #ap_distributorID# <!-- 6/5/00 JHJ -->
22:  and '16-' + convert(varchar,prop_main.agent_id) + '|' in (#listQualify(client.lstSecurity,""))#)
23:
24: <cfif not isDefined("inActives") OR #inActives# NEQ "Yes">
25:   AND status > #ap_notListed#
26: </cfif>
27: ORDER BY #srchOrder#
28: </cfquery>
29:
30: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
31:
32: <html>
33: <head>
34:   <cfoutput>
35:     <title>#ap_backofficeName# Backoffice</title>
36:   </cfoutput>
37:   <link rel="stylesheet" href="style1.css" type="text/css">
38: </head>
39:
40: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
41:
42: <p><cfinclude template="header.cfm"></p>
43:
44: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
45:   <tr bgcolor="#cccc99"><td colspan="4"><b><cfoutput>#qPropMain.recordCount#
46:   </cfoutput>Properties</b></span><b><cfoutput>#qPropMain.recordCount#
47:   </cfoutput>Properties</b></span><b><cfoutput>#qPropMain.recordCount#
48:   </cfoutput>Properties</b></span><b><cfoutput>#qPropMain.recordCount#

```

```
49: <cfif not isDefined("inActives") or #inActives# neq "yes">Include Inactive Properties</a>
50: <a href="propadmn.cfm?inactives=yes">Include Inactive Properties</a>
51: </cfelse>
52: <a href="propadmn.cfm?inactives=no">Active Properties Only</a>
53: </cfif>
54: </tr>
55: <tr bgcolor="#cccccc">
56: <td valign="bottom">Sort by <a href="propadmn.cfm?srchOrder=status"><b>Status</b></a></td>
57: <td valign="bottom">Sort by <a href="propadmn.cfm?srchOrder=name"><b>Name</b></a><br>Sort by <a href="propadmn.cfm?srchOrder=address"><b>Address</b></a><br>Sort by <a href="propadmn.cfm?srchOrder=price"><b>Price</b></a></td>
58: <td valign="bottom">Sort by <a href="propadmn.cfm?srchOrder=city"><b>City</b></a><br>Sort by <a href="propadmn.cfm?srchOrder=state"><b>State</b></a><br>Sort by <a href="propadmn.cfm?srchOrder=mls_no"><b>MLS #</b></a><br>Sort by <a href="propadmn.cfm?srchOrder=mls_no"><b>MLS #</b></a></td>
59: <td>&nbsp;</td>
60: </tr>
61: <cfoutput query="qPropMain">
62: <CFQUERY NAME="qryFindOHT" DATASOURCE="#SourceName#">
63: SELECT callingID
64: FROM adData
65: WHERE adData.callingID=qPropMain.prop_id#
66: AND callingType=0
67: </CFQUERY>
68:
69: <tr bgcolor="#IIIf(CurrentRow Mod 2, DE('fffff'), DE('eeeeee'))#">
70: <td><cfif status gt 0> #listGetAt(ls_status,status)#<cfelse> Inactive </cfif></td>
71: <td><b>#name#</b><br>#address#<br>#int(price)#</td>
72: <td>#trim(city)#, #state#<br>
73: <cfif mls_no is not "">MLS #mls_no#</cfif></td>
74: <td><a href="propform.cfm?prop_id=#prop_id#">Edit</a> | <a href="propdel2.cfm?prop_id=#prop_id#">Delete</a> |
75: <CFIF qryFindOHT.recordCount is 0>
76: <a href="OHTMaint.cfm?prop_id=#qPropMain.prop_id#">Add Online Tour</a>
77: </td>
78: <a href="OHTMaint.cfm?prop_id=#qPropMain.prop_id#">Edit Online Tour</a>
79: </td>
80: </tr>
81: </cfoutput>
82: </table></p>
83:
84:
85: </body>
86: </html>
```

```
1: <CFIF IsDefined("prop_id") IS "No">
2: <h2><font face="Verdana, Arial" color="Red">Error! No Property ID was specified!</font></h2>
3: <CFABORT>
4: </CFIF>
5:
6: <CFQUERY DATASOURCE="#sourceName#">
7: UPDATE prop_main
8: SET status = 0, s_last_date = '#dateformat(now(),"mm/dd/yyyy")#'
9:
10: WHERE prop_id = #prop_id#
11: </CFQUERY>
12:
13: <cfif isDefined("URL.ReturnURL") and isDefined("URL.ReturnAgency_ID") >
14: <cfoutput>
15: <cfset cLocation = "#URL.ReturnURL#?agency_id=#URL.ReturnAgency_ID#&displayPage=Properties">
16: <cflocation URL="#cLocation#">
17: </cfoutput>
18: <cfelse>
19: <CFLOCATION URL="propadmn.cfm">
20: </cfif>
21:
22:
23:
```

```
1: <cfinclude template="include\security.cfm">
2:
3: <cfinclude template="../propLists.cfm">
4: <cfif isdefined("prop_id")>
5:   <cfset NewRecord="No">
6: <cfelse>
7:   <cfset NewRecord="Yes">
8: </cfif>
9:
10: <cfquery name="qryPropTypes" datasource="#SourceName#">
11:   select * from propTypes
12:   where distributorID = #ap_distributorID#
13: </cfquery>
14:
15: <cfif NewRecord>
16:   <cfset PageTitle = "Add Property">
17:   <cfset ButtonText = "Add Property">
18:   <cfset name = "">
19:   <cfset address = "">
20:   <cfset city = "">
21:   <cfset county = "">
22:   <cfset state = "#ap_default_state#">
23:   <cfset cntry_id = "USA">
24:   <cfset zip = "">
25:   <cfset agent_id = "01">
26:   <cfset mls_no = "">
27:   <cfset BeginDate = "#DateFormat(Now(), "mm/dd/yyyy")#">
28:   <cfset EndDate = "#DateFormat(Now()+ap_contract_duration, "mm/dd/yyyy")#">
29:   <cfset s_start_date = "#DateFormat(Now(), "mm/dd/yyyy")#">
30:   <cfset s_last_date = "12/31/40">
31:   <cfset price = "">
32:   <cfset size = "">
33:   <cfset size_unit = "">
34:   <cfset descrptn_s = "">
35:   <cfset descrptn_l = "">
36:   <cfset sold = "N">
37:   <cfset photo_name = "">
38:   <cfset hometype = "">
39:   <cfset bedroom = "">
40:   <cfset bath = "">
41:   <cfset prodscript = "">
42:   <cfset lottype = "">
43:   <cfif isdefined("URL.ReturnAgency_id")>
44:     <cfset agency_id="#URL.ReturnAgency_ID#">
45:   <cfelse>
46:     <cfset agency_id = "#ap_agency_number#">
47:   </cfif>
48:   <cfset distributorID = "#ap_distributorID#">
49:   <cfset status = "#listFindNoCase(ls_status, "new")#">
```

```

50: <cfset bambooFile = "">
51: <cfset seeItBuyIt = "">
52: <cfset salesPrice = "">
53: <cfset showPiece = "">
54: <cfset findPropType = "">
55: <cfset communityID = "-1">
56: <cfset newspaperID = #ap_distributorID#>
57: <cfset featureStart = "">
58: <cfset featureEnd = "">
59: <cfelse>
60: <cfquery datasource="#sourceName#" NAME="Property">
61:     SELECT name,
62:            address,
63:            city,
64:            county,
65:            state,
66:            cntry_id,
67:            zip,
68:            prop_main.agent_id,
69:            mls_no,
70:            BeginDate,
71:            EndDate,
72:            price,
73:            size,
74:            size_unit,
75:            prop_main.dscrptn_s,
76:            dscrptn_l,
77:            sold,
78:            photo_name,
79:            s_start_date,
80:            s_last_date,
81:            hometype,
82:            bedroom,
83:            bath,
84:            lottype,
85:            propdscrpt,
86:            agency_id,
87:            status,
88:            seeItBuyIt,
89:            bambooFile,
90:            showPiece,
91:            salesPrice,
92:            findPropType,
93:            communityID,
94:            distributorID,
95:            newspaperID,
96:            featureStart,
97:            featureEnd
98:     FROM prop_main

```

<!--Added 5/8/00 SPE -->

```

99: WHERE prop_id = #prop_id#
100: </cfquery>
101: <cfset PageTitle = "Update Property - " & Property.name & ", " & Property.city & ", " & Property.state>
102: <cfset ButtonText = "Update Property">
103: <cfset name = Trim(Property.name)>
104: <cfset address = Trim(Property.address)>
105: <cfset city = Trim(Property.city)>
106: <cfset county = Trim(Property.county)>
107: <cfset state = Trim(Property.state)>
108: <cfset cntry_id = Trim(Property.cntry_id)>
109: <cfset zip = Trim(Property.zip)>
110: <cfset agent_id = Trim(Property.agent_id)>
111: <cfset mls_no = Trim(Property.mls_no)>
112: <cfset BeginDate = dateFormat(Trim(Property.BeginDate), "mm/dd/yyyy")>
113: <cfset EndDate = dateFormat(Trim(Property.EndDate), "mm/dd/yyyy")>
114: <cfset price = Trim(Property.price)>
115: <cfset size = Trim(Property.size)>
116: <cfset size_unit = Trim(Property.size_unit)>
117: <cfset descrptn_s = Trim(Property.descrptn_s)>
118: <cfset descrptn_l = Trim(Property.descrptn_l)>
119: <cfset sold = Trim(Property.sold)>
120: <cfset photo_name = Trim(Property.photo_name)>
121: <cfset s_start_date = dateFormat(Trim(Property.s_start_date), "mm/dd/yyyy")>
122: <cfset s_last_date = dateFormat(Trim(Property.s_last_date), "mm/dd/yyyy")>
123: <cfset hometype = Trim(Property.hometype)>
124: <cfset bedroom = Trim(Property.bedroom)>
125: <cfset bath = Trim(Property.bath)>
126: <cfset lotttype = Trim(Property.lotttype)>
127: <cfset propdscrip = Trim(Property.propdscrip)>
128: <cfset agency_id = Trim(Property.agency_id)>
129: <cfset status = Trim(Property.status)>
130: <cfset bambooFile = Trim(Property.bambooFile)>
131: <cfset seeItBuyIt = trim(property.seeItBuyIt)>
132: <cfset showPiece = Trim(Property.showPiece)>
133: <cfset salesPrice = Trim(Property.salesPrice)>
134: <cfset findPropType = trim(Property.findPropType)>
135: <cfset communityID = Property.communityID>
136: <cfif isDefined("newspaperID") and len(newspaperID) gt 0>
137: <cfset newspaperID = Property.newspaperID>
138: <cfelse>
139: <cfset newspaperID = #ap_distributorID#>
140: </cfif>
141: <cfif isDefined("distributorID") and len(distributorID) gt 0>
142: <cfset distributorID = Property.distributorID>
143: <cfelse>
144: <cfset distributorID = #ap_distributorID#>
145: </cfif>
146: <cfset featureStart = dateFormat(Trim(Property.featureStart), "mm/dd/yyyy")>
147: <cfset featureEnd = dateFormat(Trim(Property.featureEnd), "mm/dd/yyyy")>

```

<!--Added 5/8/00 STE -->

```

148:
149:
150:
151:
152:
153:
154:
155:
156:
157:
158:
159:
160:
161:
162:
163:
164:
165:
166:
167:
168:
169:
170:
171:
172:
173:
174:
175:
176:
177:
178:
179:
180:
181:
182:
183:
184:
185:
186:
187:
188:
189:
190:
191:
192:
193:
194:
195:
196:

```

```

</cfif>

<cfquery datasource="#sourceName#" NAME="q_states">
  SELECT *
  FROM states
</cfquery>

<cfquery datasource="#sourceName#" NAME="q_agents">
  SELECT lastname, firstname, agent_id, lastname+, ' +firstname AS fullName
  FROM agents
  WHERE 1=1
  <cfif isDefined("URL.ReturnAgency_id")>
    and agents.agency_id=#URL.ReturnAgency_ID#
  <!-- 8/18/00 JKL - This would allow other agents to show up in the list...?
  <cfelse>
    and agents.distributorID = #ap_distributorID#
  <-->
</cfif>
  and agents.distributorID = #ap_distributorID#
  and '16-' + convert(varchar,agents.agent_id) + '-' in (#listQualify(client.lstSecurity,"")#)
  ORDER BY lastname
</cfquery>

<cfquery name="qryCommunities" datasource="#SourceName#">
  select communityID, Name
  from communities
  where communities.distributorID = #ap_distributorID#
  order by name
</cfquery>

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">

<html>
<head>
  <cfoutput>
    <title>#ap_backofficeName# Backoffice</title>
  </cfoutput>
  <link rel="stylesheet" href="style1.css" type="text/css">
</head>

<body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">

<p><cfinclude template="header.cfm"></p>

<cfif isDefined("URL.PropertyTypeID")>
  <cfset cAddURL = "?PropertyTypeID=#URL.PropertyTypeID#">
<cfelse>
  <cfset cAddURL = "">

```



```

197: </cfif>
198:
199: <cfif isDefined("URL.ReturnURL") and isDefined("URL.ReturnAgency_id") >
200:   <cfif len(trim(cAddURL)) gt 0>
201:     <cfset cReturnURL="#URL.ReturnURL#&ReturnAgency_id=#URL.ReturnAgency_ID#">
202:   <cfelse>
203:     <cfset cReturnURL="?ReturnURL=#URL.ReturnURL#&ReturnAgency_id=#URL.ReturnAgency_ID#">
204:   </cfif>
205: <cfelse>
206:   <cfset cReturnURL = "">
207: </cfif>
208:
209:
210: <cfoutput>
211: <cfform action="propPost.cfm#cAddURL#&cReturnURL#">
212: <cfif NewRecord is "No">
213:   <input type="hidden" name="prop_id" value="#prop_id#">
214: </cfif>
215: <input type="hidden" name="s_start_date" value="#s_start_date#">
216: <!-- <input type="hidden" name="prop_type" value="00"> --> <!-- Deleted 5/8/00 SFP -->
217: <input type="hidden" name="agency_id" value="#agency_id#">
218: <input type="hidden" name="newsPaperID" value="#newsPaperID#">
219: <input type="hidden" name="distributorID" value="#distributorID#">
220:
221: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
222: <tr bgcolor="#cccc99"><td colspan="2"><b>#pageTitle#</b><b>#<span>Fields in gray are
required.</td></tr>
223: <tr bgcolor="#eeeeee">
224:   <td>status:</td>
225:   <td><select name="status">
226:     <cf_optionsList ls_list="#ls_status#" defValue="#status#">
227:   </select></td>
228: </tr>
229: <tr bgcolor="#eeeeee">
230:   <td>Property Title:</td>
231:   <td><cfinput type="text" name="name" size="20" maxlength="48" value="#name#" required="yes" message="Please enter a
property title.">
232:     <input type="hidden" name="name_required" value="Please enter a property title.">
233:   </td>
234: </tr>
235: <tr bgcolor="#eeeeee">
236:   <td>Address:</td>
237:   <td><cfinput type="text" name="address" size="20" maxlength="30" value="#address#" required="yes" message="Please enter
an address.">
238:     <input type="hidden" name="address_required" value="Please enter an address.">
239:   </td>
240: </tr>
241: <tr bgcolor="#eeeeee">
242:   <td>City:</td>

```

```
243: <td><cfinput type="text" name="city" size="20" maxlength="20" value="#city#" required="yes" message="Please enter a
city.">
244: <input type="hidden" name="city_required" value="Please enter a city.">
245: </td>
246: </tr>
247: <tr>
248: <td>County:</td>
249: <td><input type="text" name="county" size="20" maxlength="18" value="#county#"></td>
250: </tr>
251: <tr bgcolor="#eeeeee">
252: <td>State:</td>
253: <td><cfif len(#state#) NEQ 4><cfset state = "#trim(state)#" "></cfif>
254: <cfselect name="state" query="q_states" display="name" value="id" selected="#state#" size="1" required="yes" message="A
state needs to be selected."></cfselect>
255: <input type="hidden" name="state_required" value="Please select a state.">
256: </td>
257: </tr>
258: <tr bgcolor="#eeeeee">
259: <td>Zip Code:</td>
260: <td><cfinput type="text" name="zip" size="10" maxlength="10" value="#trim(zip)#" required="yes" message="Please enter a
zip code. The format should be #####."> validate="zipcode">
261: <input type="hidden" name="zip_required" value="Please enter a zip code. The format should be #####.">
262: </td>
263: </tr>
264: <tr>
265: <td>Country:</td>
266: <td><input type="text" name="cntry_id" size="5" maxlength="4" value="#cntry_id#"></td>
267: </tr>
268: <tr bgcolor="#eeeeee">
269: <td>Agent:</td>
270: <td><cfselect name="agent_id" size="1" query="q_agents" value="agent_id" required="yes" selected="#agent_id#"
display="fullName"></cfselect></td>
271: </tr>
272: <tr bgcolor="#eeeeee">
273: <td>Property Type:</td>
274: <td><select name="propDscript"><cf_optionsList ls_list="#ls_propDscript" defValue="#propDscript#"></select></td>
275: </tr>
276: <tr>
277: <td>MLS Number:</td>
278: <td><input type="text" name="mls_no" size="20" maxlength="18" value="#mls_no#"></td>
279: </tr>
280: <tr bgcolor="#eeeeee">
281: <td>Begin Date:</td>
282: <td><cfinput type="text" name="begindate" size="20" maxlength="16" value="#BeginDate#" required="yes" validate="date"
message="Please enter a begin date.">
283: <input type="hidden" name="begindate_required" value="Please enter a begin date.">
284: </td>
285: </tr>
286: <tr bgcolor="#eeeeee">
```

```

287: <td>End Date:</td>
288: <td><cfinput type="text" name="enddate" size="20" maxlength="16" value="#EndDate#" required="yes" validate="yes" date="
message="Please enter an end date.">
289: <input type="hidden" name="enddate_required" value="Please enter and end date.">
290: </td>
291: </tr>
292: <tr bgcolor="#eeeeee">
293: <td>Price:</td>
294: <td>
295: <cfif trim(price) is "">
296: <cfinput type="text" name="price" size="20" maxlength="24" required="yes" validate="integer" message="Please enter a
valid price. Enter only numeric characters.">
297: </cfif>
298: <cfinput type="text" name="price" size="20" maxlength="24" value="#trim(int(price))#" required="yes"
validate="integer" message="Please enter a valid price. Enter only numeric characters.">
299: </cfif>
300: <input type="hidden" name="price_integer" value="Please enter a valid price. Enter only numeric characters.">
301: </td>
302: </tr>
303: <tr>
304: <td>Sold For Price:</td>
305: <td><input type="text" name="salesprice" size="12" maxlength="12" value="#salesPrice#"></td>
306: </tr>
307: <tr>
308: <td>Lot Acreage:</td>
309: <td><input type="text" name="size" size="18" maxlength="10" value="#size#"></td>
310: </tr>
311: <tr>
312: <td>Bldg. Sq. Ft.:</td>
313: <td><input type="text" name="size_unit" size="10" maxlength="5" value="#size_unit#"></td>
314: </tr>
315: <tr bgcolor="#eeeeee">
316: <td>Home Type:</td>
317: <td><select name="homeType"><cf_optionsList ls_list="#ls_homeType#" defValue="#homeType#"></select></td>
318: </tr>
319: <tr bgcolor="#eeeeee">
320: <td>Number of Bedrooms:</td>
321: <td><cfinput type="text" name="bedroom" size="5" maxlength="5" value="#trim(bedroom)#" required="yes" validate="float"
message="Please enter the number of bedrooms. Enter only numeric characters.">
322: <input type="hidden" name="bedroom_float" value="Please enter the number of bedrooms. Enter only numeric characters
and a decimal point, if needed.">
323: </td>
324: </tr>
325: <tr bgcolor="#eeeeee">
326: <td>Number of Baths:</td>
327: <td><cfinput type="text" name="bath" size="5" maxlength="5" value="#trim(bath)#" required="yes" validate="float"
message="Please enter the number of baths. Enter only numeric characters.">
328: <input type="hidden" name="bath_float" value="Please enter the number of baths. Enter only numeric characters and a
decimal point, if needed.">

```

```

329:         </td>
330:     </tr>
331: </tr>
332: <td>Lot Type:</td>
333: <td><select name="lotype"><cf_optionsList ls_list="#ls_lotype#" defValue="#lotype#"></select></td>
334: </tr>
335:
336:
337: <td>Community:</td>
338: <td>
339:     <select name="communityID">
340:         <option value="-1"><cfif communityID is "-1"> selected</cfif>>-None-
341:         <cfset cTestCommunity = communityID>
342:         <cfloop query="qryCommunities">
343:             <option value="#qryCommunities.communityID#"><cfif #cTestCommunity# is #qryCommunities.communityID#>
selected</cfif>>#qryCommunities.Name#
344:         </cfloop>
345:     </select>
346: </td>
347: </tr>
348:
349:
350: <td>Specialty Pages:</td>
351: <td>
352:     <select name="findPropType" multiple>
353:         <cfloop query="qryPropTypes">
354:             <option value="#qryPropTypes.propTypeID#"><cfif listFind(#findPropType#,#qryPropTypes.propTypeID#) gt 0>
selected</cfif>>#qryPropTypes.name#
355:         </cfloop>
356:     </select>
357: </td>
358: </tr>
359:
360: <tr bgcolor="#eeeeee">
361:     <td>Short Description:</td>
362:     <td><cfinput type="text" name="descrptn_s" size="30" maxLength="255" value="#descrptn_s#" required="yes" message="Please
enter a short description of the property.">
363:         <input type="hidden" name="descrptn_s_required" value="Please enter a short description of the property.">
364:     </td>
365: </tr>
366: <!--
367: <tr>
368:     <td>Bamboo URL:</td>
369:     <td><cfinput type="text" name="bamboofile" size="53" maxLength="128" value="#bamboofile#"></td>
370: </tr>
371: <!-->
372: <tr>
373:     <td>See it Buy It URL:</td>
374:     <td>

```

```

375:     <input type="text" name="seeItBuyIt" size="50" maxlength="50" value="#seeItBuyIt#">
376:     <!--Usually http://www.seeitbuyit.com/vtour.html?idnumber</i>
377:     </td>
378: </tr>
379:
380: <tr>
381:     <td>Show Piece:</td>
382:     <td><select name="showPiece" ><cf_optionslist ls_list="#ls_showPiece#" defValue="3"></select></td>
383: </tr>
384:
385: <!--
386:     <tr bgcolor="#eeeeee">
387:         <td>Feature Begin Date:</td>
388:         <td><cfinput type="text" name="featureStart" size="20" maxlength="16" value="#featureStart#" required="no"
389:             validate="date" message="Please enter a begin date.">
390:         <td><cfinput type="text" name="featureEnd" size="20" maxlength="16" value="#featureEnd#" required="no" validate="date"
391:             message="Please enter an end date.">
392:         <td><cfinput type="text" name="featureEnd_required" value="Please enter and end date.">
393:         <td><cfinput type="hidden" name="featureStart_required" value="Please enter a begin date.">
394:     </tr>
395:
396:     <tr bgcolor="#eeeeee">
397:         <td>Feature End Date:</td>
398:         <td><cfinput type="text" name="featureEnd" size="20" maxlength="16" value="#featureEnd#" required="no" validate="date"
399:             message="Please enter an end date.">
400:         <td><cfinput type="text" name="featureEnd_required" value="Please enter and end date.">
401:         <td><cfinput type="hidden" name="featureStart_required" value="Please enter a begin date.">
402:     </tr>
403:
404: <tr>
405:     <td colspan="2">Features:</td>
406:     <td colspan="2"><table border="1" rows="5" cols="50" wrap="virtual"><dscrip1_1#></td>
407:     <td colspan="2"><input type="submit" value="Submit" value="#ButtonText#">
408:     <td colspan="2"><input type="submit" value="Online Tours" name="oht">
409:     <td colspan="2"><input type="reset" value="Clear"></td>
410:     <td colspan="2"></td>
411:     <td colspan="2"></td>
412:     <td colspan="2"></td>
413:     <td colspan="2"></td>
414:     <td colspan="2"></td>
415:     <td colspan="2"></td>
416:     <td colspan="2"></td>
417:     <td colspan="2"></td>
418:     <td colspan="2"></td>

```

Country	Year	Population (millions)	Urban population (millions)	Urban population (%)	Population density (per sq km)	Urban population density (per sq km)	Population growth rate (%)	Urban population growth rate (%)	Population growth rate (%)	Urban population growth rate (%)	Population growth rate (%)	Urban population growth rate (%)
Algeria	1980	11.0	4.0	36.4	10.0	10.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	1985	11.5	4.5	39.1	10.5	10.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	1990	12.0	5.0	41.7	11.0	11.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	1995	12.5	5.5	44.0	11.5	11.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2000	13.0	6.0	46.2	12.0	12.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2005	13.5	6.5	48.1	12.5	12.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2010	14.0	7.0	50.0	13.0	13.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2015	14.5	7.5	51.7	13.5	13.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2020	15.0	8.0	53.3	14.0	14.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2025	15.5	8.5	54.8	14.5	14.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2030	16.0	9.0	56.3	15.0	15.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2035	16.5	9.5	57.6	15.5	15.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2040	17.0	10.0	58.8	16.0	16.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2045	17.5	10.5	60.0	16.5	16.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2050	18.0	11.0	61.1	17.0	17.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2055	18.5	11.5	62.2	17.5	17.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2060	19.0	12.0	63.2	18.0	18.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2065	19.5	12.5	64.1	18.5	18.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2070	20.0	13.0	65.0	19.0	19.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2075	20.5	13.5	65.9	19.5	19.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2080	21.0	14.0	66.7	20.0	20.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2085	21.5	14.5	67.4	20.5	20.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2090	22.0	15.0	68.2	21.0	21.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2095	22.5	15.5	68.9	21.5	21.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2100	23.0	16.0	69.6	22.0	22.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2105	23.5	16.5	70.2	22.5	22.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2110	24.0	17.0	70.8	23.0	23.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2115	24.5	17.5	71.4	23.5	23.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2120	25.0	18.0	72.0	24.0	24.0	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2125	25.5	18.5	72.6	24.5	24.5	1.5	1.5	1.5	1.5	1.5	1.5
Algeria	2130	26.0	19.0	73.1								

```

50:
51:
52:
53: <CFIF nCallingType is 0>
54:   <CFQUERY NAME="qryParamCntrs" DATASOURCE="#sourceName#">
55:     SELECT DISTINCT p_param.param_cntr
56:     FROM p_param
57:     WHERE p_param.dataGroup=5
58:     AND p_param.prop_id=#nCallingID#
59:     ORDER BY p_param.param_cntr
60:   </CFQUERY>
61: <CFELSEIF nCallingType is 1>
62:   <CFQUERY NAME="qryParamCntrs" DATASOURCE="#sourceName#">
63:     SELECT DISTINCT agent_param.param_cntr
64:     FROM agent_param
65:     WHERE agent_param.dataGroup=5
66:     AND agent_param.agent_id=#nCallingID#
67:     ORDER BY agent_param.param_cntr
68:   </CFQUERY>
69: <CFSET listParamCntrs = ValueList(qryParamCntrs.param_cntr)>
70:
71: <!-- Delimited lists for various uses -->
72: <CFSET listFieldNames = ValueList(qryParamNames.name)> <!-- "OHTTitle" -->
73:
74:
75: <CFOUTPUT>
76: <CFIF nCallingType is 0>
77:   <CFSET cFileName=#ap_OHT_Path# & "#nCallingID#\OHTDisplay.htm">
78: <CFELSEIF nCallingType is 1>
79:   <CFSET cFileName=#ap_OHT_Path# & "Agent#nCallingID#\OHTDisplay.htm">
80: </CFIF>
81:
82: <CFSET cToWrite = "">
83:
84: <CFSET cToWrite = cToWrite & "<HTML><HEAD><TITLE>Online Home Tour</TITLE>">
85:
86: <CFSET cToWrite = cToWrite & "<link rel=stylesheet href=../../style1.css type=text/css>">
87:
88: <CFSET cToWrite = cToWrite & "</HEAD><BODY bgcolor=#ffffff>">
89:
90: <CFIF len(trim(qryFindAd.headerfilename)) gt 0>
91:   <CFSET cToWrite = cToWrite & "<DIV ALIGN=center><IMG SRC=#qryFindAd.headerfilename#></DIV><BR>">
92: </CFIF>
93:
94: <CFFILE ACTION="WRITE"
95:   FILE="#cFileName#"
96:   OUTPUT="#cToWrite#">
97:
98:

```

```

99: <CFIF nCallingType is 0>
100: <!-- Insert information about property here -->
101: <CFQUERY NAME="qryPropInfo" DATASOURCE="#SourceName#">
102: SELECT * FROM prop_main
103: WHERE prop_main.prop_id = #qryFindAd.callingID#
104: </CFQUERY>
105:
106: <CFSET cToWrite = "<DIV ALIGN=center><TABLE WIDTH=400 BORDER=0><TR>">
107: <CFSET cToWrite = cToWrite & "<TD WIDTH=50%>#qryPropInfo.address#<BR>">
108: <CFSET cToWrite = cToWrite & "#trim(qryPropInfo.city)#, #trim(qryPropInfo.state)# #trim(qryPropInfo.zip)#</TD>">
109: <CFSET cToWrite = cToWrite & "<TD ALIGN=RIGHT WIDTH=50%>#dollarFormat(qryPropInfo.price)#</TD>">
110:
111: <CFSET cToWrite = cToWrite & "</TR></TABLE></DIV>">
112:
113: <CFELSEIF nCallingType is 1>
114: <!-- Insert information about the agent here -->
115: <cfquery name="qryAgentInfo" datasource="#SourceName#">
116: select firstname, lastname, title, specialty, workphone, faxphone, cellphone, email, homephone, pub_home, otherPhone,
agency_id, agencyEmail
from agents
where agents.agent_id=#qryFindAd.callingID#
</cfquery>
117:
118: <cfquery name="qryAgencyInfo" datasource="#SourceName#">
119: select name
120: from agency
121: where agency.agency_id=#qryAgentInfo.agency_id#
122: </cfquery>
123:
124: <cfset cToWrite = cToWrite & "<DIV ALIGN=center><TABLE WIDTH=575 BORDER=0>">
125: <cfset cToWrite = cToWrite & "<tr><td align=center colspan=4><h3><b>#trim(qryAgentInfo.firstName)#</td>">
126: #trim(qryAgentInfo.lastName)#>
127: <cfif len(trim(qryAgentInfo.title)) gt 0>
128: <cfset cToWrite = cToWrite & ", #qryAgentInfo.title#">
129: </cfif>
130: <cfset cToWrite = cToWrite & "</b></h3></td></tr>">
131:
132: <CFSET cToWrite = cToWrite & "<tr><TD align=right><b>Specialty:</b></td><td>#qryAgentInfo.specialty#</td>">
133: <CFSET cToWrite = cToWrite & "<TD align=right><b>Work Phone:</b></td><td>#qryAgentInfo.workphone#</td></tr>">
134: <CFSET cToWrite = cToWrite & "<tr><TD align=right><b>Fax Number:</b></td><td>#qryAgentInfo.faxphone#</td>">
135: <CFSET cToWrite = cToWrite & "<TD align=right><b>Cell Phone:</b></td><td>#qryAgentInfo.cellphone#</td></tr>">
136:
137: <cfif len(trim(qryAgentInfo.otherPhone)) gt 0>
138: <CFSET cToWrite = cToWrite & "<tr><td align=right><b>Other Phone:</b></td><td>#qryAgentInfo.otherPhone#</td>">
139: <CFSET cToWrite = cToWrite & "</tr><td align=right><b>pub_home is 'Y'">
140: <CFELSE>
141: <cfset cToWrite = cToWrite & "<tr><td align=right><b>pub_home is 'Y'">
142: <CFIF>
143: <cfset cToWrite = cToWrite & "<tr><td align=right><b>pub_home is 'Y'">
144: <CFIF>
145: <cfif len(trim(qryAgentInfo.homePhone)) gt 0 AND qryAgentInfo.pub_home is "Y">

```



```

146:         <CFSET cToWrite = cToWrite & "<TD align=right><b>Residence Phone:</b></td><td>#qryAgentInfo.homePhone#</td></tr>">
147:     </cfelse>
148:     <cfset cToWrite = cToWrite & "<td>&nbsp;</td><td>&nbsp;</td></tr>">
149: </cfif>
150:
151:     <cfif len(trim(qryAgentInfo.email)) gt 0>
152:         <CFSET cToWrite = cToWrite & "<tr><TD align=right><b>Email:</b></td><td><a href=mailto:#{qryAgentInfo.email}#{qryAgentInfo.email}#</a></td>">
153:     </cfelse>
154:     <cfset cToWrite = cToWrite & "<tr><td>&nbsp;</td><td>&nbsp;</td></tr>">
155: </cfif>
156:
157:     <cfif len(trim(qryAgencyInfo.name)) gt 0>
158:         <cfset cToWrite = cToWrite & "<td align=right><b>Agency:</b></td><td>#qryAgencyInfo.name#</td></tr>">
159:     </cfelse>
160:     <cfset cToWrite = cToWrite & "<tr><td>&nbsp;</td><td>&nbsp;</td></tr>">
161: </cfif>
162:
163:     <cfif len(trim(qryAgentInfo.agencyEmail)) gt 0>
164:         <cfset cToWrite = cToWrite & "<tr><td>&nbsp;</td><td>&nbsp;</td></tr>">
165:     <cfset cToWrite = cToWrite & "<td align=right><b>Agency Email:</b></td><td>#qryAgentInfo.agencyEmail#</td></tr>">
166:     </cfelse>
167:     </cfif>
168:
169:     <cfset cToWrite = cToWrite & "<tr><td align=center colspan=4><a href=../../FindProperty_Result.cfm?agent_id=#qryFindAd.callingID#>#qryAgentInfo.firstName#</a></td></tr>">
170:
171:     <CFSET cToWrite = cToWrite & "</TABLE></DIV>">
172:
173: </CFIF>
174: <CFFILE ACTION="APPEND"
175:     FILE="#cFileName#"
176:     OUTPUT="#cToWrite#">
177:
178: <CFSET cToWrite = "<TABLE BORDER=0 CELLSPACING=10 ALIGN=CENTER WIDTH=600>">
179: <CFFILE ACTION="APPEND"
180:     FILE="#cFileName#"
181:     OUTPUT="#cToWrite#">
182:
183:
184: <CFLOOP FROM=1 TO=#listlen(listParamCntrs)# INDEX=nParamIndex>
185:     <CFSET cToWrite = ">
186:
187:     <!-- Title -->
188:     <CFIF nCallingType is 0>
189:         <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
190:             SELECT param_value FROM p_param
191:             WHERE prop_id=#nCallingID# AND dataGroup=5
192:             AND param_cntr=#listGetAt(listParamCntrs,nParamIndex)#

```

```

193:         AND param_name='OHTTitle'
194:     </CFQUERY>
195:     <CFELSEIF nCallingType is 1>
196:         <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
197:             SELECT param_value FROM agent_param
198:             WHERE agent_id=#nCallingId# AND dataGroup=5
199:             AND param_cnr=#listGetAt(listParamCntrs,nParamIndex)#
200:             AND param_name='OHTTitle'
201:         </CFQUERY>
202:     </CFIF>
203:     <CFSET cTitle = qryFindInfo.param_value>
204:     <CFIF len(trim(cTitle)) gt 0>
205:         <CFSET cUseTitle = "YES">
206:     <CFELSE>
207:         <CFSET cUseTitle = "NO">
208:     </CFIF>
209:
210:     <!-- Image Align -->
211:     <CFIF nCallingType is 0>
212:         <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
213:             SELECT param_value FROM p_param
214:             WHERE prop_id=#nCallingId# AND dataGroup=5
215:             AND param_cnr=#listGetAt(listParamCntrs,nParamIndex)#
216:             AND param_name='OHTImgAln'
217:         </CFQUERY>
218:     <CFELSEIF nCallingType is 1>
219:         <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
220:             SELECT param_value FROM agent_param
221:             WHERE agent_id=#nCallingId# AND dataGroup=5
222:             AND param_cnr=#listGetAt(listParamCntrs,nParamIndex)#
223:             AND param_name='OHTImgAln'
224:         </CFQUERY>
225:     </CFIF>
226:     <CFSET cImageAlign = ucase(qryFindInfo.param_value)>
227:
228:     <!-- Image Name -->
229:     <CFIF nCallingType is 0>
230:         <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
231:             SELECT param_value FROM p_param
232:             WHERE prop_id=#nCallingId# AND dataGroup=5
233:             AND param_cnr=#listGetAt(listParamCntrs,nParamIndex)#
234:             AND param_name='OHTImage'
235:         </CFQUERY>
236:     <CFELSEIF nCallingType is 1>
237:         <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
238:             SELECT param_value FROM agent_param
239:             WHERE agent_id=#nCallingId# AND dataGroup=5
240:             AND param_cnr=#listGetAt(listParamCntrs,nParamIndex)#
241:             AND param_name='OHTImage'

```

```

242:      </CFQUERY>
243:    </CFIF>
244:    <CFSET cImageName = qryFindInfo.param_value>
245:
246:    <!-- Text -->
247:    <CFIF nCallingType is 0>
248:      <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
249:        SELECT param_value FROM p_param
250:        WHERE prop_id=#nCallingID# AND dataGroup=5
251:        AND param_cntr=#listGetAt(listParamCntrs,nParamIndex)#
252:        AND param_name='OHTText'
253:      </CFQUERY>
254:      <CFELSEIF nCallingType is 1>
255:        <CFQUERY NAME="qryFindInfo" DATASOURCE="#SourceName#">
256:          SELECT param_value FROM agent_param
257:          WHERE agent_id=#nCallingID# AND dataGroup=5
258:          AND param_cntr=#listGetAt(listParamCntrs,nParamIndex)#
259:          AND param_name='OHTText'
260:        </CFQUERY>
261:      </CFIF>
262:      <CFIF len(trim(cImageName)) gt 0>
263:        <CFSET cToWrite = cToWrite & "<TR><TD><P>">
264:        <CFIF cImageAlign is "MIDDLE">
265:          <CFSET cToWrite = cToWrite & "<DIV ALIGN=center><IMG SRC=#getFileFromPath(cImageName) # BORDER=0 ALIGN=cImageAlign#
            HSPACE=4></DIV>">
266:          <CFELSE>
267:            <CFSET cToWrite = cToWrite & "<IMG SRC=#getFileFromPath(cImageName) # BORDER=0 ALIGN=cImageAlign# HSPACE=4>">
268:          </CFIF>
269:        <CFELSE>
270:          <CFSET cToWrite = cToWrite & "<TR><TD><P>">
271:        </CFIF>
272:
273:        <CFIF cUseTitle is "YES">
274:          <CFSET cToWrite = cToWrite & "<H3>#cTitle#</H3>">
275:        </CFIF>
276:
277:        <CFIF qryFindInfo.recordCount GT 0 and len(trim(qryFindInfo.param_value)) gt 0>
278:          <CFSET cToWrite = cToWrite & "#paragraphFormat(qryFindInfo.param_value) #</TD></TR>">
279:        <CFELSE>
280:          <CFSET cToWrite = cToWrite & "</P></TD></TR>">
281:        </CFIF>
282:
283:        <CFFILE ACTION="APPEND"
284:          FILE="#cFileName#"
285:          OUTPUT="#cToWrite#">
286:      </CFLOOP>
287:
288:      <CFSET cToWrite="</TABLE>">
289:

```

```

290: <CFIF len(trim(qryFindAd.footerfilename)) gt 0>
291:   <CFSET cToWrite = cToWrite & "<DIV ALIGN=center><IMG SRC=#qryFindAd.footerfilename#></DIV>">
292: </CFIF>
293:
294: <CFSET cToWrite = cToWrite & "</BODY></HTML>">
295:
296:
297: <CFFILE ACTION="APPEND"
298:   FILE="#cFileName#"
299:   OUTPUT="#cToWrite#">
300:
301: <CFQUERY NAME="qryUpdateAd" DATASOURCE="#SourceName#">
302:   UPDATE AdData
303:   SET ohtfilename='OHT/images/<cfif nCallingType is 1>Agent</cfif>#nCallingID#/OHTDisplay.htm'
304:   WHERE adData.callingID=#nCallingID# AND
305:         adData.callingType=#nCallingType#
306: </CFQUERY>
307: </CFOUTPUT>
308:
309: <!-- All done with generation, so now go back to main display mode for this property -->
310: <CFIF nCallingType is 0>
311:   <CFLOCATION URL="OHTMaint.cfm?prop_id=#nCallingID#" ADDTOKEN="NO">
312: <CFELSEIF nCallingType is 1>
313:   <CFLOCATION URL="OHTMaint.cfm?agent_id=#nCallingID#" ADDTOKEN="NO">
314: </CFIF>
315: </body>
316: </html>

```

```

1:  <cfparam name="URL.Action" default="View">
2:  <cfparam name="dgStill" default="1">  <!-- Still types? -->
3:  <cfparam name="URL.parm counter" default="-1">  <!-- If editing, this will have a number -->
4:  <cfparam name="URL.EnteredFields" default="">  <!-- these are fields already entered before changing the image type -->
5:  <cfparam name="URL.ImageType" default="0">  <!-- the image type -->
6:  <cfparam name="URL.CallingType" default="0">  <!-- Calling Type (0=Prop_id, 1=Agent_id) -->
7:
8:  <cfparam name="URL.prop_id" default="-1">
9:  <cfparam name="URL.agent_id" default="-1">
10:
11:  <cfif URL.prop_id gt -1>
12:    <cfset nCallingID = URL.prop_id>
13:    <cfset nCallingType = 0>
14:    <cfelseif URL.agent_id gt -1>
15:    <cfset nCallingID = URL.agent_id>
16:    <cfset nCallingType = 1>
17:    <cfelse>
18:    <!-- We don't know what we are trying to look up -->
19:    <cflocation URL="ohtadm.cfm" addtoken="NO">
20:  </cfif>
21:
22:  <cfif nCallingType is 0>
23:    <!-- Find the agent based on the passed prop_id -->
24:    <cfquery name="qryAgent" datasource="#sourceName#">
25:      SELECT prop_main.agent_id,agents.name,agents.firstname,agents.lastname
26:    FROM prop_main,agents
27:    WHERE prop_main.prop_id = #nCallingID#
28:    AND prop_main.agent_id = agents.agent_id
29:  </cfquery>
30:  <cfelseif nCallingType is 1>
31:    <!-- Find the agent based on the passed agent_id -->
32:    <cfquery name="qryAgent" datasource="#sourceName#">
33:      SELECT agent_id,name,firstname,lastname
34:    FROM agents
35:    WHERE agents.agent_id = #nCallingID#
36:  </cfquery>
37:  </cfif>
38:
39:  <cfif qryAgent.recordCount is 0>
40:    <!-- If an agent could not be found, then go back -->
41:    <CFIF nCallingType is 0>
42:      <cflocation URL="ohtadm.cfm" addtoken="NO">
43:    <CFELSEIF nCallingType is 1>
44:      <cflocation URL="AgentBioadm.cfm" addtoken="NO">
45:    <CFELSE>
46:      <cflocation URL="ohtadm.cfm" addtoken="NO">
47:    </CFIF>
48:  </cfif>
49:

```

```

50: <!-- First get the address information about this property -->
51: <CFIF nCallingType is 0>
52:   <cfquery name="qryPropertyInfo" datasource="#sourceName#">
53:     SELECT prop_id, name, city, state
54:     FROM prop_main
55:     WHERE prop_main.prop_id = #URL.prop_id#
56:   </cfquery>
57: </CFIF>
58:
59: <!-- Get specific parameter information about this property -->
60: <CFIF nCallingType is 0>
61:   <cfquery name="qryParameters" datasource="#sourceName#">
62:     SELECT p_param.param_id, p_param.agency_id, p_param.param_name, p_param.param_value, p_param.param_cntr,
63:            param_defs.description, param_defs.label, param_defs.displayOrder, param_defs.restrictions, param_defs.type
64:     FROM param_defs, p_param
65:     WHERE p_param.prop_id=#URL.prop_id#
66:           AND p_param.param_id = param_defs.id
67:           ORDER BY p_param.param_cntr,param_defs.displayOrder
68:   </cfquery>
69: <CFELSEIF nCallingType is 1>
70:   <cfquery name="qryParameters" datasource="#sourceName#">
71:     SELECT agent_param.param_id, agent_param.agency_id, agent_param.param_name, agent_param.param_value,
72:            param_defs.description, param_defs.label, param_defs.displayOrder, param_defs.restrictions, param_defs.type
73:     FROM param_defs, agent_param
74:     WHERE agent_param.agent_id=#nCallingID#
75:           AND agent_param.param_id = param_defs.id
76:           ORDER BY agent_param.param_cntr,param_defs.displayOrder
77:   </cfquery>
78: </CFIF>
79:
80: <!-- Parameter names for the image fields -->
81: <cfquery name="qryParamNames" datasource="#sourceName#">
82:   SELECT
83:     DISTINCT id, name, description, label, displayOrder, restrictions, type, selectOptions
84:   FROM param_defs
85:   WHERE securityLevel=1
86:   AND dataGroup = 5
87:   ORDER BY displayOrder
88: </cfquery>
89:
90:
91: <!-- qryImageTypes will load the image types for the pull down while
92:   adding or editing a photo -->
93: <cfquery name="qryImageTypes" datasource="#sourceName#">
94:   SELECT label,counter,value,agency_id
95:   FROM param_allowed
96:   WHERE param_allowed.id = 9
97:   ORDER BY param_allowed.counter

```



```

146:         <CFSET URL.Action = "View">
147:     <CFELSEIF URL.Action is "Edit">
148:         <!-- A Paragraph has been selected for editing -->
149:
150:     <CFELSEIF URL.Action is "Deleted">
151:         <!-- Delete the selected image -->
152:         <!-- Set default values for the edit fields -->
153:         <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
154:             <CFSET aFieldValues[nIndex] = "">
155:         </CFLOOP>
156:
157:         <!-- <br><br><font color="red" size="2">Paragraph has been removed!</font></br><br> -->
158:         <CFSET URL.Action = "View">
159:     <CFELSEIF URL.Action is "Updated">
160:         <!-- Set default values for the edit fields -->
161:         <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
162:             <CFSET aFieldValues[nIndex] = "">
163:         </CFLOOP>
164:
165:         <!-- <br><br><font color="teal" size="2">Paragraph has been updated!</font></br><br> -->
166:         <CFSET URL.Action = "View">
167:     </CFIF>
168:
169:     <CFQUERY NAME="qryFindAd" DATASOURCE="#SourceName#">
170:         SELECT * FROM AdData
171:         WHERE CallingID=#nCallingID#
172:         AND callingType=#nCallingType#
173:     </CFQUERY>
174:     <tr bgcolor="eeeeee">
175:         <td width="20%">
176:             <CFIF nCallingType is 0>
177:                 <form name="frmAdData" enctype="multipart/form-data" action="OHTAdUpdate.cfm?prop_id=#nCallingID#" method="post">
178:                     <CFELSEIF nCallingType is 1>
179:                         <form name="frmAdData" enctype="multipart/form-data" action="OHTAdUpdate.cfm?agent_id=#nCallingID#" method="post">
180:                     </CFIF>
181:                     Header Image:</td>
182:                 <td>
183:                     <input type="FILE" name="edtHeader">
184:                     <cfif qryFindAd.recordCount gt 0><em>Currently: #getFileFromPath(qryFindAd.headerFilename) #</em></cfif></td>
185:                 </tr>
186:                 <tr bgcolor="eeeeee">
187:                     <td width="20%">Footer Image:</td>
188:                     <td>
189:                         <input type="FILE" name="edtFooter">
190:                         <cfif qryFindAd.recordCount gt 0><em>Currently: #getFileFromPath(qryFindAd.footerFilename) #</em></cfif></td>
191:                     </tr>
192:                     <tr bgcolor="eeeeee">
193:                         <td width="20%">URL:</td>
194:                         <td><input type="TEXT" name="edtURL" value="#qryFindAd.OtherURL#"></td>

```



```

195: </tr>
196: <tr bgcolor="eeeeee">
197:   <td width="20%">Run Dates:</td>
198:   <td>From <input type="TEXT" size="10" name="edtStartDate" value="#DateFormat(qryFindAd.startDate,"mm/dd/yyyy")#"> To
199:   <input type="TEXT" size="10" name="edtStopDate" value="#dateformat(qryFindAd.stopDate,"mm/dd/yyyy")#"></td>
200: </tr>
201: <input type="hidden" name="edtPrimaryPic" value="">
202: <!--
203: <tr bgcolor="eeeeee">
204:   <td width="20%">Primary Picture:</td>
205:   <td>
206:     <input type="FILE" name="edtPrimaryPic">
207:     <cfif qryFindAd.recordCount gt 0><em>Currently: #getFileFromPath(qryFindAd.primaryPic)</em></cfif></td>
208:   </tr>
209:
210:   <tr bgcolor="eeeeee">
211:     <td colspan="2">
212:       <font color="red">Recommended image size for Primary Picture is 150 pixels in width by 75 pixels in height.</font>
213:     </td>
214:   </tr>
215:   <tr bgcolor="eeeeee">
216:     <td colspan="2">
217:       <cfif qryFindAd.recordCount is 0>
218:         <CFIF nCallingType is 0>
219:           <input type="submit" name="btnUpdate" value="Add Tour Info">
220:         <CFELSEIF nCallingType is 1>
221:           <input type="submit" name="btnUpdate" value="Add Agent Info">
222:         </CFIF>
223:       <cfelse>
224:         <CFIF nCallingType is 0>
225:           <input type="submit" name="btnUpdate" value="Update Tour">
226:         <CFELSEIF nCallingType is 1>
227:           <input type="submit" name="btnUpdate" value="Update Info">
228:         </CFIF>
229:       </cfif>
230:     <input type="reset" value="Clear">
231:     <cfif qryFindAd.recordCount gt 0>
232:       <CFIF nCallingType is 0>
233:         <input type="submit" name="btnGenerate" value="Generate Tour">
234:       <CFELSEIF nCallingType is 1>
235:         <input type="submit" name="btnGenerate" value="Generate Page">
236:       </CFIF>
237:     <cfif len(trim(qryFindAd.ohthtfilename)) gt 0>
238:       <CFIF nCallingType is 0>
239:         <input type="BUTTON" name="btnShowMe" value="Display Tour"
240:         onclick="location.href='../oht/images/#nCallingID#/ohtdisplay.htm'">
241:       <CFELSEIF nCallingType is 1>
242:         <input type="BUTTON" name="btnShowMe" value="Display Page"

```

```

242: onclick="location.href='../oht/images/Agent#nCallingID#ohtdisplay.htm'">
243:     </CFIF>
244:     </cfif>
245:     <CFIF nCallingType is 0>
246:         <input type="submit" name="btnDelete" value="Delete Tour">
247:         <CFELSEIF nCallingType is 1>
248:             <input type="submit" name="btnDelete" value="Delete Page">
249:         </CFIF>
250:     </cfif>
251:     <cfif nCallingType is 0>
252:         <input type="button" name="btnToMenu" value="Show All" onclick="location.href='ohtadm.cfm'">
253:         <cfelseif nCallingType is 1>
254:             <input type="button" name="btnToMenu" value="Show All" onclick="location.href='agentbioadm.cfm'">
255:         </cfif>
256:     </form>
257: </td>
258: </tr>
259: </table></p>
260: <cfif qryFindAd.recordcount gt 0>
261: <p><table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
262:     <!-- First see if there are any images to display -->
263:     <cfif #qryParameters.recordcount# is 0>
264:         <tr bgcolor="cccccc">
265:             <td><b class="h2">No paragraphs are associated with this <CFIF nCallingType is 0>property<CFELSEIF nCallingType is
1>agent</CFIF></b></td>
266:         </td></tr>
267:     </cfelse>
268:     <!-- there are paragraphs, so display the labels first -->
269:     <tr bgcolor="cccccc">
270:         <cfloop from="1" TO="#listlen(listLabels)#" index="nIndex">
271:             <td align="center"><b>#listGetAt(listLabels, nIndex)#</b></td>
272:         </cfloop>
273:         <td colspan="2"><b><tabsp></td></tr>
274:     </cfif>
275:
276:     <!-- Now for the actual data -->
277:     <CFSET lEditrow = False>
278:     <CFSET cImageName = "">
279:     <CFSET nRow = 0>
280:     <CFSET nOldParamCounter = -1>
281:     <CFSET nParamCounter = -1>
282:     <CFSET nMaxParamCounter = -1>
283:     <CFSET nColumn = 0>
284:
285:     <CFLOOP QUERY="qryParameters">
286:         <CFSET nRow = nRow + 1>
287:         <CFIF qryParameters.param_name IS listGetAt(listFieldNames, 1)>
288:             <CFSET nColumn = 0>

```

```

289: <CFSET nMaxParamCounter = max(nMaxParamCounter, qryParameters.param_cntr)>
290: <CFSET nParamCounter = qryParameters.param_cntr>
291: <CFIF nParamCounter is URL.param_counter>
292: <CFSET lEditrow = TRUE>
293: <CFELSE>
294: <CFSET lEditrow = FALSE>
295: </CFIF>
296: <tr bgcolor="eeeeee">
297: </CFIF>
298: <CFSET nColumn = nColumn + 1>
299: <CFIF lEditrow>
300: <CFSET aFieldValues[nColumn] = qryParameters.param_value>
301: </CFIF>
302: <CFIF listGetAt(listFieldNames,nColumn) is "imgType">
303: <td <CFIF lEditrow IS true>bgcolor="ffffff"</CFIF> valign="top">
304: <CFIF qryParameters.param_value is "0">
305: Standard Photo
306: <CFIF lEditrow is true><CFSET URL.ImageType = "0"></CFIF>
307: <CFELSEIF qryParameters.param_value is "1">
308: Bamboo Image
309: <CFIF lEditrow is true><CFSET URL.ImageType = "1"></CFIF>
310: <CFELSEIF qryParameters.param_value is "2">
311: IPIX Image
312: <CFIF lEditrow is true><CFSET URL.ImageType = "2"></CFIF>
313: <CFELSE>
314: #qryParameters.param_value#
315: <CFIF lEditrow is true><CFSET URL.ImageType = "-1"></CFIF>
316: </CFIF>
317: </td>
318: <CFELSE>
319: <td <CFIF lEditrow IS true>bgcolor="ffffff"</CFIF> valign="top">
320: <cfif trim(qryParameters.param_value) IS "">
321: &nbsp;
322: <cfelse>
323: #HTMLEditFormat(qryParameters.param_value)#
324: </CFIF></td>
325: </CFIF>
326:
327: <CFIF nColumn is nTotalCols-2> <!-- the last column with info was displayed -->
328: <td <CFIF lEditrow is true>bgcolor="ffffff"</CFIF> colspan="2" valign="top">
329: <CFIF nCallingType is 0>
330: <a href="OHTMaint.cfm?Action=Edit&prop_id=#URL.prop_id&parm_counter=#qryParameters.param_cntr#">Edit</a><hr>
331: <a href="OHTUpdate.cfm?Action=Delete&prop_id=#URL.prop_id&parm_counter=#qryParameters.param_cntr#">Delete</a></td>
332: <CFELSEIF nCallingType is 1>
333: <a href="OHTMaint.cfm?Action=Edit&agent_id=#nCallingID#&parm_counter=#qryParameters.param_cntr#">Edit</a><hr>
334: <a href="OHTUpdate.cfm?Action=Delete&agent_id=#nCallingID#&parm_counter=#qryParameters.param_cntr#">Delete</a></td>
335: </CFIF>

```

```

336:      </td>
337:    </tr>
338:    <CFSET nColumn = 0>
339:    </CFIF>
340:  </CFLOOP>
341:
342:  </table></p>
343:
344:  <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
345:    <!-- Now allow the user to add or edit an image -->
346:    <tr bgcolor="cccccc">
347:      <td colspan="#nTotalCols#"
348:        <CFIF #URL.Action# is "Add">
349:          <b>Add A Paragraph</b>:
350:          <input type="hidden" name="Action" VALUE="Add">
351:          <CFELSEIF #URL.Action# is "Edit">
352:            <b>Edit Selected Paragraph:</b>
353:            <input type="hidden" name="Action" VALUE="Edit">
354:            <CFELSEIF #URL.Action# is "View">
355:              <b>Add A Paragraph:</b>
356:              <input type="hidden" name="Action" VALUE="Add">
357:            </CFIF>
358:          </td>
359:        </tr>
360:
361:      <tr>
362:        <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
363:          <td bgcolor="eeeeee" valign="bottom">
364:            <!-- Moved the text area (paragraph) to a row immediately under the other input data --3pg 0404800-->
365:            <cfif findNoCase("Text", #listGetAt(listLabels, nIndex)#) neq 0>
366:              <cfset labelId = #nIndex#>
367:              <cfelse>
368:                <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, nIndex)#</b></font>
369:              </cfif>
370:            </td>
371:          </CFLOOP>
372:        </tr>
373:
374:        <form name="frmValues" enctype="multipart/form-data" action="OHTUpdate.cfm" method="post">
375:          <tr valign="top" bgcolor="eeeeee">
376:            <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
377:              <CFSET cFieldType = ucase(trim(listGetAt(listFieldTypes, nIndex)))>
378:              <CFIF cFieldType is "TEXT">
379:                <CFIF listGetAt(listFieldNames, nIndex) is "imgType">
380:                  <td>
381:                    <CFIF #URL.Action# is "Edit">
382:                      <CFIF aFieldValues[nIndex] is "0">
383:                        <I>Standard Photo</I><br>
384:                        <CFELSEIF aFieldValues[nIndex] is "1">

```

```

385:      <I>Bamboo Image</I><br>
386:      <CFELSEIF aFieldValues[nIndex] is "2">
387:      <I>PIX Image</I><br>
388:      <CFELSE>
389:      <I>#aFieldValues[nIndex]#</I><br>
390:      </CFIF>
391:      </CFIF>
392:      <SELECT NAME="FIELD#nIndex#">
393:      <CFLOOP QUERY="qryImageTypes">
394:      <CFIF URL.ImageType is "0" and qryImageTypes.value is "0">
395:      <CFSET lShowOption = true>
396:      <CFELSEIF URL.ImageType is not "0" and qryImageTypes.value is not "0">
397:      <CFSET lShowOption = true>
398:      <CFELSE>
399:      <CFSET lShowOption = False>
400:      </CFIF>
401:      <CFIF lShowOption is true>
402:      <OPTION value=#qryImageTypes.value# <CFIF #trim(aFieldValues[nIndex])# is
      #trim(qryImageTypes.value)#>SELECTED</CFIF>#trim(label)#</OPTION>
      </CFIF>
403:      </CFLOOP>
404:      </SELECT>
405:      <br>
406:      <CFIF URL.Action is not "Edit">
407:      <!-- If they want to change the image type, they will need to delete the image and reenter it -->
408:      <CFIF URL.ImageType is "0">
409:      <CFIF nCallingType is 0>
410:      <font face="Verdana, Arial" size="1"><a
      href="OHTMaint.cfm?Action=#URL.Action#&prop_id=#URL.prop_id#&ImageType=1&parm_counter=#URL.parm_counter#">To Add Bamboo or
      IPIX<br>images, Click Here</a><br><font color="red">(Warning: by clicking,<br>form will reset.)</font></font>
      <CFELSEIF nCallingType is 1>
411:      <font face="Verdana, Arial" size="1"><a
      href="OHTMaint.cfm?Action=#URL.Action#&agent_id=#nCallingID#&ImageType=1&parm_counter=#URL.parm_counter#">To Add Bamboo or
      IPIX<br>images, Click Here</a><br><font color="red">(Warning: by clicking,<br>form will reset.)</font></font>
      </CFIF>
412:      <CFELSE>
413:      <CFIF nCallingType is 0>
      <font face="Verdana, Arial" size="1"><a
      href="OHTMaint.cfm?Action=#URL.Action#&prop_id=#URL.prop_id#&ImageType=0&parm_counter=#URL.parm_counter#">To Add a standard
      photo, Click Here</a><br><font color="red">(Warning: by clicking,<br>form will reset.)</font></font>
      <CFELSEIF nCallingType is 1>
414:      <font face="Verdana, Arial" size="1"><a
      href="OHTMaint.cfm?Action=#URL.Action#&agent_id=#nCallingID#&ImageType=0&parm_counter=#URL.parm_counter#">To Add a standard
      photo, Click Here</a><br><font color="red">(Warning: by clicking,<br>form will reset.)</font></font>
      </CFIF>
415:      </CFIF>
416:      </td>
417:      <CFELSE>
418:      <CFIF nCallingType is 0>
419:      <font face="Verdana, Arial" size="1"><a
      href="OHTMaint.cfm?Action=#URL.Action#&prop_id=#URL.prop_id#&ImageType=0&parm_counter=#URL.parm_counter#">To Add a standard
      photo, Click Here</a><br><font color="red">(Warning: by clicking,<br>form will reset.)</font></font>
      <CFELSEIF nCallingType is 1>
420:      <font face="Verdana, Arial" size="1"><a
      href="OHTMaint.cfm?Action=#URL.Action#&agent_id=#nCallingID#&ImageType=0&parm_counter=#URL.parm_counter#">To Add a standard
      photo, Click Here</a><br><font color="red">(Warning: by clicking,<br>form will reset.)</font></font>
      </CFIF>
421:      </CFIF>
422:      </td>
423:      </td>
424:      <CFELSE>

```

```

425:         <td>
426:         <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
427:         </td>
428:     </CFIF>
429:     <CFELSEIF cFieldType is "FILE">
430:     <td>
431:     <CFIF URL.Action# is "Edit">
432:     <CFIF URL.ImageType is "0">
433:     <I>#getFileFromPath(aFieldValues[nIndex])#</I><br>
434:     <CFELSE>
435:     #aFieldValues[nIndex]#<br>
436:     </CFIF>
437:     </CFIF>
438:     <CFIF URL.ImageType is "0">
439:     <INPUT TYPE="FILE" NAME="Field#nIndex#" SIZE="20">
440:     <CFELSE>
441:     <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
442:     </CFIF>
443:     </td>
444:     <CFELSEIF cFieldType is "TEXTAREA">
445:     <td>
446:     <!-- Moved the text area to a row immediately under the other input data --SPL 0404800 -->
447:     <cfset textId = #nIndex#>
448:     </td>
449:     <CFELSEIF cFieldType is "CHECKBOX">
450:     <td ALIGN="CENTER">
451:     <INPUT TYPE="CHECKBOX" NAME="Field#nIndex#" SIZE="70" <CFIF #aFieldValues[nIndex]# is "ON">CHECKED</CFIF>>
452:     </td>
453:     <CFELSEIF cFieldType is "SELECT">
454:     <td>
455:     <CFSET listColOptions = replace(ListGetAt(listFieldOptions, nIndex,"|"),",","","All")>
456:     <CFIF listlen(listColOptions) gt 0>
457:     <SELECT NAME="Field#nIndex#">
458:     <CFLOOP FROM="1" TO="#listlen(listColOptions)#" INDEX="nListInd">
459:     <CFSET cOption = listGetAt(listColOptions, nListInd, ",")>
460:     <OPTION <CFIF #aFieldValues[nIndex]# is #cOption#>SELECTED</CFIF>#cOption#
461:     </CFLOOP>
462:     </SELECT>
463:     </CFIF>
464:     </td>
465:     </CFIF>
466:     </CFLOOP>
467:     </tr>
468:     <tr valign="top" bgcolor="teal">
469:     <!-- Moved the text area to a row immediately under the other input data --SPL 0404900-->
470:     <td colspan="#listlen(listLabels)#">
471:     <cfif isDefined("textId")>
472:     <font faces="Verdana, Arial" size="2"><b>#listGetAt(listLabels, labelId)#</b>:</font><br>
473:     <TEXTAREA ROWS="8" COLS="80" WRAP="VIRTUAL" NAME="Field#textId#">#HTMLEditFormat(aFieldValues[textId])#</TEXTAREA>

```

```

474:         </cfif>
475:         </td>
476:     </tr>
477:     <tr bgcolor="eeeeee">
478:         <td colspan="#nTotalCols#">
479:             <CFIF nMaxParamCounter is -1>
480:                 <CFSET nMaxParamCounter = 1>
481:             </CFELSE>
482:                 <CFSET nMaxParamCounter = nMaxParamCounter + 1>
483:             </CFIF>
484:             <CFIF #URL.Action# is "View">
485:                 <input type="hidden" name="Action" VALUE="ADD">
486:                 <INPUT TYPE="SUBMIT" VALUE="Add New Paragraph" NAME="btnSubmit">
487:             </CFIF>
488:             <input type="hidden" name="parm_counter" VALUE="#nMaxParamCounter#">
489:             <CFELSEIF #URL.Action# is "Edit">
490:                 <input type="hidden" name="Action" VALUE="EDIT">
491:                 <INPUT TYPE="SUBMIT" VALUE="Update Paragraph">
492:                 <INPUT TYPE="RESET" VALUE="Reset Information">
493:                 <CFIF nCallingType is 0>
494:                     <INPUT TYPE="BUTTON" VALUE="Cancel" NAME="btnSubmit"
ONCLICK="location.href='OHTMaint.cfm?prop_id=#prop_id&Action=View'">
                     <CFELSEIF nCallingType is 1>
495:                         <INPUT TYPE="BUTTON" VALUE="Cancel" NAME="btnSubmit"
ONCLICK="location.href='OHTMaint.cfm?agent_id=#nCallingID&Action=View'">
496:                     </CFIF>
497:                 </CFIF>
498:             <input type="hidden" name="parm_counter" VALUE="#URL.Parm_Counter#">
499:             </td>
500:         </td>
501:     </tr>
502: </tr>
503:
504: <CFSET nImageTypeField = listFindNoCase(listFieldNames, "imgType")>
505:
506: <input type="hidden" name="imageField" VALUE="#nImageTypeField#">
507: <CFIF nCallingType is 0>
508:     <input type="hidden" name="prop_id" VALUE="#URL.prop_id#">
509: <CFELSEIF nCallingType is 1>
510:     <input type="hidden" name="agent_id" VALUE="#nCallingID#">
511: </CFIF>
512: <input type="hidden" name="FieldLabels" VALUE="#listLabels#">
513: <input type="hidden" name="FieldTypes" VALUE="#listFieldTypes#">
514: <input type="hidden" name="Field_Names" VALUE="#listFieldNames#">
515: </form>
516: </taole></p>
517:
518: </cfif>
519: </cfoutput>
520:

```

521: </body>  
522: </html>

-----



```

1: <cfparam name="URL.Action" default="View">
2: <cfparam name="dgStill" default="1"> <!-- Still types? -->
3: <cfparam name="URL.param_counter" default="-1"> <!-- If editing, this will have a number -->
4: <cfparam name="URL.EnteredFields" default=""> <!-- these are fields already entered before changing the image type -->
5: <cfparam name="URL.ImageType" default="0"> <!-- the image type -->
6: <cfparam name="URL.CallingType" default="0"> <!-- Calling Type (0=Prop_id, 1=Agent_id) -->
7:
8: <cfparam name="URL.prop_id" default="-1">
9: <cfparam name="URL.agent_id" default="-1">
10:
11: <cfif URL.prop_id gt -1>
12:   <cfset nCallingID = URL.prop_id>
13:   <cfset nCallingType = 0>
14: <cfelseif URL.agent_id gt -1>
15:   <cfset nCallingID = URL.agent_id>
16:   <cfset nCallingType = 1>
17: <cfelse>
18:   <!-- We don't know what we are trying to look up -->
19:   <cflocation URL="ohtadm.cfm" addtoken="NO">
20: </cfif>
21:
22: <cfif nCallingType is 0>
23:   <!-- Find the agent based on the passed prop_id -->
24:   <cfquery name="qryAgent" datasource="#sourceName#">
25:     SELECT prop_main.agent_id,agents.name
26:     FROM prop_main,agents
27:     WHERE prop_main.prop_id = #nCallingID#
28:     AND prop_main.agent_id = agents.agent_id
29:   </cfquery>
30:   <cfelseif nCallingType is 1>
31:     <!-- Find the agent based on the passed agent_id -->
32:     <cfquery name="qryAgent" datasource="#sourceName#">
33:       SELECT agent_id,name
34:       FROM agents
35:       WHERE agents.agent_id = #nCallingID#
36:     </cfquery>
37:   </cfif>
38:
39:   <cfif qryAgent.recordCount is 0>
40:     <!-- If an agent could not be found, then go back -->
41:     <cflocation URL="ohtadm.cfm" addtoken="NO">
42:   </cfif>
43:
44:   <!-- First get the address information about this property -->
45:   <cfquery name="qryPropertyInfo" datasource="#sourceName#">
46:     SELECT prop_id, name, city, state
47:     FROM prop_main
48:     WHERE prop_main.prop_id = #URL.prop_id#
49:   </cfquery>

```

```

50:
51: <!-- Get specific parameter information about this property -->
52: <cfquery name="qryParameters" datasource="#sourceName#">
53:   SELECT p_param.param_id, p_param.agency_id, p_param.param_name, p_param.param_value, p_param.param_cntr,
54:     param_defs.description, param_defs.label, param_defs.displayOrder, param_defs.restrictions, param_defs.type
55:   FROM param_defs, p_param
56:   WHERE p_param.prop_id=#URL.prop_id#
57:     AND p_param.param_id = param_defs.id
58:   ORDER BY p_param.param_cntr,param_defs.displayOrder
59: </cfquery>
60:
61: <!-- Parameter names for the image fields -->
62: <cfquery name="qryParamNames" datasource="#sourceName#">
63:   SELECT
64:     DISTINCT id, name, description, label, displayOrder, restrictions, type, selectOptions
65:   FROM param_defs
66:   WHERE securityLevel=1
67:     AND dataGroup = 5
68:   ORDER BY displayOrder
69: </cfquery>
70:
71:
72: <!-- qryImageTypes will load the image types for the pull down while
73:   adding or editing a photo -->
74: <cfquery name="qryImageTypes" datasource="#sourceName#">
75:   SELECT label,counter,value,agency_id
76:   FROM param_allowed
77:   WHERE param_allowed.id = 9
78:   ORDER BY param_allowed.counter
79: </cfquery>
80:
81:
82: <!-- Delimited lists for various uses -->
83: <cfset listLabels = ValueList(qryParamNames.label)> <!-- "Use Name" -->
84: <cfset listFieldNames = ValueList(qryParamNames.name)> <!-- "OPTION" -->
85: <cfset listFieldTypes = ValueList(qryParamNames.type)> <!-- TEXT, Field, etc. -->
86: <cfset listFieldOptions = QuotedValueList(qryParamNames.selectOptions,"|")>
87:
88: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
89:
90: <html>
91: <head>
92:   <cfoutput>
93:     <title#ap_backofficeName# Backoffice</title>
94:   </cfoutput>
95:   <link rel="stylesheet" href="style1.css" type="text/css">
96:   <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
97: </head>
98:

```

```

99: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" style="margin-left: 40px; margin-right: 40px; margin-top: 40px; margin-bottom: 40px; width: 100%; height: 100%; border: 1px solid black; padding: 5px;">
100:
101: <p><cfinclude template="header.cfm"></p>
102:
103: <cfoutput>
104: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
105: <tr bgcolor="cccc99"><td colspan="2"><span class="h2"><b>Online Home Tours</b></span></td></tr>
106: <tr bgcolor="cccccc"><td colspan="2"><b>General Online Home Tour Property Information</b><b><br><b>Property
ID</b>: #URL.prop_id# <b>Agent</b>: #qryAgent.name#</td></tr>
107: <!-- #? because of Edit and Delete columns -->
108: <CFSET nTotalCols = qryParamNames.recordCount+2>
109: <CFSET aFieldValues = ArrayNew(1)>
110:
111: <CFIF URL.Action is "View">
112: <!-- Set default values for the edit fields -->
113: <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
114: <CFSET aFieldValues[nIndex] = "">
115: </CFLOOP>
116:
117: <CFELSEIF URL.Action is "Add">
118: <!-- Up'oad and add the parsed paragraph information to the database -->
119:
120: <!-- <br><br><font color="teal" size="+2">Paragraph has been added!</font></b><br><br> -->
121: <CFSET URL.Action = "View">
122: <CFELSEIF URL.Action is "Edit">
123: <!-- A Paragraph has been selected for editing -->
124:
125: <CFELSEIF URL.Action is "Deleted">
126: <!-- Delete the selected image -->
127: <!-- Set default values for the edit fields -->
128: <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
129: <CFSET aFieldValues[nIndex] = "">
130: </CFLOOP>
131:
132: <!-- <br><br><font color="red" size="+2">Paragraph has been removed!</font></b><br><br> -->
133: <CFSET URL.Action = "View">
134: <CFELSEIF URL.Action is "Updated">
135: <!-- Set default values for the edit fields -->
136: <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
137: <CFSET aFieldValues[nIndex] = "">
138: </CFLOOP>
139:
140: <!-- <br><br><font color="teal" size="+2">Paragraph has been updated!</font></b><br><br> -->
141: <CFSET URL.Action = "View">
142: </CFIF>
143:
144: <CFQUERY NAME="qryFindAd" DATASOURCE="#SourceName#">
145: SELECT * FROM AdData
146: WHERE CallingID=#nCallingID#

```

```
147: AND callingType=#nCallingType#
148: </CFQUERY>
149: <tr bgcolor="eeeeee">
150: <td width="20%">
151: <form name="frmAddData" enctype="multipart/form-data" action="OHTAdUpdate.cfm?prop_id=#URL.prop_id#" method="post">
152: Header Image:</td>
153: <td>
154: <input type="FILE" name="edtHeader">
155: <cfif qryFindAd.recordCount gt 0><em>Currently: #getFileFromPath(qryFindAd.headerFilename) #</em></cfif></td>
156: </tr>
157: <tr bgcolor="eeeeee">
158: <td width="20%">Footer Image:</td>
159: <td>
160: <input type="FILE" name="edtFooter">
161: <cfif qryFindAd.recordCount gt 0><em>Currently: #getFileFromPath(qryFindAd.footerFilename) #</em></cfif></td>
162: </tr>
163: <tr bgcolor="eeeeee">
164: <td width="20%">URL:</td>
165: <td><input type="TEXT" name="edtURL" value="#qryFindAd.OtherURL#"></td>
166: </tr>
167: <tr bgcolor="eeeeee">
168: <td width="20%">Run Dates:</td>
169: <td>From <input type="TEXT" size="10" name="edtStartDate" value="#DateFormat(qryFindAd.startDate,"mm/dd/yyyy") #> To
170: <input type="TEXT" size="10" name="edtStopDate" VALUE="#dateformat(qryFindAd.stopDate,"mm/dd/yyyy") #></td>
171: </tr>
172: <tr bgcolor="eeeeee">
173: <td colspan="2">
174: <input type="submit" name="btnUpdate" value="Add Tour Info">
175: <cfelse>
176: <input type="submit" name="btnUpdate" value="Update Tour">
177: </cfif>
178: <input type="reset" value="Reset Info">
179: <cfif qryFindAd.recordCount gt 0>
180: <input type="submit" name="btnGenerate" value="Generate Tour">
181: <cfif len(trim(qryFindAd.ohthFilename)) gt 0>
182: <input type="BUTTON" name="btnShowMe" value="Display Tour"
onclick="location.href='../oht/images/#URL.prop_id#/ohtdisplay.htm'">
</cfif>
183: <input type="submit" name="btnDelete" value="Delete Tour">
184: </cfif>
185: <input type="button" name="btnToMenu" value="Display All Tours" onclick="location.href='ohtadm.cfm'">
186: </form>
187: </td>
188: </tr>
189: </table></p>
190: <cfif qryFindAd.recordcount gt 0>
191: <p><table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
192: <tr>
193: <td colspan="2">
```



```

243:      IPIX Image
244:      <CFIF lEditrow is true><CFSET URL.ImageType = "2"></CFIF>
245:      <CFELSE>
246:      #qryParameters.param_value#
247:      <CFIF lEditrow is true><CFSET URL.ImageType = "-1"></CFIF>
248:      </CFIF>
249:      </td>
250:      <CFELSE>
251:      <td <CFIF lEditrow IS true>bgcolor="ffffff"></CFIF> valign="top">#qryParameters.param_value#</td>
252:      </CFIF>
253:
254:      <CFIF nColumn is nTotalCols-2> <!-- the last column with info was displayed -->
255:      <td <CFIF lEditrow is true>bgcolor="ffffff"></CFIF> colspan="2" valign="top">
256:      <a href="OHTMaint.cfm?Action=Edit&prop_id=#URL.prop_id&param_counter=#qryParameters.param_cntr#">Edit</a>
257:      <a href="OHTUpdate.cfm?Action=Delete&prop_id=#URL.prop_id&param_counter=#qryParameters.param_cntr#">Delete</a></td>
258:      </td>
259:      </tr>
260:      <CFSET nColumn = 0>
261:      </CFIF>
262:      </CFLOOP>
263:
264:      </table></p>
265:
266:      <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
267:      <!-- Now allow the user to add or edit an image -->
268:      <tr bgcolor="cccccc">
269:      <td colspan="#nTotalCols#">
270:      <CFIF #URL.Action# is "Add">
271:      <b>Add A Paragraph</b>:
272:      <input type="hidden" name="Action" VALUE="Add">
273:      <CFELSEIF #URL.Action# is "Edit">
274:      <b>Edit Selected Paragraph:</b>
275:      <input type="hidden" name="Action" VALUE="Edit">
276:      <CFELSEIF #URL.Action# is "View">
277:      <b>Add A Paragraph:</b>
278:      <input type="hidden" name="Action" VALUE="Add">
279:      </CFIF>
280:      </td>
281:      </tr>
282:
283:      <tr>
284:      <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
285:      <td bgcolor="eeeeee" valign="bottom">
286:      <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, nIndex)#</b></font>
287:      </td>
288:      </CFLOOP>
289:      </tr>
290:
291:      <form name="frmValues" enctype="multipart/form-data" action="OHTUpdate.cfm" method="post">

```

```

292: <tr valign="top" bgcolor="eeeeee">
293: <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
294: <CFSET cFieldType = ucase(trim(listGetAt(listFieldTypes, nIndex)))>
295: <CFIF cFieldType is "TEXT">
296: <CFIF listGetAt(listFieldNames, nIndex) is "imgType">
297: <td>
298: <CFIF #URL.Action# is "Edit">
299: <CFIF aFieldValues[nIndex] is "0">
300: <I>Standard Photo</I><br>
301: <CFELSEIF aFieldValues[nIndex] is "1">
302: <I>Bamboo Image</I><br>
303: <CFELSEIF aFieldValues[nIndex] is "2">
304: <I>IPIX Image</I><br>
305: <CFELSE>
306: <I>#aFieldValues[nIndex]#</I><br>
307: </CFIF>
308: </CFIF>
309: <SELECT NAME="FIELD#nIndex#">
310: <CFLOOP QUERY="qryImageTypes">
311: <CFIF URL.ImageType is "0" and qryImageTypes.value is "0">
312: <CFSET lShowOption = true>
313: <CFELSEIF URL.ImageType is not "0" and qryImageTypes.value is not "0">
314: <CFSET lShowOption = true>
315: <CFELSE>
316: <CFSET lShowOption = False>
317: </CFIF>
318: <CFIF lShowOption is true>
319: <OPTION value=#qryImageTypes.value# <CFIF #trim(aFieldValues[nIndex])# is
#trim(qryImageTypes.value)#>SELECTED</CFIF>#trim(label)#</OPTION>
</CFIF>
</CFLOOP>
</SELECT>
<br>
<CFIF URL.Action is not "Edit">
<!-- If they want to change the image type, they will need to delete the image and reenter it -->
<CFIF URL.ImageType is "0">
<font face="Verdana, Arial" size="1"><a
href="OHTMaint.cfm?Action=#URL.Action#&prop_id=#URL.prop_id&ImageType=1&param_counter=#URL.param_counter#">To Add Bamboo or
IPIX<br>images, Click Here</a></font>
<CFELSE>
<font face="Verdana, Arial" size="1"><a
href="OHTMaint.cfm?Action=#URL.Action#&prop_id=#URL.prop_id&ImageType=0&param_counter=#URL.param_counter#">To Add a
standard photo, Click Here</a></font>
</CFIF>
</td>
<CFELSE>
<td>
<INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">

```

```

336:         </td>
337:     </CFIF>
338:     <CFELSEIF cFieldType is "FILE">
339:         <td>
340:             <CFIF #URL.Action# is "Edit">
341:                 <CFIF URL.ImageType is "0">
342:                     <I>#getFileFromPath(aFieldValues[nIndex])#</I><br>
343:                 <CFELSE>
344:                     #aFieldValues[nIndex]#<br>
345:                 </CFIF>
346:             </CFIF>
347:             <CFIF URL.ImageType is "0">
348:                 <INPUT TYPE="FILE" NAME="Field#nIndex#" SIZE="20">
349:             <CFELSE>
350:                 <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
351:             </CFIF>
352:         </td>
353:     <CFELSEIF cFieldType is "TEXTAREA">
354:         <td>
355:             <TEXTAREA ROWS="8" COLS="30" WRAP="VIRTUAL" NAME="Field#nIndex#">#aFieldValues[nIndex]#</TEXTAREA>
356:         </td>
357:     <CFELSEIF cFieldType is "CHECKBOX">
358:         <td ALIGN="CENTER">
359:             <INPUT TYPE="CHECKBOX" NAME="Field#nIndex#" SIZE="70" <CFIF #aFieldValues[nIndex]# is "ON">CHECKED</CFIF>>
360:         </td>
361:     <CFELSEIF cFieldType is "SELECT">
362:         <td>
363:             <CFSET listColOptions = replace(ListGetAt(listFieldOptions, nIndex,"|"), "','',"All")>
364:             <CFIF listlen(listColOptions) gt 0>
365:                 <SELECT NAME="Field#nIndex#">
366:                     <CFLOOP FROM="1" TO="#listlen(listColOptions)#" INDEX="nListInd">
367:                         <CFSET option = listGetAt(listColOptions, nListInd, ", ")>
368:                         <OPTION <CFIF #aFieldValues[nIndex]# is #option#>SELECTED</CFIF>>#option#
369:                     </CFLOOP>
370:                 </SELECT>
371:             </CFIF>
372:         </td>
373:     </CFIF>
374: </CFLOOP>
375: </tr>
376:
377: <tr bgcolor="eeeeee">
378:     <td colspan="#nTotalCols#">
379:         <CFIF nMaxParamCounter is -1>
380:             <CFSET nMaxParamCounter = 1>
381:         <CFELSE>
382:             <CFSET nMaxParamCounter = nMaxParamCounter + 1>
383:         </CFIF>
384:         <CFIF #URL.Action# is "View">

```



```
385: <input type="hidden" name="Action" value="ADD">
386: <INPUT TYPE="SUBMIT" VALUE="Add New Paragraph" NAME="btnSubmit">
387:
388: <input type="hidden" name="param_counter" VALUE="#nMaxParamCounter#">
389: <CFELSEIF #URL.Action# is "Edit">
390: <input type="hidden" name="Action" VALUE="EDIT">
391: <INPUT TYPE="SUBMIT" VALUE="Update Paragraph">
392: <INPUT TYPE="RESET" VALUE="Reset Information">
393: <INPUT TYPE="BUTTON" VALUE="Cancel" NAME="btnSubmit"
ONCLICK="location.href='OHTMaint.cfm?prop_id=#prop_id#&Action=View'">
394: <input type="hidden" name="param_counter" VALUE="#URL.Param_Counter#">
395: </CFIF>
396: </td>
397: </tr>
398:
399: <CFSET nImageTypeField = listFindNoCase(listFieldNames,"imgType")>
400:
401: <input type="hidden" name="imageField" VALUE="#nImageTypeField#">
402: <input type="hidden" name="prop_id" VALUE="#URL.prop_id#">
403: <input type="hidden" name="FieldLabels" VALUE="#listLabels#">
404: <input type="hidden" name="FieldTypes" VALUE="#listFieldTypes#">
405: <input type="hidden" name="FieldNames" VALUE="#listFieldNames#">
406: </form>
407: </table></p>
408:
409: </cfif>
410: </cfoutput>
411:
412: </body>
413: </html>
```

```
1: <CFPARAM NAME="ACTION" DEFAULT="Cancel">
2:
3: <CFIF isDefined("prop_id")>
4:   <CFSET nCallingID = prop_id>
5:   <CFSET nCallingType = 0>
6:   <CFELSEIF isDefined("agent_id")>
7:     <CFSET nCallingID = agent_id>
8:     <CFSET nCallingType = 1>
9:   </CFIF>
10:
11: <!--- <CFSET prop_id = #prop_id#> --->
12:
13: <HTML>
14: <TITLE>Property Image Upload Results</TITLE>
15:
16: <CFIF #Action# is "Cancel">
17:   <CFIF nCallingType is 0>
18:     <CFLOCATION URL="imageMaint.cfm?prop_id=#nCallingID#" ADDTOKEN="NO">
19:   <CFELSEIF nCallingType is 1>
20:     <CFLOCATION URL="imageMaint.cfm?agent_id=#nCallingID#" ADDTOKEN="NO">
21:   </CFIF>
22:
23: </CFIF>
24:
25: <BODY BGCOLOR="WHITE">
26:   <!--- <CFINCLUDE TEMPLATE="acmlinks.cfm" ><p>--->
27:   <CFAPPLICATION NAME="RealStuff" CLIENTMANAGEMENT="Yes">
28:
29:   <CFIF #Action# is "Add">
30:     Field Values:<BR>
31:     <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
32:       <CFSET cNewField = "FORM.Field" & nIndex>
33:       <CFOUTPUT>#cNewField# = #evaluate(cNewField)#<BR></CFOUTPUT>
34:     </CFLOOP>
35:     <BR>
36:     <HR>
37:
38:
39:   <!--- First try to find out what kind of image is being uploaded --->
40:   <CFSET nImageTypeLoc = listFindNoCase(FORM.Field_Names,'imgType')>
41:   <CFIF nImageTypeLoc GT 0>
42:     <CFSET cImageField = 'FORM.FIELD' & nImageTypeLoc>
43:     <CFSET nImageType = #evaluate(cImageField)#>
44:     <CFOUTPUT>Image Type : #nImageType#<BR></CFOUTPUT>
45:   <CFELSE>
46:     <CFSET nImageType = -1>
47:   </CFIF>
48:
49:   <!--- !!!!!!! --->
```

```

50: <!-- <CFSET nImageType = 0> -->
51:
52: <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
53:   <CFSET nParamID = -1>
54:
55:   <CFQUERY NAME="qryFindParamID" DATASOURCE="#SourceName#">
56:     SELECT * FROM param_defs
57:     WHERE dataGroup=5
58:     AND agency_id in (10, #ap_agency_number#)
59:     AND name='#listGetAt(FORM.Field_Names,nIndex) #'
60:   </CFQUERY>
61:
62:   <CFIF qryFindParamID.recordCount GT 0>
63:     <CFSET nParamID = qryFindParamID.id>
64:   </CFIF>
65:
66:   <CFSET cFieldType = ucase(trim(listGetAt(FORM.FieldTypes, nIndex)))>
67:   <CFSET cNewField = "FORM.FIELD" & nIndex>
68:
69:   <CFIF cFieldType is "TEXT">
70:     <cfoutput>Inserting data:
71:     #nCallingID#, #nParamID#, #ap_agency_number#, #parm_counter#, #qryFindParamID.name#, #Evaluate(cNewField)#, 5</cfoutput> <br>
72:     <CFSET cTextToSend = evaluate(cNewField)>
73:     <CFSET cTextToSend = preservesingleQuotes(cTextToSend)>
74:     <CFIF nCallingType is 0>
75:       <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
76:         INSERT INTO p_param(prop_id,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
77:         VALUES (#prop_id#, #nParamID#, #ap_agency_number#, #parm_counter#, #qryFindParamID.name#, '#cTextToSend', 5)
78:       </CFQUERY>
79:     <CFELSEIF nCallingType is 1>
80:       <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
81:         INSERT INTO agent_param(agent_id,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
82:         VALUES (#nCallingID#, #nParamID#, #ap_agency_number#, #parm_counter#, '#cTextToSend', 5)
83:       </CFIF>
84:     <CFELSEIF cFieldType is "TEXTAREA">
85:       <cfoutput>Inserting Text Area data:
86:       #nCallingID#, #nParamID#, #ap_agency_number#, #parm_counter#, #qryFindParamID.name#, #Evaluate(cNewField)#, 5</cfoutput> <br>
87:       <CFSET cTextToSend = evaluate(cNewField)>
88:       <CFSET cTextToSend = preservesingleQuotes(cTextToSend)>
89:       <CFIF nCallingType is 0>
90:         <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
91:           INSERT INTO p_param(prop_id,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
92:           VALUES (#prop_id#, #nParamID#, #ap_agency_number#, #parm_counter#, #qryFindParamID.name#, '#cTextToSend', 5)
93:         </CFQUERY>
94:       <CFELSEIF nCallingType is 1>
95:         <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
96:           INSERT INTO agent_param(agent_id,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
97:           VALUES (#nCallingID#, #nParamID#, #ap_agency_number#, #parm_counter#, #qryFindParamID.name#, '#cTextToSend', 5)

```

```

97:      </CFQUERY>
98:    </CFIF>
99:    <CFELSEIF cFieldType is "CHECKBOX">
100:      <cfoutput>Inserting checkbox data:
101:      #nCallingID#, #nParamID#, #ap_agency_number#, #parm_counter#, 'qryFindParamID.name#', #Evaluate(cNewField)#', 5</cfoutput> <br>
102:      <CFSET cTextToSend = evaluate(cNewField)>
103:      <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
104:      <CFIF nCallingType is 0>
105:        <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
106:          INSERT INTO p_param(prop_id,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
107:          VALUES (#prop_id#, #nParamID#, #ap_agency_number#, #parm_counter#, 'qryFindParamID.name#', #cTextToSend#, 5)
108:        </CFQUERY>
109:      <CFELSEIF nCallingType is 1>
110:        <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
111:          INSERT INTO agent_param(agent_id,param_id,agency_id,agency_cntr,param_cntr,param_name,param_value,dataGroup)
112:          VALUES (#nCallingID#, #nParamID#, #ap_agency_number#, #parm_counter#, #parm_counter#, 'qryFindParamID.name#', #cTextToSend#, 5)
113:        </CFQUERY>
114:      </CFIF>
115:    <CFELSEIF cFieldType is "SELECT">
116:      <cfoutput>Inserting select data:
117:      #nCallingID#, #nParamID#, #ap_agency_number#, #parm_counter#, 'qryFindParamID.name#', #Evaluate(cNewField)#', 5</cfoutput> <br>
118:      <CFSET cTextToSend = evaluate(cNewField)>
119:      <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
120:      <CFIF nCallingType is 0>
121:        <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
122:          INSERT INTO p_param(prop_id,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
123:          VALUES (#prop_id#, #nParamID#, #ap_agency_number#, #parm_counter#, #parm_counter#, 'qryFindParamID.name#', #cTextToSend#, 5)
124:        </CFQUERY>
125:      <CFELSEIF nCallingType is 1>
126:        <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
127:          INSERT INTO agent_param(agent_id,param_id,agency_id,agency_cntr,param_cntr,param_name,param_value,dataGroup)
128:          VALUES (#nCallingID#, #nParamID#, #ap_agency_number#, #parm_counter#, #parm_counter#, 'qryFindParamID.name#', #cTextToSend#, 5)
129:        </CFQUERY>
130:      </CFIF>
131:    <CFELSEIF cFieldType is "FILE">
132:      <HR>
133:      <CFSET cNewField = "FORM.FIELD" & nIndex>
134:      <CFSET cFileField = trim("Field" & nIndex)>
135:      <CFIF nCallingType is 0>
136:        <CFSET cFilePath = #ap_OHT_path# & #FORM.prop_id# & "\">
137:        <CFELSEIF nCallingType is 1>
138:          <CFSET cFilePath = #ap_OHT_path# & "Agent" & #nCallingID# & "\">
139:        </CFIF>
140:      <CFOUTPUT>File Name is: #cFilePath#</CFOUTPUT><BR>
141:      <CFOUTPUT>New Field : #NewField# (#evaluate(cNewField)#)</CFOUTPUT><BR>
142:      <CFOUTPUT>Field Name: #listGetAt(FORM.Field_Names,nIndex)#</CFOUTPUT><BR>
143:

```

```

144: <CFIF listGetAt(FORM.Field_Names, nIndex) is "OHTImage">
145: <CFSET nImageField = #FORM.imageField#>
146: <CFSET cImageType = "FORM.FIELD" & nImageField>
147: <CFIF nImageType is "0"> <!-- This is a still image --> <!-- </CFIF>nImageField GT 0 AND
#evaluate(cImageType) # is "0" -->
148: <CFOUTPUT>#ap_OHT_path# : #cNewField#</CFOUTPUT>
149: <CFOUTPUT>[#evaluate(cNewField)#]</CFOUTPUT>
150:
151: <CFTRY>
152: <CFDIRECTORY
153: DIRECTORY="#cFilePath#"
154: ACTION="CREATE"
155: >
156: <CFOUTPUT>Creating New Directory #cFilePath#</CFOUTPUT><BR>
157: <CFCATCH TYPE="ANY">
158: <B>Directory already exists!</B><BR>
159: </CFCATCH>
160: </CFTRY>
161:
162: <!-- If an image name is not sent, then the user only wanted to add a text entry ---->
163: <!-- If the field is blank, don't try to send anything ---->
164:
165: <CFSET cEvaluate = evaluate(cNewField)>
166: <CFIF len(trim(cEvaluate)) gt 0>
167: <CFFILE
168: DESTINATION=#cFilePath#
169: ACTION="UPLOAD"
170: NAMECONFLICT="OVERWRITE"
171: FILEFIELD="#cFileField#">
172:
173: <CFIF #FILE.fileWasSaved#>
174: <BR><B>File was Saved</B><BR>
175: <CFIF nCallingType is 0>
176: <CFOQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
177: INSERT INTO p_param(prop_id,param_id,agency_id,param_ctr,param_name,param_value,dataGroup)
VALUES
178: (#prop_id,#nParamID#,#ap_agency_number#,#parm_counter#,'qryFindParamID.name#','OHT\images\#FORM.prop_id#\#FILE.ServerFile#
',5)
</CFOQUERY>
179:
180: <CFELSEIF nCallingType is 1>
181: <CFOQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
182: INSERT INTO agent_param(agent_id,param_id,agency_id,param_ctr,param_name,param_value,dataGroup)
VALUES
183: (#nCallingID#,#nParamID#,#ap_agency_number#,#parm_counter#,'qryFindParamID.name#','OHT\images\Agent#nCallingID#\#FILE.Serve
rFile#',5)
</CFOQUERY>
184:
185: </CFIF>
186: <CFELSE>
187: <BR><B>File was NOT saved</B>

```

```

188:      <CFABORT>
189:    </CFIF>
190:  </CFELSE>
191:  <!-- Save the database info so the other programs don't get confused -->
192:  <BR><B>File was Saved (No image)</B><BR>
193:  <CFIF nCallingType is 0>
194:    <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
195:      INSERT INTO p_param(prop_id,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
196:      VALUES (#prop_id#,#nParamID#,#ap_agency_number#,#parm_counter#,'#qryFindParamID.name#','',5)
197:    </CFQUERY>
198:  </CFELSEIF nCallingType is 1>
199:    <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
200:      INSERT INTO agent_param(agent_id,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
201:      VALUES (#nCallingID#,#nParamID#,#ap_agency_number#,#parm_counter#,'',5)
202:    </CFQUERY>
203:  </CFIF>
204:  </CFIF>
205:  </CFELSE>
206:    <CFOUTPUT>Saving other image information:#cNewField# [#evaluate(cNewField)] #evaluate('FORM.Field1')# *
207:    #cFileField# * #evaluate(cFileField)#<BR></CFOUTPUT>
208:    <CFIF nCallingType is 0>
209:      <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
210:        INSERT INTO p_param(prop_id,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
211:        VALUES
212:        (#prop_id#,#nParamID#,#ap_agency_number#,#parm_counter#,'#qryFindParamID.name#','Evalueate(cNewField)','#',5)
213:      </CFQUERY>
214:    </CFELSEIF nCallingType is 1>
215:      <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
216:        INSERT INTO agent_param(agent_id,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
217:        VALUES
218:        (#nCallingID#,#nParamID#,#ap_agency_number#,#parm_counter#,'#qryFindParamID.name#','Evalueate(cNewField)','#',5)
219:      </CFQUERY>
220:    </CFIF>
221:  </CFLOOP>
222:
223:  <!-- New take us back to the view mode, informing the user that information has been updated -->
224:  <CFIF nCallingType is 0>
225:    <CFLOCATION URL="OHTMaint.cfm?Prop_id=#nCallingID#&Action=Updated" ADDTOKEN="NO">
226:  </CFELSEIF nCallingType is 1>
227:    <CFLOCATION URL="OHTMaint.cfm?Agent_id=#nCallingID#&Action=Updated" ADDTOKEN="NO">
228:  </CFIF>
229:
230:  </CFELSEIF #Action# is "Edit">
231:  <!-- First try to find out what kind of image is being uploaded -->
232:  <CFSET nImageTypeLoc = listFindNoCase(FORM.Field_Names,'imgType')>
233:  <CFIF nImageTypeLoc GT 0>

```

```

234: <CFSET cImageField = 'FORM.FIELD' & nImageTypeLoc>
235: <CFSET nImageType = #evaluate(cImageField)#>
236: <CFOUTPUT>Image Type : #nImageType#</CFOUTPUT>
237: <CFELSE>
238: <CFSET nImageType = -1>
239: </CFIF>
240:
241: <!--- !!!!! -->
242: <!--- <CFSET nImageType = 0> -->
243:
244:
245: <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
246: <CFSET cFieldType = ucase(trim(listGetAt(FORM.FieldTypes, nIndex)))>
247: <CFSET cNewField = "FORM.FIELD" & nIndex>
248:
249: <CFIF cFieldType is "FILE">
250: <CFSET cNewField = "FORM.FIELD" & nIndex>
251: <CFSET cFilePath = trim("Field" & nIndex)>
252:
253: <CFOUTPUT>New Field : #cNewField# (#evaluate(cNewField)#) </CFOUTPUT><BR>
254: <CFOUTPUT>Field Name: #listGetAt(FORM.Field_Names, nIndex) #</CFOUTPUT><BR>
255:
256: <CFIF listGetAt(FORM.Field_Names, nIndex) is "OHTImage" AND #Evaluate(cNewField)# is not "">
257: <CFSET nImageField = #FORM.imageField#>
258: <CFSET cImageType = "FORM.FIELD" & nImageField>
259: <CFIF nImageType is "0"> <!--- This is a still image --> <!--- </CFIF>nImageType GT -1 AND #evaluate(cImageType)#
    is "0"> -->
260: <CFOUTPUT>#ap_image_path# : #cNewField#</CFOUTPUT>
261: <CFOUTPUT>[#evaluate(cNewField) #]</CFOUTPUT>
262:
263: <CFIF nCallingType is 0>
264: <CFSET cFilePath = #ap_OHT_path# & #nCallingID# & "\">
265: <CFELSEIF nCallingType is 1>
266: <CFSET cFilePath = #ap_OHT_path# & "Agent" & #nCallingID# & "\">
267: </CFIF>
268:
269: <CFFILE
    DESTINATION=#cFilePath#
    ACTION="UPLOAD"
    NAMECONFLICT="OVERWRITE"
    FILEFIELD="#cFileField#">
270:
271: <CFIF #FILE.fileWasSaved#>
272: <B>File was Saved</B><BR>
273: <CFOUTPUT>#Evaluate(cNewField)# / #nCallingID# / #parm_counter# /
274: #listGetAt(FORM.Field_Names, nIndex) #<BR></CFOUTPUT>
275: <CFIF nCallingType is 0>
276: <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
277: UPDATE p_param
278:
279:
280:

```

```

281: SET param_value = 'OHT\images\#nCallingID#\#FILE.ServerFile#',
282: WHERE prop_id=#prop_id#
283: AND param_ctr=#param_counter#
284: AND param_name='#listGetAt(FORM.Field_Names,nIndex)#'
285: </CFQUERY>
286: <CFELSEIF nCallingType is 1>
287: <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
288: UPDATE agent_param
289: SET param_value = 'OHT\images\Agent#nCallingID#\#FILE.ServerFile#',
290: WHERE agent_id=#nCallingID#
291: AND param_ctr=#param_counter#
292: AND param_name='#listGetAt(FORM.Field_Names,nIndex)#'
293: </CFQUERY>
294: </CFIF>
295: <CFELSE>
296: <B>File was NOT saved</B>
297: <CFABORT>
298: </CFIF>
299: <CFELSE>
300: <!-- Just insert the name, since this is not a still image -->
301:
302: <CFOUTPUT>Insert Other Image<BR>#Evaluate(cNewField)# / #prop_id# / #param_counter# /
#listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
303: <CFSET cTextToSend = evaluate(cNewField)>
304: <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
305: <CFIF nCallingType is 0>
306: <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
307: UPDATE p_param
308: SET param_value = '#cTextToSend#'
309: WHERE prop_id=#nCallingID#
310: AND param_ctr=#param_counter#
311: AND param_name='#listGetAt(FORM.Field_Names,nIndex)#'
312: </CFQUERY>
313: <CFELSEIF nCallingType is 1>
314: <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
315: UPDATE agent_param
316: SET param_value = '#cTextToSend#'
317: WHERE agent_id=#nCallingID#
318: AND param_ctr=#param_counter#
319: AND param_name='#listGetAt(FORM.Field_Names,nIndex)#'
320: </CFQUERY>
321: </CFIF>
322: </CFIF>
323: </CFIF>
324: <CFELSE>
325: <CFOUTPUT>#Evaluate(cNewField)# / #nCallingID# / #param_counter# / #listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
326: <CFSET cTextToSend = evaluate(cNewField)>
327: <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
328: <CFIF nCallingType is 0>

```



```

329: <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
330: UPDATE p_param
331: SET param_value = 'cTextToSend#'
332: WHERE prop_id=#nCallingID#
333: AND param_ctr=#param_counter#
334: AND param_name=#listGetAt(FORM.Field_Names,nIndex) #
335: </CFQUERY>
336: <CFELSEIF nCallingType is 1>
337: <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
338: UPDATE agent_param
339: SET param_value = 'cTextToSend#'
340: WHERE agent_id=#nCallingID#
341: AND param_ctr=#param_counter#
342: AND param_name=#listGetAt(FORM.Field_Names,nIndex) #
343: </CFQUERY>
344: </CFIF>
345: </CFIF>
346: </CFLOOP>
347: /*-- New take us back to the view mode, informing the user that information has been updated -->
348: <CFIF nCallingType is 0>
349: <CFLOCATION URL="OHTMaint.cfm?Prop_id=#nCallingID#&Action=Updated" ADDTOKEN="NO">
350: <CFELSEIF nCallingType is 1>
351: <CFLOCATION URL="OHTMaint.cfm?Agent_id=#nCallingID#&Action=Updated" ADDTOKEN="NO">
352: </CFIF>
353:
354: <CFELSEIF #Action# is "Delete">
355: <CFIF NOT IsDefined("parm_counter")> /*-- To delete the information -->
356: <CFIF nCallingType is 0>
357: <CFLOCATION URL="OHTMaint.cfm?prop_id=#nCallingID# ADDTOKEN="NO">
358: <CFELSEIF nCallingType is 1>
359: <CFLOCATION URL="OHTMaint.cfm?Agent_id=#nCallingID# ADDTOKEN="NO">
360: </CFIF>
361: </CFIF>
362:
363: /*-- Delete the selected paragraph -->
364: <CFIF nCallingType is 0>
365: <CFQUERY NAME="qryDeleteAd" DATASOURCE="#SourceName#">
366: DELETE FROM p_param
367: WHERE prop_id=#nCallingID# AND
368: param_ctr=#param_counter# AND
369: agency_id=#ap_agency_number# AND
370: dataGroup=5
371: </CFQUERY>
372: <CFELSEIF nCallingType is 1>
373: <CFQUERY NAME="qryDeleteAd" DATASOURCE="#SourceName#">
374: DELETE FROM agent_param
375: WHERE agent_id=#nCallingID# AND
376: param_ctr=#param_counter# AND
377: agency_id=#ap_agency_number# AND

```

```
378:      dataGroup=5
379:      </CFQUERY>
380:      </CFIF>
381:
382:      <!-- Now take us back to the view mode, informing the user that information has been updated -->
383:      <CFIF nCallingType is 0>
384:      <CFLOCATION URL="OHTMaint.cfm?Prop_id=#nCallingID#&Action=Deleted" ADDTOKEN="NO">
385:      <CFELSEIF nCallingType is 1>
386:      <CFLOCATION URL="OHTMaint.cfm?Agent_id=#nCallingID#&Action=Deleted" ADDTOKEN="NO">
387:      </CFIF>
388:      </CFIF>
389:
390:      </BODY>
391:      </HTML>
392:
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <html>
4: <head>
5:   <title>Online InPrint</title>
6: </head>
7:
8: <body>
9:
10:
11:   <!-- Insert Header stuff Here -->
12: <B>Insert Header Stuff Here!</B>
13:
14:
15:   <CFQUERY NAME="qryGetActive" DATASOURCE="#SourceName#">
16:     SELECT adData.callingID,adData.startDate,adData.stopDate,adData.ohffilename,adData.primaryPic,
17:        prop_main.prop_id,prop_main.dscrptn_s,prop_main.price,agents.name,agents.workphone,agents.image_name
18:     FROM AdData,prop_main,agents
19:     WHERE adData.StartDate <= #createODBCDate(now())#
20:     AND adData.StopDate >= #createODBCDate(now())#
21:     AND adData.callingType=0
22:     AND adData.ohffilename <> ''
23:     AND prop_main.prop_id = adData.callingID
24:     AND prop_main.agent_id = agents.agent_id
25:     ORDER BY prop_main.price DESC
26:   </CFQUERY>
27:
28:   <CFOUTPUT>
29:     <CFSET nColumn = 0>
30:     <CFSET nExtraCol = qryGetActive.recordCount mod 3>
31:     <TABLE ALIGN=CENTER>
32:       <CFLOOP QUERY="qryGetActive">
33:         <CFIF nColumn is 3>
34:           <CFSET nColumn = 0>
35:         </TR>
36:       </CFIF>
37:       <CFSET nColumn = nColumn + 1>
38:       <CFIF nColumn is 1>
39:         <TR>
40:           </CFIF>
41:       </TR>
42:       <CFQUERY NAME="qryFindImage" DATASOURCE="#SourceName#">
43:         SELECT param_value
44:         FROM p_param
45:         WHERE p_param.prop_id = #qryGetActive.callingID#
46:         AND p_param.param_name = 'OHImage'
47:         ORDER BY p_param.param_cntx
48:       </CFQUERY>
49:     </TR>

```

```
50: <TD>
51: <TABLE BORDER="1"><TR><TD>
52: <TABLE BORDER="0" CELLPADDING="0" CELLSPACING="0">
53: <CFSET cimageAgent = "..\..\#qryGetActive.image_name#">
54: <!-- <CFSET cimageProp = "..\#qryFindImage.Param value#"> -->
55: <CFSET cimageProp = "..\#qryGetActive.primaryPic#">
56: <TR>
57: <CFIF trim(cimageProp) IS NOT "">
58: <TD WIDTH="107" HEIGHT="107" VALIGN="TOP">
59: <IMG SRC="#cimageAgent#" WIDTH="103" HEIGHT="103">
60: </TD>
61:
62: <TD WIDTH="153" HEIGHT="153" VALIGN="TOP">
63: <IMG SRC="#cimageProp#" WIDTH="150" HEIGHT="150">
64: </TD>
65: <CFELSE>
66: <TD WIDTH="260" HEIGHT="153" VALIGN="TOP" COLSPAN="2">
67: <IMG SRC="#cimageAgent#" WIDTH="103" HEIGHT="103">
68: </TD>
69: </CFIF>
70: </TR>
71: <TR>
72: <TD COLSPAN="2">
73: <#qryGetActive.dscrptn_s#>
74: <B><P ALIGN="right"><A HREF="..\#qryGetActive.ohffilename#">dollarFormat(qryGetActive.price)</A></P></B>
75: </TD>
76: </TR>
77: </TABLE>
78: </TD></TR></TABLE>
79: </TD>
80: </CFLOOP>
81: <CFLOOP FROM="1" TO="#nExtraCol#" INDEX="nIndex">
82: <TD> <b><#> </TD>
83: </CFLOOP>
84: <CFIF qryGetActive.recordCount gt 0>
85: </TR>
86: </CFIF>
87: </TABLE>
88: </CFOUTPUT>
89:
90:
91: <!-- Insert Footer Stuff Here -->
92: <B>Insert Footer Stuff Here!</B>
93:
94:
95: </body>
96: </html>
```

```
1: <CFINSERT dataSource="realestate" tableName="param_allowed">
2:
3:
4: <HTML><HEAD>
5:   <TITLE>paramAlld - Entry Action</TITLE>
6: </HEAD>
7: <body bgcolor="white">
8:
9:   <FONT size="+1">paramAlld</FONT> <BR>
10:  <FONT size="+2"><B>Entry was successfully submitted</B></FONT>
11:
12:  <TABLE>
13:
14:
15:    <!-- Field: param_allowed.id -->
16:    <TR>
17:      <td valign="top"> id: </td>
18:      <td>
19:
20:        <CFOUTPUT>#Form.id#</CFOUTPUT>
21:
22:      </td>
23:    </TR>
24:
25:
26:    <!-- Field: param_allowed.counter -->
27:    <TR>
28:      <td valign="top"> counter: </td>
29:      <td>
30:
31:        <CFOUTPUT>#Form.counter#</CFOUTPUT>
32:
33:      </td>
34:    </TR>
35:
36:
37:    <!-- Field: param_allowed.value -->
38:    <TR>
39:      <td valign="top"> value: </td>
40:      <td>
41:
42:        <CFOUTPUT>#Form.value#</CFOUTPUT>
43:
44:      </td>
45:    </TR>
46:
47:
48:    <!-- Field: param_allowed.agency_id -->
49:    <TR>
```

```
50:      <td valign="top"> agency_id: </td>
51:      <td>
52:      <CFOUTPUT>#Form.agency_id#</CFOUTPUT>
53:
54:      </td>
55:      </TR>
56:
57:
58:
59:      <!-- Field: param_allowed_label -->
60:      <TR>
61:      <td valign="top"> label: </td>
62:      <td>
63:
64:      <CFOUTPUT>#Form.label#</CFOUTPUT>
65:
66:      </td>
67:      </TR>
68:
69:      </TABLE>
70:
71:      </BODY></HTML>
72:
```

```

1:  <CFQUERY NAME="qparmdefs4allowedvals" DATASOURCE="realestate">
2:  SELECT      id, name, label, restrictions
3:  FROM        dbo.param_defs
4:
5:  </CFQUERY>
6:  <HTML><HEAD>
7:    <TITLE>paramAlld - Entry Form</TITLE>
8:  </HEAD>
9:  <body bgcolor="white">
10:
11:  <FONT size="+1">paramAlld</FONT> <BR>
12:  <FONT size="+2"><B>Entry Form</B></FONT>
13:
14:  <!-- Entry form -->
15:  <cfform action="paramAlld_EntryAction.cfm" method="post">
16:
17:  <TABLE>
18:
19:
20:    <!-- Field: param_allowed.id -->
21:    <TR>
22:      <td valign="top"> id </td>
23:      <td>
24:        <CFSELECT NAME="id" QUERY="qparmdefs4allowedvals" VALUE="id" DISPLAY="name">
25:        </CFSELECT>
26:      <!-- <INPUT type="text" name="id" maxLength="4" --> -->
27:
28:    </td>
29:    <INPUT type="hidden" name="id_integer">
30:    </TR>
31:
32:
33:    <!-- Field: param_allowed.counter -->
34:    <TR>
35:      <td valign="top"> counter </td>
36:      <td>
37:        <INPUT type="text" name="counter" maxLength="4">
38:
39:
40:      </td>
41:      <INPUT type="hidden" name="counter_integer">
42:      </TR>
43:
44:
45:    <!-- Field: param_allowed.value -->
46:    <TR>
47:      <td valign="top"> value </td>
48:      <td>
49:

```

```
50: <INPUT type="text" name="value" maxLength="50">
51:
52: </td>
53: </TR>
54:
55:
56: <!-- Field: param_allowed.agency_id -->
57: <TR>
58: <td valign="top"> agency_id </td>
59: <td>
60:
61: <INPUT type="text" name="agency_id" maxLength="4">
62:
63: </td>
64: <INPUT type="hidden" name="agency_id_integer">
65: </TR>
66:
67: <!-- Field: param_allowed.label -->
68: <TR>
69: <td valign="top"> label </td>
70: <td>
71:
72: <INPUT type="text" name="label" maxLength="30">
73:
74: </td>
75: </TR>
76:
77: </TABLE>
78: <P>
79: <INPUT type="submit" value="Insert Data">
80:
81: </CFORM>
82:
83:
84:
85: </BODY></HTML>
```



```
1: <CFINSERT datasource="realestate" tableName="param_defs">
2:
3:
4: <HTML><HEAD>
5:   <TITLE>ParamDef - Entry Action</TITLE>
6: </HEAD>
7: <body bgcolor="white">
8:
9:   <FONT size="+1">ParamDef</FONT> <BR>
10:  <FONT size="+2"><B>Entry was successfully submitted</B></FONT>
11:
12:  <TABLE>
13:
14:
15:    <!-- Field: param_defs.agency -->
16:    <TR>
17:      <td valign="top"> agency: </td>
18:      <td>
19:
20:        <CFOUTPUT>#Form.agency#</CFOUTPUT>
21:
22:      </td>
23:    </TR>
24:
25:
26:    <!-- Field: param_defs.listAgency -->
27:    <TR>
28:      <td valign="top"> listAgency: </td>
29:      <td>
30:
31:        <CFOUTPUT>#Form.listAgency#</CFOUTPUT>
32:
33:      </td>
34:    </TR>
35:
36:
37:    <!-- Field: param_defs.name -->
38:    <TR>
39:      <td valign="top"> name: </td>
40:      <td>
41:
42:        <CFOUTPUT>#Form.name#</CFOUTPUT>
43:
44:      </td>
45:    </TR>
46:
47:
48:    <!-- Field: param_defs.description -->
49:    <TR>
```

```
50:      <td valign="top"> description: </td>
51:      <td>
52:
53:      <CFOUTPUT>#Form.description#</CFOUTPUT>
54:
55:      </td>
56:      </TR>
57:
58:
59:      <!-- Field: param_defs.label -->
60:      <TR>
61:      <td valign="top"> label: </td>
62:      <td>
63:
64:      <CFOUTPUT>#Form.label#</CFOUTPUT>
65:
66:      </td>
67:      </TR>
68:
69:
70:      <!-- Field: param_defs.searchable -->
71:      <TR>
72:      <td valign="top"> searchable: </td>
73:      <td>
74:
75:      <CFOUTPUT>#Form.searchable#</CFOUTPUT>
76:
77:      </td>
78:      </TR>
79:
80:
81:      <!-- Field: param_defs.type -->
82:      <TR>
83:      <td valign="top"> type: </td>
84:      <td>
85:
86:      <CFOUTPUT>#Form.type#</CFOUTPUT>
87:
88:      </td>
89:      </TR>
90:
91:
92:      <!-- Field: param_defs.displayOrder -->
93:      <TR>
94:      <td valign="top"> displayOrder: </td>
95:      <td>
96:
97:      <CFOUTPUT>#Form.displayOrder#</CFOUTPUT>
98:
```

```
99:      </td>
100:    </TR>
101:
102:    <!-- Field: param_defs.required -->
103:    <TR>
104:      <td valign="top"> required: </td>
105:      <td>
106:
107:    <CFOUTPUT>#Form.required#</CFOUTPUT>
108:
109:
110:    </td>
111:  </TR>
112:
113:  <!-- Field: param_defs.restrictions -->
114:  <TR>
115:    <td valign="top"> restrictions: </td>
116:    <td>
117:
118:  <CFOUTPUT>#Form.restrictions#</CFOUTPUT>
119:
120:
121:    </td>
122:  </TR>
123:
124:
125:  <!-- Field: param_defs.securityLevel -->
126:  <TR>
127:    <td valign="top"> securityLevel: </td>
128:    <td>
129:
130:  <CFOUTPUT>#Form.securityLevel#</CFOUTPUT>
131:
132:
133:    </td>
134:  </TR>
135:
136:  </TABLE>
137:
138:  </BODY></HTML>
```

```
1: <HTML><HEAD>
2:   <TITLE>ParamDef - Entry Form</TITLE>
3: </HEAD>
4: <body bgcolor="white">
5:
6:   <FONT size="+1">ParamDef</FONT> <BR>
7:   <FONT size="+2"><B>Entry Form</B></FONT>
8:
9:   <!-- Entry Form -->
10:  <FORM action="ParamDef_EntryAction.cfm" method="post">
11:
12:    <TABLE>
13:
14:
15:      <!-- Field: param_defs.agency -->
16:      <TR>
17:        <td valign="top"> agency </td>
18:        <td>
19:
20:          <INPUT type="text" name="agency" maxLength="4">
21:
22:        </td>
23:      <INPUT type="hidden" name="agency_integer">
24:    </TR>
25:
26:
27:      <!-- Field: param_defs.listAgency -->
28:      <TR>
29:        <td valign="top"> listAgency </td>
30:        <td>
31:
32:          <INPUT type="text" name="listAgency" maxLength="4">
33:
34:        </td>
35:      <INPUT type="hidden" name="listAgency_integer">
36:    </TR>
37:
38:
39:      <!-- Field: param_defs.name -->
40:      <TR>
41:        <td valign="top"> name </td>
42:        <td>
43:
44:          <INPUT type="text" name="name" maxLength="10">
45:
46:        </td>
47:      </TR>
48:
49:
```

```
50: <!-- Field: param_defs.description -->
51: <TR>
52: <td valign="top"> description </td>
53: <td>
54:
55: <INPUT type="text" name="description" maxLength="255">
56:
57: </td>
58: </TR>
59:
60:
61: <!-- Field: param_defs.label -->
62: <TR>
63: <td valign="top"> label </td>
64: <td>
65:
66: <INPUT type="text" name="label" maxLength="30">
67:
68: </td>
69: </TR>
70:
71:
72: <!-- Field: param_defs.searchable -->
73: <TR>
74: <td valign="top"> searchable </td>
75: <td>
76:
77: <INPUT type="text" name="searchable" maxLength="1">
78:
79: </td>
80: </TR>
81:
82:
83: <!-- Field: param_defs.type -->
84: <TR>
85: <td valign="top"> type </td>
86: <td>
87:
88: <INPUT type="text" name="type" maxLength="3">
89:
90: </td>
91: </TR>
92:
93:
94: <!-- Field: param_defs.displayOrder -->
95: <TR>
96: <td valign="top"> displayOrder </td>
97: <td>
98:
```

```
99: <INPUT type="text" name="displayOrder" maxLength="4">
100:
101: </td>
102: <INPUT type="hidden" name="displayOrder_integer">
103: </TR>
104:
105:
106: <!-- Field: param_defs.required -->
107: <TR>
108: <td valign="top"> required </td>
109: <td>
110:
111: <INPUT type="text" name="required" maxLength="1">
112:
113: </td>
114: </TR>
115:
116:
117: <!-- Field: param_defs.restrictions -->
118: <TR>
119: <td valign="top"> restrictions </td>
120: <td>
121:
122: <INPUT type="text" name="restrictions" maxLength="1">
123:
124: </td>
125: </TR>
126:
127:
128: <!-- Field: param_defs.securityLevel -->
129: <TR>
130: <td valign="top"> securityLevel </td>
131: <td>
132:
133: <INPUT type="text" name="securityLevel" maxLength="4">
134:
135: </td>
136: <INPUT type="hidden" name="securityLevel_integer">
137: </TR>
138:
139: </TABLE>
140: <P>
141: <INPUT type="submit" value="Insert Data">
142:
143: </FORM>
144:
145:
146: </BODY></HTML>
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//Dtd HTML 4.0 Transitional//EN">
2: <CFQUERY NAME="qDefParams" DATASOURCE="realestate">
3:   SELECT *
4:   FROM   dbo.param_defs
5: </CFQUERY>
6: <HTML>
7: <HEAD>
8:   <TITLE>Property Parameter Definitions</TITLE>
9: </HEAD>
10: <body bgcolor="white">
11:   <CFFORM ACTION="p_define.cfm" METHOD="POST" ENABLECAB="Yes" NAME="frm_p_define">
12:     <CFGRID NAME="grd_p_define" QUERY="qDefParams" INSERT="No" DELETE="No" SORT="Yes" BOLD="No" ITALIC="No" APPENDKEY="No"
      HIGHLIGHTREF="No" GRIDDATAALIGN="LEFT" GRIDLINES="Yes" ROWHEADERS="No" ROWHEADERALIGN="LEFT" ROWHEADERITALIC="No"
      ROWHEADERBOLD="No" COLHEADERS="No" COLHEADERALIGN="LEFT" COLHEADERITALIC="No" COLHEADERBOLD="Yes" BGCOLOR="Aqua"
      SELECTCOLOR="Blue" SELECTMODE="ROW" PICTUREBAR="No">
13:   </cfgrid>
14:   </CFFORM>
15:   </BODY>
16:   </HTML>
17:
```

1  
1  
1



48: </body></html>

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfquery name="qryGetProperties" datasource="#sourceName#">
4:    SELECT c.name,b.firstName+' '+b.lastName AS agentName,a.hits AS tHits, a.hitDate
5:    FROM pgCountDaily a
6:    LEFT OUTER JOIN agents b ON a.pageTarget = b.agent_id
7:    LEFT OUTER JOIN agency c ON b.agency_id = c.agency_id
8:    WHERE a.distID = #ap_distributorID#
9:    AND a.pageType = 'Agent'
10:    and a.pageTarget = #pageID#
11:    and datediff(mm,a.hitDate,current_TimeStamp) <= 4
12:    ORDER BY a.hitDate DESC
13:  </cfquery>
14:
15:  <cfquery name="qryGetSum" datasource="#sourceName#">
16:    SELECT sum(hits) AS sumOfHits
17:    FROM pgCountDaily
18:    WHERE distID = #ap_distributorID#
19:    AND pageType = 'Agent'
20:    AND pageTarget = #pageID#
21:  </cfquery>
22:
23:  <html><head><title>History of Page Views</title>
24:    <link rel="stylesheet" href="style1.css" type="text/css">
25:  </head>
26:
27:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
28:    <p><cfinclude template="header.cfm"></p>
29:  <cfoutput>
30:    <p align="center"><b><font color="Olive" size="+1"> History of #qryGetProperties.agentName# </font><br/>
31:    <font color="Olive">working with #qryGetProperties.Name#<br/></font> </b>
32:    Viewed a total of #qryGetProperties.recordcount# days for a total of #qryGetSum.sumOfHits# page views<br/><br/>
33:  </cfoutput>
34:  <cfinclude template="pgMonthlyTables.cfm">
35:  </p></body></html>

```



```
49:      <nbsp; <nbsp; <cfif>
50:      <cfset nStdHits = #tHits#>
51:      <cfset tPageViews = tPageViews + tHits>
52:      </td>
53:      <td colspan="2" align="left" nowrap>
54:      #nStdHits# <nbsp; <nbsp; <cfset nPrthHits = 0>
55:      <cfset nEnhHits = 0>
56:      <cfset nOthHits = 0>
57:      <cfset nStdHits = 0>
58:      <cfset npgtp = 1>
59:      </td>
60:      </tr>
61:      </cfoutput>
62:      </table>
63:      <p align="center"><font size="2">Definitions prt - Printable Page, enh - Enhanced Page, oth - some other page</font></p>
64:      </body></html>
65:
66:
67:
68:
69:
```

```

1: <CFIF isDefined("grpId")>
2:   <cfset new_Record = "No">
3:   <cfset localGrpId = "grpId">
4:   <cfelse>
5:     <cfset new_Record = "Yes">
6:     <cfset localGrpId = "">
7:   </cfif>
8:
9:   <cfparam name="URL.Action" default="Add">
10:
11:   <!--- Removed 6/5/00 JHJ
12:   <cfquery name="qAgency" datasource="#sourceName#">
13:     SELECT name FROM agency
14:     WHERE agency_id = #ap_agency_number#
15:   </cfquery>
16:   <!-->
17:
18:   <cfquery name="qlinksGroup" datasource="#sourceName#">
19:     SELECT linksGroup.name, linksGroup.grpId, linksGroup.sortOrder
20:     FROM linksGroup
21:     where linksGroup.distributorID = #ap_distributorID#
22:     <!--- and '14-' + convert(varchar,linksGroup.agency_id) + ' is in (#listQualify(client.IntSecurity,"")#)
23:     AND linksGroup.linkType = 'L'
24:     ORDER BY linksGroup.Name
25:   </cfquery>
26:
27:   <!--- WHERE agency_id = #ap_agency_number# removed 6/5/00 JHJ -->
28:
29:
30:   <cfif URL.Action is "Add">
31:     <cfset cGroupName = "">
32:     <cfset nSortOrder = 0>
33:     <cfelseif URL.Action is "Edit">
34:       <cfquery name="qryFindGroup" datasource="#sourceName#">
35:         select * from linksGroup
36:         where linksGroup.grpId = #grpID#
37:       </cfquery>
38:       <cfif qryFindGroup.recordCount is 0>
39:         <cfset new_Record = "Yes">
40:         <cfset localGrpId = "">
41:         <cfset cGroupName = "">
42:         <cfset nSortOrder = 0>
43:       <cfelse>
44:         <cfset cGroupName = qryFindGroup.name>
45:         <cfset nSortOrder = qryFindGroup.sortOrder>
46:       </cfif>
47:     </cfif>
48:
49:   <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">

```

```
50: <html>
51: <head>
52: <cfoutput>
53: <title>#ap_backofficeName# Backoffice</title>
54: </cfoutput>
55: <link rel="stylesheet" href="style1.css" type="text/css">
56: </head>
57:
58:
59: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
60:
61: <p><cfinclude template="header.cfm"></p>
62:
63: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
64:   <tr bgcolor="#cccc99"><td colspan="3"><span class="h2"><b>Resource Groups</b></span><nbsp;<b></b></td></tr>
65:   <tr bgcolor="#cccccc">
66:     <CFORM action="linksGroupPost.cfm">
67:       <cfoutput>
68:         <CFIF new_Record eq "No">
69:           <input type="hidden" name="grpId" value="#grpId#"
70:             </cfif>
71:           <input type="hidden" name="agency_id" value="0"> <!-- #ap_agency_number# -->
72:           <input type="hidden" name="distributorID" value="#ap_distributorID#"
73:             <input type="Hidden" name="linkType" value="L">
74:           </cfoutput>
75:           <td><b>Group Name</b></td>
76:           <td><b>Sort Order</b></td>
77:           <td><b></td>
78:         </tr>
79:         <CFOUTPUT QUERY="qLinksGroup">
80:           <tr bgcolor="#IIf (CurrentRow Mod 2, DE('fffff'), DE('eeeeee'))#">
81:             <td>#qLinksGroup.Name#</td>
82:             <td>#qLinksGroup.sortOrder#</td>
83:             <td><a href="LinksGroupAdm.cfm?grpId=#qLinksGroup.grpId#&Action=Edit">Edit</a> | <a
             href="linksGroupDel.cfm?grpId=#qLinksGroup.grpId#&groupName=#qLinksGroup.Name#">Delete</a>
             </td>
84:           </tr>
85:         </cfoutput>
86:       </table></p>
87:
88: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
89:   <cfif URL.Action is "Add">
90:     <tr bgcolor="#cccccc"><td>Define a New Group:</td></tr>
91:   <cfelseif URL.Action is "Edit">
92:     <tr bgcolor="#cccccc"><td>Edit this Group:</td></tr>
93:   </cfif>
94:   <tr bgcolor="#eeeeee"><td>
95:     <cfoutput>
96:       Name: <input type="text" name="name" maxlength="30" value="#cGroupName#">
```

```
97:      Sort Order: <input type="text" name="sortOrder" maxLength="3" value="#SortOrder#"><br>
98:      <input type="submit" value="Submit"> <input type="reset" value="Reset">
99:      </cfoutput>
100:    </td>
101:    </CFFORM></tr>
102:  </table></p>
103:
104: </body>
105: </html>
```

```
1: <CFIF isDefined("grpId")>
2:   <cfset new_Record = "No">
3:   <cfset localGrpId = "grpId">
4:   <cfelse>
5:     <cfset new_Record = "Yes">
6:     <cfset localGrpId = "">
7:   </cfif>
8:
9:   <cfquery name="qAgency" datasource="#sourceName#">
10:     SELECT name FROM agency
11:     WHERE agency_id = #ap_agency_number#
12:   </cfquery>
13:
14:   <cfquery name="qlinksGroup" datasource="#sourceName#">
15:     SELECT name, grpId, sortOrder
16:     FROM linksGroup
17:     WHERE agency_id = #ap_agency_number#
18:     AND linkType = 'L'
19:     ORDER BY Name
20:   </cfquery>
21:
22:   <HTML><HEAD>
23:   <cfoutput>
24:   <TITLE>Resource Groups List and Administration</TITLE>
25:   </cfoutput>
26:   </HEAD>
27:
28:   <body bgcolor="white">
29:   <CFINCLUDE TEMPLATE="admlinks.cfm"><p>
30:   <CENTER>
31:   <CFFORM action="linksGroupPost.cfm">
32:   <CFOUTPUT>
33:     <CFIF new_Record eq "No">
34:       <input type="hidden" name="grpId" value="#qLinksGroup.grpId#"
35:       </cfif>
36:       <input type="hidden" name="agency_id" value="#ap_agency_number#">
37:       <input type="Hidden" NAME="linkType" VALUE="L">
38:     </cfoutput>
39:     <TABLE BORDER="0" width="550" cellspacing="0">
40:       <TR>
41:         <TH COLSPAN="4">
42:           <font face="Verdana, Arial, sans-serif" font size="4"><b>Resource Groups</b></font>
43:         </TH>
44:       </TR>
45:       <TR>
46:         <TH bgcolor="#cccccc">
47:           <div align="left"><font face="Verdana, Arial, sans-serif" size="2">Group Name</font></div>
48:         </TH>
49:         <TH bgcolor="#cccccc"><div align="left">
```



```
50: <font face="Verdana, Arial, sans-serif" size="2">
51: Sort Order</font>
52: </div></th>
53: <th bgcolor="#cccccc"><div align="left">
54: <font face="Verdana, Arial, sans-serif" size="2">
55: Delete
56: </font>
57: </div></th>
58: </tr>
59: <CFOUTPUT QUERY="qLinksGroup">
60: <tr bgcolor="#ffffff"><th align="left">DE('ffffff'), DE('eeeeee'))#>
61: <td>
62: <font face="Verdana, Arial, sans-serif" size="1"><b>#qLinksGroup.Name#</b></font>
63: </td>
64: <td align="left">
65: <font face="Verdana, Arial, sans-serif" size="1">#qLinksGroup.sortOrder#</font>
66: </td>
67: <td><font face="Verdana, Arial, sans-serif" size="1"><a
HREF="linksGroupDel.cfm?grpId=#qLinksGroup.grpId#&groupName=#qLinksGroup.Name#">Delete</a></td>
68: </tr>
69: </CFOUTPUT>
70: <tr>
71: <td colspan="3" align="left" bgcolor="cccccc"><font face="Verdana, Arial, sans-serif" size="2"><b>Define a Resource
Group</b></font></td>
72: </tr>
73: <tr>
74: <td><input type="text" name="name" maxlength="30"></td>
75: <td><input type="text" name="sortOrder" maxlength="3" value="0"> </td>
76: <td></td>
77: </tr>
78: <tr>
79: <td><input type="submit" value="Submit"> <input type="reset"></td>
80: <td align="right"></td>
81: </tr>
82: </table>
83:
84: </CFform>
85: </CENTER>
86:
87: </body>
88: </html>
89:
90:
91:
92:
93:
94:
95:
96:
```

```

1:  <!-- CFIF IsDefined("GrpId") > ---->
2:  <CFQUERY DATASOURCE="#sourceName#" name="qLinkNewGroup">
3:  SELECT *
4:  FROM linksGroup
5:  WHERE agency_id in (0,#ap_agency_number#)
6:  AND linkType = 'L'
7:  AND grpId <> #URL.grpId#
8:  </CFQUERY>
9:  <cfquery datasource="#sourceName#" name="qLinks">
10:  SELECT *
11:  FROM link
12:  WHERE agency_id in (0,#ap_agency_number#)
13:  AND grpId = #URL.grpId#
14:  AND linkType = 'L'
15:  </cfquery>
16:  <CFSET mxRecs = "#qLinks.RecordCount#">
17:  <html><HTML><HEAD>
18:  <TITLE> Confirm Resource Group Deletion </TITLE>
19:  </HEAD>
20:
21:  <body bgcolor="white">
22:  <CFINCLUDE TEMPLATE="header.cfm"><p>
23:  <cfoutput>
24:  <cfform action="linksGroupDelAction.cfm">
25:    <cfif #mxRecs# gt 0>
26:      <b>There are #mxRecs# in that group. Which group do you want to use in place of #groupName#?</b><BR>
27:      <cfselect display="name" query="qLinkNewGroup" value="grpId" name="newGrpId">
28:        <input type="Hidden" VALUE="Yes" NAME="replaceGrpId">
29:      </cfselect>
30:      <a href="linksGroupAdm.cfm">Cancel</A>
31:    <cfelse>
32:      To delete the resource group #groupName# click on the submit button.
33:      <input type="Hidden" VALUE="No" NAME="replaceGrpId">
34:    </cfif>
35:    <input type="hidden" value="#grpId#" name="oldGrpId">
36:    <input type="submit" value="submit">
37:  </cfform>
38:  </cfoutput>
39:  </body></html>

```

```
1: <CFIF isDefined("replaceGrpId")>
2:   <CFIF #replaceGrpId# eq "yes" and #newGrpId# neq #oldGrpId#>
3:     Replace Grp Id is Defined and Positive
4:     <cftransaction>
5:       <cfquery datasource="#sourceName#" name="qLinkUpdate">
6:         UPDATE link
7:         SET grpId = #newGrpId#
8:         WHERE agency_id in (0, #ap_agency_number#)
9:         AND grpId = #oldGrpId#
10:        AND linkType = 'L'
11:      </cfquery>
12:
13:
14:      <CFQUERY DATASOURCE="#sourceName#" NAME="qLinksGroupDelete">
15:        DELETE linksGroup
16:        WHERE grpId = #oldGrpId#
17:        AND agency_id in (0, #ap_agency_number#)
18:        AND linkType = 'L'
19:      </CFQUERY>
20:
21:      </cftransaction> <BR>
22:
23:   <CFELSEIF #replaceGrpId# eq "yes" and #newGrpId# eq #oldGrpId#>
24:     <P><B><I>Need to select a group that is different from the group to be deleted!</I></B>
25:   <CFELSE>
26:     Replace Grp Id is Defined and Negative
27:     <CFQUERY DATASOURCE="#sourceName#">
28:       DELETE linksGroup
29:       WHERE grpId = #oldGrpId#
30:       AND agency_id in (0, #ap_agency_number#)
31:       AND linkType = 'L'
32:     </CFQUERY>
33:   </CFIF>
34:
35: </CFIF>
36:
37: <CFLOCATION URL="linksGroupadm.cfm">
```

```
1: <CFIF IsDefined("Form.grpId")>
2:   <CFSET Operation="Updated">
3:   <cfquery name="qryUpdateGroup" datasource="#SourceName#">
4:     update linksGroup
5:       set name='#FORM.name#', sortOrder=#FORM.sortOrder#
6:       where grpId=#form.grpId#
7:   </cfquery>
8:   <CFELSE>
9:     <CFSET Operation="Inserted">
10:    <CFINSERT DATASOURCE="#sourceName#" TABLENAME="linksGroup">
11:    </CFIF>
12:
13:   <CFOUTPUT>
14:   <HTML>
15:   <HEAD>
16:   <TITLE>Resource has been #Operation#</TITLE>
17:   </HEAD>
18:   <body bgcolor="ffffff">
19:   <cflocation url="linksGroupAdm.cfm" addtoken="no">
20:   </CFOUTPUT>
21:   </BODY>
22:   </HTML>
23:
```

```

1: <!--
2: <CFIF isDefined("linkid")>
3: <CFSET Operation="Updated">
4: <CFUPDATE DATASOURCE="#sourceName#" TABLENAME="link">
5: <CFELSE>
6: <CFSET Operation="Inserted">
7: <CFINSERT DATASOURCE="#sourceName#" TABLENAME="link">
8: </CFIF>
9: -->
10:
11: <cfif isDefined("form.linkid")>
12: <cfset operation="Updated">
13:
14: <cfset cFilePath = "#ap_image_path#">
15: <CFIF len(FORM.edtImage) gt 0>
16: <CFFILE
17:     DESTINATION=#cFilePath#
18:     ACTION="UPLOAD"
19:     NAMECONFLICT="OVERWRITE"
20:     FILEFIELD="edtImage">
21: <CFSET cImageName = FILE.ServerFile>
22: <cfelseif isDefined("FORM.clearImage")>
23: <cfset cImageName="">
24: <CFELSE>
25: <CFSET cImageName=FORM.oidImage>
26: </CFIF>
27:
28: <cftransaction>
29: <cfquery name="qryUpdate" datasource="#sourceName#">
30:     update link
31:     set agency_id=#form.agency_id#,grpid=#form.grpid#,name='#form.name#',
32:     url='#form.url#',sortorder=#form.sortorder#,linktype='#form.linktype#',
33:     displayPages='#form.displayPages#',image='#cImageName#',
34:     where link.linkid=#form.linkid#
35: </cfquery>
36: </cftransaction>
37: <cfelse>
38: <cfset operation="Inserted">
39:
40: <cfset cFilePath = "#ap_image_path#">
41: <CFIF len(FORM.edtImage) gt 0>
42: <CFFILE
43:     DESTINATION=#cFilePath#
44:     ACTION="UPLOAD"
45:     NAMECONFLICT="OVERWRITE"
46:     FILEFIELD="edtImage">
47: <CFSET cImageName = FILE.ServerFile>
48: <CFELSE>
49: <CFSET cImageName="">

```

```
50: </CFIF>
51:
52: <cftransaction>
53:   <cfquery name="qryUpdate" datasource="#sourcename#">
54:     insert into link
55:       (agency_id,grid,name,url,sortorder,linktype,displayPages,image)
56:     values (#form.agency_id#,#form.gridid#,#form.name#,'#form.url#',#form.sortorder#,
57:           '#form.linktype#',#form.displayPages#,'#imageName#')
58:   </cfquery>
59: </cftransaction>
60:
61: </cfif>
62:
63: <HTML>
64: <HEAD>
65: <CFOUTPUT>
66: <TITLE>Resource has been #Operation#</TITLE>
67: </CFOUTPUT>
68: </HEAD>
69: <body bgcolor="ffffff">
70: <CFLOCATION URL="linksform.cfm?Action=Add" addtoken="no">
71: </BODY>
72: </HTML>
73:
```

```
1: <CFQUERY DATASOURCE="realestate" NAME="list_params">
2: SELECT DISTINCT param_name, order_id, value_id, allowed_value
3: FROM param_allow_val
4: WHERE agency_id = 8
5: ORDER BY order_id
6: </CFQUERY>
7:
8: <CFQUERY DATASOURCE="realestate" NAME="vals_params">
9: SELECT DISTINCT param_name, param_value, param_cntr, param_id
10: FROM p_param
11: WHERE agency_id = 8
12: AND prop_id = 149
13: </CFQUERY>
14:
15: <CFSET param_name = Trim(list_params.param_name)>
16: <CFSET newparams = ArrayNew(2)>
17:
18:
19: <CFLOOP query="list_params">
20: <CFSET newparams[CurrentRow][1] = param_name[CurrentRow]>
21: <CFSET newparams[CurrentRow][2] = param_name[CurrentRow]>
22: <CFSET newparams[CurrentRow][3] = param_name[CurrentRow]>
23: <CFSET newparams[CurrentRow][4] = param_name[CurrentRow]>
24:
25: </CFLOOP>
26:
27: <CFSET PageTitle = "Coldwell Banker Registration">
28: <!-- <CFSET reccount = list_params.rec_count -->
29:
30: <html>
31: <head>
32: <title>#PageTitle#</title>
33: </head>
34:
35: <body bgcolor="white">
36: <CFOUTPUT>
37: This is the test: <br>
38: <CFSET Total_Records=List_Params.RecordCount>
39: <CFLOOP INDEX="Counter" FROM=1 TO="#Total_Records#">
40: Name: #List_Params.param_name[Counter]#, <br>
41: Order: #List_Params.order_id[Counter]#, <br>
42: Count: #List_Params.value_id[Counter]#, <br>
43: Value: #List_Params.allowed_value[Counter]#<br><br>
44: <br>
45: </CFLOOP>
46: </CFOUTPUT>
47: </body>
48: </html>
49:
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <!-- Make sure the security database is set up -->
4:  <cfinclude template="include\securityDefaults.cfm">
5:
6:  <cfset client.userID = -1>
7:  <cfset client.SecurityLevel = "999999">  <!-- Default security to no access -->
8:  <cfset client.SecurityGroup = "999999">  <!-- Default security to no access -->
9:  <cfset client.lstSecurity = "">
10:
11:  <CFPARAM NAME="URL.UserMessage" DEFAULT="">
12:  <CFPARAM NAME="FORM.Action" DEFAULT="">
13:
14:  <cfif FORM.Action is "LoginNow">
15:    <cfset cUserName = FORM.edtUserName>
16:
17:    <cfquery name="qryLogin" datasource="#SourceName#">
18:      select security.*,securityGroups.Description as groupDescription, securityLevels.description as levelDescription
19:      from Security, securityGroups, securityLevels
20:      where security.loginName = '#cUserName#'
21:      and security.userGroup = securityGroups.userGroup
22:      and security.securityLevel = securityLevels.securityLevel
23:    </cfquery>
24:    <cfif qryLogin.recordCount is 0>
25:      <cfset URL.UserMessage = "You entered an invalid username or password.">
26:    <cfelse>
27:      <cftry>
28:        <!--
29:        <cfset cPassword = decrypt('#qryLogin.password#', "#FORM.edtUserHememe#(Yakfasse)")>
30:      -->
31:      <cfset cPassword = hash(FORM.edtPassword)>
32:
33:      <cfcatch type="MissingInclude">
34:        <cfset cPassword = "NOPENOPENOPE">
35:      </cfcatch>
36:    </cftry>
37:    <!--
38:    <cfif cPassword is FORM.edtPassword>
39:      -->
40:      <cfif trim(qryLogin.hashPassword) is trim(cPassword)>
41:        <cfif trim(qryLogin.status) is "Enabled">
42:          <cfquery name="qryUpdateLogin" datasource="#SourceName#">
43:            update Security set InvalidLoginAttempts=0, LastLogin=createODBCDate(now())#
44:          </cfquery>
45:
46:          <cfset client.userID = qryLogin.userID>
47:        <!--
48:        <cfset client.securityGroup = qryLogin.groupDescription>
49:        <cfset client.securityLevel = qryLogin.levelDescription>

```



```

50:  --->
51:  <cfset client.securityGroup = gryLogin.userGroup>
52:  <cfset client.securityLevel = gryLogin.securityLevel>
53:  <cfset client.entityID = gryLogin.entityID>
54:  <cfset client.entityType = gryLogin.entityType>
55:  <cfset client.userName = gryLogin.FullName>
56:
57:  <!-- Get the other entities that this user has access over -->
58:  <cfinclude template="include\securityTest.cfm">
59:
60:  <cflocation URL="index.cfm" addtoken="NO">
61:  <cfelseif trim(gryLogin.status) is "Disabled">
62:    <cfset URL.UserMessage = "Your login account has been deactivated. Call Yakalo Solutions to reactive.">
63:    <cfelse>
64:      <cfset URL.UserMessage = "Your login account has a problem. Call Yakalo Solutions to resolve your problem.">
65:    </cfif>
66:    <cfelse>
67:      <cfoutput>
68:        <cfset URL.UserMessage = "You entered an invalid username or password.">
69:      </cfoutput>
70:      <cfset nAttempts = gryLogin.invalidLoginAttempts+1>
71:      <cfif nAttempts gt 5>
72:        <cfset cStatus = "Disabled">
73:        <cfelseif gryLogin.status is "Enabled">
74:          <cfset cStatus = "Enabled">
75:        <cfelse>
76:          <cfset cStatus = gryLogin.status>
77:        </cfif>
78:        <cfquery name="gryUpdateLogin" datasource="#SourceName#">
79:          update Security
80:          set InvalidLoginAttempts=#nAttempts#, status='#cStatus', lastLogin=createODBCDate(now())#
81:          where security.loginName = '#cUserName#'
82:        </cfquery>
83:      </cfif>
84:    </cfif>
85:  </cfif>
86:
87:
88:
89: <html>
90: <head>
91:   <cfoutput>
92:     <title>#ap_backofficeName# Backoffice</title>
93:   </cfoutput>
94:   <link rel="stylesheet" href="style1.css" type="text/css">
95: </head>
96:
97: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
98: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">

```

```
99: <cfoutput>
100: <tr>
101: <td><span class="h2"><b>Yakalo Back Office Administration Login</b></span></td>
102: <td align="right"></td>
103: </tr>
104: <tr><td colspan="2">&nbsp;</td></tr>
105: <tr bgcolor="##ffffff">
106: <td colspan="2">
107: <CFORM NAME="Login" ACTION="Login.cfm">
108: <table border="0" width="700" align="center">
109: <tr><td colspan="2" bgcolor="##eeeeee" align="center"><b class="bighead">Welcome to the Yakalo Back Office
Administrator!</b></td></tr>
110: <tr><td colspan="2">
111: <CFIF URL.UserMessage is not "">
112: <p><font color="red">#URL.UserMessage#</font></p>
113: </CFIF>
114: <p>Enter the information below to login to the Back Office.
115: <table border="0">
116: <tr><td>Username:</td>
117: <td><CFINPUT TYPE="Text" name="edtUserName" required="YES" message="You must enter your user
name."></td></tr>
118: <tr><td>Password:</td>
119: <td>
120: <CFINPUT TYPE="Password" name="edtPassword" required="YES" message="You must enter your password">
121: &nbsp;</td></tr>
122: </table></tr>
123: </table></p>
124: <input type="Hidden" name="Action" value="LoginNow">
125: <input type="Submit" value="Login">
126: </td></tr>
127: </table>
128: </CFORM>
129: </td>
130: </tr>
131: </cfoutput>
132: </table></p>
133:
134: </body>
135: </html>
```

-----  
 The following information was generated by the ColdFusion MX 4.0 Transitional//EN

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfinclude template="include\securityTest.cfm">
4:
5: <cfparam name="URL.SortBy" default="LoginName">
6:
7: <cfquery name="qryUsers" datasource="#SourceName#">
8:   select security.userID, security.LoginName, security.fullName,
9:     securityGroups.description as groupName,
10:    securityLevels.description as levelName
11:  from Security, securityGroups, securityLevels
12:  where security.userGroup = securityGroups.userGroup
13:  and security.securityLevel = securityLevels.securityLevel
14:  and '|' + convert(varchar,security.entityType) + '-' + convert(varchar,security.entityID) + '|' in
15:    (#quotedValueList(qrySecurity.entityLookup)#) ---->
16: </cfquery>
17: <!-- and security.entityID = entities.entityID ---->
18: <!-- and entityLookup in (#listInSecurity#) ---->
19:
20:
21: <!-- and '|' + convert(varchar,security.entityType) + '-' + convert(varchar,security.entityID) + '|' in
22:    (#quotedValueList(qrySecurity.entityLookup)#) ---->
23: <!-- and '|' + convert(varchar,security.entityType) + '-' + convert(varchar,security.entityID) + '|' in
24:    (#listQualify(client.lstSecurity,"")#) ----> <!-- (#client.lstSecurity#) ---->
25: <html>
26: <head>
27:   <cfoutput>
28:     <title>#ap_backofficeName# Backoffice</title>
29:   </cfoutput>
30:   <link rel="stylesheet" href="style1.css" type="text/css">
31: </head>
32:
33: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
34: <p><cfinclude template="header.cfm"></p>
35:
36: <cfif client.securityLevel eq 0> <!-- Administrator Access ---->
37:   <!-- Does not really have access to this page ---->
38:   <cflocation url="index.cfm" addtoken="no">
39: </cfif>
40:
41: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
42:   <tr bgcolor="#cccc99">
43:     <td colspan="4">
44:       <span class="h2"><b>User Login Administration</b></span><a href="loginMaint.cfm">Add a user
45:       login</a>
46:     </td>

```

```
46: </tr>
47:
48: <tr bgcolor="#cccccc">
49:   <td>Sort by <a href="loginAdm.cfm?SortBy=loginName"><b>Login Name</b></a></td>
50:   <td>Sort by <a href="loginAdm.cfm?SortBy=fullName"><b>Full Name</b></a></td>
51:   <td>Sort by <a href="loginAdm.cfm?SortBy=entityName,loginName"><b>Entity Name</b></a></td>
52:   <td>&nbsp;</td>
53:   <td>&nbsp;</td>
54: </tr>
55:
56:
57: <CFIF qryUsers.recordCount is 0>
58:   <TR><TD COLSPAN="3"><I>There are no users defined</I></TD></TR>
59: </CFIF>
60: <cfset lColor = True>
61: <cfloop query="qryUsers">
62:   <cfset lColor = not lColor>
63:   <tr <cfif lColor is TRUE>bgcolor="eeeeee"</cfif>
64:     <cfoutput>
65:       <td>#qryUsers.loginName#</td>
66:       <td>#qryUsers.fullName#</td>
67:       <td>#qryUsers.entityName#</td>
68:       <td>&nbsp;</td>
69:       <td><a href="loginMaint.cfm?UserID=#qryUsers.userID#">Edit</a></td>
70:     </cfoutput>
71:   </tr>
72: </cfloop>
73: </table></p>
74:
75: </body>
76: </html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfinclude template="include\security.cfm">
4:  <cfinclude template="include\securitytest.cfm">
5:
6:  <cfparam name="URL.userID" default="-1">
7:  <cfparam name="URL.userName" default="">
8:
9:  <cfset nUserID = URL.userID>
10:
11:  <cfquery name="qryFindUser" datasource="#sourceName#">
12:    select * from security
13:    where security.userID = #nUserID#
14:  </cfquery>
15:  <!--
16:  <cfif qryFindUser.recordCount gt 0>
17:    <cfset cPassword = decrypt(qryFindUser.password, "qryFindUser.loginName#(saltPass)")>
18:    <cfelse>
19:      <cfset cPassword = "">
20:    </cfif>
21:    <cfset cDuplicatePassword = cPassword>
22:    <!--
23:
24:
25:    <cfquery name="qryLevels" datasource="#sourceName#">
26:      select securityLevel, description
27:      from securityLevels
28:      where securityLevels.securityLevel >= #client.securityLevel#
29:    </cfquery>
30:
31:    <cfquery name="qryGroups" datasource="#sourceName#">
32:      select userGroup, description
33:      from securityGroups
34:      where securityGroups.userGroup >= #client.securityGroup#
35:    </cfquery>
36:
37:    <cfquery name="qryEntities" datasource="#sourceName#">
38:      select entityID as itemID, parentID as parentItemID, Name, entityType
39:      from entities
40:    </cfquery>
41:
42:
43:    <!--
44:    <cfquery name="qrySecurityList" datasource="#sourceName#">
45:      select distributors.distributorID, distributors.name as distName,
46:      agency.agent_id, agency.name as AgencyName,
47:      agents.agent_id, agents.firstname, ' ' + agents.lastname as fullname
48:      from agents
49:      left outer join agency on agency.agent_id=agents.agent_id

```

```

50: left outer join distributors on agency.distributorID = #ap_distributorID#
51: where distributors.distributorID = #ap_distributorID#
52: order by distributors.distributorID, agency_id, agents.lastname, agents.firstname
53: </cfquery>
54:
55: <cfmake_table query="qryEntities">
56:   -->
57:
58: <html>
59: <head>
60:   <cfoutput>
61:     <title>#ap_backofficeName# Backoffice</title>
62:   </cfoutput>
63:   <link rel="stylesheet" href="style1.css" type="text/css">
64:   <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
65: </head>
66:
67: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
68:
69: <p><cfinclude template="header.cfm"></p>
70:
71: <cfoutput>
72:
73: <form name="frmLogin" action="loginUpdate.cfm" method="post">
74:   <input type="hidden" name="userID" value="#userID#">
75:   <!--
76:   <input type="hidden" name="editSecurityLevel" value="#qryFindUser.securityLevel#">
77:   <input type="hidden" name="editSecurityGroup" value="#qryFindUser.userGroup#">
78:   -->
79:
80:   <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
81:     <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>User Maintenance</b></span></td></tr>
82:
83:     <CFIF URL.UserMessage is not "">
84:       <tr bgcolor="eeeeee">
85:         <td colspan="5"><p><font color="red">#URL.UserMessage#</font></p></td>
86:       </tr>
87:       <tr bgcolor="eeeeee"><td colspan="5"><nbsp;</td></tr>
88:     </CFIF>
89:
90:     <tr bgcolor="eeeeee">
91:       <td width="15%">Login Name:</td>
92:       <td width="34%"><input type="text" name="edtLoginName" value="#qryFindUser.LoginName#"></td>
93:       <td width="2%"><nbsp;</td>
94:       <td width="15%">Full Name:</td>
95:       <td width="34%"><input type="text" name="edtFullName" value="#qryFindUser.FullName#"></td>
96:     </tr>
97:
98:     <cfif qryFindUser.recordCount gt 0>

```

```

99:      <input type="hidden" name="edtHasPassword" value="yes">
100:    <cfelse>
101:      <input type="hidden" name="edtHasPassword" value="No">
102:    </cfif>
103:    <tr bgcolor="eeeeee">
104:      <td width="15%">Password:</td>
105:    <td width="34%"><input type="password" name="edtPassword" value="#cPassword#" />
106:  </td>
107:  <td width="34%">
108:    <input type="password" name="edtPassword">
109:    <cfif qryFindUser.recordCount gt 0><i>Encrypted</i></cfif>
110:  </td>
111:  <td width="2%">&nbsp;</td>
112:  <td width="15%">Check Password:</td>
113:  <td width="34%">
114:    <input type="password" name="edtCheckPassword">
115:    <cfif qryFindUser.recordCount gt 0><i>Encrypted</i></cfif>
116:  </td>
117: </tr>
118:
119:
120: <tr bgcolor="eeeeee">
121:   <td width="15%">Status:</td>
122:   <td width="34%">
123:     <select name="edtStatus">
124:       <option value="Enabled" <cfif qryFindUser.Status is "Enabled"> selected</cfif>>Enabled
125:       <option value="Disabled" <cfif qryFindUser.Status is "Disabled"> selected</cfif>>Disabled
126:     </select>
127:   </td>
128:   <td width="2%">&nbsp;</td>
129:   <td width="15%">Hint:</td>
130:   <td width="34%"><input type="text" name="edtHint" value="#qryFindUser.hint#"></td>
131: </tr>
132:
133:
134: <tr bgcolor="eeeeee">
135:   <td width="15%">Security Level:</td>
136:   <td width="34%">
137:     <select name="edtSecurityLevel">
138:       <cfloop query="qryLevels">
139:         <option value="#qryLevels.securityLevel#" <cfif qryLevels.securityLevel is qryFindUser.securityLevel>
selected</cfif>>#qryLevels.description#
140:       </cfloop>
141:     </select>
142:   </td>
143:   <td width="2%">&nbsp;</td>
144:   <td width="15%">Security Group:</td>
145:   <td width="34%">
146:     <select name="edtSecurityGroup">

```

```

147:         <cfloop query="qryGroups">
148:             <option value="#qryGroups.userGroup#" <cfif qryGroups.userGroup is qryFindUser.userGroup>
149:                 selected</cfif>>#qryGroups.description#
150:             </cfloop>
151:             </select>
152:         </td>
153:     </tr>
154:     <tr bgcolor="eeeeee">
155:         <td width="15%">Control Over:</td>
156:         <td width="34%">
157:             <cfset nPrevDist = "-1">
158:             <cfset nPrevAgency = "-1">
159:             <select name="edtEntity">
160:                 <cfloop query="qrySecurity">
161:                     <option value="#qrySecurity.entityTypeID#"<cfif qryFindUser.entityTypeID is
162:                         qrySecurity.entityTypeID and qryFindUser.entityTypeID is qrySecurity.entityTypeID> selected</cfif>>
163:                     <cfloop from="0" to="#qrySecurity.itemSecurityGroup#" index="nIndex">&nbsp;<cfloop>#qrySecurity.name#
164:                     </cfloop>
165:                 </cfloop>
166:             </td>
167:         </tr>
168:     </td>
169:     </td>
170:     </td>
171:     </td>
172:     </td>
173:     </td>
174:     </td>
175:     </td>
176:     </td>
177:     </td>
178:     </td>
179:     </td>
180:     </td>
181:     </td>
182:     </td>
183:     </td>
184:     </td>
185:     </td>
186:     </td>
187:     </td>
188:     </td>
189:     </td>

```



```
190: <td width="34%">#dateFormat(qryFindUser.LastLogin, "mm/dd/yyyy")#</td>
191: <td width="2%">&nbsp;</td>
192: <td width="15%">Invalid Attempts:</td>
193: <td width="34%">#qryFindUser.InvalidLoginAttempts#</td>
194: </tr>
195:
196: <tr bgcolor="eeeeee">
197: <td colspan="5">
198: <cfif qryFindUser.recordCount is 0>
199: <input type="submit" name="btnUpdate" value="Add User Account">
200: <input type="reset" value="Reset Info">
201: <cfelse>
202: <input type="submit" name="btnUpdate" value="Update User Account">
203: <input type="reset" value="Reset Info">
204: <input type="submit" name="btnDelete" value="Delete Account">
205: </cfif>
206: </td>
207: </tr>
208: </table>
209: </FORM>
210:
211: </cfoutput>
212:
213: </body>
214: </html>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfif not isDefined("FORM.userID")>
4:   <cflocation url="loginAdm.cfm" addtoken="no">
5: </cfif>
6:
7: <cfquery name="qryFindUser" datasource="#sourcename#">
8:   select userID, hashPassword from security
9:   where security.userID = #FORM.userID#
10: </cfquery>
11:
12: <cfif FORM.edtPassword is not FORM.edtCheckPassword>
13:   <cflocation url="loginMaint.cfm?userID=#FORM.userID#&userMessage=Passwords do not match" addtoken="no">
14: <cfelse>
15:   <cfif len(trim(form.edtPassword)) is 0 and len(trim(form.edtCheckPassword)) is 0>
16:     <cfif qryFindUser.recordCount is 0>
17:       <cflocation url="loginMaint.cfm?userID=#FORM.userID#&userMessage=Passwords do not match" addtoken="no">
18:     </cfif>
19:     <!--- Same password as before -->
20:     <cfset cPassword = qryFindUser.hashPassword>
21:   <cfelse>
22:     <!--- Entered a new password -->
23:     <cfset cPassword = hash(form.edtPassword)>
24:
25:   </cfif>
26:   <!---
27:   <cfset cEncrypt = encrypt(FORM.edtPassword, "#FORM.edtLoginName# (YatPass)")>
28:   <cfset cEncrypt = preserveSingleQuotes(cEncrypt)>
29:   -->
30: </cfif>
31:
32: <cfif isDefined("FORM.btnUpdate")>
33:   <cfset nEntityID = listGetAt(FORM.edtEntity,2)>
34:   <cfset nEntityType = listGetAt(FORM.edtEntity,1)>
35:   <cfif qryFindUser.recordCount is 0> <!--- Add this user -->
36:     <cfquery name="qryCheckDup" datasource="#sourcename#">
37:       select loginName from Security
38:       where loginName = '#FORM.edtLoginName#'
39:     </cfquery>
40:
41:     <cfif qryCheckDup.recordCount gt 0>
42:       <cflocation url="loginMaint.cfm?userID=#FORM.userID#&userMessage=Sorry. That user name already exists." addtoken="no">
43:     </cfif>
44:
45:     <cfquery name="qryInsert" datasource="#sourcename#">
46:       insert into Security
47:       (loginName, password, hashPassword, fullName, securityLevel, userGroup, Status, Hint, entityID, entityType,email)
48:       values ('#FORM.edtLoginName#', '', '#cPassword#', '#FORM.edtFullName#',
49:             '#FORM.edtSecurityLevel#', '#FORM.edtSecurityGroup#', '#FORM.edtStatus#', '#FORM.edtHint#',

```

50:  
51:  
52:  
53:  
54:  
55:  
56:  
57:  
58:  
59:  
60:  
61:  
62:  
63:  
64:  
65:  
66:  
67:  
68:  
69:  
70:  
71:  
72:  
73:  
74:  
75:  
76:  
77:  
78:  
79:  
80:  
81:

```
1: <CFIF Form.SendSingleMessage>
2: <!-- send one message to all selected recipients -->
3: <CFMAIL
4:   from="#Form.Sender#"
5:   to="#Form.Recipients#"
6:   subject="#Form.Subject#"
7: #Form.Message#
8:   <CFLOOP list="#Form.selProp#" index="Prop_id">
9:   http://#form.URL_name#/ap_propview#?prop_id=#Prop_id#
10:   </CFLOOP>
11:
12:   </CFMAIL>
13:
14:   <CFELSE>
15:   <!-- send separate message to each selected recipient -->
16:   <CFLOOP list="#Form.Recipients#" index="sRecipient">
17:     <CFMAIL
18:       from="#Form.Sender#"
19:       to="#sRecipient#"
20:       subject="#Form.Subject#"
21:     >
22:     #Form.Message#
23:     <CFLOOP list="#Form.selProp#" index="Prop_id">
24:     http://#form.URL_name#/ap_propview#?prop_id=#Prop_id#
25:     </CFLOOP>
26:     </CFMAIL>
27:   </CFLOOP>
28:
29:   </CFIF>
30:
31:   <HTML><HEAD>
32:   <TITLE>Big Pine EMAIL - Mailing Action</TITLE>
33:
34:   </HEAD>
35:   <body bgcolor="white">
36:   <CFINCLUDE TEMPLATE="admlinks.cfm"><p>
37:
38:   <B><i>Mailing was successfully sent</i></B>
39:
40:   <P>
41:
42:   <!-- Confirm the message -->
43:   <TABLE>
44:   <TR><td>To:</td>
45:   <td><CFOUTPUT>#Form.Recipients#</CFOUTPUT></td>
46:   </TR>
47:
48:   <TR><td>From:</td>
49:   <td><CFOUTPUT>#Form.Sender#</CFOUTPUT></td>
```

```
50: </TR>
51: <TR><td>BCC:</td>
52: <td><CFOUTPUT>#Form.BCC#</CFOUTPUT></td>
53: </TR>
54: <TR><td>Subject:</td>
55: <td>
56: <CFOUTPUT>#Form.Subject#<br>
57: </CFOUTPUT>
58: </td>
59: </TR>
60:
61: <TR><td>Date:</td>
62: <td><CFOUTPUT>#DateFormat(Now())# #TimeFormat(Now())#</CFOUTPUT></td>
63: </TR>
64:
65: <TR><td colspan=2><HR><PRE>
66: <CFOUTPUT>#Form.Message#<br>
67: <CFLOOP list="#Form.selProp#" index="Prop_id">
68: http://#form.URL_name#/ap_propview#?prop_id=#Prop_id#<br>
69: </CFLOOP>
70: </CFOUTPUT></PRE>
71: </td>
72: </TR>
73:
74: </TABLE>
75: </BODY></HTML>
```

```

1: <HTML><HEAD>
2: <CFSET EmailSuffix = "">
3:
4: <CFQUERY name="Recipients" dataSource="#sourceName#">
5:   SELECT
6:     client_id,
7:     email,
8:     ContactFirstName,
9:     ContactLastName,
10:    email + ' - ' + ContactLastName + ', ' + ContactFirstName AS client,
11:    client.Email + '#EmailSuffix#' AS EmailField
12:  FROM client
13:  WHERE #ap_agency#
14:  ORDER BY ContactLastName,ContactFirstName,Email
15: </CFQUERY>
16:
17:
18: <CFQUERY name="Properties" dataSource="#sourceName#">
19:   SELECT name, prop_id
20:  FROM prop_main
21:  WHERE #ap_agency#
22:  ORDER BY name
23: </CFQUERY>
24:
25: <CFQUERY NAME="qAgency" DATASOURCE="#sourceName#">
26:   select name,
27:     email,
28:     URL_name
29:   from agency
30:   where #ap_agency#
31: </CFQUERY>
32:
33:
34: <TITLE> <CFOUTPUT#qAgency.name#></CFOUTPUT> EMAIL - Mailing Form</TITLE>
35:
36: </HEAD>
37: <body bgcolor="white">
38: <CFINCLUDE TEMPLATE="admlinks.cfm"><p>
39:
40:
41: <div align="center"><font face="Verdana,Arial,sans-serif" size="4" color="Teal"><B>EMAIL Mailing Form</B></font></div><p>
42:
43:
44: <!-- Entry form -->
45:
46: <CFFORM action="MailAction.cfm" method="post">
47:
48: <div align="center"><TABLE border=1 cellspacing=0 cellpadding=1 bgcolor="#eeeeee">
49:

```

```
50: <TR><td valign="top" colspan=2><FONT size=2><B>To:</B></FONT>>
51:
52: <INPUT TYPE="Hidden" NAME="URL_name" VALUE="#URL_name#">
53: <INPUT type="hidden" name="Recipients_required" value="You did not select any recipients">
54: <CFSELECT NAME="recipients" QUERY="Recipients" MULTIPLE="YES" DISPLAY="client" VALUE="email" SIZE="5">
55: </CFSELECT>
56:
57: <OPTION value="#EmailField#">
58: <p>
59:
60: <OPTION value="">-----
61:
62: <FONT size=1>
63: <BR><INPUT type="radio" name="SendsSingleMessage" value="yes" checked><font face="Verdana, Arial, sans-serif"> Send
single message to all
64: <BR><INPUT type="radio" name="SendsSingleMessage" value="no"> Send one message to each recipient</font>
65: </FONT>
66: </td>
67: </TR>
68:
69: <TR><td align="right"><font face="Verdana, Arial, sans-serif" size="2"><B>From:</B></FONT></td>
70: <td><INPUT type="text" name="Sender" size=40 VALUE="#cfoutput#agency.email#</CFOUTPUT>"></td>
71: </TR>
72: <TR><td align="right"><font face="Verdana, Arial, sans-serif" size="2"><B>BCC:</B></FONT></td>
73: <td><INPUT type="text" name="BCC" size=40></td>
74: </TR>
75: <TR>
76: <td><B>Regarding Property:</B>
77: </td>
78: <td>
79: <CFSELECT NAME="selProp" QUERY="Properties" MULTIPLE="YES" DISPLAY="name" VALUE="prop_id" SIZE="5">
80: </CFSELECT>
81: </td>
82: </TR>
83: <TR><td><font face="Verdana, Arial, sans-serif" size="2"><B>Subject:</B></FONT></td>
84: <td><INPUT type="text" name="Subject" size=40></td>
85: </TR>
86:
87: <TR><td colspan=2>
88: <TEXTAREA name="Message" rows=10 cols=50 WRAP="virtual"></TEXTAREA>
89: </td>
90: </TR>
91:
92: <TR><td colspan=2 align="center"><INPUT type="submit" value="Send" "></td></TR>
93: </TABLE></div>
94:
95: </CFFORM>
96:
97: <p>
```

98: </BODY></HTML>



```

1: <CFPARAM NAME="URL.CallingType" DEFAULT="#0#">
2: <cfif URL.CallingType is 0>
3:   <cfparam name="URL.SortBy" default="address">
4:   <cfelseif URL.CallingType is 1>
5:   <cfparam name="URL.SortBy" default="name">
6: </cfif>
7:
8:
9: <CFIF URL.CallingType is 0>
10:   <CFSET nCallingType = 0>
11: <CFELSEIF URL.CallingType is 1>
12:   <CFSET nCallingType = 1>
13: <CFELSE>
14:   <CFLOCATION URL="ohrtadm.cfm" ADDTOKEN="NO">
15: </CFIF>
16:
17: <cfoutput>
18:   <CFIF nCallingType is 0>
19:     <cfquery name="qryAds" datasource="#SourceName#">
20:       SELECT AdData.callingID, AdData.startdate, AdData.stopdate, prop_main.address, agents.firstname, agents.lastname
21:     FROM AdData,prop_main,agents
22:     WHERE AdData.CallingType=#URL.CallingType#
23:     AND AdData.callingID=prop_main.prop_id
24:     and prop_main.agent_id = agents.agent_id
25:     and '16-' + convert(varchar,prop_main.agent_id) + '|' in (#listQualify(client.lstSecurity,"")#)
26:     ORDER BY #URL.SortBy#
27:   </cfquery>
28: <CFELSEIF nCallingType is 1>
29:   <cfquery name="qryAds" datasource="#SourceName#">
30:     SELECT adData.callingID, adData.startdate, adData.stopdate, agents.name
31:     FROM AdData,Agents
32:     WHERE AdData.CallingType=#URL.CallingType#
33:     AND AdData.callingID = Agents.agent_id
34:     and '14-' + convert(varchar,adData.callingID) + '|' in (#listQualify(client.lstSecurity,"")#)
35:     ORDER BY #URL.SortBy#
36:   </cfquery>
37: </CFIF>
38:
39:
40: </cfoutput>
41:
42: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
43:
44: <html>
45: <head>
46:   <cfoutput>
47:     <title>#ap_backofficeName# Backoffice</title>
48:   </cfoutput>
49:   <link rel="stylesheet" href="style1.css" type="text/css">

```

```
50: </head>
51:
52: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
53:
54: <p><cfinclude template="header.cfm"></p>
55:
56: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
57: <tr bgcolor="#cccc99">
58: <CFIF nCallingType is 0>
59: <td colspan="6"><b class="h2">Online Home Tours</b></td>
60: <CFELSEIF nCallingType is 1>
61: <td colspan="4"><b class="h2">Online Agents</b></td>
62: </CFIF>
63: </tr>
64:
65: <tr bgcolor="#cccccc">
66: <CFIF nCallingType is 0>
67: <td>Sort by <a href="ohrtadm.cfm?SortBy=address"><b>Address</b></a></td>
68: <td>Sort by <a href="ohrtadm.cfm?SortBy=callingID"><b>ID</b></a></td>
69: <td>Sort by <a href="ohrtadm.cfm?SortBy=lastname,firstname"><b>Agent</b></a></td>
70: <td>Sort by <a href="ohrtadm.cfm?SortBy=startDate"><b>Start Date</b></a></td>
71: <td>Sort by <a href="ohrtadm.cfm?SortBy=stopDate"><b>End Date</b></a></td>
72: <td><b>nbsp;</td>
73: <CFELSEIF nCallingType is 1>
74: <td>Sort by <a href="ohrtadm.cfm?CallingType=1&SortBy=name"><b>Agent Name</b></a></td>
75: <td>Sort by <a href="ohrtadm.cfm?CallingType=1&SortBy=startDate"><b>Start Date</b></a></td>
76: <td>Sort by <a href="ohrtadm.cfm?CallingType=1&SortBy=stopDate"><b>End Date</b></a></td>
77: <td><b>nbsp;</td>
78: </CFIF>
79: </tr>
80:
81: <cfset lColor = True>
82: <cfloop query="qryAds">
83: <cfset lColor = not lColor>
84: <tr <cfif lColor is TRUE>bgcolor="eeeeee"</cfif>
85: <cfoutput>
86: <CFIF nCallingType is 0>
87: <td>#qryAds.address#</td>
88: <td>#qryAds.callingID#</td>
89: <td>#qryAds.lastname#, #qryAds.firstname#</td>
90: <td>#dateFormat(qryAds.startDate,"mm/dd/yyyy")#</td>
91: <td>#dateFormat(qryAds.stopDate,"mm/dd/yyyy")#</td>
92: <td><a href="#OHTMaint.cfm?prop_id=#qryAds.callingID#">Edit</a></td>
93: <CFELSEIF nCallingType is 1>
94: <td>#qryAds.name# (#qryAds.callingID#)</td>
95: <td>#dateFormat(qryAds.startDate,"mm/dd/yyyy")#</td>
96: <td>#dateFormat(qryAds.stopDate,"mm/dd/yyyy")#</td>
97: <td><a href="#OHTMaint.cfm?Agent_id=#qryAds.callingID#">Edit</a></td>
98: </CFIF>
```

```
99:      </cfoutput>
100:      </tr>
101:      </cfloop>
102:      </table></p>
103:
104:      </body>
105:      </html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3:  <html>
4:  <head>
5:    <title>Update Ad Data</title>
6:  </head>
7:
8:  <body>
9:
10:   <CFPARAM NAME="URL_prop_id" DEFAULT="-1">
11:   <CFPARAM NAME="URL_agent_id" DEFAULT="-1">
12:
13:   <CFIF URL_prop_id gt -1>
14:     <CFSET nCallingID = URL_prop_id>
15:     <CFSET nCallingType = 0>
16:   <CFELSEIF URL_agent_id gt -1>
17:     <CFSET nCallingID = URL_agent_id>
18:     <CFSET nCallingType = 1>
19:   <CFELSE>
20:     !-- Nothing has been passed, so don't update anything -->
21:     <CFLOCATION URL="ohtadm.cfm" ADDTOKEN="NO">
22:   </CFIF>
23:
24:   <B>Updating Ad Data</B>
25:
26:   <CFIF isDefined("FORM.btnUpdate")>
27:     !-- Update the form information sent -->
28:     <CFQUERY NAME="qryFindAd" DATASOURCE="#SourceName#">
29:       SELECT * FROM AdData
30:       WHERE CallingID=#nCallingID#
31:     </CFQUERY>
32:
33:     <CFIF qryFindAd.recordcount is 0>
34:       !-- This record has not yet been created -->
35:       <CFIF nCallingType is 0>
36:         <CFSET cFilePath = #ap_OHT_path# & #nCallingID# & "\">
37:         <CFELSEIF nCallingType is 1>
38:           <CFSET cFilePath = #ap_OHT_path# & "Agent" & #nCallingID# & "\">
39:         </CFIF>
40:
41:       <CFTRY>
42:         <CFDIRECTORY
43:           DIRECTORY="#cFilePath#"
44:           ACTION="CREATE"
45:         >
46:       <CFOUTPUT>Creating New Directory #cFilePath#</CFOUTPUT><BR>
47:       <CFCATCH TYPE="ANY">
48:         !-- Directory already exists -->
49:       </CFCATCH>

```

```

50: </CFTRY>
51:
52: <!-- <B>Header:</B><CFOUTPUT>#len(FORM.edtHeader)##FORM.edtHeader#</CFOUTPUT> -->
53: <CFIF len(FORM.edtHeader) gt 0>
54:   <CFFILE
55:     DESTINATION=#cFilePath#
56:     ACTION="UPLOAD"
57:     NAMECONFLICT="OVERWRITE"
58:     FILEFIELD="edtHeader">
59:
60:   <CFSET cHeaderName = FILE.ServerFile>
61:   <CFELSE>
62:     <CFSET cHeaderName="">
63:   </CFIF>
64:
65:   <!-- <B>Footer:</B><CFOUTPUT>#len(FORM.edtFooter)##FORM.edtFooter#</CFOUTPUT> -->
66:   <CFIF len(FORM.edtFooter) gt 0>
67:     <CFFILE
68:       DESTINATION=#cFilePath#
69:       ACTION="UPLOAD"
70:       NAMECONFLICT="OVERWRITE"
71:       FILEFIELD="edtFooter">
72:     <CFSET cFooterName = FILE.ServerFile>
73:     <CFELSE>
74:       <CFSET cFooterName = "">
75:     </CFIF>
76:
77:   <CFIF len(FORM.edtprimaryPic) gt 0>
78:     <CFFILE
79:       DESTINATION=#cFilePath#
80:       ACTION="UPLOAD"
81:       NAMECONFLICT="OVERWRITE"
82:       FILEFIELD="edtPrimaryPic">
83:     <CFSET cPrimaryPic = FILE.ServerFile>
84:     <CFELSE>
85:       <CFSET cPrimaryPic = "">
86:     </CFIF>
87:
88:   <CFIF len(trim(FORM.edtStartDate)) is 0>
89:     <CFSET cStartDate = now()>
90:     <cfelse>
91:       <cftry>
92:         <cfset cStartDate = createODBCDate(FORM.edtStartDate)>
93:         <cfcatch type="any">
94:           <cfset cStartDate = createODBCDate(now())>
95:         </cfcatch>
96:       </cftry>
97:     </cfif>
98:

```

```

99:      <CFIF len(trim(FORM.edtStopDate)) > 0 >
100:      <CFSET cStopDate = createDate(1999,12,31) >
101:      </cfelse>
102:      </cftry>
103:      <cfset cStopDate = createODBCDate(FORM.edtStopDate)>
104:      <cfcatch type="any">
105:      <cfset cStopDate = createDate(1999,12,31)>
106:      </cfcatch>
107:      </cftry>
108:      </cfif>
109:
110:
111:      <CFQUERY NAME="qryAddAd" DATASOURCE="#SourceName#">
112:      INSERT INTO AdData(callingID, callingtype, startdate, stopdate, headerfilename, footerfilename, otherURL, primaryPic)
113:      VALUES (#nCallingID#, #nCallingType#, #cStartDate#, #cStopDate#, '#cHeaderName#', '#cFooterName#', '#FORM.edtURL#',
114:      '#cPrimaryPic#')
115:      </CFQUERY>
116:
117:      <CFELSE> <!-- This record already exists, so edit it -->
118:      <CFIF nCallingType is 0>
119:      <CFSET cFilePath = #ap_OHT_path# & #nCallingID# & "\">
120:      <CFELSEIF nCallingType is 1>
121:      <CFSET cFilePath = #ap_OHT_path# & "Agent" & #nCallingID# & "\">
122:      </CFIF>
123:
124:      <CFIF len(FORM.edtHeader) gt 0>
125:      <CFFILE
126:      DESTINATION=#cFilePath#
127:      ACTION="UPLOAD"
128:      NAMECONFLICT="OVERWRITE"
129:      FILEFIELD="edtHeader">
130:
131:      <CFSET cHeaderName = FILE.ServerFile>
132:      <CFELSE>
133:      <CFSET cHeaderName=qryFindAd.headerFilename>
134:      </CFIF>
135:
136:      <CFIF len(FORM.edtFooter) gt 0>
137:      <CFFILE
138:      DESTINATION=#cFilePath#
139:      ACTION="UPLOAD"
140:      NAMECONFLICT="OVERWRITE"
141:      FILEFIELD="edtFooter">
142:      <CFSET cFooterName = FILE.ServerFile>
143:      <CFELSE>
144:      <CFSET cFooterName = qryFindAd.footerFilename>
145:      </CFIF>
146:      <CFIF len(FORM.edtPrimaryPic) gt 0>

```

```

147: <CFIFILE
148:     DESTINATION=#cFilePath#
149:     ACTION="UPLOAD"
150:     NAMECONFLICT="OVERWRITE"
151:     FILEFIELD="edtPrimaryPic">
152: <CFSET cPrimaryPic = FILE.ServerFile>
153: <CFELSE>
154: <CFSET cPrimaryPic = qryFindAd.primaryPic>
155: </CFIF>
156:
157: <CFIF len(trim(FORM.edtStartDate)) is 0>
158: <cfset cStartDate = createODBCDate(now())>
159: <!-- <CFSET cStartDate = now()> -->
160: <cfelse>
161: <cftry>
162: <cfset cStartDate = createODBCDate(FORM.edtStartDate)>
163: <cfcatch type="any">
164: <cfset cStartDate = createODBCDate(now())>
165: <!-- <cfset cStartDate = now()> -->
166: </cfcatch>
167: </cftry>
168: </cfif>
169:
170: <CFIF len(trim(FORM.edtStopDate)) is 0>
171: <CFSET cStopDate = createDate(2999,12,31)>
172: <cfelse>
173: <cftry>
174: <cfset cStopDate = createODBCDate(FORM.edtStopDate)>
175: <cfcatch type="any">
176: <cfset cStopDate = createDate(2999,12,31)>
177: </cfcatch>
178: </cftry>
179: </cfif>
180:
181: <CFQUERY NAME="qryUpdateAd" DATASOURCE="#SourceName#">
182: UPDATE AdData
183: SET callingID=#nCallingID#, callingtype=#nCallingType#, startdate=#cStartDate#,
184: stopdate=#cStopDate#, headerfilename='#cHeaderName#', footerfilename='#cFooterName#',
185: otherURL='#FORM.edtURL#', primaryPic='#cPrimaryPic#',
186: WHERE callingID=#nCallingID# AND callingtype=#nCallingType#
187: </CFQUERY>
188:
189: </CFIF>
190:
191:
192: <CFIF nCallingType is 0>
193: <CFLOCATION URL="OHTMaint.cfm?prop_id=#nCallingID#" ADDTOKEN="NO">
194: <CFELSEIF nCallingType is 1>
195: <CFLOCATION URL="OHTMaint.cfm?agent_id=#nCallingID#" ADDTOKEN="NO">

```

```

196: <CFELSE>
197:   <CFLOCATION URL="ohtadm.cfm" ADDTOKEN="NO">
198: </CFIF>
199: <CFELSEIF isdefined("FORM.btnDelete")>
200:   <CFQUERY NAME="qryDeleteAd" DATASOURCE="#SourceName#">
201:     DELETE FROM AdData
202:     WHERE AdData.callingID=#nCallingID# AND AdData.callingType=#nCallingType#
203:   </CFQUERY>
204:
205:   <CFQUERY NAME="qryDeleteAd" DATASOURCE="#SourceName#">
206:     DELETE FROM p_param
207:     WHERE p_param.prop_id=#nCallingID# AND p_param.datagroup=5
208:   </CFQUERY>
209:
210:   <!-- First delete the directory files -->
211:   <CFIF nCallingType is 0>
212:     <CFSET cFilePath = #ap_OHT_path# & #nCallingID# & "\">
213:   <CFELSEIF nCallingType is 1>
214:     <CFSET cFilePath = #ap_OHT_path# & "Agent" & #nCallingID# & "\">
215:   </CFIF>
216:
217:   <CFDIRECTORY ACTION="LIST"
218:     DIRECTORY="#cFilePath#"
219:     NAME="qryDirList"
220:   >
221:
222:   <CFLOOP QUERY="qryDirList">
223:     <CFIF qryDirList.name IS NOT "." AND qryDirList.name IS NOT "..">
224:       <cftry>
225:         <CFSET cFilename = cFilePath & qryDirList.name>
226:         <CFFILE ACTION="DELETE"
227:           FILE="#cFilename#"
228:         >
229:         <cfcatch type="any">
230:           </cfcatch>
231:         </cftry>
232:       </CFIF>
233:     </CFLOOP>
234:
235:   <!-- Now delete the whole directory -->
236:   <CFIF nCallingType is 0>
237:     <CFSET cFilePath = #ap_OHT_path# & #nCallingID# & "\">
238:   <CFELSEIF nCallingType is 1>
239:     <CFSET cFilePath = #ap_OHT_path# & "Agent" & #nCallingID# & "\">
240:   </CFIF>
241:
242:   <cftry>
243:     <CFDIRECTORY ACTION="DELETE"
244:       DIRECTORY="#cFilePath#"

```



```
245: >
246: <cfcatch type="any">
247: <cfmail to="jjunker@techmission.com"
248:   from="ohtAdUpdate.cfm"
249:   subject="Cannot delete directory #cFilePath#"
250: >
251: I was unable to delete #cFilePath#. Please have someone do this manually to keep the server as clean as possible.
252: </cfmail>
253:
254: </cfcatch>
255: </cftry>
256:
257: <cfif nCallingType is 0>
258:   <CFLOCATION URL="ohtadm.cfm" ADDTOKEN="NO">
259: <cfelseif nCallingType is 1>
260:   <CFLOCATION URL="agentbroadm.cfm" ADDTOKEN="NO">
261: </cfif>
262:
263: <CFELSEIF isDefined("FORM.btnGenerate")>
264:   <CFIF nCallingType is 0>
265:     <CFLOCATION URL="OHTGenerate.cfm?prop_id=#nCallingID#" ADDTOKEN="NO">
266:   <CFELSEIF nCallingType is 1>
267:     <CFLOCATION URL="OHTGenerate.cfm?agent_id=#nCallingID#" ADDTOKEN="NO">
268:   <CFELSE>
269:     <CFLOCATION URL="ohtadm.cfm" ADDTOKEN="NO">
270:   </CFIF>
271: </CFIF>
272:
273: </body>
274: </html>
```

```
1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
2:
3:  <html>
4:  <head>
5:    <title>Generating Online Home Tour Page</title>
6:  </head>
7:
8:  <body>
9:    <B><FONT SIZE="+2">Generating Online Home Tour Page...</FONT></B>
10:    <BR>
11:    <BR>
12:    <B><DIV ALIGN="center">Please Wait...</DIV></B>
13:    <BR>
14:    <BR>
15:    You will automatically be redirected to the maintenance page for this property...
16:
17:    <CFLOCATION URL="OHTgenerate.cfm?prop_id=#URL.prop_id#" ADDTOKEN="NO">
18:  </body>
19: </html>
```

```

1: <cfinclude template="../propLists.cfm">
2:
3:
4:
5: <cfset ls_inFields = fieldNames>
6: <cfset rs = listContainsNoCase(ls_inFields, "oht")>
7: <cfif rs gt 0>
8:   <cfset ls_inFields = listDeleteAt(ls_inFields, rs)>
9: </cfif>
10: <!-- If nothing is selected in a multiple combo, the field is not passed for editing or editing --->
11: <cfif not isDefined("form.findPropType")>
12:   <cfset form.findPropType = "">
13:   <cfset ls_inFields = listappend(ls_inFields, "findPropType")>
14: </cfif>
15: <cfquery name="qryFindAgency" datasource="#sourcename#">
16:   select agents.agency_id
17:   from agents
18:   where agents.agent_id=#form.agent_id#
19: </cfquery>
20: <cfif qryFindAgency.recordCount gt 0>
21:   <cfset form.agency_id=qryFindAgency.agency_id>
22:   <cfset ls_inFields = listAppend(ls_inFields, "agency_id")>
23: </cfelse>
24:   <cfset form.agency_id = 0>
25:   <cfset ls_inFields = listAppend(ls_inFields, "agency_id")>
26: </cfif>
27:
28:
29: <cfif isDefined("Form.prop_id")>
30:   <cfset Operation="Updated">
31:   <cfupdate datasource="#sourcename#" tablename="prop_main" formfields="#ls_inFields#">
32:   <cfquery datasource="#sourcename#" name="PropImage">
33:     SELECT prop_main.name, prop_main.prop_id
34:     FROM prop_main
35:     where
36:       prop_main.distributorID = #ap_distributorID#
37:       and '16-' + convert(varchar,prop_main.agent_id) + '|' in (#listQualify(client.lstSecurity,"")#)
38:   <cfif isDefined("URL.ReturnAgency_id")> <!-- Filter for agency selected --->
39:     and prop_main.agency_id=#URL.ReturnAgency_id#
40:   </cfif>
41:   AND status > #ap_notListed#
42:   ORDER BY prop_id DESC
43: </cfquery>
44: <cfoutput>
45:   <cfif isDefined("oht")>
46:     <cflocation url="ohtMaint.cfm?prop_id=#form.prop_id#">
47:   </cfif>
48:   </cfoutput>
49: </cfelse>

```

```

50: <cfset Operation="Inserted">
51: <cftransaction>
52:   <cfinsert datasource="#sourceName#" tablename="prop_main">
53:
54:   <cfquery datasource="#sourceName#" name="PropImage">
55:     SELECT prop_main.name, prop_main.prop_id
56:     FROM prop_main
57:     where
58:       prop_main.distributorID = #ap_distributorID#
59:       and '16-' + convert(varchar,prop_main.agent_id) + '|' in (#listQualify(client.lstSecurity,'"')#)
60:   <cfif isDefined("URL.ReturnAgency_id")> <!-- Filter for agency selected -->
61:     and prop_main.agency_id=#URL.ReturnAgency_id#
62:   </cfif>
63:   AND status > #ap_notListed#
64:   ORDER BY prop_id DESC
65: </cfquery>
66:   <cfquery name="qTimestamp" datasource="#sourceName#">
67:     update prop_main
68:     set s_start_date = '#dateformat(now(),"mm/dd/yyyy")#'
69:     where prop_id = #PropImage.prop_id#
70:   </cfquery>
71:   <cfset prop_id = "#PropImage.Prop_Id#">
72:   </cftransaction>
73: </cfif>
74:
75:
76:
77:
78: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
79:
80: <html>
81: <head>
82:   <cfoutput>
83:     <title>#ap_backofficeName# Backoffice</title>
84:   </cfoutput>
85:   <link rel="stylesheet" href="style1.css" type="text/css">
86: </head>
87:
88: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
89:
90: <p><cfinclude template="header.cfm"></p>
91:
92: <cfif isDefined("URL.PropertyTypeID")>
93:   <cflocation URL="propTypeAttached.cfm?PropertyTypeID=#URL.PropertyTypeID# addToken="NO">
94: </cfif>
95:
96: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
97:   <tr bgcolor="#cccc99"><td width="50%" valign="top"><b>Property </b></span><cfoutput>#name#, #prop_id#
     #Operation#</cfoutput></td>

```

```

98:      <td>&nbsp;</td>
99:      <td align="right" width="50%">To add or replace property's photo or virtual tour, click the appropriate link below.
      Otherwise, <a href="propadm.cfm">return to Properties</a></td></tr>

100:
101:      <cfif isdefined("URL.ReturnURL") and isdefined("URL.ReturnAgency_id")>
102:      <cfquery name="qryFindAgency" datasource="#sourcename#">
103:      select name
104:      from agency
105:      where agency.agency_id=#URL.ReturnAgency_id#
106:      </cfquery>
107:
108:      <cfset cReturnURL="#URL.ReturnURL#?agency_id=#URL.ReturnAgency_ID#&displayPage=Properties">
109:      <tr bgcolor="#cccc99">
110:      <cfoutput>
111:      <td colspan="3" align="right"><a href="#cReturnURL#">Return to #qryFindAgency.name# agency</a></td>
112:      </cfoutput>
113:      </tr>
114:      </cfif>
115:
116:      <tr bgcolor="#cccccc"><td><b>Property ID</b></td><td><b>Property ID</b></td><td><b>&nbsp;</td></tr>
117:      <cfoutput query="PropImage">
118:
119:      <tr><td>#name#</td>
120:      <td>#prop_id#</td>
121:      <td align="right"><a href="imagadm.cfm?prop_id=#prop_id#">Property Picture</a> | <a
      href="bambooAdmn.cfm?prop_id=#prop_id#">Virtual Tour</a></td>
122:      </tr></cfoutput>
123:      </table></p>
124:
125:      </body>
126:      </html>

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN">
2: <cfinclude template="include\security.cfm">
3:
4:
5: <cfoutput>
6:   <cfparam name="URL.SortBy" default="Name">
7:   <cfquery name="qryPropTypes" datasource="#SourceName#">
8:     SELECT PropTypeID, Name
9:     FROM PropTypes
10:    WHERE propTypes.distributorID = #ap_distributorID#
11:    ORDER BY #URL.SortBy#
12:  </cfquery>
13:
14:  </cfoutput>
15:
16:
17:  <html>
18:  <head>
19:    <cfoutput>
20:      <title>#ap_backofficeName# Backoffice</title>
21:    </cfoutput>
22:    <link rel="stylesheet" href="style1.css" type="text/css">
23:  </head>
24:
25:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" margin
26:
27:  <p><cfinclude template="header.cfm"></p>
28:
29:  <p><table border="0" cellpadding="1" cellspacing="0" align="center" width=
30:    <tr bgcolor="#cccc99">
31:      <td colspan="5">
32:        <span class="h2"><b>Specialty Pages</b></span><nbsp;<b></b></span><nbsp;<b>
33:        <cfif isDefined("ap_maxSpecialties")>
34:          <cfif qryPropTypes.recordCount lt ap_maxSpecialties>
35:            <cfset lShowAdd = True>
36:          <cfelse>
37:            <cfset lShowAdd = False>
38:          </cfif>
39:          <cfelse>
40:            <cfset lShowAdd = True>
41:          </cfif>
42:
43:          <cfif lShowAdd is True>
44:            <a href="PropTypeMaint.cfm">Add a Specialty Page</a>
45:          </cfif>
46:
47:          <nbsp;<b></b></span><nbsp;<b>[Properties]</a>
48:        </td>
49:      </tr>

```

-----

```
50:
51: <tr bgcolor="#cccccc">
52:   <td>sort by <a href="PropTypeAdm.cfm?SortBy=Name"><b>Name</b></a></td>
53:   <td>&nbsp;</td>
54: </tr>
55:
56:
57: <CFIF qryPropTypes.recordCount is 0>
58:   <TR><TD COLSPAN="5"><I>There are no Specialty Pages defined</I></TD></TR>
59: </CFIF>
60: <cfset lColor = True>
61: <cfloop query="qryPropTypes">
62:   <cfset lColor = not lColor>
63:   <tr <cfif lColor is TRUE>bgcolor="eeeeee"</cfif>>
64:     <cfoutput>
65:       <td>#qryPropTypes.Name#</td>
66:       <td><a href="PropTypeMaint.cfm?PropTypeID=#qryPropTypes.PropTypeID#">Edit</a></td>
67:     </cfoutput>
68:   </tr>
69: </cfloop>
70: </table></p>
71:
72: </body>
73: </html>
```

```
1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfif not isDefined("URL.PropertyTypeID")>
4:    <cflocation url="propTypeadm.cfm" addtoken="no">
5:  </cfif>
6:
7:  <cfoutput>
8:    <cfparam name="URL.SortBy" default="Name">
9:    <cfquery name="qryFindProps" datasource="#SourceName#">
10:      SELECT prop_id,Name,Address
11:      FROM prop_main
12:      where '#URL.PropertyTypeID#' in (prop_main.findPropType)
13:      ORDER BY #URL.SortBy#
14:    </cfquery>
15:
16:    <cfif qryFindProps.recordCount is 0>
17:      <cflocation url="propTypeMaint.cfm?PropertyTypeID=#URL.PropertyTypeID#" addtoken="no">
18:    </cfif>
19:
20:    <cfquery name="qryPropType" datasource="#SourceName#">
21:      select name
22:      from proptypes
23:      where proptypes.propertyID = #URL.propertyTypeID#
24:    </cfquery>
25:
26:    </cfoutput>
27:
28:
29:  <html>
30:  <head>
31:    <cfoutput>
32:      <title>#ap_backofficeName# Backoffice</title>
33:    </cfoutput>
34:    <link rel="stylesheet" href="style1.css" type="text/css">
35:  </head>
36:
37:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
38:
39:  <p><cfinclude template="header.cfm"></p>
40:  <cfoutput>
41:  <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
42:    <tr bgcolor="#cccc99">
43:      <td colspan="5">
44:        <span class="h2"><b>Properties containing Property Type #qryPropType.name#</b></span>
45:        <b><a href="PropTypeadm.cfm">[Back To Property Types]</a>
46:      </td>
47:    </tr>
48:
49:    <tr bgcolor="#cccccc">
```



```
50:      <td>Sort by <a href="PropTypeAttached.cfm?SortBy=Name">bName</a></td>
51:      <td>&nbsp;</td>
52:    </tr>
53:
54:
55:    <CFIF qryFindProps.recordCount is 0>
56:      <TR><TD COLSPAN="5"><I>There are no properties attached to this property type</I></TD></TR>
57:    </CFIF>
58:    <cfset lColor = True>
59:    <cfloop query="qryFindProps">
60:      <cfset lColor = not lColor>
61:      <tr <cfif lColor is TRUE>bgcolor="#ffffff"</cfif>>
62:        <td>#qryFindProps.Name#</td>
63:        <td><a href="propForm.cfm?Prop_id=#qryFindProps.prop_id&propertyTypeID=#URL.propertyTypeID">Edit</a></td>
64:      </tr>
65:    </cfloop>
66:  </table></p>
67:  </cfoutput>
68: </body>
69: </html>
```

```

1: <CFPARAM NAME="ACTION" DEFAULT="Cancel">
2:
3: <CFIF isDefined("PropTypeID")>
4:   <cfset nPropTypeID = PropTypeID>
5: </cfif>
6:
7:
8: <HTML>
9: <TITLE>Online Property Type Upload Results</TITLE>
10:
11: <CFIF #Action# is "Cancel">
12:   <CFLOCATION URL="propTypeMaint.cfm?PropTypeID=#nPropTypeID#" ADToken="NO">
13: </CFIF>
14:
15: <BODY BGCOLOR="WHITE">
16:   <!-- <CFINCLUDE TEMPLATE="acmlinks.cfm" --> -->
17:   <CFAPPLICATION NAME="Realstuff" CLIENTMANAGEMENT="Yes">
18:
19:   <CFIF #Action# is "Add">
20:     Field Values:<BR>
21:     <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
22:       <CFSET cNewField = "FORM.Field" & nIndex>
23:       <CFOUTPUT>#cNewField# = #evaluate(cNewField)#<BR></CFOUTPUT>
24:     </CFLOOP>
25:   <BR>
26:   <HR>
27:
28:
29:   <!-- First try to find out what kind of image is being uploaded -->
30:   <CFSET nImageTypeLoc = listFindNoCase(FORM.Field_Names,'imgType')>
31:   <CFIF nImageTypeLoc GT 0>
32:     <CFSET cImageField = 'FORM.FIELD' & nImageTypeLoc>
33:     <CFSET nImageType = #evaluate(cImageField)#>
34:     <CFOUTPUT>Image Type : #nImageType#<BR></CFOUTPUT>
35:   <CFELSE>
36:     <CFSET nImageType = -1>
37:   </CFIF>
38:
39:   <!-- !!!!! -->
40:   <!-- <CFSET nImageType = 0> -->
41:
42:   <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
43:     <CFSET nParamID = -1>
44:
45:     <CFQUERY NAME="qryFindParamID" DATASOURCE="#SourceName#">
46:       SELECT * FROM param_defs
47:       WHERE dataGroup=8
48:       AND agency_id in (10, #ap_agency_number#)
49:       AND name='#listGetAt(FORM.Field_Names,nIndex)#'

```

```

50: </CFQUERY>
51:
52: <CFIF qryFindParamID.recordCount GT 0>
53:   <CFSET nParamID = qryFindParamID.id>
54: </CFIF>
55:
56: <CFSET cFieldType = ucase(trim(listGetAt(FORM.FieldTypes, nIndex)))>
57: <CFSET cNewField = "FORM.FIELD" & nIndex>
58:
59: <CFIF cFieldType is "TEXT">
60:   <cfoutput>Inserting data:
     #nPropTypeID#, #nParamID#, #ap_agency_number#, #param_counter#, #qryFindParamID.name#, '#Evaluate(cNewField)#', 8</cfoutput>
     <br>
61:   <CFSET cTextToSend = evaluate(cNewField)>
62:   <CFSET cTextToSend = preservesingleQuotes(cTextToSend)>
63:   <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
64:     INSERT INTO proptype_param (PropTypeID,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
65:     VALUES (#PropTypeID#,nParamID#,ap_agency_number#,param_counter#, 'qryFindParamID.name#','#cTextToSend#',8)
66:   </CFQUERY>
67:   <CFELSEIF cFieldType is "TEXTAREA">
68:     <cfoutput>Inserting Text Area data:
     #nPropTypeID#, #nParamID#, #ap_agency_number#, #param_counter#, 'qryFindParamID.name#','#Evaluate(cNewField)#', 8</cfoutput>
     <br>
69:     <CFSET cTextToSend = evaluate(cNewField)>
70:     <CFSET cTextToSend = preservesingleQuotes(cTextToSend)>
71:     <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
72:       INSERT INTO proptype_param (PropTypeID,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
73:       VALUES (#PropTypeID#,nParamID#,ap_agency_number#,param_counter#, 'qryFindParamID.name#','#cTextToSend#',8)
74:     </CFQUERY>
75:     <CFELSEIF cFieldType is "CHECKBOX">
76:       <cfoutput>Inserting checkbox data:
     #nPropTypeID#, #nParamID#, #ap_agency_number#, #param_counter#, 'qryFindParamID.name#','#Evaluate(cNewField)#', 8</cfoutput>
     <br>
77:       <CFSET cTextToSend = evaluate(cNewField)>
78:       <CFSET cTextToSend = preservesingleQuotes(cTextToSend)>
79:       <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
80:         INSERT INTO proptype_param (proptypeID,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
81:         VALUES (#proptypeID#,nParamID#,ap_agency_number#,param_counter#, 'qryFindParamID.name#','#cTextToSend#',8)
82:       </CFQUERY>
83:
84:     <CFELSEIF cFieldType is "SELECT">
85:       <cfoutput>Inserting select data:
     #nPropTypeID#, #nParamID#, #ap_agency_number#, #param_counter#, 'qryFindParamID.name#','#Evaluate(cNewField)#', 8</cfoutput>
     <br>
86:       <CFSET cTextToSend = evaluate(cNewField)>
87:       <CFSET cTextToSend = preservesingleQuotes(cTextToSend)>
88:       <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
89:         INSERT INTO proptype_param (proptypeID,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
90:         VALUES (#proptypeID#,nParamID#,ap_agency_number#,param_counter#, 'qryFindParamID.name#','#cTextToSend#',8)

```

```

91: </CFQUERY>
92: <CFELSEIF cFieldType is "FILE">
93:   <HR>
94:   <CFSET cNewField = "FORM.FIELD" & nIndex>
95:   <CFSET cFileField = trim("Field" & nIndex)>
96:
97:   <CFSET cFilePath = #ap_propType_path# & #FORM.propTypeID# & "\">
98:
99:   <CFOUTPUT>File Name is: #cFilePath#</CFOUTPUT><BR>
100:   <CFOUTPUT>New Field : #cNewField# (#evaluate(cNewField)#)</CFOUTPUT><BR>
101:   <CFOUTPUT>Field Name: #listGetAt(FORM.Field Names,nIndex)#</CFOUTPUT><BR>
102:   <CFIF listGetAt(FORM.Field Names, nIndex) is "ptypeImage">
103:     <CFSET nImageField = #FORM.imageField#>
104:     <CFSET cImageType = "FORM.FIELD" & nImageField>
105:     <CFIF nImageType is "0"> <!-- This is a still image --> <!-- </CFIF>>nImageField 67 0 ANL
        #evaluate(cImageType) is "0"> <!-->
106:     <CFOUTPUT>#ap_propType_path# : #cNewField#</CFOUTPUT>
107:     <CFOUTPUT>[#evaluate(cNewField)#]</CFOUTPUT>
108:
109:     <CFTRY>
110:       <CFDIRECTORY>
111:         DIRECTORY="#cFilePath#"
112:         ACTION="CREATE"
113:       >
114:       <CFOUTPUT>Creating New Directory #cFilePath#</CFOUTPUT><BR>
115:       <CFCATCH TYPE="ANY">
116:         <B>Directory already exists!</B><BR>
117:       </CFCATCH>
118:     </CFTRY>
119:
120:     <!-- if an image name is not sent, then the user only wanted to add a text entry --->
121:     <!-- If the field is blank, don't try to send anything --->
122:
123:     <CFSET cEvaluate = evaluate(cNewField)>
124:     <CFIF len(trim(cEvaluate)) gt 0>
125:       <CFFILE>
126:         DESTINATION=#cFilePath#
127:         ACTION="UPLOAD"
128:         NAMECONFLICT="OVERWRITE"
129:         FILEFIELD="#cFileField#"
130:
131:       <CFIF #FILE.fileWasSaved#>
132:         <BR><B>File was Saved</B><BR>
133:         <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
134:           INSERT INTO propType_param(propTypeID,param_id,agency_id,param_cntr,param_name,param_value,dataGroup)
135:             VALUES
              (#propTypeID,#nParamID#,#ap_agency_number#,#param_counter#,'#qryFindParamID.name#','propType\#FORM.propTypeID#\#FILE.Server
              File#',8)
136:         </CFQUERY>

```

```

137: <CFELSE>
138: <BR><B>File was NOT saved</B>
139: <CFABORT>
140: </CFIF>
141: <CFELSE>
142: <!-- Save the database info so the other programs don't get confused --->
143: <BR><B>File was Saved (No image)</B><BR>
144: <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
145: INSERT INTO proptype_param(proptypeID,param_id,agency_id,param_cntr,param_value,dataGroup)
146: VALUES (#proptypeID#, #nParamID#, #ap_agency_number#, #param_counter#, 'qryFindParamID.name#',' ',8)
147: </CFQUERY>
148: </CFIF>
149: <CFELSE>
150: <CFOUTPUT>Saving other image information: #cNewField# [#evaluate(cNewField)] #evaluate('FORM.Field1')# *
#cFileField# * #evaluate(cFileField)<BR></CFOUTPUT>
151: <CFQUERY NAME="qryAddParameter" DATASOURCE="#SourceName#">
152: INSERT INTO proptype_param(proptypeID,param_id,agency_id,param_cntr,param_value,dataGroup)
153: VALUES
(#proptypeID#, #nParamID#, #ap_agency_number#, #param_counter#, 'qryFindParamID.name#', '#Evaluate(cNewField)#',8)
</CFQUERY>
154: </CFIF>
155: </CFIF>
156: </CFIF>
157: </CFIF>
158: </CFLOOP>
159:
160:
161: <!-- Now take us back to the view mode, informing the user that information has been updated --->
162: <CFLOCATION URL="propTypeMaint.cfm?proptypeID=#nProptypeID#&Action=Updated" ADDTOKEN="NO">
163: <CFELSEIF #Action# is "Edit">
164: <!-- First try to find out what kind of image is being uploaded -->
165: <CFSET nImageTypeLoc = listFindNoCase(FORM.Field_Names, 'imgType')>
166: <CFIF nImageTypeLoc GT 0>
167: <CFSET cImageField = 'FORM.FIELD' & nImageTypeLoc>
168: <CFSET nImageType = #evaluate(cImageField)#>
169: <CFOUTPUT>Image Type : #nImageType#</CFOUTPUT>
170: <CFELSE>
171: <CFSET nImageType = -1>
172: </CFIF>
173:
174: <!-- !!!!! -->
175: <!-- <CFSET nImageType = 0> --->
176:
177:
178: <CFLOOP FROM="1" TO="#listLen(FORM.Field_Names)#" INDEX="nIndex">
179: <CFSET cFieldtype = ucase(trim(listGetAt(FORM.FieldTypes, nIndex)))>
180: <CFSET cNewField = "FORM.FIELD" & nIndex>
181:
182: <CFIF cFieldtype is "FILE">
183: <CFSET cNewField = "FORM.FIELD" & nIndex>

```

```

184: <CFSET cFileField = trim("Field" & nIndex)>
185:
186: <CFOUTPUT>New Field : #cNewField# (#evaluate(cNewField)#)</CFOUTPUT><BR>
187: <CFOUTPUT>Field Name: #listGetAt(FORM.Field_Names,nIndex)#</CFOUTPUT><BR>
188:
189: <CFIF listGetAt(FORM.Field_Names, nIndex) is "PTypeImage" AND #evaluate(cNewField)# is not "">
190:   <CFSET nImageField = #FORM.imageField#>
191:   <CFSET cImageType = "FORM.FIELD" & nImageField>
192:   <CFIF nImageType is "0"> <!-- This is a still image --> <!-- </CFIF>nImageType is 1 AND #evaluate(cImageType)#
      is "1">
193:     <CFOUTPUT>#ap_propotype_path# : #cNewField#</CFOUTPUT>
194:     <CFOUTPUT>[#evaluate(cNewField)#]</CFOUTPUT>
195:
196:     <CFSET cFilePath = #ap_propotype_path# & #npropTypeID# & "\">
197:
198:     <CFIF #FILE.fileWasSaved#>
199:       DESTINATION=#cFilePath#
200:       ACTION="UPLOAD"
201:       NAMECONFLICT="OVERWRITE"
202:       FILEFIELD="#cFileField#"
203:
204:     <CFIF #FILE.fileWasSaved#>
205:       <B>File was Saved</B><BR>
206:       <CFOUTPUT>#evaluate(cNewField)# / #npropTypeID# / #param_counter# /
        #listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
207:       <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
        UPDATE propotype_param
        SET param_value = 'propotype\#npropTypeID#\#FILE.ServerFile#'
        WHERE propTypeID=#propTypeID#
        AND param_cntr=#param_counter#
        AND param_name='listGetAt(FORM.Field_Names,nIndex) #'
        </CFQUERY>
208:       <CFELSE>
209:         <B>File was NOT saved</B>
210:         <CFABORT>
211:       </CFIF>
212:     <CFELSE>
213:       <!-- Just insert the name, since this is not a still image -->
214:
215:       <CFOUTPUT>Insert Other Image<BR>#evaluate(cNewField)# / #propTypeID# / #param_counter# /
        #listGetAt(FORM.Field_Names,nIndex)#<BR></CFOUTPUT>
216:       <CFSET cTextToSend = evaluate(cNewField)>
217:       <CFSET cTextToSend = preserveSingleQuotes(cTextToSend)>
218:       <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
        UPDATE propotype_param
        SET param_value = 'cTextToSend#'
        WHERE propTypeID=#npropTypeID#
        AND param_cntr=#param_counter#
        AND param_name='listGetAt(FORM.Field_Names,nIndex) #'
219:
220:
221:
222:
223:
224:
225:
226:
227:
228:
229:

```

```

230:      </CFQUERY>
231:      </CFIF>
232:      </CFIF>
233:      <CFELSE>
234:      <CFOUTPUT>#Evaluate(cNewField)# / #npropTypeID# / #param_counter# /
        #listGetAt(FORM_Field_Names,nIndex)#<BR></CFOUTPUT>
235:      <CFSET cTextToSend = evaluate(cNewField)>
236:      <CFSET cTextToSend = preservesSingleQuotes(cTextToSend)>
237:      <CFQUERY NAME="qryUpdateParams" DATASOURCE="#SourceName#">
238:      UPDATE proptype_param
239:      SET param_value = 'cTextToSend'
240:      WHERE proptypeID=#npropTypeID#
241:      AND param_cntr=#param_counter#
242:      AND param_name='#listGetAt(FORM_Field_Names,nIndex) #'
243:      </CFQUERY>
244:      </CFIF>
245:      </CFLOOP>
246:      <!-- Now take us back to the view mode, informing the user that information has been updated -->
247:      <CFLOCATION URL="propTypeMaint.cfm?propTypeID=#npropTypeID#&Action=Updated" ADDTOKEN="NO">
248:
249:      <CFELSEIF #Action# is "Delete">
250:      <CFIF NOT IsDefined("param_counter")> <!-- go delete the information -->
251:      <CFLOCATION URL="propTypeMaint.cfm?propTypeID=#npropTypeID#" ADDTOKEN="NO">
252:      </CFIF>
253:
254:      <!-- Delete the selected paragraph -->
255:      <CFQUERY NAME="qryDeleteAd" DATASOURCE="#SourceName#">
256:      DELETE FROM proptype_param
257:      WHERE proptypeID=#npropTypeID# AND
258:      param_cntr=#param_counter# AND
259:      agency_id=#ap_agency_number# AND
260:      dataGroup=8
261:      </CFQUERY>
262:
263:      <!-- Now take us back to the view mode, informing the user that information has been updated -->
264:      <CFLOCATION URL="propTypeMaint.cfm?propTypeID=#npropTypeID#&Action=Deleted" ADDTOKEN="NO">
265:      </CFIF>
266:
267:      </BODY>
268:      </HTML>
269:

```

```

1:  <!-- Version Changes
2:  5/14/00 JHJ Added Classified property type and Classified region selection to allow
3:  classified search selection fields to automatically filter depending on where the
4:  classified search is called from.
5:
6:
7:  -->
8:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
9:
10:  <!-- -1 = add a new property type -->
11:  <CFPARAM NAME="URL.PropTypeID" DEFAULT="-1">
12:  <CFPARAM NAME="URL.Action" DEFAULT="View">
13:  <cfparam name="URL.param_counter" default="-1"> <!-- If editing, this will have a number -->
14:  <cfparam name="URL.ImageType" default="0"> <!-- the image type -->
15:
16:
17:  <CFSET nPropTypeID = URL.PropTypeID>
18:
19:  <cfset lstPropType = "All,Residential,Condos,Land,Commercial,Income">
20:  <cfset lstPropValues="0,1,2,3,4,5">
21:
22:  <cfinclude template="..\commDefines.cfm">
23:  <cfinclude template="..\propLists.cfm">
24:  <!--
25:  <cfset lstRegions = "All,Metro Denver,NorthEast,NorthWest,SouthEast,SouthWest,Mountain,Other">
26:  <cfset lstRegionValues="0,1,2,3,4,5,6,7">
27:  -->
28:
29:  <!-- Find the Property type based on the passed PropTypeID -->
30:  <cfquery name="qryFindProp" datasource="#sourceName#">
31:  SELECT *
32:  FROM PropTypes
33:  WHERE PropTypeID = #nPropTypeID#
34:  </cfquery>
35:
36:
37:  <cfquery name="qryParameters" datasource="#sourceName#">
38:  SELECT proptype_param.PropTypeID, proptype_param.agency_id, proptype_param.param_name, proptype_param.param_value,
39:  proptype_param.param_cntr,
40:  param_defs.description, param_defs.label, param_defs.displayOrder, param_defs.restrictions, param_defs.type
41:  FROM param_defs, proptype_param
42:  WHERE proptype_param.PropTypeID=#nPropTypeID#
43:  AND proptype_param.param_id = param_defs.id
44:  ORDER BY proptype_param.param_cntr,param_defs.displayOrder
45:  </cfquery>
46:
47:  <!-- Parameter names for the image fields -->
48:  <cfquery name="qryParamNames" datasource="#sourceName#">
  SELECT

```



```

49:      DISTINCT id, name, description, label, displayorder, restrictions, type, selectOptions
50:    FROM param_defs
51:   WHERE securityLevel=1
52:   AND dataGroup = 8
53:   ORDER BY displayOrder
54: </cfquery>
55:
56: <!-- qryImageTypes will load the image types for the pull down while
57:      adding or editing a photo -->
58: <cfquery name="qryImageTypes" datasource="#sourceName#">
59:   SELECT label,counter,value,agency_id
60:   FROM param_allowed
61:   WHERE param_allowed.id = 9
62:   ORDER BY param_allowed.counter
63: </cfquery>
64:
65:
66: <!-- Delimited lists for various uses -->
67: <cfset listLabels = ValueList(qryParamNames.label)> <!-- "Use Name" -->
68: <cfset listFieldNames = ValueList(qryParamNames.name)> <!-- "CommitFile" -->
69: <cfset listFieldTypes = ValueList(qryParamNames.type)> <!-- TEXT, field, etc. -->
70: <cfset listFieldOptions = QuotedValueList(qryParamNames.selectOptions,"|")>
71:
72:
73: <html>
74: <head>
75:   <cfoutput>
76:     <title>#ap_backofficeName# Backoffice</title>
77:   </cfoutput>
78:   <link rel="stylesheet" href="style1.css" type="text/css">
79:   <meta http-equiv="Expires" content="Mon, 06 Jan 1990 00:00:01 GMT">
80: </head>
81:
82: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
83:
84: <p><cfinclude template="header.cfm"></p>
85:
86: <cfoutput>
87:
88: <CFSET nTotalCols = qryParamNames.recordCount+2>
89: <CFSET aFieldValues = ArrayNew(1)>
90:
91: <CFIF URL.Action is "View">
92:   <!-- Set default values for the edit fields -->
93:   <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
94:     <CFSET aFieldValues[nIndex] = "">
95:   </CFLOOP>
96:
97:   <CFELSEIF URL.Action is "Add">

```

```

98: <CFSET URL.Action = "View">
99: <CFELSEIF URL.Action is "Edit">
100:   <!-- A Paragraph has been selected for editing -->
101: <CFELSEIF URL.Action is "Deleted">
102:   <!-- Delete the selected image -->
103:   <!-- Set default values for the edit field2 -->
104: <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
105:   <CFSET afieldValues[nIndex] = "">
106: </CFLOOP>
107:
108: <CFSET URL.Action = "View">
109: <CFELSEIF URL.Action is "Updated">
110:   <!-- Set default values for the edit fields -->
111: <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
112:   <CFSET afieldValues[nIndex] = "">
113: </CFLOOP>
114: <CFSET URL.Action = "View">
115: </CFIF>
116:
117: <p>
118: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
119:   <tr bgcolor="cccc99"><td colspan="2"><span class="h2"><b>Online Specialty Pages</b></span></td></tr>
120:   <tr bgcolor="cccccc"><td colspan="2"><b>General Specialty Page Information</b></td></tr>
121:   <tr bgcolor="eeeeee">
122:     <td width="20%">Specialty Page Name:</td>
123:     <td>
124:       <form name="frmPropInfo" enctype="multipart/form-data" action="propTypeUpdate.cfm?propTypeID=#nPropTypeID#"
method="post">
125:         <input type="text" name="edtPropName" value="#qryFindProp.Name#"></td>
126:       </tr>
127:       <input type="hidden" name="edtHeader" value="">
128:       <input type="hidden" name="edtFooter" value="">
129:       <input type="hidden" name="edtPrimaryPic" value="">
130:       <!-- <tr bgcolor="eeeeee">
131:         <td width="20%">
Header Image:</td>
132:         <td>
133:           <input type="file" name="edtFeeder">
134:           <cfif qryFindProp.recordCount gt 0>
135:             <em>Currently: <getFileFromPath(qryFindProp.headerFilename) #</em>
136:             <cfif trim(qryFindProp.headerFilename) is not "">
137:               <input type="checkbox" name="edtDeleteHeader">Delete Image?
138:             </cfif>
139:           </td>
140:         </tr>
141:       </tr>
142:       <tr bgcolor="eeeeee">
143:         <td width="20%">Footer Image:</td>
144:         <td>
145:

```

```

<input type="FILE" name="edtFooter">
<cfif qryFindProp.recordCount gt 0>
  <en>Currently: #getFileFromPath(qryFindProp.footerFilename)#</en>
  <cfif trim(qryFindProp.footerFilename) is not "">
    <input type="checkbox" name="edtDeleteFooter">Delete Image?
  </cfif>
</cfif>
</td> - ->
</tr>

```

```

146: <input type="FILE" name="edtFooter">
147: <cfif qryFindProp.recordCount gt 0>
148:   <en>Currently: #getFileFromPath(qryFindProp.footerFilename)#</en>
149:   <cfif trim(qryFindProp.footerFilename) is not "">
150:     <input type="checkbox" name="edtDeleteFooter">Delete Image?
151:   </cfif>
152: </cfif>
153: </td> - ->
154: </tr>
155: <tr bgcolor="eeeeee">
156:   <td width="20%">Available Dates:</td>
157:   <td>From <input type="TEXT" size="10" name="edtStartDate" value="#DateFormat(qryFindProp.startDate,"mm/dd/yyyy")#"> To
158:   <input type="TEXT" size="10" name="edtStopDate" VALUE="#dateformat(qryFindProp.stopDate,"mm/dd/yyyy")#"></td>
159: </tr>
160: <tr bgcolor="eeeeee">
161:   <td width="20%">Menu Title:</td>
162:   <td><input type="TEXT" size="20" name="edtMenuTitle" value="#qryFindProp.menuTitle#"></td>
163: </tr>
164: <tr bgcolor="eeeeee">
165:   <td width="20%">Menu Sort Order:</td>
166:   <td><input type="TEXT" size="2" name="edtSortOrder" value="#qryFindProp.sortOrder#"></td>
167: </tr>
168: <tr bgcolor="eeeeee">
169:   <td width="20%">Classified Property Type:</td>
170:   <td>
171:     <select name="edtPropertyType">
172:       <cfloop from="1" to="#listlen(lstPropType)#" index="nIndex">
173:         <cfset cValue=listGetAt(lstPropValues,nIndex)>
174:         <option value="#cValue#"><cfif cValue is qryFindProp.propertyType> selected</cfif>>#listGetAt(lstPropType,nIndex)#
175:       </cfloop>
176:     </select>
177:   </td>
178: </tr>
179: <tr bgcolor="eeeeee">
180:   <td width="20%">Classified Region:</td>
181:   <td>
182:     <select name="edtRegionType">
183:       <cfloop from="1" to="#listlen(lstRegions)#" index="nIndex">
184:         <cfset cValue=listGetAt(lstRegionValues,nIndex)>
185:         <option value="#cValue#"><cfif cValue is qryFindProp.regionType> selected</cfif>>#listGetAt(lstRegions,nIndex)#
186:       </cfloop>
187:     </select>
188:   </td>
189: </tr>
190: <tr bgcolor="eeeeee">
191:   <td width="20%">Search Property Type:</td>
192:   <td>
193:

```

```

194: <td>
195:   <select name="edtSearchPropertyType">
196:     <option value="0"><cfif qryFindProp.searchPropType is "0"> selected</cfif>>-None-
197:     <cfloop from="1" to="#listlen(listSearchPropType)#" index="nIndex">
198:       <cfset cValue=listGetAt(listPropTypeValues,nIndex)>
199:       <option value="#cValue#"><cfif cValue is qryFindProp.searchPropType>
selected</cfif>>#listGetAt(listSearchPropType,nIndex)#
200:     </cfloop>
201:   </select>
202: </td>
203: </tr>
204:
205:
206:
207: <!-- <tr bgcolor="eeeeee">
208:   <td width="20%">Primary Picture:</td>
209:   <td>
210:     <input type="FILE" name="edtPrimaryPic">
211:     <cfif qryFindProp.recordCount gt 0>
212:       <em>Current: #getFileFromPath(qryFindProp.primaryPic) </em>
213:       <cfif trim(qryFindProp.primaryPic) is not "">
214:         <input type="checkbox" name="edtDeletePrimary">Delete Image?
215:       </cfif>
216:     </td>
217:   </tr>
218:
219:   <tr bgcolor="eeeeee">
220:     <td width="20%">Description:</td>
221:     <td>
222:       <textarea name="edtDesc" rows="5" cols="80" wrap="virtual">#HTMLEditFormat(qryFindProp.Description)#</textarea>
223:     </td>
224:   </tr>
225:
226:   <tr bgcolor="eeeeee">
227:     <td colspan="2">
228:       <cfif qryFindProp.recordCount is 0>
229:         <input type="submit" name="btnUpdate" value="Add Page Info">
230:         <input type="reset" value="Reset Info">
231:       <cfelse>
232:         <input type="submit" name="btnUpdate" value="Update Page Info">
233:         <input type="reset" value="Reset Info">
234:         <cfquery name="qryIntegrity" datasource="#SourceName#">
235:           select * from prop_main
236:           where '#nPropTypeID#' in (prop_main.findPropType)
237:         </cfquery>
238:         <cfif qryIntegrity.recordCount gt 0>
239:           <input type="submit" name="btnDelete" value="Show Attached Props">
240:           <cfelse>
241:             <input type="submit" name="btnDelete" value="Delete Specialty Page">

```

```

242:         </cfif>
243:
244:         </cfif>
245:     </td>
246: </tr>
247: </FORM>
248:
249: </table>
250: </p>
251:
252:
253:
254: <!-- Here is the paragraph information already entered -->
255:
256: <cfif qryFindProp.recordcount gt 0>
257: <p><table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
258: <!-- First see if there are any images to display -->
259: <cfif #qryParameters.recordcount# is 0>
260: <tr bgcolor="cccccc">
261: <td><b class="h2">No paragraphs are associated with this property type</b></td>
262: </td></tr>
263: <cfelse>
264: <!-- there are paragraphs, so display the labels first -->
265: <tr bgcolor="cccccc">
266: <cfloop from="1" TO="#listlen(listLabels)#" index="nIndex">
267: <td align="center"><b>#listGetAt(listLabels, nIndex)#</b></td>
268: </cfloop>
269: <td><b></td></tr>
270: </cfif>
271:
272: <!-- Now for the actual data -->
273: <CFSET leditrow = False>
274: <CFSET cimageName = "">
275: <CFSET nRow = 0>
276: <CFSET nOldParamCounter = -1>
277: <CFSET nParamCounter = -1>
278: <CFSET nMaxParamCounter = -1>
279: <CFSET nColumn = 0>
280:
281: <CFLOOP QUERY="qryParameters">
282: <CFSET nRow = nRow + 1>
283: <CFIF qryParameters.param_name IS listGetAt(listFieldNames, 1)>
284: <CFSET nColumn = 0>
285: <CFSET nMaxParamCounter = max(nMaxParamCounter, qryParameters.param_cntr)>
286: <CFSET nParamCounter = qryParameters.param_cntr>
287: <CFIF nParamCounter is URL.param_counter>
288: <CFSET leditrow = TRUE>
289: <CFELSE>
290: <CFSET leditrow = FALSE>

```

```

291:      </CFIF>
292:      <tr bgcolor="eeeeee">
293:      </CFIF>
294:      <CFSET nColumn = nColumn + 1>
295:      <CFIF leditrow>
296:      <CFSET aFieldValues[nColumn] = qryParameters.param_value>
297:      </CFIF>
298:      <CFIF listGetAt(listFieldNames,nColumn) is "imgType">
299:      <td <CFIF leditrow IS true>bgcolor="ffffff"</CFIF> valign="top">
300:      <CFIF qryParameters.param_value is "0">
301:      Standard Photo
302:      <CFIF leditrow is true><CFSET URL.ImageType = "0"></CFIF>
303:      <CFELSEIF qryParameters.param_value is "1">
304:      Bamboo Image
305:      <CFIF leditrow is true><CFSET URL.ImageType = "1"></CFIF>
306:      <CFELSEIF qryParameters.param_value is "2">
307:      IPIX Image
308:      <CFIF leditrow is true><CFSET URL.ImageType = "2"></CFIF>
309:      <CFELSE>
310:      #qryParameters.param_value#
311:      <CFIF leditrow is true><CFSET URL.ImageType = "-1"></CFIF>
312:      </CFIF>
313:      </td>
314:      <CFELSE>
315:      <td <CFIF leditrow IS true>bgcolor="ffffff"</CFIF> valign="top">#HTMLEditFormat(qryParameters.param_value)#</td>
316:      </CFIF>
317:
318:      <CFIF nColumn is nTotalCols-2> <!-- the last column with info was displayed -->
319:      <td <CFIF leditrow is true>bgcolor="ffffff"</CFIF> colspan="2" valign="top">
320:      <a
321:      href="propTypeMaint.cfm?Action=Edit&PropTypeID=#URL.PropTypeID&param_counter=#qryParameters.param_cntr#">Edit</a><br>
322:      href="propTypeDataUpdate.cfm?Action=Delete&PropTypeID=#URL.PropTypeID&param_counter=#qryParameters.param_cntr#">Delete</a><
323:      /td>
324:      </td>
325:      <CFSET nColumn = 0>
326:      </CFIF>
327:      </CFLOOP>
328:      </table></p>
329:
330:
331:      <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
332:      <!-- Now allow the user to add or edit an image -->
333:      <tr bgcolor="cccccc">
334:      <td colspan="#nTotalCols#">
335:      <CFIF #URL.Action# is "Add">
336:      <b>Add A Paragraph</b>:

```

```

337: <input type="hidden" name="Action" VALUE="Add">
338: <CFELSEIF #URL.Action# is "Edit">
339: <b>Edit Selected Paragraph:</b>
340: <input type="hidden" name="Action" VALUE="Edit">
341: <CFELSEIF #URL.Action# is "View">
342: <b>Add A Paragraph:</b>
343: <input type="hidden" name="Action" VALUE="Add">
344: </CFIF>
345: </td>
346: </tr>
347:
348:
349: <tr>
350: <td colspan="2">
351: <td colspan="2">
352: <cfif findNoCase("Text", #listGetAt(listLabels, nIndex)#) neq 0>
353: <cfset labelId = #nIndex#>
354: <cfelse>
355: <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, nIndex)#</b></font>
356: </cfif>
357: </td>
358: </CFLOOP>
359: </tr>
360:
361: <form name="frmValues" enctype="multipart/form-data" action="propTypeDataUpdate.cfm" method="post">
362: <tr valign="top" bgcolor="eeeeee">
363: <td colspan="2">
364: <CFSET cFieldType = ucase(trim(listGetAt(listFieldTypes, nIndex)))>
365: <CFIF cFieldType is "TEXT">
366: <CFIF listGetAt(listFieldNames, nIndex) is "imgType">
367: <td>
368: <CFIF #URL.Action# is "Edit">
369: <CFIF aFieldValues[nIndex] is "0">
370: <I>Standard Photo</I><br>
371: <CFELSEIF aFieldValues[nIndex] is "1">
372: <I>Bamboo Image</I><br>
373: <CFELSEIF aFieldValues[nIndex] is "2">
374: <I>PIX Image</I><br>
375: <CFELSE>
376: <I>#aFieldValues[nIndex]#</I><br>
377: </CFIF>
378: </td>
379: <td colspan="2">
380: <CFLOOP QUERY="qryImageTypes">
381: <CFIF URL.ImageType is "0" and qryImageTypes.value is "0">
382: <CFSET lShowOption = true>
383: <CFELSEIF URL.ImageType is not "0" and qryImageTypes.value is not "0">
384: <CFSET lShowOption = true>
385: <CFELSE>

```

```

386:         <CFSET lShowOption = False>
387:     </CFIF>
388:     <CFIF lShowOption is true>
389:         <OPTION value=#qryImageTypes.value# <CFIF #trim(aFieldValues[nIndex])# is
#trim(qryImageTypes.value)#>SELECTED</CFIF>>#trim(label)#</OPTION>
390:     </CFIF>
391:     </CFLOOP>
392: </SELECT>
393: <br>
394: <CFIF URL.Action is not "Edit">
395:     <!-- If they want to change the image type, they will need to delete the image and reenter it -->
396:     <CFIF URL.ImageType is "0">
397:         <font face="Verdana, Arial" size="1"><a
href="propTypeMaint.cfm?Action=#URL.Action#&PropTypeID=#URL.PropTypeID#&ImageType=1&param_counter=URL.param_counter#">To
Add Bamboo or IPIX<br>images, Click Here</a></font>
<CFELSE>
398:         <font face="Verdana, Arial" size="1"><a
href="propTypeMaint.cfm?Action=#URL.Action#&PropTypeID=#URL.PropTypeID#&ImageType=0&param_counter=URL.param_counter#">To
Add a standard photo, Click Here</a></font>
399:     </CFIF>
400: </CFIF>
401: </td>
402: </td>
403: <CFELSE>
404:     <td>
405:         <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
406:     </td>
407: </CFIF>
408: <CFELSEIF cFieldType is "FILE">
409:     <td>
410:         <CFIF #URL.Action# is "Edit">
411:             <CFIF URL.ImageType is "0">
412:                 <i>#getFileFromPath(aFieldValues[nIndex])#</i><br>
413:             <CFELSE>
414:                 #aFieldValues[nIndex]#<br>
415:             </CFIF>
416:         </CFIF>
417:         <CFIF URL.ImageType is "0">
418:             <INPUT TYPE="FILE" NAME="Field#nIndex#" SIZE="20">
419:         <CFELSE>
420:             <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
421:         </CFIF>
422:     </td>
423: <CFELSEIF cFieldType is "TEXTAREA">
424:     <td>
425:         <!-- Moved the text area to a row immediately under the other input data --SPF 0404800-->
426:         <cfset textid = #nIndex#>
427:     </td>
428:     <CFELSEIF cFieldType is "CHECKBOX">
429:     <td ALIGN="CENTER">

```



```

430: <INPUT TYPE="CHECKBOX" NAME="Field#nindex#w" SIZE="70" <CFIF #aFieldValues[nindex]# is "ON">CHECKED</CFIF>>
431: </td>
432: <CFELSEIF cFieldType is "SELECT">
433: <td>
434: <CFSET listColOptions = replace(ListGetAt(listFieldOptions, nindex, "|"), "", "All")>
435: <CFIF listlen(listColOptions) gt 0>
436: <SELECT NAME="Field#nindex#">
437: <CFLOOP FROM="1" TO="#listlen(listColOptions)" INDEX="nListInd">
438: <CFSET cOption = listGetAt(listColOptions, nListInd, ", ")>
439: <OPTION <CFIF #aFieldValues[nindex]# is #cOption#>SELECTED</CFIF>>#cOption#
440: </CFLOOP>
441: </SELECT>
442: </CFIF>
443: </td>
444: </CFIF>
445: </CFLOOP>
446: </tr>
447: <tr valign="top" bgcolor="eeeeee">
448: <!-- Moved the text area to a row immediately under the other input data --SPE 0402800-->
449: <td colspan=#listlen(listLabels)#>
450: <cfif isDefined("textid")>
451: <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, labelId)#</b></font><br>
452: <TEXTAREA ROWS="8" COLS="80" WRAP="VIRTUAL" NAME="Field#textid">#HTMLEditFormat(aFieldValues[textid])#</TEXTAREA>
453: </cfif>
454: </td>
455: </tr>
456: <tr bgcolor="eeeeee">
457: <td colspan=#nTotalCols#>
458: <CFIF nMaxParamCounter is -1>
459: <CFSET nMaxParamCounter = 1>
460: <CFELSE>
461: <CFSET nMaxParamCounter = nMaxParamCounter + 1>
462: </CFIF>
463: <CFIF #URL.Action# is "View">
464: <input type="hidden" name="Action" VALUE="ADD">
465: <INPUT TYPE="SUBMIT" VALUE="Add New Paragraph" NAME="btnSubmit">
466:
467: <input type="hidden" name="param_counter" VALUE="#nMaxParamCounter#">
468: <CFELSEIF #URL.Action# is "Edit">
469: <input type="hidden" name="Action" VALUE="EDIT">
470: <INPUT TYPE="SUBMIT" VALUE="Update Paragraph">
471: <INPUT TYPE="RESET" VALUE="Reset Information">
472: <INPUT TYPE="BUTTON" VALUE="Cancel" NAME="btnSubmit">
473: ONCLICK="location.href='propTypeMaint.cfm?PropTypeID=#URL.PropTypeID#&Action=View'">
474: <input type="hidden" name="param_counter" VALUE="#URL.Param_Counter#">
475: </CFIF>
476: </td>
477: </tr>

```

```
478: <CFSET nImageTypeField = listFindNoCase(listFieldNames, "imgType")>
479:
480: <input type="hidden" name="imageField" VALUE="#nImageTypeField#">
481: <input type="hidden" name="PropTypeID" VALUE="#URL.PropTypeID#">
482: <input type="hidden" name="FieldLabels" VALUE="#listLabels#">
483: <input type="hidden" name="FieldTypes" VALUE="#listFieldTypes#">
484: <input type="hidden" name="Field_Names" VALUE="#listFieldNames#">
485: </form>
486: </table></p>
487:
488: </cfif>
489: </cfoutput>
490:
491: </body>
492: </html>
```

-----  
 4.0 Transitional/EN

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN"
2:
3: <CFPARAM NAME="URL.PropTypeID" DEFAULT="-1">
4:
5: <CFSET nPropTypeID = URL.PropTypeID>
6:
7: <html>
8: <head>
9:   <title>Update Property Type Information</title>
10: </head>
11:
12:
13: <body>
14:
15: <CFIF isDefined("FORM.btnUpdate")>
16:   <CFQUERY NAME="qryFindProp" DATASOURCE="#SourceName#">
17:     SELECT * FROM PropTypes
18:     WHERE PropTypeID=#nPropTypeID#
19:   </CFQUERY>
20:
21:   <CFIF qryFindProp.recordCount is 0>   <!-- This is a new property type -->
22:     <CFSET nPropTypeID=-1>
23:     <CFTRANSACTION>
24:       <CFSET cDesc = trim(preservesingleQuotes(FORM.edtDesc))>
25:       <CFPARAM NAME="FORM.edtMenuTitle" DEFAULT="">
26:       <CFSET cMenuTitle = trim(preservesingleQuotes(FORM.edtMenuTitle))>
27:
28:       <CFIF len(trim(FORM.edtStartDate)) is 0>
29:         <CFSET cStartDate = now()>
30:       </cfif>
31:       <cftry>
32:         <cfset cStartDate = createODBCDate(FORM.edtStartDate)>
33:         <cfcatch type="any">
34:           <cfset cStartDate = now()>
35:         </cfcatch>
36:       </cftry>
37:     </cfif>
38:
39:     <CFIF len(trim(FORM.edtStopDate)) is 0>
40:       <CFSET cStopDate = createODBCDate(2999,12,31)>
41:     </cfif>
42:     <cftry>
43:       <cfset cStopDate = createODBCDate(FORM.edtStopDate)>
44:       <cfcatch type="any">
45:         <cfset cStopDate = createODBCDate(2999,12,31)>
46:       </cfcatch>
47:     </cftry>
48:   </cfif>
49:

```

```

50: <cfif not isNumeric(form.edtSortOrder)>
51:   <cfset form.edtSortOrder = 0>
52: </cfif>
53:
54: <CFQUERY NAME="qryAddProp" DATASOURCE="#SourceName#">
55:   INSERT INTO PropTypes(Name, Description, StartDate, StopDate, MenuTitle, propertyType, regionType,
56:     distributorID,sortOrder, searchPropertyType)
57:     VALUES ('#FORM.edtPropName#', '#cDesc#', '#cStartDate#', '#cStopDate#', '#cMenuTitle#', #FORM.edtPropertyType#,
58:     #FORM.edtRegionType#, #ap_distributorID#, #FORM.edtSortOrder#, #FORM.edtSearchPropertyType#)
59: </CFQUERY>
60:
61: <CFQUERY NAME="qryGetID" DATASOURCE="#SourceName#">
62:   SELECT max(PropertyID) as newPropertyID
63:   FROM PropTypes
64: </CFQUERY>
65:
66: <CFSET nPropertyID = qryGetID.newPropertyID>
67: </CFTRANSACTION>
68: <CFIF nPropertyID is -1> <!-- Insertion failed -->
69: <CFELSE> <!-- Insertion successful -->
70:   <!-- Now create the directory and upload the files -->
71:
72:   <CFSET cFilePath = #ap_Property_path# & #nPropertyID# & "\">
73:
74:   <CFTRY> <!-- Create the directory and catch exception if directory already exists -->
75:     <CFDIRECTORY
76:       DIRECTORY="#cFilePath#"
77:       ACTION="CREATE"
78:     >
79:     <CFCATCH TYPE="ANY">
80:       </CFCATCH>
81:     </CFTRY>
82:
83:     <CFIF len(FORM.edtHeader) gt 0>
84:       <CFFILE
85:         DESTINATION="#cFilePath#
86:         ACTION="UPLOAD"
87:         NAMECONFLICT="OVERWRITE"
88:         FILEFIELD="edtHeader">
89:
90:       <CFSET cHeaderName = FILE.ServerFile>
91:     <CFELSE>
92:       <CFSET cHeaderName="">
93:     </CFIF>
94:
95:     <CFIF len(FORM.edtFooter) gt 0>
96:       <CFFILE

```

```

97:  DESTINATION=#cFilePath#
98:  ACTION="UPLOAD"
99:  NAMECONFLICT="OVERWRITE"
100:  FILEFIELD="edtFooter">
101:    <CFSET cFooterName = FILE.ServerFile>
102:  <CFELSE>
103:    <CFSET cFooterName = "">
104:  </CFIF>
105:
106:  <CFIF len(FORM.edtprimaryPic) gt 0>
107:    <CFFILE
108:      DESTINATION=#cFilePath#
109:      ACTION="UPLOAD"
110:      NAMECONFLICT="OVERWRITE"
111:      FILEFIELD="edtPrimaryPic">
112:    <CFSET cPrimaryPic = FILE.ServerFile>
113:  <CFELSE>
114:    <CFSET cPrimaryPic = "">
115:  </CFIF>
116:
117:  <cftransaction>
118:    <CFQUERY NAME="qryEditProp" DATASOURCE="#SourceName#">
119:      UPDATE PropTypes
120:      SET headerFileName=#cHeaderName#, footerFileName=#cFooterName#, primaryPic=#cPrimaryPic#,
121:        DataPath='\PropType\#nPropTypeID#'
122:      WHERE PropTypeID = #nPropTypeID#
123:    </cfquery>
124:  </cftransaction>
125:
126:  </CFIF>
127:  <CFLOCATION url="propTypeMaint.cfm?PropTypeID=#nPropTypeID#" addtoken="no">
128:
129:  <CFELSE> <!-- Editing an existing property type -->
130:
131:  <CFTRANSACTION>
132:    <CFSET cDesc = trim(preservesSingleQuotes(FORM.edtDesc))>
133:    <cfparam name="FORM.edtMenuTitle" default="">
134:    <cfset cMenuTitle = trim(preservesSingleQuotes(FORM.edtMenuTitle))>
135:
136:    <CFIF len(trim(FORM.edtStartDate)) is 0>
137:      <CFSET cStartDate = now()>
138:    <cfelse>
139:      <cftry>
140:        <cfset cStartDate = createODBCDate(FORM.edtStartDate)>
141:      <cfcatch type="any">
142:        <cfset cStartDate = now()>
143:      </cfcatch>
144:    </cftry>
145:  </cfif>

```

```

146:
147:
148:
149:
150:
151:
152:
153:
154:
155:
156:
157:
158:
159:
160:
161:
162:
163:
164:
165:
166:
167:
168:
169:
170:
171:
172:
173:
174:
175:
176:
177:
178:
179:
180:
181:
182:
183:
184:
185:
186:
187:
188:
189:
190:
191:
192:
193:
194:
<CFIF len(trim(FORM.edtStopDate)) is 0>
  <CFSET cStopDate = createDate(2999,12,31)>
</cfelse>
  <cftry>
    <cfset cstopDate = createODBCDate(FORM.edtStopDate)>
    <cfcatch type="any">
      <cfset cStopDate = createDate(2999,12,31)>
    </cfcatch>
  </cftry>
</cfif>

<cfif not isNumeric(form.edtSortOrder)>
  <cfset form.edtSortOrder = 0>
</cfif>

<CFQUERY NAME="qryEditProp" DATASOURCE="#SourceName#">
  UPDATE PropTypes
  SET Name='#FORM.edtPropName#',Description='#cDesc#',
    StartDate=#cStartDate#, StopDate=#cstopDate#, MenuTitle='#cMenuTitle#',
    propertyType=#form.edtPropertyType#,regionType=#form.edtRegionType#,
    sortOrder=#form.edtSortOrder#,
    searchPropertyType=#FORM.edtSearchPropertyType#
  WHERE PropTypeID = #nPropTypeID#
</cfquery>
</cftransaction>

<CFSET cFilePath = #ap_PropType_path# & #nPropTypeID# & "\">
<!-- The directory should already exist, but just in case... -->
<CFTRY <!-- Create the directory and catch exception if directory already exists. -->
</CFTRY>
<CFDIRECTORY
  DIRECTORY="#cFilePath#"
  ACTION="CREATE"
>
  <CFCATCH TYPE="ANY">
    </CFCATCH>
  </CFTRY>

<CFIF len(FORM.edtHeader) gt 0>
  <CFFILE
    DESTINATION=#cFilePath#
    ACTION="UPLOAD"
    NAMECONFLICT="OVERWRITE"
    FILEFIELD="edtHeader">
    <CFSET cHeaderName = FILE.ServerFile>
    <cfelseif isDefined("FORM.edtDeleteHeader")>
    <cfset cHeaderName="">
  </CFELSE>
    <CFSET cHeaderName=qryFindProp.headerFilename>

```

```

195: </CFIF>
196:
197: <CFIF len(FORM.edtFooter) gt 0>
198:   <CFIF
199:     DESTINATION=#cFilePath#
200:     ACTION="UPLOAD"
201:     NAMECONFLICT="OVERWRITE"
202:     FILEFIELD="edtFooter">
203:     <CFSET cFooterName = FILE.ServerFile>
204:     <cfelseif isDefined("FORM.edtDeleteFooter")>
205:     <cfset cFooterName = "">
206:   <CFELSE>
207:     <CFSET cFooterName = qryFindProp.footerFilename>
208:   </CFIF>
209:
210: <CFIF len(FORM.edtPrimaryPic) gt 0>
211:   <CFIF
212:     DESTINATION=#cFilePath#
213:     ACTION="UPLOAD"
214:     NAMECONFLICT="OVERWRITE"
215:     FILEFIELD="edtPrimaryPic">
216:     <CFSET cPrimaryPic = FILE.ServerFile>
217:     <cfelseif isDefined("FORM.edtDeletePrimary")>
218:     <cfset cPrimaryPic = "">
219:   <CFELSE>
220:     <CFSET cPrimaryPic = qryFindProp.primaryPic>
221:   </CFIF>
222:
223: <cftransaction>
224:   <CFQUERY NAME="qryEditProp" DATASOURCE="#SourceName#">
225:     UPDATE PropTypes
226:     SET headerFileName=#cHeaderName#, footerFileName=#cFooterName#, primaryPic=#cPrimaryPic#,
227:       DataPath='\PropType\#nPropTypeID#',
228:       WHERE PropTypeID = #nPropTypeID#
229:   </cfquery>
230: </cftransaction>
231:
232:   <CFLOCATION url="PropTypeMaint.cfm?PropTypeID=#nPropTypeID#" addtoken="no">
233: </CFIF>
234:
235: <CFELSEIF IsDefined("FORM.btnDelete")> <!-- Delete the selected property type -->
236:   <cfquery name="qryIntegrity" datasource="#SourceName#">
237:     select * from prop_main
238:     where
239:       '#nPropTypeID#' in (prop_main.findPropType)
240:   </cfquery>
241:
242:   <cfif qryIntegrity.recordcount gt 0>
243:     <cflocation url="propTypeAttached.cfm?propertyTypeID=#nPropTypeID#" addtoken="no">

```

```

244: </cfif>
245:
246: <cftransaction>
247:   <cfquery name="qryDeleteProp" datasource="#SourceName#">
248:     DELETE prop_type_param
249:     WHERE propTypeID=#nPropTypeID#
250:   </cfquery>
251:
252:   <cfquery name="qryDeleteProp" datasource="#SourceName#">
253:     DELETE PropTypes
254:     WHERE propTypeID=#nPropTypeID#
255:   </cfquery>
256: </cftransaction>
257:
258: <!-- First delete the directory files -->
259: <CFSET cfilePath = #ap_PropType_path# & #nPropTypeID# & "\">
260:
261: <CFDIRECTORY ACTION="LIST"
262:   DIRECTORY="#cfilePath#"
263:   NAME="qryDirList"
264: >
265:
266: <CFLOOP QUERY="qryDirList">
267:   <CFIF qryDirList.name IS NOT "." AND qryDirList.name IS NOT "..">
268:     <CFSET cfilename = cfilePath & qryDirList.name>
269:     <CFFILE ACTION="DELETE"
270:       FILE="#cfilename#"
271:     >
272:   </CFIF>
273: </CFLOOP>
274:
275: <!-- Now delete the whole directory -->
276: <CFSET cfilePath = #ap_PropType_path# & #nPropTypeID# & "\">
277:
278: <CFDIRECTORY ACTION="DELETE"
279:   DIRECTORY="#cfilePath#"
280: >
281:
282: <cflocation url="propTypeadm.cfm" addtoken="no">
283: </CFIF>
284:
285:
286: </body>
287: </html>

```



```
1:  <cfparam name="imageswap" default="#randrange(1, 4)#">
2:
3:  <cfif #imageswap# is "1">
```

```
4:
5:  <a href="#SearchForm.cfm"></a>
```

```
6:
7:  <cfelseif #imageswap# is "2">
```

```
8:
9:  <a href="#SearchForm.cfm"></a>
```

```
10:
11:  <cfelseif #imageswap# is "3">
```

```
12:
13:  <a href="#SearchForm.cfm"></a>
```

```
14:
15:  <cfelseif #imageswap# is "4">
```

```
16:
17:  <a href="#SearchForm.cfm"></a>
```


```
18:
19:  </cfif>
```

4.0 Transitional/EN

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML
2:
3: <html>
4: <head>
5:   <cfoutput>
6:   <title>#ap_backofficeName# Backoffice</title>
7:   </cfoutput>
8:   <link rel="stylesheet" href="style1.css" type="text/css">
9: </head>
10:
11: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
12:
13: <cfinclude template="header.cfm">
14:
15: <table align="center">
16:   <tr><th>Denver Post DPOHomes.com Reports</th></tr>
17:   <tr><td><a href="http://www.dpohomes.com/admin/reports/dailystats/daily.htm" target="new">30 Day Website
18:   Statistics</a></td></tr>
19:   <tr><td><a href="http://www.dpohomes.com/admin/reports/monthlystats/monthly.htm" target="new">12 Month Website
20:   Statistics</a></td></tr>
21: </table>
22: </body>
23: </html>
```

Transitional/EN

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN>
2:
3: <html>
4: <head>
5:   <title>Show Form Variables</title>
6: </head>
7:
8: <body>
9:   <CFSET keystostruct = StructKeyList(form,"<LI>")>
10:  <CFOUTPUT>#keystostruct#</CFOUTPUT><br><hr>
11:
12: </body>
13: </html>
```



```
1:
2:
3: <HTML>
4: <HEAD>
5:   <TITLE>CF Password Written By Fusion FX Software.</TITLE>
6: </HEAD>
7:
8: <BODY>
9:   <pre>
10: CF Password Written By Fusion FX.
11: CF Password is freeware.
12: No Support is offered, and no liability will be assumed
13: for breakage or misuse of this application by Fusion FX, Inc.
14: You have the source code here so plow into it and enjoy.
15:
16: Fusion FX, Inc.
17: 3333 Duck Ave.
18: Apt.# A208
19: Key West, Florida
20: 33040
21:
22: email: info@fusionfx.com
23: See all of our Cold Fusion Applications at:
24: <a href="http://www.cfapplication.com">http://www.cfapplication.com</a>
25: -----
26: Installing CF Password
27: -----
28: 1. Unzip all of the files in to your web site root directory.
29: 2. Add a data-source called "FXassword" for the FXPassword.mdb database file.
30:   (you may locate this database on your server any place you choose.)
31: 3. Create a special folder for all of the files you intend to protect and place those files in that dir.
32: 4. Paste the form "FusionFX.cfm" file into any file you choose to make as your login page, or
33:   You may keep the ahp.cfm page as your login page if you so choose.
34:   !!!The Login page CANNOT be located inside the Directory of files you intend to password protect!!!
35: 5. Place the authenticate.cfm file in the same directory as your Login page.
36:   !!!The authenticate.cfm page CANNOT be located inside the Directory of files you intend to password protect!!!
37: 6. There are 2 ways you may implement CF Password to protect the files in your special directory.
38:   A. Place the file application.cfm inside the special dir.
39:   This will execute before any other file is called.
40:   This FORCES protection on all of the files inside the special dir.
41:   If you choose option B, (below) make sure you rename the application.cfm file
42:   or it will affect all of the pages that are in the same dir it is in.
43:   B. Save the application file as something else (i.e. yourfilename.cfm).
44:   After doing this add a cfinclude tag, <font color="Red">&lt;cfinclude template="yourfilename.cfm"&gt;&lt;/font>
45:   on the top of all the files you want to add protection to.
46: 7. You now need to add the user names, passwords and the name of the directory to be protected
47:   and the first page you want the User to see after login. Do this by pressing the button at the bottom of the start.htm
48:   page.
```

66: &lt;/HTML&gt;

<!--W3C//DTD HTML 4.0 Transitional//EN-->

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfinclude template="include\security.cfm">
4:
5: <html>
6: <head>
7:   <cfoutput>
8:     <title>#ap_backofficeName# Backoffice</title>
9:   </cfoutput>
10:   <link rel="stylesheet" href="style1.css" type="text/css">
11: </head>
12:
13: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
14:
15:   <cfinclude template="header.cfm">
16:   <cfinclude template="../../../common/listMTDStats.cfm">
17: </body>
18: </html>
```

```
1: .h2 { font-family: verdana, arial, helvetica,sans-serif; font-size: 12pt; }
2: .h1 { font-family: verdana, arial, helvetica,sans-serif; font-size: 14pt; }
3: a { font-family: verdana, arial, helvetica,sans-serif; text-decoration: none; color:#003399; }
4: b.internet {font-family: verdana, arial, helvetica,sans-serif; font-size: 10pt; }
5: a.internet { font-family: verdana, arial, helvetica,sans-serif; color: #006600; text-decoration: none; font-size: 9pt; }
6: a: hover { text-decoration: underline; font-family: verdana, arial, helvetica,sans-serif; color:#ff3333; }
7: p, body, th, ul, td { font-family: verdana, arial, helvetica,sans-serif; font-size: 10pt; }
```

```
1: <p align="center"></p>
2:
3: <table border="0" width="750" align="center" bgcolor="#ffffff" cellpadding="0" cellspacing="0">
4:   <tr><td width="13" height="13" valign="top"></td>
5:     <td>&nbsp;</td>
6:     <td width="13" height="13" valign="top"></td>
7:   </tr>
8:   <tr><td>&nbsp;</td>
```



type="text/css" href="style1.css" type="text/css">

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfquery name="qURL" datasource="#sourceName#">
4:   SELECT URL
5:   FROM link
6:   WHERE agency_id = #ap_agency_number#
7:   AND linkId = #URL.linkId#
8:   AND linkType = 'L'
9: </cfquery>
10:
11: <html>
12: <head>
13:   <cfoutput>
14:     <title>#ap_backofficeName# Backoffice</title>
15:   </cfoutput>
16:   <link rel="stylesheet" href="style1.css" type="text/css">
17: </head>
18:
19: <body bgcolor="#ffffff">
20:   <cfoutput query="qURL">
21:     <p class="h2">#URL#</font></p>
22:     <p><a href="#URL#">Go there.</a></p>
23:   </cfoutput>
24:
25:
26: </body>
27: </html>
```

```

1:
2:
3:
4:
5:
6:
7:
8:
9:
10:
11:
12:
13:
14:
15:
16:
17:
18:
19:
20:
21:
22:
23:
24:
25:
26:
27:
28:
29:
30:
31:
32:
33:
34:
35:
36:
37:
38:
39:
40:
41:
42:
43:
44:
45:
46:
47:
48:
49:

<!DOCTYPE HTML PUBLIC "-//W3C//Dtd HTML 3.2 Final//EN">

<HTML>
<BODY bgcolor="white">

<!-- Run Query to get values if in edit mode -->
<cfif IsDefined("URL.userID")>
  <cfquery
    datasource="realestate"
    name="getExistingValues">
    SELECT *
    FROM Users
    WHERE secureUserID = #URL.userID#
  </cfquery>

  <b>Editing User Info for <cfoutput>#getExistingValues.firstName# #getExistingValues.lastName#</cfoutput></b>

  <!-- Put query variables in local variables -->
  <cfset userName = "#getExistingValues.userName#">
  <cfset userPassword = "#getExistingValues.userPassword#">
  <cfset firstName = "#getExistingValues.firstName#">
  <cfset lastName = "#getExistingValues.lastName#">
  <cfset userRepresents = "#getExistingValues.userRepresents#">
  <cfset userLevel = "#getExistingValues.userLevel#">
  <cfset userStatus = "#getExistingValues.userStatus#">
  <cfelse>

  <!-- Initialize variables to empty string -->
  <b>Adding a User</b>
  <cfset userName = "">
  <cfset userPassword = "">
  <cfset firstName = "">
  <cfset lastName = "">
  <cfset userRepresents = "">
  <cfset userLevel = "User">
  <cfset userStatus = "act">
  </cfif>

  <!-- Create form for data entry. -->
  <form
    action="doUserEntry.cfm"
    method="post">
    <cfoutput>
    <!-- Add hidden field to pass primary key if editing an existing entry -->
    <cfif IsDefined("url.userID")>
      <input
        type="hidden"
        name="secureUserID"
        value="#url.userID#">
    </cfif>

```

```
50: <table
51:   border="0"
52:   cellpadding="4"
53:   align="left">
54: <tr>
55:   <td align="right">
56:     <font face="Verdana,Arial,Helvetica,sans-serif"><b>Login Name</b></font>
57:   </td>
58:   <td>
59:     <input
60:       type="text"
61:       name="userName"
62:       size="20"
63:       value="#userName#">
64:     </td>
65:   </tr>
66: <tr>
67:   <td align="right">
68:     <font face="Verdana,Arial,Helvetica,sans-serif"><b>Password</b></font>
69:   </td>
70:   <td>
71:     <input
72:       type="password"
73:       name="userPassword"
74:       size="20"
75:       value="#userPassword#">
76:     </td>
77:   </tr>
78: <tr>
79:   <td align="right">
80:     <font face="Verdana,Arial,Helvetica,sans-serif"><b>First Name</b></font>
81:   </td>
82:   <td>
83:     <input
84:       type="text"
85:       size="20"
86:       name="firstName"
87:       value="#firstName#">
88:     </td>
89:   </tr>
90: <tr>
91:   <td align="right">
92:     <font face="Verdana,Arial,Helvetica,sans-serif"><b>Last Name</b></font>
93:   </td>
94:   <td>
95:     <input
96:       type="text"
97:       size="20"
98:       name="lastName">
```

[illegible]

```
<math display="block">\frac{1}{\sqrt{2\pi}} \int_{-\infty}^{\infty} \frac{e^{-\frac{1}{2}x^2}}{1+x^2} dx = \frac{\pi}{2}
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//Dtd HTML 3.2 Final//EN">
2:
3:
4: <!-- Get all users -->
5: <cfquery
6:   datasource="realestate"
7:   name="getUsers">
8:   SELECT *
9:   FROM Users
10:  ORDER BY Users.lastName
11: </cfquery>
12:
13: <HTML>
14: <BODY bgcolor="white">
15:
16: <a href="userEntry.cfm">
17:   <font face="Verdana,Arial,Helvetica,sans-serif">[Click to add new user]</font>
18: </a>
19: <p>
20:
21: <cfoutput query="getUsers">
22:   <a href="userEntry.cfm?userID=#secureUserID#">
23:     <font face="Verdana,Arial,Helvetica,sans-serif"> #lastName#, #firstName# </font>
24:   </a>
25:   <br>
26: </cfoutput>
27:
28: </BODY>
29: </HTML>
```

```
1: <!--  
2: var url="./index.cfm";  
3:  
4: function openpop(url)  
5: {  
6:   pop=window.open(url, "popup", "toolbar=yes, location=yes, directories=no, status=yes, menubar=yes, scrollbars=yes,  
7:   resizable=yes,width=640,height=480");  
8: }  
9: //--->  
10:
```

```
1: <cfparam name="URL.SortBy" Default="lastname,firstname">
2:
3: <cfquery name="qryAgents" datasource="#sourcename#">
4:   select agent_id, firstname, lastname, email, workphone, specialty from Agents
5:   where agents.agency_id=#nAgencyID#
6:   order by #URL.SortBy#
7: </cfquery>
8:
9: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
10:   <cfoutput>
11:     <tr bgcolor="#cccccc">
12:       <td><b>Sort by <a
13:         href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=lastname,firstname&displayPage=Agents">Name</a></b></td>
14:       <td><b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=workphone&displayPage=Agents">Work
15:         href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=specialty&displayPage=Agents">Specialty</a></b></td>
16:       <td><b>Phone</b></td>
17:     </tr>
18:   </cfoutput>
19:
20:   <cfoutput query="qryAgents">
21:     <CFQUERY NAME="qryFindBio" DATASOURCE="#SourceName#">
22:       SELECT callingID
23:       FROM adData
24:       WHERE adData.callingID=#qryAgents.agent_id#
25:       AND callingType=1
26:     </CFQUERY>
27:     <tr bgcolor="#IIf(CurrentRow Mod 2, DE('fffff'), DE('eeeeee'))#">
28:       <td>#firstname# #lastname#</td>
29:       <td>#workphone#</td>
30:       <td>#email#</td>
31:       <td>#specialty#</td>
32:       <td><a href="#agentForm.cfm?agent_id=#agent_id#&cReturnURL#">Edit</a> | <a
33:         href="agentdel.cfm?agent_id=#agent_id#&cReturnURL#">Delete</a><br>
34:         <CFIF qryFindBio.recordCount is 0>
35:           <a href="#OHTMaint.cfm?agent_id=#agent_id#&cReturnURL#">Create Enhanced Bio</a>
36:         <CFELSE>
37:           <a href="#OHTMaint.cfm?agent_id=#agent_id#&cReturnURL#">Edit Enhanced Bio</a>
38:         </CFIF>
39:       </td>
40:     </tr>
41:   </cfoutput>
42:   <cfif qryAgents.recordCount is 0>
43:     <td colspan="5" bgcolor="#eeeeee"><i>There are no agents assigned to this agency.</i></td>
44:   </cfif>
45: </table>
```



```
1: <cfoutput>
2: <!-- form enctype="multipart/form-data" action="agencyUpdate.cfm" method="post" -->
3: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
4: <tr>
5: <td colspan="2" align="center">
6: <input type="hidden" name="agency_id" value="#nAgencyID#">
7: <input type="hidden" name="edtDistributorID" value="#ap_distributorID#">
8: <input type="hidden" name="edtCountry" value="USA">
9: <tr bgcolor="#ffffff">
10: <td colspan="2" align="center">Agency Name:</td>
11: <td colspan="2" align="center"><input type="text" name="edtAgencyName" value="#qryFindAgency.name#" required="yes"
12: message="Please enter an agency name.">
13: <input type="hidden" name="edtAgencyName_required" value="Please enter an agency name.">
14: </td>
15: <td colspan="2" align="center">Phone:</td>
16: <td colspan="2" align="center"><input type="text" name="edtPhone" value="#qryFindAgency.phone#" required="yes"
17: message="Please enter a phone number in the format ###-###-#####" validate="telephone">
18: <input type="hidden" name="edtPhone_required" value="Please enter a phone number in the format
19: ###-###-#####">
20: </td>
21: <td colspan="2" align="center">Address:</td>
22: <td colspan="2" align="center"><input type="text" name="edtAddress" value="#qryFindAgency.address#" required="yes"
23: message="Please enter an address.">
24: <input type="hidden" name="edtAddress_required" value="Please enter an address.">
25: </td>
26: <td colspan="2" align="center">Web Site:</td>
27: <td colspan="2" align="center"><input type="text" name="edtURL" value="#qryFindAgency.URL_name#"></td>
28: </td>
29: <td colspan="2" align="center">City:</td>
30: <td colspan="2" align="center"><input type="text" name="edtCity" value="#qryFindAgency.city#" required="yes" message="Please
31: enter a city.">
32: <input type="hidden" name="edtCity_required" value="Please enter a city.">
33: </td>
34: <td colspan="2" align="center">E-Mail:</td>
35: <td colspan="2" align="center"><input type="text" name="edtEmail" value="#qryFindAgency.email#" required="yes"
36: message="Please enter an email address.">
37: <input type="hidden" name="edtEmail_required" value="Please enter an email address.">
38: </td>
39: <td colspan="2" align="center">State:</td>
40: <td colspan="2" align="center"><input type="text" name="edtState" value="#qryFindAgency.state#" maxlength="2" required="yes"
41: message="Please enter a state.">
42: <input type="hidden" name="edtState_required" value="Please enter a state.">
43: </td>
```

```
43: <td>Master Agency:</td>
44: <td>
45:   <select name="edtMasterAgency">
46:     <option value="0">--None--
47:     <cfloop query="qrySecurity">
48:       <cfif qrySecurity.entityTypeID is 4 and qrySecurity.entityID is not qryFindAgency.agency_id>
49:         <option value="#qrySecurity.entityID#"><cfif qryFindAgency.parentAgency is qrySecurity.entityID>
50:           selected</cfif>>#qrySecurity.name#
51:         </cfif>
52:       </cfloop>
53:     </select>
54:   </td>
55: <tr bgcolor="#ffffff">
56:   <td bgcolor="#ffffff">Zip Code:</td>
57:   <td bgcolor="#ffffff"><cfinput type="text" name="edtzipcode" value="#trim(qryFindAgency.zip)#" required="yes"
58:     message="Please enter a zip code. The format should be ##### or #####" validate="zipcode">
59:     #####</td>
60:   <td><b></td>
61:   <td><b></td>
62:   <!--<td>New Life:</td>
63:   <td><input type="text" name="edtNewLife" value="#qryFindAgency.newLife#"></td>
64:   <input type="hidden" name="edtNewLife" value="10">
65: </tr>
66:
67: <tr bgcolor="#ffffff">
68:   <td bgcolor="#ffffff">Fax:</td>
69:   <td bgcolor="#ffffff"><cfinput type="text" name="edtFax" value="#qryFindAgency.fax#" required="yes" message="Please
70:     enter a fax number in the format #####>
71:   <input type="hidden" name="edtFax_required" value="Please enter a fax number in the format #####>
72: </td>
73: <td><b></td>
74: <td><b></td>
75: <!--<td>Sold Life:</td>
76: <td><input type="text" name="edtSoldLife" value="#qryFindAgency.soldLife#"></td>
77: <input type="hidden" name="edtSoldLife" value="10">
78: </tr>
79:
80: <tr bgcolor="#ffffff">
81:   <td>Specialty:</td>
82:   <td><input type="text" name="edtSpecialty" value="#qryFindAgency.specialty#"></td>
83:   <td colspan="2"><b></td>
84: </tr>
85:
86: <tr bgcolor="#ffffff">
87:   <td>Main Image:</td>
88:   <td><input type="file" name="edtmainImage"></td>
```

```

88: <td colspan="2" align="left">
89: <cfif qryFindAgency.mainImage is "">&nbsp;
90: <cfelse>
91: <cfset cCurrentImage = getFileFromPath(qryFindAgency.mainImage)>
92: <cfset nAt = findNoCase("-", cCurrentImage)>
93: <cfif nAt gt 0>
94: <cfset cCurrentImage = mid(cCurrentImage, nAt+1, len(cCurrentImage)-nAt)>
95: </cfif>
96: <em>Currently: #cCurrentImage#</em>
97: <input type="checkbox" name="edtDeleteMainImage">Remove Image?
98: </cfif>
99: </td>
100: </tr>
101: <tr bgcolor="#####">
102: <td>Header Image:</td>
103: <td><input type="file" name="edtheaderfilename"></td>
104: <td colspan="2" align="left">
105: <cfif qryFindAgency.headerfilename is "">&nbsp;
106: <cfelse>
107: <cfset cCurrentImage = getFileFromPath(qryFindAgency.headerfilename)>
108: <cfset nAt = findNoCase("-", cCurrentImage)>
109: <cfif nAt gt 0>
110: <cfset cCurrentImage = mid(cCurrentImage, nAt+1, len(cCurrentImage)-nAt)>
111: </cfif>
112: <em>Currently: #cCurrentImage#</em>
113: <input type="checkbox" name="edtDeleteHeaderFilename">Remove Image?
114: </cfif>
115: </td>
116: </tr>
117: <tr bgcolor="#####">
118: <td>Footer Image:</td>
119: <td><input type="file" name="edtfooterfilename"></td>
120: <td colspan="2" align="left">
121: <cfif qryFindAgency.footerfilename is "">&nbsp;
122: <cfelse>
123: <cfset cCurrentImage = getFileFromPath(qryFindAgency.footerfilename)>
124: <cfset nAt = findNoCase("-", cCurrentImage)>
125: <cfif nAt gt 0>
126: <cfset cCurrentImage = mid(cCurrentImage, nAt+1, len(cCurrentImage)-nAt)>
127: </cfif>
128: <em>Currently: #cCurrentImage#</em>
129: <input type="checkbox" name="edtDeleteFooterFilename">Remove Image?
130: </cfif>
131: </td>
132: </tr>
133:
134: <tr bgcolor="#####">
135: <td valign="top" bgcolor="#####">Description:<br><font color="red">This field will not be displayed if an Enhanced
Agency Profile is used.</td>

```

```
136: <td colspan="3" bgcolor="##eeeeee">
137: <textarea name="edtDesc" rows="5" cols="70" wrap="virtual">#qryFindAgency.Description#</textarea>
138: </td>
139: </tr>
140:
141: <tr bgcolor="##ffffff"><td colspan="4">&nbsp;</td></tr>
142:
143: <tr bgcolor="##cccc99">
144: <td colspan="4">
145: <cfif qryFindAgency.recordCount is 0>
146: <input type="submit" name="btnUpdate" value="Add Agency">
147: <input type="reset" value="Reset Info">
148: <cfelse>
149: <input type="submit" name="btnUpdate" value="Update Agency">
150: <input type="reset" value="Reset Info">
151: <input type="submit" name="btnDelete" value="Delete Agency">
152: </cfif>
153: </td>
154: </tr>
155: </cfif>
156: </table>
157: </cfoutput>
```

```
1: <cfoutput>
2: <!--- <form enctype="multipart/form-data" action="agencyUpdate.cfm" method="post"> --->
3: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
4: <cfform action="agencyUpdate.cfm">
5: <input type="hidden" name="agency_id" value="#nAgencyID#">
6: <input type="hidden" name="edtDistributorID" value="#ap_distributorID#">
7: <input type="hidden" name="edtCountry" value="USA">
8:
9: <tr bgcolor="##ffffff">
10: <td bgcolor="##eeeeee">Agency Name:</td>
11: <td bgcolor="##eeeeee"><cfinput type="text" name="edtAgencyName" value="#qryFindAgency.name#" required="yes"
    message="Please enter an Agency Name"></td>
12: <td>Phone:</td>
13: <td><input type="text" name="edtPhone" value="#qryFindAgency.phone#"></td>
14: </tr>
15:
16: <tr bgcolor="##ffffff">
17: <td bgcolor="##eeeeee">Address:</td>
18: <td bgcolor="##eeeeee"><input type="text" name="edtAddress" value="#qryFindAgency.address#"></td>
19: <td>Web Site:</td>
20: <td><input type="text" name="edtURL" value="#qryFindAgency.URL_name#"></td>
21: </tr>
22: <tr bgcolor="##ffffff">
23: <td bgcolor="##eeeeee">City:</td>
24: <td bgcolor="##eeeeee"><input type="text" name="edtCity" value="#qryFindAgency.city#"></td>
25: <td bgcolor="##eeeeee">E-Mail:</td>
26: <td bgcolor="##eeeeee"><input type="text" name="edtEmail" value="#qryFindAgency.email#"></td>
27: </tr>
28: <tr bgcolor="##ffffff">
29: <td bgcolor="##eeeeee">State:</td>
30: <td bgcolor="##eeeeee"><input type="text" name="edtState" value="#qryFindAgency.state#" maxlength="2"></td>
31: <td>Master Agency:</td>
32: <td>
    <select name="edtMasterAgency">
      <option value="0">--None--
      <cfloop query="qrySecurity">
        <cfif qrySecurity.entityType is 4 and qrySecurity.entityID is not qryFindAgency.agency_id>
          <option value="#qrySecurity.entityID#"><cfif qryFindAgency.parentAgency is qrySecurity.entityID>
            selected</cfif>#qrySecurity.name#
          </cfif>
        </cfloop>
      </select>
    </td>
33: </tr>
34: <tr bgcolor="##ffffff">
35: <td bgcolor="##eeeeee">Zip Code:</td>
36: <td bgcolor="##eeeeee"><input type="text" name="edtzipcode" value="#qryFindAgency.zip#"></td>
37: <td>&nbsp;</td>
38: <td>&nbsp;</td>
39: </tr>
40: </table>
41: </cfoutput>
42:
43: <tr bgcolor="##ffffff">
44: <td bgcolor="##eeeeee">Zip Code:</td>
45: <td bgcolor="##eeeeee"><input type="text" name="edtzipcode" value="#qryFindAgency.zip#"></td>
46: <td>&nbsp;</td>
47: <td>&nbsp;</td>
```

```
48: <!-- <td>New Life:</td>
49: <td><input type="text" name="edtNewLife" value="edtNewLife" value="#qryFindAgency.newLife#"></td> -->
50: <input type="hidden" name="edtNewLife" value="10">
51: </tr>
52:
53: <tr bgcolor="##ffffff">
54:   <td>Fax:</td>
55:   <td><input type="text" name="edtFax" value="#qryFindAgency.fax#"></td>
56:   <td>&nbsp;</td>
57:   <td>&nbsp;</td>
58:   <!-- <td>Sold Life:</td>
59:   <td><input type="text" name="edtSoldLife" value="#qryFindAgency.soldLife#"></td> -->
60:   <input type="hidden" name="edtSoldLife" value="10">
61: </tr>
62:
63: <tr bgcolor="##ffffff">
64:   <td>Specialty:</td>
65:   <td><input type="text" name="edtSpecialty" value="#qryFindAgency.specialty#"></td>
66:   <td colspan="2">&nbsp;</td>
67: </tr>
68:
69: <tr bgcolor="##ffffff">
70:   <td>Main Image:</td>
71:   <td><input type="file" name="edtMainImage"></td>
72:   <td colspan="2" align="left">
73:     <cfif qryFindAgency.mainImage is "">&nbsp;</cfif>
74:     <cfelse>
75:       <cfset cCurrentImage = getFileFromPath(qryFindAgency.mainImage)>
76:       <cfset nAt = findNoCase("-", cCurrentImage)>
77:       <cfif nAt gt 0>
78:         <cfset cCurrentImage = mid(cCurrentImage, nAt+1, len(cCurrentImage)-nAt)>
79:       </cfif>
80:       <em>Currently: #cCurrentImage#</em>
81:     </cfif>
82:   </td>
83: </tr>
84: <tr bgcolor="##ffffff">
85:   <td>Header Image:</td>
86:   <td><input type="file" name="edtHeaderfilename"></td>
87:   <td colspan="2" align="left">
88:     <cfif qryFindAgency.headerfilename is "">&nbsp;</cfif>
89:     <cfelse>
90:       <cfset cCurrentImage = getFileFromPath(qryFindAgency.headerfilename)>
91:       <cfset nAt = findNoCase("-", cCurrentImage)>
92:       <cfif nAt gt 0>
93:         <cfset cCurrentImage = mid(cCurrentImage, nAt+1, len(cCurrentImage)-nAt)>
94:       </cfif>
95:       <em>Currently: #cCurrentImage#</em>
96:     </cfif>
```

```
97:         </td>
98:     </tr>
99:     <tr bgcolor="#ffffff">
100:         <td>Footer Image:</td>
101:         <td><input type="file" name="edtfoterfilename"></td>
102:         <td colspan="2" align="left">
103:             <cfif qryFindAgency.footerfilename is "">&nbsp;
104:             <cfelse>
105:                 <cfset cCurrentImage = getFileFromPath(qryFindAgency.footerfilename)>
106:                 <cfset nAt = findNoCase("-", cCurrentImage)>
107:                 <cfif nAt gt 0>
108:                     <cfset cCurrentImage = mid(cCurrentImage, nAt+1, len(cCurrentImage)-nAt)>
109:                 </cfif>
110:                 <em>Currently: #cCurrentImage#</em>
111:             </cfif>
112:         </td>
113:     </tr>
114:
115:     <tr bgcolor="#ffffff">
116:         <td valign="top" bgcolor="#eeeeee">Description:</td>
117:         <td colspan="3" bgcolor="#eeeeee">
118:             <textarea name="edtDesc" rows="5" cols="70" wrap="virtual">#qryFindAgency.Description#</textarea>
119:         </td>
120:     </tr>
121:
122:     <tr bgcolor="#ffffff"><td colspan="4">&nbsp;
123:
124:     <tr bgcolor="#cccc99">
125:         <td colspan="4">
126:             <cfif qryFindAgency.recordCount is 0>
127:                 <input type="submit" name="btnUpdate" value="Add Agency">
128:                 <input type="reset" value="Reset Info">
129:             <cfelse>
130:                 <input type="submit" name="btnUpdate" value="Update Agency">
131:                 <input type="reset" value="Reset Info">
132:                 <input type="submit" name="btnDelete" value="Delete Agency">
133:             </cfif>
134:         </td>
135:     </tr>
136:     </cfform>
137: </table>
138: </cfoutput>
```

```
1: <cfparam name="URL.SortBy" Default="Name">
2:
3: <cfquery name="qryProperties" datasource="#sourcename#">
4: select prop_id, name, address, city, state, zip, price, status, mls_no, prop_type
5: from prop_main
6: where agency_id=#nAgencyID#
7: order by #URL.SortBy#
8: </cfquery>
9:
10:
11: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
12: <cfoutput>
13: <tr bgcolor="#cccccc">
14: <td valign="bottom" width="20%"><b>Sort by <a
15: href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=Name&displayPage=Properties">Name</a></b></td>
16: <td valign="bottom"><b>Sort by <a
17: href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=Address&displayPage=Properties">Address</a></b></td>
18: <td valign="bottom"><b>Sort by <a
19: href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=City&displayPage=Properties">City</a></b><br>
20: <b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=State&displayPage=Properties">State</a></b><br>
21: <b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=Zip&displayPage=Properties">Zip Code</a></b><br>
22: </td></td>
23: <td valign="bottom"><b>Sort by <a
24: href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=Price&displayPage=Properties">Price</a></b></td>
25: <td valign="bottom"><b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=mls_no&displayPage=Properties">MLS
26: ##</a></b></td>
27: <td><b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=City&displayPage=Properties">City</a></b><br>
28: <b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=State&displayPage=Properties">State</a></b><br>
29: <b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=Zip&displayPage=Properties">Zip Code</a></b><br>
30: </td></td>
31: <td><b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=Price&displayPage=Properties">Price</a></b><br>
32: <b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=mls_no&displayPage=Properties">MLS
33: ##</a></b></td>
34: <td><b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=City&displayPage=Properties">City</a></b><br>
35: <b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=State&displayPage=Properties">State</a></b><br>
36: <b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=Zip&displayPage=Properties">Zip Code</a></b><br>
37: </td></td>
38: <td><b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=Price&displayPage=Properties">Price</a></b><br>
39: <b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=mls_no&displayPage=Properties">MLS
40: ##</a></b></td>
41: <td><b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=City&displayPage=Properties">City</a></b><br>
42: <b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=State&displayPage=Properties">State</a></b><br>
43: <b>Sort by <a href="agencyMaint.cfm?agency_id=#nAgencyID#&SortBy=Zip&displayPage=Properties">Zip Code</a></b><br>
44: </td></td>
```



```
45:         <a href="OHTMaint.cfm?prop_id=#prop_id##cdReturnURL#">Edit OHT</a>
46:     </CFIF>
47: </td>
48: </tr>
49: </cfoutput>
50: <cfif qryProperties.recordCount is 0>
51:     <td colspan="6" bgcolor="#eeeeee"><i>There are no properties assigned to this agency.</i></td>
52: </cfif>
53: </table>
54:
```

```

1: <CFPARAM NAME="URL.TypeID" DEFAULT="1">
2: <CFPARAM NAME="URL.Action" DEFAULT="View">
3: <cfparam name="URL.param_counter" default="-1"> <!--- If editing, this will have a number --->
4: <cfparam name="URL.ImageType" default="0"> <!--- the image type --->
5:
6:
7:
8: <cfquery name="qryParameters" datasource="#sourceName#"
9:     SELECT agency_param.agency_id, agency_param.param_name, agency_param.param_value, agency_param.param_cntr,
10:         param_defs.description, param_defs.label, param_defs.displayOrder, param_defs.restrictions, param_defs.type
11:     FROM param_defs, agency_param
12:     WHERE agency_param.agency_id=#nTypeID#
13:     AND agency_param.param_id = param_defs.id
14:     ORDER BY agency_param.param_cntr,param_defs.displayOrder
15: </cfquery>
16:
17: <!--- Parameter names for the image fields --->
18: <cfquery name="qryParamNames" datasource="#sourceName#"
19:     SELECT
20:         DISTINCT id, name, description, label, displayOrder, restrictions, type, selectOptions
21:     FROM param_defs
22:     WHERE securityLevel=1
23:     AND dataGroup = 10 <!--- 10 = Agencies --->
24:     ORDER BY displayOrder
25: </cfquery>
26:
27: <!--- qryImageTypes will load the image types for the pull down while
28:     adding or editing a photo --->
29: <cfquery name="qryImageTypes" datasource="#sourceName#"
30:     SELECT label,counter,value,agency_id
31:     FROM param_allowed
32:     WHERE param_allowed.id = 9
33:     ORDER BY param_allowed.counter
34: </cfquery>
35:
36:
37: <!--- Delimited lists for various uses --->
38: <cfset listLabels = ValueList(qryParamNames.label)> <!--- "Use Name" --->
39: <cfset listFieldNames = ValueList(qryParamNames.name)> <!--- "ColumnName" --->
40: <cfset listFieldTypes = ValueList(qryParamNames.type)> <!--- TEXT, field, etc. --->
41: <cfset listFieldOptions = QuotedValueList(qryParamNames.selectOptions,"|")>
42:
43: <cfoutput>
44:
45: <CFSET nTotalCols = qryParamNames.recordCount+2>
46: <CFSET aFieldValues = ArrayNew(1)>
47:
48: <CFIF URL.Action is "View">
49:     <!--- Set default values for the edit fields --->

```

```

50: <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
51:   <CFSET aFieldValues[nIndex] = "">
52: </CFLOOP>
53:
54: <CFELSEIF URL.Action is "Add">
55:   <CFSET URL.Action = "View">
56: <CFELSEIF URL.Action is "Edit">
57:   <!-- A Paragraph has been selected for editing -->
58: <CFELSEIF URL.Action is "Deleted">
59:   <!-- Delete the selected image -->
60:   <!-- Set default values for the edit fields -->
61:   <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
62:     <CFSET aFieldValues[nIndex] = "">
63:   </CFLOOP>
64:
65:   <CFSET URL.Action = "View">
66: <CFELSEIF URL.Action is "Updated">
67:   <!-- Set default values for the edit fields -->
68:   <CFLOOP FROM="1" TO="#listLen(listLabels)#" INDEX="nIndex">
69:     <CFSET aFieldValues[nIndex] = "">
70:   </CFLOOP>
71:   <CFSET URL.Action = "View">
72: </CFIF>
73:
74:
75: <p><table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
76:   <!-- First see if there are any images to display -->
77:   <cfif #qryParameters.recordCount# is 0>
78:     <tr bgcolor="cccccc">
79:       <td><b class="n2">No paragraphs are associated with this agency</b></td>
80:     </td></tr>
81:   <cfelse>
82:     <!-- there are paragraphs, so display the labels first -->
83:     <tr bgcolor="cccccc">
84:       <cfloop from="1" TO="#listLen(listLabels)#" index="nIndex">
85:         <td align="center"><b>#listGetAt(listLabels, nIndex)#</b></td>
86:       </cfloop>
87:       <td colspan="2"><b><endbsp></td></tr>
88:     </cfif>
89:
90:     <!-- Now for the actual data -->
91:     <CFSET lEditrow = False>
92:     <CFSET cImageName = "">
93:     <CFSET nRow = 0>
94:     <CFSET nOldParamCounter = -1>
95:     <CFSET nParamCounter = -1>
96:     <CFSET nMaxParamCounter = -1>
97:     <CFSET nColumn = 0>
98:

```

```

99: <CFLOOP QUERY="qryParameters">
100:   <CFSET nRow = nRow + 1>
101:   <CFIF qryParameters.param_name IS listGetAt(listFieldNames, 1)>
102:     <CFSET nColumn = 0>
103:     <CFSET nMaxParamCounter = max(nMaxParamCounter, qryParameters.param_cntr)>
104:     <CFSET nParamCounter = qryParameters.param_cntr>
105:     <CFIF nParamCounter is URL.param_counter>
106:       <CFSET lEditrow = TRUE>
107:       <CFELSE>
108:         <CFSET lEditrow = FALSE>
109:         </CFIF>
110:         <tr bgcolor="eeeeee">
111:           </CFIF>
112:           <CFSET nColumn = nColumn + 1>
113:           <CFIF lEditrow>
114:             <CFSET aFieldValues[nColumn] = qryParameters.param_value>
115:             </CFIF>
116:             <CFIF listGetAt(listFieldNames,nColumn) is "imgType">
117:               <td <CFIF lEditrow IS true>bgcolor="ffffff"</CFIF> valign="top">
118:                 <CFIF qryParameters.param_value is "0">
119:                   Standard Photo
120:                   <CFIF lEditrow is true><CFSET URL.ImageType = "0"></CFIF>
121:                   <CFELSEIF qryParameters.param_value is "1">
122:                     Bamboo Image
123:                     <CFIF lEditrow is true><CFSET URL.ImageType = "1"></CFIF>
124:                     <CFELSEIF qryParameters.param_value is "2">
125:                       IPIX Image
126:                       <CFIF lEditrow is true><CFSET URL.ImageType = "2"></CFIF>
127:                       <CFELSE>
128:                         #qryParameters.param_value#
129:                         <CFIF lEditrow is true><CFSET URL.ImageType = "-1"></CFIF>
130:                         </CFIF>
131:                       </td>
132:                       <CFELSE>
133:                         <td <CFIF lEditrow IS true>bgcolor="ffffff"</CFIF> valign="top">
134:                           <cfif trim(qryParameters.param_value) IS "">
135:                             <nbsp;
136:                             <cfelse>
137:                               #qryParameters.param_value#
138:                             </CFIF></td>
139:                           </CFIF>
140:
141:                         <CFIF nColumn is nTotalCols-2> <!-- the last column with info was displayed -->
142:                         <td <CFIF lEditrow is true>bgcolor="ffffff"</CFIF> colspan="2" valign="top">
143:                           <a
144:                             href="agencyMaint.cfm?Action=Edit&agency_id=#URL.agency_id&param_counter=#qryParameters.param_cntr#&displayPage=Template">E
                             dit</a><hr>
                             <a
                             href="agencyDataUpdate.cfm?Action=Delete&agency_id=#URL.agency_id&param_counter=#qryParameters.param_cntr#">Delete</a></td>

```

```

145:         </td>
146:     </tr>
147:     <CFSET nColumn = 0>
148:     </CFIF>
149: </CFLOOP>
150:
151: </table></p>
152:
153:
154: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
155:     <!-- Now allow the user to add or edit an image -->
156:     <tr bgcolor="cccccc">
157:         <td colspan="#nTotalCols#"
158:             <CFIF #URL.Action# is "Add">
159:                 <b>Add A Paragraph</b>:
160:                 <input type="hidden" name="Action" VALUE="Add">
161:                 <CFELSEIF #URL.Action# is "Edit">
162:                 <b>Edit Selected Paragraph:</b>
163:                 <input type="hidden" name="Action" VALUE="Edit">
164:                 <CFELSEIF #URL.Action# is "View">
165:                 <b>Add A Paragraph:</b>
166:                 <input type="hidden" name="Action" VALUE="Add">
167:                 </CFIF>
168:         </td>
169:     </tr>
170:
171:     <tr>
172:         <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
173:             <td bgcolor="#####" valign="bottom">
174:                 <!-- Moved the text area (paragraph) to a row immediately under the other input data -->
175:                 <cfif findNocase("Text", #listGetAt(listLabels, nIndex)#) neq 0>
176:                     <cfset labelId = #nIndex#>
177:                     <cfelse>
178:                         <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, nIndex)#</b></font>
179:                     </cfif>
180:                 </td>
181:             </CFLOOP>
182:         </tr>
183:
184:         <form name="firmValues" enctype="multipart/form-data" action="agencyDataUpdate.cfm" method="post">
185:             <tr valign="top" bgcolor="#####">
186:                 <CFLOOP FROM="1" TO="#listlen(listLabels)#" INDEX="nIndex">
187:                     <CFSET cFieldType = ucase(trim(listGetAt(listFieldTypes, nIndex)))>
188:                     <CFIF cFieldType is "TEXT">
189:                         <CFIF listGetAt(listFieldNames, nIndex) is "imgType">
190:                             <td>
191:                                 <CFIF #URL.Action# is "Edit">
192:                                     <CFIF aFieldValues[nIndex] is "0">
193:                                         <I>Standard Photo</I><br>

```

```

194: <CFELSEIF aFieldValues[nIndex] Is "1">
195:   <I>Bamboo Image</I><br>
196: <CFELSEIF aFieldValues[nIndex] is "2">
197:   <I>PIX Image</I><br>
198: <CFELSE>
199:   <I>#aFieldValues[nIndex]#</I><br>
200: </CFIF>
201: </CFIF>
202: <SELECT NAME="FIELD#nIndex#">
203:   <CFLOOP QUERY="qryImageTypes">
204:     <CFIF URL.ImageType is "0" and qryImageTypes.value is "0">
205:       <CFSET lShowOption = true>
206:     <CFELSEIF URL.ImageType is not "0" and qryImageTypes.value is not "0">
207:       <CFSET lShowOption = true>
208:     <CFELSE>
209:       <CFSET lShowOption = False>
210:     </CFIF>
211:     <CFIF lShowOption is true>
212:       <OPTION value=#qryImageTypes.value# <CFIF #trim(aFieldValues[nIndex])# is
         #trim(qryImageTypes.value)#>SELECTED</CFIF>>#trim(label)#</OPTION>
         </CFIF>
213:       </CFLOOP>
214:     </SELECT>
215:   <br>
216:   <CFIF URL.Action is not "Edit">
217:     <!-- If they want to change the image type, they will need to delete the image and reenter it -->
218:     <CFIF URL.ImageType is "0">
219:       <font face="Verdana, Arial" size="1"><a
         href="agencyMaint.cfm?Action=#URL.Action#&agency_id=#URL.agency_id#&ImageType=1&param_counter=#URL.param_counter#&displayPag
         e=Template">To Add Bamboo or PIX<br>images, Click Here</a><br><font color="red">(Warning: by clicking,<br>form will
         reset.)</font></font>
220:       <CFELSE>
221:         <font face="Verdana, Arial" size="1"><a
         href="agencyMaint.cfm?Action=#URL.Action#&agency_id=#URL.agency_id#&ImageType=0&param_counter=#URL.param_counter#&displayPag
         e=Template">To Add a standard photo, Click Here</a><br><font color="red">(Warning: by clicking,<br>form will
         reset.)</font></font>
222:       </CFIF>
223:     </CFIF>
224:   </td>
225: <CFELSE>
226:   <td>
227:     <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
228:   </td>
229: </CFIF>
230: <CFELSEIF cFieldtype is "FILE">
231:   <td>
232:     <CFIF #URL.Action# is "Edit">
233:       <CFIF URL.ImageType is "0">
234:         <em>#getFileFromPath(aFieldValues[nIndex])#</em><br>
235:

```

```

236: <CFELSE>
237:   #aFieldValues[nIndex]#<br>
238: </CFIF>
239: </CFIF>
240: <CFIF URL.ImageType is "0">
241:   <INPUT TYPE="FILE" NAME="Field#nIndex#" SIZE="20">
242: <CFELSE>
243:   <INPUT TYPE="TEXT" NAME="Field#nIndex#" SIZE="20" VALUE="#aFieldValues[nIndex]#">
244: </CFIF>
245: </td>
246: <CFELSEIF cFieldType is "TEXTAREA">
247:   <td bgcolor="#ffffff">
248:     <!-- Moved the text area to a row immediately under the other input data --SP# 0404800 -->
249:     <cfset textId = #nIndex#>&nbsp;
250:   </td>
251: <CFELSEIF cFieldType is "CHECKBOX">
252:   <td ALIGN="CENTER">
253:     <INPUT TYPE="CHECKBOX" NAME="Field#nIndex#" SIZE="70" <CFIF #aFieldValues[nIndex]# is "ON">CHECKED</CFIF>>
254:   </td>
255: <CFELSEIF cFieldType is "SELECT">
256:   <td>
257:     <CFSET listColOptions = replace(ListGetAt(listFieldOptions, nIndex, "|"), ",", "All")>
258:     <CFIF listLen(listColOptions) gt 0>
259:       <SELECT NAME="Field#nIndex#">
260:         <CFLOOP FROM="1" TO="#listLen(listColOptions)#" INDEX="nListInd">
261:           <CFSET cOption = listGetAt(listColOptions, nListInd, ",")>
262:           <OPTION <CFIF #aFieldValues[nIndex]# is #cOption#>SELECTED</CFIF>>#cOption#
263:         </CFLOOP>
264:       </SELECT>
265:     </td>
266:   </CFIF>
267: </CFLOOP>
268: </tr>
269: <tr valign="TOP" bgcolor="ffffff">
270: <!-- Moved the text area to a row immediately under the other input data --SP# 0404800 -->
271:   <td colspan="#listLen(listLabels)#">
272:     <cfif isDefined("textId")>
273:       <font face="Verdana, Arial" size="2"><b>#listGetAt(listLabels, labelId)#</b></font><br>
274:       <TEXTAREA ROWS="8" COLS="80" WRAP="VIRTUAL" NAME="Field#textId#">#aFieldValues[textId]#</TEXTAREA>
275:     </cfif>
276:   </td>
277: </tr>
278: <tr bgcolor="ffffff">
279:   <td colspan="#nTotalCols#">
280:     <CFIF nMaxParamCounter is -1>
281:       <CFSET nMaxParamCounter = 1>
282:     <CFELSE>
283:       <CFSET nMaxParamCounter = nMaxParamCounter + 1>
284:

```

```
285: </CFIF>
286: <CFIF #URL.Action# is "View">
287:   <input type="hidden" name="Action" value="ADD">
288:   <INPUT TYPE="SUBMIT" VALUE="Add New Paragraph" NAME="btnSubmit">
289:
290:   <input type="hidden" name="param_counter" value="#nMaxParamCounter#">
291:   <CFELSEIF #URL.Action# is "Edit">
292:     <input type="hidden" name="Action" value="EDIT">
293:     <INPUT TYPE="SUBMIT" VALUE="Update Paragraph">
294:     <INPUT TYPE="RESET" VALUE="Reset Information">
295:     <INPUT TYPE="BUTTON" VALUE="Cancel" NAME="btnSubmit"
ONCLICK="location.href='agencyMaint.cfm?agency_id=#URL.agency_id#&displayPage=Template'">
296:     <input type="hidden" name="param_counter" value="#URL.Param_Counter#">
297:     </CFIF>
298:   </td>
299: </tr>
300:
301: <CFSET nImageTypeField = listFindNoCase(listFieldNames,"imgType")>
302:
303:   <input type="hidden" name="imageField" value="#nImageTypeField#">
304:   <input type="hidden" name="agency_id" value="#URL.agency_id#">
305:   <input type="hidden" name="fieldLabels" value="#listLabels#">
306:   <input type="hidden" name="fieldTypes" value="#listFieldTypes#">
307:   <input type="hidden" name="field_names" value="#listFieldNames#">
308: </form>
309: </table></p>
310:
311: </cfoutput>
```



```
1: <!-- Security Include File -->
2:
3: <cfparam name="client.securityLevel" default="1">
4: <cfparam name="client.securityGroup" default="1">
5: <cfparam name="client.userID" default="1">
6: <cfparam name="client.securityTopLevel" default="1">
7: <cfparam name="client.entityID" default="1">
8: <cfparam name="client.entityType" default="1">
9: <cfparam name="client.username" default="">
10:
11: <cfif admin_forceLogin is True>
12:     <cfif client.userID is -1>
13:         <cflocation url="login.cfm" addtoken="no">
14:     <cfelseif not isdefined("lSecurityTested")>
15:         <cfinclude template="securityTest.cfm">
16:     </cfif>
17: <cfelseif client.userID is -1>
18:     <cfset client.securityLevel = 1>
19:     <cfset client.securityGroup = 1>
20:     <cfset client.entityID = 1>
21:     <cfset client.entityType = 1>
22:     <cfinclude template="securityTest.cfm">
23: </cfif>
24: <cfset lSecurityTested = True>
25:
```

First make sure the security information is set up correctly.

```
1: <!-- First make sure the security information is set up correctly -->
2:
3: <cftransaction>
4:
5:   <cfquery name="qryCheckSecurity" datasource="#SourceName#">
6:     select securityLevel from securityLevels
7:   </cfquery>
8:
9:   <cfif qryCheckSecurity.recordCount is 0>
10:     <cfquery name="qryInsertSecurity" datasource="#SourceName#">
11:       insert into securityLevels
12:         (securityLevel, description, notes)
13:       values (1, 'Administrator', '')
14:     </cfquery>
15:     <cfquery name="qryInsertSecurity" datasource="#SourceName#">
16:       insert into securityLevels
17:         (securityLevel, description, notes)
18:       values (2, 'Office Manager', '')
19:     </cfquery>
20:     <cfquery name="qryInsertSecurity" datasource="#SourceName#">
21:       insert into securityLevels
22:         (securityLevel, description, notes)
23:       values (3, 'User', '')
24:     </cfquery>
25:   </cfelse>
26:     <cfquery name="qryCheckSecurity" datasource="#SourceName#">
27:       select securityLevel from securityLevels
28:       where description = 'Administrator'
29:     </cfquery>
30:     <cfif qryCheckSecurity.recordCount is 0>
31:       <cfquery name="qryInsertSecurity" datasource="#SourceName#">
32:         insert into securityLevels
33:           (securityLevel, description, notes)
34:         values (1, 'Administrator', '')
35:       </cfquery>
36:     </cfif>
37:   </cfif>
38:
39:   <cfquery name="qryCheckSecurity" datasource="#SourceName#">
40:     select userGroup from securityGroups
41:   </cfquery>
42:   <cfif qryCheckSecurity.recordCount is 0>
43:     <cfquery name="qryInsertSecurity" datasource="#SourceName#">
44:       insert into securityGroups
45:         (userGroup, description, notes)
46:       values (1, 'Yakalo Administrator', 'Has authority over entire system')
47:     </cfquery>
48:     <cfquery name="qryInsertSecurity" datasource="#SourceName#">
49:       insert into securityGroups
```

```
50: (userGroup, description, notes)
51: values (2, 'Master Distributor', 'Can create Distributors, (Master) Agencies, and Agents')
52: </cfquery>
53: <cfquery name="qryInsertSecurity" datasource="#SourceName#">
54: insert into securityGroups
55: (userGroup, description, notes)
56: values (3, 'Distributor', 'Can create (Master) Agencies and Agents')
57: </cfquery>
58: <cfquery name="qryInsertSecurity" datasource="#SourceName#">
59: insert into securityGroups
60: (userGroup, description, notes)
61: values (4, 'Master Agency', 'Can create Agencies and Agents')
62: </cfquery>
63: <cfquery name="qryInsertSecurity" datasource="#SourceName#">
64: insert into securityGroups
65: (userGroup, description, notes)
66: values (5, 'Agency', 'Can create Agents')
67: </cfquery>
68: <cfquery name="qryInsertSecurity" datasource="#SourceName#">
69: insert into securityGroups
70: (userGroup, description, notes)
71: values (6, 'Agent', 'Can only change specific agent information')
72: </cfquery>
73:
74: </cfif>
75:
76: <cfquery name="qryCheckSecurity" datasource="#SourceName#">
77: select userID from security
78: </cfquery>
79: <cfif qryCheckSecurity.recordCount is 0>
80: <cfquery name="qryGetGroup" datasource="#SourceName#">
81: select userGroup from securityGroups
82: where description = 'Yakalo Administrator'
83: </cfquery>
84: <cfset nUserGroup = qryGetGroup.userGroup>
85:
86: <cfquery name="qryGetLevel" datasource="#SourceName#">
87: select securityLevel from securityLevels
88: where description = 'Administrator'
89: </cfquery>
90: <cfset nSecurityLevel = qryGetLevel.securityLevel>
91:
92: <cfquery name="qryGetEntity" datasource="#SourceName#">
93: select entityID from entities
94: where entities.name = 'Yakalo Solutions'
95: </cfquery>
96:
97: <cfif qryGetEntity.recordCount is 0>
98: <cfquery name="qryInsertEntity" datasource="#SourceName#">
```

```
99:      insert into Entities
100:      (name, entityType, parentID, url)
101:      values ('Yakalo Solutions', #nUserGroup#, 0, 'http://www.yakalo.net')
102:    </cfquery>
103:
104:    <cfquery name="qryGetEntity" datasource="#sourcename#">
105:      select entityID from entities
106:      where entities.name = 'Yakalo Solutions'
107:    </cfquery>
108:  </cfif>
109:  <cfset nEntityID = qryGetEntity.entityID>
110:
111:  <cfset cEncrypt = encrypt("Yakalo.Access", "Yakalo.adm(YakPass)")>
112:  <cfset cEncrypt = preservesingleQuotes(cEncrypt)>
113:  <cfquery name="qryInsertSecurity" datasource="#SourceName#">
114:    insert into security
115:    (loginName, Password, fullName, securityLevel, userGroup, status, entityID)
116:    values ('Yakalo.adm', '#cEncrypt', 'Yakalo Administrator', #nSecurityLevel#, #nUserGroup#, 'Enabled', #nEntityID#)
117:  </cfquery>
118:
119:  </cfif>
120:
121:  </cftransaction>
122:
```

```
1:  <!-- Brute force method for calculating security -->
2:
3:  <!-- Item-Subtype-Item-ID|Name|ItemSecurityGroup|ParentID| --->
4:  <!-- The absolute top level is Yakalo Administrator --->
5:  <cfset lstSecurity = "1-1|Yakalo Solutions|1|0-0|0|">
6:
7:  <!-- Master Distributors --->
8:  <cfquery name="qryGetDist" datasource="#sourcename#">
9:    select distributors.distributorID, distributors.name from distributors
10:    where distributors.parentID = 0
11:  </cfquery>
12:
13:  <cfloop query="qryGetDist">
14:    <cfset lstSecurity =
15:      listAppend(lstSecurity, "|2-#qryGetDist.distributorID|#qryGetDist.name#|2|1-1|#qryGetDist.distributorID|", "~")>
16:    </cfloop>
17:
18:  <!-- Distributors --->
19:  <cfquery name="qryGetDist" datasource="#sourcename#">
20:    select distributors.distributorID, distributors.name, distributors.parentID from distributors
21:    where distributors.parentID > 0
22:  </cfquery>
23:
24:  <cfloop query="qryGetDist">
25:    <cfset nAt = listContainsNoCase(lstSecurity, "|2-#qryGetDist.parentID|", "~")>
26:    <cfif nAt gt 0>
27:      <cfif nAt is listlen(lstSecurity)>
28:        <cfset lstSecurity = listAppend(lstSecurity,
29:          "|2-#qryGetDist.distributorID|#qryGetDist.name#|3|2-#qryGetDist.parentID|#qryGetDist.distributorID|", "~")>
30:      </cfif>
31:    </cfif>
32:  </cfloop>
33:
34:  <!-- Master Agencies --->
35:  <cfquery name="qryGetAgency" datasource="#sourcename#">
36:    select agency.agency_id, agency.name, agency.distributorID from agency
37:    where agency.parentAgency = 0 and agency.distributorid > 0
38:  </cfquery>
39:  <cfloop query="qryGetAgency">
40:    <cfset nAt = listContainsNoCase(lstSecurity, "|2-#qryGetAgency.distributorID|", "~")>
41:    <cfif nAt gt 0>
42:      <cfif nAt is listlen(lstSecurity, "~")>
43:        <cfset lstSecurity = listAppend(lstSecurity,
44:          "|4-#qryGetAgency.agency_id|#qryGetAgency.name#|4|2-#qryGetAgency.distributorID|#qryGetAgency.distributorID|", "~")>
45:      </cfif>
46:    </cfif>
47:  </cfloop>
```

```

46: nAt+1,"|4-#qryGetAgency.agency_id#|#qryGetAgency.name#|4|2-#qryGetAgency.distributorID#|#qryGetAgency.distributorID#|", "~")>
47:   </cfif>
48: </cfif>
49: </cfloop>
50: <!-- Agencies ---->
51: <cfquery name="qryGetAgency" datasource="#source#">
52:   select agency.agency_id, agency.name, agency.parentAgency, agency.distributorID from agency
53:   where agency.parentAgency > 0
54: </cfquery>
55: <cfloop query="qryGetAgency">
56:   <cfset nAt = listContainsNoCase(lstSecurity,"|4-#qryGetAgency.parentAgency#|", "~")>
57:   <cfif nAt gt 0>
58:     <cfif nAt is listlen(lstSecurity, "~")>
59:       <cfset lstSecurity = listAppend(lstSecurity,
60:         "|4-#qryGetAgency.agency_id#|#qryGetAgency.name#|5|4-#qryGetAgency.parentAgency#|#qryGetAgency.distributorID#|", "~")>
61:       <cfset lstSecurity = listInsertAt(lstSecurity,
62:         nAt+1,"|4-#qryGetAgency.agency_id#|#qryGetAgency.name#|5|4-#qryGetAgency.parentAgency#|#qryGetAgency.distributorID#|", "~")>
63:     </cfif>
64:   </cfif>
65:   </cfloop>
66:   <cfset lstSecurity = listAppend(lstSecurity, "|4-0|Unaffiliated Agents|5|0-0|#ap_distributorID#|", "~")>
67:
68:   <!-- Agents ---->
69:   <cfquery name="qryGetAgents" datasource="#source#">
70:     select agents.agent_id, agents.firstname + ' ' + agents.lastname as name, agents.agency_id, agents.distributorID
71:     from agents
72:     where agents.distributorID = #ap_distributorID#
73:   <!-- Where (agents.agency_id > 0 or agents.distributorID = #ap_distributorID#) ---->
74:   </cfquery>
75:   <cfloop query="qryGetAgents">
76:     <cfset nAt = listContainsNoCase(lstSecurity,"|4-#qryGetAgents.agency_id#|", "~")>
77:     <cfif nAt gt 0>
78:       <cfif nAt is listlen(lstSecurity, "~")>
79:         <cfset lstSecurity = listAppend(lstSecurity,
80:           "|6-#qryGetAgents.agent_id#|#qryGetAgents.name#|6|4-#qryGetAgents.agency_id#|#qryGetAgents.distributorID#|", "~")>
81:         <cfset lstSecurity = listInsertAt(lstSecurity,
82:           nAt+1,"|6-#qryGetAgents.agent_id#|#qryGetAgents.name#|6|4-#qryGetAgents.agency_id#|#qryGetAgents.distributorID#|", "~")>
83:       </cfif>
84:     </cfif>
85:   </cfloop>
86:
87:   <!-- Now we set the actual security information for the user that is logged in ---->
88:
89:   <cfset qrySecurity = queryNew("entityID, name, entityType, itemSecurityGroup, parentID, entityLookup")>

```

```

90:
91: <!--- <cfset temp = queryAddRow(qrySecurity, listlen(lstSecurity))> --->
92:
93: <!--- <cfoutput>#lstSecurity#<br></cfoutput> --->
94:
95: <cfset lstInSecurity = ">"
96: <cfset lFoundLevel = False>
97: <cfset nGroupLevel = client.entityType>
98: <cfset nQueryRow = 0>
99:
100: <cfloop from="1" to="#listlen(lstSecurity, "~")#" index="nIndex">
101:   <cfset lstRow = listGetAt(lstSecurity, nIndex, "~")>
102:   <!--- <cfoutput>#lstRow#<br></cfoutput> --->
103:   <cfset cItemID = listGetAt(listGetAt(lstRow, 1, "|"), 2, "-")>
104:   <!--- <cfset cItemSubType = listGetAt(listGetAt(lstRow, 1, "|"), 1, "-")> --->
105:
106:   <!--- <cfoutput>#lstRow#<br></cfoutput> --->
107:   <cfset cItemSubType = listGetAt(lstRow, 3, "|")>
108:   <cfif cItemSubType is 6 and listGetAt(lstRow, 4, "|") is "6-0" and listGetAt(lstRow, 5, "|") is #ap_distributorID#>
109:     <!-- Agents who have been added but have no parent agency --->
110:     <cfset lFoundLevel = True>
111:     <cfelseif cItemSubType is 5 and listGetAt(lstRow, 4, "|") is "0-0" and listGetAt(lstRow, 5, "|") is #ap_distributorID# and
       trim(listGetAt(lstRow, 2, "|")) is "Unaffiliated Agents">
112:       <cfset lFoundLevel = True>
113:     <cfelseif lFoundLevel is True and cItemSubType lte nGroupLevel>
114:       <cfset lFoundLevel = False> <!--- The next type of this sub level has been found, so no access is allowed --->
115:     <cfelseif cItemID is client.entityID and cItemSubType is client.entityType>
116:       <cfset lFoundLevel = True>
117:     </cfif>
118:
119:     <cfif lFoundLevel>
120:       <cfset nQueryRow = nQueryRow + 1>
121:       <cfset temp = queryAddRow(qrySecurity, 1)>
122:       <cfset cToInsert = listGetAt(lstRow, 1, "|")>
123:       <cfset lstInSecurity = listAppend(lstInSecurity, "|" & cToInsert & "|" & ",")>
124:       <!--- <cfoutput>#lstRow# ~ #cItemID# ~ #cItemSubType# ~ #client.entityID# ~ #client.entityType# ~
           #lFoundLevel#<br></cfoutput> --->
125:
126:       <cfset temp = querySetCell(qrySecurity, "entityType", cItemSubType, nQueryRow)>
127:       <cfset temp = querySetCell(qrySecurity, "entityID", cItemID, nQueryRow)>
128:       <cfset temp = querySetCell(qrySecurity, "name", listGetAt(lstRow, 2, "|"), nQueryRow)>
129:       <cfset temp = querySetCell(qrySecurity, "itemSecurityGroup", listGetAt(lstRow, 3, "|"), nQueryRow)>
130:       <cfset temp = querySetCell(qrySecurity, "parentID", listGetAt(lstRow, 4, "|"), nQueryRow)>
131:       <cfset temp = querySetCell(qrySecurity, "entityLookup", "|" & cItemSubType & "-" & cItemID & "|", nQueryRow)>
132:     </cfif>
133:   </cfloop>
134:
135:   <!--- <cfset client.lstSecurity = listQualify(lstInSecurity, "")> --->
136:

```

```

137: <cfset client.lstSecurity = lstInSecurity>
138: <cfset lstSecurity = ""> <!--- clear this out since we don't want to fill up the server's heap --->
139: <cfset lstInSecurity = "">
140:
141: <!---
142: <table>
143: <tr>
144: <td>
145: <cfoutput>
146: <cfloop list="#client.lstSecurity#" index="nValue">
147: <nValue#> <br>
148: </cfloop>
149: </cfoutput>
150: </td>
151: <td>
152: <cfoutput query="qrySecurity">
153: <#qrySecurity.entityID#, #qrySecurity.name#, #qrySecurity.entityType#, #qrySecurity.itemSecurityGroup#,
    #qrySecurity.parentID#><br>
154: </cfoutput>
155: </td>
156: <td>
157: <cfoutput>
158: <cfloop list="#client.lstSecurity#" index="nValue">
159: <nValue#><br>
160: </cfloop>
161: </cfoutput>
162: </td>
163: </tr>
164: </table>
165: <!--- listSort(lstSecurity, "list(nocase)" --->
166: <hr>
167: <cfoutput><client.entityID#, #current entityType#></cfoutput>
168:
169: <!-->

```



```
1: <cfquery name="qryListInfo" datasource="#source#"#sourceName#">
2: select '6-'+convert(char(20),agents.agent_id) as itemID, '4-'+convert(char(20),agents.agency_id) as parentItemID, 6 as
3: itemType, agents.firstname+' '+agents.lastname as Name
4: from agents
5: union
6: select '4-'+convert(char(20),agency.agency_id) as itemID, '4-'+convert(char(20),agency.parentAgency) as parentItemID, 5 as
7: itemType, agency.name as name
8: from agency
9: where agency.parentAgency > 0
10: union
11: select '4-'+convert(char(20),agency.agency_id) as itemID, '2-'+convert(char(20),agency.distributorID) as parentItemID, 4 as
12: itemType, agency.name as name
13: from agency
14: where agency.parentAgency = 0
15: union
16: select '2-'+convert(char(20),distributors.distributorID) as itemID, '2-'+convert(char(20),distributors.parentID) as
17: parentItemID, 3 as itemType, distributors.name as name
18: from distributors
19: where distributors.parentID > 0
20: union
21: select '2-'+convert(char(20),distributors.distributorID) as itemID, '1-1' as parentItemID, 2 as itemType, distributors.name
22: as name
23: from distributors
24: where distributors.parentID = 0
25: </cfquery>
26: <hr>
27: <cfx_make_tree query="qryListInfo">
28: <cfoutput query="qryListInfo">
29:     #itemID#, #parentItemID#, #itemType#, #name#<br>
30: </cfoutput>
```

Author	Year	Country	Sample Size	Study Design	Findings
Wang et al.	2005	China	1,000	Case-control	Increased risk of lung cancer with high alcohol intake.
Li et al.	2006	China	1,200	Case-control	No significant association between alcohol and lung cancer.
Chen et al.	2007	China	1,500	Case-control	Increased risk of lung cancer with high alcohol intake.
Wang et al.	2008	China	1,800	Case-control	No significant association between alcohol and lung cancer.
Li et al.	2009	China	2,000	Case-control	Increased risk of lung cancer with high alcohol intake.
Chen et al.	2010	China	2,200	Case-control	No significant association between alcohol and lung cancer.
Wang et al.	2011	China	2,500	Case-control	Increased risk of lung cancer with high alcohol intake.
Li et al.	2012	China	2,800	Case-control	No significant association between alcohol and lung cancer.
Chen et al.	2013	China	3,000	Case-control	Increased risk of lung cancer with high alcohol intake.
Wang et al.	2014	China	3,200	Case-control	No significant association between alcohol and lung cancer.
Li et al.	2015	China	3,500	Case-control	Increased risk of lung cancer with high alcohol intake.
Chen et al.	2016	China	3,800	Case-control	No significant association between alcohol and lung cancer.
Wang et al.	2017	China	4,000	Case-control	Increased risk of lung cancer with high alcohol intake.
Li et al.	2018	China	4,200	Case-control	No significant association between alcohol and lung cancer.
Chen et al.	2019	China	4,500	Case-control	Increased risk of lung cancer with high alcohol intake.
Wang et al.	2020	China	4,800	Case-control	No significant association between alcohol and lung cancer.
Li et al.	2021	China	5,000	Case-control	Increased risk of lung cancer with high alcohol intake.
Chen et al.	2022	China	5,200	Case-control	No significant association between alcohol and lung cancer.
Wang et al.	2023	China	5,500	Case-control	Increased risk of lung cancer with high alcohol intake.
Li et al.	2024	China	5,800	Case-control	No significant association between alcohol and lung cancer.
Chen et al.	2025	China	6,000	Case-control	Increased risk of lung cancer with high alcohol intake.

```

1: <cfoutput>
2: <p align="center">
3: <table cellpadding="5" >
4: <tr>
5: <td><a href="#ap_reportsPath#/dailystats/index.html">Webtrends Site Stats - MTD</a></td>
6: <td rowspan="5" align="center">WebTrends - month to date<br/></td>
7: </tr>
8: <tr>
9: <td><a href="#ap_reportsPath#/monthlystats/index.html">WebTrends Site Stats - YTD</a></td>
10: </tr>
11: <tr>
12: <td><a href="#pgPropViewReport.cfm">Property Views Stats</a></td>
13: </tr>
14: <tr>
15: <td><a href="#pgAgentViewReport.cfm">Agent Views Stats</a></td>
16: </tr>
17: <tr>
18: <td><a href="#pgAgencyViewReport.cfm">Agency Views Stats</a></td>
19: </tr>
20: <tr><td colspan="2"><br/>Past Statistics</td></tr>
21: <tr><td colspan="2"><a href="#ap_reportsPath#/dailystats/October.html">October 2000</a></td></tr>
22: <tr><td colspan="2"><a href="#ap_reportsPath#/dailystats/September00/index.html">September 2000</a></td></tr>
23: <tr><td colspan="2"><a href="#ap_reportsPath#/dailystats/August00/index.html">August 2000</a></td></tr>
24: </table>
25: </p>
26: </cfoutput>

```

```

1:  <!-- Page Counter v0.5 --->
2:  <!-- Three required variables are nNewsID, cPageType and a nTargetID --->
3:
4:  <cftry>
5:    <cflock scope="SERVER" throwontimeout="Yes" timeout="15">
6:      <cfif not isdefined("server.history")>
7:        <cfset server.history=arrayNew(2)>
8:      </cfif>
9:    </cflock>
10:    <cfcatch type="Lock">
11:      <cfset defHistory = "No">
12:    </cfcatch>
13:  </cftry>
14:
15:  <!-- Check variable validity --->
16:  <cfparam name="nNewsID" default="0">
17:  <cfparam name="cPageType" default="unknown">
18:  <cfparam name="nTargetID" default="0">
19:  <cfif isdefined("http_referer")>
20:    <cfset cReferer = http_referer>
21:  </cfif>
22:  <cfset cReferer = "none">
23:  </cfif>
24:  <cfif isdefined("remote_addr")>
25:    <cfset cRemoteAddr = remote_addr>
26:  </cfif>
27:  <cfset cRemoteAddr = "none">
28:  </cfif>
29:
30:  <!-- Store the page view data --->
31:  <cftry>
32:    <cflock scope="SERVER" throwontimeout="Yes" timeout="25">
33:      <cfset iArraySize = ArrayLen(server.history) + 1>
34:      <cfset server.history[iArraySize][1]=now()>
35:      <cfset server.history[iArraySize][2]=ap_distributorID>
36:      <cfset server.history[iArraySize][3]=nNewsID>
37:      <cfset server.history[iArraySize][4]=cPageType>
38:      <cfset server.history[iArraySize][5]=nTargetID>
39:      <cfset server.history[iArraySize][6]=cReferer>
40:      <cfset server.history[iArraySize][7]=cRemoteAddr>
41:    </cflock>
42:    <cfcatch type="Lock">
43:      <!-- Couldn't obtain a lock so save the data directly--->
44:      <cfquery name="qrySaveHistory" datasource="#sourceName#">
45:        INSERT INTO pageCount
46:          VALUES (now()#,#ap_distributorID,#nNewsID,#cPageType#,#nTargetID#,#cReferer#,#cRemoteAddr#',9,1)
47:      </cfquery>
48:    </cfcatch>
49:  </cftry>

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3: <cfinclude template="include\checkSecurity.cfm">
4: <cfset client.gotoPage = "agencyAdm.cfm">
5:
6: <!---
7: <cfinclude template="include\securityTest.cfm">
8: -->
9:
10: <cfparam name="URL.sortBy" default="name">
11: <cfset client.lookupID = -1>
12: <cfset client.detailID = -1>
13: <cfset client.lookupDistID = -1>
14: <cfset client.lookupAgencyID = -1>
15:
16: <!--- Display rows -->
17: <cfparam name="nStartFrom" default="1">
18: <cfparam name="nDisplay" default="#client.displayRows#">
19: <cfparam name="nEnd" default="#client.displayRows#">
20:
21:
22: <cfquery name="qryEditList" dataSource="#ap_dataSource#">
23:   select agency.agency_id, agency.name, agency.address, agency.city, agency.url_name,
24:   agencyBios.agencyID as agencyBioID
25:   from agency
26:   join securityAccess on
27:     (securityAccess.entityType = #ap_securityMastAgency# or securityAccess.entityType = #ap_securityAgency#
28:    and securityAccess.entityID = agency.agency_id
29:    and securityAccess.hierarchyID like '#client.hierarchyID#%'
30:    left outer join agencyBios on agencyBios.agencyID = agency.agency_id
31: </cfquery>
32:
33: <html>
34: <head>
35:   <cfoutput>
36:     <title>#client.backofficeName# Backoffice</title>
37:   </cfoutput>
38:   <link rel="stylesheet" href="style1.css" type="text/css">
39: </head>
40:
41:
42: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
43: <cfinclude template="include\nocache.cfm">
44: <p><cfinclude template="include\header.cfm"></p>
45:
46: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
47:   <tr bgcolor="#cccc99">
48:     <td colspan="6">
49:       <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">

```

```

50: <tr>
51:   <td align="left">
52:     <span class="h2"><b>Agency Administration</b></span>
53:   </td>
54:   <td align="right">
55:     <cfif #ntoDisplay# gte qryEditList.recordCount>
56:       <cfset cToDisplay = min(qryEditList.recordCount, #ntoDisplay#)>
57:     </cfif>
58:     <cfif qryEditList.recordCount gte #ntoDisplay#>
59:       <cfset cToDisplay = min(qryEditList.recordCount, #nEnd#)>
60:     </cfif>
61:     <cfset cStartFrom = min(qryEditList.recordCount, #nStartFrom#)>
62:     <cfoutput>{Viewing records #cstartFrom# to #ctoDisplay# out of #qryEditList.recordCount#}</cfoutput>
63:   </td>
64: </tr>
65: </table>
66: </td>
67: </tr>
68:
69: <cfif trim(client.userName) is not "">
70:   <tr bgcolor="#cccc99">
71:     <td colspan="6" align="center">
72:       <cfoutput>&nbsp;<b>#client.userName#</b></cfoutput>
73:     </td>
74:   </tr>
75: </cfif>
76: <cfset client.userName = "">
77: <cfset client.lookupID = -1>
78: <cfset client.detailID = -1>
79: <cfset client.lookupDistID = -1>
80: <cfset client.lookupAgencyID = -1>
81:
82: <tr bgcolor="#cccc99">
83:   <td colspan="6">
84:     &nbsp;<b>#agencyMaint.cfm">Add an agency</a>
85:   </td>
86: </tr>
87:
88: <tr bgcolor="#cccccc">
89:   <td>Sort by <a href="agencyAdm.cfm?SortBy=name"><b>Name</b></a></td>
90:   <td>Sort by <a href="agencyAdm.cfm?SortBy=address"><b>Address</b></a></td>
91:   <td>Sort by <a href="agencyAdm.cfm?SortBy=city"><b>City</b></a></td>
92:   <td>Sort by <a href="agencyAdm.cfm?SortBy=url_name"><b>URL</b></a></td>
93:   <td align="center">Agency Info</td>
94:   <td align="center">Enhanced Bio</td>
95: </tr>
96:
97: <CFIF qryEditList.recordCount is 0>
98:

```

```

99: <TR><TD COLSPAN="5"><I>There are no agents defined</I><K><A href="#add">Add</A><A href="#edit">Edit</A></TD></TR></IF>
100: </CFIF>
101: <cfset lColor = True>
102: <form action="agencyChoice.cfm" method="post">
103: <cfoutput query="qryEditList" startrow="#nstartFrom#" maxrows="#ntoDisplay#">
104: <cfset lColor = not lColor>
105: <tr valign="center" <cfif lColor is TRUE>bgcolor="####eeee"</cfif>>
106: <td>#qryEditList.name#</td>
107: <td>#qryEditList.address#</td>
108: <td>#qryEditList.city#</td>
109: <td>#qryEditList.url_name#</td>
110: <td align="center"><input type="image" name="edit#qryEditList.agency_id#" src="#ap_commonImages#edit.gif" alt="Edit"
border="0"></td>
111: <td align="center">
112: <cfif trim(qryEditList.agencyBioID) is "" or qryEditList.agencyBioID lte 0>
113: <input type="image" name="bioAdd#qryEditList.agency_id#" src="#ap_commonImages#add.gif" alt="Add" border="0">
114: <cfelse>
115: <input type="image" name="bioEdit#qryEditList.agency_id#" src="#ap_commonImages#edit.gif" alt="Edit" border="0">
116: </cfif>
117: </td>
118: </tr>
119: </cfoutput>
120: </form>
121: </table></p>
122:
123: <CFSET nPrevStart = nStartFrom-nToDisplay>
124: <CFSET nNextStart = nStartFrom+nToDisplay>
125: <CFSET nPrevEnd = #nPrevStart#+nToDisplay-1>
126: <CFSET nNextEnd = #nNextStart#+nToDisplay-1>
127: <cfif nPrevStart gte 1 or nNextStart lte qryEditList.recordCount>
128: <table border="0" align="center">
129: <tr>
130: <cfif nPrevStart gte 1>
131: <td>
132: <form action="agencyAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
133: <input type="hidden" name="nStartFrom" value="#nPrevStart#">
134: <input type="hidden" name="nToDisplay" value="#nToDisplay#">
135: <input type="hidden" name="nEnd" value="#nPrevEnd#">
136: <input type="submit" value="Previous #nToDisplay#">
137: </FORM>
138: </td>
139: </cfif>
140: <cfif nNextStart lte qryEditList.recordCount>
141: <td>
142: <form action="agencyAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
143: <input type="hidden" name="nStartFrom" value="#nNextStart#">
144: <input type="hidden" name="nToDisplay" value="#nToDisplay#">
145: <input type="hidden" name="nEnd" value="#nNextEnd#">
146: <cfset nLeftToShow = min(nToDisplay, (qryEditList.recordcount - cToDisplay))>

```

```
147:         <input type="submit" value="Next" #urlafToShow#>
148:     </form>
149:     </td>
150: </cfif>
151: </tr>
152: </table>
153: </cfif>
154: </body>
155: </html>
156:
157:
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <cfset client.gotoPage = "agencyBioAdm.cfm">
4:
5:
6: <cfparam name="URL.sortBy" default="agencyName">
7: <cfset client.lookupID = -1>
8: <cfset client.detailID = -1>
9: <cfset client.imageType = -1>
10: <cfset client.lookupDistID = -1>
11: <cfset client.lookupAgencyID = -1>
12:
13: <cfinclude template="include\clearOldFields.cfm">
14:
15: <!-- Display rows -->
16: <cfparam name="nStartFrom" default="1">
17: <cfparam name="nToShow" default="#client.displayRows#">
18: <cfparam name="nEnd" default="#client.displayRows#">
19:
20:
21: <cfquery name="qryEditList" dataSource="#ap_dataSource#">
22:   select agencyBios.agencyID, agency.name as agencyName
23:   from agencyBios
24:   join securityAccess on
25:     (securityAccess.entityType = #ap_securityMastAgency# or securityAccess.entityType = #ap_securityAgency#
26:      and securityAccess.entityID = agencyBios.agencyID
27:      and securityAccess.hierarchyID like '#client.hierarchyID#%'
28:      left outer join agency on agency.agency_id = agencyBios.agencyID
29:      order by #url.sortBy#
30: </cfquery>
31:
32: <html>
33: <head>
34:   <cfoutput>
35:     <title>#client.backofficeName# Backoffice Agency Bio Admin</title>
36:   </cfoutput>
37:   <link rel="stylesheet" href="style1.css" type="text/css">
38: </head>
39:
40:
41: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
42: <cfinclude template="include\nocache.cfm">
43: <p><cfinclude template="include\header.cfm"></p>
44:
45: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
46:   <tr bgcolor="#cccc99">
47:     <td colspan="3">
48:       <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">
49:         <tr>

```



```

50: <td align="left">
51: <span class="h2"><b>Enhanced Agency Bio Administration</b></span>
52: </td>
53: <td align="right">
54: <cfif #nToDisplay# gte qryEditList.recordCount>
55: <cfset cToDisplay = min(qryEditList.recordCount, #nToDisplay#)>
56: </cfif>
57: <cfif qryEditList.recordCount gte #nToDisplay#>
58: <cfset cToDisplay = min(qryEditList.recordCount, #nEnd#)>
59: </cfif>
60: <cfset cStartFrom = min(qryEditList.recordCount, #nStartFrom#)>
61: <cfoutput>{Viewing records #cStartFrom# to #cToDisplay# out of #qryEditList.recordCount#}</cfoutput>
62: </td>
63: </tr>
64: </table>
65: </td>
66: </tr>
67:
68: <cfif trim(client.userName) is not "">
69: <tr bgcolor="#cccc99">
70: <td colspan="3" align="center">
71: <cfoutput>&nbsp;&nbsp;&nbsp;<b>client.userName</b></td>
72: </td>
73: </tr>
74: </cfif>
75: <cfset client.userName = "">
76: <cfset client.lookupID = -1>
77: <cfset client.detailID = -1>
78:
79:
80: <tr bgcolor="#cccccc">
81: <td>Sort by <a href="agencyBioAdm.cfm?SortBy=agencyName"><b>Agency</b></a></td>
82: <td>&nbsp;&nbsp;&nbsp;</td>
83: <td>&nbsp;&nbsp;&nbsp;</td>
84: </tr>
85:
86:
87: <CFIF qryEditList.recordCount is 0>
88: <TR><TD COLSPAN="3"><I>There are no agency bios defined</I></TD></TR>
89: </CFIF>
90: <cfset lColor = True>
91: <form action="agencyBioChoice.cfm" method="post">
92: <cfoutput query="qryEditList" startrow="#nstartFrom#" maxrows="#nToShow#">
93: <cfset lColor = not lColor>
94: <tr valign="center" <cfif lColor is TRUE>bgcolor="#eeeeee"</cfif>>
95: <td>#qryEditList.agencyName#</td>
96: <td align="center"><input type="image" name="edit#qryEditList.agencyID#" src="#ap_commonImages#edit.gif" alt="Edit"
border="0"></td>
97: <td align="center"><input type="image" name="view#qryEditList.agencyID#" src="#ap_commonImages#view.gif" alt="View"

```

```

border="0"></td>
98:      </tr>
99:      </cfoutput>
100:    </form>
101:  </table></p>
102:
103:  <CFSET nPrevStart = nStartFrom-nToDisplay>
104:  <CFSET nNextStart = nStartFrom+nToDisplay>
105:  <CFSET nPrevEnd   = #nPrevStart#+nToDisplay-1>
106:  <CFSET nNextEnd   = #nNextStart#+nToDisplay-1>
107:  <cfif nPrevStart gte 1 or nNextStart lte qryEditList.recordCount>
108:    <table border="0" align="center">
109:      <tr>
110:        <cfif nPrevStart gte 1>
111:          <td>
112:            <form action="agencyBioAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
113:              <input type="hidden" name="nStartFrom" value="#nPrevStart#">
114:              <input type="hidden" name="nToDisplay" value="#nToDisplay#">
115:              <input type="hidden" name="nEnd" value="#nPrevEnd#">
116:              <input type="submit" value="Previous #nToDisplay#">
117:            </FORM>
118:          </td>
119:        </cfif>
120:        <cfif nNextStart lte qryEditList.recordCount>
121:          <td>
122:            <form action="agencyBioAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
123:              <input type="hidden" name="nStartFrom" value="#nNextStart#">
124:              <input type="hidden" name="nToDisplay" value="#nToDisplay#">
125:              <input type="hidden" name="nEnd" value="#nNextEnd#">
126:              <cfset nLeftToShow = min(nnToDisplay, (qryEditList.recordcount - cToDisplay))>
127:              <input type="submit" value="Next #nLeftToShow#">
128:            </form>
129:          </td>
130:        </cfif>
131:      </tr>
132:    </table>
133:  </cfif>
134:
135: </body>
136: </html>
137:

```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <html>
4: <head>
5:   <title>Agency Bio Choice</title>
6: </head>
7:
8: <body>
9:
10:   <cfloop collection="#form#" item="cName">
11:     <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
12:       <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
13:       <cfset client.lookupID = val(cValue)>
14:       <cfset client.detailID = -1>
15:       <cfset client.userName = "">
16:       <cflocation url="agencyBioMaint.cfm" addToken="no">
17:     <cfelseif ucase(left(#cName#,4)) is "VIEW" and findNoCase(".X", #cName#,1) gt 0>
18:       <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
19:       <cfset client.lookupID = val(cValue)>
20:       <cfset client.detailID = -1>
21:       <cfset client.userName = "">
22:       <cflocation url="..agencyBioView.cfm?agencyID=#client.lookupID# addToken="no">
23:     </cfif>
24:   </cfloop>
25:
26:   <cfset client.lookupID = -1>
27:   <cfset client.detailID = -1>
28:   <cfset client.userName = "">
29:   <cflocation url="agencyBioAdm.cfm" addToken="no">
30:
31:
32: </body>
33: </html>
```

1954-1955 1956-1957 1958-1959 1960-1961 1962-1963 1964-1965 1966-1967 1968-1969 1970-1971 1972-1973 1974-1975 1976-1977 1978-1979 1980-1981 1982-1983 1984-1985 1986-1987 1988-1989 1990-1991 1992-1993 1994-1995 1996-1997 1998-1999 2000-2001 2002-2003 2004-2005 2006-2007 2008-2009 2010-2011 2012-2013 2014-2015 2016-2017 2018-2019 2020-2021 2022-2023 2024-2025 2026-2027 2028-2029 2030-2031 2032-2033 2034-2035 2036-2037 2038-2039 2040-2041 2042-2043 2044-2045 2046-2047 2048-2049 2050-2051 2052-2053 2054-2055 2056-2057 2058-2059 2060-2061 2062-2063 2064-2065 2066-2067 2068-2069 2070-2071 2072-2073 2074-2075 2076-2077 2078-2079 2080-2081 2082-2083 2084-2085 2086-2087 2088-2089 2090-2091 2092-2093 2094-2095 2096-2097 2098-2099 2100-2101 2102-2103 2104-2105 2106-2107 2108-2109 2110-2111 2112-2113 2114-2115 2116-2117 2118-2119 2120-2121 2122-2123 2124-2125 2126-2127 2128-2129 2130-2131 2132-2133 2134-2135 2136-2137 2138-2139 2140-2141 2142-2143 2144-2145 2146-2147 2148-2149 2150-2151 2152-2153 2154-2155 2156-2157 2158-2159 2160-2161 2162-2163 2164-2165 2166-2167 2168-2169 2170-2171 2172-2173 2174-2175 2176-2177 2178-2179 2180-2181 2182-2183 2184-2185 2186-2187 2188-2189 2190-2191 2192-2193 2194-2195 2196-2197 2198-2199 2200-2201 2202-2203 2204-2205 2206-2207 2208-2209 2210-2211 2212-2213 2214-2215 2216-2217 2218-2219 2220-2221 2222-2223 2224-2225 2226-2227 2228-2229 2230-2231 2232-2233 2234-2235 2236-2237 2238-2239 2240-2241 2242-2243 2244-2245 2246-2247 2248-2249 2250-2251 2252-2253 2254-2255 2256-2257 2258-2259 2260-2261 2262-2263 2264-2265 2266-2267 2268-2269 2270-2271 2272-2273 2274-2275 2276-2277 2278-2279 2280-2281 2282-2283 2284-2285 2286-2287 2288-2289 2290-2291 2292-2293 2294-2295 2296-2297 2298-2299 2300-2301 2302-2303 2304-2305 2306-2307 2308-2309 2310-2311 2312-2313 2314-2315 2316-2317 2318-2319 2320-2321 2322-2323 2324-2325 2326-2327 2328-2329 2330-2331 2332-2333 2334-2335 2336-2337 2338-2339 2340-2341 2342-2343 2344-2345 2346-2347 2348-2349 2350-2351 2352-2353 2354-2355 2356-2357 2358-2359 2360-2361 2362-2363 2364-2365 2366-2367 2368-2369 2370-2371 2372-2373 2374-2375 2376-2377 2378-2379 2380-2381 2382-2383 2384-2385 2386-2387 2388-2389 2390-2391 2392-2393 2394-2395 2396-2397 2398-2399 2400-2401 2402-2403 2404-2405 2406-2407 2408-2409 2410-2411 2412-2413 2414-2415 2416-2417 2418-2419 2420-2421 2422-2423 2424-2425 2426-2427 2428-2429 2430-2431 2432-2433 2434-2435 2436-2437 2438-2439 2440-2441 2442-2443 2444-2445 2446-2447 2448-2449 2450-2451 2452-2453 2454-2455 2456-2457 2458-2459 2460-2461 2462-2463 2464-2465 2466-2467 2468-2469 2470-2471 2472-2473 2474-2475 2476-2477 2478-2479 2480-2481 2482-2483 2484-2485 2486-2487 2488-2489 2490-2491 2492-2493 2494-2495 2496-2497 2498-2499 2500-2501 2502-2503 2504-2505 2506-2507 2508-2509 2510-2511 2512-2513 2514-2515 2516-2517 2518-2519 2520-2521 2522-2523 2524-2525 2526-2527 2528-2529 2530-2531 2532-2533 2534-2535 2536-2537 2538-2539 2540-2541 2542-2543 2544-2545 2546-2547 2548-2549 2550-2551 2552-2553 2554-2555 2556-2557 2558-2559 2560-2561 2562-2563 2564-2565 2566-2567 2568-2569 2570-2571 2572-2573 2574-2575 2576-2577 2578-2579 2580-2581 2582-2583 2584-2585 2586-2587 2588-2589 2590-2591 2592-2593 2594-2595 2596-2597 2598-2599 2600-2601 2602-2603 2604-2605 2606-2607 2608-2609 2610-2611 2612-2613 2614-2615 2616-2617 2618-2619 2620-2621 2622-2623 2624-2625 2626-2627 2628-2629 2630-2631 2632-2633 2634-2635 2636-2637 2638-2639 2640-2641 2642-2643 2644-2645 2646-2647 2648-2649 2650-2651 2652-2653 2654-2655 2656-2657 2658-2659 2660-2661 2662-2663 2664-2665 2666-2667 2668-2669 2670-2671 2672-2673 2674-2675 2676-2677 2678-2679 2680-2681 2682-2683 2684-2685 2686-2687 2688-2689 2690-2691 2692-2693 2694-2695 2696-2697 2698-2699 2700-2701 2702-2703 2704-2705 2706-2707 2708-2709 2710-2711 2712-2713 2714-2715 2716-2717 2718-2719 2720-2721 2722-2723 2724-2725 2726-2727 2728-2729 2730-2731 2732-2733 2734-2735 2736-2737 2738-2739 2740-2741 2742-2743 2744-2745 2746-2747 2748-2749 2750-2751 2752-2753 2754-2755 2756-2757 2758-2759 2760-2761 2762-2763 2764-2765 2766-2767 2768-2769 2770-2771 2



```

50:         if (!isValidDate(testform.edtEndDate,Value)) {
51:             if (removeSpaces(testform.edtEndDate.value) == "") {
52:                 results = results + " * Please enter a valid ending date.\r";
53:             }
54:         }
55:         else {
56:             results = results + " * " + testform.edtEndDate.value + " ' is not valid. Please enter a valid ending date.\r";
57:         }
58:         lResult = false;
59:     }
60:     if (!lResult) {
61:         window.alert(results);
62:     }
63:     return lResult;
64: }
65: -->
66: </script>
67:
68: <html>
69: <head>
70:     <cfoutput>
71:     <title>#client.backofficeName# Backoffice Agency Bio Maintenance</title>
72:     </cfoutput>
73:     <link rel="stylesheet" href="style1.css" type="text/css">
74:     </head>
75:
76:     <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
77:     <cfinclude template="include\nocache.cfm">
78:
79:     <p><cfinclude template="include\header.cfm"></p>
80:
81:     <cfoutput>
82:
83:     <form action="agencyBioUpdate.cfm" method="post" enctype="multipart/form-data" onsubmit="return validate(this)">
84:         <input type="hidden" name="agencyID" value="#nAgencyID#">
85:         <input type="hidden" name="distributorID" value="#nDistributorID#">
86:         <input type="hidden" name="originalHeaderImage" value="#qryFindBio.headerImage#">
87:         <input type="hidden" name="originalUserHeader" value="#qryFindBio.userHeaderImage#">
88:         <input type="hidden" name="originalFooterImage" value="#qryFindBio.footerImage#">
89:         <input type="hidden" name="originalUserFooter" value="#qryFindBio.userFooterImage#">
90:         <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
91:             <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Agency Bio Maintenance for
92:                 <cfif client.lookupID is -1>
93:                     &nbsp;   <b> (Create a new agency bio)
94:                 </cfif>
95:             </td></tr>
96:
97:             <CFIF client.userName is not "">

```

```

98:     <tr bgcolor="#eeeeee">
99:         <td colspan="5"><p><font color="red">#client.userName</font></p></td>
100:     </tr>
101:     <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
102: </CFIF>
103: <cfset client.userName = "">
104:
105:     <tr bgcolor="##eeeeee">
106:         <td width="15%">Header Image:</td>
107:         <td colspan="4">
108:             <input type="file" name="edtHeaderImage" size="30">
109:             <cfif trim(qryFindBio.headerImage) is not "">
110:                 <i>&nbsp;<img alt="Header Image" data-bbox="110 490 275 510" style="vertical-align: middle;"/></i>
111:                 </cfif>
112:             </td>
113:         </tr>
114:     <tr bgcolor="##eeeeee">
115:         <td width="15%">Footer Image:</td>
116:         <td colspan="4">
117:             <input type="file" name="edtFooterImage" size="30">
118:             <cfif trim(qryFindBio.footerImage) is not "">
119:                 <i>&nbsp;<img alt="Footer Image" data-bbox="119 490 435 510" style="vertical-align: middle;"/></i>
120:                 </cfif>
121:             </td>
122:         </tr>
123:
124:     <tr bgcolor="##eeeeee">
125:         <td width="15%"><b>Begin Date:</b></td>
126:         <td colspan="4">
127:             <input type="text" name="edtBeginDate" value="#dateFormat(qryFindBio.beginDate, "mm/dd/yyyy")#"
128:             size="10"><i>(MM/DD/YY or MM/DD/YYYY)</i></td>
129:         </tr>
130:     <tr bgcolor="##eeeeee">
131:         <td width="15%"><b>End Date:</b></td>
132:         <td colspan="4">
133:             <input type="text" name="edtEndDate" value="#dateFormat(qryFindBio.endDate, "mm/dd/yyyy")#"
134:             size="10"><i>(MM/DD/YY or MM/DD/YYYY)</i></td>
135:         </tr>
136:
137:     <tr bgcolor="##eeeeee">
138:         <td colspan="5">Alternate URL:</td>
139:         <td colspan="5">
140:             <input type="text" name="edtAlternateURL" value="qryFindBio.alternateURL#" size="40"></td>
141:         </tr>
142:
143:     <tr bgcolor="eeeeee">
144:         <td colspan="5">
145:             <cfif qryFindBio.recordCount is 0>
146:                 <td colspan="5">
147:                     <input type="submit" name="btnUpdate" value="Add Agency Bio">
148:                     <input type="reset" value="Reset Info">
149:                 </td>
150:             </cfif>
151:         </tr>

```

```

145: <input type="submit" name="btnUpdate" value="Update Agency Bio">
146: <input type="reset" value="Reset Info">
147: <input type="submit" name="btnView" value="View Agency Bio">
148: </td>
149: <td align="right">
150: <input type="submit" name="btnDelete" value="Delete Agency Bio">
151: </td>
152: </cfif>
153: </tr>
154: </table>
155: </form>
156: </cfoutput>
157:
158: <!-- If this community page has already been created, allow paragraph editing -->
159:
160: <cfif qryFindBio.recordCount gt 0>
161: <script language="JavaScript">
162: <!--
163: function validateDetail(testform) {
164: var results = "";
165: var lResult = true;
166:
167: if ((removeSpaces(testform.edtSortOrder.value) != "") && (!isNumber(testform.edtSortOrder.value))) {
168: results = results + " * " + testform.edtSortOrder.value + " is not a valid numeric sort order value.\r";
169: lResult = false;
170: }
171:
172: if (!lResult) {
173: window.alert(results);
174: }
175:
176: return lResult;
177: }
178: -->
179: </script>
180:
181: <cfquery name="qryDetail" dataSource="#ap_dataSource#">
182: select agencyBioDetail.*, imageTypes.description as imageName
183: from agencyBioDetail
184: left outer join imageTypes on imageTypes.imageType = agencyBioDetail.imageType
185: where agencyBioDetail.agencyID = #client.lookupID#
186: order by agencyBioDetail.sortOrder
187: </cfquery>
188:
189: <cfquery name="qryEdit" dataSource="#ap_dataSource#">
190: select agencyBioDetail.*,
191: imageTypes.isFormField, imageTypes.isApplet, imageTypes.isURL
192: from agencyBioDetail
193: left outer join imageTypes on imageTypes.imageType = agencyBioDetail.imageType

```



[illegible]

```

194: where agencyBioDetail.agencyID = #client.agencyBioDetailID#
195: and agencyBioDetail.agencyBioDetailID = #client.detailID#
196: </cfquery>
197: <cfquery name="qryImageTypes" dataSource="#ap_dataSource#">
198: select imageType, description, isFormField, isApplet, isURL
199: from imageTypes
200: order by description
201: </cfquery>
202:
203: <!-- Set default values -->
204: <cfif qryEdit.recordCount is 0> <!-- New record -->
205: <cfif isDefined("client.old_sortOrder")>
206: <cfset nSortOrder = client.old_sortOrder>
207: <cfelse>
208: <cfset nSortOrder = "1">
209: </cfif>
210:
211: <cfquery name="qryDefault" dataSource="#ap_dataSource#">
212: select imageType from imageTypes
213: where imageTypes.description = 'Standard Photo'
214: </cfquery>
215: <cfif client.imageType gt -1>
216: <cfset nImageType = client.imageType>
217: <cfelseif qryDefault.recordCount gt 0>
218: <cfset nImageType = qryDefault.imageType>
219: <cfelse>
220: <cfset nImageType = 0>
221: </cfif>
222:
223: <cfelse> <!-- Existing record -->
224: <cfif isDefined("client.old_sortOrder")>
225: <cfset nSortOrder = client.old_sortOrder>
226: <cfelse>
227: <cfset nSortOrder = qryEdit.sortOrder>
228: </cfif>
229:
230: <cfif client.imageType gt -1>
231: <cfset nImageType = client.imageType>
232: <cfelse>
233: <cfset nImageType = qryEdit.imageType>
234: </cfif>
235: </cfif>
236: <cfif isDefined("client.old_title")>
237: <cfset cTitle = client.old_title>
238: <cfelse>
239: <cfset cTitle = trim(qryEdit.title)>
240: </cfif>
241: <cfif isDefined("client.old_alignment")>
242: <cfset cAlignment = client.old_alignment>

```

```

243: <cfelse>
244: <cfset cAlignment = trim(qryEdit.alignment)>
245: </cfif>
246: <cfif isDefined("client.old_desc")>
247: <cfset cDesc = client.old_desc>
248: <cfelse>
249: <cfset cDesc = trim(qryEdit.text)>
250: </cfif>
251:
252: <cfquery name="qryImageInfo" dataSource="#ap_dataSource#">
253: select formTitle, isFormField, isApplet, isURL
254: from imageTypes
255: where imageTypes.imageType = #nImageType#
256: </cfquery>
257:
258: <form action="agencyBioUpdate.cfm" method="post" enctype="multipart/form-data" onSubmit="return validateDetail(this)">
259: <cfoutput>
260: <input type="hidden" name="agencyID" value="#client.lookupID#">
261: <input type="hidden" name="distributorID" value="#nDistributorID#">
262: <input type="hidden" name="agencyBioDetailID" value="#client.detailID#">
263: <input type="hidden" name="originalImage" value="#qryEdit.image#">
264: <input type="hidden" name="originalUserImage" value="#qryEdit.userName#">
265: </cfoutput>
266:
267: <cfif qryDetail.recordCount is 0>
268: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
269: <tr><td colspan="6"><i><b>There are no paragraphs defined.</b></i></td></tr>
270: <tr><td colspan="6"><b><em></em></b></td></tr>
271: </table>
272: <cfelse>
273: <table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
274: <tr valign="top" bgcolor="#cccccc">
275: <td><b>Image Type</b></td>
276: <td><b>Title</b></td>
277: <td><b>Text</b></td>
278: <td><b>Image Name</b></td>
279: <td><b>Alignment</b></td>
280: <td><b>Order</b></td>
281: <td><b><em></em></td>
282: </tr>
283: <cfoutput query="qryDetail">
284: <tr valign="top" bgcolor=" "><cfif qryDetail.agencyBioDetailID is client.detailID>#ffffff<cfelse>#eeeeee</cfif><td>
285: <td> <cfif trim(qryDetail.imageName) is "><b><em></em></b></td>
286: <td> <cfif trim(qryDetail.imageName) is "><b><em></em></b></td>
287: <td> <cfif trim(qryDetail.title) is "><b><em></em></b></td>
288: <td> <cfif trim(qryDetail.title) is "><b><em></em></b></td>
289: <td> <cfif trim(qryDetail.title) is "><b><em></em></b></td>
290: <td> <cfif trim(qryDetail.title) is "><b><em></em></b></td>
291: <td>

```

```

292:         <cfif trim(qryDetail.text) != ""><b>#qryDetail.text#</b></td>
293:     </td>
294: <td>
295:     <cfif trim(qryDetail.userName) is "">&nbsp;</cfif>#qryDetail.userName#
296: </td>
297: <td>#qryDetail.alignment#</td>
298: <td>#qryDetail.sortOrder#</td>
299: <td align="center">
300:     <input type="image" name="edit#qryDetail.agencyBioDetailID#" src="#ap_commonImages#edit.gif" alt="Edit"
        border="0">
301: <hr>
302: <input type="image" name="delete#qryDetail.agencyBioDetailID#" src="#ap_commonImages#delete.gif" alt="Delete"
        border="0">
303: </td>
304: </tr>
305: </cfoutput>
306: </table>
307: </cfif>
308: <cfoutput>
309: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
310: <tr><td colspan="5">&nbsp;</td></tr>
311: <cfif client.detailID is -1>
312: <tr bgcolor="#cccccc"><td colspan="5"><b>Add a paragraph</b></td></tr>
313: <cfelse>
314: <tr bgcolor="#cccccc"><td colspan="5"><b>Edit this paragraph</b></td></tr>
315: </cfif>
316: <tr valign="top" bgcolor="#eeeeee">
317: <td><b>Image Type</b></td>
318: <td><b>Title</b></td>
319: <td><b>#qryImageInfo.formTitle#</b></td>
320: <td><b>Alignment</b></td>
321: <td><b>Order</b></td>
322: </tr>
323: <tr valign="top" bgcolor="#eeeeee">
324: <td>
325: <select name="editImageType">
326: <cfloop query="qryImageTypes">
327: <option value="#qryImageTypes.imageType#"><cfif qryImageTypes.imageType is nImageType>
        selected</cfif>#qryImageTypes.description#
328: </cfloop>
329: </select>
330: <cfif qryImageTypes.recordCount gt 1>
331: <input type="submit" name="btnImageType" value="Change">
332: </cfif>
333: </td>
334: <td><input type="text" name="editTitle" value="#cTitle#"></td>
335: <td>
336: <cfif qryImageInfo.isFormField is "Y">
337: <input type="File" name="editImage"></td>

```

```

338: <cfelseif qryImageInfo.isApplet is "Y">
339:   <input type="text" name="editImage">
340: <cfelseif qryImageInfo.isURL is "Y">
341:   <input type="text" name="editImage">
342: <cfelse> <!-- The default if a new entry -->
343:   <input type="File" name="editImage"></td>
344: </cfif>
345: </td>
346: <td>
347:   <select name="editAlignment">
348:     <option value="left"><cfif lcase(cAlignment) is "left"> selected</cfif>>Left
349:     <option value="middle"><cfif lcase(cAlignment) is "middle"> selected</cfif>>Middle
350:     <option value="right"><cfif lcase(cAlignment) is "right"> selected</cfif>>Right
351:   </select>
352: </td>
353: <td><input type="text" name="editSortOrder" value="#nSortOrder#" size="2"></td>
354: </tr>
355: <tr valign="top" bgcolor="#eeeeee">
356:   <td colspan="5">
357:     <b>Text:</b><br>
358:     <textarea name="edtDesc" rows="5" cols="80" wrap="virtual">#trim(cDesc)#</textarea>
359:   </td>
360: </tr>
361: <tr bgcolor="eeeeee">
362:   <td colspan="5">
363:     <cfif qryEdit.recordCount is 0>
364:       <input type="submit" name="btnUpdateDetail" value="Add Paragraph">
365:       <input type="reset" value="Reset Info">
366:     <cfelse>
367:       <input type="submit" name="btnUpdateDetail" value="Update Paragraph">
368:       <input type="reset" value="Reset Info">
369:       <input type="submit" name="btnCancelDetail" value="Cancel">
370:     </cfif>
371:   </td>
372: </tr>
373: </table>
374: </cfoutput>
375: </form>
376: </cfif>
377:
378:
379: </body>
380: </html>

```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3:  <cfif not isDefined("form.agencyID")>
4:    <cfset client.lookupID = -1>
5:    <cfset client.detailID = -1>
6:    <cfset client.imageType = -1>
7:    <cfset client.userName = "">
8:    <cflocation url="agencyBioAdm.cfm" addToken="no">
9:  </cfif>
10:
11:  <cfquery name="qryFindBio" datasource="#ap_datasource#">
12:    select agencyBios.agencyID
13:    from agencyBios
14:    where agencyBios.agencyID = #form.agencyID#
15:  </cfquery>
16:
17:  <cfinclude template="include\clearOldFields.cfm">
18:  <cfset client.userName = "">
19:  <cfset client.imageType = -1>
20:
21:  <cfif isDefined("form.btnImageType")>
22:    <!-- A change in the image type has been requested -->
23:    <cfset client.lookupID = form.agencyID>
24:    <cfset client.detailID = form.agencyBioDetailID>
25:    <cfset client.imageType = form.edtImageType>
26:
27:    <cfset client.old_title = form.edtTitle>
28:    <cfset client.old_alignment = form.edtAlignment>
29:    <cfset client.old_sortOrder = form.edtSortOrder>
30:    <cfset client.old_desc = form.edtDesc>
31:
32:    <cflocation url="agencyBioMaint.cfm" addToken="no">
33:  </cfif>
34:
35:
36:  <cfif isDefined("form.btnCancelDetail")> <!-- Cancel detail edit -->
37:    <cfset client.lookupID = #form.agencyID#>
38:    <cfset client.detailID = -1>
39:    <cfset client.imageType = -1>
40:    <cfset client.userName = "">
41:    <cflocation url="agencyBioMaint.cfm" addToken="no">
42:
43:  <cfelseif isDefined("form.btnCancelDelete")> <!-- Cancel detail edit -->
44:    <cfset client.lookupID = #form.agencyID#>
45:    <cfset client.detailID = -1>
46:    <cfset client.imageType = -1>
47:    <cfset client.userName = "Deletion canceled.">
48:    <cflocation url="agencyBioMaint.cfm" addToken="no">
49:

```

```

50: <cfelseif isDefined("form.btnUpdateDetail")>
51:   <cflocation url="../agencyBioView.cfm?agencyID=#form.agencyID#" addToken="no">
52:
53: <cfelseif isDefined("form.btnUpdateDetail")>
54:   <cfquery name="qryFindDetail" dataSource="#ap_dataSource#">
55:     select agencyBioDetailID
56:     from agencyBioDetail
57:     where agencyBioDetail.agencyBioDetailID = #form.agencyBioDetailID#
58:   </cfquery>
59:
60:   <cfif qryFindDetail.recordCount is 0>
61:     <cfset cTitle = preservesingleQuotes(form.edtTitle)>
62:     <cfset cDesc = preservesingleQuotes(form.edtDesc)>
63:     <cfset nSortOrder = val(form.edtSortOrder)>
64:
65:     <cfquery name="qryImageType" dataSource="#ap_dataSource#">
66:       select imageType, isFormField, isApplet, isURL
67:       from imageTypes
68:       where imageTypes.imageType = #form.edtImageType#
69:     </cfquery>
70:
71:     <cfif qryImageType.isFormField is "Y">
72:       <cfif trim(form.edtImage) is "">
73:         <cfset cImage = form.originalImage>
74:         <cfset cUserImage = form.originalUserImage>
75:       <cfelse>
76:         <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
77:           select distributors.enhAgencyImages
78:           from distributors
79:           where distributors.distributorID = #form.distributorID#
80:         </cfquery>
81:
82:         <!--- Upload the file to a unique name --->
83:         <cfif
84:           destination = "#qryImagePath.enhAgencyImages#"
85:           action = "UPLOAD"
86:           nameConflict = "OVERWRITE"
87:           field = "edtImage"
88:         >
89:
90:         <cfset cImage = file.serverFile>
91:         <cfset cUserImage = file.serverFile>
92:
93:         <cfset cImagePath = file.serverDirectory & "\">
94:         <cfset cNewImage = "#cImagePath#trim(form.agencyID)#_file.serverFile#">
95:
96:         <cfif fileExists(cNewImage)>
97:           <cfif
98:             action = "DELETE"

```

```

99:         file="#cNewImage#"
100:     >
101: </cfif>
102:
103: <!--- Now rename the unique uploaded file to the new name --->
104: <cffile
105:     action = "RENAME"
106:     source = "#file.serverDirectory#\#file.serverFile#"
107:     destination="#cNewImage#"
108: >
109:
110:     <cfset cImage = cNewImage>
111: </cfif>
112: <cfelseif qryImageType.isURL is "Y">
113:     <cfset cImage = form.edtImage>
114:     <cfset cUserImage = form.edtImage>
115: <cfelseif qryImageType.isApplet is "Y">
116:     <cfset cImage = form.edtImage>
117:     <cfset cUserImage = form.edtImage>
118: <cfelse>
119:     <cfset cImage = form.edtImage>
120:     <cfset cUserImage = form.edtImage>
121: </cfif>
122:
123:
124: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
125:     insert into agencyBioDetail
126:     (agencyID, sortOrder, title, image, username, imageType,
127:      alignment, text)
128:     values
129:     (#form.agencyID#, #nsortOrder#, '#cTitle#',
130:      '#cImage#', '#cUserImage#', #form.edtImageType#, '#form.edtAlignment#',
131:      '#cDesc#')
132: </cfquery>
133:
134: <cfset client.lookupID = form.agencyID>
135: <cfset client.detailID = -1>
136: <cfset client.imageType = form.edtImageType> <!--- keep last inserted image type --->
137:
138: <cflocation url="agencyBioMaint.cfm" addToken="no">
139:
140: <cfelse>
141:     <cfset cTitle = preservesingleQuotes(form.edtTitle)>
142:     <cfset cDesc = preservesingleQuotes(form.edtDesc)>
143:     <cfset nsortOrder = val(form.edtSortOrder)>
144:
145:     <cfquery name="qryImageType" dataSource="#ap_dataSource#">
146:         select imageType, isFormField, isApplet, isURL
147:         from imageTypes

```

```

148: where imageTypes.imageType = #form.edtImageType#
149: </cfquery>
150:
151: <cfif qryImageType.isFormField is "Y">
152:   <cfif trim(form.edtImage) is "">
153:     <cfset cImage = form.originalImage>
154:     <cfset cUserImage = form.originalUserImage>
155:   <cfelse>
156:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
157:       select distributors.enhAgencyImages
158:       from distributors
159:       where distributors.distributorID = #form.distributorID#
160:     </cfquery>
161:     <!--- Upload the file to a unique name --->
162:     <cffile
163:       destination = "#qryImagePath.enhAgencyImages#"
164:       action = "UPLOAD"
165:       nameconflict = "OVERWRITE"
166:       fieldid = "edtImage"
167:     >
168:
169:     <cfset cImage = file.serverFile>
170:     <cfset cUserImage = file.serverFile>
171:
172:     <cfset cImagePath = file.serverDirectory & "\">
173:     <cfset cNewImage = "#cImagePath#trim(form.agencyID)#_#file.serverFile#">
174:
175:     <cfif fileExists(cNewImage)>
176:       <cffile
177:         action = "DELETE"
178:         file="#cNewImage#"
179:       >
180:     </cfif>
181:
182:     <!--- Now rename the unique uploaded file to the new name --->
183:     <cffile
184:       action = "RENAME"
185:       source = "#file.serverDirectory#\#file.serverFile#"
186:       destination="#cNewImage#"
187:     >
188:
189:     <cfset cImage = cNewImage>
190:   </cfif>
191:   <cfelseif qryImageType.isURL is "Y">
192:     <cfset cImage = form.edtImage>
193:     <cfset cUserImage = form.edtImage>
194:   <cfelseif qryImageType.isApplet is "Y">
195:     <cfset cImage = form.edtImage>
196:     <cfset cUserImage = form.edtImage>

```



```

197: <cfelse>
198: <cfset cImage = form.edtImage>
199: <cfset cUserImage = form.edtImage>
200: </cfif>
201:
202: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
203:   update agencyBioDetail
204:   set
205:     sortOrder = #nsortOrder#,
206:     title = #cTitle#,
207:     imageType = #form.edtImageType#,
208:     alignment = '#form.edtAlignment#',
209:     image = '#cImage#',
210:     userName = '#cUserImage#',
211:     text = '#cDesc#'
212:   where agencyBioDetail.agencyBioDetailID = #form.agencyBioDetailID#
213: </cfquery>
214:
215: <cfset client.lookupID = form.agencyID>
216: <cfset client.detailID = -1>
217: <cfset client.imageType = -1>
218:
219: <cflocation url="agencyBioMaint.cfm" addToken="no">
220:
221: </cfif>
222:
223: <cfelseif isDefined("form.btnUpdate")>
224: <cfif qryFindBio.recordCount is 0>
225:   <cfset client.lookupID = -1>
226:   <cfset client.detailID = -1>
227:   <cfset client.userName = "There was an error while creating the agency bio page.">
228:   <cftransaction>
229:     <cfif trim(form.edtHeaderImage) is "">
230:       <cfset cHeaderImage = form.originalHeaderImage>
231:       <cfset cUserHeaderImage = form.originalUserHeader>
232:     <cfelse>
233:       <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
234:         select distributors.enhAgencyImages
235:         from distributors
236:         where distributors.distributorID = #form.distributorID#
237:       </cfquery>
238:       <!-- Upload the file to a unique name -->
239:       <cffile
240:         destination = "#qryImagePath.EnhAgencyImages#"
241:         action = "UPLOAD"
242:         nameconflict = "OVERWRITE"
243:         filefield = "edtHeaderImage"
244:       >
245:

```

```

246: <cfset cImage = file.serverFile>
247: <cfset cUserHeaderImage = file.serverFile>
248:
249: <cfset cImagePath = file.serverDirectory & "\">
250: <cfset cNewImage = "#cImagePath#trim(form.agencyID)#_file.serverFile#">
251:
252: <cfif fileExists(cNewImage)>
253:   <cffile
254:     action = "DELETE"
255:     file="#cNewImage#"
256:   >
257: </cfif>
258:
259: <!--- Now rename the unique uploaded file to the new name --->
260: <cffile
261:   action = "RENAME"
262:   source = "#file.serverDirectory#\#file.serverFile#"
263:   destination="#cNewImage#"
264: >
265: <cfset cHeaderImage = cNewImage>
266: </cfif>
267:
268: <cfif trim(form.edtFooterImage) is "">
269:   <cfset cFooterImage = form.originalFooterImage>
270:   <cfset cUserFooterImage = form.originalUserFooter>
271: <cfelse>
272:   <cfquery name="qryImagePath" datasource="#ap_dataSource#">
273:     select distributors.enhAgencyImages
274:     from distributors
275:     where distributors.distributorID = #form.distributorID#
276:   </cfquery>
277:   <!--- Upload the file to a unique name --->
278:   <cffile
279:     destination = "#qryImagePath.enhAgencyImages#"
280:     action = "UPLOAD"
281:     nameconflict = "OVERWRITE"
282:     filefield = "edtFooterImage"
283:   >
284:
285:   <cfset cImage = file.serverFile>
286:   <cfset cUserFooterImage = file.serverFile>
287:
288:   <cfset cImagePath = file.serverDirectory & "\">
289:   <cfset cNewImage = "#cImagePath#trim(form.agencyID)#_file.serverFile#">
290:
291:   <cfif fileExists(cNewImage)>
292:     <cffile
293:       action = "DELETE"
294:       file="#cNewImage#"

```

```

295: >
296: </cfif>
297:
298: <!-- Now rename the unique uploaded file to the new name -->
299: <cffile
300:   action = "RENAME"
301:   source = "#file.serverDirectory#\#file.serverFile#"
302:   destination="#cNewImage#"
303: >
304: <cfset cFooterImage = cNewImage>
305: </cfif>
306:
307: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
308:   insert into agencyBios
309:     (agencyID, distributorID, headerImage, userHeaderImage,
310:      footerImage, userFooterImage, beginDate, endDate, alternateURL)
311:   values
312:     (#form.agencyID#, #form.distributorID#,
313:      '#cHeaderImage#', '#cUserHeaderImage#',
314:      '#cFooterImage#', '#cUserFooterImage#',
315:      '#form.edtBeginDate#', '#form.edtEndDate#',
316:      '#form.edtAlternateURL#')
317: </cfquery>
318:
319: <cfset nAgencyID = form.agencyID>
320: <cfset client.lookupID = nAgencyID>
321:
322: <cfset client.userName = "Agency Bio was created.">
323: </cftransaction>
324:
325: <cfif client.lookupID gt 0>
326:   <cflocation url="agencyBioMaint.cfm" addToken="no">
327: <cfelse>
328:   <cflocation url="agencyBioAdm.cfm" addToken="no">
329: </cfif>
330:
331: <cfelse>
332: <cfset client.lookupID = form.agencyID>
333: <cfset client.detailID = -1>
334: <cfset client.userName = "There was an error while updating the agency bio information.">
335: </cftransaction>
336:   <cfif trim(form.edtHeaderImage) is "">
337:     <cfset cHeaderImage = form.originalHeaderImage>
338:     <cfset cUserHeaderImage = form.originalUserHeader>
339:   <cfelse>
340:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
341:       select distributors.enhAgencyImages
342:       from distributors
343:       where distributors.distributorID = #form.distributorID#

```

```

344: </cfquery>
345: <!-- Upload the file to a unique name -->
346: <cffile
347:     destination = "#qryImagePath.enhAgencyImages#"
348:     action = "UPLOAD"
349:     nameconflict = "OVERWRITE"
350:     filefield = "edtHeaderImage"
351: >
352:
353: <cfset cImage = file.serverFile>
354: <cfset cUserHeaderImage = file.serverFile>
355:
356: <cfset cImagePath = file.serverDirectory & "\">
357: <cfset cNewImage = "#cImagePath#trim(form.agencyID)#_#file.serverFile#">
358:
359: <cfif fileExists(cNewImage)>
360:     <cffile
361:         action = "DELETE"
362:         file="#cNewImage#"
363:     >
364: </cfif>
365:
366: <!-- Now rename the unique uploaded file to the new name -->
367: <cffile
368:     action = "RENAME"
369:     source = "#file.serverDirectory#\#file.serverFile#"
370:     destination="#cNewImage#"
371: >
372: <cfset cHeaderImage = cNewImage>
373: </cfif>
374:
375: <cfif trim(form.edtFooterImage) is "">
376:     <cfset cFooterImage = form.originalFooterImage>
377:     <cfset cUserFooterImage = form.originalUserFooter>
378: <cfelse>
379:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
380:         select distributors.enhAgencyImages
381:         from distributors
382:         where distributors.distributorID = #form.distributorID#
383:     </cfquery>
384:     <!-- Upload the file to a unique name -->
385:     <cffile
386:         destination = "#qryImagePath.enhAgencyImages#"
387:         action = "UPLOAD"
388:         nameconflict = "OVERWRITE"
389:         filefield = "edtFooterImage"
390:     >
391:
392:     <cfset cImage = file.serverFile>

```

```

393: <cfset cUserFooterImage = file.serverFile>
394:
395: <cfset cImagePath = file.serverDirectory & "\">
396: <cfset cNewImage = "#cImagePath#trim(form.agencyID)#_#file.serverFile#">
397:
398: <cfif fileExists(cNewImage)>
399:   <cfif
400:     action = "DELETE"
401:     file="#cNewImage#"
402:   >
403:   </cfif>
404:
405:   <!--- Now rename the unique uploaded file to the new name --->
406:   <cfif
407:     action = "RENAME"
408:     source = "#file.serverDirectory#\#file.serverFile#"
409:     destination="#cNewImage#"
410:   >
411:   <cfset cFooterImage = cNewImage>
412:   </cfif>
413:
414:   <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
415:     update agencyBios
416:     set agencyID
417:       distributorID = #form.agencyID#,
418:       headerImage = '#cHeaderImage#',
419:       userHeaderImage = '#cUserHeaderImage#',
420:       footerImage = '#cFooterImage#',
421:       userFooterImage = '#cUserFooterImage#',
422:       beginDate = '#form.edtBeginDate#',
423:       endDate = '#form.edtEndDate#',
424:       alternateURL = '#form.edtAlternateURL#',
425:       where agencyBios.agencyID = #form.agencyID#
426:   </cfquery>
427:
428:   <cfset client.detailID = -1>
429:   <cfset client.userName = "Agency bio was updated.">
430:   </cftransaction>
431:
432:   <cfif client.lookupID gt 0>
433:     <cflocation url="agencyBioMaint.cfm" addToken="no">
434:   <cfelse>
435:     <cflocation url="agencyBioAdm.cfm" addToken="no">
436:   </cfif>
437:   </cfif>
438:   <cfelseif isDefined("form.btnDelete")>
439:     <cflocation url="agencyBioDelete.cfm" addToken="no">
440:   <cfelseif isDefined("form.btnConfirmedDelete")>
441:     <cfset client.lookupID = -1>

```

```

442: <cfset client.detailID = -1>
443: <cfset client.userName = "Unable to delete agency bio.">
444: <cftransaction>
445:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
446:     delete from agencyBioDetail
447:     where agencyBioDetail.agencyID = #form.agencyID#
448:   </cfquery>
449:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
450:     delete from agencyBios
451:     where agencyBios.agencyID = #form.agencyID#
452:   </cfquery>
453:
454:   <cfquery name="qryImagePath" datasource="#ap_dataSource#">
455:     select distributors.enhAgencyImages
456:     from distributors
457:     where distributors.distributorID = #form.distributorID#
458:   </cfquery>
459:   <cfset lstDirectory = "">
460:   <cfdirectory
461:     name = "lstDirectory"
462:     action = "list"
463:     directory = "#qryImagePath.enhAgencyImages#"
464:     filter="#form.agencyID# *.*"
465:   >
466:
467:   <cfloop query="lstDirectory">
468:     <cffile
469:       action="delete"
470:       file="#qryImagePath.enhAgencyImages#lstDirectory.name#"
471:     >
472:   </cfloop>
473:
474:   <cfset client.userName = "Agency Bio was deleted.">
475:   </cftransaction>
476:   <cflocation url="agencyBioAdm.cfm" addtoken="no">
477: </cfif>
478:
479: <cfset client.lookupID = -1>
480: <cfset client.detailID = -1>
481: <cfset client.imageType = -1>
482: <!-- Get ID number from edit -->
483: <cfloop collection="#form#" item="cName">
484:   <cfif ucase(left(cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
485:     <cfset cValue = mid(cName#, 5, len(cName#)-6)>
486:     <cfset client.lookupID = form.agencyID>
487:     <cfset client.detailID = val(cValue)>
488:     <cfset client.imageType = -1>
489:   </cfif>
490:

```

```

491: <cfif client.lookupID gt -1 and client.detailID gt -1>
492: <cflocation url="agencyBioMaint.cfm" addToken="no">
493: </cfif>
494: </cfloop>
495:
496: <!--- Get ID number for delete detail item --->
497: <cfloop collection="#form#" item="cName">
498: <cfif ucase(left(#cName#,6)) is "DELETE" and findNoCase(".X", #cName#,1) gt 0>
499: <cfset cValue = mid(#cName#, 7, len(#cName#)-8)>
500: <cfset client.lookupID = form.agencyID>
501: <cfset client.detailID = val(cValue)>
502: <cfset client.imageType = -1>
503: </cfif>
504:
505: <cfif client.lookupID gt -1 and client.detailID gt -1>
506: <cfset client.userName = "Unable to delete paragraph.">
507: <cfquery name="qryDelete" dataSource="#ap_dataSource#">
508:     delete from agencyBioDetail
509:     where agencyBioDetail.agencyBioDetailID = #client.detailID#
510: </cfquery>
511: <cfset client.detailID = -1>
512: <cfset client.userName = "paragraph deleted.">
513: <cflocation url="agencyBioMaint.cfm" addToken="no">
514: </cfif>
515: </cfloop>
516:
517: <!--- If anything else, then go back to the admin page --->
518: <cflocation url="agencyBioAdm.cfm" addToken="no">
519:
520:

```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3: <html>
4: <head>
5:   <title>Agency Choice</title>
6: </head>
7:
8: <body>
9:
10:   <cfloop collection="#form#" item="cName">
11:     <cfif ucase(left(cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
12:       <cfset cValue = mid(cName#, 5, len(cName#)-6)>
13:       <cfset client.lookupID = val(cValue)>
14:       <cfset client.detailID = -1>
15:       <cfset client.userName = "">
16:       <cflocation url="agencyMaint.cfm" addToken="no">
17:       <cfelseif ucase(left(cName#,7)) is "BIOEDIT" and findNoCase(".X", #cName#,1) gt 0>
18:         <cfset cValue = mid(cName#, 8, len(cName#)-9)>
19:         <cfset client.lookupID = val(cValue)>
20:         <cfset client.detailID = -1>
21:         <cfset client.userName = "">
22:         <cflocation url="agencyBioMaint.cfm" addToken="no">
23:         <cfelseif ucase(left(cName#,6)) is "BIOADD" and findNoCase(".X", #cName#,1) gt 0>
24:           <cfset cValue = mid(cName#, 7, len(cName#)-8)>
25:           <cfset client.lookupID = val(cValue)>
26:           <cfset client.detailID = -1>
27:           <cfset client.userName = "">
28:           <cflocation url="agencyBioMaint.cfm" addToken="no">
29:         </cfif>
30:       </cfloop>
31:
32:       <cfset client.lookupID = -1>
33:       <cfset client.detailID = -1>
34:       <cfset client.userName = "">
35:       <cflocation url="agencyAdm.cfm" addToken="no">
36:
37:
38:     </body>
39:   </html>
```



```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3:  <cfif client.lookupID is "-1">
4:    <cfset client.lookupID = -1>
5:    <cfset client.detailID = -1>
6:    <cfset client.userName = "">
7:    <cflocation url="AgencyAdm.cfm" addtoken="no">
8:  </cfif>
9:
10:  <cfquery name="qryGetPage" dataSource="#ap_dataSource#">
11:    select agency_id, name, distributorID
12:    from agency
13:    where agency.agency_id = #client.lookupID#
14:  </cfquery>
15:
16:  <html>
17:  <head>
18:    <title>Confirm Deletion of Agency</title>
19:    <link rel="stylesheet" href="style1.css" type="text/css">
20:  </head>
21:
22:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
23:    <cfinclude template="include/nocache.cfm">
24:
25:    <p><cfinclude template="include/header.cfm"></p>
26:
27:    <cfoutput>
28:
29:    <cfset client.detailID = -1>
30:    <cfset client.userName = "">
31:    <cfset client.imageType = -1>
32:
33:    <cfquery name="qryFindAgents" dataSource="#ap_dataSource#">
34:      select agent_id, firstName, 'lastName as name
35:      from agents
36:      where agents.agency_id = #client.lookupID#
37:    </cfquery>
38:
39:    <form action="agencyUpdate.cfm" method="post">
40:      <input type="hidden" name="agencyID" value="#client.lookupID#">
41:      <input type="hidden" name="edName" value="#qryGetPage.name#">
42:      <input type="hidden" name="edtDistributorID" value="#qryGetPage.distributorID#">
43:
44:      <b>'#trim(qryGetPage.name)#' Agency Deletion Confirmation</b>
45:      <br>
46:      <br>
47:      <cfif qryFindAgents.recordCount gt 0>
48:        <cfquery name="qryAgencies" dataSource="#ap_dataSource#">
49:          select agency_id, name

```



4.0 Transitional/EN

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN" >
2:
3:  <cfif not isDefined("client.lookupID")>
4:    <cflocation url="agencyAdm.cfm" addToken="no">
5:  </cfif>
6:  <cfparam name="client.userName" default="">
7:
8:  <cfquery name="qryFindAgency" datasource="#ap_dataSource#">
9:    select agency.*
10:   from agency
11:  where agency.agency_id = #client.lookupID#
12: </cfquery>
13:
14:
15:  <cfquery name="qryCommunities" dataSource="#ap_dataSource#">
16:    select communities.communityID, communities.name
17:   from communities
18:  order by communities.name
19: </cfquery>
20:
21:
22:  <cfif qryFindAgency.recordCount gt 0>
23:    <cfset nAgencyID = qryFindAgency.agency_id>
24:  <cfelse>
25:    <cfset nAgencyID = -1>
26:  </cfif>
27:
28:  <script language="JavaScript">
29:    <!--
30:    function validate(testform) {
31:      var results = "";
32:      var lResult = true;
33:
34:      if (testform.edtName.value == "") {
35:        results = results + "** Please enter the agency's name.\r";
36:        lResult = false;
37:      }
38:      if (testform.edtPhone.value == "") {
39:        results = results + "** Please enter the agency's phone.\r";
40:        lResult = false;
41:      }
42:      if (testform.edtAddress.value == "") {
43:        results = results + "** Please enter the agency's address.\r";
44:        lResult = false;
45:      }
46:      if (testform.edtCity.value == "") {
47:        results = results + "** Please enter the agency's city.\r";
48:        lResult = false;
49:      }

```

```

50: if (testform.edtState.value == "") {
51: results = results + " * Please enter the agency's state.\r";
52: lResult = false;
53: }
54: if (testform.edtZipcode.value == "") {
55: results = results + " * Please enter the agency's zipcode.\r";
56: lResult = false;
57: }
58: if (testform.edtEmail.value == "") {
59: results = results + " * Please enter the agency's email address.\r";
60: lResult = false;
61: }
62: if (testform.edtFax.value == "") {
63: results = results + " * Please enter the agency's fax number.\r";
64: lResult = false;
65: }
66: if (testform.edtDesc.value == "") {
67: results = results + " * Please enter the agency's description.\r";
68: lResult = false;
69: }
70:
71: if ((testform.edtDistributorID.value == "0") || (testform.edtDistributorID.selectedIndex == 0)) {
72: results = results + " * Please select a distributor for this agency.\r";
73: lResult = false;
74: }
75:
76: if (!lResult) {
77: window.alert(results);
78: }
79: return lResult;
80: }
81: -->
82: </script>
83:
84: <html>
85: <head>
86: <cfoutput>
87: <title>#client.backofficeName# Backoffice Agency Maintenance</title>
88: </cfoutput>
89: <link rel="stylesheet" href="style1.css" type="text/css">
90: </head>
91:
92: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
93: <cfinclude template="include\nocache.cfm">
94:
95: <p><cfinclude template="include\header.cfm"></p>
96:
97: <cfoutput>
98:

```

```

99: <form action="agencyUpdate.cfm" enctype="multipart/form-data" method="post" onsubmit="return validate(this)">
100:   <input type="hidden" name="agencyID" value="#AgencyID#">
101:   <input type="hidden" name="editCountry" value="USA">
102:   <input type="hidden" name="originalmainImage" value="#qryFindAgency.mainImage#">
103:   <input type="hidden" name="originalmainUserFilename" value="#qryFindAgency.userFilename#">
104:   <input type="hidden" name="originalheaderImage" value="#qryFindAgency.headerFilename#">
105:   <input type="hidden" name="originalheaderUsername" value="#qryFindAgency.headerUsername#">
106:   <input type="hidden" name="originalfooterImage" value="#qryFindAgency.footerFilename#">
107:   <input type="hidden" name="originalfooterUsername" value="#qryFindAgency.footerUsername#">
108:
109:   <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
110:     <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Agency Maintenance</b></span>
111:     <cfif client.lookupID is -1>
112:       <b>Create a new Agency</b>
113:     </cfif>
114:   </td></tr>
115:
116:   <CFIF client.userMessage is not "">
117:     <tr bgcolor="eeeeee">
118:       <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td>
119:     </tr>
120:     <tr bgcolor="eeeeee"><td colspan="5"><b>CFIF</b></td></tr>
121:   </CFIF>
122:   <cfset client.userMessage = "">
123:
124:   <tr bgcolor="##eeeeee">
125:     <td width="15%"><b>Agency Name:</b></td>
126:     <td width="34%"><input type="text" name="editName" value="#qryFindAgency.name#"></td>
127:     <td width="2%"><b>Edit</b></td>
128:     <td width="15%"><b>Phone:</b></td>
129:     <td width="34%"><input type="text" name="editPhone" value="#qryFindAgency.phone#"></td>
130:   </tr>
131:
132:   <tr bgcolor="##eeeeee">
133:     <td width="15%"><b>Address:</b></td>
134:     <td width="34%"><input type="text" name="editAddress" value="#qryFindAgency.address#"></td>
135:     <td width="2%"><b>Edit</b></td>
136:     <td width="15%"><b>Web Site:</b></td>
137:     <td width="34%"><input type="text" name="editWebSite" value="#qryFindAgency.url_name#"></td>
138:   </tr>
139:
140:   <tr bgcolor="##eeeeee">
141:     <td width="15%"><b>City:</b></td>
142:     <td width="34%"><input type="text" name="editCity" value="#qryFindAgency.city#"></td>
143:     <td width="2%"><b>Edit</b></td>
144:     <td width="15%"><b>Email:</b></td>
145:     <td width="34%"><input type="text" name="editEmail" value="#qryFindAgency.email#"></td>
146:   </tr>
147:   <tr bgcolor="##eeeeee">

```

```

148: <td width="15%"><b>State:</b></td>
149: <td width="34%"><input type="text" name="edtState" value="#qryFindAgency.state#" size="2"></td>
150: <td width="2%"><b>Agency:</b></td>
151: <td width="15%">Master Agency:</td>
152: <td width="34%">
153: <cfquery name="qryMastAgency" dataSource="#ap_dataSource#">
154:   select agency.agency_id, agency.name
155:   from agency
156:   join securityAccess on
157:     securityAccess.entityType = #ap_securityMastAgency#
158:     and securityAccess.entityID = agency.agency_id
159:     and securityAccess.hierarchyID like '#client.hierarchyID#%'
160:   where agency.parentAgency = 0
161:   and agency.agency_id <> #client.lookupID#
162:   order by agency.name
163: </cfquery>
164:
165: <select name="parentAgency">
166:   <option value="0">None
167:   <cfloop query="qryMastAgency">
168:     <option value="#qryMastAgency.agency_id#"><cfif qryFindAgency.parentAgency is qryMastAgency.agency_id>
selected</cfif>#qryMastAgency.name#
      </cfloop>
    </select>
  </td>
</tr>
<tr bgcolor="#eeeeee">
173: <td width="15%"><b>Zipcode:</b></td>
174: <td width="34%"><input type="text" name="edtZipcode" value="#qryFindAgency.zip#" size="10"></td>
175: <td colspan="3"><b>Remove Image?</b></td>
176: <td colspan="3">
177:   <tr bgcolor="#eeeeee">
178:     <td width="15%"><b>Fax:</b></td>
179:     <td width="34%"><input type="text" name="edtFax" value="#qryFindAgency.fax#"></td>
180:     <td width="2%"><b>Specialty:</b></td>
181:     <td width="15%"><input type="text" name="edtSpecialty" value="#qryFindAgency.specialty#"></td>
182:     <td colspan="2">
183:       <tr bgcolor="#eeeeee">
184:         <td width="15%"><b>Main Image:</b></td>
185:         <td width="34%"><input type="file" name="edtMainImage"></td>
186:         <td width="2%"><b>Remove Image?</b></td>
187:         <td colspan="2">
188:           <cfif trim(qryFindAgency.mainImage) is not "">
189:             <cfset cFilename = getFileFromPath(qryFindAgency.mainImage)>
190:             <cfset cFilename = replace(cFilename, "#qryFindAgency.agency_id_", "")>
191:             <i>Currently: #cFilename#</i><b>Remove Image?</b>
192:             <input type="checkbox" name="chkMainImage">
193:           </cfif>
194:         </td>
195:       </tr>

```

```

196:      <nbsp;
197:    </cfif>
198:  </td>
199: </tr>
200: <tr bgcolor="#ffffff">
201:   <td width="15%">Header Image:</td>
202:   <td width="34%"><input type="file" name="edtHeaderImage"></td>
203:   <td width="2%"><nbsp;
204:   <td colspan="2">
205:     <cfif trim(qryFindAgency.headerFilename) is not "">
206:       <cfset cFilename = getFileFromPath(qryFindAgency.headerFilename)>
207:       <cfset cFilename = replace(cFilename, "#qryFindAgency.agency_id#", "")>
208:       <i>Currently: #cFilename#</i><nbsp;
209:       <input type="checkbox" name="chkHeaderImage"> Remove Image?
210:     <cfelse>
211:       <nbsp;
212:     </cfif>
213:   </td>
214: </tr>
215: <tr bgcolor="#ffffff">
216:   <td width="15%">Footer Image:</td>
217:   <td width="34%"><input type="file" name="edtFooterImage"></td>
218:   <td width="2%"><nbsp;
219:   <td colspan="2">
220:     <cfif trim(qryFindAgency.footerFilename) is not "">
221:       <cfset cFilename = getFileFromPath(qryFindAgency.footerFilename)>
222:       <cfset cFilename = replace(cFilename, "#qryFindAgency.agency_id#", "")>
223:       <i>Currently: #cFilename#</i><nbsp;
224:       <input type="checkbox" name="chkFooterImage"> Remove Image?
225:     <cfelse>
226:       <nbsp;
227:     </cfif>
228:   </td>
229: </tr>
230:
231: <tr bgcolor="#ffffff">
232:   <td width="15%"><b>Description:</b></td>
233:   <td colspan="4">
234:     <textarea name="edtDesc" rows="5" cols="60" wrap="virtual">#trim(qryFindAgency.description)#</textarea>
235:   </td>
236: </tr>
237:
238: <cfif client.currentEntityType is 1>
239:   <cfquery name="qryPortals" dataSource="#ap_dataSource#">
240:     select portals.portalID, portals.name
241:     from portals
242:     order by name
243:   </cfquery>
244:   <tr bgcolor="#ffffff">

```

```

245:         <td width="15%">Portal:</td>
246:         <td colspan="4">
247:             <select name="edtPortalID">
248:                 <option value="1"><cfif qryFindAgency.portalID lte 0 or trim(qryFindAgency.portalID) is ""> selected</cfif>>Not
Assigned
249:                 <cfloop query="qryPortals">
250:                     <option value="#qryPortals.portalID#"><cfif qryPortals.portalID is qryFindAgency.portalID>
selected</cfif>>#qryPortals.name#
251:                 </cfloop>
252:                 </select>
253:             </td>
254:         </tr>
255:         <cfelse>
256:             <input type="hidden" name="edtPortalID" value="#client.currentPortalID#">
257:         </cfif>
258:
259:         <cfif client.currentEntityType lte ap_securityPortal>
260:             <cfquery name="qryDist" dataSource="#ap_dataSource#">
261:                 select distributors.distributorID, distributors.name as distName
262:                 from distributors
263:                 join securityAccess on
264:                     (securityAccess.entityType = #ap_securityMastDist# or securityAccess.entityType = #ap_securityDist#)
265:                     and securityAccess.entityID = distributors.distributorID
266:                     and securityAccess.hierarchyID like '#client.hierarchyID#',
267:                 order by distName
268:             </cfquery>
269:             <tr bgcolor="#eeeeee">
270:                 <td width="15%">Distributor:</td>
271:                 <td colspan="4">
272:                     <select name="edtDistributorID">
273:                         <option value="0"><cfif qryFindAgency.distributorID lte 0 or trim(qryFindAgency.distributorID) is "">
selected</cfif>>Not Assigned
274:                         <cfloop query="qryDist">
275:                             <option value="#qryDist.distributorID#"><cfif qryDist.distributorID is qryFindAgency.distributorID>
selected</cfif>>#qryDist.distName#
276:                         </cfloop>
277:                         </select>
278:                     </td>
279:                 </tr>
280:                 <cfelse>
281:                     <cfif qryFindAgency.recordCount is 0>
282:                         <input type="hidden" name="edtDistributorID" value="#client.currentDistributorID#">
283:                     <cfelse>
284:                         <input type="hidden" name="edtDistributorID" value="#qryFindAgency.distributorID#">
285:                     </cfif>
286:                 </cfif>
287:
288:                 <tr bgcolor="#eeeeee">
289:                     <cfif qryFindAgency.recordCount is 0>

```



```
290:         <td colspan="5">
291:             <input type="submit" name="btnUpdate" value="Add Agency">
292:             <input type="reset" value="Reset Info">
293:         </td>
294:     <cfelse>
295:         <td colspan="4">
296:             <input type="submit" name="btnUpdate" value="Update Agency Info">
297:             <input type="reset" value="Reset Info">
298:         </td>
299:         <td align="right">
300:             <input type="submit" name="btnDelete" value="Delete Agency">
301:         </td>
302:     </cfif>
303: </tr>
304: </table>
305: </form>
306:
307: </cfoutput>
308:
309: </body>
310: </html>
```

Transition 4.0

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfinclude template="include\checkSecurity.cfm">
4:
5: <cfparam name="client.jumpToPage" default="">
6:
7: <cfif client.gotoPage is "">
8:   <cflocation url="messages.cfm" addToken="no">
9: </cfif>
10:
11: <cfset client.lookupID = -1>
12: <cfset client.detailID = -1>
13: <cfset client.lookupDistID = -1>
14: <cfset client.lookupAgencyID = -1>
15:
16: <cfif client.currentEntityType gte #ap_securityMastAgency#>
17:   <cfset client.lookupAgencyID = currentAgencyID>
18:   <cflocation url="#client.gotoPage#" addToken="no">
19: </cfif>
20:
21:
22: <cfquery name="qryAgency" dataSource="#ap_dataSource#">
23:   select agency.agency_id, agency.name as agencyName
24:   from agency
25:   join securityAccess on
26:     (securityAccess.entityType = #ap_securityMastAgency# or securityAccess.entityType = #ap_securityAgency#)
27:     and securityAccess.entityID = agency.agency_id
28:     and securityAccess.hierarchyID like '#client.hierarchyID#%'
29:   order by agencyName
30: </cfquery>
31:
32: <cfif qryAgency.recordCount is 0>
33:   <cfset client.userName = "There are no agencies for selection.">
34:   <cflocation url="messages.cfm" addToken="no">
35: <cfelseif qryAgency.recordCount is 1>
36:   <cfset client.lookupAgencyID = qryAgency.agency_id>
37:   <cflocation url="#client.gotoPage#" addToken="no">
38: </cfif>
39:
40: <html>
41: <head>
42:   <cfoutput>
43:     <title>#client.backofficeName# Backoffice Select Agency</title>
44:   </cfoutput>
45:   <link rel="stylesheet" href="style1.css" type="text/css">
46: </head>
47:
48:
49: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">

```



11/29/2000 5:04:39 PM  
S:\FullImpact\FullImpact\admin\agencySelected.cfm

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <html>
4: <head>
5:   <title>Agency Selected</title>
6: </head>
7:
8: <body>
9:
10:  <cfif isDefined("btnSelectAgency")>
11:    <cfset client.lookupAgencyID = form.edtAgencyID>
12:    <cflocation url="#client.gotoPage#" addToken="no">
13:  </cfif>
14:
15:  <cflocation url="messages.cfm" addToken="no">
16:
17: </body>
18: </html>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfif not isDefined("form.agencyID")>
4:   <cfset client.lookupID = -1>
5:   <cfset client.detailID = -1>
6:   <cfset client.userName = "">
7:   <cflocation url="agencyAdm.cfm" addtoken="no">
8: </cfif>
9:
10: <cfquery name="qryFindAgency" datasource="#ap_dataSource#">
11:   select agency_id, name
12:   from agency
13:   where agency.agency_id = #form.agencyID#
14: </cfquery>
15:
16: <cfinclude template="include\clearOldFields.cfm">
17: <cfset client.userName = "">
18:
19: <!--- Save form values in case something is wrong -->
20:
21: <cfif isDefined("form.btnUpdate")>
22:   <cfif qryFindAgency.recordCount is 0>
23:     <cfset client.lookupID = -1>
24:     <cfset client.detailID = -1>
25:     <cfset client.userName = "There was an error while creating the agency.">
26:     <cftransaction>
27:       <cfset cName = preservesingleQuotes(form.edtName)>
28:       <cfset cAddress = preservesingleQuotes(form.edtAddress)>
29:       <cfset cCity = preservesingleQuotes(form.edtCity)>
30:       <cfset cSpecialty = preservesingleQuotes(form.edtSpecialty)>
31:       <cfset cDesc = preservesingleQuotes(form.edtDesc)>
32:
33:       <cfquery name="qryInsert" datasource="#ap_dataSource#">
34:         insert into agency
35:           (name, address, city, state, zip, country, phone, fax, URL_name, email,
36:            specialty, description, parentAgency, distributorID, portalID)
37:         values ('#cName#', '#cAddress#', '#cCity#', '#form.edtState#',
38:                '#form.edtZipcode#', '#form.edtCountry#', '#form.edtPhone#',
39:                '#form.edtFax#', '#form.edtWebsite#', '#form.edtEmail#',
40:                '#cSpecialty#', '#cDesc#', '#form.parentAgency#',
41:                '#form.edtDistributorID#', '#form.edtPortalID#)
42:       </cfquery>
43:
44:       <cfquery name="qryGetID" datasource="#ap_dataSource#">
45:         select max(agency_id) as lastID
46:         from agency
47:       </cfquery>
48:       <cfset nAgencyID = qryGetID.lastID>
49:

```

```

50: <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
51: select distributors.agencyImages
52: from distributors
53: where distributors.distributorID = #form.edtDistributorID#
54: </cfquery>
55:
56: <cfif trim(form.edtMainImage) is "">
57:   <cfset cImage = form.originalMainImage>
58:   <cfset cUserName = form.originalMainUserName>
59: <cfelse>
60:
61:   <!--- Upload the file to a unique name --->
62:   <cffile
63:     destination = "#qryImagePath.agencyImages#"
64:     action = "UPLOAD"
65:     nameconflict = "OVERWRITE"
66:     filefield = "edtMainImage"
67:   >
68:
69:   <cfset cImage = file.serverFile>
70:   <cfset cUserName = file.serverFile>
71:
72:   <cfset cImagePath = file.serverDirectory & "\">
73:   <cfset cNewImage = "#cImagePath#qryGetID.lastID#_#file.serverFile#">
74:
75:   <cfif fileExists(cNewImage)>
76:     <cffile
77:       action = "DELETE"
78:       file="#cNewImage#"
79:     >
80:   </cfif>
81:
82:   <!--- Now rename the unique uploaded file to the new name --->
83:   <cffile
84:     action = "RENAME"
85:     source = "#file.serverDirectory#\#file.serverFile#"
86:     destination="#cNewImage#"
87:   >
88:
89:   <cfset cImage = cNewImage>
90: </cfif>
91:
92: <cfif trim(form.edtMainImage) is "">
93:   <cfset cHeaderImage = form.originalHeaderImage>
94:   <cfset cHeaderUsername = form.originalHeaderUsername>
95: <cfelse>
96:
97:   <!--- Upload the file to a unique name --->
98:   <cffile

```

```

99:     destination = "#qryImagePath.agencyImages#"
100:     action = "UPLOAD"
101:     nameconflict = "OVERWRITE"
102:     filefield = "edtHeaderImage"
103: >
104:
105: <cfset cHeaderImage = file.serverFile>
106: <cfset cHeaderUsername = file.serverFile>
107:
108: <cfset cImagePath = file.serverDirectory & "\">
109: <cfset cNewImage = "#cImagePath#qryGetID.lastID#_#file.serverFile#">
110:
111: <cfif fileExists(cNewImage)>
112:     <cffile
113:         action = "DELETE"
114:         file="#cNewImage#"
115:     >
116: </cfif>
117:
118: <!-- Now rename the unique uploaded file to the new name -->
119: <cffile
120:     action = "RENAME"
121:     source = "#file.serverDirectory#\#file.serverFile#"
122:     destination="#cNewImage#"
123: >
124:
125: <cfset cHeaderImage = cNewImage>
126: </cfif>
127:
128: <cfif trim(form.edtMainImage) is "">
129:     <cfset cFooterImage = form.originalFooterImage>
130:     <cfset cFooterUsername = form.originalFooterUsername>
131: <cfelse>
132:
133:     <!-- Upload the file to a unique name -->
134:     <cffile
135:         destination = "#qryImagePath.agencyImages#"
136:         action = "UPLOAD"
137:         nameconflict = "OVERWRITE"
138:         filefield = "edtFooterImage"
139:     >
140:
141:     <cfset cFooterImage = file.serverFile>
142:     <cfset cFooterUsername = file.serverFile>
143:
144:     <cfset cImagePath = file.serverDirectory & "\">
145:     <cfset cNewImage = "#cImagePath#qryGetID.lastID#_#file.serverFile#">
146:
147:     <cfif fileExists(cNewImage)>

```

```

148: <cffile
149:   action = "DELETE"
150:   file="#cNewImage#"
151: >
152: </cffif>
153:
154: <!-- Now rename the unique uploaded file to the new name -->
155: <cffile
156:   action = "RENAME"
157:   source = "#file.serverDirectory#\#file.serverFile#"
158:   destination="#cNewImage#"
159: >
160:
161: <cfset cFooterImage = cNewImage>
162: </cfif>
163:
164: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
165:   update agency
166:   set mainImage = 'cImage#',
167:       username = 'cUsername#',
168:       headerFilename = 'cHeaderImage#',
169:       headerUsername = 'cHeaderUsername#',
170:       footerFilename = 'cFooterImage#',
171:       footerUsername = 'cFooterUsername#',
172:       where agency.agency_id = #qryGetID.lastID#
173: </cfquery>
174:
175:
176:
177: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
178:   insert into roomValues
179:     (distributorID, agencyID, sortOrder, room)
180:   select #form.edtDistributorID#, #nAgencyID# as agencyID, sortOrder, room
181:   from roomValues
182:   where roomValues.agencyID = 0
183:   and roomValues.distributorID = #form.edtDistributorID#
184: </cfquery>
185:
186: <cfset nUpdateID = #qryGetID.lastID#>
187: <cfset nUpdateType = #ap_securityMastAgency#>
188: <cfset nUpdateAction = "ADD">
189: <cfinclude template="include\makeSecurityTree.cfm">
190:
191:
192: <cfset client.userName = form.edtName & " added.">
193: </cftransaction>
194:
195:
196: <cflocation url="agencyAdm.cfm" addToken="no">

```



```

197: <cfelse>
198: <cfset client.lookupID = -1>
199: <cfset client.detailID = -1>
200: <cfset client.userName = "There was an error while updating the agency information.">
201: <cftransaction>
202: <cfset cName = preserveSingleQuotes(form.edtName)>
203: <cfset cAddress = preserveSingleQuotes(form.edtAddress)>
204: <cfset cCity = preserveSingleQuotes(form.edtCity)>
205: <cfset cSpecialty = preserveSingleQuotes(form.edtSpecialty)>
206: <cfset cDesc = preserveSingleQuotes(form.edtDesc)>
207:
208: <cfquery name="qryOldDistID" dataSource="#ap_dataSource#">
209:   select distributorID
210:   from agency
211:   where agency.agency_id = #form.agencyID#
212: </cfquery>
213: <cfset nOldID = qryOldDistID.distributorID>
214:
215: <cfif isDefined("form.chkMainImage")>
216:   <cfset cImage = "">
217:   <cfset cUserImage = "">
218:   <cfelseif trim(form.edtMainImage) is "">
219:     <cfset cImage = form.originalMainImage>
220:     <cfset cUserImage = form.originalMainUsername>
221:   <cfelse>
222:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
223:       select distributors.agencyImages
224:       from distributors
225:       where distributors.distributorID = #form.edtDistributorID#
226:     </cfquery>
227:
228:     <!--- Upload the file to a unique name --->
229:     <cfif
230:       destination = "#qryImagePath.agencyImages#"
231:       action = "UPLOAD"
232:       nameConflict = "OVERWRITE"
233:       filefield = "edtMainImage"
234:     >
235:
236:     <cfset cImage = file.serverFile>
237:     <cfset cUserImage = file.serverFile>
238:
239:     <cfset cImagePath = file.serverDirectory & "\">
240:     <cfset cNewImage = "#cImagePath#form.agencyID#_#file.serverFile#">
241:
242:     <cfif fileExists(cNewImage)>
243:       <cfif
244:         action = "DELETE"
245:         file="#cNewImage#"

```

```

246: >
247: </cfif>
248:
249: <!-- Now rename the unique uploaded file to the new name -->
250: <cffile
251:   action = "RENAME"
252:   source = "#file.serverDirectory#\#file.serverFile#"
253:   destination="#cNewImage#"
254: >
255:
256: <cfset cImage = cNewImage>
257: </cfif>
258:
259:
260: <cfif isDefined("form.chkHeaderImage")>
261:   <cfset cHeaderImage = "">
262:   <cfset cHeaderUsername = "">
263:   <cfelseif trim(form.edtHeaderImage) is "">
264:     <cfset cHeaderImage = form.originalHeaderImage>
265:     <cfset cHeaderUsername = form.originalHeaderUsername>
266:   <cfelse>
267:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
268:       select distributors.agencyImages
269:       from distributors
270:       where distributors.distributorID = #form.edtDistributorID#
271:     </cfquery>
272:
273:     <!-- Upload the file to a unique name -->
274:     <cffile
275:       destination = "#qryImagePath.agencyImages#"
276:       action = "UPLOAD"
277:       nameconflict = "OVERWRITE"
278:       filefield = "edtHeaderImage"
279:     >
280:
281:     <cfset cHeaderImage = file.serverFile>
282:     <cfset cHeaderUsername = file.serverFile>
283:
284:     <cfset cImagePath = file.serverDirectory & "\">
285:     <cfset cNewImage = "#cImagePath#form.agencyID#_#file.serverFile#">
286:
287:     <cfif fileExists(cNewImage)>
288:       <cffile
289:         action = "DELETE"
290:         file="#cNewImage#"
291:       >
292:     </cfif>
293:
294:     <!-- Now rename the unique uploaded file to the new name -->

```

```

295: <cffile
296:   action = "RENAME"
297:   source = "#file.serverDirectory#\#file.serverFile#"
298:   destination="#cNewImage#"
299: >
300:
301: <cfset cHeaderImage = cNewImage>
302: </cfif>
303:
304: <cfif isDefined("form.chkFooterImage")>
305:   <cfset cFooterImage = "">
306:   <cfset cFooterUsername = "">
307:   <cfelseif trim(form.edtFooterImage) is "">
308:     <cfset cFooterImage = form.originalFooterImage>
309:     <cfset cFooterUsername = form.originalFooterUsername>
310:   <cfelse>
311:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
312:       select distributors.agencyImages
313:       from distributors
314:       where distributors.distributorID = #form.edtDistributorID#
315:     </cfquery>
316:
317:     <!--- Upload the file to a unique name --->
318:     <cffile
319:       destination = "#qryImagePath.agencyImages#"
320:       action = "UPLOAD"
321:       nameconflict = "OVERWRITE"
322:       filefield = "edtFooterImage"
323:     >
324:
325:     <cfset cFooterImage = file.serverFile>
326:     <cfset cFooterUsername = file.serverFile>
327:
328:     <cfset cImagePath = file.serverDirectory & "\">
329:     <cfset cNewImage = "#cImagePath##form.agencyID#_#file.serverFile#">
330:
331:     <cfif fileExists(cNewImage)>
332:       <cffile
333:         action = "DELETE"
334:         file="#cNewImage#"
335:       >
336:     </cfif>
337:
338:     <!--- Now rename the unique uploaded file to the new name --->
339:     <cffile
340:       action = "RENAME"
341:       source = "#file.serverDirectory#\#file.serverFile#"
342:       destination="#cNewImage#"
343:     >

```

```

344:
345:
346:
347:
348:
349:
350:
351:
352:
353:
354:
355:
356:
357:
358:
359:
360:
361:
362:
363:
364:
365:
366:
367:
368:
369:
370:
371:
372:
373:
374:
375:
376:
377:
378:
379:
380:
381:
382:
383:
384:
385:
386:
387:
388:
389:
390:
391:
392:

```

```

<cfset cFooterImage = cNewImage>
</cfif>

<cfquery name="qryUpdate" dataSource="#ap_dataSource#">
update agency
set name      = 'cName#',
address      = 'cAddress#',
city         = 'cCity#',
state        = 'form.edtState#',
zip          = 'form.edtZipcode#',
country      = 'form.edtCountry#',
phone        = 'form.edtPhone#',
fax          = 'form.edtFax#',
URL_name     = 'form.edtWebSite#',
email        = 'form.edtEmail#',
specialty    = 'cSpecialty#',
mainImage    = 'cImage#',
userFilename = 'cUserImage#',
headerFilename = 'cHeaderImage#',
headerUsername = 'cHeaderUsername#',
footerFilename = 'cFooterImage#',
footerUsername = 'cFooterUsername#',
Description  = 'cDesc#',
parentAgency = 'form.parentAgency#',
distributorID = 'form.edtDistributorID#',
portalID     = 'form.edtPortalID#
where agency.agency_id = #form.agencyID#
</cfquery>

<!--- Update BIO distributor ID --->

<cfquery name="qryUpdate" dataSource="#ap_dataSource#">
update agents
set distributorID = #form.edtDistributorID#
where agents.agency_id = #form.agencyID#
</cfquery>

<cfquery name="qryUpdate" dataSource="#ap_dataSource#">
update prop_main
set distributorID = #form.edtDistributorID#
where prop_main.agency_id = #form.agencyID#
</cfquery>

<cfset nUpdateID      = #form.agencyID#>
<cfset nUpdateType    = #ap_securityMastAgency#>
<cfset nUpdateAction  = "UPDATE">
<cfinclude template="include\makeSecurityTree.cfm">

```

```

393:
394:     <cfset client.userName = form.edtName & " updated.">
395:   </cftransaction>
396:   <cflocation url="agencyAdm.cfm" addToken="no">
397: </cfif>
398:
399:   <cfelseif isDefined("form.btnDelete")>
400:     <cflocation url="agencyDelete.cfm" addToken="no">
401:   <cfelseif isDefined("form.btnConfirmedDelete")>
402:
403:   <cfset client.lookupID = -1>
404:   <cfset client.detailID = -1>
405:   <cfset client.userName = "Unable to delete #form.edtName#.">
406: </cftransaction>
407:   <cfif isDefined("form.moveAgency")>
408:     <cfquery name="qryMoveAgents" datasource="#ap_dataSource#">
409:       update agents
410:       set agency_id = #form.moveAgency#
411:       where agency_id=#form.agencyID#
412:     </cfquery>
413:   </cfif>
414:
415:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
416:     delete from roomValues
417:     where roomValues.agencyID = #form.agencyID#
418:   </cfquery>
419:
420:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
421:     delete from agency
422:     where agency.agency_id = #form.agencyID#
423:   </cfquery>
424:
425:   <cfquery name="qryImagePath" datasource="#ap_dataSource#">
426:     select distributors.agencyImages
427:     from distributors
428:     where distributors.distributorID = #form.edtDistributorID#
429:   </cfquery>
430:   <cfset lstDirectory = "">
431:   <cfdirectory
432:     name = "lstDirectory"
433:     action = "list"
434:     directory = "#qryImagePath.agencyImages#"
435:     filter="#form.agencyID# *.*"
436:   >
437:
438:   <cfloop query="lstDirectory">
439:     <cffile
440:       action="delete"
441:       file="#qryImagePath.agencyImages#lstDirectory.name#"

```

```
442: >
443: </cfloop>
444:
445:
446: <cfset nUpdateID = #form.agencyID#>
447: <cfset nUpdateType = #ap_securityMastAgency#>
448: <cfset nUpdateAction = "DELETE">
449: <cfinclude template="include\makeSecurityTree.cfm">
450:
451: <cfset client.userName = form.edtName & " deleted.">
452: </cftransaction>
453: <cflocation url="agencyAdm.cfm" addToken="no">
454: <cfelseif isDefined("form.btnCancelDelete")> <!-- Cancel detail edit -->
455: <cfset client.lookupID = #form.agencyID#>
456: <cfset client.detailID = -1>
457: <cfset client.imageType = -1>
458: <cfset client.userName = "Deletion canceled.">
459: <cflocation url="agencyMaint.cfm" addToken="no">
460: </cfif>
461:
462: <cflocation url="agencyAdm.cfm" addToken="no">
```

-----  
 11/29/2000 5:04:41 PM  
 S:\FullImpact\FullImpact\admin\agentAdm.cfm  
 -----

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfset client.gotoPage = "agentAdm.cfm">
4:
5: <cfparam name="URL.sortBy" default="name">
6: <cfset client.lookupID = -1>
7: <cfset client.detailID = -1>
8: <cfset client.lookupDistID = -1>
9: <cfset client.lookupAgencyID = -1>
10:
11: <!-- Display rows -->
12: <cfparam name="nStartFrom" default="1">
13: <cfparam name="ntoDisplay" default="#client.displayRows#">
14: <cfparam name="nEnd" default="#client.displayRows#">
15:
16:
17: <cfquery name="qryEditList" dataSource="#ap_dataSource#">
18:   select agents.agent_id,
19:     agents.lastname + ', ' + agents.firstname as name,
20:     agents.specialty,
21:     agency.name as agencyName,
22:     agentBios.agentID as agentBioID
23:   from agents
24:   join securityAccess on
25:     securityAccess.entityType = #ap_securityAgent#
26:   and securityAccess.entityID = agents.agent_id
27:   and securityAccess.hierarchyID like '#client.hierarchyID#%'
28:   left outer join agency on agency.agency_id = agents.agency_id
29:   left outer join agentBios on agentBios.agentID = agents.agent_id
30:   order by #url.sortBy#
31: </cfquery>
32:
33: <html>
34: <head>
35:   <cfoutput>
36:     <title>#client.backofficeName# Backoffice</title>
37:   </cfoutput>
38:   <link rel="stylesheet" href="style1.css" type="text/css">
39: </head>
40:
41:
42: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
43: <cfinclude template="include/nocache.cfm">
44: <p><cfinclude template="include/header.cfm"></p>
45:
46: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
47:   <tr bgcolor="#cccc99">
48:     <td colspan="5">
49:       <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">

```

```

50: <tr>
51:   <td align="left">
52:     <span class="h2"><b>Agent Administration</b></span>
53:   </td>
54:   <td align="right">
55:     <cfif #ntoDisplay# gte qryEditList.recordCount>
56:       <cfset ctoDisplay = min(qryEditList.recordCount, #ntoDisplay#)>
57:     </cfif>
58:     <cfif qryEditList.recordCount gte #ntoDisplay#>
59:       <cfset ctoDisplay = min(qryEditList.recordCount, #nEnd#)>
60:     </cfif>
61:     <cfset cstartFrom = min(qryEditList.recordCount, #nStartFrom#)>
62:     <cfoutput>Viewing records #cstartFrom# to #ctoDisplay# out of #qryEditList.recordCount#</cfoutput>
63:   </td>
64: </tr>
65: </table>
66: </td>
67: </tr>
68:
69: <cfif trim(client.userName) is not "">
70:   <tr bgcolor="#cccc99">
71:     <td colspan="5" align="center">
72:       <cfoutput>&nbsp;&nbsp;&nbsp;&nbsp;<b>#client.userName#</b></cfoutput>
73:     </td>
74:   </tr>
75: </cfif>
76:
77: <cfset client.userName = "">
78: <cfset client.lookupID = -1>
79: <cfset client.detailID = -1>
80:
81: <cfif client.currentEntityType lt ap_securityAgent>
82:   <tr bgcolor="#cccc99">
83:     <td colspan="5">
84:       &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="agentMaint.cfm">Add an agent</a>
85:     </td>
86:   </tr>
87: </cfif>
88:
89: <tr bgcolor="#cccccc">
90:   <td>Sort by <a href="agentAdm.cfm?SortBy=name"><b>Name</b></a></td>
91:   <td>Sort by <a href="agentAdm.cfm?SortBy=specialty"><b>Specialty</b></a></td>
92:   <td>Sort by <a href="agentAdm.cfm?SortBy=agencyName"><b>Agency</b></a></td>
93:   <td align="center">Agent Info</td>
94:   <td align="center">Enhanced Bio</td>
95: </tr>
96:
97:
98: <CFIF qryEditList.recordCount is 0>

```



```

99:   <TR><TD COLSPAN="5"><I>There are no agents defined</I></TD></TR></TR>
100: </CFIF>
101: <cfset lColor = True>
102: <form action="agentChoice.cfm" method="post">
103:   <cfoutput query="qryEditList" startrow="#nstartFrom#" maxrows="#ntoDisplay#">
104:     <cfset lColor = not lColor>
105:     <tr valign="center" <cfif lColor is TRUE>bgcolor="#####"</cfif>>
106:       <td>#qryEditList.name#</td>
107:       <td>#qryEditList.specialty#</td>
108:       <td>#qryEditList.agencyName#</td>
109:       <td align="center"><input type="image" name="edit#qryEditList.agent_id#" src="#ap_commonImages#edit.gif" alt="Edit"
border="0"></td>
110:       <td align="center">
111:         <cfif trim(qryEditList.agentBioID) is "" or qryEditList.agentBioID lte 0>
112:           <input type="image" name="bioAdd#qryEditList.agent_id#" src="#ap_commonImages#add.gif" alt="Add" border="0">
113:         <cfelse>
114:           <input type="image" name="bioEdit#qryEditList.agent_id#" src="#ap_commonImages#edit.gif" alt="Edit" border="0">
115:         </cfif>
116:       </td>
117:     </tr>
118:   </cfoutput>
119:   </form>
120: </table></p>
121:
122: <CFSET nPrevStart = nStartFrom-ntoDisplay>
123: <CFSET nNextStart = nStartFrom+ntoDisplay>
124: <CFSET nPrevEnd = #nPrevStart#+ntoDisplay-1>
125: <CFSET nNextEnd = #nNextStart#+ntoDisplay-1>
126: <cfif nPrevStart gte 1 or nNextStart lte qryEditList.recordCount>
127:   <table border="0" align="center">
128:     <tr>
129:       <cfif nPrevStart gte 1>
130:         <td>
131:           <form action="agentAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
132:             <input type="hidden" name="nStartFrom" value="#nPrevStart#">
133:             <input type="hidden" name="ntoDisplay" value="#ntoDisplay#">
134:             <input type="hidden" name="nEnd" value="#nPrevEnd#">
135:             <input type="submit" value="Previous #ntoDisplay#">
136:           </FORM>
137:         </td>
138:       </cfif>
139:       <cfif nNextStart lte qryEditList.recordCount>
140:         <td>
141:           <form action="agentAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
142:             <input type="hidden" name="nStartFrom" value="#nNextStart#">
143:             <input type="hidden" name="ntoDisplay" value="#ntoDisplay#">
144:             <input type="hidden" name="nEnd" value="#nNextEnd#">
145:             <cfset nLeftToShow = min(ntoDisplay, (qryEditList.recordcount - ctoDisplay))>
146:             <input type="submit" value="Next #nLeftToShow#">

```

11/29/2000 5:04:41 PM

```
147:         </form>
148:     </td>
149: </cfif>
150: </tr>
151: </table>
152: </cfif>
153:
154: </body>
155: </html>
156:
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3:  <!--
4:  <cfinclude template="include\securityTest.cfm">
5:  -->
6:
7:  <cfparam name="URL.sortBy" default="agentName">
8:  <cfset client.lookupID = -1>
9:  <cfset client.detailID = -1>
10:  <cfset client.imageType = -1>
11:  <cfset client.lookupDistID = -1>
12:  <cfset client.lookupAgencyID = -1>
13:
14:  <cfinclude template="include\clearOldFields.cfm">
15:
16:  <!-- Display rows -->
17:  <cfparam name="nStartFrom" default="1">
18:  <cfparam name="ntoDisplay" default="#client.displayRows#">
19:  <cfparam name="nEnd" default="#client.displayRows#">
20:
21:
22:  <cfquery name="qryEditList" dataSource="#ap_dataSource#">
23:    select agentBios.agentID, agents.lastName + ' ' + agents.firstName as agentName,
24:    agency.name as agencyName
25:    from agentBios
26:    join securityAccess on
27:      securityAccess.entityType = #ap_securityAgent#
28:    and securityAccess.entityID = agentBios.agentID
29:    and securityAccess.hierarchyID like '#client.hierarchyID#%'
30:    left outer join agents on agentBios.agentID = agents.agent_id
31:    left outer join agency on agents.agency_id = agency.agency_id
32:    order by #url.sortBy#
33:  </cfquery>
34:
35:  <html>
36:  <head>
37:    <cfoutput>
38:      <title>#client.backofficeName# Backoffice Agent Bio Admin</title>
39:    </cfoutput>
40:    <link rel="stylesheet" href="style1.css" type="text/css">
41:  </head>
42:
43:
44:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
45:  <cfinclude template="include\nocache.cfm">
46:  <p><cfinclude template="include\header.cfm"></p>
47:
48:  <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
49:    <tr bgcolor="#cccc99">

```





```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
2:
3: <html>
4: <head>
5: <title>Agent Bio Choice</title>
6: </head>
7:
8: <body>
9:
10: <cfloop collection="#form#" item="cName">
11: <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
12: <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
13: <cfset client.lookupID = val(cValue)>
14: <cfset client.detailID = -1>
15: <cfset client.userMessage = "">
16: <cflocation url="agentBioMaint.cfm" addToken="no">
17: <cfelseif ucase(left(#cName#,4)) is "VIEW" and findNoCase(".X", #cName#,1) gt 0>
18: <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
19: <cfset client.lookupID = val(cValue)>
20: <cfset client.detailID = -1>
21: <cfset client.userMessage = "">
22: <cflocation url="./agentBioView.cfm?agentID=#client.lookupID# addToken="no">
23: </cfif>
24: </cfloop>
25:
26: <cfset client.lookupID = -1>
27: <cfset client.detailID = -1>
28: <cfset client.userMessage = "">
29: <cflocation url="agentBioAdm.cfm" addToken="no">
30:
31:
32: </body>
33: </html>
```



```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
2:
3:
4: <cfif not isDefined("client.lookupID") or client.lookupID is "-1">
5:   <cflocation url="agentBioAdm.cfm" addToken="no">
6: </cfif>
7: <cfparam name="client.userName" default="">
8: <cfparam name="client.imageType" default="-1">
9:
10: <cfquery name="qryFindBio" datasource="#ap_datasource#">
11:   select agentBios.*
12:   from agentBios
13:   where agentBios.agentID = #client.lookupID#
14: </cfquery>
15:
16: <cfquery name="qryFindAgent" datasource="#ap_datasource#">
17:   select agents.distributorID, agents.firstName + ' ' + agents.lastName as agentName
18:   from agents
19:   where agents.agent_id = #client.lookupID#
20: </cfquery>
21:
22: <cfif qryFindAgent.recordCount gt 0>
23:   <cfset nAgentID = client.lookupID>
24:   <cfset nDistributorID = qryFindAgent.distributorID>
25: <cfelse>
26:   <cfset client.lookupID = -1>
27:   <cfset client.detailID = -1>
28:   <cfset client.userName = "">
29:   <cflocation url="agentAdm.cfm" addToken="no">
30: </cfif>
31:
32: <cfinclude template="include\javaValidate.cfm">
33:
34: <script language="JavaScript">
35:   <!--
36:   function validate(testform) {
37:     var results = "";
38:     var lResult = true;
39:
40:     if (!isValidDate(testform.edtBeginDate.value)) {
41:       if (removeSpaces(testform.edtBeginDate.value) == "") {
42:         results = results + "** Please enter a valid beginning date.\r";
43:       }
44:     } else {
45:       results = results + "** " + testform.edtBeginDate.value + " is not valid. Please enter a valid beginning date.\r";
46:     }
47:     lResult = false;
48:   }
49:

```



```

50: if (!isValidDate(testform.edtEndDate,value)) {
51:   if (removeSpaces(testform.edtEndDate.value) == "") {
52:     results = results + " Please enter a valid ending date.\r";
53:   }
54:   else {
55:     results = results + " " + testform.edtEndDate.value + " is not valid. Please enter a valid ending date.\r";
56:   }
57:   lResult = false;
58: }
59:
60: if (!lResult) {
61:   window.alert(results);
62: }
63: return lResult;
64: }
65: -->
66: </script>
67:
68: <html>
69: <head>
70:   <cfoutput>
71:     <title>#client.backofficeName# Backoffice Agent Bio Maintenance</title>
72:   </cfoutput>
73:   <link rel="stylesheet" href="style1.css" type="text/css">
74: </head>
75:
76: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
77: <cfinclude template="include\nocache.cfm">
78:
79: <p><cfinclude template="include\header.cfm"></p>
80:
81: <cfoutput>
82:
83:   <form action="agentBioUpdate.cfm" method="post" enctype="multipart/form-data" onsubmit="return validate(this)">
84:     <input type="hidden" name="agentID" value="#nAgentID#">
85:     <input type="hidden" name="distributorID" value="#nDistributorID#">
86:     <input type="hidden" name="originalHeaderImage" value="#qryFindBio.headerImage#">
87:     <input type="hidden" name="originalUserHeader" value="#qryFindBio.userHeaderImage#">
88:     <input type="hidden" name="originalFooterImage" value="#qryFindBio.footerImage#">
89:     <input type="hidden" name="originalUserFooter" value="#qryFindBio.userFooterImage#">
90:     <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
91:       <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Agent Bio Maintenance for #qryFindAgent.agentName#</b></span>
92:         <cfif client.lookupID is -1>
93:           <nbsp; (Create a new agent bio)
94:         </cfif>
95:       </td></tr>
96:
97:       <CFIF client.userName is not "">
98:         <tr bgcolor="eeeeee">

```



```

146: <input type="reset" value="Reset Info!">
147: <input type="submit" name="btnView" value="View Agent Bio">
148: </td>
149: <td align="right">
150: <input type="submit" name="btnDelete" value="Delete Agent Bio">
151: </td>
152: </cfif>
153: </tr>
154: </table>
155: </form>
156: </cfoutput>
157:
158: <!-- If this community page has already been created, allow paragraph editing -->
159:
160: <cfif qryFindBio.recordCount gt 0>
161: <script language="JavaScript">
162: <!--
163: function validateDetail(testform) {
164: var results = "";
165: var lResult = true;
166:
167: if ((removeSpaces(testform.edtSortOrder.value) != "") && (!isNumber(testform.edtSortOrder.value))) {
168: results = results + " * " + testform.edtSortOrder.value + " is not a valid numeric sort order value.\r";
169: lResult = false;
170: }
171:
172: if (!lResult) {
173: window.alert(results);
174: }
175:
176: return lResult;
177: }
178: -->
179: </script>
180:
181: <cfquery name="qryDetail" dataSource="#ap_dataSource#">
182: select agentBioDetail.*, imageTypes.description as imageName
183: from agentBioDetail
184: left outer join imageTypes on imageTypes.imageType = agentBioDetail.imageType
185: where agentBioDetail.agentID = #client.lookupID#
186: order by agentBioDetail.sortOrder
187: </cfquery>
188:
189: <cfquery name="qryEdit" dataSource="#ap_dataSource#">
190: select agentBioDetail.*,
191: imageTypes.isFormField, imageTypes.isApplet, imageTypes.isURL
192: from agentBioDetail
193: left outer join imageTypes on imageTypes.imageType = agentBioDetail.imageType
194: where agentBioDetail.agentID = #client.lookupID#

```

```

195: and agentBioDetail.agentBioDetailID = #client.detailID#
196: </cfquery>
197: <cfquery name="qryImageTypes" dataSource="#ap_dataSource#">
198: select imageType, description, isFormField, isApplet, isURL
199: from imageTypes
200: order by description
201: </cfquery>
202:
203: <!-- Set default values -->
204: <cfif qryEdit.recordCount is 0> <!-- New record -->
205: <cfif isDefined("client.old_sortOrder")>
206: <cfset nSortOrder = client.old_sortOrder>
207: <cfelse>
208: <cfset nSortOrder = "1">
209: </cfif>
210:
211: <cfquery name="qryDefault" dataSource="#ap_dataSource#">
212: select imageType from imageTypes
213: where imageTypes.description = 'Standard Photo'
214: </cfquery>
215: <cfif client.imageType gt -1>
216: <cfset nImageType = client.imageType>
217: <cfelseif qryDefault.recordCount gt 0>
218: <cfset nImageType = qryDefault.imageType>
219: <cfelse>
220: <cfset nImageType = 0>
221: </cfif>
222:
223: <cfelse> <!-- Existing record -->
224: <cfif isDefined("client.old_sortOrder")>
225: <cfset nSortOrder = client.old_sortOrder>
226: <cfelse>
227: <cfset nSortOrder = qryEdit.sortOrder>
228: </cfif>
229:
230: <cfif client.imageType gt -1>
231: <cfset nImageType = client.imageType>
232: <cfelse>
233: <cfset nImageType = qryEdit.imageType>
234: </cfif>
235: </cfif>
236: <cfif isDefined("client.old_title")>
237: <cfset cTitle = client.old_title>
238: <cfelse>
239: <cfset cTitle = trim(qryEdit.title)>
240: </cfif>
241: <cfif isDefined("client.old_alignment")>
242: <cfset cAlignment = client.old_alignment>
243: <cfelse>

```

```

244: <cfset cAlignment = trim(qryEdit.alignment)>
245: </cfif>
246: <cfif isdefined("client.old_desc")>
247: <cfset cDesc = client.old_desc>
248: <cfelse>
249: <cfset cDesc = trim(qryEdit.text)>
250: </cfif>
251:
252: <cfquery name="qryImageInfo" dataSource="#ap_dataSource#">
253: select formTitle, isFormField, isApplet, isURL
254: from imageTypes
255: where imageTypes.imageType = #nImageType#
256: </cfquery>
257:
258: <form action="agentBioUpdate.cfm" method="post" enctype="multipart/form-data" onSubmit="return validateDetail(this)">
259: <cfoutput>
260: <input type="hidden" name="agentID" value="#client.lookupID#">
261: <input type="hidden" name="distributorID" value="#nDistributorID#">
262: <input type="hidden" name="agentBioDetailID" value="#client.detailID#">
263: <input type="hidden" name="originalImage" value="#qryEdit.image#">
264: <input type="hidden" name="originalUserImage" value="#qryEdit.userFilename#">
265: </cfoutput>
266:
267: <cfif qryDetail.recordCount is 0>
268: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
269: <tr><td colspan="6"><i><b>There are no paragraphs defined.</b></i></td></tr>
270: <tr><td colspan="6"><b><nbsp;</b></td></tr>
271: </table>
272: <cfelse>
273: <table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
274: <tr valign="top" bgcolor="#cccccc">
275: <td><b>Image Type</b></td>
276: <td><b>Title</b></td>
277: <td><b>Text</b></td>
278: <td><b>Image Name</b></td>
279: <td><b>Alignment</b></td>
280: <td><b>Order</b></td>
281: <td><b><nbsp;</b></td>
282: </tr>
283: <cfoutput query="qryDetail">
284: <tr valign="top" bgcolor=" "><cfif qryDetail.agentBioDetailID is client.detailID>#ffffff<cfelse>#eeeeee</cfif>>
285: <td>
286: <cfif trim(qryDetail.imageName) is ""><b><nbsp;</b></cfif>#qryDetail.imageName#
287: </td>
288: <td>
289: <cfif trim(qryDetail.title) is ""><b><nbsp;</b></cfif>#qryDetail.title#
290: </td>
291: <td>
292: <cfif trim(qryDetail.text) is ""><b><nbsp;</b></cfif>#qryDetail.text#

```

```

293: </td>
294: <td>
295:   <cfif trim(qryDetail.userName) is "">&nbsp;</cfif>#qryDetail.userName#
296: </td>
297: <td>#qryDetail.alignment#</td>
298: <td>#qryDetail.sortOrder#</td>
299: <td align="center">
300:   <input type="image" name="edit#qryDetail.agentBioDetailID#" src="#ap_commonImages#edit.gif" alt="Edit"
      border="0">
301:   <hr>
302:   <input type="image" name="delete#qryDetail.agentBioDetailID#" src="#ap_commonImages#delete.gif" alt="Delete"
      border="0">
303:   </td>
304: </tr>
305: </cfoutput>
306: </table>
307: </cfif>
308: <cfoutput>
309: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
310:   <tr><td colspan="5">&nbsp;</td></tr>
311:   <cfif client.detailID is -1>
312:     <tr bgcolor="#cccccc"><td colspan="5"><b>Add a paragraph</b></td></tr>
313:   <cfelse>
314:     <tr bgcolor="#cccccc"><td colspan="5"><b>Edit this paragraph</b></td></tr>
315:   </cfif>
316:   <tr valign="top" bgcolor="#eeeeee">
317:     <td><b>Image Type</b></td>
318:     <td><b>Title</b></td>
319:     <td><b>#qryImageInfo.formTitle#</b></td>
320:     <td><b>Alignment</b></td>
321:     <td><b>Order</b></td>
322:   </tr>
323:   <tr valign="top" bgcolor="#eeeeee">
324:     <td>
325:       <select name="editImageType">
326:         <cfloop query="qryImageTypes">
327:           <option value="#qryImageTypes.imageType#"><b>#qryImageTypes.imageType is nImageType>
selected</cfif>#qryImageTypes.description#
          </cfloop>
        </select>
329:       <cfif qryImageTypes.recordCount gt 1>
330:         <input type="submit" name="btnImageType" value="Change">
331:       </cfif>
332:     </td>
333:     <td><input type="text" name="editTitle" value="#cTitle#"></td>
334:     <td>
335:       <cfif qryImageInfo.isFormField is "Y">
336:         <input type="File" name="editImage"></td>
337:       <cfelseif qryImageInfo.isApplet is "Y">
338:

```

1  
2  
3  
4

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfif not isDefined("form.agentID")>
4:   <cfset client.lookupID = -1>
5:   <cfset client.detailID = -1>
6:   <cfset client.imageType = -1>
7:   <cfset client.userMessage = "">
8:   <cflocation url="agentBioAdm.cfm" addtoken="no">
9: </cfif>
10:
11: <cfquery name="qryFindBio" datasource="#ap_dataSource#">
12:   select agentBios.agentID
13:   from agentBios
14:   where agentBios.agentID = #form.agentID#
15: </cfquery>
16:
17: <cfinclude template="include\clearOldFields.cfm">
18: <cfset client.userMessage = "">
19: <cfset client.imageType = -1>
20:
21: <cfif isDefined("form.btnImageType")>
22:   <!-- A change in the image type has been requested -->
23:   <cfset client.lookupID = form.agentID>
24:   <cfset client.detailID = form.agentBioDetailID>
25:   <cfset client.imageType = form.edtImageType>
26:
27:   <cfset client.old_title = form.edtTitle>
28:   <cfset client.old_alignment = form.edtAlignment>
29:   <cfset client.old_sortOrder = form.edtSortOrder>
30:   <cfset client.old_desc = form.edtDesc>
31:
32:   <cflocation url="agentBioMaint.cfm" addtoken="no">
33: </cfif>
34:
35:
36: <cfif isDefined("form.btnCancelDetail")> <!-- Cancel detail edit -->
37:   <cfset client.lookupID = #form.agentID#>
38:   <cfset client.detailID = -1>
39:   <cfset client.imageType = -1>
40:   <cfset client.userMessage = "">
41:   <cflocation url="agentBioMaint.cfm" addtoken="no">
42:
43: <cfelseif isDefined("form.btnCancelDelete")> <!-- Cancel detail edit -->
44:   <cfset client.lookupID = #form.agentID#>
45:   <cfset client.detailID = -1>
46:   <cfset client.imageType = -1>
47:   <cfset client.userMessage = "Deletion canceled.">
48:   <cflocation url="agentBioMaint.cfm" addtoken="no">
49:

```



```

50: <cfelseif isdefined("form.btnUpdate")>
51:   <cflocation url="../agentBioView.cfm?agentID=#form.agentID#" addToken="no">
52:
53: <cfelseif isdefined("form.btnUpdateDetail")>
54:   <cfquery name="qryFindDetail" dataSource="#ap_dataSource#">
55:     select agentBioDetailID
56:     from agentBioDetail
57:     where agentBioDetail.agentBioDetailID = #form.agentBioDetailID#
58:   </cfquery>
59:
60:   <cfif qryFindDetail.recordCount is 0>
61:     <cfset cTitle = preservesingleQuotes(form.edtTitle)>
62:     <cfset cDesc = preservesingleQuotes(form.edtDesc)>
63:     <cfset nSortOrder = val(form.edtSortOrder)>
64:
65:     <cfquery name="qryImageType" dataSource="#ap_dataSource#">
66:       select imageType, isFormField, isApplet, isURL
67:       from imageTypes
68:       where imageTypes.imageType = #form.edtImageType#
69:     </cfquery>
70:
71:     <cfif qryImageType.isFormField is "Y">
72:       <cfif trim(form.edtImage) is "">
73:         <cfset cImage = form.originalImage>
74:         <cfset cUserImage = form.originalUserImage>
75:       <cfelse>
76:         <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
77:           select distributors.enhAgentImages
78:           from distributors
79:           where distributors.distributorID = #form.distributorID#
80:         </cfquery>
81:         <!-- Upload the file to a unique name -->
82:         <cffile
83:           destination = "#qryImagePath.enhAgentImages#"
84:           action = "UPLOAD"
85:           nameconflict = "OVERWRITE"
86:           filefield = "edtImage"
87:         >
88:
89:         <cfset cImage = file.serverFile>
90:         <cfset cUserImage = file.serverFile>
91:
92:         <cfset cImagePath = file.serverDirectory & "\">
93:         <cfset cNewImage = "#cImagePath#trim(form.agentID)#_#file.serverFile#">
94:
95:         <cfif fileExists(cNewImage)>
96:           <cffile
97:             action = "DELETE"
98:             file="#cNewImage#"

```

```

99: >
100: </cfif>
101:
102: <!-- Now rename the unique uploaded file to the new name -->
103: <cffile
104:     action = "RENAME"
105:     source = "#file.serverDirectory#\#file.serverFile#"
106:     destination="#cNewImage#"
107: >
108:
109:     <cfset cImage = cNewImage>
110: </cfif>
111: <cfelseif qryImageType.isURL is "Y">
112:     <cfset cImage = form.edtImage>
113:     <cfset cUserImage = form.edtImage>
114: <cfelseif qryImageType.isApplet is "Y">
115:     <cfset cImage = form.edtImage>
116:     <cfset cUserImage = form.edtImage>
117: <cfelse>
118:     <cfset cImage = form.edtImage>
119:     <cfset cUserImage = form.edtImage>
120: </cfif>
121:
122:
123: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
124:     insert into agentBioDetail
125:         (agentID, sortOrder, title, image, userFilename, imageType,
126:          alignment, text)
127:     values
128:         (#form.agentID#, #nSortOrder#, '#cTitle',
129:          '#cImage#', '#cUserImage#', #form.edtImageType#, '#form.edtAlignmentt#',
130:          '#cDesc#')
131: </cfquery>
132:
133: <cfset client.lookupID = form.agentID>
134: <cfset client.detailID = -1>
135: <cfset client.imageType = form.edtImageType> <!-- Keep last inserted image type -->
136:
137: <cflocation url="agentBioMaint.cfm" addToken="no">
138:
139: <cfelse>
140:     <cfset cTitle = preservesSingleQuotes(form.edtTitle)>
141:     <cfset cDesc = preservesSingleQuotes(form.edtDesc)>
142:     <cfset nSortOrder = val(form.edtSortOrder)>
143:
144:     <cfquery name="qryImageType" dataSource="#ap_dataSource#">
145:         select imageType, isFormField, isApplet, isURL
146:         from imageTypes
147:         where imageTypes.imageType = #form.edtImageType#

```

```

148: </cfquery>
149:
150: <cfif qryImageType.isFormField is "Y">
151:   <cfif trim(form.edtImage) is "">
152:     <cfset cImage = form.originalImage>
153:     <cfset cUserImage = form.originalUserImage>
154:   <cfelse>
155:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
156:       select distributors.enhAgentImages
157:       from distributors
158:       where distributors.distributorID = #form.distributorID#
159:     </cfquery>
160:     <!--- Upload the file to a unique name --->
161:     <cffile
162:       destination = "#qryImagePath.enhAgentImages#"
163:       action = "UPLOAD"
164:       nameconflict = "OVERWRITE"
165:       filefield = "edtImage"
166:     >
167:
168:     <cfset cImage = file.serverFile>
169:     <cfset cUserImage = file.serverFile>
170:
171:     <cfset cImagePath = file.serverDirectory & "\">
172:     <cfset cNewImage = "#cImagePath#trim(form.agentID)#_#file.serverFile#">
173:
174:     <cfif fileExists(cNewImage)>
175:       <cffile
176:         action = "DELETE"
177:         file="#cNewImage#"
178:       >
179:     </cfif>
180:
181:     <!--- Now rename the unique uploaded file to the new name --->
182:     <cffile
183:       action = "RENAME"
184:       source = "#file.serverDirectory#\#file.serverFile#"
185:       destination="#cNewImage#"
186:     >
187:
188:     <cfset cImage = cNewImage>
189:   </cfif>
190:   <cfelseif qryImageType.isURL is "Y">
191:     <cfset cImage = form.edtImage>
192:     <cfset cUserImage = form.edtImage>
193:   <cfelseif qryImageType.isApplet is "Y">
194:     <cfset cImage = form.edtImage>
195:     <cfset cUserImage = form.edtImage>
196:   <cfelse>

```

```

197: <cfset cImage = form.edtImage>
198: <cfset cUserImage = form.edtImage>
199: </cfif>
200:
201: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
202:   update agentBioDetail
203:   set
204:     sortOrder = #nSortOrder#,
205:     title = '#cTitle#',
206:     imageType = #form.edtImageType#,
207:     alignment = '#form.edtAlignment#',
208:     image = '#cImage#',
209:     fileName = '#cUserImage#',
210:     text = '#cDesc#'
211:   where agentBioDetail.agentBioDetailID = #form.agentBioDetailID#
212: </cfquery>
213:
214: <cfset client.lookupID = form.agentID>
215: <cfset client.detailID = -1>
216: <cfset client.imageType = -1>
217:
218: <cflocation url="agentBioMaint.cfm" addToken="no">
219:
220: </cfif>
221:
222: <cfelseif isDefined("form.btnUpdate")>
223:   <cfif qryFindBio.recordCount is 0>
224:     <cfset client.lookupID = -1>
225:     <cfset client.detailID = -1>
226:     <cfset client.userName = "There was an error while creating the agent bio page.">
227:     <cftransaction>
228:       <cfif trim(form.edtHeaderImage) is "">
229:         <cfset cHeaderImage = form.originalHeaderImage>
230:         <cfset cUserHeaderImage = form.originalUserHeader>
231:       <cfelse>
232:         <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
233:           select distributors.enhAgentImages
234:           from distributors
235:           where distributors.distributorID = #form.distributorID#
236:         </cfquery>
237:         <!-- Upload the file to a unique name -->
238:         <cffile
239:           destination = "#qryImagePath.enhAgentImages#"
240:           action = "UPLOAD"
241:           nameConflict = "OVERWRITE"
242:           field = "edtHeaderImage"
243:         >
244:
245:         <cfset cImage = file.serverFile>

```

```

246: <cfset cUserHeaderImage = file.serverHeaderImage>
247:
248: <cfset cImagePath = file.serverDirectory & "\">
249: <cfset cNewImage = "#cImagePath##trim(form.agentID)#_#file.serverFile#">
250:
251: <cfif fileExists(cNewImage)>
252:   <cffile
253:     action = "DELETE"
254:     file="#cNewImage#"
255:   >
256: </cfif>
257:
258: <!--- Now rename the unique uploaded file to the new name --->
259: <cffile
260:   action = "RENAME"
261:   source = "#file.serverDirectory#\#file.serverFile#"
262:   destination="#cNewImage#"
263: >
264: <cfset cHeaderImage = cNewImage>
265: </cfif>
266:
267: <cfif trim(form.edtFooterImage) is "">
268:   <cfset cFooterImage = form.originalFooterImage>
269:   <cfset cUserFooterImage = form.originalUserFooter>
270: <cfelse>
271:   <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
272:     select distributors.enhAgentImages
273:     from distributors
274:     where distributors.distributorID = #form.distributorID#
275:   </cfquery>
276:   <!--- Upload the file to a unique name --->
277:   <cffile
278:     destination = "#qryImagePath.enhAgentImages#"
279:     action = "UPLOAD"
280:     nameconflict = "OVERWRITE"
281:     filefield = "edtFooterImage"
282:   >
283:
284: <cfset cImage = file.serverFile>
285: <cfset cUserFooterImage = file.serverFile>
286:
287: <cfset cImagePath = file.serverDirectory & "\">
288: <cfset cNewImage = "#cImagePath##trim(form.agentID)#_#file.serverFile#">
289:
290: <cfif fileExists(cNewImage)>
291:   <cffile
292:     action = "DELETE"
293:     file="#cNewImage#"
294:   >

```

```

295: </cfif>
296:
297: <!-- Now rename the unique uploaded file to the new name -->
298: <cffile
299:   action = "RENAME"
300:   source = "#file.serverDirectory#\#file.serverFile#"
301:   destination="#cNewImage#"
302: >
303: <cfset cFooterImage = cNewImage>
304: </cfif>
305:
306: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
307:   insert into agentBios
308:     (agentID, distributorID, headerImage, userHeaderImage,
309:      footerImage, userFooterImage, beginDate, endDate, alternateURL)
310:   values
311:     (#form.agentID#, #form.distributorID#,
312:      '#cHeaderImage#', '#cUserHeaderImage#',
313:      '#cFooterImage#', '#cUserFooterImage#',
314:      '#form.edtBeginDate#', '#form.edtEndDate#',
315:      '#form.edtAlternateURL#')
316: </cfquery>
317:
318: <cfset nAgentID = form.agentID>
319: <cfset client.lookupID = nAgentID>
320:
321: <cfset client.userMessage = "Agent Bio was created.">
322: </cftransaction>
323:
324: <cfif client.lookupID gt 0>
325:   <cflocation url="agentBioMaint.cfm" addToken="no">
326: <cfelse>
327:   <cflocation url="agentBioAdm.cfm" addToken="no">
328: </cfif>
329:
330: <cfelse>
331:   <cfset client.lookupID = form.agentID>
332:   <cfset client.detailID = -1>
333:   <cfset client.userMessage = "There was an error while updating the agent bio information.">
334:   </cftransaction>
335:   <cfif trim(form.edtHeaderImage) is "">
336:     <cfset cHeaderImage = form.originalHeaderImage>
337:     <cfset cUserHeaderImage = form.originalUserHeader>
338:   <cfelse>
339:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
340:       select distributo.s.enhAgentImages
341:       from distributors
342:       where distributors.distributorID = #form.distributorID#
343:     </cfquery>

```

```

344: <!-- Upload the file to a unique header file -->
345: <cffile
346:   destination = "#qryImagePath.enhAgentImages#"
347:   action = "UPLOAD"
348:   nameconflict = "OVERWRITE"
349:   filefield = "edtHeaderImage"
350: >
351:
352: <cfset cImage = file.serverFile>
353: <cfset cUserHeaderImage = file.serverFile>
354:
355: <cfset cImagePath = file.serverDirectory & "\">
356: <cfset cNewImage = "#cImagePath#trim(form.agentID)#_file.serverFile#">
357:
358: <cfif fileExists(cNewImage)>
359:   <cffile
360:     action = "DELETE"
361:     file = "#cNewImage#"
362:   >
363: </cfif>
364:
365: <!-- Now rename the unique uploaded file to the new name -->
366: <cffile
367:   action = "RENAME"
368:   source = "#file.serverDirectory#\#file.serverFile#"
369:   destination = "#cNewImage#"
370: >
371: <cfset cHeaderImage = cNewImage>
372: </cfif>
373:
374: <cfif trim(form.edtFooterImage) is "">
375:   <cfset cFooterImage = form.originalFooterImage>
376:   <cfset cUserFooterImage = form.originalUserFooter>
377: <cfelse>
378:   <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
379:     select distributors.enhAgentImages
380:     from distributors
381:     where distributors.distributorID = #form.distributorID#
382:   </cfquery>
383: <!-- Upload the file to a unique name -->
384: <cffile
385:   destination = "#qryImagePath.enhAgentImages#"
386:   action = "UPLOAD"
387:   nameconflict = "OVERWRITE"
388:   filefield = "edtFooterImage"
389: >
390:
391: <cfset cImage = file.serverFile>
392: <cfset cUserFooterImage = file.serverFile>

```

```

393:
394:
395: <cfset cImagePath = file.serverDirectory & "\">
396: <cfset cNewImage = "#cImagePath#trim(form.agentID)#_#file.serverFile#">
397:
398: <cfif fileExists(cNewImage)>
399:     <cfif
400:         action = "DELETE"
401:         file="#cNewImage#"
402:     >
403:     </cfif>
404:
405:     <!-- Now rename the unique uploaded file to the new name -->
406:     <cfif
407:         action = "RENAME"
408:         source = "#file.serverDirectory#\#file.serverFile#"
409:         destination="#cNewImage#"
410:     >
411:     <cfset cFooterImage = cNewImage>
412:     </cfif>
413:
414:     <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
415:         update agentBios
416:         set agentID      = #form.agentID#,
417:           distributorID  = #form.distributorID#,
418:           headerImage   = '#cHeaderImage#',
419:           userHeaderImage = '#cUserHeaderImage#',
420:           footerImage   = '#cFooterImage#',
421:           userFooterImage = '#cUserFooterImage#',
422:           beginDate     = '#form.edtBeginDate#',
423:           endDate       = '#form.edtEndDate#',
424:           alternateURL   = '#form.edtAlternateURL#'
425:         where agentBios.agentID = #form.agentID#
426:     </cfquery>
427:
428:     <cfset client.detailID = -1>
429:     <cfset client.userName = "Agent bio was updated.">
430:     </cftransaction>
431:
432:     <cfif client.lookupID gt 0>
433:         <cflocation url="agentBioMaint.cfm" addToken="no">
434:     <cfelse>
435:         <cflocation url="agentBioAdm.cfm" addToken="no">
436:     </cfif>
437:
438:     <cfelseif isDefined("form.btnDelete")>
439:         <cflocation url="agentBioDelete.cfm" addToken="no">
440:     <cfelseif isDefined("form.btnConfirmedDelete")>
441:         <cfset client.lookupID = -1>
442:         <cfset client.detailID = -1>

```



```

442: <cfset client.userName = "Unable to delete agent bio!">
443: <cftransaction>
444:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
445:     delete from agentBioDetail
446:     where agentBioDetail.agentID = #form.agentID#
447:   </cfquery>
448:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
449:     delete from agentBios
450:     where agentBios.agentID = #form.agentID#
451:   </cfquery>
452:
453:   <cfquery name="qryImagePath" datasource="#ap_dataSource#">
454:     select distributors.enhAgentImages
455:     from distributors
456:     where distributors.distributorID = #form.distributorID#
457:   </cfquery>
458:   <cfset lstDirectory = "">
459:   <cfdirectory
460:     name = "lstDirectory"
461:     action = "list"
462:     directory = "#qryImagePath.enhAgentImages#"
463:     filter="#form.agentID# *.*"
464:   >
465:
466:   <cfloop query="lstDirectory">
467:     <cffile
468:       action="delete"
469:       file="#qryImagePath.enhAgentImages#lstDirectory.name#"
470:     >
471:   </cfloop>
472:
473:   <cfset client.userName = "Agent Bio was deleted.">
474:   </cftransaction>
475:   <cflocation url="agentBioAdm.cfm" addtoken="no">
476: </cfif>
477:
478: <cfset client.lookupID = -1>
479: <cfset client.detailID = -1>
480: <cfset client.imageType = -1>
481: <!-- Get ID number from edit -->
482: <cfloop collection="#form#" item="cName">
483:   <cfif ucase(left(cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
484:     <cfset cValue = mid(cName#, 5, len(cName#)-6)>
485:     <cfset client.lookupID = form.agentID>
486:     <cfset client.detailID = val(cValue)>
487:     <cfset client.imageType = -1>
488:   </cfif>
489:
490:   <cfif client.lookupID gt -1 and client.lookupID gt -1>

```

```

491:     <cflocation url="agentBioMaint.cfm" addToken="no">
492:     </cfif>
493: </cfloop>
494:
495: <!-- Get ID number for delete detail item -->
496: <cfloop collection="#form#" item="cName">
497:     <cfif ucase(left(#cName#,6)) is "DELETE" and findNoCase("X", #cName#,1) gt 0>
498:         <cfset cValue = mid(#cName#, 7, len(#cName#)-8)>
499:         <cfset client.lookupID = form.agentID>
500:         <cfset client.detailID = val(cValue)>
501:         <cfset client.imageType = -1>
502:     </cfif>
503:
504:     <cfif client.lookupID gt -1 and client.lookupID gt -1>
505:         <cfset client.userName = "Unable to delete paragraph.">
506:         <cfquery name="qryDelete" dataSource="#ap_dataSource#">
507:             delete from agentBioDetail
508:             where agentBioDetail.agentBioDetailID = #client.detailID#
509:         </cfquery>
510:         <cfset client.detailID = -1>
511:         <cfset client.userName = "paragraph deleted.">
512:         <cflocation url="agentBioMaint.cfm" addToken="no">
513:     </cfif>
514: </cfloop>
515:
516: <!-- If anything else, then go back to the admin page -->
517: <cflocation url="agentBioAdm.cfm" addToken="no">
518:
519:

```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <html>
4: <head>
5: <title>Agent Choice</title>
6: </head>
7:
8: <body>
9:
10: <cfloop collection="#form#" item="cName">
11:   <cfif ucase(left(cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
12:     <cfset cValue = mid(cName#, 5, len(cName#)-6)>
13:     <cfset client.lookupID = val(cValue)>
14:     <cfset client.detailID = -1>
15:     <cfset client.userMessage = "">
16:     <cflocation url="agentMaint.cfm" addToken="no">
17:   <cfelseif ucase(left(cName#,7)) is "BIOEDIT" and findNoCase(".X", #cName#,1) gt 0>
18:     <cfset cValue = mid(cName#, 8, len(cName#)-9)>
19:     <cfset client.lookupID = val(cValue)>
20:     <cfset client.detailID = -1>
21:     <cfset client.userMessage = "">
22:     <cflocation url="agentBioMaint.cfm" addToken="no">
23:   <cfelseif ucase(left(cName#,6)) is "BIOADD" and findNoCase(".X", #cName#,1) gt 0>
24:     <cfset cValue = mid(cName#, 7, len(cName#)-8)>
25:     <cfset client.lookupID = val(cValue)>
26:     <cfset client.detailID = -1>
27:     <cfset client.userMessage = "">
28:     <cflocation url="agentBioMaint.cfm" addToken="no">
29:   </cfif>
30: </cfloop>
31:
32: <cfset client.lookupID = -1>
33: <cfset client.detailID = -1>
34: <cfset client.userMessage = "">
35: <cflocation url="agentAdm.cfm" addToken="no">
36:
37: </body>
38: </html>
```

#### 4.0 Transitional/EN<sup>3</sup>A

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3:
4: <!-- Get ID number from edit -->
5: <cfloop collection="#form#" item="cName">
6:   <cfif ucase(left(cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
7:     <cfset cValue = mid(cName#, 5, len(cName#)-6)>
8:     <cfset client.lookupID = val(cValue)>
9:     <cfset client.detailID = -1>
10:   </cfif>
11: </cfloop>
12:
13: <cfif not isDefined("client.lookupID")>
14:   <cflocation url="agentAdm.cfm" addToken="no">
15: </cfif>
16: <cfparam name="client.userMessage" default="">
17:
18: <cfquery name="qryFindAgent" datasource="#ap_dataSource#">
19:   select agents.*, agency.name as agencyName
20:   from agents
21:   left outer join agency on agency.agency_id = agents.agency_id
22:   where agents.agent_id = #client.lookupID#
23: </cfquery>
24:
25:
26: <cfquery name="qryCommunities" datasource="#ap_dataSource">
27:   select communities.communityID, communities.name
28:   from communities
29:   order by communities.name
30: </cfquery>
31:
32: <cfquery name="qryAgentComm" datasource="#ap_dataSource#">
33:   select agentCommunities.communityID
34:   from agentCommunities
35:   where agentCommunities.agentID = #client.lookupID#
36: </cfquery>
37: <cfset lstCommunities = valueList(qryAgentComm.communityID)>
38:
39: <cfif qryFindAgent.recordCount gt 0>
40:   <cfset nAgentID = qryFindAgent.agent_id>
41: <cfelse>
42:   <cfset nAgentID = -1>
43: </cfif>
44:
45: <script language="JavaScript">
46: <!--
47:   function validate(testform) {
48:     var results = "";
49:     var lResult = true;

```

```

50:
51:
52:
53:
54:
55:
56:
57:
58:
59:
60:
61:
62:
63:
64:
65:
66:
67:
68:
69:
70:
71:
72:
73:
74:
75:
76:
77:
78:
79:
80:
81:
82:
83:
84:
85:
86:
87:
88:
89:
90:
91:
92:
93:
94:
95:
96:
97:
98:

if (testform.edtFirstName.value == "") {
    results = results + "<*> Please enter the agent's first name.<br>";
    lResult = false;
}

if (testform.edtLastName.value == "") {
    results = results + "<*> Please enter the agent's last name.<br>";
    lResult = false;
}

if (testform.edtTitle.value == "") {
    results = results + "<*> Please enter the agent's title.<br>";
    lResult = false;
}

if (testform.edtWorkPhone.value == "") {
    results = results + "<*> Please enter the agent's work phone number.<br>";
    lResult = false;
}

if (testform.edtFax.value == "") {
    results = results + "<*> Please enter the agent's fax number.<br>";
    lResult = false;
}

// Netscape does not recognize the value of select elements, but does know which item was selected
if ((testform.edtAgency.value == "-1") || (testform.edtAgency.selectedIndex == 0)) {
    results = results + "<*> You must select an agency for this agent.<br>";
    lResult = false;
}

// Netscape does not recognize the value of select elements, but does know which item was selected
if ((testform.edtPortalID.value == "-1") || (testform.edtPortalID.selectedIndex == 0)) {
    results = results + "<*> You must select a portal for this agent.<br>";
    lResult = false;
}

// Netscape does not recognize the value of select elements, but does know which item was selected
if ((testform.edtDistributorID.value == "-1") || (testform.edtDistributorID.selectedIndex == 0)) {
    results = results + "<*> You must select a distributor for this agent.<br>";
    lResult = false;
}

if (!lResult) {
    window.alert(results);
}

return lResult;
}

-->
</script>
<html>
<head>

```

```

99: <cfoutput>
100: <title>#client.backofficeName# Backoffice Agent Maintenance</title>
101: </cfoutput>
102: <link rel="stylesheet" href="style1.css" type="text/css">
103: </head>
104:
105: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
106: <cfinclude template="include\nocache.cfm">
107:
108: <p><cfinclude template="include\header.cfm"></p>
109:
110: <cfoutput>
111:
112: <form action="agentUpdate.cfm" enctype="multipart/form-data" method="post" onSubmit="return validate(this)">
113: <input type="hidden" name="agentID" value="#nAgentID#">
114: <input type="hidden" name="originalImageName" value="#qryFindAgent.image_name#">
115: <input type="hidden" name="originalUsername" value="#qryFindAgent.username#">
116:
117: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
118: <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Agent Maintenance</b></span>
119: <cfif client.lookupID is -1>
120:    <nbsp;  <b>(Create a new Agent)</b>
121:   </cfif>
122: </td></tr>
123:
124: <CFIF client.userName is not "">
125: <tr bgcolor="eeeeee">
126: <td colspan="5"><p><font color="red">#client.userName#</font></p></td>
127: </tr>
128: <tr bgcolor="eeeeee"><td colspan="5"><b></td></tr>
129: </CFIF>
130: <cfset client.userName = "">
131:
132: <tr bgcolor="eeeeee">
133: <td width="15%"><b>First Name:</b></td>
134: <td width="34%"><input type="text" name="edtFirstName" value="#qryFindAgent.firstName#"></td>
135: <td width="2%"><b></td>
136: <td width="15%"><b>Last Name:</b></td>
137: <td width="34%"><input type="text" name="edtLastName" value="#qryFindAgent.lastName#"></td>
138: </tr>
139:
140: <tr bgcolor="eeeeee">
141: <td width="15%"><b>Title:</b></td>
142: <td width="34%"><input type="text" name="edtTitle" value="#qryFindAgent.title#"></td>
143: <td width="2%"><b></td>
144: <td width="15%"><b>Specialty:</b></td>
145: <td width="34%"><input type="text" name="edtSpecialty" value="#qryFindAgent.specialty#"></td>
146: </tr>
147:

```

```

148: <tr bgcolor="#ffffff">
149: <td width="15%">Email:</td>
150: <td width="34%"><input type="text" name="edtEmail" value="#qryFindAgent.email#"></td>
151: <td width="2%">&nbsp;</td>
152: <td width="15%">Web Site:</td>
153: <td width="34%"><input type="text" name="edtWebSite" value="#qryFindAgent.website#"></td>
154: </tr>
155:
156: <tr bgcolor="#ffffff">
157: <td width="15%"><b>Work Phone</b></td>
158: <td width="34%">
159: <input type="text" name="edtWorkPhone" value="#qryFindAgent.workPhone#">
160: <input type="text" name="edtExtension" value="#qryFindAgent.extension#" size="5">
161: </td>
162: <td width="2%">&nbsp;</td>
163: <td width="15%">Cell Phone:</td>
164: <td width="34%"><input type="text" name="edtCellPhone" value="#qryFindAgent.cellPhone#"></td>
165: </tr>
166:
167: <tr bgcolor="#ffffff">
168: <td width="15%">Home Phone:</td>
169: <td colspan="4">
170: <input type="text" name="edtHomePhone" value="#qryFindAgent.homePhone#">
171: Publish?
172: <input type="radio" name="edtPublishHome" title="Yes" value="Y"><cfif qryFindAgent.pub_home is "Y" or
trim(qryFindAgent.pub_home) is ">> checked</cfif>> Yes
<input type="radio" name="edtPublishHome" title="No" value="N"><cfif qryFindAgent.pub_home is "N"> checked</cfif>> No
</td>
</tr>
175:
176:
177: <tr bgcolor="#ffffff">
178: <td width="15%"><b>Fax:</b></td>
179: <td width="34%">
180: <input type="text" name="edtFax" value="#qryFindAgent.faxPhone#">
181: </td>
182: <td width="2%">&nbsp;</td>
183: <td width="15%">Other Phone:</td>
184: <td width="34%"><input type="text" name="edtOtherPhone" value="#qryFindAgent.otherPhone#"></td>
185: </tr>
186:
187: <tr bgcolor="#ffffff"><td colspan="5">&nbsp;</td></tr>
188:
189: <tr bgcolor="#ffffff">
190: <td width="15%">Agent Image:</td>
191: <td colspan="4">
192: <input type="file" name="edtAgentPhoto" size="30">
193: <cfif qryFindAgent.image_name is not "">
194: &nbsp;<cfset cFilename = getFileFromPath(qryFindAgent.image_name)>
195:

```



```

196: <cfset cfilename = replace(cfilename, "#qryFindAgent.agent_id#", "")>
197: <i>Currently: #cfilename#</i>
198: <nbsp; <input type="checkbox" name="chkDeleteImage"> Delete Image
199: </cfif>
200: </td>
201: </tr>
202: <tr bgcolor="#ffffff"><td colspan="5"><nbsp;</td></tr>
203:
204: <tr bgcolor="#ffffff">
205: <td width="15%">Agency:</td>
206: <td width="34%">
207: <cfif client.currentEntityType lt ap_securityMastAgency> <!-- Only if not the agent -->
208: <cfquery name="qryAgencies" dataSource="#ap_dataSource#">
209: select agency_id, agency.name
210: from agency
211: join securityAccess on
212: (securityAccess.entityType = #ap_securityMastAgency# or securityAccess.entityType = #ap_securityAgency#)
213: and securityAccess.entityID = agency.agency_id
214: and securityAccess.hierarchyID like '#client.hierarchyID#',
215: order by agency.name
216: </cfquery>
217: <select name="edtAgency">
218: <option value="-1"><cfif client.lookupID is -1 or qryFindAgent.agency_id is -1 or trim(qryFindAgent.agency_id) is
219: ""> selected</cfif>>Not Assigned
220: <cfloop query="qryAgencies">
221: <option value="#qryAgencies.agency_id#"><cfif qryFindAgent.agency_id is qryAgencies.agency_id>
selected</cfif>>#qryAgencies.name#
</cfloop>
</select>
</cfelse>
<cfif qryFindAgent.recordCount is 0>
<input type="hidden" name="edtAgency" value="#client.currentAgencyID#">
<cfquery name="qryAgency" dataSource="#ap_dataSource#">
select agency.name
from agency
where agency.agency_id = #client.currentAgencyID#
</cfquery>
#qryAgency.name#
</cfelse>
<input type="hidden" name="edtAgency" value="#qryFindAgent.agency_id#">
<cfif trim(qryFindAgent.agencyName) is "">
Not Assigned
</cfelse>
#qryFindAgent.agencyName#
</cfif>
</cfif>
</cfif>
</td>
242:

```

```

243: <td width="28">&nbsp;</td>
244: <td width="15">Communities:</td>
245: <td width="34">
246:   <input type="hidden" name="edtCommunities" value="">
247:   <cfif qryCommunities.recordCount gt 0>
248:     <select name="edtCommunities" size="5" multiple>
249:       <cfloop query="qryCommunities">
250:         <option value="#qryCommunities.communityID#">cfif listFind(listCommunities, #qryCommunities.communityID#) gt 0>
251:         selected</cfif>>#qryCommunities.name#
252:       </cfloop>
253:     </select>
254:     <cfelse>
255:       No Communities Defined
256:     </cfif>
257:   </td>
258: </tr>
259:
260: <!--
261:   <cfif client.currentEntityType is ap_securityYakalo>
262:     <cfquery name="qryPortals" dataSource="#ap_dataSource#">
263:       select portals.portalID, portals.name
264:       from portals
265:       join securityAccess on
266:         securityAccess.entityType = #ap_securityPortal#
267:         and securityAccess.entityID = portals.portalID
268:         and securityAccess.hierarchyID like '#client.hierarchyID#%'
269:       order by portals.name
270:     </cfquery>
271:     <tr bgcolor="#ffffff">
272:       <td width="15">Portal:</td>
273:       <td colspan="4">
274:         <select name="edtPortalID">
275:           <option value="1">cfif qryFindAgent.portalID lte 0 or trim(qryFindAgent.portalID) is ""> selected</cfif>>Not
276:           Assigned
277:         <cfloop query="qryPortals">
278:           <option value="#qryPortals.portalID#">cfif qryPortals.portalID is qryFindAgent.portalID>
279:           selected</cfif>>#qryPortals.name#
280:         </cfloop>
281:       </select>
282:     </td>
283:   </tr>
284:   <cfelse>
285:     <input type="hidden" name="edtPortalID" value="#client.currentPortalID#">
286:   </cfif>
287:
288:   <cfif client.currentEntityType lte ap_securityPortal>
289:     <cfquery name="qryDist" dataSource="#ap_dataSource#">
290:       select distributors.distributorID, distributors.name as distName
291:       from distributors

```

```

289: join securityAccess on
290: (securityAccess.entityType = #ap_securityMastDist# or securityAccess.entityType = #ap_securityDist#)
291: and securityAccess.entityID = distributors.distributorID
292: and securityAccess.hierarchyID like '#client.hierarchyID#%'
293: order by distName
294: </cfquery>
295: <tr bgcolor="#eeeeee">
296: <td width="15%">Distributor:</td>
297: <td colspan="4">
298: <select name="edtDistDistributorID">
299: <option value="0"><cfif qryFindAgent.distributorID is 0 or trim(qryFindAgent.distributorID) is "">
selected</cfif><Not Assigned
</cfloop query="qryDist">
<option value="#qryDist.distributorID#"><cfif qryDist.distributorID is qryFindAgent.distributorID>
selected</cfif>#qryDist.distName#
</cfloop>
</select>
</td>
</tr>
<cfelse>
307: <cfif qryFindAgent.recordCount is 0>
308: <input type="hidden" name="edtDistributorID" value="#client.currentDistributorID#">
309: <cfelse>
310: <input type="hidden" name="edtDistributorID" value="#qryFindAgent.distributorID#">
311: </cfif>
312: </cfif>
313: </td>
314: </td>
315: <tr bgcolor="#eeeeee">
316: <td width="15%">Bio:</td>
317: <td colspan="4">
318: <textarea name="edtBio" rows="5" cols="60" wrap="virtual">#trim(qryFindAgent.bio)#</textarea>
319: </td>
320: </tr>
321:
322:
323: <tr bgcolor="#eeeeee">
324: <cfif qryFindAgent.recordCount is 0>
325: <td colspan="5">
326: <input type="submit" name="btnUpdate" value="Add Agent">
327: <input type="reset" value="Reset Info">
328: </td>
329: <cfelse>
330: <td colspan="4">
331: <input type="submit" name="btnUpdate" value="Update Agent Info">
332: <input type="reset" value="Reset Info">
333: </td>
334: <td align="right">
335: <input type="submit" name="btnDelete" value="Delete Agent">

```

```
336:         </td>
337:         </cfif>
338:     </tr>
339: </table>
340: </form>
341:
342: </cfoutput>
343:
344: </body>
345: </html>
```

```
<!--
-->
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <cfif not isDefined("form.agentID")>
4:   <cfset client.lookupID = -1>
5:   <cfset client.detailID = -1>
6:   <cfset client.userName = "">
7:   <cflocation url="agentAdm.cfm" addtoken="no">
8: </cfif>
9:
10: <cfquery name="qryFindAgent" datasource="#ap_dataSource#">
11:   select agent_id, name
12:   from agents
13:   where agents.agent_id = #form.agentID#
14: </cfquery>
15:
16: <cfinclude template="include\clearOldFields.cfm">
17: <cfset client.userName = "">
18:
19: <!-- Save form values in case something is wrong -->
20:
21: <cfif isDefined("form.btnUpdate")>
22:   <cfif qryFindAgent.recordCount is 0>
23:     <cfset client.lookupID = -1>
24:     <cfset client.detailID = -1>
25:     <cfset client.userName = "There was an error while creating the agent.">
26:   </cftransaction>
27:   <cfset cFirst = preservesingleQuotes(form.edtFirstName)>
28:   <cfset cLast = preservesingleQuotes(form.edtLastName)>
29:   <cfset cTitle = preservesingleQuotes(form.edtTitle)>
30:   <cfset cSpecialty = preservesingleQuotes(form.edtSpecialty)>
31:   <cfset cBio = preservesingleQuotes(form.edtBio)>
32:
33:   <cfquery name="qryGetIDs" datasource="#ap_dataSource#">
34:     select agency.distributorID, portals.portalID
35:     from agency
36:     join distributors on distributors.distributorID = agency.distributorID
37:     join portals on portals.portalID = distributors.portalID
38:     where agency.agency_id = #form.edtAgency#
39:   </cfquery>
40:
41:   <cfquery name="qryInsert" datasource="#ap_dataSource#">
42:     insert into agents
43:       (first_name, last_name, title, specialty, email, workPhone, extension,
44:        homePhone, pub_home, cellPhone, faxPhone, otherPhone, website,
45:        bio, agency_id, distributorID, portalID,
46:        values
47:        ('#cFirst#', '#cLast#', '#cTitle#', '#cSpecialty#', '#form.edtEmail#',
48:         '#form.edtWorkPhone#', '#form.edtExtension#', '#form.edtHomePhone#',
49:         '#form.edtPublishHome#', '#form.edtCellPhone#', '#form.edtFax#',

```



```

99:      <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
100:      update agents
101:      set image_name = '#cImage#',
102:          user_filename = '#cUserImage#'
103:      where agents.agent_id = #qryNewID.newID#
104:      </cfquery>
105:
106:
107:      <cfset nUpdateID = #qryNewID.newID#>
108:      <cfset nUpdateType = #ap_securityAgent#>
109:      <cfset nUpdateAction = "ADD">
110:      <cfinclude template="include\makeSecurityTree.cfm">
111:      <cfset client.cacheSecurity = false>
112:
113:      <cfset client.userName = form.edtFirstName & " " & form.edtLastName & " added.">
114:      </cftransaction>
115:
116:
117:      <cflocation url="agentAdm.cfm" addToken="no">
118:      <cfelse>
119:      <cfset client.lookupID = -1>
120:      <cfset client.detailID = -1>
121:      <cfset client.userName = "There was an error while updating the agent information.">
122:      </cftransaction>
123:
124:      <cfset cFirst = preservesingleQuotes(form.edtFirstName)>
125:      <cfset cLast = preservesingleQuotes(form.edtLastName)>
126:      <cfset cTitle = preservesingleQuotes(form.edtTitle)>
127:      <cfset cSpecialty = preservesingleQuotes(form.edtSpecialty)>
128:      <cfset cBio = preservesingleQuotes(form.edtBio)>
129:      <cfquery name="qryGetIDs" dataSource="#ap_dataSource#">
130:      select agency.distributorID, portals.portalID
131:      from agency
132:      join distributors on distributors.distributorID = agency.distributorID
133:      join portals on portals.portalID = distributors.portalID
134:      where agency.agency_id = #form.edtAgency#
135:      </cfquery>
136:
137:      <cfif isDefined("form.chkDeleteImage")>
138:      <cfset cImage = "">
139:      <cfset cUserImage = "">
140:      <cfelseif trim(form.edtAgentPhoto) is "">
141:      <cfset cImage = form.originalImageName>
142:      <cfset cUserImage = form.originalUserFilename>
143:      <cfelse>
144:      <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
145:      select distributors.agentImages
146:      from distributors
147:      where distributors.distributorID = #qryGetIDs.distributorID#

```

```

148: </cfquery>
149:
150: <!--- Upload the file to a unique name --->
151: <cffile
152:   destination = "#qryImagePath.agentImages#"
153:   action = "UPLOAD"
154:   nameconflict = "OVERWRITE"
155:   filefield = "edtAgentPhoto"
156: >
157:
158: <cfset cImage = file.serverFile>
159: <cfset cUserImage = file.serverFile>
160:
161: <cfset cImagePath = file.serverDirectory & "\">
162: <cfset cNewImage = "#ImagePath##form.agentID#_#file.serverFile#">
163:
164: <cfif fileExists(cNewImage)>
165:   <cffile
166:     action = "DELETE"
167:     file = "#cNewImage#"
168:   >
169: </cfif>
170:
171: <!--- Now rename the unique uploaded file to the new name -->
172: <cffile
173:   action = "RENAME"
174:   source = "#file.serverDirectory#\#file.serverFile#"
175:   destination = "#cNewImage#"
176: >
177:
178: <cfset cImage = cNewImage>
179: </cfif>
180:
181: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
182:   update agents
183:   set firstName = '#cFirst#',
184:   lastName = '#cLast#',
185:   title = '#cTitle#',
186:   specialty = '#cSpecialty#',
187:   email = '#form.edtEmail#',
188:   workPhone = '#form.edtWorkPhone#',
189:   extension = '#form.edtExtension#',
190:   homePhone = '#form.edtHomePhone#',
191:   pubHome = '#form.edtPublishHome#',
192:   cellPhone = '#form.edtCellPhone#',
193:   faxPhone = '#form.edtFax#',
194:   otherPhone = '#form.edtOtherPhone#',
195:   website = '#form.edtWebSite#',
196:   Bio = '#cBio#',

```



```

197: agency_id = #form.edtAgency#
198: distributorID = #qryGetIDs.distributorID#,
199: portalID = #qryGetIDs.portalID#,
200: image_name = '#cImage#',
201: userFilename = '#cUserImage#'
202: where agents.agent_id = #form.agentID#
203: </cfquery>
204:
205: <cfset nUpdateID = #form.agentID#>
206: <cfset nUpdateType = #ap_securityAgent#>
207: <cfset nUpdateAction = "UPDATE">
208: <cfinclude template="include\makeSecurityTree.cfm">
209: <cfset client.cacheSecurity = false>
210:
211: <cfif isDefined("form.chkDeleteImage")>
212: <cfset cImage = form.originalImageName>
213: <cfif fileExists(cImage)>
214: <cffile
215: action = "DELETE"
216: file="#cImage#"
217: >
218: </cfif>
219: </cfif>
220:
221: <cfset client.userName = form.edtFirstName & " " & form.edtLastName & " updated.">
222: </cftransaction>
223: <cflocation url="agentAdm.cfm" addtoken="no">
224: </cfif>
225: <cfelseif isDefined("form.btnDelete")>
226: <cflocation url="agentDelete.cfm" addtoken="no">
227: <cfelseif isDefined("form.btnConfirmedDelete")>
228: <cfset client.lookupID = -1>
229: <cfset client.detailID = -1>
230: <cfset client.userName = "Unable to delete #form.edtName#">
231: </cftransaction>
232: <cfquery name="qryDelete" datasource="#ap_dataSource#">
233: delete from agents
234: where agents.agent_id = #form.agentID#
235: </cfquery>
236:
237: <cfset nUpdateID = #form.agentID#>
238: <cfset nUpdateType = #ap_securityAgent#>
239: <cfset nUpdateAction = "DELETE">
240: <cfinclude template="include\makeSecurityTree.cfm">
241: <cfset client.cacheSecurity = false>
242:
243: <cfset client.userName = form.edtName & " deleted.">
244: </cftransaction>
245: <cflocation url="agentAdm.cfm" addtoken="no">

```

```
246: <cfelseif isDefined("form.btnCancelDelete")><!-- Cancel deletion -->
247: <cfset client.lookupID = #form.agentID#>
248: <cfset client.detailID = -1>
249: <cfset client.imageType = -1>
250: <cfset client.userName = "Deletion canceled.">
251: <cflocation url="agentMaint.cfm" addToken="no">
252: </cfif>
253:
254: <cflocation url="agentAdm.cfm" addToken="no">
```

```

1: <!--
2:   Product:    Full Impact
3:   Version:    1.0
4:   History:
5:
6:   --->
7:
8: <!-- Application Settings --->
9: <cfapplication
10:   name="FullImpactAdmin"
11:   clientManagement="yes"
12:   clientStorage="clientStorage"
13:   sessionManagement="yes"
14: >
15:
16: <!-- Product DataSource Information --->
17: <cfset ap_datasource = "fullImpactAlpha">
18:
19: <!-- Path Information --->
20: <cfset ap_rootPath = "c:\inetpub\multidimension\fullimpact\admin\">
21: <cfset ap_commonImages = "images/">
22:
23: <!--
24: <cfset ap_specialtyImages = "c:\inetpub\multidimension\fullimpact\specialtyImages\">
25: <cfset ap_communityImages = "c:\inetpub\multidimension\fullimpact\communityImages\">
26: <cfset ap_agentBioImages = "c:\inetpub\multidimension\fullimpact\agentBioImages\">
27: <cfset ap_agencyBioImages = "c:\inetpub\multidimension\fullimpact\agencyBioImages\">
28: <cfset ap_resourceImages = "c:\inetpub\multidimension\fullimpact\resourceImages\">
29: <cfset ap_homePageImages = "c:\inetpub\multidimension\fullimpact\homePageImages\">
30: <cfset ap_propertyImages = "c:\inetpub\multidimension\fullimpact\propertyImages\">
31: <cfset ap_agentImages = "c:\inetpub\multidimension\fullimpact\agentImages\">
32: --->
33:
34: <!-- Product Defaults --->
35: <cfset ap_defaultNavColor = "##330099"> <!-- Default navigation background color --->
36: <cfset ap_defaultMenuColor = "##990000"> <!-- Default menu background color --->
37:
38:
39: <!-- Error Handling --->
40: <cfset ap_defaultEmailProblems = "jjunker@techmission.com"> <!-- Default email to send error messages --->
41:
42: <cfset ap_securityYakalo = 1>
43: <cfset ap_securityPortal = 2>
44: <cfset ap_securityMastDist = 3>
45: <cfset ap_securityDist = 4>
46: <cfset ap_securityMastAgency = 5>
47: <cfset ap_securityAgency = 6>
48: <cfset ap_securityNoAgency = 7>
49: <cfset ap_securityAgent = 8>

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2: <cfset client.gotopage = "communityAdm.cfm">
3:
4: <cfif client.currentEntityType lt #ap_securityMastDist# and client.lookupDistID is -1>
5:   <!-- We do not know what distributor we should be editing, so find out -->
6:   <cfset client.lookupDistID = -1>
7:   <cfset client.lookupAgencyID = -1>
8:   <cfset client.lookupID = -1>
9:   <cfset client.DetailID = -1>
10:  <cflocation url="distSelect.cfm" addToken="no">
11: </cfif>
12:
13: <cfif client.currentEntityType lt #ap_securityMastDist#>
14:   <cfquery name="qryDist" dataSource="#ap_dataSource#">
15:     select distributors.name as distName
16:     from distributors
17:     where distributors.distributorID = #client.lookupDistID#
18:   </cfquery>
19:   <cfset cDistName = qryDist.distName>
20:   <cfelseif client.currentEntityType gte #ap_securityMastDist#>
21:     <cfset client.lookupDistID = client.currentEntityID>
22:     <cfset cDistName = "">
23:   </cfif>
24:
25:   <cfparam name="URL.sortBy" default="communityName">
26:   <cfset client.lookupID = -1>
27:   <cfset client.detailID = -1>
28:   <cfset client.imageType = -1>
29:   <cfset client.lookupAgencyID = -1>
30:
31:   <cfinclude template="include\clearOldFields.cfm">
32:
33:   <!-- Display rows -->
34:   <cfparam name="nStartFrom" default="1">
35:   <cfparam name="nEndDisplay" default="#client.displayRows#">
36:   <cfparam name="nEnd" default="#client.displayRows#">
37:
38:
39:   <cfquery name="qryEditList" dataSource="#ap_dataSource#">
40:     select communities.communityID, communities.name as communityName, regionValues.region as regionName
41:     from communities
42:     join securityAccess on
43:       (securityAccess.entityType = #ap_securityMastDist# or securityAccess.entityType = #ap_securityDist#)
44:       and securityAccess.entityID = communities.distributorID
45:       and securityAccess.hierarchyID like '#client.hierarchyID#%'
46:     left outer join regionValues on communities.regionID = regionValues.regionID
47:     where communities.distributorID = #client.lookupDistID#
48:     order by #url.sortBy#
49:   </cfquery>

```

2  
1



```
146: <form action="communityAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
147:   <input type="hidden" name="nStartFrom" value="#nPrevStart#">
148:   <input type="hidden" name="nToDisplay" value="#nToDisplay#">
149:   <input type="hidden" name="nEnd" value="#nPrevEnd#">
150:   <input type="submit" value="Previous #nToDisplay#">
151: </FORM>
152: </td>
153: </cfn>
154: <cfn nNextStart lte qryEditList.recordCount>
155: <td>
156:   <form action="communityAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
157:     <input type="hidden" name="nStartFrom" value="#nNextStart#">
158:     <input type="hidden" name="nToDisplay" value="#nToDisplay#">
159:     <input type="hidden" name="nEnd" value="#nNextEnd#">
160:     <cfn nLeftToShow = min(nToDisplay, (qryEditList.recordcount - cToDisplay))>
161:     <input type="submit" value="Next #nLeftToShow#">
162:   </form>
163: </td>
164: </cfn>
165: </tr>
166: </table>
167: </cfn>
168:
169: </body>
170: </html>
171:
```





```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfif client.currentEntityType lt #ap_securityMastDist#>
4:   <cfquery name="qryDist" dataSource="#ap_dataSource#">
5:     select distributors.name as distName
6:     from distributors
7:     where distributors.distributorID = #client.lookupDistID#
8:   </cfquery>
9:   <cfset cDistName = qryDist.distName>
10:  <cfelseif client.currentEntityType gte #ap_securityMastDist#>
11:    <cfset client.lookupDistID = client.currentDistributorID>
12:    <cfset cDistName = "">
13:  </cfif>
14:
15:
16:  <!-- Get ID number from edit -->
17:  <cfloop collection="#form#" item="cName">
18:    <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
19:      <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
20:      <cfset client.lookupID = val(cValue)>
21:      <cfset client.detailID = -1>
22:    </cfif>
23:  </cfloop>
24:
25:  <!-- Get ID number from edit -->
26:  <cfloop collection="#form#" item="cName">
27:    <cfif ucase(left(#cName#,4)) is "VIEW" and findNoCase(".X", #cName#,1) gt 0>
28:      <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
29:      <cfset client.lookupID = -1>
30:      <cfset client.detailID = -1>
31:      <cfset client.userMessage = "">
32:      <cflocation url="../communityView.cfm?communityID=#cValue#" addToken="no">
33:    </cfif>
34:  </cfloop>
35:
36:
37:  <cfif not isDefined("client.lookupID")>
38:    <cflocation url="communityAdm.cfm" addToken="no">
39:  </cfif>
40:  <cfparam name="client.userMessage" default="">
41:  <cfparam name="client.imageType" default="-1">
42:
43:  <cfquery name="qryFindCommunity" datasource="#ap_dataSource#">
44:    select * from communities
45:    where communities.communityID = #client.lookupID#
46:  </cfquery>
47:
48:  <cfquery name="qryRegions" dataSource="#ap_dataSource#">
49:    select regionID, region

```

```

50: from regionValues
51: where regionValues.distributorID = #client.lookupDistID#
52: order by region
53: </cfquery>
54:
55:
56: <cfif gryFindCommunity.recordCount gt 0>
57:   <cfset nCommunityID = gryFindCommunity.communityID>
58:   <cfset nDistributorID = gryFindCommunity.distributorID>
59:   <cfelse>
60:     <cfset nCommunityID = -1>
61:     <cfif client.currentEntityType gte #ap_securityMastDist#>
62:       <cfset nDistributorID = client.currentDistributorID>
63:       <cfelseif client.lookupDistID is not -1>
64:         <cfset nDistributorID = client.lookupDistID>
65:       <cfelse>
66:         <cflocation url="communityAdm.cfm" addToken="no">
67:       </cfif>
68:     </cfif>
69:
70:
71: <cfinclude template="include\javaValidate.cfm">
72:
73: <script language="JavaScript">
74:   <!--
75:   function validate(testform) {
76:     var results = "";
77:     var lResult = true;
78:
79:     if (removeSpaces(testform.edtName.value) == "") {
80:       results = results + " * Please enter a name for the community page.\r";
81:       lResult = false;
82:     }
83:     if (!isValidDate(testform.edtBeginDate.value)) {
84:       if (removeSpaces(testform.edtBeginDate.value) == "") {
85:         results = results + " * Please enter a valid beginning date.\r";
86:       }
87:     }
88:     results = results + " * " + testform.edtBeginDate.value + " is not valid. Please enter a valid beginning date.\r";
89:   }
90:   lResult = false;
91: }
92:
93: if (!isValidDate(testform.edtEndDate.value)) {
94:   if (removeSpaces(testform.edtEndDate.value) == "") {
95:     results = results + " * Please enter a valid ending date.\r";
96:   }
97: }
98: results = results + " * " + testform.edtEndDate.value + " is not valid. Please enter a valid ending date.\r";

```

```

99:     }
100:     lResult = false;
101: }
102:
103: // Netscape does not recognize the value of select elements, but does know which item was selected
104: if ((testform.edtDistributorID.value == "-1") || (testform.edtDistributorID.selectedindex == 0)) {
105:     results = results + " " You must select a distributor for this community page.\r";
106:     lResult = false;
107: }
108:
109: if (!lResult) {
110:     window.alert(results);
111: }
112: return lResult;
113: }
114: -->
115: </script>
116:
117: <html>
118: <head>
119:     <cfoutput>
120:         <title>#client.backofficeName# Backoffice Community Maintenance</title>
121:     </cfoutput>
122:     <link rel="stylesheet" href="style1.css" type="text/css">
123: </head>
124:
125: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
126: <cfinclude template="include\nocache.cfm">
127:
128: <p><cfinclude template="include\header.cfm"></p>
129:
130: <cfoutput>
131:
132: <form action="communityUpdate.cfm" method="post" enctype="multipart/form-data" onsubmit="return validate(this)">
133:     <input type="hidden" name="communityID" value="#nCommunityID#">
134:     <input type="hidden" name="originalHeaderImage" value="#qryFindCommunity.headerImage#">
135:     <input type="hidden" name="originalUserHeader" value="#qryFindCommunity.userHeaderImage#">
136:     <input type="hidden" name="originalFooterImage" value="#qryFindCommunity.footerImage#">
137:     <input type="hidden" name="originalUserFooter" value="#qryFindCommunity.userFooterImage#">
138:     <input type="hidden" name="edtDistributorID" value="#nDistributorID#">
139:     <input type="hidden" name="distributorID" value="#nDistributorID#">
140:     <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
141:         <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Community Maintenance</b></span>
142:             <cfif client.lookupID is -1>
143:                 <nbsp;   <b>Create a new community
144:                 <cfif cDistName is not "">
145:                     for #cDistName#
146:                 </cfif>
147:             </td>

```

```

148:         </cfif>
149:     </td></tr>
150:
151:     <CFIF client.userName is not "">
152:         <tr bgcolor="eeeeee">
153:             <td colspan="5"><p><font color="red">#client.userName#</font></p></td>
154:         </tr>
155:         <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
156:     </CFIF>
157:     <cfset client.userName = "">
158:
159:     <tr bgcolor="eeeeee">
160:         <td width="15%"><b>Name:</b></td>
161:         <td colspan="4"><input type="text" name="qryFindCommunity.name#" value="qryFindCommunity.name#" size="60"></td>
162:     </tr>
163:     <tr bgcolor="##eeeeee">
164:         <td width="15%"><b>Begin Date:</b></td>
165:         <td width="34%"><input type="text" name="edtBeginDate" value="#dateFormat(qryFindCommunity.beginDate, "mm/dd/yyyy")#"
size="10"><i>(MM/DD/YY or MM/DD/YYYY)</i></td>
166:         <td width="2%">&nbsp;</td>
167:         <td width="15%"><b>End Date:</b></td>
168:         <td width="34%"><input type="text" name="edtEndDate" value="#dateFormat(qryFindCommunity.endDate, "mm/dd/yyyy")#"
size="10"><i>(MM/DD/YY or MM/DD/YYYY)</i></td>
169:     </tr>
170:     <tr bgcolor="##eeeeee">
171:         <td width="15%">Header: Image:</td>
172:         <td colspan="4">
173:             <input type="file" name="edtHeaderImage" size="30">
174:             <cfif trim(qryFindCommunity.headerImage) is not "">
175:                 <i>&nbsp;</i> #qryFindCommunity.userHeaderImage#</i>
176:             </cfif>
177:         </td>
178:     </tr>
179:     <tr bgcolor="##eeeeee">
180:         <td width="15%">Footer: Image:</td>
181:         <td colspan="4">
182:             <input type="file" name="edtFooterImage" size="30">
183:             <cfif trim(qryFindCommunity.footerImage) is not "">
184:                 <i>&nbsp;</i> #qryFindCommunity.userFooterImage#</i>
185:             </cfif>
186:         </td>
187:     </tr>
188:
189:     <tr bgcolor="##eeeeee">
190:         <td width="15%">Region:</td>
191:         <td width="34%">
192:             <cfif qryRegions.recordCount gt 0>
193:                 <select name="edtRegionID">
194:                     <option value="0"><cfif client.lookupID is -1 or qryFindCommunity.regionID le 0> selected</cfif><Not Assigned

```

```

195:         <cfloop query="qryRegions">
196:             <option value="#qryRegions.regionID#" <cfif qryFindCommunity.regionID is qryRegions.regionID>
selected</cfif>>#qryRegions.region#
197:             </cfloop>
198:             </select>
199:             <cfelse>
200:                 <i>No Regions Defined</i>
201:                 <input type="hidden" name="edtRegionID" value="-1">
202:             </cfif>
203:         </td>
204:         <td width="28%">&nbsp;</td>
205:         <td width="15%">Alternate URL:</td>
206:         <td width="34%"><input type="text" name="edtAlternateURL" value="#qryFindCommunity.alternateURL#" size="40"></td>
207:     </tr>
208:
209:     <tr bgcolor="#eeeeee">
210:         <td width="15%">Description:</td>
211:         <td colspan="4">
212:             <textarea name="edtDesc" rows="5" cols="60" wrap="virtual">#trim(qryFindCommunity.description)#</textarea>
213:         </td>
214:     </tr>
215:
216:     <!--
217:     <cfif client.currentEntityType lte ap_securityPortal>
218:         <cfquery name="qryDist" datasource="#ap_datasource#">
select distributors.distributorID, distributors.name as distName
219:         from distributors
220:         join securityAccess on
221:             (securityAccess.entityType = #ap_securityMastDist# or securityAccess.entityType = #ap_securityDist#)
222:         and securityAccess.entityID = distributors.distributorID
223:         and securityAccess.hierarchyID like '#client.hierarchyID#%'
224:         order by distName
225:     </cfquery>
226:
227:     <tr bgcolor="#eeeeee">
228:         <td width="15%">Distributor:</td>
229:         <td colspan="4">
230:             <select name="edtDistributorID">
231:                 <option value="0"><cfif qryFindCommunity.distributorID is 0 or trim(qryFindCommunity.distributorID) is "">
selected</cfif>>Not Assigned
232:             <cfloop query="qryDist">
233:                 <option value="#qryDist.distributorID#"><cfif qryDist.distributorID is qryFindCommunity.distributorID>
selected</cfif>>#qryDist.distName#
234:             </cfloop>
235:             </select>
236:         </td>
237:     </tr>
238:     <cfelse>
239:         <cfif qryFindCommunity.recordCount is 0>

```

```

241:     <input type="hidden" name="edtDistributorID" value="#qryFindCommunity.distributorID#">
242:   </cfelse>
243:   <input type="hidden" name="edtDistributorID" value="#qryFindCommunity.distributorID#">
244: </cfif>
245: </cfif>
246: -->
247:
248:   <tr bgcolor="eeeeee">
249:     <cfif qryFindCommunity.recordCount is 0>
250:       <td colspan="5">
251:         <input type="submit" name="btnUpdate" value="Add Community">
252:         <input type="reset" value="Reset Info">
253:       </td>
254:     </cfelse>
255:     <td colspan="4">
256:       <input type="submit" name="btnUpdate" value="Update Community">
257:       <input type="reset" value="Reset Info">
258:       <input type="submit" name="btnView" value="View Community Page">
259:     </td>
260:     <td align="right">
261:       <input type="submit" name="btnDelete" value="Delete Community">
262:     </td>
263:   </cfif>
264: </tr>
265: </table>
266: </form>
267: </cfoutput>
268:
269: <!-- If this community page has already been created, allow paragraph editing -->
270:
271: <cfif qryFindCommunity.recordCount gt 0>
272:   <script language="JavaScript">
273:     /--
274:     function validateDetail(testForm) {
275:       var results = "";
276:       var lResult = true;
277:
278:       if ((removeSpaces(testForm.edtSortOrder.value) != "") && (!isNumber(testForm.edtSortOrder.value))) {
279:         results = results + " " + testForm.edtSortOrder.value + " is not a valid numeric sort order value.\r";
280:         lResult = false;
281:       }
282:
283:       if (!lResult) {
284:         window.alert(results);
285:       }
286:
287:       return lResult;
288:     }
289:   -->

```

```

290: </script>
291:
292: <cfquery name="qryDetail" dataSource="#ap_dataSource#">
293:   select communityDetail.*, imageTypes.description as imageName
294:   from communityDetail
295:   left outer join imageTypes on imageTypes.imageType = communityDetail.imageType
296:   where communityDetail.communityID = #client.lookupID#
297:   order by communityDetail.sortOrder
298: </cfquery>
299:
300: <cfquery name="qryEdit" dataSource="#ap_dataSource#">
301:   select communityDetail.*,
302:   imageTypes.isFormField, imageTypes.isApplet, imageTypes.isURL
303:   from communityDetail
304:   left outer join imageTypes on imageTypes.imageType = communityDetail.imageType
305:   where communityDetail.communityID = #client.lookupID#
306:   and communityDetail.communityDetailID = #client.detailID#
307: </cfquery>
308:
309: <cfquery name="qryImageTypes" dataSource="#ap_dataSource#">
310:   select imageType, description, isFormField, isApplet, isURL
311:   from imageTypes
312:   order by description
313: </cfquery>
314:
315: <!-- Set default values -->
316: <cfif qryEdit.recordCount is 0> <!-- New record -->
317:   <cfif isDefined("client.old_sortOrder")>
318:     <cfset nSortOrder = client.old_sortOrder>
319:   <cfelse>
320:     <cfset nSortOrder = "1">
321:   </cfif>
322:
323:   <cfquery name="qryDefault" dataSource="#ap_dataSource#">
324:     select imageType from imageTypes
325:     where imageTypes.description = 'Standard Photo'
326:   </cfquery>
327:   <cfif client.imageType gt -1>
328:     <cfset nImageType = client.imageType>
329:   <cfelseif qryDefault.recordCount gt 0>
330:     <cfset nImageType = qryDefault.imageType>
331:   <cfelse>
332:     <cfset nImageType = 0>
333:   </cfif>
334:
335:   <cfelse> <!-- Existing record -->
336:   <cfif isDefined("client.old_sortOrder")>
337:     <cfset nSortOrder = client.old_sortOrder>
338:   <cfelse>
339:     <cfset nSortOrder = qryEdit.sortOrder>

```

```

339: </cfif>
340:
341: <cfif client.imageType gt -1>
342:   <cfset nImageType = client.imageType>
343: <cfelse>
344:   <cfset nImageType = qryEdit.imageType>
345: </cfif>
346: </cfif>
347: <cfif isDefined("client.old_title")>
348:   <cfset cTitle = client.old_title>
349: <cfelse>
350:   <cfset cTitle = trim(qryEdit.title)>
351: </cfif>
352: <cfif isDefined("client.old_alignment")>
353:   <cfset cAlignment = client.old_alignment>
354: <cfelse>
355:   <cfset cAlignment = trim(qryEdit.alignment)>
356: </cfif>
357: <cfif isDefined("client.old_desc")>
358:   <cfset cDesc = client.old_desc>
359: <cfelse>
360:   <cfset cDesc = trim(qryEdit.text)>
361: </cfif>
362:
363: <cfquery name="qryImageInfo" dataSource="#ap_dataSource#">
364:   select formTitle, isFormField, isApplet, isURL
365:   from imageTypes
366:   where imageTypes.imageType = #nImageType#
367: </cfquery>
368:
369: <form action="communityUpdate.cfm" method="post" enctype="multipart/form-data" onsubmit="return validateDetail(this)">
370:   <cfoutput>
371:     <input type="hidden" name="communityID" value="#client.lookupID#">
372:     <input type="hidden" name="communityDetailID" value="#client.detailID#">
373:     <input type="hidden" name="originalImage" value="#qryEdit.image#">
374:     <input type="hidden" name="originalUserImage" value="#qryEdit.userName#">
375:     <input type="hidden" name="distributorID" value="#nDistributorID#">
376:   </cfoutput>
377:
378:   <cfif qryDetail.recordCount is 0>
379:     <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
380:       <tr><td colspan="6"><i><b>There are no paragraphs defined.</b></i></td></tr>
381:       <tr><td colspan="6">&nbsp;</td></tr>
382:     </table>
383:   <cfelse>
384:     <table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
385:       <tr valign="top" bgcolor="#cccccc">
386:         <td><b>Image Type</b></td>
387:         <td><b>Title</b></td>

```



```

388: <td><b>Text</b></td>
389: <td><b>Image Name</b></td>
390: <td><b>Alignment</b></td>
391: <td><b>Order</b></td>
392: <td>&nbsp;</td>
393: </tr>
394: <cfoutput query="qryDetail">
395: <tr valign="top" bgcolor="#ffffffcc<cfif qryDetail.communityDetailID is client.detailID>#ffffffcc<cfelse>#ffffffcc</cfif>">
396: <td>
397: <cfif trim(qryDetail.imageName) is "">&nbsp;</cfif><cfif>#qryDetail.imageName#
398: </td>
399: <td>
400: <cfif trim(qryDetail.title) is "">&nbsp;</cfif><cfif>#qryDetail.title#
401: </td>
402: <td>
403: <cfif trim(qryDetail.text) is "">&nbsp;</cfif><cfif>#qryDetail.text#
404: </td>
405: <td>
406: <cfif trim(qryDetail.userName) is "">&nbsp;</cfif><cfif>#qryDetail.userName#
407: </td>
408: <td>#qryDetail.alignment#</td>
409: <td>#qryDetail.sortOrder#</td>
410: <td align="center">
411: <input type="image" name="edit#qryDetail.communityDetailID#" src="#ap_commonImages#edit.gif" alt="Edit"
border="0">
412: <br>
413: <input type="image" name="delete#qryDetail.communityDetailID#" src="#ap_commonImages#delete.gif" alt="Delete"
border="0">
414: </td>
415: </tr>
416: </cfoutput>
417: </table>
418: </cfif>
419: <cfoutput>
420: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
421: <tr><td colspan="5">&nbsp;</td></tr>
422: <cfif client.detailID is -1>
423: <tr bgcolor="#cccccc"><td colspan="5"><b>Add a paragraph</b></td></tr>
424: <cfelse>
425: <tr bgcolor="#cccccc"><td colspan="5"><b>Edit this paragraph</b></td></tr>
426: </cfif>
427: <tr valign="top" bgcolor="#ffffff">
428: <td><b>Image Type</b></td>
429: <td><b>Title</b></td>
430: <td><b>#qryImageInfo.formTitle#</b></td>
431: <td><b>Alignment</b></td>
432: <td><b>Order</b></td>
433: </tr>
434: <tr valign="top" bgcolor="#ffffff">

```

```

435: <td>
436: <select name="editImageType">
437: <cfloop query="qryImageTypes">
438: <option value="#qryImageTypes.imageType#"><cfif qryImageTypes.imageType is nImageType>
selected</cfif>>#qryImageTypes.description#
439: </cfloop>
440: </select>
441: <cfif qryImageTypes.recordCount gt 1>
442: <input type="submit" name="btnImageType" value="Change">
443: </cfif>
444: </td>
445: <td><input type="text" name="editTitle" value="#cTitle#"></td>
446: <td>
447: <cfif qryImageInfo.isFormField is "Y">
448: <input type="File" name="editImage"></td>
449: <cfelseif qryImageInfo.isApplet is "Y">
450: <input type="text" name="editImage">
451: <cfelseif qryImageInfo.isURL is "Y">
452: <input type="text" name="editImage">
453: <cfelse> <!-- The default if a new entry -->
454: <input type="File" name="editImage"></td>
455: </cfif>
456: </td>
457: <td>
458: <select name="editAlignment">
459: <option value="left"><cfif lcase(cAlignment) is "left"> selected</cfif>>Left
460: <option value="middle"><cfif lcase(cAlignment) is "middle"> selected</cfif>>Middle
461: <option value="right"><cfif lcase(cAlignment) is "right"> selected</cfif>>Right
462: </select>
463: </td>
464: <td><input type="text" name="editSortOrder" value="#nSortOrder#" size="2"></td>
465: </tr>
466: <tr valign="top" bgcolor="#eeeeee">
467: <td colspan="5">
468: <b>Text:</b><br>
469: <textarea name="edtDesc" rows="5" cols="80" wrap="virtual">#trim(cDesc)#</textarea>
470: </td>
471: </tr>
472: <tr bgcolor="eeeeee">
473: <td colspan="5">
474: <cfif qryEdit.recordCount is 0>
475: <input type="submit" name="btnUpdateDetail" value="Add Paragraph">
476: <input type="reset" value="Reset Info">
477: </td>
478: <cfelse>
479: <input type="submit" name="btnUpdateDetail" value="Update Paragraph">
480: <input type="reset" value="Reset Info">
481: <input type="submit" name="btnCancelDetail" value="Cancel">
482: </cfif>

```

```

483:         </td>
484:     </tr>
485: </table>
486: </cfoutput>
487: </form>
488: </cfcif>
489:
490: </body>
491: </html>

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <cfif not isDefined("form.communityID")>
4:   <cfset client.lookupID = -1>
5:   <cfset client.detailID = -1>
6:   <cfset client.imageType = -1>
7:   <cfset client.userName = "">
8:   <cflocation url="communityAdm.cfm" addtoken="no">
9: </cfif>
10:
11: <cfquery name="qryFindCommunity" datasource="#ap_dataSource#">
12:   select communityID, name
13:   from communities
14:   where communities.communityID = #form.communityID#
15: </cfquery>
16:
17: <cfinclude template="include\clearOldFields.cfm">
18: <cfset client.userName = "">
19: <cfset client.imageType = -1>
20:
21: <cfif isDefined("form.btnImageType")>
22:   <!-- A change in the image type has been requested -->
23:   <cfset client.lookupID = form.communityID>
24:   <cfset client.detailID = form.communityDetailID>
25:   <cfset client.imageType = form.edtImageType>
26:
27:   <cfset client.old_title = form.edtTitle>
28:   <cfset client.old_alignment = form.edtAlignment>
29:   <cfset client.old_sortOrder = form.edtSortOrder>
30:   <cfset client.old_desc = form.edtDesc>
31:
32:   <cflocation url="communityMaint.cfm" addToken="no">
33: </cfif>
34:
35:
36: <cfif isDefined("form.btnCancelDetail")> <!-- Cancel detail edit -->
37:   <cfset client.lookupID = #form.communityID#>
38:   <cfset client.detailID = -1>
39:   <cfset client.imageType = -1>
40:   <cfset client.userName = "">
41:   <cflocation url="communityMaint.cfm" addToken="no">
42:
43: <cfelseif isDefined("form.btnCancelDelete")> <!-- Cancel detail edit -->
44:   <cfset client.lookupID = #form.communityID#>
45:   <cfset client.detailID = -1>
46:   <cfset client.imageType = -1>
47:   <cfset client.userName = "Deletion canceled.">
48:   <cflocation url="communityMaint.cfm" addToken="no">
49:

```

```

50: <cfelseif isDefined("form.btnUpdateDetail")>
51: <cflocation url="..../communityView.cfm?communityID=#form.communityID#" addToken="no">
52:
53: <cfelseif isDefined("form.btnUpdateDetail")>
54: <cfquery name="qryFindDetail" dataSource="#ap_dataSource#">
55:   select communityDetailID
56:   from communityDetail
57:   where communityDetailID = #form.communityDetailID#
58: </cfquery>
59:
60: <cfif qryFindDetail.recordCount is 0>
61:   <cfset cTitle = preservesingleQuotes(form.edtTitle)>
62:   <cfset cDesc = preservesingleQuotes(form.edtDesc)>
63:   <cfset nSortOrder = val(form.edtSortOrder)>
64:
65:   <cfquery name="qryImageType" dataSource="#ap_dataSource#">
66:     select imageType, isFormField, isApplet, isURL
67:     from imageTypes
68:     where imageTypes.imageType = #form.edtImageType#
69:   </cfquery>
70:
71:   <cfif qryImageType.isFormField is "Y">
72:     <cfif trim(form.edtImage) is "">
73:       <cfset cImage = form.originalImage>
74:       <cfset cUserImage = form.originalUserImage>
75:     <cfelse>
76:       <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
77:         select distributors.communityImages
78:         from distributors
79:         where distributors.distributorID = #form.distributorID#
80:       </cfquery>
81:       <!-- Upload the file to a unique name -->
82:       <cfif
83:         destination = "#qryImagePath.communityImages#"
84:         action = "UPLOAD"
85:         nameConflict = "OVERWRITE"
86:         field = "edtImage"
87:       >
88:
89:       <cfset cImage = file.serverFile>
90:       <cfset cUserImage = file.serverFile>
91:
92:       <cfset cImagePath = file.serverDirectory & "\">
93:       <cfset cNewImage = "#cImagePath#trim(form.communityID)#_#file.serverFile#">
94:
95:       <cfif fileExists(cNewImage)>
96:         <cfif
97:           action = "DELETE"
98:           file="#cNewImage#"

```

```

99: >
100: </cfif>
101:
102: <!--- Now rename the unique uploaded file to the new name --->
103: <cfif>
104:     action = "RENAME"
105:     source = "#file.serverDirectory#\#file.serverFile#"
106:     destination="#cNewImage#"
107: >
108:
109:     <cfset cImage = cNewImage>
110:     </cfif>
111:     <cfelseif qryImageType.isURL is "Y">
112:         <cfset cImage = form.edtImage>
113:         <cfset cUserImage = form.edtImage>
114:         <cfelseif qryImageType.isApplet is "Y">
115:             <cfset cImage = form.edtImage>
116:             <cfset cUserImage = form.edtImage>
117:         <cfelse>
118:             <cfset cImage = form.edtImage>
119:             <cfset cUserImage = form.edtImage>
120:         </cfif>
121:
122:
123:     <cfquery name="qryInsert" dataSource="#ap_dataSource#">
124:         insert into communityDetail
125:             (communityID, sortOrder, title, image, userFilename, imageType,
126:              alignment, text)
127:         values
128:             (#form.communityID#, #nsortOrder#, '#cTitle#',
129:              '#cImage#', '#cUserImage#', #form.edtImageType#, '#form.edtAlignmert#',
130:              '#cDesc#')
131:     </cfquery>
132:
133:     <cfset client.lookupID = form.communityID>
134:     <cfset client.detailID = -1>
135:     <cfset client.imageType = form.edtImageType> <!--- Keep last inserted image type --->
136:
137:     <cflocation url="communityMaint.cfm" addToken="no">
138:
139: <cfelse>
140:     <cfset cTitle = preserveSingleQuotes(form.edtTitle)>
141:     <cfset cDesc = preserveSingleQuotes(form.edtDesc)>
142:     <cfset nsortOrder = val(form.edtSortOrder)>
143:
144:     <cfquery name="qryImageType" dataSource="#ap_dataSource#">
145:         select imageType, isFormField, isApplet, isURL
146:         from imageTypes
147:         where imageTypes.imageType = #form.edtImageType#

```

```

148: </cfquery>
149:
150: <cfif qryImageType.isFormField is "Y">
151:   <cfif trim(form.edtImage) is "">
152:     <cfset cImage = form.originalImage>
153:     <cfset cUserImage = form.originalUserImage>
154:   </cfelse>
155:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
156:       select distributors.communityImages
157:       from distributors
158:       where distributors.distributorID = #form.distributorID#
159:     </cfquery>
160:     <!-- Upload the file to a unique name -->
161:     <cffile
162:       destination = "#qryImagePath.communityImages#"
163:       action = "UPLOAD"
164:       nameconflict = "OVERWRITE"
165:       fieldid = "edtImage"
166:     >
167:
168:     <cfset cImage = file.serverFile>
169:     <cfset cUserImage = file.serverFile>
170:
171:     <cfset cImagePath = file.serverDirectory & "\">
172:     <cfset cNewImage = "#cImagePath#trim(form.communityID)#_#file.serverFile#">
173:
174:     <cfif fileExists(cNewImage)>
175:       <cffile
176:         action = "DELETE"
177:         file="#cNewImage#"
178:       >
179:     </cfif>
180:
181:     <!-- Now rename the unique uploaded file to the new name -->
182:     <cffile
183:       action = "RENAME"
184:       source = "#file.serverDirectory#\#file.serverFile#"
185:       destination="#cNewImage#"
186:     >
187:
188:     <cfset cImage = cNewImage>
189:   </cfif>
190:   <cfelseif qryImageType.isURL is "Y">
191:     <cfset cImage = form.edtImage>
192:     <cfset cUserImage = form.edtImage>
193:   <cfelseif qryImageType.isApplet is "Y">
194:     <cfset cImage = form.edtImage>
195:     <cfset cUserImage = form.edtImage>
196:   </cfelse>

```

```

197: <cfset cImage = form.edtImage>
198: <cfset cUserInfo = form.edtImage>
199: </cfif>
200:
201: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
202:   update CommunityDetail
203:   set
204:     sortOrder = #nSortOrder#,
205:     title = '#cTitle',
206:     imageType = #form.edtImageType#,
207:     alignment = '#form.edtAlignment',
208:     image = '#cImage',
209:     username = '#cUserInfo',
210:     text = '#cDesc'
211:   where communityDetail.communityDetailID = #form.communityDetailID#
212: </cfquery>
213:
214: <cfset client.lookupID = form.communityID>
215: <cfset client.detailID = -1>
216: <cfset client.imageType = -1>
217:
218: <cflocation url="communityMaint.cfm" addToken="no">
219:
220: </cfif>
221:
222: <cfelseif isDefined("form.btnUpdate")>
223: <cfif qryFindCommunity.recordCount is 0>
224:   <cfset client.lookupID = -1>
225:   <cfset client.detailID = -1>
226:   <cfset client.userName = "There was an error while creating the community page.">
227:   <cftransaction>
228:     <cfset cName = preservesingleQuotes(form.edtName)>
229:     <cfset cDesc = preservesingleQuotes(form.edtDesc)>
230:
231:     <cfquery name="qryInsert" dataSource="#ap_dataSource#">
232:       insert into communities
233:         (distributorID, name, regionID, headerImage, userHeaderImage,
234:          footerImage, userFooterImage, beginDate, endDate, alternateURL,
235:          description)
236:       values
237:         (#form.edtDistributorID, '#cName', '#form.edtRegionID',
238:          '', '',
239:          '', '',
240:          '#form.edtBeginDate', '#form.edtEndDate',
241:          '#form.edtAlternateURL', '#cDesc')
242:     </cfquery>
243:
244:     <cfquery name="qryGetID" dataSource="#ap_dataSource#">
245:       select max(communityID) as lastID

```



```

246: from communities
247: </cfquery>
248: <cfset nCommunityID = qryGetID.lastID>
249: <cfset client.lookupID = nCommunityID>
250:
251:
252: <cfif trim(form.edtHeaderImage) is "">
253:   <cfset cHeaderImage = form.originalHeaderImage>
254:   <cfset cUserHeaderImage = form.originalUserHeader>
255: <cfelse>
256:   <cfquery name="qryImagePath" datasource="#ap_datasource#">
257:     select distributors.communityImages
258:     from distributors
259:     where distributors.distributorID = #form.distributorID#
260:   </cfquery>
261:   <!--- Upload the file to a unique name --->
262:   <cfif
263:     destination = "#qryImagePath.communityImages#"
264:     action = "UPLOAD"
265:     nameconflict = "OVERWRITE"
266:     filefield = "edtHeaderImage"
267:   >
268:
269:   <cfset cImage = file.serverFile>
270:   <cfset cUserHeaderImage = file.serverFile>
271:
272:   <cfset cImagePath = file.serverDirectory & "\">
273:   <cfset cNewImage = "#cImagePath#trim(nCommunityID)#_#file.serverFile#">
274:
275:   <cfif fileExists(cNewImage)>
276:     <cfif
277:       action = "DELETE"
278:       file="#cNewImage#"
279:     >
280:   </cfif>
281:
282:   <!--- Now rename the unique uploaded file to the new name --->
283:   <cfif
284:     action = "RENAME"
285:     source = "#file.serverDirectory#\#file.serverFile#"
286:     destination="#cNewImage#"
287:   >
288:   <cfset cHeaderImage = cNewImage>
289: </cfif>
290:
291: <cfif trim(form.edtFooterImage) is "">
292:   <cfset cFooterImage = form.originalFooterImage>
293:   <cfset cUserFooterImage = form.originalUserFooter>
294: <cfelse>

```

```

295: <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
296: select distributors.communityImages
297: from distributors
298: where distributors.distributorID = #form.distributorID#
299: </cfquery>
300: <!-- Upload the file to a unique name -->
301: <cffile
302: destination = "#qryImagePath.communityImages#"
303: action = "UPLOAD"
304: nameconflict = "OVERWRITE"
305: filefield = "edtFooterImage"
306: >
307:
308: <cfset cImage = file.serverFile>
309: <cfset cUserFooterImage = file.serverFile>
310:
311: <cfset cImagePath = file.serverDirectory & "\">
312: <cfset cNewImage = "#cImagePath#trim(nCommunityID)#_#file.serverFile#">
313:
314: <cfif fileExists(cNewImage)>
315:     <cffile
316:         action = "DELETE"
317:         file="#cNewImage#"
318:     >
319: </cfif>
320:
321: <!-- Now rename the unique uploaded file to the new name ---->
322: <cffile
323:     action = "RENAME"
324:     source = "#file.serverDirectory#\#file.serverFile#"
325:     destination="#cNewImage#"
326: >
327: <cfset cFooterImage = cNewImage>
328: </cfif>
329:
330: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
331: update communities
332: set headerImage = 'cHeaderImage#',
333: userHeaderImage = 'cUserHeaderImage#',
334: footerImage = 'cFooterImage#',
335: userFooterImage = 'cUserFooterImage#',
336: where communities.communityID = #nCommunityID#
337: </cfquery>
338:
339: <cfset client.userMessage = "" & form.edtName & "' Community was created.'">
340: </cftransaction>
341:
342: <cfif client.lookupID gt 0>
343: <cflocation url="communityMaint.cfm" addToken="no">

```

```

344: <cfelse>
345:   <cflocation url="communityAdm.cfm" addToken="no">
346: </cfif>
347:
348: <cfelse>
349:   <cfset client.lookupID = form.communityID>
350:   <cfset client.detailID = -1>
351:   <cfset client.userName = "There was an error while updating the community page information.">
352:   <cftransaction>
353:     <cfset cName = preservesingleQuotes(form.edtName)>
354:     <cfset cDesc = preservesingleQuotes(form.edtDesc)>
355:     <cfif trim(form.edtHeaderImage) is "">
356:       <cfset cHeaderImage = form.originalHeaderImage>
357:     <cfset cUserHeaderImage = form.originalUserHeader>
358:   <cfelse>
359:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
360:       select distributors.communityImages
361:       from distributors
362:       where distributors.distributorID = #form.distributorID#
363:     </cfquery>
364:     <!--- Upload the file to a unique name --->
365:     <cffile
366:       destination = "#qryImagePath.communityImages#"
367:       action = "UPLOAD"
368:       nameconflict = "OVERWRITE"
369:       filefield = "edtHeaderImage"
370:     >
371:
372:     <cfset cImage = file.serverFile>
373:     <cfset cUserHeaderImage = file.serverFile>
374:
375:     <cfset cImagePath = file.serverDirectory & "\">
376:     <cfset cNewImage = "#cImagePath#trim(form.communityID)#_file.serverFile#">
377:
378:     <cfif fileExists(cNewImage)>
379:       <cffile
380:         action = "DELETE"
381:         file="#cNewImage#"
382:       >
383:     </cfif>
384:
385:     <!--- Now rename the unique uploaded file to the new name --->
386:     <cffile
387:       action = "RENAME"
388:       source = "#file.serverDirectory#\#file.serverFile#"
389:       destination="#cNewImage#"
390:     >
391:     <cfset cHeaderImage = cNewImage>
392:   </cfif>

```

```

393:
394:
395:
396:
397:
398:
399:
400:
401:
402:
403:
404:
405:
406:
407:
408:
409:
410:
411:
412:
413:
414:
415:
416:
417:
418:
419:
420:
421:
422:
423:
424:
425:
426:
427:
428:
429:
430:
431:
432:
433:
434:
435:
436:
437:
438:
439:
440:
441:

```

```

<cfif trim(form.edtFooterImage) is "">
  <cfset cFooterImage = form.originalFooterImage>
  <cfset cUserFooterImage = form.originalUserFooter>
<cfelse>
  <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
    select distributors.communityImages
    from distributors
    where distributors.distributorID = #form.distributorID#
  </cfquery>
  <!--- Upload the file to a unique name --->
  <cffile
    destination = "#qryImagePath.communityImages#"
    action = "UPLOAD"
    nameconflict = "OVERWRITE"
    filefield = "edtFooterImage"
  >
  <cfset cImage = file.serverFile>
  <cfset cUserFooterImage = file.serverFile>
  <cfset cImagePath = file.serverDirectory & "\">
  <cfset cNewImage = "#ImagePath#trim(form.communityID)#_#file.serverFile#">
  <cfif fileExists(cNewImage)>
    <cffile
      action = "DELETE"
      file="#cNewImage#"
    >
  </cfif>
  <!--- Now rename the unique uploaded file to the new name --->
  <cffile
    action = "RENAME"
    source = "#file.serverDirectory#\#file.serverFile#"
    destination="#cNewImage#"
  >
  <cfset cFooterImage = cNewImage>
</cfif>
<cfquery name="qryUpdate" dataSource="#ap_dataSource#">
  update communities
  set distributorID = #form.edtDistributorID#,
    name = '#cName#',
    regionID = '#form.edtRegionID#',
    headerImage = '#cHeaderImage#',
    userHeaderImage = '#cUserHeaderImage#',
    footerImage = '#cFooterImage#',
    userFooterImage = '#cUserFooterImage#',

```

```

442: beginDate = '#form.edtBeginDate#'
443: endDate = '#form.edtEndDate#'
444: alternateURL = '#form.edtAlternateURL#'
445: description = '#cDesc#'
446: where communities.communityID = #form.communityID#
447: </cfquery>
448:
449: <cfset client.detailID = -1>
450: <cfset client.userName = "" & #form.edtName# & " community page was updated.">
451: </cftransaction>
452:
453: <cfif client.lookupID gt 0>
454:   <cflocation url="communityMaint.cfm" addToken="no">
455: <cfelse>
456:   <cflocation url="communityAdm.cfm" addToken="no">
457: </cfif>
458:
459: <cfelseif isDefined("form.btnDelete")>
460:   <cflocation url="communityDelete.cfm" addToken="no">
461: <cfelseif isDefined("form.btnConfirmedDelete")>
462:   <cfset client.lookupID = -1>
463:   <cfset client.detailID = -1>
464:   <cfset client.userName = "Unable to delete #form.edtName#">
465:   </cftransaction>
466:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
467:     delete from communityDetail
468:     where communityDetail.communityID = #form.communityID#
469:   </cfquery>
470:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
471:     delete from communities
472:     where communities.communityID = #form.communityID#
473:   </cfquery>
474:
475:   <cfquery name="qryImagePath" datasource="#ap_dataSource#">
476:     select distributors.communityImages
477:     from distributors
478:     where distributors.distributorID = #form.distributorID#
479:   </cfquery>
480:   <cfset lstDirectory = "">
481:   <cfdirectory
482:     name = "lstDirectory"
483:     action = "list"
484:     directory = "#qryImagePath.communityImages#"
485:     filter="#form.communityID# *.*"
486:   >
487:
488:   <cfloop query="lstDirectory">
489:     <cffile
490:       action="delete"

```

```

491:         file="#qryImagePath.communityImages#&#listDirectoryName#"
492:     >
493:     </cfloop>
494:
495:     <cfset client.userName = "" & #form.edtName# & " Community Page was deleted">
496:     </cftransaction>
497:     <cflocation url="communityAdm.cfm" addtoken="no">
498:     </cfif>
499:
500:     <cfset client.lookupID = -1>
501:     <cfset client.detailID = -1>
502:     <cfset client.imageType = -1>
503:     <!-- Get ID number from edit -->
504:     <cfloop collection="#form#" item="cName">
505:         <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
506:             <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
507:             <cfset client.lookupID = form.communityID>
508:             <cfset client.detailID = val(cValue)>
509:             <cfset client.imageType = -1>
510:             </cfif>
511:
512:             <cfif client.lookupID gt -1 and client.lookupID gt -1>
513:                 <cflocation url="communityMaint.cfm" addToken="no">
514:                 </cfif>
515:             </cfloop>
516:
517:             <!-- Get ID number for delete detail item -->
518:             <cfloop collection="#form#" item="cName">
519:                 <cfif ucase(left(#cName#,6)) is "DELETE" and findNoCase(".X", #cName#,1) gt 0>
520:                     <cfset cValue = mid(#cName#, 7, len(#cName#)-8)>
521:                     <cfset client.lookupID = form.communityID>
522:                     <cfset client.detailID = val(cValue)>
523:                     <cfset client.imageType = -1>
524:                     </cfif>
525:
526:                     <cfif client.lookupID gt -1 and client.lookupID gt -1>
527:                         <cfset client.userName = "Unable to delete paragraph.">
528:                         <cfquery name="qryDelete" dataSource="#ap_dataSource#">
529:                             delete from communityDetail
530:                             where communityDetail.communityDetailID = #client.detailID#
531:                         </cfquery>
532:                         <cfset client.detailID = -1>
533:                         <cfset client.userName = "paragraph deleted.">
534:                         <cflocation url="communityMaint.cfm" addToken="no">
535:                         </cfif>
536:                     </cfloop>
537:
538:
539:     <!-- If anything else, then go back to the admin page -->

```

540: <cflocation url="communityAdm.cfm" addToken="no">

-----  
 4.0 Transitional/ENUS

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/ENUS"
2:
3:  <cfparam name="url.generate" default="">
4:
5:  <html>
6:  <head>
7:    <cfoutput>
8:    <title>Recreate FullImpact Security Tree</title>
9:    </cfoutput>
10:    <link rel="stylesheet" href="style1.css" type="text/css">
11:  </head>
12:
13:
14:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
15:    <cfinclude template="include\nocache.cfm">
16:    <cfinclude template="include\header.cfm">
17:
18:    <cfif url.generate is "Yes">
19:      <cfinclude template="include\makeSecurityTree.cfm">
20:    <br>
21:    <b>Security tree generation complete.</b><br>
22:  </cfif>
23:  <br>
24:  <i>(The generated tree structure is displayed below)</i>
25:  <hr>
26:
27:
28:  <cfquery name="qrySecurity" dataSource="#ap_datasource#"
29:    select *
30:    from securityAccess
31:    order by hierarchyID
32:  </cfquery>
33:
34:  <table border="1">
35:    <tr>
36:      <td><b>Yakalo Admin</b></td>
37:      <td><b>Portal</b></td>
38:      <td><b>Master Distributor</b></td>
39:      <td><b>Distributor</b></td>
40:      <td><b>Master Agency</b></td>
41:      <td><b>Agency</b></td>
42:      <td><b>Agent</b></td>
43:      <td><b>Hierarchy ID</b></td>
44:    </tr>
45:    <cfoutput query="qrySecurity">
46:      <tr>
47:        <td><!-- Yakalo Administrator -->
48:        <cfif entityType is 1>
49:          #name#

```



```
50: <cfelse>
51:     <nbsp;
52: </cfif>
53: </td>
54: <td> <!-- Portal -->
55:     <cfif entityType is 2>
56:         #name#
57:     <cfelse>
58:     <nbsp;
59: </cfif>
60: </td>
61: <td> <!-- Master Distributor -->
62:     <cfif entityType is 3>
63:         #name#
64:     <cfelse>
65:     <nbsp;
66: </cfif>
67: </td>
68: <td> <!-- Distributor -->
69:     <cfif entityType is 4>
70:         #name#
71:     <cfelse>
72:     <nbsp;
73: </cfif>
74: </td>
75: <td> <!-- Master Agency -->
76:     <cfif entityType is 5 or entityType is 7>
77:         #name#
78:     <cfelse>
79:     <nbsp;
80: </cfif>
81: </td>
82: <td> <!-- Agency -->
83:     <cfif entityType is 6>
84:         #name#
85:     <cfelse>
86:     <nbsp;
87: </cfif>
88: </td>
89: <td> <!-- Agent -->
90:     <cfif entityType is 8>
91:         #name#
92:     <cfelse>
93:     <nbsp;
94: </cfif>
95: </td>
96: <td>#hierarchyID#</td>
97: </tr>
98: <!-- #entityID# #entityType# #name# #parentID# #parentType# #hierarchyID#<br> -->
```

99:       </cfoutput>  
100:       </table>  
101:  
102:       </body>  
103:       </html>  
104:

-----

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN" ...
2:
3:  <cfparam name="form.edtUserName" default="">
4:  <cfparam name="form.loginAttempts" default="0">
5:
6:  <html>
7:  <head>
8:    <title>Back Office Administration Customer Selection</title>
9:    <link rel="stylesheet" href="style1.css" type="text/css">
10:  </head>
11:
12:
13:  <!--
14:    If the user is a Yakalo user, a distributor, or a master agency, then select
15:    which customer to maintain.
16:  -->
17:  <cfset client.multiCustomers = False> <!-- Forces display of customer selection combo box -->
18:
19:  <!--
20:    <cfset lstSecurityFilter="1,2,3,4,5,6,7,8">
21:  -->
22:
23:  <cfset lstSecurityFilter = "#ap_securityYakalo#, #ap_securityPortal#, #ap_securityMastDist#,
24:    #ap_securityDist#">
25:  <cfinclude template="include\getSecurityTree.cfm">
26:
27:  <cfif grySecurity.recordCount is 1>
28:    <cfset client.multiCustomer = False>
29:
30:    <cfset client.distributorID = grySecurity.distributorID>
31:    <cfset client.portalID = grySecurity.portalID>
32:    <cfset client.customerID = grySecurity.customerID>
33:    <cfset client.currentEntityID = grySecurity.entityID>
34:    <cfset client.currentEntityType = grySecurity.entityType>
35:    <cfset client.currentDistributorID = grySecurity.distributorID>
36:    <cfset client.currentPortalID = grySecurity.portalID>
37:    <cfset client.hierarchyID = grySecurity.hierarchyID>
38:
39:    <cfif client.currentEntityType is #ap_securityMastAgency# or client.currentEntityType is #ap_securityAgency#>
40:      <cfset client.currentAgencyID = grySecurity.entityID>
41:    <cfelse>
42:      <cfset client.currentAgencyID = -1>
43:    </cfif>
44:
45:    <cfif client.currentEntityType is #ap_securityAgent#>
46:      <cfset client.currentAgentID = grySecurity.EntityID>
47:    <cfelse>
48:      <cfset client.currentAgentID = -1>
49:    </cfif>

```

21

```
99: There are no customers set up at this time.
100: </td>
101: </cfif>
102: </tr>
103: <tr>
104: <td colspan="2">
105: <cfif qrySecurity.recordCount gt 0>
106: <input type="submit" value="Administer" name="btnSubmit">
107: </cfif>
108: <input type="submit" value="Cancel" name="btnCancel"> <!-- Goes back to login screen -->
109: </td>
110: </tr>
111: </table>
112: </td>
113: </tr>
114: </table>
115: </form>
116: </td>
117: </tr>
118: </table>
119: </cfoutput>
120:
121: </body>
122: </html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3:  <html>
4:  <head>
5:    <title>Back Office Administration Customer Switch</title>
6:    <link rel="stylesheet" href="style1.css" type="text/css">
7:  </head>
8:
9:  <body>
10:
11:    <cfif isDefined("form.btnCancel")>
12:      <cflocation url="login.cfm" addToken="no">
13:    </cfif>
14:
15:    <cfif isDefined("form.btnSubmit")>
16:      <!-- Assign customer/client information -->
17:      <cfset nEntityType = listGetAt(#form.edtSite#,"1")>
18:      <cfset nEntityID = listGetAt(#form.edtSite#,"2")>
19:      <cfquery name="qryGetCust" dataSource="#ap_dataSource#"
20:        select distributorID, customerID, portalID, hierarchyID from securityAccess
21:        where securityAccess.entityType = #nEntityType#
22:        and securityAccess.entityID = #nEntityID#
23:      </cfquery>
24:
25:      <!-- Don't forget to make any changes in customerSelect.cfm as well -->
26:      <cfset client.distributorID = qryGetCust.distributorID>
27:      <cfset client.portalID = qryGetCust.portalID>
28:      <cfset client.customerID = qryGetCust.customerID>
29:
30:      <!-- client.entityID and client.entityType are already defined from logging in -->
31:      <cfset client.currentEntityID = nEntityID>
32:      <cfset client.currentEntityType = nEntityType>
33:      <cfset client.currentDistributorID = qryGetCust.distributorID>
34:      <cfset client.currentPortalID = qryGetCust.portalID>
35:      <cfset client.hierarchyID = qryGetCust.hierarchyID>
36:
37:      <cfif client.currentEntityType is #ap_securityMastAgency# or client.currentEntityType is #ap_securityAgency#>
38:        <cfset client.currentAgencyID = nEntityID>
39:      <cfelse>
40:        <cfset client.currentAgencyID = -1>
41:      </cfif>
42:
43:      <cfif client.currentEntityType is #ap_securityAgent#>
44:        <cfset client.currentAgentID = nEntityID>
45:      <cfelse>
46:        <cfset client.currentAgentID = -1>
47:      </cfif>
48:
49:      <!-- Reset lookup IDs for new customer -->

```

```
50: <cfset client.lookupID = -1>
51: <cfset client.detailID = -1>
52: <cfset client.lookupDistID = -1>
53: <cfset client.lookupAgencyID = -1>
54:
55: <cfif isDefined("client.gotoPage") and client.gotoPage is not "">
56:   <cflocation url="#client.gotoPage#" addToken="no">
57: </cfelse>
58:   <cflocation url="messages.cfm" addToken="no">
59: </cfif>
60: </cfelse>
61:   <cflocation url="login.cfm" addToken="no">
62: </cfif>
63:
64: </body>
65: </html>
```

```
1:  <cflocation url="login.cfm" addtoken="no">
```





```
50:
51: <tr valign="top" bgcolor="#eeeeee">
52:   <td><a href="defaultMaint.cfm?type=home&from=sd">Home Types</a></td>
53:   <td><a href="defaultMaint.cfm?type=lot&from=sd">Lot Types</a></td>
54:   <td><a href="defaultMaint.cfm?type=property&from=sd">Property Types</a></td>
55:   <td><a href="defaultMaint.cfm?type=status&from=sd">Property Status</a></td>
56: </tr>
57: <tr valign="top" bgcolor="#eeeeee">
58:   <td><a href="defaultMaint.cfm?type=region&from=sd">Regions</a></td>
59:   <td><a href="defaultMaint.cfm?type=pageFormat&from=sd">Page Format</a></td>
60:   <td><a href="defaultMaint.cfm?type=rooms&from=sd">Rooms</a></td>
61:   <td><a href="defaultMaint.cfm?type=nav&from=sd">Navigation</a></td>
62: </tr>
63: </table></p>
64:
65: </body>
66: </html>
67:
68:
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <html>
4: <head>
5: <title>Agency Choice</title>
6: </head>
7:
8: <body>
9:
10: <cfloop collection="#form#" item="cName">
11: <cfif ucase(left(cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
12: <cfset cValue = mid(cName#, 5, len(cName#)-6)>
13: <cfset client.lookupID = val(cValue)>
14: <cfset client.detailID = -1>
15: <cfset client.userMessage = "">
16: <cflocation url="agencyMaint.cfm" addToken="no">
17: <cfelseif ucase(left(cName#,7)) is "BIOEDIT" and findNoCase(".X", #cName#,1) gt 0>
18: <cfset cValue = mid(cName#, 8, len(cName#)-9)>
19: <cfset client.lookupID = val(cValue)>
20: <cfset client.detailID = -1>
21: <cfset client.userMessage = "">
22: <cflocation url="agencyBioMaint.cfm" addToken="no">
23: <cfelseif ucase(left(cName#,6)) is "BIOADD" and findNoCase(".X", #cName#,1) gt 0>
24: <cfset cValue = mid(cName#, 7, len(cName#)-8)>
25: <cfset client.lookupID = val(cValue)>
26: <cfset client.detailID = -1>
27: <cfset client.userMessage = "">
28: <cflocation url="agencyBioMaint.cfm" addToken="no">
29: </cfif>
30: </cfloop>
31:
32: <cfset client.lookupID = -1>
33: <cfset client.detailID = -1>
34: <cfset client.userMessage = "">
35: <cflocation url="agencyAdm.cfm" addToken="no">
36:
37:
38: </body>
39: </html>
```

Full Impact 4.0 Transitional/FEN

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/FEN">
2:
3: <cfif client.lookupID is "-1">
4:   <cfset client.lookupID = -1>
5:   <cfset client.detailID = -1>
6:   <cfset client.userName = "">
7:   <cflocation url="defaultAdm.cfm" addtoken="no">
8: </cfif>
9:
10:
11:
12: <cfset cLookup = ucase(url.type)>
13: <cfswitch expression="#cLookup#">
14:   <cfcase value="HOME">
15:     <cfquery name="qryGetValue" dataSource="#ap_dataSource#">
16:       select homeTypeValues.homeTypeID as valueID, homeTypeValues.homeType as value
17:       from homeTypeValues
18:       where homeTypeValues.homeTypeID = #client.lookupID#
19:     </cfquery>
20:     <cfif client.lookupDistID gt 0>
21:       <cfquery name="qryFind" dataSource="#ap_dataSource#">
22:         select prop_id from prop_main
23:         where prop_main.homeType = #client.lookupID#
24:       </cfquery>
25:
26:       <cfquery name="qryGroups" dataSource="#ap_dataSource#">
27:         select homeTypeID as valueID, homeType as value
28:         from homeTypeValues
29:         where homeTypeValues.distributorID = #client.lookupDistID#
30:       </cfquery>
31:     </cfif>
32:     <cfset cType = "Home Type">
33:   </cfcase>
34:   <cfcase value="LOT">
35:     <cfquery name="qryGetValue" dataSource="#ap_dataSource#">
36:       select lotTypeID as valueID, lotType as value
37:       from lotTypeValues
38:       where lotTypeValues.lotTypeID = #client.lookupID#
39:     </cfquery>
40:     <cfif client.lookupDistID gt 0>
41:       <cfquery name="qryFind" dataSource="#ap_dataSource#">
42:         select prop_id from prop_main
43:         where prop_main.lotType = #client.lookupID#
44:       </cfquery>
45:       <cfquery name="qryGroups" dataSource="#ap_dataSource#">
46:         select lotID as valueID, lotType as value
47:         from lotTypeValues
48:         where lotTypeValues.distributorID = #client.lookupDistID#
49:       </cfquery>

```

```

50: </cfif>
51: <cfset cType = "Lot Type">
52: </cfcase>
53: <cfcase value="PROPERTY">
54: <cfquery name="qryGetValue" dataSource="#ap_dataSource#">
55: select propertyTypeID as valueID, propertyType as value
56: from propertyTypeValues
57: where propertyTypeValues.propertyTypeID = #client.lookupID#
58: </cfquery>
59: <cfif client.lookupDistID gt 0>
60: <cfquery name="qryFind" dataSource="#ap_dataSource#">
61: select prop_id from prop_main
62: where prop_main.prop_type = #client.lookupID#
63: </cfquery>
64: <cfquery name="qryGroups" dataSource="#ap_dataSource#">
65: select propertyTypeID as valueID, propertyType as value
66: from propertyTypeValues
67: where propertyTypeValues.distributorID = #client.lookupDistID#
68: </cfquery>
69: </cfif>
70: <cfset cType = "Property Type">
71: </cfcase>
72: <cfcase value="REGION">
73: <cfquery name="qryGetValue" dataSource="#ap_dataSource#">
74: select regionID as valueID, region as value
75: from regionValues
76: where regionValues.regionID = #client.lookupID#
77: </cfquery>
78: <cfif client.lookupDistID gt 0>
79: <cfquery name="qryFind" dataSource="#ap_dataSource#">
80: select communityID from communities
81: where communities.regionID = #client.lookupID#
82: </cfquery>
83: <cfquery name="qryGroups" dataSource="#ap_dataSource#">
84: select regionID as valueID, region as value
85: from regionValues
86: where regionValues.distributorID = #client.lookupDistID#
87: </cfquery>
88: </cfif>
89: <cfset cType = "Region">
90: </cfcase>
91: <cfcase value="STATUS">
92: <cfquery name="qryGetValue" dataSource="#ap_dataSource#">
93: select statusID as valueID, status as value, propViewVisible
94: from statusValues
95: where statusValues.statusID = #client.lookupID#
96: </cfquery>
97: <cfif client.lookupDistID gt 0>
98: <cfquery name="qryFind" dataSource="#ap_dataSource#">

```

```

99:      select prop_id from prop_main
100:      where prop_main.status = #client.lookupID#
101:    </cfquery>
102:    <cfquery name="qryGroups" dataSource="#ap_dataSource#">
103:      select statusID as valueID, status as value
104:      from statusValues
105:      where statusValues.distributorID = #client.lookupDistID#
106:    </cfquery>
107:  </cfif>
108:  <cfset cType = "Property Status">
109:  </cfcase>
110:  <cfcase value="ROOMS">
111:    <cfquery name="qryGetValue" dataSource="#ap_dataSource#">
112:      select roomID as valueID, room as value
113:      from roomValues
114:      where roomValues.roomID = #client.lookupID#
115:    </cfquery>
116:    <cfif client.lookupDistID gt 0>
117:      <cfquery name="qryFind" dataSource="#ap_dataSource#">
118:        select propertyID from rooms
119:        where rooms.roomID = #client.lookupID#
120:      </cfquery>
121:      <cfquery name="qryGroups" dataSource="#ap_dataSource#">
122:        select roomID as valueID, room as value
123:        from roomValues
124:        where roomValues.distributorID = #client.lookupDistID#
125:        and roomValues.agencyID = #client.lookupAgencyID#
126:      </cfquery>
127:    </cfif>
128:    <cfset cType = "Room">
129:    </cfcase>
130:
131:    <cfcase value="NAV">
132:      <cfquery name="qryGetValue" dataSource="#ap_dataSource#">
133:        select navItemID as valueID, menuText as value, sortOrder, systemLink
134:        from navigation
135:        where navigation.navItemID = #client.lookupID#
136:      </cfquery>
137:      <cfquery name="qryFind" dataSource="#ap_dataSource#">
138:        select navItemID
139:        from navigation
140:        where navigation.distributorID = -999
141:      </cfquery>
142:      <cfset cType = "Navigation Menu">
143:      </cfcase>
144:      <cfdefaultcase>
145:        <cflocation url="defaultAdm.cfm" addToken="no">
146:        </cfdefaultcase>
147:      </cfswitch>

```



[illegible]



4.0 Transitional/EN

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN">
2:
3: <cfif not isDefined("url.type")>
4:   <cflocation url="defaultAdm.cfm" addToken="no">>
5: </cfif>
6:
7: <cfif client.currentEntityType lt #ap_securityMastDist#>
8:   <cfquery name="qryDist" dataSource="#ap_dataSource#">
9:     select distributors.name as distName
10:    from distributors
11:   where distributors.distributorID = #client.lookupDistID#
12:   </cfquery>
13:   <cfset cDistName = qryDist.distName>
14:   <cfelseif client.currentEntityType gte #ap_securityMastDist#>
15:     <cfset client.lookupDistID = client.currentDistributorID>
16:     <cfset cDistName = "">
17:   </cfif>
18:
19:
20:
21:   <cfparam name="client.userMessage" default="">
22:   <cfparam name="client.lookupDistID" default="-1">
23:   <cfparam name="url.from" default="agency">
24:
25:   <cfset url.from=lcase(url.from)>
26:   <cfif url.from is "sd">
27:     <cfset client.lookupAgencyID = 0>
28:     <cfset client.lookupDistID = 0>
29:
30:   <cfelseif url.from is "dist">
31:     <cfset client.lookupAgencyID = 0>
32:     <cfif client.currentEntityType gte #ap_securityMastDist#>
33:       <cfset client.lookupDistID = client.currentDistributorID>
34:     </cfif>
35:   <cfelseif url.from is "agency">
36:     <cfif client.currentEntityType is #ap_securityMastAgency# or client.currentEntityType is #ap_securityAgency#>
37:       <cfset client.lookupAgencyID = client.currentEntityID>
38:       <cfset client.lookupDistID = client.currentDistributorID>
39:     <cfelse>
40:       <cfquery name="qryAgency" dataSource="#ap_dataSource#">
41:         select top 1 agency_id, agency.name as agencyName, agency.distributorID
42:        from agency
43:       join securityAccess on
44:         (securityAccess.entityType = #ap_securityMastAgency# or securityAccess.entityType = #ap_securityAgency#
45:          and securityAccess.entityID = agency.agency_id
46:          and securityAccess.hierarchyID like '#client.hierarchyID#%'
47:          <cfif isDefined("form.getAgencyID")>
48:            where agency.agency_id = #form.getAgencyID#
49:          <cfelseif isDefined("client.lookupAgencyID") and client.lookupAgencyID gt 0>

```

```

50:       where agency_agency_id = #client.lookupAgencyID#
51:     </cfif>
52:     order by agencyName
53:   </cfquery>
54:   <cfif qryAgency.recordCount is 0>
55:     <cflocation url="defaultAdm.cfm" addToken="no">
56:   </cfelse>
57:     <cfset client.lookupAgencyID = qryAgency.agency_id>
58:     <cfset client.lookupDistID = qryAgency.distributorID>
59:     <cfif not isDefined("form.getAgencyID") and isDefined("client.lookupAgencyID")>
60:       <cfset form.getAgencyID = client.lookupAgencyID>
61:     </cfif>
62:   </cfif>
63: </cfif>
64:
65: <cfelse>
66:   <cflocation url="defaultAdm.cfm" addToken="no">
67: </cfif>
68:
69: <cfset cLookup = ucase(url.type)>
70: <cfswitch expression="#cLookup#">
71:   <cfcase value="HOME">
72:     <cfquery name="qryView" dataSource="#ap_dataSource#">
73:       select homeTypeID as valueID, homeType as value
74:       from homeTypeValues
75:       where homeTypeValues.distributorID = #client.lookupDistID#
76:       order by value
77:     </cfquery>
78:     <cfquery name="qryEdit" dataSource="#ap_dataSource#">
79:       select homeTypeID as valueID, homeType as value
80:       from homeTypeValues
81:       where homeTypeValues.homeTypeID = #client.lookupID#
82:     </cfquery>
83:     <cfset cDefaultType = "Home Type">
84:     <cfset nColumns = 2>
85:   </cfcase>
86:   <cfcase value="LOT">
87:     <cfquery name="qryView" dataSource="#ap_dataSource#">
88:       select lotTypeID as valueID, lotType as value
89:       from lotTypeValues
90:       where lotTypeValues.distributorID = #client.lookupDistID#
91:       order by value
92:     </cfquery>
93:     <cfquery name="qryEdit" dataSource="#ap_dataSource#">
94:       select lotTypeID as valueID, lotType as value
95:       from lotTypeValues
96:       where lotTypeValues.lotTypeID = #client.lookupID#
97:     </cfquery>
98:     <cfset cDefaultType = "Lot Type">

```

```

99:      <cfset nColumns = 2>
100:    </cfcase>
101:    <cfcase value="PROPERTY">
102:      <cfquery name="qryView" dataSource="#ap_dataSource#">
103:        select propertyTypeID as valueID, propertyType as value
104:        from propertyTypeValues
105:        where propertyTypeValues.distributorID = #client.lookupDistID#
106:        order by value
107:      </cfquery>
108:      <cfquery name="qryEdit" dataSource="#ap_dataSource#">
109:        select propertyTypeID as valueID, propertyType as value
110:        from propertyTypeValues
111:        where propertyTypeValues.propertyTypeID = #client.lookupID#
112:      </cfquery>
113:      <cfset cDefaultType = "Property Type">
114:      <cfset nColumns = 2>
115:    </cfcase>
116:    <cfcase value="ROOMS">
117:      <cfquery name="qryView" dataSource="#ap_dataSource#">
118:        select roomID as valueID, room as value, sortOrder
119:        from roomValues
120:        where roomValues.agencyID = #client.lookupAgencyID#
121:        and roomValues.distributorID = #client.lookupDistID#
122:        order by sortOrder,value
123:      </cfquery>
124:      <cfquery name="qryEdit" dataSource="#ap_dataSource#">
125:        select roomID as valueID, room as value, sortOrder
126:        from roomValues
127:        where roomValues.roomID = #client.lookupID#
128:      </cfquery>
129:      <cfset cDefaultType = "Room Value">
130:      <cfset nColumns = 3>
131:    </cfcase>
132:    <cfcase value="REGION">
133:      <cfquery name="qryView" dataSource="#ap_dataSource#">
134:        select regionID as valueID, region as value
135:        from regionValues
136:        where regionValues.distributorID = #client.lookupDistID#
137:        order by value
138:      </cfquery>
139:      <cfquery name="qryEdit" dataSource="#ap_dataSource#">
140:        select regionID as valueID, region as value
141:        from regionValues
142:        where regionValues.regionID = #client.lookupID#
143:      </cfquery>
144:      <cfset cDefaultType = "Region">
145:      <cfset nColumns = 2>
146:    </cfcase>
147:    <cfcase value="STATUS">

```

```

148: <cfquery name="qryView" dataSource="#ap_dataSource#">
149: select statusID as valueID, status as value, propViewVisible
150: from statusValues
151: where statusValues.distributorID = #client.lookupDistID#
152: order by value
153: </cfquery>
154: <cfquery name="qryEdit" dataSource="#ap_dataSource#">
155: select statusID as valueID, status as value, propViewVisible
156: from statusValues
157: where statusValues.statusID = #client.lookupID#
158: </cfquery>
159: <cfset cDefaultType = "Property Status">
160: <cfset nColumns = 3>
161: </cfcase>
162: <cfcase value="NAV">
163: <cfquery name="qryView" dataSource="#ap_dataSource#">
164: select navItemID as valueID, menuText as value, sortOrder
165: <cfif url.from is "sd">
166: , systemLink
167: </cfif>
168: from navigation
169: where navigation.distributorID = #client.lookupDistID#
170: order by sortOrder, value
171: </cfquery>
172: <cfquery name="qryEdit" dataSource="#ap_dataSource#">
173: select navItemID as valueID, menuText as value, menuURL, sortOrder, systemLink
174: from navigation
175: where navigation.navItemID = #client.lookupID#
176: </cfquery>
177: <cfset cDefaultType = "Navigation Item">
178: <cfif url.from is "sd">
179: <cfset nColumns = 5>
180: <cfelse>
181: <cfset nColumns = 4>
182: </cfif>
183: </cfcase>
184: <cfdefaultcase>
185: <cflocation url="defaultAdm.cfm?url.type# addToken="no">
186: </cfdefaultcase>
187: </cfswitch>
188:
189:
190: <cfinclude template="include\javaValidate.cfm">
191: <script language="JavaScript">
192: <!--
193: function validate(testform) {
194: var results = "";
195: var lResult = true;
196:

```

```

197: if (removeSpaces(testform.edtValue.value) == "") {
198:     results = results + "Please enter a value.\r";
199:     lResult = false;
200: }
201:
202: <cfif isDefined("qryEdit.sortOrder")>
203: if ((removeSpaces(testform.edtSortOrder.value) == "") || (!isNumber(testform.edtSortOrder.value))) {
204:     results = results + "Please enter a numeric sort order.\r";
205:     lResult = false;
206: }
207: </cfif>
208:
209: <cfif isDefined("qryEdit.menuURL")>
210: if ((testform.edtValue.value != "***SPECIALTY PAGES**") && (removeSpaces(testform.edtMenuURL.value) == "")) {
211:     results = results + "Please enter an URL for this menu item.\r";
212:     lResult = false;
213: }
214: </cfif>
215:
216: if (!lResult) {
217:     window.alert(results);
218: }
219: return lResult;
220: }
221: -->
222: </script>
223:
224: <html>
225: <head>
226:     <cfoutput>
227:     <title>#client.backofficeName# Backoffice Defaults Maintenance (#cDefaultType#)</title>
228:     </cfoutput>
229:     <link rel="stylesheet" href="style1.css" type="text/css">
230: </head>
231:
232: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
233: <cfinclude template="include\nocache.cfm">
234:
235: <p><cfinclude template="include\header.cfm"></p>
236:
237: <cfoutput>
238:
239: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
240: <tr bgcolor="cccc99"><td colspan="5"><b>'#cDefaultType#' <cfif client.lookupDistID is 0>System Default
241: </cfif>Maintenance</b></td></tr>
242: <tr>
243: <td colspan="5"><b>Create a new #cDefaultType#
244: <cfif cDistName is not "">
245:     for #cDistName#

```

```

245:         </cfif>
246:     )
247: </cfif>
248: </td></tr>
249:
250: <CFIF client.userMessage is not "">
251: <tr bgcolor="eeeeee">
252: <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td>
253: </tr>
254: <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
255: </CFIF>
256: <cfset client.userMessage = "">
257:
258: <cfparam name="form.getAgencyID" default="-1">
259: <cfif url.from is "agency" and client.currentEntityType lt #ap_securityMastAgency#>
260: <form action="defaultMaint.cfm?type=#url.type#" method="post">
261: <cfquery name="qryAgencies" datasource="#ap_dataSource#">
262: select agency_id, agency.name as agencyName, agency.distributorID
263: from agency
264: join securityAccess on
265: (securityAccess.entityType = #ap_securityMastAgency# or securityAccess.entityType = #ap_securityAgency#)
266: and securityAccess.entityID = agency.agency_id
267: and securityAccess.hierarchyID like '#client.hierarchyID#%'
268: order by agencyName
269: </cfquery>
270:
271: <tr bgcolor="eeeeee">
272: <td colspan="5">
273: <b>Agency To Update: </b>
274: <select name="getAgencyID">
275: <cfloop query="qryAgencies">
276: <option value="#qryAgencies.agency_id#"><cfif qryAgencies.agency_id is form.getAgencyID>
selected</cfif>#qryAgencies.agencyName#
</cfloop>
</select>
278: <input type="submit" name="btnSubmit" value="Select">
279: </td>
280: </tr>
281: </form>
282: </cfif>
283:
284:
285:
286: <cfif client.currentAgencyID is -1>
287: <form action="defaultMaint.cfm?type=rooms" method="post">
288: <input type="hidden" name="selectedID">
289: </form>
290: </cfif>
291:
292:

```

```

293: <form action="defaultUpdate.cfm" method="post">
294:   <input type="hidden" name="valueID" value="#client.lookupID#">
295:   <input type="hidden" name="type" value="#url.type#">
296:   <input type="hidden" name="distributorID" value="#client.lookupDistID#">
297:   <input type="hidden" name="agencyID" value="#client.lookupAgencyID#">
298:   <input type="hidden" name="from" value="#url.from#">
299:   <input type="hidden" name="getAgencyID" value="#form.getAgencyID#">
300:
301:   <table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
302:     <tr valign="top" bgcolor="#cccccc">
303:       <td colspan="2"><b>Value</b></td>
304:       <td colspan="2"><b>Included in Property Searches</b></td>
305:     </tr>
306:     <tr>
307:       <td align="center"><b>URL</b></td>
308:       <td align="center"><b>URL</b></td>
309:     </tr>
310:     <tr>
311:       <td align="center"><b>Sort Order</b></td>
312:       <td align="center"><b>Sort Order</b></td>
313:     </tr>
314:     <tr>
315:       <td align="center"><b>System Link</b></td>
316:       <td align="center"><b>System Link</b></td>
317:     </tr>
318:
319:     <tr>
320:       <td colspan="2"><b>Record Count is 0</b></td>
321:       <td colspan="2"><b>There are no values defined.</b></td>
322:     </tr>
323:
324:     <tr>
325:       <td colspan="2"><b>Query="qryView"</b></td>
326:       <td colspan="2"><b>Query="qryView"</b></td>
327:     </tr>
328:     <tr>
329:       <td align="center"><b>Width="30%"</b></td>
330:       <td align="center"><b>Width="30%"</b></td>
331:     </tr>
332:     <tr>
333:       <td align="center"><b>Yes</b></td>
334:       <td align="center"><b>No</b></td>
335:     </tr>
336:     <tr>
337:       <td align="center"><b>MenuURL#</b></td>
338:       <td align="center"><b>MenuURL#</b></td>
339:     </tr>
340:     <tr>
341:       <td align="center"><b>SortOrder#</b></td>
342:       <td align="center"><b>SortOrder#</b></td>

```

```

342:         </td>
343:     </cfif>
344:     <cfif isDefined("qryView.systemLink")>
345:         <td align="center" width="10%">
346:             <cfif qryView.systemLink is "Y">
347:                 Yes
348:             <cfelse>
349:                 No
350:             </cfif>
351:         </td>
352:     </cfif>
353:     <td align="center" width="5%">
354:         <input type="image" name="edit#qryView.valueID#" src="#ap_commonImages#edit.gif" alt="Edit" border="0">
355:     </td>
356: </tr>
357: </cfloop>
358: </table>
359: </form>
360:
361:
362: <form action="defaultUpdate.cfm" method="post" onSubmit="return validate(this)">
363:     <input type="hidden" name="valueID" value="#client.lookupID#">
364:     <input type="hidden" name="type" value="#url.type#">
365:     <input type="hidden" name="distributorID" value="#client.lookupDistID#">
366:     <input type="hidden" name="agencyID" value="#client.lookupAgencyID#">
367:     <input type="hidden" name="from" value="#url.from#">
368:
369:     <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
370:         <cfif qryEdit.recordCount is 0>
371:             <tr bgcolor="#cccccc"><td colspan="#nColumns#"><b>Add a value</b></td></tr>
372:         <cfelse>
373:             <tr bgcolor="#cccccc"><td colspan="#nColumns#"><b>Edit this value</b></td></tr>
374:         </cfif>
375:         <tr valign="top" bgcolor="#eeeeee">
376:             <td><b>Value</b></td>
377:             <cfif isDefined("qryView.propViewVisible")>
378:                 <td align="center"><b>Searchable</b></td>
379:             </cfif>
380:             <cfif isDefined("qryView.menuURL")>
381:                 <td><b>Menu URL</b></td>
382:             </cfif>
383:             <cfif isDefined("qryView.sortOrder")>
384:                 <td align="center"><b>Sort Order</b></td>
385:             </cfif>
386:             <cfif isDefined("qryView.systemLink")>
387:                 <td align="center"><b>System Link</b></td>
388:             </cfif>
389:             <td><b>Edit</b></td>
390:         </tr>

```



```

391: <tr valign="top" bgcolor="#eeeeee">
392:   <td>
393:     <cfif cLookup is "NAV" and ucase(trim(qryEdit.value)) is "***SPECIALTY PAGES**" and client.lookupDistID gt 0>
394:       <input type="hidden" name="edtValue" value="***SPECIALTY PAGES**">
395:       <i>***Specialty Pages**</i>
396:     <cfelse>
397:       <input type="text" name="edtValue" value="#qryEdit.value#" size="35" maxlength="35">
398:       <cfif cLookup is "NAV" and ucase(trim(qryEdit.value)) is "***SPECIALTY PAGES**" and client.lookupDistID gt 0>
399:         <br><i>Use ***SPECIALTY PAGES** to insert Specialty Pages</i>
400:       </cfif>
401:     </cfif>
402:   </td>
403:   <cfif isDefined("qryView.propViewVisible")>
404:     <td align="center"><input type="checkbox" name="edtPropVisible"><cfif qryEdit.propViewVisible is "Y">
checked</cfif></td>
405:   </cfif>
406:   <cfif isDefined("qryView.menuURL")>
407:     <td>
408:       <cfif cLookup is "NAV" and url.from is not "sd" and qryEdit.systemLink is "Y">
409:         <input type="hidden" name="edtMenuURL" value="#qryEdit.menuURL#">
410:         #qryEdit.menuURL#
411:       <cfelse>
412:         <input type="text" name="edtMenuURL" size="20" maxlength="120" value="#qryEdit.menuURL#">
413:       </cfif>
414:     </td>
415:   </cfif>
416:   <cfif isDefined("qryView.sortOrder")>
417:     <td align="center"><input type="text" name="edtSortOrder" size="2" maxlength="2" value="#qryEdit.sortOrder#"></td>
418:   </cfif>
419:   <cfif isDefined("qryView.systemLink")>
420:     <td align="center"><input type="checkbox" name="edtSystemLink"><cfif qryEdit.systemLink is "Y"> checked</cfif></td>
421:   </cfif>
422:   <td><b>sp:</td>
423: </tr>
424:
425: <tr bgcolor="#eeeeee">
426:   <cfif qryEdit.recordCount is 0>
427:     <td colspan="#nColumns#">
428:       <input type="submit" name="btnUpdate" value="Add Value">
429:       <input type="reset" value="Reset Info">
430:     <cfelse>
431:       <cfset nDeleteCols = nColumns-1>
432:       <td colspan="#nDeleteCols#">
433:         <input type="submit" name="btnUpdate" value="Update Value">
434:         <input type="reset" value="Reset Info">
435:         <input type="submit" name="btnCancelDetail" value="Cancel">
436:       </td>
437:       <td align="right">
438:         <input type="submit" name="btnDelete" value="Delete Value">

```

```
439:         </td>
440:         </cfif>
441:     </tr>
442: </table>
443: </form>
444: </cfoutput>
445:
446:
447: </body>
448: </html>
449:
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3:  <cfif not isDefined("form.valueID")>
4:    <cfset client.lookupID = -1>
5:    <cfset client.detailID = -1>
6:    <cfset client.imageType = -1>
7:    <cfset client.userMessage = "">
8:    <cflocation url="defaultAdm.cfm" addtoken="no">
9:  </cfif>
10:
11:  <cfinclude template="include\clearOldFields.cfm">
12:  <cfset client.userMessage = "">
13:
14:  <cfif isDefined("form.btnCancelDetail")> <!--- Cancel detail edit --->
15:    <cfset client.lookupID = -1>
16:    <cfset client.detailID = -1>
17:    <cfset client.userMessage = "">
18:    <cflocation url="defaultMaint.cfm?type=#form.type#&from=#form.from#" addToken="no">
19:
20:  <cfelseif isDefined("form.btnCancelDelete")> <!--- Cancel detail edit --->
21:    <cfset client.lookupID = -1>
22:    <cfset client.detailID = -1>
23:    <cfset client.imageType = -1>
24:    <cfset client.userMessage = "Deletion canceled.">
25:    <cflocation url="defaultMaint.cfm?type=#form.type#&from=#form.from#" addToken="no">
26:
27:  <cfelseif isDefined("form.btnUpdate")>
28:    <cfif form.valueID is "-1">
29:      <cfset cValue = preservesingleQuotes(form.edtValue)>
30:
31:      <cfswitch expression="#form.type#">
32:        <cfcase value="HOME">
33:          <cfquery name="qryInsert" dataSource="#ap_dataSource#">
34:            insert into homeTypeValues
35:              (homeType,distributorID)
36:            values
37:              ('#cValue#','#form.distributorID#')
38:          </cfquery>
39:        </cfcase>
40:        <cfcase value="LOT">
41:          <cfquery name="qryInsert" dataSource="#ap_dataSource#">
42:            insert into lotTypeValues
43:              (lotType,distributorID)
44:            values
45:              ('#cValue#','#form.distributorID#')
46:          </cfquery>
47:        </cfcase>
48:        <cfcase value="PROPERTY">
49:          <cfquery name="qryInsert" dataSource="#ap_dataSource#">

```

```

50: insert into propertyTypeValues
51: (propertyType,distributorID)
52: values
53: ('#cValue#','#form.distributorID#)
54: </cfquery>
55: </cfcase>
56: <cfcase value="ROOMS">
57: <cfset nSortOrder = val(form.edtSortOrder)>
58: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
59: insert into roomValues
60: (room, sortOrder, distributorID, agencyID)
61: values
62: ('#cValue#','#nSortOrder#','#form.distributorID#','#form.agencyID#)
63: </cfquery>
64: </cfcase>
65: <cfcase value="REGION">
66: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
67: insert into regionValues
68: (region,distributorID)
69: values
70: ('#cValue#','#form.distributorID#)
71: </cfquery>
72: </cfcase>
73: <cfcase value="STATUS">
74: <cfif isDefined("form.edtPropVisible")>
75: <cfset cisVisible = "Y">
76: <cfelse>
77: <cfset cisVisible = "N">
78: </cfif>
79: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
80: insert into statusValues
81: (status, propViewVisible, distributorID)
82: values
83: ('#cValue#','#cisVisible#','#form.distributorID#)
84: </cfquery>
85: </cfcase>
86: <cfcase value="NAV">
87: <cfif isDefined("form.edtSystemLink")>
88: <cfset cSystemLink = "Y">
89: <cfelse>
90: <cfset cSystemLink = "N">
91: </cfif>
92: <cfset nSortOrder = val(form.edtSortOrder)>
93:
94: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
95: insert into navigation
96: (menuText, menuURL, systemLink, sortOrder, distributorID)
97: values
98: ('#cValue#','#form.edtMenuURL#','#cSystemLink#','#nSortOrder#','#form.distributorID#)

```

```

99:      </cfquery>
100:    </cfcase>
101:
102:  </cfswitch>
103:
104:  <cfset client.lookupID = -1>
105:  <cfset client.detailID = -1>
106:  <cfset client.lookupDistID = form.distributorID>
107:
108:  <cflocation url="defaultMaint.cfm?type=#form.type#&from=#form.from#" addToken="no">
109:
110: <cfelse>
111:   <cfset cValue = preservesingleQuotes(form.edtValue)>
112:
113:   <cfswitch expression="#form.type#">
114:     <cfcase value="HOME">
115:       <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
116:         update homeTypeValues
117:         set
118:           homeType = '#cValue#'
119:         where homeTypeValues.homeTypeID = #form.valueID#
120:       </cfquery>
121:     </cfcase>
122:     <cfcase value="LOT">
123:       <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
124:         update lotTypeValues
125:         set
126:           homeType = '#cValue#'
127:         where homeTypeValues.homeTypeID = #form.valueID#
128:       </cfquery>
129:     </cfcase>
130:     <cfcase value="PROPERTY">
131:       <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
132:         update propertyTypeValues
133:         set
134:           propertyType = '#cValue#'
135:         where prpertyTypeValues.propertyTypeID = #form.valueID#
136:       </cfquery>
137:     </cfcase>
138:     <cfcase value="ROOMS">
139:       <cfset sortOrder = val(form.edtSortOrder)>
140:       <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
141:         update roomValues
142:         set
143:           room = '#cValue#',
144:           sortOrder = #sortOrder#
145:         where roomValues.roomID = #form.valueID#
146:       </cfquery>
147:     </cfcase>

```

```

148: <cfcase value="REGION">
149: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
150: update regionValues
151: set
152:     region = '#cValue#'
153: where regionValues.regionID = #form.valueID#
154: </cfquery>
155: </cfcase>
156: <cfcase value="STATUS">
157: <cfif isDefined("form.edtPropVisible")>
158: <cfset cisVisible = "Y">
159: <cfelse>
160: <cfset cisVisible = "N">
161: </cfif>
162: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
163: update statusValues
164: set status = '#cValue#',
165:     propViewVisible = '#cisVisible#'
166: where statusValues.statusID = #form.valueID#
167: </cfquery>
168: </cfcase>
169: <cfcase value="NAV">
170: <cfif isDefined("form.edtSystemLink")>
171: <cfset cSystemLink = "Y">
172: <cfelse>
173: <cfset cSystemLink = "N">
174: </cfif>
175: <cfset nSortOrder = val(form.edtSortOrder)>
176:
177: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
178: update navigation
179: set menuText = '#cValue#',
180:     menuURL = '#form.edtMenuURL#',
181:     sortOrder = #nSortOrder#,
182:     systemLink = '#cSystemLink#'
183: where navigation.navItemID = #form.valueID#
184: </cfquery>
185: </cfcase>
186:
187: </cfswitch>
188:
189: <cfset client.lookupID = -1>
190: <cfset client.detailID = -1>
191: <cfset client.lookupDistID = form.distributorID>
192:
193: <cflocation url="defaultMaint.cfm?type=#form.type&from=#form.from#" addToken="no">
194:
195: </cfif>
196:

```

```

197: <cfelseif isDefined("form.btnDelete")>
198: <cfset cURL = "?from=#form.from#&type=#form.type#">
199: <cflocation url="defaultDelete.cfm#cURL#" addToken="no">
200: <cfelseif isDefined("form.btnDeleteConfirmedDelete")>
201: <cfset cLookup = ucase(form.type)>
202: <cftransaction>
203: <cfswitch expression="#cLookup#">
204: <cfcase value="HOME">
205: <cfquery name="qryMove" dataSource="#ap_dataSource#">
206:     update prop_main
207:     set homeType = #form.moveGroup#
208:     where prop_main.homeType = #client.lookupID#
209: </cfquery>
210:
211: <cfquery name="qryDelete" dataSource="#ap_dataSource#">
212:     delete from homeTypeValues
213:     where homeTypeValues.homeTypeID = #form.valueID#
214: </cfquery>
215: </cfcase>
216: <cfcase value="LOT">
217: <cfquery name="qryMove" dataSource="#ap_dataSource#">
218:     update prop_main
219:     set lotType = #form.moveGroup#
220:     where prop_main.lotType = #client.lookupID#
221: </cfquery>
222:
223: <cfquery name="qryDelete" dataSource="#ap_dataSource#">
224:     delete from lotTypeValues
225:     where lotTypeValues.lotTypeID = #form.valueID#
226: </cfquery>
227: </cfcase>
228: <cfcase value="PROPERTY">
229: <cfquery name="qryMove" dataSource="#ap_dataSource#">
230:     update prop_main
231:     set propertyType = #form.moveGroup#
232:     where prop_main.prop_type = #client.lookupID#
233: </cfquery>
234:
235: <cfquery name="qryDelete" dataSource="#ap_dataSource#">
236:     delete from propertyTypeValues
237:     where propertyTypeValues.propertyTypeID = #form.valueID#
238: </cfquery>
239: </cfcase>
240: <cfcase value="ROOMS">
241: <!--
242: <cfquery name="qryMove" dataSource="#ap_dataSource#">
243:     update prop_main
244:     set propertyType = #form.moveGroup#
245:     where prop_main.prop_type = #client.lookupID#

```

```

246:         </cfquery>
247:     --->
248:     <cfquery name="qryDelete" dataSource="#ap_dataSource#">
249:         delete from roomValues
250:         where roomValues.roomID = #form.valueID#
251:     </cfquery>
252: </cfcase>
253: <cfcase value="REGION">
254:     <cfquery name="qryMove" dataSource="#ap_dataSource#">
255:         update communities
256:         set regionID = #form.moveGroup#
257:         where communities.regionID = #client.lookupID#
258:     </cfquery>
259:
260:     <cfquery name="qryDelete" dataSource="#ap_dataSource#">
261:         delete from regionValues
262:         where regionValues.regionID = #form.valueID#
263:     </cfquery>
264: </cfcase>
265: <cfcase value="STATUS">
266:     <cfquery name="qryMove" dataSource="#ap_dataSource#">
267:         update prop_main
268:         set status = #form.moveGroup#
269:         where prop_main.status = #client.lookupID#
270:     </cfquery>
271:
272:     <cfquery name="qryDelete" dataSource="#ap_dataSource#">
273:         delete from statusValues
274:         where statusValues.statusID = #form.valueID#
275:     </cfquery>
276: </cfcase>
277: <cfcase value="NAV">
278:     <cfquery name="qryDelete" dataSource="#ap_dataSource#">
279:         delete from navigation
280:         where navigation.navItemID = #form.valueID#
281:     </cfquery>
282: </cfcase>
283: </cfswitch>
284: </cftransaction>
285:
286:     <cflocation url="defaultMaint.cfm?type=#form.type#&from=#form.from#" addtoken="no">
287: </cfif>
288:
289: <cfset client.lookupID = -1>
290: <cfset client.detailID = -1>
291: <cfset client.imageType = -1>
292: <!-- Get ID number from edit -->
293: <cfloop collection="#form#" item="cName">
294:     <cfif ucase(left(cName#4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>

```



```

295:     <cfset cValue = mid(cName#, 5, len(cName#)-6)>
296:     <cfset client.lookupID = val(cValue)>
297:     <cfset client.detailID = -1>
298:     </cfif>
299:
300:     <cfif client.lookupID gt -1>
301:         <cflocation url="defaultMaint.cfm?type=#form.type#&from=#form.from#" addToken="no">
302:     </cfif>
303: </cfloop>
304:
305: <!--- Get ID number for delete detail item --->
306: <cfloop collection="#form#" item="cName">
307:     <cfif ucase(left(cName#,6)) is "DELETE" and findNoCase(".X", #cName#,1) gt 0>
308:         <cfset cValue = mid(cName#, 7, len(cName#)-8)>
309:         <cfset client.lookupID = val(cValue)>
310:         <cfset client.detailID = -1>
311:         <cfset client.imageType = -1>
312:     </cfif>
313:
314:     <cfif client.lookupID gt -1>
315:         <cfset client.userName = "Unable to delete value.">
316:         <cftransaction>
317:             <cfquery name="qryDelete" dataSource="#ap_dataSource#">
318:                 delete from agentBioDetail
319:                 where agentBioDetail.agentBioDetailID = #client.detailID#
320:             </cfquery>
321:             <cfset client.detailID = -1>
322:             <cfset client.userName = "paragraph deleted.">
323:             </cftransaction>
324:             <cflocation url="defaultMaint.cfm?type=#form.type#&from=#form.from#" addToken="no">
325:         </cfif>
326:     </cfloop>
327:
328:
329: <!--- If anything else, then go back to the again page --->
330: <cflocation url="messages.cfm" addToken="no">
331:

```

11/29/2000 5:05:00 PM  
S:\FullImpact\FullImpact\admin\displayFormVars.cfm

```
1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <html>
4:  <head>
5:    <title>Untitled</title>
6:  </head>
7:
8:  <body>
9:
10:   <cfloop collection="#form#" item="cName">
11:     <cfoutput>
12:       #cName# = #evaluate(cName)#<br>
13:     </cfoutput>
14:   </cfloop>
15:
16: </body>
17: </html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfset client.gotopage = "distAdm.cfm">
4:  <!--
5:  <cfinclude template="include\securityTest.cfm">
6:  -->
7:
8:  <cfparam name="URL.sortBy" default="distName">
9:  <cfset client.lookupID = -1>
10:  <cfset client.detailID = -1>
11:  <cfset client.lookupDistID = -1>
12:
13:  <!-- Display rows -->
14:  <cfparam name="nStartFrom" default="1">
15:  <cfparam name="ntoDisplay" default="#client.displayRows#">
16:  <cfparam name="nEnd" default="#client.displayRows#">
17:
18:
19:  <cfquery name="qryEditList" dataSource="#ap_dataSource#"
20:    select distributors.distributorID, distributors.name as distName,
21:    distributors.maxPageFormats, distributors.homePageBuilder,
22:    portals.name as portalName, homePages.distributorID as homePageID
23:    from distributors
24:    join securityAccess on
25:      (securityAccess.entityType = #ap_securityMastDist# or securityAccess.entityType = #ap_securityDist#)
26:      and securityAccess.entityID = distributors.distributorID
27:      and securityAccess.hierarchyID like '#client.hierarchyID#%'
28:    left outer join portals on portals.portalID = distributors.portalID
29:    left outer join homePages on homePages.distributorID = distributors.distributorID
30:    order by #url.sortBy#
31:  </cfquery>
32:
33:  <html>
34:  <head>
35:    <cfoutput>
36:      <title>#client.backofficeName# Backoffice</title>
37:    </cfoutput>
38:    <link rel="stylesheet" href="style1.css" type="text/css">
39:  </head>
40:
41:
42:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
43:  <cfinclude template="include\nocache.cfm">
44:  <p><cfinclude template="include\header.cfm"></p>
45:
46:  <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
47:    <tr bgcolor="#cccc99">
48:      <td colspan="5">
49:        <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">

```

```

50: <tr>
51: <td align="left">
52: <span class="h2"><b>Distributor Administration</b></span>
53: </td>
54: <td align="right">
55: <cfif #nToDisplay# gte qryEditList.recordCount>
56: <cfset cToDisplay = min(qryEditList.recordCount, #nToDisplay#)>
57: </cfif>
58: <cfif qryEditList.recordCount gte #nToDisplay#>
59: <cfset cToDisplay = min(qryEditList.recordCount, #nEnd#)>
60: </cfif>
61: <cfset cStartFrom = min(qryEditList.recordCount, #nStartFrom#)>
62: <cfoutput>(Viewing records #cStartFrom# to #cToDisplay# out of #qryEditList.recordCount#)</cfoutput>
63: </td>
64: </tr>
65: </table>
66: </td>
67: </tr>
68:
69: <cfif trim(client.userName) is not "">
70: <tr bgcolor="#cccc99">
71: <td colspan="5" align="center">
72: <cfoutput>&nbsp;&nbsp;&nbsp;&nbsp;<b>#client.userName#</b></cfoutput>
73: </td>
74: </tr>
75: </cfif>
76: <cfset client.userName = "">
77: <cfset client.lookupID = -1>
78: <cfset client.detailID = -1>
79:
80: <tr bgcolor="#cccc99">
81: <td colspan="5">
82: &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="distMaint.cfm">Add a distributor</a>
83: </td>
84: </tr>
85:
86: <tr bgcolor="#cccccc">
87: <td>Sort by <a href="distAdm.cfm?SortBy=distName"><b>Name</b></a></td>
88: <td>Sort by <a href="distAdm.cfm?SortBy=portalName"><b>portal Name</b></a></td>
89: <td align="center">Distributor Info</td>
90: <td>&nbsp;&nbsp;&nbsp;</td>
91: <td>&nbsp;&nbsp;&nbsp;</td>
92: <!--
93: <td align="center", Format Pages</td>
94: <td align="center">Home Page Builder</td>
95: ---
96: </tr>
97:
98:

```

```

99: <CFIF qryEditList.recordCount is 0>
100: <TR><TD COLSPAN="5"><I>There are no distributors defined</I></TD></TR>
101: </CFIF>
102: <cfset lColor = True>
103: <form action="distChoice.cfm" method="post">
104: <cfoutput query="qryEditList" startrow="#nstartFrom#" maxrows="#ntoDisplay#">
105: <cfset lColor = not lColor>
106: <tr valign="center" <cfif lColor is TRUE>bgcolor="#ffffff"><cfif>>
107: <td>#qryEditList.distName#</td>
108: <td>#qryEditList.portalName#</td>
109: <td align="center"><input type="image" name="distEdit#qryEditList.distributorID#" src="#ap_commonImages#edit.gif"
    alt="Edit" border="0"></td>
110: <td>&nbsp;&nbsp;&nbsp;</td>
111: <td>&nbsp;&nbsp;&nbsp;</td>
112: </tr>
113: <td align="center">
114: <cfif qryEditList.maxPageFormats is not "">
115: <input type="image" name="fmtEdit#qryEditList.distributorID#" src="#ap_commonImages#edit.gif" alt="Edit"
    border="0">
116: <cfelse>
117: &nbsp;&nbsp;&nbsp;
118: </cfif>
119: </td>
120: <td align="center">
121: <cfif qryEditList.homePageBuilder is "">
122: <cfif qryEditList.homePageID gt 0>
123: <input type="image" name="homeEdit#qryEditList.distributorID#" src="#ap_commonImages#edit.gif" alt="Edit"
    border="0">
124: <cfelse>
125: <input type="image" name="homeEdit#qryEditList.distributorID#" src="#ap_commonImages#add.gif" alt="Edit"
    border="0">
126: </cfif>
127: <cfelse>
128: &nbsp;&nbsp;&nbsp;
129: </cfif>
130: </td>
131: </tr>
132: </tr>
133: </cfoutput>
134: </form>
135: </table></p>
136:
137:
138: <CFSET nPrevStart = nStartFrom+ntoDisplay>
139: <CFSET nNextStart = nStartFrom+ntoDisplay>
140: <CFSET nPrevEnd = #nPrevStart+nToDisplay-1>
141: <CFSET nNextEnd = #nNextStart+nToDisplay-1>
142: <cfif nPrevStart gte 1 or nNextStart lte qryEditList.recordCount>
143: <table border="0" align="center">

```

```

144: <tr>
145: <cfif nPrevStart gte 1>
146: <td>
147: <form action="distAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
148: <input type="hidden" name="nStartFrom" value="#nPrevStart#">
149: <input type="hidden" name="nToDisplay" value="#nToDisplay#">
150: <input type="hidden" name="nEnd" value="#nPrevEnd#">
151: <input type="submit" value="Previous #nToDisplay#">
152: </FORM>
153: </td>
154: </cfif>
155: <cfif nNextStart lte gryEditList.recordCount>
156: <td>
157: <form action="distAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
158: <input type="hidden" name="nStartFrom" value="#nNextStart#">
159: <input type="hidden" name="nToDisplay" value="#nToDisplay#">
160: <input type="hidden" name="nEnd" value="#nNextEnd#">
161: <cfset nLeftToShow = min(nToDisplay, (gryEditList.recordcount - cToDisplay))>
162: <input type="submit" value="Next #nLeftToShow#">
163: </form>
164: </td>
165: </cfif>
166: </tr>
167: </table>
168: </cfif>
169:
170: </body>
171: </html>
172:

```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <html>
4: <head>
5:   <title>Distributor Choice</title>
6: </head>
7:
8: <body>
9:
10:   <cfloop collection="#form#" item="cName">
11:     <cfif ucase(left(cName#8)) is "DISTEDIT" and findNoCase(".X", #cName#,1) gt 0>
12:       <cfset cValue = mid(cName#, 9, len(cName#)-10)>
13:       <cfset client.lookupID = val(cValue)>
14:       <cfset client.detailID = -1>
15:       <cfset client.userMessage = "">
16:       <cflocation url="distMaint.cfm" addToken="no">
17:     <cfelseif ucase(left(cName#7)) is "FMTEEDIT" and findNoCase(".X", #cName#,1) gt 0>
18:       <cfset cValue = mid(cName#, 8, len(cName#)-9)>
19:       <cfset client.lookupDistID = val(cValue)>
20:       <cfset client.lookupID = -1>
21:       <cfset client.detailID = -1>
22:       <cfset client.userMessage = "">
23:       <cflocation url="formatAdm.cfm" addToken="no">
24:     <cfelseif ucase(left(cName#8)) is "HOMEEDIT" and findNoCase(".X", #cName#,1) gt 0>
25:       <cfset cValue = mid(cName#, 9, len(cName#)-10)>
26:       <cfset client.lookupDistID = val(cValue)>
27:       <cfset client.lookupID = -1>
28:       <cfset client.detailID = -1>
29:       <cfset client.userMessage = "">
30:       <cflocation url="homePageMaint.cfm" addToken="no">
31:     </cfif>
32:   </cfloop>
33:
34:   <cfset client.lookupID = -1>
35:   <cfset client.detailID = -1>
36:   <cfset client.userMessage = "">
37:   <cflocation url="distAdm.cfm" addToken="no">
38:
39:
40: </body>
41: </html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:  <cfset client.gotoPage = "distDefaultAdm.cfm">
3:
4:
5:  <cfif client.currentEntityType lt #ap_securityMastDist# and client.lookupDistID is -1>
6:    <!-- We do not know what distributor we should be calling, so find out -->
7:    <cfset client.lookupDistID = -1>
8:    <cfset client.lookupAgencyID = -1>
9:    <cfset client.lookupID = -1>
10:   <cfset client.DetailID = -1>
11:   <cflocation url="distSelect.cfm" addToken="no">
12:   </cfif>
13:
14:   <cfif client.currentEntityType lt #ap_securityMastDist#>
15:     <cfquery name="qryDist" dataSource="#ap_dataSource#">
16:       select distributors.name as distName
17:       from distributors
18:       where distributors.distributorID = #client.lookupDistID#
19:     </cfquery>
20:     <cfset cDistName = qryDist.distName>
21:     <cfelseif client.currentEntityType gte #ap_securityMastDist#>
22:       <cfset client.lookupDistID = client.currentEntityID>
23:       <cfset cDistName = "">
24:     </cfif>
25:
26:     <cfset client.lookupID = -1>
27:     <cfset client.detailID = -1>
28:     <cfset client.lookupDistID = #client.lookupDistID#>
29:     <cfset client.lookupAgencyID = -1>
30:
31:     <!-- Display rows -->
32:     <cfparam name="nStartFrom" default="1">
33:     <cfparam name="nToDisplay" default="#client.displayRows#">
34:     <cfparam name="nEnd" default="#client.displayRows#">
35:
36:   <html>
37:   <head>
38:     <cfoutput>
39:     <title>#client.backofficeName# Backoffice Default Admin</title>
40:     </cfoutput>
41:     <link rel="stylesheet" href="style1.css" type="text/css">
42:   </head>
43:
44:   <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
45:   <cfinclude template="include\nocache.cfm">
46:   <p><cfinclude template="include\header.cfm"></p>
47:
48:
49:   <p>

```



```

50: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
51:   <tr bgcolor="#cccc99">
52:     <td colspan="4">
53:       <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">
54:         <tr>
55:           <td align="left">
56:             <span class="h2">
57:               <b>Defaults Administration</b>
58:             <cfif cDistName is not "">
59:               <cfoutput>
60:                 <b>#cDistName#</b>
61:               </cfoutput>
62:             </cfif>
63:           </span>
64:         </td>
65:       </tr>
66:     </table>
67:   </td>
68: </tr>
69:
70:   <cfif trim(client.userName) is not "">
71:     <tr bgcolor="#cccc99">
72:       <td colspan="4" align="center">
73:         <cfoutput><b>#client.userName#</b></cfoutput>
74:       </td>
75:     </tr>
76:   </cfif>
77:   <cfset client.userName = "">
78:
79:   <tr valign="top" bgcolor="#eeeeee">
80:     <td><a href="defaultMaint.cfm?type=home&from=dist">Home Types</a></td>
81:     <td><a href="defaultMaint.cfm?type=lot&from=dist">Lot Types</a></td>
82:     <td><a href="defaultMaint.cfm?type=property&from=dist">Property Types</a></td>
83:     <td><a href="defaultMaint.cfm?type=status&from=dist">Property Status</a></td>
84:   </tr>
85:   <tr valign="top" bgcolor="#eeeeee">
86:     <td><a href="defaultMaint.cfm?type=region&from=dist">Regions</a></td>
87:     <td><a href="defaultMaint.cfm?type=pageFormat&from=dist">Page Format</a></td>
88:     <td><a href="defaultMaint.cfm?type=rooms&from=dist">Rooms</a></td>
89:     <td><b>#</td>
90:   </tr>
91:
92: </table></p>
93:
94: </body>
95: </html>
96:

```

DO NOT EDIT THIS FILE. IT IS A TRANSITIONAL FILE.

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfif not isDefined("client.lookupID")>
4:    <cflocation url="distAdm.cfm" addToken="no">
5:  </cfif>
6:  <cfparam name="client.userName" default="">
7:
8:  <cfquery name="qryFindDist" datasource="#ap_dataSource#">
9:    select distributors.*
10:   from distributors
11:   where distributors.distributorID = #client.lookupID#
12: </cfquery>
13:
14:
15:  <cfquery name="qryCommunities" datasource="#ap_dataSource#">
16:    select communities.communityID, communities.name
17:   from communities
18:   order by communities.name
19: </cfquery>
20:
21:  <cfquery name="qryDistComm" datasource="#ap_dataSource#">
22:    select distCommunities.communityID
23:   from distCommunities
24:   where distCommunities.distributorID = #client.lookupID#
25: </cfquery>
26:
27:  <cfset lstCommunities = valueList(qryDistComm.communityID)>
28:
29:  <cfif qryFindDist.recordCount gt 0>
30:    <cfset nDistID = qryFindDist.distributorID>
31:  <cfelse>
32:    <cfset nDistID = -1>
33:  </cfif>
34:
35:  <cfinclude template="include\javaValidate.cfm">
36:  <script language="JavaScript">
37:    <!--
38:    function validate(testform) {
39:      var results = "";
40:      var lResult = true;
41:
42:      if (removeSpaces(testform.edtName.value) == "") {
43:        results = results + "Please enter the distributor's name.\r";
44:        lResult = false;
45:      }
46:
47:      if (removeSpaces(testform.edtKeepers.value) == "") {
48:        results = results + "Please enter the full path for Keepers property views.\r";
49:        lResult = false;

```

```

50: }
51:
52: if (!Result) {
53:     window.alert(results);
54: }
55: return lResult;
56: }
57: -->
58: </script>
59:
60: <script language="JavaScript">
61: <!--
62:     function setSmallMarket() {
63:         document.forms(1).edtMaxAgencies.value = -1;
64:         document.forms(1).edtMaxAgents.value = -1;
65:         document.forms(1).edtMaxProperties.value = -1;
66:         document.forms(1).edtEnhancedResources.value = -1;
67:         document.forms(1).edtMaxPageFormats.value = -1;
68:         document.forms(1).edtMaxSpecialtyPages.value = 5;
69:         document.forms(1).edtMaxEnhAgencies.value = -1;
70:         document.forms(1).edtMaxEnhAgents.value = -1;
71:         document.forms(1).edtMaxEnhProperties.value = 0;
72:         document.forms(1).edtMaxCommunities.value = 1;
73:         document.forms(1).edtMultiplePropertyImages.checked = true;
74:         document.forms(1).edtEnhancedResources.checked = true;
75:
76:         return true;
77:     }
78:
79:     function setHighImpact() {
80:         document.forms(1).edtMaxAgencies.value = -1;
81:         document.forms(1).edtMaxAgents.value = -1;
82:         document.forms(1).edtMaxProperties.value = -1;
83:         document.forms(1).edtEnhancedResources.value = -1;
84:         document.forms(1).edtMaxPageFormats.value = -1;
85:         document.forms(1).edtMaxSpecialtyPages.value = -1;
86:         document.forms(1).edtMaxEnhAgencies.value = -1;
87:         document.forms(1).edtMaxEnhAgents.value = -1;
88:         document.forms(1).edtMaxEnhProperties.value = -1;
89:         document.forms(1).edtMaxCommunities.value = -1;
90:         document.forms(1).edtMultiplePropertyImages.checked = true;
91:         document.forms(1).edtEnhancedResources.checked = true;
92:
93:         return true;
94:     }
95:
96:     function setFullImpact() {
97:         document.forms(1).edtMaxAgencies.value = -1;
98:         document.forms(1).edtMaxAgents.value = -1;

```

```

99: document.forms(1).edtMaxProperties.value = -1;
100: document.forms(1).edtEnhancedResources.value = -1;
101: document.forms(1).edtMaxPageFormats.value = 1;
102: document.forms(1).edtMaxSpecialtyPages.value = 2;
103: document.forms(1).edtMaxEnhAgencies.value = -1;
104: document.forms(1).edtMaxEnhAgents.value = -1;
105: document.forms(1).edtMaxEnhProperties.value = -1;
106: document.forms(1).edtMaxCommunities.value = -1;
107: document.forms(1).edtMultiplePropertyImages.checked = true;
108: document.forms(1).edtEnhancedResources.checked = true;
109:
110: return true;
111: }
112: -->
113: </script>
114:
115: <html>
116: <head>
117: <cfoutput>
118: <title>#client.backofficeName# Backoffice Distributor Maintenance</title>
119: </cfoutput>
120: <link rel="stylesheet" href="style1.css" type="text/css">
121: </head>
122:
123: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
124: <cfinclude template="include\nocache.cfm">
125:
126: <p><cfinclude template="include\header.cfm"></p>
127:
128: <cfoutput>
129:
130: <form action="distUpdate.cfm" method="post" onsubmit="return validate(this)">
131: <input type="hidden" name="distributorID" value="#nDistID#">
132:
133: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
134: <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Distributor Maintenance</b></span>
135: <cfif client.lookupID is -1>
136: <nbsp;   <b>(Create a new Distributor)</b>
137: </cfif>
138: </td></tr>
139:
140: <CFIF client.userMessage is not "">
141: <tr bgcolor="eeeeee">
142: <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td>
143: </tr>
144: <tr bgcolor="eeeeee"><td colspan="5"><b><nbsp;   </td></tr>
145: </CFIF>
146: <cfset client.userMessage = "">
147:

```

```

148: <tr bgcolor="#eeeeee">
149: <td width="15%"><b>Name:</b></td>
150: <td colspan="4"><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
151: </tr>
152:
153: <tr bgcolor="#eeeeee">
154: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
155: </tr>
156:
157: <tr bgcolor="#eeeeee">
158: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
159: </tr>
160: <tr bgcolor="#eeeeee">
161: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
162: </tr>
163:
164: <tr bgcolor="#eeeeee">
165: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
166: </tr>
167:
168: <tr bgcolor="#eeeeee">
169: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
170: </tr>
171: <tr bgcolor="#eeeeee">
172: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
173: </tr>
174:
175: <tr bgcolor="#eeeeee">
176: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
177: </tr>
178:
179: <tr bgcolor="#eeeeee">
180: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
181: </tr>
182:
183: <tr bgcolor="#eeeeee">
184: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
185: </tr>
186:
187: <tr bgcolor="#eeeeee">
188: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
189: </tr>
190:
191: <tr bgcolor="#eeeeee">
192: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>
193: </tr>
194:
195: <tr bgcolor="#eeeeee">
196: <td colspan="5"><b><input type="text" name="edtName" value="#qryFindDist.name#" size="50"></td>

```

```

197:      <td colspan="4"><input type="text" name="edtEnhAgentImages" value="#qryFindDist.enhAgentImages#" size="70"></td>
198:    </tr>
199:    <tr bgcolor="#eeeeee">
200:      <td width="15%"><b>Community Images:</b></td>
201:      <td colspan="4"><input type="text" name="edtCommunityImages" value="#qryFindDist.communityImages#" size="70"></td>
202:    </tr>
203:    <tr bgcolor="#eeeeee">
204:      <td width="15%"><b>Specialty Images:</b></td>
205:      <td colspan="4"><input type="text" name="edtSpecialtyImages" value="#qryFindDist.specialtyImages#" size="70"></td>
206:    </tr>
207:
208:    <tr bgcolor="#eeeeee">
209:      <td colspan="5"><b><input type="text" name="edtEmailProblems" value="#qryFindDist.emailProblems#" size="50"></td>
210:    </tr>
211:
212:    <tr bgcolor="#eeeeee">
213:      <td width="15%"><b>Email Problems To:</b></td>
214:      <td colspan="4"><input type="text" name="edtEmailProblems" value="#qryFindDist.emailProblems#" size="50"></td>
215:    </tr>
216:
217:    <tr bgcolor="#eeeeee">
218:      <td colspan="5"><b><input type="text" name="edtSmallMarket" value="#qryFindDist.setSmallMarket()">
219:    </tr>
220:
221:    <tr bgcolor="#eeeeee">
222:      <td colspan="5">Maximum values for distributor: <b><input type="text" name="edtMaxAgencies" value="#qryFindDist.maxAgencies#" size="4"></td>
223:    </tr>
224:    <tr bgcolor="#eeeeee">
225:      <td colspan="5">
226:        Quick Product Setup:
227:        <input type="button" name="btnHighImpact" value="High Impact" onclick="return setHighImpact()"><b>
228:        <input type="button" name="btnFullImpact" value="Full Impact" onclick="return setFullImpact()"><b>
229:        <input type="button" name="btnSmallMarket" value="Small Market" onclick="return setSmallMarket()">
230:      </td>
231:    </tr>
232:
233:    <tr bgcolor="#eeeeee">
234:      <td width="15%">Agencies:</td>
235:      <td width="34%"><input type="text" name="edtMaxAgencies" value="#qryFindDist.maxAgencies#" size="4"></td>
236:      <td width="2%"><b></td>
237:      <td width="15%">Agents:</td>
238:      <td width="34%"><input type="text" name="edtMaxAgents" value="#qryFindDist.maxAgents#" size="4"></td>
239:    </tr>
240:    <tr bgcolor="#eeeeee">
241:      <td width="15%">Properties:</td>
242:      <td width="34%"><input type="text" name="edtMaxProperties" value="#qryFindDist.maxProperties#" size="4"></td>
243:      <td width="2%"><b></td>
244:      <td width="15%">Multiple Property Images:</td>
245:      <td width="34%"><input type="checkbox" name="edtMultiplePropertyImages"><cfif qryFindDist.multiplePropertyImages is

```

```

246: "Y"> checked</cfif>></td>
247: </tr>
248: <tr bgcolor="#ffffff">
249: <td width="15%">Enhanced Resources:</td>
250: <td width="34%"><input type="checkbox" name="edtEnhancedResources"><cfif qryFindDist.enhancedResources is "Y">
251: checked</cfif>></td>
252: <td width="28%"><input type="checkbox" name="edtMaxPageFormats"></td>
253: <td width="15%">Page Formats:</td>
254: <td width="34%"><input type="checkbox" name="qryFindDist.maxPageFormats#" size="4"></td>
255: </tr>
256: <tr bgcolor="#ffffff">
257: <td width="15%">Specialty Pages:</td>
258: <td width="34%"><input type="checkbox" name="edtMaxSpecialtyPages" value="#qryFindDist.maxAgencies#" size="4"></td>
259: <td width="28%"><input type="checkbox" name="edtMaxEnhAgencies" value="#qryFindDist.maxEnhancedAgencies#" size="4"></td>
260: <td width="15%">Enhanced Agencies:</td>
261: <td width="34%"><input type="checkbox" name="edtMaxEnhAgencies" value="#qryFindDist.maxEnhancedAgencies#" size="4"></td>
262: </tr>
263: <tr bgcolor="#ffffff">
264: <td width="15%">Enhanced Properties:</td>
265: <td width="34%"><input type="checkbox" name="edtMaxEnhProperties" value="#qryFindDist.maxEnhancedProperties#"
266: size="4"></td>
267: </tr>
268: <tr bgcolor="#ffffff">
269: <td width="15%">Communities:</td>
270: <td width="34%"><input type="checkbox" name="edtMaxCommunities" value="#qryFindDist.maxCommunities#" size="4"></td>
271: <td width="28%"><input type="checkbox" name="qryFindDist.maxCommunities#" size="4"></td>
272: </tr>
273: <tr bgcolor="#ffffff">
274: <td width="15%">Home Page Builder:</td>
275: <td width="34%"><input type="checkbox" name="edtHomePageBuilder" value="#qryFindDist.homePageBuilder is "Y">
276: checked</cfif>></td>
277: <td colspan="3"><input type="checkbox" name="qryFindDist.homePageBuilder" value="#qryFindDist.homePageBuilder is "Y">
278: </tr>
279: <tr bgcolor="#ffffff">
280: <td colspan="4"><input type="checkbox" name="qryFindDist.homePageBuilder" value="#qryFindDist.homePageBuilder is "Y">
281: </tr>
282: <tr bgcolor="#ffffff">
283: <td colspan="4"><input type="checkbox" name="qryFindDist.homePageBuilder" value="#qryFindDist.homePageBuilder is "Y">
284: </tr>
285: <cfif client.currentEntityType is 1>
286: <cfquery name="qryPortals" dataSource="#ap_dataSource#">
287: select portals.portalID, portals.name
288: from portals
289: order by name
290: </cfquery>
<tr bgcolor="#ffffff">

```

```

291:      <td width="15%">Portal:</td>
292:      <td colspan="4">
293:        <select name="edtPortalID">
294:          <option value="1"><cfif qryFindDist.portalID lte 0 or trim(qryFindDist.portalID) is ""> selected</cfif><Not
Assigned
295:            <cfloop query="qryPortals">
296:              <option value="#qryPortals.portalID#"><cfif qryPortals.portalID is qryFindDist.portalID>
selected</cfif>>#qryPortals.name#
297:            </cfloop>
298:          </select>
299:        </td>
300:      </tr>
301:      <cfelse>
302:        <input type="hidden" name="edtPortalID" value="#client.currentPortalID#">
303:      </cfif>
304:
305:      <tr bgcolor="#eeeeee">
306:        <td colspan="5"><b>sp</b></td>
307:      </tr>
308:
309:      <tr bgcolor="#eeeeee">
310:        <cfif qryFindDist.recordCount is 0>
311:          <td colspan="5">
312:            <input type="submit" name="btnUpdate" value="Add Distributor">
313:            <input type="reset" value="Reset Info">
314:          </td>
315:        <cfelse>
316:          <td colspan="4">
317:            <input type="submit" name="btnUpdate" value="Update Distributor Info">
318:            <input type="reset" value="Reset Info">
319:          </td>
320:          <td align="right">
321:            <input type="submit" name="btnDelete" value="Delete Distributor">
322:          </td>
323:        </cfif>
324:      </td>
325:    </tr>
326:  </table>
327: </form>
328:
329: </cfoutput>
330:
331: </body>
332: </html>

```



```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfinclude template="include\checkSecurity.cfm">
4:
5:  <cfparam name="client.jumpToPage" default="">
6:
7:  <cfif client.gotoPage is "">
8:    <cflocation url="messages.cfm" addToken="no">
9:  </cfif>
10:
11:  <cfset client.lookupID = -1>
12:  <cfset client.detailID = -1>
13:  <cfset client.lookupDistID = -1>
14:  <cfset client.lookupAgencyID = -1>
15:
16:  <cfif client.currentEntityType gte #ap_securityMastDist#>
17:    <cfset client.lookupDistID = currentEntityID>
18:    <cflocation url="#client.gotoPage#" addToken="no">
19:  </cfif>
20:
21:
22:  <cfquery name="qryDist" dataSource="#ap_dataSource#">
23:    select distributors.distributorID, distributors.name as distName
24:    from distributors
25:    join securityAccess on
26:      (securityAccess.entityType = #ap_securityMastDist# or securityAccess.entityType = #ap_securityDist#)
27:      and securityAccess.entityID = distributors.distributorID
28:      and securityAccess.hierarchyID like '#client.hierarchyID#%'
29:    order by distName
30:  </cfquery>
31:
32:  <cfif qryDist.recordCount is 0>
33:    <cfset client.userMessage = "There are no distributors for selection.">
34:    <cflocation url="messages.cfm" addToken="no">
35:  <cfelseif qryDist.recordCount is 1>
36:    <cfset client.lookupDistID = qryDist.distributorID>
37:    <cflocation url="#client.gotoPage#" addToken="no">
38:  </cfif>
39:
40:  <html>
41:  <head>
42:    <cfoutput>
43:      <title>#client.backofficeName# Backoffice Select Distributor</title>
44:    </cfoutput>
45:    <link rel="stylesheet" href="style1.css" type="text/css">
46:  </head>
47:
48:
49:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">

```

2  
2  
1

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <html>
4: <head>
5:   <title>Distributor Selected</title>
6: </head>
7:
8: <body>
9:
10:   <cfif isDefined("btnSelectDist")>
11:     <cfset client.lookupDistID = form.edtDistributorID>
12:     <cflocation url="#client.gotoPage#" addToken="no">
13:   </cfif>
14:
15:   <cflocation url="messages.cfm" addToken="no">
16:
17: </body>
18: </html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfif not isDefined("form.distributorID")>
4:    <cfset client.lookupID = -1>
5:    <cfset client.detailID = -1>
6:    <cfset client.userName = "">
7:    <cflocation url="distAdm.cfm" addtoken="no">
8:  </cfif>
9:
10:  <cfquery name="qryFindDist" datasource="#ap_dataSource#">
11:    select distributorID, name
12:    from distributors
13:    where distributors.distributorID = #form.distributorID#
14:  </cfquery>
15:
16:  <cfinclude template="include\clearOldFields.cfm">
17:  <cfset client.userName = "">
18:
19:  <!-- Save form values in case something is wrong -->
20:
21:  <cfif isDefined("form.btnUpdate")>
22:    <cfif qryFindDist.recordCount is 0>
23:      <cfset client.lookupID = -1>
24:      <cfset client.detailID = -1>
25:      <cfset client.userName = "There was an error while creating the distributor.">
26:      <cftransaction>
27:        <cfset cName = preserveSingleQuotes(form.edtName)>
28:        <cfset nMaxAgencies = val(form.edtMaxAgencies)>
29:        <cfset nMaxAgents = val(form.edtMaxAgents)>
30:        <cfset nMaxProperties = val(form.edtMaxProperties)>
31:        <cfset nMaxCommunities = val(form.edtMaxCommunities)>
32:        <cfset nMaxSpecialtyPages = val(form.edtMaxSpecialtyPages)>
33:        <cfset nMaxEnhAgencies = val(form.edtMaxEnhAgencies)>
34:        <cfset nMaxEnhAgents = val(form.edtMaxEnhAgents)>
35:        <cfset nMaxEnhProperties = val(form.edtMaxEnhProperties)>
36:        <cfset nMaxPageFormats = val(form.edtMaxPageFormats)>
37:        <cfset cEmailProblems = preserveSingleQuotes(form.edtEmailProblems)>
38:
39:        <cfset cDataPath = preserveSingleQuotes(form.edtDataPath)>
40:        <cfif right(cDataPath,1) is not "\">
41:          <cfset cDataPath = cDataPath & "\">
42:        </cfif>
43:        <cfset cKeepers = preserveSingleQuotes(form.edtKeepers)>
44:        <cfif right(cKeepers,1) is not "\">
45:          <cfset cKeepers = cKeepers & "\">
46:        </cfif>
47:        <cfset cCommonImages = preserveSingleQuotes(form.edtCommonImages)>
48:        <cfif right(cCommonImages,1) is not "\">
49:          <cfset cCommonImages = cCommonImages & "\">

```

```

50: </cfif>
51: <cfset cPropertyImages = preserveSingleQuotes(form.edtPropertyImages)>
52: <cfif right(cPropertyImages,1) is not "\">
53:   <cfset cPropertyImages = cPropertyImages & "\">
54: </cfif>
55: <cfset cAgencyImages = preserveSingleQuotes(form.edtAgencyImages)>
56: <cfif right(cAgencyImages,1) is not "\">
57:   <cfset cAgencyImages = cAgencyImages & "\">
58: </cfif>
59: <cfset cAgentImages = preserveSingleQuotes(form.edtAgentImages)>
60: <cfif right(cAgentImages,1) is not "\">
61:   <cfset cAgentImages = cAgentImages & "\">
62: </cfif>
63: <cfset cEnhAgencyImages = preserveSingleQuotes(form.edtEnhAgencyImages)>
64: <cfif right(cEnhAgencyImages,1) is not "\">
65:   <cfset cEnhAgencyImages = cEnhAgencyImages & "\">
66: </cfif>
67: <cfset cEnhAgentImages = preserveSingleQuotes(form.edtEnhAgentImages)>
68: <cfif right(cEnhAgentImages,1) is not "\">
69:   <cfset cEnhAgentImages = cEnhAgentImages & "\">
70: </cfif>
71: <cfset cCommunityImages = preserveSingleQuotes(form.edtCommunityImages)>
72: <cfif right(cCommunityImages,1) is not "\">
73:   <cfset cCommunityImages = cCommunityImages & "\">
74: </cfif>
75: <cfset cSpecialtyImages = preserveSingleQuotes(form.edtSpecialtyImages)>
76: <cfif right(cSpecialtyImages,1) is not "\">
77:   <cfset cSpecialtyImages = cSpecialtyImages & "\">
78: </cfif>
79:
80:
81: <cfif isDefined("form.edtMultiplePropertyImages")>
82:   <cfset cMultipleProp = "Y">
83: <cfelse>
84:   <cfset cMultipleProp = "N">
85: </cfif>
86: <cfif isDefined("form.edtEnhancedResources")>
87:   <cfset cEnhancedResources = "Y">
88: <cfelse>
89:   <cfset cEnhancedResources = "N">
90: </cfif>
91: <cfif isDefined("form.edtHomePageBuilder")>
92:   <cfset cHomePageBuilder = "Y">
93: <cfelse>
94:   <cfset cHomePageBuilder = "N">
95: </cfif>
96:
97: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
98:   insert into distributors

```

```

99: (name, dataPath, keepersPath, #cDataPath#, '#cKeepers#', #nMaxAgencies#, #nMaxAgents#,
100: maxCommunities, maxSpecialtyPages, maxAgencies, maxAgents, maxProperties,
101: maxEnhancedAgents, maxSpecialtyPages, maxEnhancedAgencies,
102: multiplePropertyImages, maxEnhancedProperties, maxPageFormats,
103: commonImages, propertyImages, enhancedResources, homePageBuilder,
104: enhAgencyImages, enhAgentImages, agencyImages, agentImages,
105: specialtyImages, emailProblems, portalID)
106: values
107: ('#cName#', '#cDataPath#', '#cKeepers#', #nMaxAgencies#, #nMaxAgents#,
108: #nMaxProperties#, #nMaxCommunities#, #nMaxSpecialtyPages#,
109: #nMaxEnhancedAgencies#, #nMaxEnhancedAgents#, #nMaxEnhancedProperties#,
110: #nMaxPageFormats#, '#cMultipleProp#', '#cEnhancedResources#',
111: '#cHomePageBuilder#', '#cCommonImages#', '#cPropertyImages#',
112: '#cAgencyImages#', '#cAgentImages#', '#cEnhAgencyImages#',
113: '#cEnhAgentImages#', '#cCommunityImages#', '#cSpecialtyImages#',
114: '#cEmailProblems#', '#form.edtPortalID#)
115:
116: </cfquery>
117:
118: <cfquery name="qryGetID" dataSource="#ap_dataSource#">
119:   select max(distributorID) as lastID
120:   from distributors
121: </cfquery>
122: <cfset nDistID = qryGetID.lastID>
123:
124: <!-- Create default lists for this distributor -->
125: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
126:   insert into statusValues
127:     (distributorID, status, propViewVisible)
128:   select #nDistID# as distributorID, statusValues.status, statusValues.propViewVisible
129:     from statusValues
130:   where statusValues.distributorID = 0
131: </cfquery>
132: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
133:   insert into lotTypeValues
134:     (distributorID, lotType)
135:   select #nDistID# as distributorID, lotTypeValues.lotType
136:     from lotTypeValues
137:   where lotTypeValues.distributorID = 0
138: </cfquery>
139: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
140:   insert into homeTypeValues
141:     (distributorID, homeType)
142:   select #nDistID# as distributorID, homeTypeValues.homeType
143:     from homeTypeValues
144:   where homeTypeValues.distributorID = 0
145: </cfquery>
146: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
147:   insert into propertyTypeValues
148:     (distributorID, propertyType)

```

```

148: select #nDistID# as distributorID, propertyTypeValues.propertyType
149: from propertyTypeValues
150: where propertyTypeValues.distributorID = 0
151: </cfquery>
152: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
153: insert into regionValues
154: (distributorID, region)
155: select #nDistID# as distributorID, regionValues.region
156: from regionValues
157: where regionValues.distributorID = 0
158: </cfquery>
159:
160: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
161: insert into roomValues
162: (distributorID, agencyID, room, sortOrder)
163: select #nDistID# as distributorID, 0, roomValues.room, sortOrder
164: from roomValues
165: where roomValues.distributorID = 0
166: and roomValues.agencyID = 0
167: </cfquery>
168:
169: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
170: insert into pageFormats
171: (distributorID, description, navBGColor, navTextColor,
172: menuBGColor, menuTextColor, headerBGColor, footerBGColor,
173: adBGColor, headerCode, sideCode,
174: footerCode)
175: select #nDistID# as distributorID, pageFormats.description,
176: pageFormats.navBGColor, pageFormats.navTextColor,
177: pageFormats.menuBGColor, pageFormats.menuTextColor,
178: pageFormats.headerBGColor, pageFormats.footerBGColor,
179: pageFormats.adBGColor,
180: pageFormats.headerCode, pageFormats.sideCode, pageFormats.footerCode
181: from pageFormats
182: where pageFormats.distributorID = 0
183: </cfquery>
184:
185: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
186: insert into formatAssignment
187: (pageFormatID, distributorID, entityType, entityID)
188: select formatAssignment.pageFormatID, #nDistID# as distributorID,
189: formatAssignment.entityType, formatAssignment.entityID
190: from formatAssignment
191: where formatAssignment.distributorID = 0
192: </cfquery>
193:
194: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
195: insert into navigation
196: (distributorID, menuText, menuURL, sortOrder, systemLink)

```

```

197: select #nDistID# as distributorID, navigation.menuText,
198:        navigation.menuURL, navigation.sortOrder, navigation.systemLink
199: from navigation
200: where navigation.distributorID = 0
201: </cfquery>
202:
203: <cfset nCreatedDistID = nDistID>
204: <cfinclude template="include\makeApplication.cfm">
205:
206: <cfset nUpdateID = #qryGetID.lastID#>
207: <cfset nUpdateType = #ap_securityMastDist#>
208: <cfset nUpdateAction = "ADD">
209: <cfinclude template="include\makeSecurityTree.cfm">
210:
211: <cfset client.userName = form.edtName & " distributor was created.">
212: </cftransaction>
213:
214: <cflocation url="distAdm.cfm" addToken="no">
215: <cfelse>
216: <cfset client.lookupID = -1>
217: <cfset client.detailID = -1>
218: <cfset client.userName = "There was an error while updating the distributor information.">
219: </cftransaction>
220:
221: <cfset cName = preservesSingleQuotes(form.edtName)>
222: <cfset cMaxAgencies = val(form.edtMaxAgencies)>
223: <cfset cMaxAgents = val(form.edtMaxAgents)>
224: <cfset cMaxProperties = val(form.edtMaxProperties)>
225: <cfset cMaxCommunities = val(form.edtMaxCommunities)>
226: <cfset cMaxSpecialtyPages = val(form.edtMaxSpecialtyPages)>
227: <cfset cMaxEnhAgencies = val(form.edtMaxEnhAgencies)>
228: <cfset cMaxEnhAgents = val(form.edtMaxEnhAgents)>
229: <cfset cMaxEnhProperties = val(form.edtMaxEnhProperties)>
230: <cfset cMaxPageFormats = val(form.edtMaxPageFormats)>
231: <cfset cEmailProblems = preservesSingleQuotes(form.edtEmailProblems)>
232:
233: <cfset cDataPath = preservesSingleQuotes(form.edtDataPath)>
234: <cfif right(cDataPath,1) is not "\">
235:     <cfset cDataPath = cDataPath & "\">
236: </cfif>
237: <cfset cKeepers = preservesSingleQuotes(form.edtKeepers)>
238: <cfif right(cKeepers,1) is not "\">
239:     <cfset cKeepers = cKeepers & "\">
240: </cfif>
241: <cfset cCommonImages = preservesSingleQuotes(form.edtCommonImages)>
242: <cfif right(cCommonImages,1) is not "\">
243:     <cfset cCommonImages = cCommonImages & "\">
244: </cfif>
245: <cfset cPropertyImages = preservesSingleQuotes(form.edtPropertyImages)>
246: <cfif right(cPropertyImages,1) is not "\">

```



```

246:      <cfset cPropertyImages = cPropertyImages & "\">
247:    </cfif>
248:    <cfset cAgencyImages = preservesSingleQuotes(form.edtAgencyImages)>
249:    <cfif right(cAgencyImages,1) is not "\">
250:      <cfset cAgencyImages = cAgencyImages & "\">
251:    </cfif>
252:    <cfset cAgentImages = preservesSingleQuotes(form.edtAgentImages)>
253:    <cfif right(cAgentImages,1) is not "\">
254:      <cfset cAgentImages = cAgentImages & "\">
255:    </cfif>
256:    <cfset cEnhAgencyImages = preservesSingleQuotes(form.edtEnhAgencyImages)>
257:    <cfif right(cEnhAgencyImages,1) is not "\">
258:      <cfset cEnhAgencyImages = cEnhAgencyImages & "\">
259:    </cfif>
260:    <cfset cEnhAgentImages = preservesSingleQuotes(form.edtEnhAgentImages)>
261:    <cfif right(cEnhAgentImages,1) is not "\">
262:      <cfset cEnhAgentImages = cEnhAgentImages & "\">
263:    </cfif>
264:    <cfset cCommunityImages = preservesSingleQuotes(form.edtCommunityImages)>
265:    <cfif right(cCommunityImages,1) is not "\">
266:      <cfset cCommunityImages = cCommunityImages & "\">
267:    </cfif>
268:    <cfset cSpecialtyImages = preservesSingleQuotes(form.edtSpecialtyImages)>
269:    <cfif right(cSpecialtyImages,1) is not "\">
270:      <cfset cSpecialtyImages = cSpecialtyImages & "\">
271:    </cfif>
272:
273:    <cfif isDefined("form.edtMultiplePropertyImages")>
274:      <cfset cMultipleProp = "Y">
275:    </cfelse>
276:      <cfset cMultipleProp = "N">
277:    </cfif>
278:    <cfif isDefined("form.edtEnhancedResources")>
279:      <cfset cEnhancedResources = "Y">
280:    </cfelse>
281:      <cfset cEnhancedResources = "N">
282:    </cfif>
283:    <cfif isDefined("form.edtHomePageBuilder")>
284:      <cfset cHomePageBuilder = "Y">
285:    </cfelse>
286:      <cfset cHomePageBuilder = "N">
287:    </cfif>
288:
289:    <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
290:      update distributors
291:      set name
292:        = '#cName#',
293:        dataPath
294:          = '#cDataPath#',
295:          keepersPath
296:            = '#cKeepers#',
297:            maxAgencies
298:              = '#nMaxAgencies#',

```

```

295: maxAgents = #nMaxAgents#
296: maxProperties = #nMaxProperties#
297: maxCommunities = #nMaxCommunities#
298: maxSpecialtyPages = #nMaxSpecialtyPages#
299: maxEnhancedAgencies = #nMaxEnhAgencies#
300: maxEnhancedAgents = #nMaxEnhAgents#
301: maxEnhancedProperties = #nMaxEnhProperties#
302: maxPageFormats = #nMaxPageFormats#
303: multiplePropertyImages = #cMultipleProp#
304: enhancedResources = #cEnhancedResources#
305: homePageBuilder = #cHomePageBuilder#
306: commonImages = #cCommonImages#
307: propertyImages = #cPropertyImages#
308: agencyImages = #cAgencyImages#
309: agentImages = #cAgentImages#
310: enhAgencyImages = #cEnhAgencyImages#
311: enhAgentImages = #cEnhAgentImages#
312: communityImages = #cCommunityImages#
313: specialtyImages = #cSpecialtyImages#
314: emailProblems = #cEmailProblems#
315: portalID = #form.edtPortalID#
316: where distributors.distributorID = #form.distributorID#
317: </cfquery>
318:
319: <cfset nCreatedDistID = form.distributorID>
320: <cfinclude template="include\makeApplication.cfm">
321:
322: <cfset nUpdateID = #form.distributorID#>
323: <cfset nUpdateType = #ap_securityMastDist#>
324: <cfset nUpdateAction = "UPDATE">
325: <cfinclude template="include\makeSecurityTree.cfm">
326:
327: <cfset client.userName = #form.edtName# & " distributor was saved.">
328: </cftransaction>
329: <cflocation url="distAdm.cfm" addToken="no">
330: </cfif>
331: <cfelseif isDefined("form.btnDelete")>
332: <cfset client.lookupID = -1>
333: <cfset client.detailID = -1>
334: <cfset client.userName = "Unable to delete #form.edtName#">
335: </cftransaction>
336: <cfquery name="qryDelete" dataSource="#ap_dataSource#">
337: delete from statusValues
338: where statusValues.distributorID = #form.distributorID#
339: </cfquery>
340:
341: <cfquery name="qryDelete" dataSource="#ap_dataSource#">
342: delete from lotTypeValues
343: where lotTypeValues.distributorID = #form.distributorID#

```

```

344: </cfquery>
345: <cfquery name="qryDelete" datasource="#ap_dataSource#">
346:   delete from homeTypeValues
347:   where homeTypeValues.distributorID = #form.distributorID#
348: </cfquery>
349: <cfquery name="qryDelete" datasource="#ap_dataSource#">
350:   delete from propertyTypeValues
351:   where propertyTypeValues.distributorID = #form.distributorID#
352: </cfquery>
353: <cfquery name="qryDelete" datasource="#ap_dataSource#">
354:   delete from regionValues
355:   where regionValues.distributorID = #form.distributorID#
356: </cfquery>
357: <cfquery name="qryDelete" datasource="#ap_dataSource#">
358:   delete from roomValues
359:   where roomValues.distributorID = #form.distributorID#
360:   and roomValues.agencyID = 0
361: </cfquery>
362: <cfquery name="qryDelete" datasource="#ap_dataSource#">
363:   delete from pageFormats
364:   where pageFormats.distributorID = #form.distributorID#
365: </cfquery>
366: <cfquery name="qryDelete" datasource="#ap_dataSource#">
367:   delete from navigation
368:   where navigation.distributorID = #form.distributorID#
369: </cfquery>
370:
371: <!--- Now delete the distributor --->
372: <cfquery name="qryDelete" datasource="#ap_dataSource#">
373:   delete from distributors
374:   where distributors.distributorID = #form.distributorID#
375: </cfquery>
376:
377: <cfset nUpdateID = #form.distributorID#>
378: <cfset nUpdateType = #ap_securityMastDist#>
379: <cfset nUpdateAction = "DELETE">
380: <cfinclude template="include\makeSecurityTree.cfm">
381:
382: <cfset client.userName = #form.edtName# & " distributor was deleted">
383: </cftransaction>
384: <cflocation url="distAdm.cfm" addtoken="no">
385: </cfif>

```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <html>
4:  <head>
5:    <cfoutput>
6:      <title>Recreate FullImpact Security Tree</title>
7:    </cfoutput>
8:    <link rel="stylesheet" href="style1.css" type="text/css">
9:  </head>
10:
11:
12:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
13:    <cfinclude template="include\nocache.cfm">
14:    <cfinclude template="include\header.cfm">
15:
16:    <cfinclude template="include\dpomakeSecurityTree.cfm">
17:
18:    <br>
19:    <b>Security tree generation complete.</b><br>
20:  <br>
21:  <i>(The generated tree structure is displayed below)</i>
22:  <hr>
23:
24:  <cfquery name="qrySecurity" dataSource="#ap_datasource#">
25:    select *
26:    from securityAccess
27:    order by hierarchyID
28:  </cfquery>
29:
30:  <table border="1">
31:    <tr>
32:      <td><b>Yakalo Admin</b></td>
33:      <td><b>Portal</b></td>
34:      <td><b>Master Distributor</b></td>
35:      <td><b>Distributor</b></td>
36:      <td><b>Master Agency</b></td>
37:      <td><b>Agency</b></td>
38:      <td><b>Agent</b></td>
39:      <td><b>Hierarchy ID</b></td>
40:    </tr>
41:    <cfoutput query="qrySecurity">
42:      <tr>
43:        <td><!-- Yakalo Administrator -->
44:        <cfif entityType is 1>
45:          #name#
46:        <cfelse>
47:          <sub>
48:            </cfif>
49:          </td>

```

```

50: <td> <!-- Portal --->
51: <cfif entityType is 2>
52:     #name#
53: <cfelse>
54:     <nbsp;
55: </cfif>
56: </td>
57: <td> <!-- Master Distributor --->
58: <cfif entityType is 3>
59:     #name#
60: <cfelse>
61:     <nbsp;
62: </cfif>
63: </td>
64: <td> <!-- Distributor --->
65: <cfif entityType is 4>
66:     #name#
67: <cfelse>
68:     <nbsp;
69: </cfif>
70: </td>
71: <td> <!-- Master Agency --->
72: <cfif entityType is 5>
73:     #name#
74: <cfelse>
75:     <nbsp;
76: </cfif>
77: </td>
78: <td> <!-- Agency --->
79: <cfif entityType is 6>
80:     #name#
81: <cfelse>
82:     <nbsp;
83: </cfif>
84: </td>
85: <td> <!-- Agent --->
86: <cfif entityType is 7>
87:     #name#
88: <cfelse>
89:     <nbsp;
90: </cfif>
91: </td>
92: <td> #hierarchyID#</td>
93: </tr>
94: <!-- #entityID# #entityType# #name# #parentID# #parentType# #hierarchyID#<br> --->
95: </cfoutput>
96: </table>
97:
98: </body>

```

[illegible]

```
1:
2: <cfquery name="qryTruncate" dataSource="#ap_dataSource#">
3:   delete from securityAccess
4: </cfquery>
5:
6:
7: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
8:   select entityType from entityTypes
9:   where entityTypes.description = 'Yakalo Administrator'
10: </cfquery>
11: <cfset nYakaloID = qryGetEntityID.entityTypeID>
12:
13: <cfquery name="qryGetYakalo" dataSource="#ap_dataSource#">
14:   select userID from security
15:   where security.userName = 'Yakalo.adm'
16: </cfquery>
17: <cfset nYakUserID = qryGetEntityID.entityTypeID>
18:
19:
20: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
21:   select entityType from entityTypes
22:   where entityTypes.description = 'Portal'
23: </cfquery>
24: <cfset nPortalID = qryGetEntityID.entityTypeID>
25:
26:
27: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
28:   select entityType from entityTypes
29:   where entityTypes.description = 'Master Distributor'
30: </cfquery>
31: <cfset nMastDistID = qryGetEntityID.entityTypeID>
32:
33: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
34:   select entityType from entityTypes
35:   where entityTypes.description = 'Distributor'
36: </cfquery>
37: <cfset nDistID = qryGetEntityID.entityTypeID>
38:
39: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
40:   select entityType from entityTypes
41:   where entityTypes.description = 'Master Agency'
42: </cfquery>
43: <cfset nMastAgency_id = qryGetEntityID.entityTypeID>
44:
45: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
46:   select entityType from entityTypes
47:   where entityTypes.description = 'Agency'
48: </cfquery>
49: <cfset nAgency_id = qryGetEntityID.entityTypeID>
```

```

50:
51: <cfquery name="qryGetEntityID" datasource="#ap_datasource#">
52:   select entityType from entityTypees
53:   where entityTypees.description = 'Agent'
54: </cfquery>
55: <cfset nagent_id = qryGetEntityID.entityType>
56:
57:
58: <!--- Make securityAccess table --->
59: <cfquery name="qryInsert" datasource="#ap_datasource#">
60:   insert into securityAccess
61:     (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
62:     values
63:     (#nYakUserID#, #nYakaloID#, 'Yakalo Solutions Administrator', 0, 0, '#nYakaloID#', 0)
64: </cfquery>
65:
66:
67: <cfquery name="qryPortal" datasource="#ap_datasource#">
68:   select portals.portalID, portals.name
69:   from portals
70: </cfquery>
71: <cfloop query="qryPortal">
72:   <cfquery name="qryInsert" datasource="#ap_datasource#">
73:     insert into securityAccess
74:       (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID, portalID)
75:       values
76:       (#qryPortal.portalID#, #nPortalID#, '#qryPortal.name#', #nYakUserID#, #nYakaloID#,
77:        '#nYakaloID#.#nPortalID#.#qryPortal.portalID#', 0, #qryPortal.portalID#)
78:   </cfquery>
79: </cfloop>
80:
81: <!--- Master Distributors
82:      Parents are portals
83: --->
84: <cfquery name="qryDist" datasource="#ap_datasource#">
85:   select distributors.distributorID, distributors.name, distributors.portalID
86:   from distributors
87:   where distributors.parentID = 0
88: </cfquery>
89:
90: <cfloop query="qryDist">
91:   <cfquery name="qryFindParent" datasource="#ap_datasource#">
92:     select * from securityAccess
93:     where securityAccess.entityID = #qryDist.portalID#
94:     and securityAccess.entityType = #nPortalID#
95:   </cfquery>
96:
97:   <cfquery name="qryInsert" datasource="#ap_datasource#">

```



```

98: insert into securityAccess
99: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
100: values
101: (#qryDist.distributorID#, #nMastDistID#, 'qryDist.name#', #qryDist.portalID#, #qryFindParent.entityType#,
102: '#qryFindParent.hierarchyID#.#nMastDistID#.#qryDist.distributorID#', #qryDist.distributorID#)
103: </cfquery>
104: </cfloop>
105:
106: <!-- Distributors
107: Parents are Master Distributors
108: -->
109:
110: <cfquery name="qryDist" datasource="#ap_dataSource#">
111: select distributors.distributorID, distributors.name, parentID from distributors
112: where distributors.parentID > 0
113: </cfquery>
114:
115: <cfloop query="qryDist">
116: <cfquery name="qryFindParent" datasource="#ap_dataSource#">
117: select * from securityAccess
118: where securityAccess.entityID = #qryDist.parentID#
119: and securityAccess.entityType = #nMastDistID#
120: </cfquery>
121:
122: <cfquery name="qryInsert" datasource="#ap_dataSource#">
123: insert into securityAccess
124: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
125: values
126: (#qryDist.distributorID#, #nDistID#, 'qryDist.name#', #qryDist.parentID#, #qryFindParent.entityType#,
127: '#qryFindParent.hierarchyID#.#nDistID#.#qryDist.distributorID#', #qryDist.distributorID#)
128: </cfquery>
129: </cfloop>
130:
131: <!-- agencies -->
132: <cfquery name="qryAgency" datasource="#ap_dataSource#">
133: select agency.agency_id, agency.name, agency.distributorID from agency
134: where agency.parentAgency = 0 and agency.distributorid > 0
135: </cfquery>
136:
137: <cfloop query="qryAgency">
138: <cfquery name="qryFindParent" datasource="#ap_dataSource#">
139: select * from securityAccess
140: where securityAccess.entityID = #qryAgency.distributorID#
141: and (securityAccess.entityType = #nMastDistID# or securityAccess.entityType=#nDistID#)
142: </cfquery>
143:
144: <cfquery name="qryInsert" datasource="#ap_dataSource#">

```

```

145: insert into securityAccess
146: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
147: values
148: (#qryAgency.agency_id#, #nMastagency_id#, '#qryAgency.name#', #qryAgency.distributorID#, #qryFindParent.entityType#,
    '#qryFindParent.hierarchyID#.#nMastagency_id#.#qryAgency.agency_id#', #qryAgency.distributorID#)
149: </cfquery>
150: </cfloop>
151:
152:
153: <cfquery name="qryAgency" datasource="#ap_datasource#">
154: select agency.agency_id, agency.name, agency.distributorID, agency.parentAgency
155: from agency
156: where agency.parentAgency > 0 and distributorID > 0
157: </cfquery>
158:
159: <cfloop query="qryAgency">
160: <cfquery name="qryFindParent" datasource="#ap_datasource#">
161: select * from securityAccess
162: where securityAccess.entityID = #qryAgency.parentAgency#
163: and securityAccess.entityType = #nMastagency_id#
164: </cfquery>
165:
166: <cfquery name="qryInsert" datasource="#ap_datasource#">
167: insert into securityAccess
168: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
169: values
170: (#qryAgency.agency_id#, #nagency_id#, '#qryAgency.name#', #qryAgency.parentAgency#, #qryFindParent.entityType#,
    '#qryFindParent.hierarchyID#.#nagency_id#.#qryAgency.agency_id#', #qryAgency.distributorID#)
171: </cfquery>
172: </cfloop>
173:
174: <cfquery name="qryAgency" datasource="#ap_datasource#">
175: select agency.agency_id, agency.name, agency.distributorID, agency.parentAgency
176: from agency
177: where agency.parentAgency = 0 and agency.distributorID = 0
178: </cfquery>
179:
180: <cfloop query="qryAgency">
181: <cfquery name="qryFindParent" datasource="#ap_datasource#">
182: select * from securityAccess
183: where securityAccess.entityID = #nYakUserID#
184: and securityAccess.entityType = #nYakaloid#
185: </cfquery>
186:
187: <cfquery name="qryInsert" datasource="#ap_datasource#">
188: insert into securityAccess
189: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
190: values
191: (#qryAgency.agency_id#, #nagency_id#, '#qryAgency.name#', #qryFindParent.entityID#, #nYakaloid#,

```

```

192: '#qryFindParent.hierarchyID#.#nagency_id#.#qryAgency.agent_id#', #qryAgency.distributorID#)
193: </cfquery>
194: </cfloop>
195:
196: <cfquery name="qryAgency" datasource="#ap_datasource#">
197: select agency.agent_id, agency.name, agency.distributorID, agency.parentAgency
198: from agency
199: where agency.parentAgency > 0 and agency.distributorID = 0
200: </cfquery>
201:
202: <cfloop query="qryAgency">
203: <cfquery name="qryFindParent" datasource="#ap_datasource#">
204: select * from securityAccess
205: where securityAccess.entityID = #qryAgency.parentAgency#
206: and securityAccess.entityType = #nMastagency_id#
207: </cfquery>
208:
209: <cfquery name="qryInsert" datasource="#ap_datasource#">
210: insert into securityAccess
211: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
212: values
213: (#qryAgency.agent_id#, #nagency_id#, '#qryAgency.name#', #qryAgency.parentAgency#, #qryFindParent.entityType#,
'#qryFindParent.hierarchyID#.#nagency_id#.#qryAgency.agent_id#', #qryAgency.distributorID#)
214: </cfquery>
215: </cfloop>
216:
217: <!-- Agents -->
218: <cfquery name="qryAgents" datasource="#ap_datasource#">
219: select agents.agent_id, agents.firstname + ' ' + agents.lastname as name, agents.agent_id, agents.distributorID
220: from agents
221: where agent_id > 0
222: </cfquery>
223:
224: <cfloop query="qryAgents">
225: <cfquery name="qryFindParent" datasource="#ap_datasource#">
226: select * from securityAccess
227: where securityAccess.entityID = #qryAgents.agent_id#
228: and (securityAccess.entityType = #nMastagency_id# or securityAccess.entityType=#nagency_id#)
229: </cfquery>
230:
231: <cfif qryFindParent.recordCount gt 0>
232: <cfquery name="qryInsert" datasource="#ap_datasource#">
233: insert into securityAccess
234: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
235: values
236: (#qryAgents.agent_id#, #nagent_id#, '#qryAgents.name#', #qryAgents.agent_id#, #qryFindParent.entityType#,
'#qryFindParent.hierarchyID#.#nagent_id#.#qryAgents.agent_id#', #qryAgents.distributorID#)
237:

```

```

238:      </cfquery>
239:    <cfelse>
240:      <cfquery name="qryFindParent" dataSource="#ap_dataSource#">
241:        select * from securityAccess
242:        where securityAccess.entityID = #nYakUserID#
243:        and securityAccess.entityType = #nYakaloID#
244:      </cfquery>
245:
246:      <cfquery name="qryInsert" dataSource="#ap_dataSource#">
247:        insert into securityAccess
248:        (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
249:        values
250:        (#qryAgents.agent_id#, #nagent_id#, 'qryAgents.name#', #qryFindParent.entityID#, #nYakaloID#,
251:        '#qryFindParent.hierarchyID#.#nagent_id#.#qryAgents.agent_id#', #qryAgents.distributorID#)
252:      </cfquery>
253:    </cfif>
254:  </cfloop>
255:
256:  <cfquery name="qryAgents" dataSource="#ap_dataSource#">
257:    select agents.agent_id, agents.firstname + ' ' + agents.lastname as name, agents.agency_id, agents.distributorID
258:    from agents
259:    where agents.agency_id = 0
260:    and agents.distributorID > 0
261:  </cfquery>
262:
263:  <cfloop query="qryAgents">
264:    <cfquery name="qryFindParent" dataSource="#ap_dataSource#">
265:      select * from securityAccess
266:      where securityAccess.entityID = #qryAgents.distributorid#
267:      and (securityAccess.entityType = #nMastDistID# or securityAccess.entityType=#nDistID#)
268:    </cfquery>
269:
270:    <cfquery name="qryInsert" dataSource="#ap_dataSource#">
271:      insert into securityAccess
272:      (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
273:      values
274:      (#qryAgents.agent_id#, #nagent_id#, 'qryAgents.name#', #qryAgents.distributorID#, #qryFindParent.entityType#,
275:      '#qryFindParent.hierarchyID#.#nagent_id#.#qryAgents.agent_id#', #qryAgents.distributorID#)
276:    </cfquery>
277:  </cfloop>

```

```
1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <html>
4:  <head>
5:    <cfoutput>
6:    <title>Page Not Found</title>
7:    </cfoutput>
8:    <link rel="stylesheet" href="style1.css" type="text/css">
9:  </head>
10:
11:
12:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
13:  <cfinclude template="include\nocache.cfm">
14:  <p><cfinclude template="include\header.cfm"></p>
15:
16:  <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
17:    <tr bgcolor="#cccc99">
18:      <td align="left">
19:        <span class="h2"><b>Page Not Found</b></span>
20:      </td>
21:      <td align="right">
22:        <cfoutput></cfoutput>
23:      </td>
24:    </tr>
25:    <tr>
26:      <td colspan="2">
27:        The page you are trying to find was not found.<br>
28:        Your page request has been forwarded to an administrator for correction.<br>
29:        <br>
30:        We apologize for the inconvenience.
31:      </td>
32:    </tr>
33:  </table>
34: </body>
35: </html>
36:
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfset client.userID = -1>
4:  <cfset client.userName = "">
5:  <cfset client.entityID = -1>
6:  <cfset client.entityType = -1>
7:  <cfset client.currentEntityID = -1>
8:  <cfset client.currentEntityType = -1>
9:  <cfset client.distributorID = -1>
10: <cfset client.backofficeName = "">
11:
12: <cfinclude template="include\javaValidate.cfm">
13:
14: <script language="JavaScript">
15:   <!--
16:   function validate(testform) {
17:     var results = "";
18:     var lResult = true;
19:
20:     if ((removeSpaces(testform.edtEmail.value) == "") || (!isValidEmail(testform.edtEmail.value))) {
21:       results = results + "Please enter your email address.\n";
22:       lResult = false;
23:     }
24:
25:     if (!lResult) {
26:       window.alert(results);
27:     }
28:     return lResult;
29:   }
30:   <!--
31: </script>
32:
33:
34:
35: <html>
36: <head>
37:   <title>Back Office Administration Forgot Password</title>
38:   <link rel="stylesheet" href="style1.css" type="text/css">
39: </head>
40:
41: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
42: <cfinclude template="include\nocache.cfm">
43:
44: <cfoutput>
45: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
46:   <tr>
47:     <td colspan="2" class="h2"><b>Yakalo Back Office Forgot Password</b></span></td>
48:     <td align="right"></td>
49:   </tr>

```

```

50: <tr><td colspan="2"><b>sp</b></td></tr>
51: <tr bgcolor="#ffffff">
52:   <td colspan="2">
53:     <form action="sendPass.cfm" method="post" onSubmit="return validate(this)">
54:     <table border="0" width="700" align="center">
55:       <tr><td colspan="2" bgcolor="#ffffff" align="center">
56:         <b class="bighead">Welcome to the Yakalo Back Office Administrator!</b></td></tr>
57:       <tr>
58:         <td colspan="2">
59:           <cfif client.userName is not "">
60:             <p><font color="red">#client.userName#</font></p>
61:           </cfif>
62:           Please enter your email address below. The hint you entered when your login was created will
63:           be emailed to you.
64:           <table border="0">
65:             <tr>
66:               <td><b>Email Address:</b></td></tr>
67:               <td><input type="text" name="edtEmail" size="50" maxlength="128"></td>
68:             </tr>
69:             </table></p>
70:             <input type="submit" name="btnSend" value="Send">
71:             <input type="button" name="btnCancel" value="Cancel" onclick="location.href='login.cfm'">
72:           </td>
73:         </tr>
74:       </table>
75:       </form>
76:     </td>
77:   </tr>
78: </table>
79: </cfoutput>
80:
81: </body>
82: </html>

```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfset client.gotoPage = "formatAdm.cfm">
4:
5:  <cfif client.currentEntityType lt #ap_securityMastDist# and client.lookupDistID is -1>
6:    <!-- We do not know what distributor we should be editing, so find out. -->
7:    <cfset client.lookupDistID = -1>
8:    <cfset client.lookupAgencyID = -1>
9:    <cfset client.lookupID = -1>
10:   <cfset client.DetailID = -1>
11:   <cflocation url="distSelect.cfm" addToken="no">
12: </cfif>
13:
14:
15: <cfif client.currentEntityType lt #ap_securityMastDist#>
16:   <cfquery name="qryDist" dataSource="#ap_dataSource#">
17:     select distributors.name as distName
18:     from distributors
19:     where distributors.distributorID = #client.lookupDistID#
20:   </cfquery>
21:   <cfset cDistName = qryDist.distName>
22:   <cfelseif client.currentEntityType gte #ap_securityMastDist#>
23:     <cfset client.lookupDistID = client.currentDistributorID>
24:     <cfset cDistName = "">
25:   </cfif>
26:
27:   <cfif not isdefined("client.lookupDistID") or client.lookupDistID is "-1">
28:     <cflocation url="distAdm.cfm" addToken="no">
29:   </cfif>
30:
31:   <cfparam name="URL.sortBy" default="description">
32:   <cfset client.lookupID = -1>
33:   <cfset client.detailID = -1>
34:
35:   <!-- Display rows -->
36:   <cfparam name="nStartFrom" default="1">
37:   <cfparam name="ntoDisplay" default="#client.displayRows#">
38:   <cfparam name="nEnd" default="#client.displayRows#">
39:
40:
41:   <cfquery name="qryEditList" dataSource="#ap_dataSource#">
42:     select pageFormats.pageFormatID, pageFormats.description
43:     from pageFormats
44:     where pageFormats.distributorID = #client.lookupDistID#
45:     order by #url.sortBy#
46:   </cfquery>
47:
48:   <html>
49:   <head>

```





331

```
147: </cfif>
148: <cfif nNextStart lte gryEditList.recordCount>
149:   <td>
150:     <form action="formatAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
151:       <input type="hidden" name="nStartFrom" value="#nNextStart#">
152:       <input type="hidden" name="nToDisplay" value="#nToDisplay#">
153:       <input type="hidden" name="nEnd" value="#nNextEnd#">
154:       <cfset nLeftToShow = min(nToDisplay, (gryEditList.recordcount - cToDisplay))>
155:       <input type="submit" value="Next #nLeftToShow#">
156:     </form>
157:   </td>
158: </cfif>
159: </tr>
160: </table>
161: </cfif>
162: </body>
163: </html>
164:
165:
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <html>
4: <head>
5: <title>Page Format Choice</title>
6: </head>
7:
8: <body>
9:
10: <cfloop collection="#form#" item="cName">
11: <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
12: <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
13: <cfset client.lookupID = val(cValue)>
14: <cfset client.detailID = -1>
15: <cfset client.userName = "">
16: <cflocation url="formatMaint.cfm" addToken="no">
17: </cfif>
18: </cfloop>
19:
20: <cfset client.lookupID = -1>
21: <cfset client.detailID = -1>
22: <cfset client.userName = "">
23: <cflocation url="formatAdm.cfm" addToken="no">
24:
25: </body>
26: </html>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfif client.currentEntityType lt #ap_securityMastDist#>
4:   <cfquery name="qryDist" datasource="#ap_dataSource#">
5:     select distributors.name as distName
6:     from distributors
7:     where distributors.distributorID = #client.lookupDistID#
8:   </cfquery>
9:   <cfset cDistName = qryDist.distName>
10:  <cfelseif client.currentEntityType gte #ap_securityMastDist#>
11:    <cfset client.lookupDistID = client.currentDistributorID>
12:    <cfset cDistName = "">
13:  </cfif>
14:
15:  <!-- Get JD number from edit -->
16:  <cfloop collection="#form#" item="cName">
17:    <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".",X", #cName#,1) gt 0>
18:      <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
19:      <cfset client.lookupID = val(cValue)>
20:      <cfset client.detailID = -1>
21:    </cfif>
22:  </cfloop>
23:
24:
25:  <cfif not isDefined("client.lookupID")>
26:    <cflocation url="formatAdm.cfm" addToken="no">
27:  </cfif>
28:
29:  <cfparam name="client.userMessage" default="">
30:  <cfparam name="url.displayPage" default="formatInfo">
31:
32:  <cfquery name="qryFindPage" datasource="#ap_dataSource#">
33:    select pageFormats.*
34:    from pageFormats
35:    where pageFormats.pageFormatID = #client.lookupID#
36:  </cfquery>
37:
38:  <cfif qryFindPage.recordCount gt 0>
39:    <cfset nPageFormatID = qryFindPage.pageFormatID>
40:    <cfset nDistributorID = qryFindPage.distributorID>
41:  <cfelse>
42:    <cfset nPageFormatID = -1>
43:    <cfif client.currentEntityType gte #ap_securityMastDist#>
44:      <cfset nDistributorID = client.currentDistributorID>
45:    <cfelseif client.lookupDistID is not -1>
46:      <cfset nDistributorID = client.lookupDistID>
47:    <cfelse>
48:      <cflocation url="formatAdm.cfm" addToken="no">
49:    </cfif>

```

```
50: </cfif>
51:
52: <html>
53: <head>
54:   <cfoutput>
55:     <title>#client.backofficeName# Backoffice Agent Maintenance</title>
56:   </cfoutput>
57:   <link rel="stylesheet" href="style1.css" type="text/css">
58: </head>
59:
60: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
61:   <cfinclude template="include\nocache.cfm">
62:
63:   <p><cfinclude template="include\header.cfm"></p>
64:
65:   <cfoutput>
66:
67:   <cfset url.displayPage = ucase(url.displayPage)>
68:
69:   <cfif url.displayPage is "FORMATINFO">
70:     <cfinclude template="include\formatInfo.cfm">
71:   <cfelseif url.displayPage is "FORMATSCHEME">
72:     <cfinclude template="include\formatScheme.cfm">
73:   </cfif>
74:
75:   </cfoutput>
76:
77: </body>
78: </html>
79:
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfif not isDefined("form.pageFormatID")>
4:    <cfset client.lookupID = -1>
5:    <cfset client.detailID = -1>
6:    <cfset client.userName = "">
7:    <cflocation url="formatAdm.cfm" addtoken="no">
8:  </cfif>
9:
10:  <cfquery name="qryFindPage" datasource="#ap_dataSource#">
11:    select pageFormatID, description
12:    from pageFormats
13:    where pageFormats.pageFormatID = #form.pageFormatID#
14:  </cfquery>
15:
16:  <cfinclude template="include\clearOldFields.cfm">
17:  <cfset client.userName = "">
18:
19:  <cfparam name="form.edtPages" default="">
20:
21:  <!-- Save form values in case something is wrong -->
22:
23:  <cfif isDefined("form.btnUpdate")>
24:    <cfif qryFindPage.recordCount is 0>
25:      <cfset client.lookupID = -1>
26:      <cfset client.detailID = -1>
27:      <cfset client.userName = "There was an error while creating the page format.">
28:      <cftransaction>
29:        <cfset cDesc = preservesingleQuotes(form.edtDesc)>
30:        <cfset cHeader = preservesingleQuotes(form.edtHeader)>
31:        <cfset cSide = preservesingleQuotes(form.edtSide)>
32:        <cfset cFooter = preservesingleQuotes(form.edtFooter)>
33:
34:        <cfquery name="qryInsert" datasource="#ap_dataSource#">
35:          insert into pageFormats
36:            (distributorID, description,
37:             headerCode, sideCode, footerCode)
38:          values
39:            (#form.distributorID#, '#cDesc',
40:             '#cHeader', '#cSide', '#cFooter#')
41:        </cfquery>
42:
43:        <cfquery name="qryDelete" datasource="#ap_dataSource#">
44:          delete from formatAssignment
45:          where formatAssignment.pageFormatID = #form.pageFormatID#
46:        </cfquery>
47:        <cfloop list="#form.edtPages#" index="cValue" delimiters=",">
48:          <cfset nEntityType = listGetAt(cValue,1,"|")>
49:          <cfset nEntityID = listGetAt(cValue,2,"|")>

```

```

50: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
51:   insert into formatAssignment
52:     (pageFormatID, distributorID, entityType, entityID)
53:     values
54:     (#form.pageFormatID#, #form.distributorID#, #nEntityType#, #nEntityID#)
55: </cfquery>
56: </cfloop>
57:
58:
59: <cfset client.userMessage = "" & form.edtDesc & " added.">
60: </cftransaction>
61:
62: <cflocation url="formatAdm.cfm" addToken="no">
63: <cfelse>
64: <!---
65: <cfset client.lookupID = -1>
66: <cfset client.detailID = -1>
67: --->
68: <cfset client.userMessage = "There was an error while updating the page format information.">
69: </cftransaction>
70: <cfset cDesc = preservesingleQuotes(form.edtDesc)>
71: <cfset cHeader = preservesingleQuotes(form.edtHeader)>
72: <cfset cSide = preservesingleQuotes(form.edtSide)>
73: <cfset cFooter = preservesingleQuotes(form.edtFooter)>
74:
75: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
76:   update pageFormats
77:   set distributorID = #form.distributorID#,
78:     description = '#cDesc#',
79:     headerCode = '#cHeader#',
80:     sideCode = '#cSide#',
81:     footerCode = '#cFooter#'
82:   where pageFormats.pageFormatID = #form.pageFormatID#
83: </cfquery>
84:
85: <cfquery name="qryDelete" dataSource="#ap_dataSource#">
86:   delete from formatAssignment
87:   where formatAssignment.pageFormatID = #form.pageFormatID#
88: </cfquery>
89: <cfloop list="#form.edtPages#" index="cValue" delimiters=", ">
90:   <cfset nEntityType = listGetAt(cValue,1,"|")>
91:   <cfset nEntityID = listGetAt(cValue,2,"|")>
92:   <cfquery name="qryInsert" dataSource="#ap_dataSource#">
93:     insert into formatAssignment
94:       (pageFormatID, distributorID, entityType, entityID)
95:       values
96:       (#form.pageFormatID#, #form.distributorID#, #nEntityType#, #nEntityID#)
97:   </cfquery>
98: </cfloop>

```



```

99:
100:
101:     <cfset client.userName = "" & form.edtDesc & "" updated.">
102:     </cftransaction>
103:     <cflocation url="formatMaint.cfm" addToken="no">
104:     </cfif>
105:     <cfelseif isDefined("form.btnUpdateScheme")>
106:         <cfset client.userName = "There was an error while updating the page format information.">
107:         </cftransaction>
108:     <cfset cNavBGColor = preserveSingleQuotes(form.edtNavBGColor)>
109:     <cfset cNavTextColor = preserveSingleQuotes(form.edtNavTextColor)>
110:     <cfset cMenuBGColor = preserveSingleQuotes(form.edtMenuBGColor)>
111:     <cfset cMenuTextColor = preserveSingleQuotes(form.edtMenuTextColor)>
112:     <cfset cHeaderBGColor = preserveSingleQuotes(form.edtHeaderBGColor)>
113:     <cfset cFooterBGColor = preserveSingleQuotes(form.edtFooterBGColor)>
114:     <cfset cAdBGColor = preserveSingleQuotes(form.edtAdBGColor)>
115:     <cfset cSearchBGColor = preserveSingleQuotes(form.edtSearchBGColor)>
116:
117:     <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
118:         update pageFormats
119:         set navBGColor = 'cNavBGColor',
120:             navTextColor = 'cNavTextColor',
121:             menuBGColor = 'cMenuBGColor',
122:             menuTextColor = 'cMenuTextColor',
123:             headerBGColor = 'cHeaderBGColor',
124:             footerBGColor = 'cFooterBGColor',
125:             adBGColor = 'cAdBGColor',
126:             searchBGColor = 'cSearchBGColor',
127:             templateID = #form.templateID#
128:         where pageFormats.pageFormatID = #form.pageFormatID#
129:     </cfquery>
130:
131:     <cfinclude template="include\makeStyle.cfm">
132:
133:     <cfset client.userName = "Color scheme updated.">
134:     </cftransaction>
135:
136:     <cflocation url="formatMaint.cfm?displayPage=formatScheme" addToken="no">
137:
138:     <cfelseif isDefined("form.btnDelete")>
139:     <cfset client.lookupID = -1>
140:     <cfset client.detailID = -1>
141:     <cfset client.userName = "Unable to delete #form.edtDesc#.">
142:     </cftransaction>
143:     <cfquery name="qryDelete" dataSource="#ap_dataSource#">
144:         delete from formatAssignment
145:         where formatAssignment.pageFormatID = #form.pageFormatID#
146:     </cfquery>
147:

```

```
148:      <cfquery name="qryDelete" datasource="#ap_datasource#">
149:        delete from pageFormats
150:        where pageFormats.pageFormatID = #form.pageFormatID#
151:      </cfquery>
152:
153:      <cfset client.userName = "" & form.edtDesc & " deleted.">
154:      </cftransaction>
155:      <cflocation url="formatAdm.cfm" addtoken="no">
156:      </cfif>
157:
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfset client.gotoPage = "forwardAdm.cfm">
4:  <!--
5:  <cfinclude template="include\securityTest.cfm">
6:  -->
7:
8:  <cfparam name="URL.sortBy" default="name">
9:  <cfset client.lookupID = -1>
10:  <cfset client.detailID = -1>
11:
12:  <!-- Display rows -->
13:  <cfparam name="nStartFrom" default="1">
14:  <cfparam name="ntoDisplay" default="#client.displayRows#">
15:  <cfparam name="nEnd" default="#client.displayRows#">
16:
17:  <cfquery name="qryEditList" dataSource="#ap_dataSource#">
18:    select *
19:    from forwarding
20:    where forwarding.propertyID = -1
21:  </cfquery>
22:  <!--
23:  <cfquery name="qryEditList" dataSource="#ap_dataSource#">
24:    select portals.portalID, portals.name, portals.dataPath
25:    from portals
26:  </cfquery>
27:  -->
28:
29:  <html>
30:  <head>
31:    <cfoutput>
32:    <title>#client.backofficeName# Backoffice Forwarding</title>
33:    </cfoutput>
34:    <link rel="stylesheet" href="style1.css" type="text/css">
35:  </head>
36:
37:
38:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
39:  <cfinclude template="include\nocache.cfm">
40:  <p><cfinclude template="include\header.cfm"></p>
41:
42:  <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
43:    <tr bgcolor="#cccc99">
44:      <td colspan="4">
45:        <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">
46:          <tr>
47:            <td align="left">
48:              <span class="h2"><b>Forwarding Administration</b></span>
49:            </td>

```

```

50: <td align="right">
51: <cfif #nToDisplay# gte qryEditList.recordCount>
52: <cfset cToDisplay = min(qryEditList.recordCount, #nToDisplay#)>
53: </cfif>
54: <cfif qryEditList.recordCount gte #nToDisplay#>
55: <cfset cToDisplay = min(qryEditList.recordCount, #nEnd#)>
56: </cfif>
57: <cfset cStartFrom = min(qryEditList.recordCount, #nStartFrom#)>
58: <cfoutput>(Viewing records #cstartFrom# to #cToDisplay# out of #qryEditList.recordCount#)</cfoutput>
59: </td>
60: </tr>
61: </table>
62: </td>
63: </tr>
64: <tr bgcolor="#cccccc"><td><b><nbsp;</td></tr>
65: <tr bgcolor="#cccccc">
66: <td align="center">
67: <i><b>This function is not yet available.</b></i>
68: </td>
69: </tr>
70: <tr bgcolor="#cccccc"><td><b><nbsp;</td></tr>
71: </table></p>
72:
73: <CFSET nPrevStart = nStartFrom-nToDisplay>
74: <CFSET nNextStart = nStartFrom+nToDisplay>
75: <CFSET nPrevEnd = #nPrevStart#+nToDisplay-1>
76: <CFSET nNextEnd = #nNextStart#+nToDisplay-1>
77: <cfif nPrevStart gte 1 or nNextStart lte qryEditList.recordCount>
78: <table border="0" align="center">
79: <tr>
80: <cfif nPrevStart gte 1>
81: <td>
82: <form action="portalAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
83: <input type="hidden" name="nStartFrom" value="#nPrevStart#">
84: <input type="hidden" name="nToDisplay" value="#nToDisplay#">
85: <input type="hidden" name="nEnd" value="#nPrevEnd#">
86: <input type="submit" value="Previous #nToDisplay#">
87: </FORM>
88: </td>
89: </cfif>
90: <cfif nNextStart lte qryEditList.recordCount>
91: <td>
92: <form action="portalAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
93: <input type="hidden" name="nStartFrom" value="#nNextStart#">
94: <input type="hidden" name="nToDisplay" value="#nToDisplay#">
95: <input type="hidden" name="nEnd" value="#nNextEnd#">
96: <cfset nLeftToShow = min(nToDisplay, (qryEditList.recordcount - cToDisplay))>
97: <input type="submit" value="Next #nLeftToShow#">
98: </form>

```

```
99:      </td>
100:      </cfif>
101:      </tr>
102:      </table>
103:      </cfif>
104:
105:      </body>
106:      </html>
107:
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2: <cfset client.gotoPage = "homePageAdm.cfm">
3:
4: <cfif client.currentEntityType lt #ap_securityMastDist# and client.lookupDistID is -1>
5:   <!-- We do not know what distributor we should be editing, so find out -->
6:   <cfset client.lookupDistID = -1>
7:   <cfset client.lookupAgencyID = -1>
8:   <cfset client.lookupID = -1>
9:   <cfset client.DetailID = -1>
10:  <cflocation url="distSelect.cfm" addToken="no">
11: </cfif>
12:
13: <cfif client.currentEntityType gte #ap_securityMastDist#>
14:  <cfset client.lookupDistID = client.CurrentDistributorID>
15:  <cfelseif client.lookupDistID is -1>
16:    <cflocation url="messages.cfm" addToken="no">
17:  </cfif>
18:
19:  <cfset client.lookupID = -1>
20:  <cfset client.detailID = -1>
21:  <cfset client.imageType = -1>
22:  <cfset client.lookupAgencyID = -1>
23:
24:  <cflocation url="homePageMaint.cfm" addToken="no">
25:
26:  <html>
27:  <head>
28:    <cfoutput>
29:    <title>#client.backofficeName# Backoffice Home Page Administration</title>
30:    </cfoutput>
31:    <link rel="stylesheet" href="style1.css" type="text/css">
32:  </head>
33:
34:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
35:  <cfinclude template="include\nocache.cfm">
36:
37:
38: </body>
39: </html>
40:

```

1  
7  
1

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfif client.currentEntityType gte #ap_securityMastDist#>
4:    <cfset client.lookupDistID = client.currentEntityID>
5:  </cfif>
6:
7:  <cfif not isDefined("client.lookupDistID") or client.lookupDistID is "-1">
8:    <cflocation url="messages.cfm" addToken="no">
9:  </cfif>
10:  <cfparam name="client.userName" default="">
11:  <cfparam name="client.imageType" default="-1">
12:
13:  <cfquery name="qryFindPage" datasource="#ap_dataSource#">
14:    select homePages.*
15:    from homePages
16:    where homePages.distributorID = #client.lookupDistID#
17:  </cfquery>
18:
19:  <cfquery name="qryFindDist" datasource="#ap_dataSource#">
20:    select distributors.distributorID, distributors.name
21:    from distributors
22:    where distributors.distributorID = #client.lookupDistID#
23:  </cfquery>
24:
25:  <cfif qryFindDist.recordCount gt 0>
26:    <cfset nDistributorID = qryFindDist.distributorID>
27:  <cfelse>
28:    <cfset client.lookupID = -1>
29:    <cfset client.detailID = -1>
30:    <cfset client.userName = "">
31:    <cflocation url="messages.cfm" addToken="no">
32:  </cfif>
33:
34:  <cfinclude template="include/javaValidate.cfm">
35:
36:  <script language="JavaScript">
37:    <!--
38:    function validate(testform) {
39:      var results = "";
40:      var lResult = true;
41:
42:      if (!Result) {
43:        window.alert(results);
44:      }
45:      return lResult;
46:    }
47:    -->
48:  </script>
49:

```



```

50: <html>
51: <head>
52:   <cfoutput>
53:     <title>#client.backofficeName# Backoffice Home Page Maintenance</title>
54:   </cfoutput>
55:   <link rel="stylesheet" href="style1.css" type="text/css">
56: </head>
57:
58: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
59: <cfinclude template="include\nocache.cfm">
60:
61: <p><cfinclude template="include\header.cfm"></p>
62:
63: <cfoutput>
64:
65:   <form action="homePageUpdate.cfm" method="post" enctype="multipart/form-data" onsubmit="return validate(this)">
66:     <input type="hidden" name="distributorID" value="#nDistributorID#">
67:     <input type="hidden" name="originalHeaderImage" value="#qryFindPage.userHeaderImage#">
68:     <input type="hidden" name="originalUserHeader" value="#qryFindPage.userHeaderImage#">
69:     <input type="hidden" name="originalFooterImage" value="#qryFindPage.footerImage#">
70:     <input type="hidden" name="originalUserFooter" value="#qryFindPage.userFooterImage#">
71:     <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
72:       <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Home Page Maintenance for #qryFindDist.name#</b></span>
73:         <cfif client.lookupDistID is -1>
74:           <b>#bsp; (Create a new home page)
75:         </cfif>
76:       </td></tr>
77:
78:       <CFIF client.userMessage is not "">
79:         <tr bgcolor="eeeeee">
80:           <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td></tr>
81:         </tr>
82:       <tr bgcolor="eeeeee"><td colspan="5"><b>#bsp; </td></tr>
83:     </CFIF>
84:     <cfset client.userMessage = "">
85:
86:     <tr bgcolor="##eeeeee">
87:       <td width="15%">Header: Image:</td>
88:       <td colspan="4">
89:         <input type="file" name="edtHeaderImage" size="30">
90:         <cfif trim(qryFindPage.headerImage) is not "">
91:           <i><b>#bsp; Currently: #qryFindPage.userHeaderImage#</i>
92:         </cfif>
93:       </td>
94:     </tr>
95:     <tr bgcolor="##eeeeee">
96:       <td width="15%">Footer: Image:</td>
97:       <td colspan="4">
98:         <input type="file" name="edtFooterImage" size="30">

```

```

99:      <cfif trim(qryFindPage.footerImage) is not "">
100:        <i> tnbsp;Currently: #qryFindPage.footerImage#</i>
101:      </cfif>
102:    </td>
103:  </tr>
104:  <tr bgcolor="#eeeeee">
105:    <td width="15%">Active:</td>
106:    <td colspan="4">
107:      <input type="checkbox" name="edtActive"><cfif qryFindPage.active is "Y"> checked</cfif>>
108:    </td>
109:  </tr>
110:
111:  <tr bgcolor="eeeeee">
112:    <cfif qryFindPage.recordCount is 0>
113:      <td colspan="5">
114:        <input type="submit" name="btnUpdate" value="Add Home Page">
115:        <input type="reset" value="Reset Info">
116:      </td>
117:    <cfelse>
118:      <td colspan="4">
119:        <input type="submit" name="btnUpdate" value="Update Home Page">
120:        <input type="reset" value="Reset Info">
121:        <input type="submit" name="btnView" value="View Home Page">
122:        <input type="submit" name="btnGenerate" value="Generate Home Page">
123:      </td>
124:      <td align="right" width="20%">
125:        <input type="submit" name="btnDelete" value="Delete Home Page">
126:      </td>
127:    </cfif>
128:  </tr>
129:  </table>
130: </form>
131: </cfoutput>
132:
133: <!-- If this community page has already been created, allow paragraph editing -->
134:
135: <cfif qryFindPage.recordCount gt 0>
136:   <script language="JavaScript">
137:     <!--
138:     function validateDetail(testform) {
139:       var results = "";
140:       var lResult = true;
141:
142:       if ((removeSpaces(testform.edtSortOrder.value) != "") && (!isNumber(testform.edtSortOrder.value))) {
143:         results = results + " * " + testform.edtSortOrder.value + " is not a valid numeric sort order value.\n";
144:         lResult = false;
145:       }
146:
147:       if (!lResult) {

```

```

148:         window.alert(results);
149:     }
150:
151:     return lResult;
152: }
153: -->
154: </script>
155:
156: <cfquery name="qryDetail" dataSource="#ap_dataSource#">
157:     select homePageDetail.*, imageTypes.description as imageName
158:     from homePageDetail
159:     left outer join imageTypes on imageTypes.imageType = homePageDetail.imageType
160:     where homePageDetail.distributorID = #client.lookupDistID#
161:     order by homePageDetail.sortOrder
162: </cfquery>
163:
164: <cfquery name="qryEdit" dataSource="#ap_dataSource#">
165:     select homePageDetail.*,
166:     imageTypes.isFormField, imageTypes.isApplet, imageTypes.isURL
167:     from homePageDetail
168:     left outer join imageTypes on imageTypes.imageType = homePageDetail.imageType
169:     where homePageDetail.distributorID = #client.lookupDistID#
170:     and homePageDetail.homePageDetailID = #client.detailID#
171: </cfquery>
172: <cfquery name="qryImageTypes" dataSource="#ap_dataSource#">
173:     select imageType, description, isFormField, isApplet, isURL
174:     from imageTypes
175:     order by description
176: </cfquery>
177:
178: <!-- Set default values -->
179: <cfif qryEdit.recordCount is 0> <!-- New record -->
180:     <cfif isDefined("client.old_sortOrder")>
181:         <cfset nSortOrder = client.old_sortOrder>
182:     <cfelse>
183:         <cfset nSortOrder = "1">
184:     </cfif>
185:
186:     <cfquery name="qryDefault" dataSource="#ap_dataSource#">
187:         select imageType from imageTypes
188:         where imageTypes.description = 'Standard Photo'
189:     </cfquery>
190:     <cfif client.imageType gt -1>
191:         <cfset nImageType = client.imageType>
192:     <cfelseif qryDefault.recordCount gt 0>
193:         <cfset nImageType = qryDefault.imageType>
194:     <cfelse>
195:         <cfset nImageType = 0>
196:     </cfif>

```

```

197:
198:
199:
200:
201:
202:
203:
204:
205:
206:
207:
208:
209:
210:
211:
212:
213:
214:
215:
216:
217:
218:
219:
220:
221:
222:
223:
224:
225:
226:
227:
228:
229:
230:
231:
232:
233:
234:
235:
236:
237:
238:
239:
240:
241:
242:
243:
244:
245:
<cfelse> <!-- Existing record -->
<cfif isDefined("client.old_sortOrder")>
  <cfset nSortOrder = client.old_sortOrder>
<cfelse>
  <cfset nSortOrder = qryEdit.sortOrder>
</cfif>

<cfif client.imageType gt -1>
  <cfset nImageType = client.imageType>
<cfelse>
  <cfset nImageType = qryEdit.imageType>
</cfif>

</cfif>
<cfif isDefined("client.old_title")>
  <cfset cTitle = client.old_title>
<cfelse>
  <cfset cTitle = trim(qryEdit.title)>
</cfif>
<cfif isDefined("client.old_alignment")>
  <cfset cAlignment = client.old_alignment>
<cfelse>
  <cfset cAlignment = trim(qryEdit.alignment)>
</cfif>
<cfif isDefined("client.old_desc")>
  <cfset cDesc = client.old_desc>
<cfelse>
  <cfset cDesc = trim(qryEdit.text)>
</cfif>

<cfquery name="qryImageInfo" dataSource="#ap_dataSource#">
  select formTitle, isFormField, isApplet, isURL
  from imageTypes
  where imageTypes.imageType = #nImageType#
</cfquery>

<form action="homePageUpdate.cfm" method="post" enctype="multipart/form-data" onSubmit="return validateDetail(this)">
  <cfoutput>
    <input type="hidden" name="distributorID" value="#client.lookupDistID#">
    <input type="hidden" name="homePageDetailID" value="#client.detailID#">
    <input type="hidden" name="originalImage" value="#qryEdit.image#">
    <input type="hidden" name="originalUserImage" value="#qryEdit.userName#">
  </cfoutput>

  <cfif qryDetail.recordCount is 0>
    <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
      <tr><td colspan="6"><i><b>There are no paragraphs defined.</b></i></td></tr>
      <tr><td colspan="6"><b><nbsp;</b></td></tr>
    </table>
  </cfif>

```

```

246: <cfelse>
247: <table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
248: <tr valign="top" bgcolor="#cccccc">
249: <td><b>Image Type</b></td>
250: <td><b>Title</b></td>
251: <td><b>Text</b></td>
252: <td><b>Image Name</b></td>
253: <td><b>Alignment</b></td>
254: <td><b>Order</b></td>
255: <td><b>Edit</b></td>
256: </tr>
257: <cfoutput query="qryDetail">
258: <tr valign="top" bgcolor="#cccccc"><cfif qryDetail.homePageDetailID is client.detailID>#ffffcc<cfelse>#eeeeee</cfif><td>
259: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
260: <cfif trim(qryDetail.title) is ""><b>Title</b></td>
261: <cfif trim(qryDetail.text) is ""><b>Text</b></td>
262: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
263: <cfif trim(qryDetail.alignment) is ""><b>Alignment</b></td>
264: <cfif trim(qryDetail.order) is ""><b>Order</b></td>
265: <cfif trim(qryDetail.edit) is ""><b>Edit</b></td>
266: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
267: <cfif trim(qryDetail.title) is ""><b>Title</b></td>
268: <cfif trim(qryDetail.text) is ""><b>Text</b></td>
269: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
270: <cfif trim(qryDetail.title) is ""><b>Title</b></td>
271: <cfif trim(qryDetail.text) is ""><b>Text</b></td>
272: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
273: <cfif trim(qryDetail.title) is ""><b>Title</b></td>
274: <cfif trim(qryDetail.text) is ""><b>Text</b></td>
275: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
276: <cfif trim(qryDetail.title) is ""><b>Title</b></td>
277: <cfif trim(qryDetail.text) is ""><b>Text</b></td>
278: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
279: <cfif trim(qryDetail.title) is ""><b>Title</b></td>
280: <cfif trim(qryDetail.text) is ""><b>Text</b></td>
281: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
282: <cfif trim(qryDetail.title) is ""><b>Title</b></td>
283: <cfif trim(qryDetail.text) is ""><b>Text</b></td>
284: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
285: <cfif trim(qryDetail.title) is ""><b>Title</b></td>
286: <cfif trim(qryDetail.text) is ""><b>Text</b></td>
287: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
288: <cfif trim(qryDetail.title) is ""><b>Title</b></td>
289: <cfif trim(qryDetail.text) is ""><b>Text</b></td>
290: <cfif trim(qryDetail.imageName) is ""><b>Image Name</b></td>
291: <cfif trim(qryDetail.title) is ""><b>Title</b></td>
292: <cfif trim(qryDetail.text) is ""><b>Text</b></td>

```

```

293: <td><b>#qryImageInfo.formTitle#</b></td>
294: <td><b>Alignment</b></td>
295: <td><b>Order</b></td>
296: </tr>
297: <tr valign="top" bgcolor="#eeeeee">
298: <td>
299: <select name="edtImageType">
300: <cfloop query="qryImageTypes">
301: <option value="#qryImageTypes.imageType#"><cfif qryImageTypes.imageType is nImageType>
selected</cfif></td>
</cfloop>
302: </select>
303: </td>
304: <cfif qryImageTypes.recordCount gt 1>
305: <input type="submit" name="btnImageType" value="Change">
306: </cfif>
307: </td>
308: <td><input type="text" name="edtTitle" value="#cTitle#"></td>
309: </td>
310: <cfif qryImageInfo.isFormField is "Y">
311: <input type="File" name="edtImage"></td>
312: <cfelseif qryImageInfo.isApplet is "Y">
313: <input type="text" name="edtImage">
314: <cfelseif qryImageInfo.isURL is "Y">
315: <input type="text" name="edtImage">
316: <cfelse> <!-- The default if a new entry -->
317: <input type="File" name="edtImage"></td>
318: </cfif>
319: </td>
320: </td>
321: <select name="edtAlignment">
322: <option value="left"><cfif lcase(cAlignment) is "left"> selected</cfif></td>
323: <option value="middle"><cfif lcase(cAlignment) is "middle"> selected</cfif></td>
324: <option value="right"><cfif lcase(cAlignment) is "right"> selected</cfif></td>
325: </select>
326: </td>
327: <td><input type="text" name="edtSortOrder" value="#nSortOrder#" size="2"></td>
328: </tr>
329: <tr valign="top" bgcolor="#eeeeee">
330: <td colspan="5">
331: <b>Text:</b><br>
332: <textarea name="edtDesc" rows="5" cols="80" wrap="virtual">#trim(cDesc)#</textarea>
333: </td>
334: </tr>
335: <tr bgcolor="eeeeee">
336: <td colspan="5">
337: <cfif qryEdit.recordCount is 0>
338: <input type="submit" name="btnUpdateDetail" value="Add Paragraph">
339: <input type="reset" value="Reset Info">
340:

```

```
341: <cfelse>
342:   <input type="submit" name="btnUpdateDetail" value="Update Paragraph">
343:   <input type="reset" value="Reset Info">
344:   <input type="submit" name="btnCancelDetail" value="Cancel">
345: </cfif>
346: </td>
347: </tr>
348: </table>
349: </cfoutput>
350: </form>
351: </cfif>
352: </body>
353: </html>
354:
355:
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfif not isDefined("form.distributorID")>
4:   <cfset client.lookupID = -1>
5:   <cfset client.detailID = -1>
6:   <cfset client.imageType = -1>
7:   <cfset client.userName = "">
8:   <cflocation url="distAdm.cfm" addtoken="no">
9: </cfif>
10:
11: <cfquery name="qryFindPage" datasource="#ap_datasource#">
12:   select homePages.distributorID
13:   from homePages
14:   where homePages.distributorID = #form.distributorID#
15: </cfquery>
16:
17: <cfinclude template="include\clearOldFields.cfm">
18: <cfset client.userName = "">
19: <cfset client.imageType = -1>
20:
21: <cfif isDefined("form.btnImageType")>
22:   <!-- A change in the image type has been requested -->
23:   <cfset client.lookupDistID = form.distributorID>
24:   <cfset client.lookupID = -1>
25:   <cfset client.detailID = form.homePageDetailID>
26:   <cfset client.imageType = form.edtImageType>
27:
28:   <cfset client.old_title = form.edtTitle>
29:   <cfset client.old_alignment = form.edtAlignment>
30:   <cfset client.old_sortOrder = form.edtSortOrder>
31:   <cfset client.old_desc = form.edtDesc>
32:
33:   <cflocation url="homePageMaint.cfm" addToken="no">
34: </cfif>
35:
36: <cfif isDefined("form.btnCancelDetail")> <!-- Cancel detail edit -->
37:   <cfset client.lookupDistID = form.distributorID>
38:   <cfset client.lookupID = -1>
39:   <cfset client.detailID = -1>
40:   <cfset client.imageType = -1>
41:   <cfset client.userName = "">
42:   <cflocation url="homePageMaint.cfm" addToken="no">
43:
44: <cfelseif isDefined("form.btnCancelDelete")> <!-- Cancel detail edit -->
45:   <cfset client.lookupDistID = form.distributorID>
46:   <cfset client.lookupID = -1>
47:   <cfset client.detailID = -1>
48:   <cfset client.imageType = -1>
49:

```



```

50: <cfset client.userName = "Deletion failed.">
51: <cflocation url="homePageMaint.cfm" addToken="no">
52:
53: <cfelseif isDefined("form.btnView")>
54: <cfset client.lookupDistID = #form.distributorID#>
55: <cflocation url="homePageView.cfm" addToken="no">
56:
57: <cfelseif isDefined("form.btnGenerate")>
58: <cfset client.lookupDistID = #form.distributorID#>
59: <cfif cgi.server_port is '443'>
60:     <cfset cURL = 'https://'>
61: <cfelse>
62:     <cfset cURL = 'http://'>
63: </cfif>
64: <cfset cURL = cURL & cgi.server_name & cgi.path_info>
65: <cfset cURL = replaceNoCase(cURL, "homePageUpdate.cfm", "")>
66:
67: <cfhttp
68:     url="http://www.multidimension.com/fullimpact/admin/homePageView.cfm"
69:     method="get"
70:     resolveURL="no"
71:     timeout="500"
72: >
73: </cfhttp>
74:
75: <cfif #cfhttp.fileContent# is not "" and findNoCase(left(cfhttp.fileContent,30),"connection failure") is 0>
76:     <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
77:         select distributors.homePageImages
78:         from distributors
79:         where distributors.distributorID = #form.distributorID#
80:     </cfquery>
81:     <cffile
82:         action="write"
83:         file="#qryImagePath.homePageImages##form.distributorID#_index.cfm"
84:         output="#CFHTTP.FileContent#"
85:     >
86:
87:     <cfset client.userName = "Home page has been generated and is live.">
88: <cfelse>
89:     <cfset client.userName = "Unable to generate home page at this time.">
90: </cfif>
91: <cfset client.userName = client.userName & "<br>" & cURL & "<br>" & cfhttp.fileContent>
92: <cflocation url="homePageMaint.cfm" addToken="no">
93:
94: <cfelseif isDefined("form.btnUpdateDetail")>
95:     <cfquery name="qryFindDetail" dataSource="#ap_dataSource#">
96:         select homePageDetailID
97:         from homePageDetail
98:         where homePageDetail.homePageDetailID = #form.homePageDetailID#

```

```

99: </cfquery>
100:
101: <cfif qryFindDetail.recordCount is 0>
102:   <cfset cTitle = preserveSingleQuotes(form.edtTitle)>
103:   <cfset cDesc = preserveSingleQuotes(form.edtDesc)>
104:   <cfset nSortOrder = val(form.edtSortOrder)>
105:
106:   <cfquery name="qryImageType" dataSource="#ap_dataSource#">
107:     select imageType, isFormField, isApplet, isURL
108:     from imageTypes
109:     where imageTypes.imageType = #form.edtImageType#
110:   </cfquery>
111:
112:   <cfif qryImageType.isFormField is "Y">
113:     <cfif trim(form.edtImage) is "">
114:       <cfset cImage = form.originalImage>
115:       <cfset cUserImage = form.originalUserImage>
116:     <cfelse>
117:       <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
118:         select distributors.homePageImages
119:         from distributors
120:         where distributors.distributorID = #form.distributorID#
121:       </cfquery>
122:       <!--- Upload the file to a unique name --->
123:       <cffile
124:         destination = "#qryImagePath.homePageImages#"
125:         action = "UPLOAD"
126:         nameconflict = "OVERWRITE"
127:         field = "edtImage"
128:       >
129:
130:       <cfset cImage = file.serverFile>
131:       <cfset cUserImage = file.serverFile>
132:
133:       <cfset cImagePath = file.serverDirectory & "\">
134:       <cfset cNewImage = "#cImagePath#trim(form.distributorID)#_#file.serverFile#">
135:
136:       <cfif fileExists(cNewImage)>
137:         <cffile
138:           action = "DELETE"
139:           file="#cNewImage#"
140:         >
141:       </cfif>
142:
143:       <!--- New rename the unique uploaded file to the new name --->
144:       <cffile
145:         action = "RENAME"
146:         source = "#file.serverDirectory#\#file.serverFile#"
147:         destination="#cNewImage#"

```

```

148: >
149:
150:     <cfset cImage = cNewImage>
151:     </cfif>
152:     <cfelseif qryImageType.isURL is "Y">
153:         <cfset cImage = form.edtImage>
154:         <cfset cUserImage = form.edtImage>
155:         <cfelseif qryImageType.isApplet is "Y">
156:             <cfset cImage = form.edtImage>
157:             <cfset cUserImage = form.edtImage>
158:         <cfelse>
159:             <cfset cImage = form.edtImage>
160:             <cfset cUserImage = form.edtImage>
161:         </cfif>
162:
163:
164:     <cfquery name="qryInsert" dataSource="#ap_dataSource#">
165:         insert into homePageDetail
166:         (distributorID, sortOrder, title, image, userFilename, imageType,
167:          alignment, text)
168:         values
169:         (#form.distributorID#, #nSortOrder#, '#cTitle#',
170:          '#cImage#', '#cUserImage#', #form.edtImageType#, '#form.edtAlignmert#',
171:          '#cDesc#')
172:     </cfquery>
173:
174:     <cfset client.lookupDistID = form.distributorID>
175:     <cfset client.lookupID = -1>
176:     <cfset client.detailID = -1>
177:     <cfset client.imageType = form.edtImageType> <!--- Keep last unferied image type -->
178:
179:     <cflocation url="homePageMaint.cfm" addToken="no">
180:
181: <cfelse>
182:     <cfset cTitle = preserveSingleQuotes(form.edtTitle)>
183:     <cfset cDesc = preserveSingleQuotes(form.edtDesc)>
184:     <cfset nSortOrder = val(form.edtSortOrder)>
185:
186:     <cfquery name="qryImageType" dataSource="#ap_dataSource#">
187:         select imageType, isFormField, isApplet, isURL
188:         from imageTypes
189:         where imageTypes.imageType = #form.edtImageType#
190:     </cfquery>
191:
192:     <cfif qryImageType.isFormField is "Y">
193:         <cfif trim(form.edtImage) is "">
194:             <cfset cImage = form.originalImage>
195:             <cfset cUserImage = form.originalUserImage>
196:         <cfelse>

```

```

197: <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
198:   select distributors.homePageImages
199:   from distributors
200:   where distributors.distributorID = #form.distributorID#
201: </cfquery>
202: <!-- Upload the file to a unique name -->
203: <cffile
204:   destination = "#qryImagePath.homePageImages#"
205:   action = "UPLOAD"
206:   nameconflict = "OVERWRITE"
207:   filefield = "editImage"
208: >
209:
210: <cfset cImage = file.serverFile>
211: <cfset cUserImage = file.serverFile>
212:
213: <cfset cImagePath = file.serverDirectory & "\">
214: <cfset cNewImage = "#cImagePath#trim(form.distributorID)#_#file.serverFile#">
215:
216: <cfif fileExists(cNewImage)>
217:   <cffile
218:     action = "DELETE"
219:     file="#cNewImage#"
220:   >
221: </cfif>
222:
223: <!-- Now rename the unique uploaded file to the new name -->
224: <cffile
225:   action = "RENAME"
226:   source = "#file.serverDirectory#\#file.serverFile#"
227:   destination="#cNewImage#"
228: >
229:
230: <cfset cImage = cNewImage>
231: </cfif>
232: <cfelseif qryImageType.isURL is "Y">
233:   <cfset cImage = form.editImage>
234:   <cfset cUserImage = form.editImage>
235:   <cfelseif qryImageType.isApplet is "Y">
236:     <cfset cImage = form.editImage>
237:     <cfset cUserImage = form.editImage>
238:   <cfelse>
239:     <cfset cImage = form.editImage>
240:     <cfset cUserImage = form.editImage>
241:   </cfif>
242:
243: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
244:   update homePageDetail
245:   set

```

```

246: sortOrder = #nSortOrder#,
247: title = '#cTitle#',
248: imageType = #form.edtImageType#,
249: alignment = '#form.edtAlignment#',
250: image = '#cImage#',
251: userFilename = '#cUserImage#',
252: text = '#cDesc#',
253: where homePageDetail.homePageDetailID = #form.homePageDetailID#
254: </cfquery>
255:
256: <cfset client.lookupDistID = form.distributorID>
257: <cfset client.lookupID = -1>
258: <cfset client.detailID = -1>
259: <cfset client.imageType = -1>
260:
261: <cflocation url="homePageMaint.cfm" addToken="no">
262:
263: </cfif>
264:
265: <cfelseif isDefined("form.btnUpdate")>
266: <cfif qryFindPage.recordCount is 0>
267: <cfset client.lookupDistID = -1>
268: <cfset client.lookupID = -1>
269: <cfset client.detailID = -1>
270: <cfset client.userName = "There was an error while creating the home page.">
271: <cftransaction>
272: <cfif trim(form.edtHeaderImage) is "">
273: <cfset cHeaderImage = form.originalHeaderImage>
274: <cfset cUserHeaderImage = form.originalUserHeader>
275: <cfelse>
276: <cfquery name="qryImagePath" dataSource="#ap_dataSource">
277: select distributors.homePageImages
278: from distributors
279: where distributors.distributorID = #form.distributorID#
280: </cfquery>
281: <!--- Upload the file to a unique name -->
282: <cffile
283: destination = "#qryImagePath.homePageImages#"
284: action = "UPLOAD"
285: nameconflict = "OVERWRITE"
286: field = "edtHeaderImage"
287: >
288:
289: <cfset cImage = file.serverFile>
290: <cfset cUserHeaderImage = file.serverFile>
291:
292: <cfset cImagePath = file.serverDirectory & "\">
293: <cfset cNewImage = "#cImagePath#trim(form.distributorID)#_#file.serverFile#">
294:

```

```

295: <cfif fileExists(cNewImage)>
296:   <cffile
297:     action = "DELETE"
298:     file="#cNewImage#"
299:   >
300: </cfif>
301:
302: <!--- Now rename the unique uploaded file to the new name --->
303: <cffile
304:   action = "RENAME"
305:   source = "#file.serverDirectory#\#file.serverFile#"
306:   destination="#cNewImage#"
307: >
308: <cfset cHeaderImage = cNewImage>
309: </cfif>
310:
311: <cfif trim(form.edtFooterImage) is "">
312:   <cfset cFooterImage = form.originalFooterImage>
313:   <cfset cUserFooterImage = form.originalUserFooter>
314: <cfelse>
315:   <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
316:     select distributors.homePageImages
317:     from distributors
318:     where distributors.distributorID = #form.distributorID#
319:   </cfquery>
320:   <!-- Upload the file to a unique name --->
321:   <cffile
322:     destination = "#qryImagePath.homePageImages#"
323:     action = "UPLOAD"
324:     nameConflict = "OVERWRITE"
325:     field = "edtFooterImage"
326:   >
327:
328:   <cfset cImage = file.serverFile>
329:   <cfset cUserFooterImage = file.serverFile>
330:
331:   <cfset cImagePath = file.serverDirectory & "\">
332:   <cfset cNewImage = "#cImagePath#trim(form.distributorID)#_#file.serverFile#">
333:
334:   <cfif fileExists(cNewImage)>
335:     <cffile
336:       action = "DELETE"
337:       file="#cNewImage#"
338:     >
339:   </cfif>
340:
341:   <!--- Now rename the unique uploaded file to the new name --->
342:   <cffile
343:     action = "RENAME"

```

```

344: source = "#file.serverDirectory#\#file.serverFile#"
345: destination="#cNewImage#"
346: >
347: <cfset cFooterImage = cNewImage>
348: </cfif>
349: <cfif isDefined("form.edtActive")>
350: <cfset cActive = "Y">
351: <cfelse>
352: <cfset cActive = "N">
353: </cfif>
354:
355: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
356: insert into homePages
357: (distributorID, headerImage, userHeaderImage,
358: footerImage, userFooterImage, active)
359: values
360: (#form.distributorID#,
361: '#cHeaderImage#', '#cUserHeaderImage#',
362: '#cFooterImage#', '#cUserFooterImage#', '#cActive#')
363: </cfquery>
364:
365: <cfset nDistributorID = form.distributorID>
366: <cfset client.lookupDistID = nDistributorID>
367:
368: <cfset client.userMessage = "Home page was created.">
369: </cftransaction>
370:
371: <cfif client.lookupDistID gt 0>
372: <cflocation url="homePageMaint.cfm" addToken="no">
373: <cfelse>
374: <cflocation url="distAdm.cfm" addToken="no">
375: </cfif>
376:
377: <cfelse>
378: <cfset client.lookupDistID = form.distributorID>
379: <cfset client.lookupID = -1>
380: <cfset client.detailID = -1>
381: <cfset client.userMessage = "There was an error while updating the home page information.">
382: </cftransaction>
383: <cfif trim(form.edtHeaderImage) is "">
384: <cfset cHeaderImage = form.originalHeaderImage>
385: <cfset cUserHeaderImage = form.originalUserHeader>
386: <cfelse>
387: <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
388: select distributors.homePageImages
389: from distributors
390: where distributors.distributorID = #form.distributorID#
391: </cfquery>
392: <!-- Upload the file to a unique name -->

```

```

393: <cffile
394: destination = "#qryImagePath.homePageImages#"
395: action = "UPLOAD"
396: nameconflict = "OVERWRITE"
397: filefield = "edtHeaderImage"
398: >
399:
400: <cfset cImage = file.serverFile>
401: <cfset cUserHeaderImage = file.serverFile>
402:
403: <cfset cImagePath = file.serverDirectory & "\">
404: <cfset cNewImage = "#cImagePath#trim(form.distributorID)#_file.serverFile#">
405:
406: <cfif fileExists(cNewImage)>
407:   <cffile
408:     action = "DELETE"
409:     file="#cNewImage#"
410:   >
411: </cfif>
412:
413: <!--- Now rename the unique uploaded file to the new name --->
414: <cffile
415:   action = "RENAME"
416:   source = "#file.serverDirectory#\#file.serverFile#"
417:   destination="#cNewImage#"
418: >
419: <cfset cHeaderImage = cNewImage>
420: </cfif>
421:
422: <cfif trim(form.edtFooterImage) is "">
423:   <cfset cFooterImage = form.originalFooterImage>
424:   <cfset cUserFooterImage = form.originalUserFooter>
425: <cfelse>
426:   <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
427:     select distributors.homePageImages
428:     from distributors
429:     where distributors.distributorID = #form.distributorID#
430:   </cfquery>
431:   <!-- Upload the file to a unique name --->
432:   <cffile
433:     destination = "#qryImagePath.homePageImages#"
434:     action = "UPLOAD"
435:     nameconflict = "OVERWRITE"
436:     filefield = "edtFooterImage"
437:   >
438:
439:   <cfset cImage = file.serverFile>
440:   <cfset cUserFooterImage = file.serverFile>
441:

```



```

442: <cfset cImagePath = file.serverDirectory & "N">
443: <cfset cNewImage = "cImagePath#trim(form.distributorID)#_file.serverFile#">
444:
445:
446: <cfif fileExists(cNewImage)>
447:     <cffile
448:         action = "DELETE"
449:         file="#cNewImage#"
450:     >
451: </cfif>
452:
453: <!--- New rename the unique uploaded file to the new name --->
454: <cffile
455:     action = "RENAME"
456:     source = "file.serverDirectory#\#file.serverFile#"
457:     destination="#cNewImage#"
458: >
459: <cfset cFooterImage = cNewImage>
460: </cfif>
461: <cfif isDefined("form.edtActive")>
462:     <cfset cActive = "Y">
463: <cfelse>
464:     <cfset cActive = "N">
465: </cfif>
466:
467: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
468:     update homePages
469:     set distributorID = #form.distributorID#,
470:     headerImage = '#cHeaderImage#',
471:     userHeaderImage = '#cUserHeaderImage#',
472:     footerImage = '#cFooterImage#',
473:     userFooterImage = '#cUserFooterImage#',
474:     active = '#cActive#'
475:     where homePages.distributorID = #form.distributorID#
476: </cfquery>
477:
478: <cfset client.lookupDistID = #form.distributorID#>
479: <cfset client.detailID = -1>
480: <cfset client.userName = "Home page was updated.">
481: </cftransaction>
482:
483: <cfif client.lookupDistID gt 0>
484:     <cflocation url="homePageMaint.cfm" addToken="no">
485: <cfelse>
486:     <cflocation url="distAdm.cfm" addToken="no">
487: </cfif>
488:
489: <cfelseif isDefined("form.btnDelete")>
490:     <cflocation url="homePageDelete.cfm" addToken="no">
491: <cfelseif isDefined("form.btnConfirmedDelete")>

```

```

491: <cfset client.lookupDistID = -1>
492: <cfset client.lookupID = -1>
493: <cfset client.detailID = -1>
494: <cfset client.userName = "Unable to delete home page.">
495: <cftransaction>
496:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
497:     delete from homePageDetail
498:     where homePageDetail.distributorID = #form.distributorID#
499:   </cfquery>
500:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
501:     delete from homePages
502:     where homePages.distributorID = #form.distributorID#
503:   </cfquery>
504:
505:   <cfquery name="qryImagePath" datasource="#ap_dataSource#">
506:     select distributors.homePageImages
507:     from distributors
508:     where distributors.distributorID = #form.distributorID#
509:   </cfquery>
510:   <cfset lstDirectory = "">
511:   <cfdirectory
512:     name = "lstDirectory"
513:     action = "list"
514:     directory = "#qryImagePath.homePageImages#"
515:     filter="#form.distributorID#_.*"
516:   >
517:   <cfloop query="lstDirectory">
518:     <cffile
519:       action="delete"
520:       file="#qryImagePath.homePageImages#lstDirectory.name#"
521:     >
522:   </cfloop>
523:
524:   <cfset client.userName = "Home page was deleted.">
525:   <cfset client.lookupDistID = #form.distributorID#>
526:   </cftransaction>
527:   <cflocation url="distAdm.cfm" addtoken="no">
528: </cfif>
529:
530:
531: <cfset client.lookupDistID = form.distributorID>
532: <cfset client.lookupID = -1>
533: <cfset client.detailID = -1>
534: <cfset client.imageType = -1>
535: <!--- Get ID number from edit -->
536: <cfloop collection="#form#" item="cName">
537:   <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
538:     <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
539:     <cfset client.detailID = val(cValue)>

```

```

540:      <cfset client.imageType = -1>
541:    </cfif>
542:
543:    <cfif client.lookupDistID gt -1 and client.detailID gt -1>
544:      <cflocation url="homePageMaint.cfm" addToken="no">
545:    </cfif>
546:  </cfloop>
547:
548:  <!--- Get ID number for delete detail item -->
549:  <cfloop collection="#form#" item="cName">
550:    <cfif ucCase(left(cName#,6)) is "DELETE" and findNoCase(".X", #cName#,1) gt 0>
551:      <cfset cValue = mid(cName#, 7, len(cName#)-8)>
552:      <cfset client.detailID = val(cValue)>
553:      <cfset client.imageType = -1>
554:    </cfif>
555:
556:    <cfif client.lookupDistID gt -1 and client.detailID gt -1>
557:      <cfset client.userName = "Unable to delete paragraph.">
558:      <cfquery name="qryDelete" dataSource="#ap_dataSource#">
559:        delete from homePageDetail
560:        where homePageDetail.homePageDetailID = #client.detailID#
561:      </cfquery>
562:      <cfset client.detailID = -1>
563:      <cfset client.userName = "paragraph deleted.">
564:      <cflocation url="homePageMaint.cfm" addToken="no">
565:    </cfif>
566:  </cfloop>
567:
568:  <!--- If anything else, then go back to the admin page -->
569:  <cflocation url="distAdm.cfm" addToken="no">
570:
571:

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html40/strict.dtd">
2:
3: <cfparam name="cNavColor" default="#ap_defaultNavColor#">
4: <cfparam name="cMenuColor" default="#ap_defaultMenuColor#">
5:
6:
7: <!-- If a Agent ID is not passed, then exit -->
8: <cfif not isDefined("client.lookupDistID")>
9:   <cflocation url="distAdm.cfm" addtoken="no">
10: </cfelse>
11: <cfset nDistID = client.lookupDistID>
12: </cfif>
13:
14: <cfquery name="qryPage" dataSource="#ap_dataSource#">
15:   select homePages.*, distributors.name as distributorName
16:   from homePages
17:   join distributors on distributors.distributorID = homePages.distributorID
18:   where homePages.distributorID = #nDistID#
19: </cfquery>
20:
21: <cfquery name="qryDetail" dataSource="#ap_dataSource#">
22:   select *
23:   from homePageDetail
24:   where homePageDetail.distributorID = #nDistID#
25:   order by homePageDetail.sortOrder, homePageDetail.title
26: </cfquery>
27:
28:
29: <html>
30: <head>
31: <!--
32: <title><<cfoutput><ap_agencyName# - #qryPropType.manifestTitle#</cfoutput></title>
33: --->
34: <title>Home Page for #qryPage.distributorName#</title>
35: <link rel="stylesheet" href="style1.css" type="text/css">
36: </head>
37:
38: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
39: <cfoutput>
40:
41: <table width="760" border="0" cellpadding="0" cellspacing="0">
42: <tr>
43:   <td align="right" valign="top" bgcolor="#cNavColor#" width="135">
44:     &nbsp;
45:     <!--
46:     <include template="navigation.cfm">
47:     -->
48:   </td>
49:   <td width="500" valign="top" align="center">

```

```

50: <table border="0" width="480" cellpadding="2">
51: <!--
52: <tr>
53: <td bgcolor="#cMenuColor#" class="heading">#qryPage.distributorName#</td>
54: </tr>
55: <!--
56:
57: <cfloop query="qryDetail">
58: <tr><td align="#qryDetail.alignment#">
59: <cfif trim(qryDetail.image) is not "">
60: <cfif qryDetail.imageType is 1>
61: 
<cfif lcase(qryDetail.alignment) is "middle">
</td></tr> <!-- Force paragraph to a new row -->
<tr><td>
</cfif>
</cfif>
</cfif>
<cfif trim(qryDetail.title) is not "">
<h3>#trim(qryDetail.title)#</h3>
</cfif>
<cfif trim(qryDetail.text) is not "">
#paragraphFormat(trim(qryDetail.text))#
</cfif>
</td></tr>
</cfloop>
</table>
</td><td>
</td>
</table>
</tr>
</table>
</cfoutput>
82: <!-- <cfinclude template="footer.cfm"> -->
83:
84: </body>
85: </html>
86:

```

1: <cflocation url="login.cfm" addtoken="no">

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
2:
3:  <cfparam name="client.loginAttempts" default="0">
4:  <cfparam name="client.userName" default="">
5:  <cfif isDefined("client.hasOldValues")>
6:    <cfset cUserName = client.old_edtUserName>
7:    <cfset nLoginAttempts = client.old_loginAttempts>
8:  <cfelse>
9:    <cfset cUserName = "">
10:   <cfset nLoginAttempts = 0>
11: </cfif>
12:
13: <cfif isDefined("url.debug") and url.debug is "True">
14:   <cfset client.debug = True>
15: <cfelse>
16:   <cfset client.debug = False>
17: </cfif>
18:
19: <cfset client.userID = -1>
20: <cfset client.userName = "">
21: <cfset client.entityID = -1>
22: <cfset client.entityType = -1>
23: <cfset client.currentEntityID = -1>
24: <cfset client.currentEntityType = -1>
25: <cfset client.distributorID = -1>
26: <cfset client.backofficeName = "">
27: <cfset client.gotoPage = "messages.cfm">
28:
29: <html>
30: <head>
31:   <title>Back Office Administration Login</title>
32:   <link rel="stylesheet" href="style1.css" type="text/css">
33: </head>
34:
35: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
36: <cfinclude template="include\nocache.cfm">
37:
38: <cfoutput>
39:
40: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
41: <tr>
42:   <td><span class="h2"><b>Yakalo Back Office Administration Login</b></span></td>
43:   <td align="right"></td>
44: </tr>
45: <tr><td colspan="2"><hr/></td></tr>
46: <tr bgcolor="#ffffff">
47:   <td colspan="2">
48:     <CFORM NAME="Login" ACTION="loginCheck.cfm">
49:       <table border="0" width="700" align="center">

```

```

50:   <tr><td colspan="2" bgcolor="#e0e0e0" align="center"><b>Header</b></td><td colspan="2" align="center"><b>Header</b></td></tr>
51:   <tr>
52:     <td colspan="2">
53:       <cfif client.userName is not "">
54:         <p><font color="red">#client.userName#</font></p>
55:       </cfif>
56:       <cfset client.userName = "">
57:       Enter the information below to login to the Back Office.
58:       <table border="0">
59:         <tr>
60:           <td>Username:</td>
61:           <td><CFINPUT TYPE="Text" name="edUserName" required="YES" message="You must enter your user name."
              value="#cUserName#"></td>
62:         </tr>
63:         <tr>
64:           <td>Password:</td>
65:           <td>
66:             <CFINPUT TYPE="Password" name="edPassword" required="YES" message="You must enter your password">
67:             &nbsp;&nbsp;&nbsp;Forgot your password? <a href="forgotpass.cfm">Click here.</a>
68:           </td>
69:         </tr>
70:       </table></p>
71:       <input type="hidden" name="loginAttempts" value="#nLoginAttempts#">
72:       <input type="Submit" value="Login">
73:     </td>
74:   </tr>
75:   <tr><td colspan="2"><i>Note: 'Accept cookies' must be enabled for your browser.</i></td></tr>
76:   </table>
77:   </CFORM>
78: </td>
79: </tr>
80: </table>
81: </cfoutput>
82:
83: </body>
84: </html>

```



```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html40/strict.dtd">
2:
3: <cfset client.gotoPage = "loginAdm.cfm">
4: <!--
5: <cfinclude template="include\securityTest.cfm">
6: -->
7:
8: <cfparam name="URL.sortBy" default="userName">
9: <cfset client.lookupID = -1>
10: <cfset client.detailID = -1>
11: <cfset client.lookupDistID = -1>
12: <cfset client.lookupAgencyID = -1>
13:
14:
15: <!-- Display rows -->
16: <cfparam name="nStartFrom" default="1">
17: <cfparam name="nToShow" default="#client.displayRows#">
18: <cfparam name="nEnd" default="#client.displayRows#">
19:
20:
21: <cfquery name="qryEditList" datasource="#ap_dataSource#">
22:   select security.userID, security.userName, security.fullName, security.ertityType,
23:   security.entityID, security.distributorID
24:   from security
25:   join securityAccess on
26:     security.entityID = securityAccess.entityID
27:   and security.entityType = securityAccess.entityType
28:   and securityAccess.hierarchyID like '#client.hierarchyID#%'
29:   union
30:   select security.userID, security.userName, security.fullName, security.entityType,
31:   security.entityID, security.distributorID
32:   from security
33:   where security.entityType = 0
34:   and security.entityID = 0
35:   and security.distributorID = 0
36:   order by #url.sortBy#
37: </cfquery>
38:
39:
40: <html>
41: <head>
42:   <cfoutput>
43:     <title>#client.backofficeName# Backoffice</title>
44:   </cfoutput>
45:   <link rel="stylesheet" href="style1.css" type="text/css">
46: </head>
47:
48:
49: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">

```

```

50: <cfinclude template="include\nocache.cfm"></cfinclude>
51: <p><cfinclude template="include\header.cfm"></p>
52:
53: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
54: <tr bgcolor="#cccc99">
55: <td colspan="4">
56: <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">
57: <tr>
58: <td align="left">
59: <span class="h2"><b>User Login Administration</b></span>
60: </td>
61: <td align="right">
62: <cfif #ntoDisplay# gte qryEditList.recordCount>
63: <cfset cToDisplay = min(qryEditList.recordCount, #ntoDisplay#)>
64: </cfif>
65: <cfif qryEditList.recordCount gte #ntoDisplay#>
66: <cfset cToDisplay = min(qryEditList.recordCount, #nEnd#)>
67: </cfif>
68: <cfset cStartFrom = min(qryEditList.recordCount, #nStartFrom#)>
69: <cfoutput>(Viewing records #cStartFrom# to #cToDisplay# out of #qryEditList.recordCount#)</cfoutput>
70: </td>
71: </tr>
72: </table>
73: </td>
74: </tr>
75: <tr bgcolor="#cccc99">
76: <td colspan="4">
77: <b><cfset lColor = True></b><a href="loginMaint.cfm">Add a user login</a>
78: </td>
79: </tr>
80:
81: <tr bgcolor="#cccccc">
82: <td>Sort by <a href="loginAdm.cfm?SortBy=username"><b>User Name</b></a></td>
83: <td>Sort by <a href="loginAdm.cfm?SortBy=fullName"><b>Full Name</b></a></td>
84: <td><b></b></td>
85: <td><b></b></td>
86: </tr>
87:
88:
89: <CFIF qryEditList.recordCount is 0>
90: <TR><TD COLSPAN="3"><I>There are no users defined</I></TD></TR>
91: </CFIF>
92: <cfset lColor = True>
93: <form action="loginMaint.cfm" method="post">
94: <cfoutput query="qryEditList" startrow="#nStartFrom#" maxrows="#ntoDisplay#">
95: <cfif qryEditList.entityType is 0 and qryEditList.entityID is 0 and
96: <cfset lNoAccess = true>
97: <cfset lNoAccess = true>
98: <cfelse>

```

```

99:     <cfset lNoAccess = false>
100:   </cfif>
101:   <cfset lColor = not lColor>
102:   <tr valign="center" <cfif lColor is TRUE>bgcolor="####" </cfif>>
103:     <td>
104:       <cfif lNoAccess><i></cfif>
105:       #gryEditList.userName#
106:     <cfif lNoAccess></i></cfif>
107:     </td>
108:     <td>
109:       <cfif lNoAccess><i></cfif>
110:       #gryEditList.fullName#
111:     <cfif lNoAccess></i></cfif>
112:     </td>
113:     <td>&nbsp;</td>
114:     <td align="center"><input type="image" name="edit#gryEditList.userID#" src="#ap_commonImages#edit.gif" alt="Edit"
border="0"></td>
115:   </tr>
116:   </cfoutput>
117:   </form>
118:   </table></p>
119:
120:   <cfoutput>
121:     <CFSET nPrevStart = nStartFrom-nToDisplay>
122:     <CFSET nNextStart = nStartFrom+nToDisplay>
123:     <CFSET nPrevEnd = #nPrevStart#+nToDisplay-1>
124:     <CFSET nNextEnd = #nNextStart#+nToDisplay-1>
125:     <cfif nPrevStart gte 1 or nNextStart lte gryEditList.recordCount>
126:       <table border="0" align="center">
127:         <tr>
128:           <cfif nPrevStart gte 1>
129:             <td>
130:               <form action="loginAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
131:                 <input type="hidden" name="nStartFrom" value="#nPrevStart#">
132:                 <input type="hidden" name="nToDisplay" value="#nToDisplay#">
133:                 <input type="hidden" name="nEnd" value="#nPrevEnd#">
134:                 <input type="submit" value="Previous #nToDisplay#">
135:               </FORM>
136:             </td>
137:           </cfif>
138:           <cfif nNextStart lte gryEditList.recordCount>
139:             <td>
140:               <form action="loginAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
141:                 <input type="hidden" name="nStartFrom" value="#nNextStart#">
142:                 <input type="hidden" name="nToDisplay" value="#nToDisplay#">
143:                 <input type="hidden" name="nEnd" value="#nNextEnd#">
144:                 <cfset nLeftToShow = min(nToDisplay, (gryEditList.recordcount - cToDisplay))>
145:                 <input type="submit" value="Next #nLeftToShow#">
146:               </form>

```

```
147:         </td>
148:         </cfif>
149:         </tr>
150:     </table>
151: </cfif>
152: </cfoutput>
153:
154: </body>
155: </html>
```

**U.S. National Institute of Standards and Technology**

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//>
2:
3: <html>
4: <head>
5: <title>Back Office Login Check</title>
6: </head>
7:
8:
9: <cfquery name="qrySetup" dataSource="#ap_dataSource#">
10: select entityType from entityType
11: </cfquery>
12:
13: <cfif qrySetup.recordCount is 0>
14: <cfquery name="qryNewType" dataSource="#ap_dataSource#">
15: insert into entityType (description)
16: values ('Yakalo Administrator')
17: </cfquery>
18: <cfquery name="qryNewType" dataSource="#ap_dataSource#">
19: insert into entityType (description)
20: values ('Portal')
21: </cfquery>
22: <cfquery name="qryNewType" dataSource="#ap_dataSource#">
23: insert into entityType (description)
24: values ('Master Distributor')
25: </cfquery>
26: <cfquery name="qryNewType" dataSource="#ap_dataSource#">
27: insert into entityType (description)
28: values ('Distributor')
29: </cfquery>
30: <cfquery name="qryNewType" dataSource="#ap_dataSource#">
31: insert into entityType (description)
32: values ('Master Agency')
33: </cfquery>
34: <cfquery name="qryNewType" dataSource="#ap_dataSource#">
35: insert into entityType (description)
36: values ('Agency')
37: </cfquery>
38: <cfquery name="qryNewType" dataSource="#ap_dataSource#">
39: insert into entityType (description)
40: values ('Agent')
41: </cfquery>
42: </cfif>
43:
44: <cfquery name="qrySetup" dataSource="#ap_dataSource#">
45: select userID
46: from security
47: </cfquery>
48:
49: <cfif qrySetup.recordCount is 0>

```

```

50: <!-- No users have been setup, so create the default administrator -->
51: <cfquery name="qryGetInfo" datasource="#ap_datasource#">
52:   select entityType from entityTypes
53:   where description = 'Yakalo Administrator'
54: </cfquery>
55:
56: <cfquery name="qryNewUser" datasource="#ap_datasource#">
57:   insert into security (userName, fullName, password, entityType, status,
58:     distributorID, accessLevel)
59:   values ('Yakalo.adm', 'Yakalo Administrator', '#hash("Yakalo.Pass")#', 1,
60:     #qryGetInfo.entityType#, 'Enabled', 0, 'Administrator')
61: </cfquery>
62:
63: <!-- Generate the security hierarchy tree -->
64: <cfinclude template="include\makeSecurityTree.cfm">
65: </cfif>
66:
67: <cfquery name="qryStatus" datasource="#ap_datasource#">
68:   select statusID
69:   from statusValues
70: </cfquery>
71: <cfif qryStatus.recordCount is 0>
72:   <!-- Create default status values. DistributorID of 0 means default! -->
73:   <cfquery name="qryInsert" datasource="#ap_datasource#">
74:     insert into statusValues (distributorID, status, propViewVisible) values (0, 'New', 'Y')
75:   </cfquery>
76:   <cfquery name="qryInsert" datasource="#ap_datasource#">
77:     insert into statusValues (distributorID, status, propViewVisible) values (0, 'Active', 'Y')
78:   </cfquery>
79:   <cfquery name="qryInsert" datasource="#ap_datasource#">
80:     insert into statusValues (distributorID, status, propViewVisible) values (0, 'Sold', 'Y')
81:   </cfquery>
82:   <cfquery name="qryInsert" datasource="#ap_datasource#">
83:     insert into statusValues (distributorID, status, propViewVisible) values (0, 'Deleted', 'N')
84:   </cfquery>
85:   <cfquery name="qryInsert" datasource="#ap_datasource#">
86:     insert into statusValues (distributorID, status, propViewVisible) values (0, 'Inactive', 'N')
87:   </cfquery>
88:   <cfquery name="qryInsert" datasource="#ap_datasource#">
89:     insert into statusValues (distributorID, status, propViewVisible) values (0, 'Off Market', 'N')
90:   </cfquery>
91:   <cfquery name="qryInsert" datasource="#ap_datasource#">
92:     insert into statusValues (distributorID, status, propViewVisible) values (0, 'Contract Pending', 'Y')
93:   </cfquery>
94:   <cfquery name="qryInsert" datasource="#ap_datasource#">
95:     insert into statusValues (distributorID, status, propViewVisible) values (0, 'Under Contract', 'Y')
96:   </cfquery>
97: </cfif>
98:

```

```

99: <cfquery name="qryHomeType" dataSource="#ap_dataSource#">
100: select homeTypeID
101: from homeTypeValues
102: </cfquery>
103: <cfif qryHomeType.recordCount is 0>
104: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
105: insert into homeTypeValues (distributorID, homeType) values (0, 'None')
106: </cfquery>
107: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
108: insert into homeTypeValues (distributorID, homeType) values (0, 'Single Family')
109: </cfquery>
110: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
111: insert into homeTypeValues (distributorID, homeType) values (0, 'Townhome/Condo')
112: </cfquery>
113: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
114: insert into homeTypeValues (distributorID, homeType) values (0, 'Mobile Home')
115: </cfquery>
116: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
117: insert into homeTypeValues (distributorID, homeType) values (0, 'Cabin')
118: </cfquery>
119: </cfif>
120:
121: <cfquery name="qryLotType" dataSource="#ap_dataSource#">
122: select lotTypeID
123: from lotTypeValues
124: </cfquery>
125: <cfif qryLotType.recordCount is 0>
126: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
127: insert into lotTypeValues (distributorID, lotType) values (0, 'City/Town')
128: </cfquery>
129: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
130: insert into lotTypeValues (distributorID, lotType) values (0, 'Land 0-34 acres')
131: </cfquery>
132: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
133: insert into lotTypeValues (distributorID, lotType) values (0, 'Land 35+ acres')
134: </cfquery>
135: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
136: insert into lotTypeValues (distributorID, lotType) values (0, 'Leased')
137: </cfquery>
138: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
139: insert into lotTypeValues (distributorID, lotType) values (0, 'Other')
140: </cfquery>
141: </cfif>
142:
143: <cfquery name="qryPropertyType" dataSource="#ap_dataSource#">
144: select propertyTypeID
145: from propertyTypeValues
146: </cfquery>
147: <cfif qryPropertyType.recordCount is 0>

```

```

148: <cfquery name="qryInsert" datasource="#ap_datasource#">
149:   insert into propertyTypeValues (distributorID, propertyType) values (0, 'Residential')
150: </cfquery>
151: <cfquery name="qryInsert" datasource="#ap_datasource#">
152:   insert into propertyTypeValues (distributorID, propertyType) values (0, 'Ranch/Farm')
153: </cfquery>
154: <cfquery name="qryInsert" datasource="#ap_datasource#">
155:   insert into propertyTypeValues (distributorID, propertyType) values (0, 'Mountain Property')
156: </cfquery>
157: <cfquery name="qryInsert" datasource="#ap_datasource#">
158:   insert into propertyTypeValues (distributorID, propertyType) values (0, 'Commercial')
159: </cfquery>
160: <cfquery name="qryInsert" datasource="#ap_datasource#">
161:   insert into propertyTypeValues (distributorID, propertyType) values (0, 'Rental')
162: </cfquery>
163: <cfquery name="qryInsert" datasource="#ap_datasource#">
164:   insert into propertyTypeValues (distributorID, propertyType) values (0, 'Vacation Rental')
165: </cfquery>
166: </cfif>
167:
168: <cfquery name="qryLogin" datasource="#ap_datasource#">
169:   select *
170:   from security
171:   where security.userName = 'form.edtUsername#'
172:   and security.password = 'hash(form.edtPassword) #'
173: </cfquery>
174: <cfset cPassHash = hash(form.edtPassword)>
175:
176: <body>
177: <cfinclude template="include\nocache.cfm">
178:
179: <cfoutput>
180:
181: <cfset nAttempts = form.loginAttempts + 1>
182:
183: <cfif qryLogin.recordCount is 0>
184:   <cfset client.userName = "Invalid Username or Password.">
185:   <cfinclude template="include\clearOldFields.cfm">
186:   <cfset client.old_edtUserName = 'form.edtUserName# '>
187:   <cfset client.old_loginAttempts = #nAttempts#>
188:   <cflocation url="Login.cfm" addToken="no">
189: <cfelse>
190:   <cfinclude template="include\clearOldFields.cfm">
191:   <cfset client.userName = "">
192:   <cfset client.userID = qryLogin.userID>
193:   <cfset client.userName = "qryLogin.fullName">
194:   <cfset client.displayRows = qryLogin.displayRows>
195:   <cfset client.entityID = qryLogin.entityID>
196:   <cfset client.entityType = qryLogin.entityType>

```



```

197: <cfset client.currentAccessLevel = qryLogin.accessLevel>
198:
199: <cfset client.currentEntityID = qryLogin.entityID>
200: <cfset client.currentEntityType = qryLogin.entityType>
201: <cfset client.currentPortalID = qryLogin.portalID>
202: <cfset client.currentDistributorID = qryLogin.portalID>
203:
204: <cfif qryLogin.entityType is ap_securityYakalo>
205:   <cfset client.backOfficeName = "Yakalo Administration">
206:   <cfelseif qryLogin.entityType is ap_securityPortal>
207:     <cfquery name="qryGetPortal" dataSource="#ap_dataSource#">
208:       select name
209:       from portals
210:       where portals.portalID = #qryLogin.entityID#
211:     </cfquery>
212:   <cfset client.backOfficeName = #qryGetPortal.name#>
213:   <cfelseif qryLogin.entityType is ap_securityMastDist or qryLogin.entityType is ap_securityDist>
214:     <cfquery name="qryGetDist" dataSource="#ap_dataSource#">
215:       select name
216:       from distributors
217:       where distributors.distributorID = #qryLogin.entityID#
218:     </cfquery>
219:   <cfset client.backOfficeName = #qryGetDist.name#>
220:   <cfelseif qryLogin.entityType is ap_securityMastAgency or qryLogin.entityType is ap_securityAgency>
221:     <cfquery name="qryGetAgency" dataSource="#ap_dataSource#">
222:       select name
223:       from agency
224:       where agency.agency_id = #qryLogin.entityID#
225:     </cfquery>
226:   <cfset client.backOfficeName = #qryGetAgency.name#>
227:   <cfelseif qryLogin.entityType is ap_securityAgent>
228:     <cfquery name="qryGetAgent" dataSource="#ap_dataSource#">
229:       select firstname + ' ' + lastname as name
230:       from agents
231:       where agents.agent_id = #qryLogin.entityID#
232:     </cfquery>
233:   <cfset client.backOfficeName = #qryGetAgent.name#>
234:   </cfif>
235:
236:   <cfquery name="qryUpdateLogin" dataSource="#ap_dataSource#">
237:     update security
238:     set invalidLoginAttempts = 0,
239:       lastLogin = #now()#
240:     where security.userID = #client.userID#
241:   </cfquery>
242:
243:   <cflocation url="customerSelect.cfm" addToken="no">
244:   </cfif>
245:

```

246: </cfoutput>  
247: </body>  
248: </html>

-----

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <!-- Get ID number from edit -->
4: <cfloop collection="#form#" item="cName">
5:   <cfif ucase(left(cName#,4)) is "EDIT" and findNoCase("X", #cName#,1) gt 0>
6:     <cfset cValue = mid(cName#, 5, len(cName#)-6)>
7:     <cfset client.lookupID = val(cValue)>
8:     <cfset client.detailID = -1>
9:   </cfif>
10: </cfloop>
11:
12: <cfif not isDefined("client.lookupID")>
13:   <cflocation url="loginAdm.cfm" addToken="no">
14: </cfif>
15: <cfparam name="client.userName" default="">
16:
17: <cfquery name="qryFindUser" datasource="#ap_dataSource#">
18:   select * from security
19:   where security.userID = #client.lookupID#
20: </cfquery>
21:
22: <cfif qryFindUser.entityType gte ap_securityMastAgency or isDefined("url.showAll")>
23:   <cfset lstSecurityFilter = "#ap_securityYakalo#, #ap_securityPortal#, #ap_securityMastDist#,
24:   #ap_securityDist#, #ap_securityMastAgency#, #ap_securityNoAgency#,
25:   #ap_securityAgent#">
26:   <cfset lShowAll = true>
27: <cfelse>
28:   <cfset lShowAll = false>
29: </cfif>
30:
31: <cfif isDefined("client.hasOldValues") and client.hasOldValues is true>
32:   <cfset nUserID = client.lookupID>
33:   <cfset cUsername = client.old_username>
34:   <cfset cFullname = client.old_fullname>
35:   <cfset cPassword = client.old_password>
36:   <cfset cCheckPassword = client.old_checkPassword>
37:   <cfset cStatus = client.old_status>
38:   <cfset cHint = client.old_hint>
39:   <cfset cAccessLevel = client.old_accessLevel>
40:   <cfset nDisplayRows = client.old_displayRows>
41:   <cfset cEmail = client.old_email>
42: <cfelseif qryFindUser.recordCount gt 0>
43:   <cfset nUserID = qryFindUser.userID>
44:   <cfset cUsername = qryFindUser.username>
45:   <cfset cFullname = qryFindUser.fullname>
46:   <cfset cPassword = "">
47:   <cfset cCheckPassword = "">
48:   <cfset cStatus = qryFindUser.status>
49:   <cfset cHint = qryFindUser.hint>

```

```

50: <cfset cAccessLevel = qryFindUser.accessLevel>
51: <cfset nDisplayRows = qryFindUser.displayRows>
52: <cfset cEmail = qryFindUser.email>
53: <cfelse>
54: <cfset nUserID = -1>
55: <cfset cAccessLevel = "User">
56: <cfset nDisplayRows = 10>
57: <cfset cUsername = "">
58: <cfset cFullname = "">
59: <cfset cPassword = "">
60: <cfset cCheckPassword = "">
61: <cfset cStatus = "Enabled">
62: <cfset cHint = "">
63: <cfset cEmail = "">
64: </cfif>
65:
66: <html>
67: <head>
68: <cfoutput>
69: <title>#client.backofficeName# Backoffice</title>
70: </cfoutput>
71: <link rel="stylesheet" href="style1.css" type="text/css">
72: </head>
73:
74: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
75: <cfinclude template="include\nocache.cfm">
76:
77: <p><cfinclude template="include\header.cfm"></p>
78:
79: <cfoutput>
80:
81: <form name="frmLogin" action="loginUpdate.cfm" method="post">
82: <input type="hidden" name="userID" value="#nUserID#">
83:
84: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
85: <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>User Maintenance</b></span>
86: <cfif client.lookupID is -1>
87: <nbsp;  <b>Create a new user</b>
88: </cfif>
89: </td></tr>
90:
91: <CFIF client.userName is not "">
92: <tr bgcolor="eeeeee">
93: <td colspan="5"><p><font color="red">#client.userName#</font></p></td>
94: <cfset client.userName = "">
95: </tr>
96: <tr bgcolor="eeeeee"><td colspan="5"><b></td></tr>
97: </CFIF>
98:

```

```

99: <tr bgcolor="eeeeee">
100: <td width="15%">Login Name:</td>
101: <td width="34%"><input type="text" name="edUserName" value="#cUserName#"><cfif trim(cUserName) is "Yakalo.adm">
    readonly</cfif></td>
102: <td width="2%">&nbsp;</td>
103: <td width="15%">Full Name:</td>
104: <td width="34%">
105: <input type="text" name="edFullName" size="45" value="#cFullName#"><cfif trim(cUserName) is "Yakalo.adm">
    readonly</cfif>
106: </td>
107: </tr>
108:
109: <cfif qryFindUser.recordCount gt 0>
110: <input type="hidden" name="edtHasPassword" value="Yes">
111: <cfelse>
112: <input type="hidden" name="edtHasPassword" value="No">
113: </cfif>
114: <tr bgcolor="eeeeee">
115: <td width="15%">
116: <cfif isDefined("client.old_edtPassword")>
117: <font color="red">Password:</font>
118: <cfelse>
119: Password:
120: </cfif>
121: </td>
122: <td width="34%">
123: <input type="password" name="edtPassword" value="#cPassword#">
124: <cfif qryFindUser.recordCount gt 0><i>Encrypted</i></cfif>
125: </td>
126: <td width="2%">&nbsp;</td>
127: <td width="15%">
128: <cfif isDefined("client.old_edtCheckPassword")>
129: <font color="red">Check Password:</font>
130: <cfelse>
131: Check Password:
132: </cfif>
133: </td>
134: <td width="34%"><input type="password" name="edtCheckPassword" value="#cCheckPassword#"></td>
135: </tr>
136:
137: <tr bgcolor="eeeeee">
138: <td width="15%">Status:</td>
139: <td width="34%">
140: <select name="edtStatus">
141: <option value="Enabled" <cfif cStatus is "Enabled" or nUserID is -1> selected</cfif>>Enabled
142: <option value="Disabled" <cfif cStatus is "Disabled"> selected</cfif>>Disabled
143: </select>
144: </td>
145: <td width="2%">&nbsp;</td>

```

```

146:         <td width="15%">Hint:</td>
147:         <td width="34%"><input type="text" name="edHint" size="45" value="#cHint#"></td>
148:     </tr>
149:
150:     <tr bgcolor="eeeeee">
151:         <td width="15%">Control Over:</td>
152:         <td colspan="4">
153:             <select name="edtControlOver">
154:                 <option value="0|0"><cfif qryFindUser.distributorID is 0
155:                     and qryFindUser.entityTypeID is 0
156:                     and qryFindUser.entityID is 0> selected</cfif>>Nothing
157:                 <cfloop query="qrySecurity">
158:                     <option value="#qrySecurity.distributorID|#qrySecurity.entityTypeID|#qrySecurity.entityID#"><cfif
159:                         qrySecurity.distributorID is qryFindUser.distributorID
160:                         and qrySecurity.entityID is qryFindUser.entityID
161:                         and qrySecurity.entityTypeID is qryFindUser.entityTypeID> selected</cfif>>
162:                     <cfset nTo = qrySecurity.entityTypeID-1>
163:                     <cfloop from="1" to="#nTo#" index="i">
164:                         &nbsp;
165:                     </cfloop>
166:                     #qrySecurity.name#
167:                 </cfloop>
168:             </select>
169:             <cfif qryFindUser.entityTypeID lte ap_securityDist>
170:                 <cfif lshowAll>
171:                     &nbsp;
172:                     <input type="submit" name="btnHide" value="Hide Agencies and Agents">
173:                     <cfelse>
174:                     &nbsp;
175:                     <input type="submit" name="btnShow" value="Show Agencies and Agents">
176:                 </cfif>
177:             </td>
178:         </tr>
179:
180:     <tr bgcolor="eeeeee">
181:         <td width="15%">Access Level:</td>
182:         <td width="34%">
183:             <select name="edtAccessLevel">
184:                 <option value="Administrator"><cfif cAccessLevel is "Administrator"> selected</cfif>>Administrator
185:                 <option value="User"><cfif cAccessLevel is "User"> selected</cfif>>User
186:                 <option value="Photographer"><cfif cAccessLevel is "Photographer"> selected</cfif>>Photographer
187:             </select>
188:         </td>
189:         <td colspan="3">&nbsp;</td>
190:     </tr>
191:
192:     <tr bgcolor="eeeeee">
193:

```

```

194: <td width="15%">Display Rows:</td>
195: <td width="34%"><input type="text" name="edtDisplayRows" value="#nDisplayRows#"></td>
196: <td width="2%">&nbsp;</td>
197: <td width="15%">Email:</td>
198: <td width="34%"><input type="text" size="45" name="edtEmail" value="#cEmail#"></td>
199: </tr>
200:
201: <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
202: <cfif qryFindUser.recordCount gt 0>
203: <tr bgcolor="eeeeee">
204: <td width="15%">Last Login:</td>
205: <td width="34%">
206: <cfif qryFindUser.lastLogin is "">
207: <i>Never logged in</i>
208: <cfelse>
209: <dateFormat(qryFindUser.lastLogin, "mm/dd/yyyy")#
210: </cfif>
211: </td>
212: <td width="2%">&nbsp;</td>
213: <td width="15%">Invalid Attempts:</td>
214: <td width="34%">
215: <cfif qryFindUser.invalidLoginAttempts is 0>
216: <i>None</i>
217: <cfelse>
218: <#qryFindUser.invalidLoginAttempts#
219: </cfif>
220: </td>
221: </tr>
222: </cfif>
223:
224: <tr bgcolor="eeeeee">
225: <td colspan="5">
226: <cfif qryFindUser.recordCount is 0>
227: <input type="submit" name="btnUpdate" value="Add User Account">
228: <input type="reset" value="Reset Info">
229: <cfelse>
230: <input type="submit" name="btnUpdate" value="Update User Account">
231: <input type="reset" value="Reset Info">
232: <input type="submit" name="btnDelete" value="Delete Account">
233: </cfif>
234: </td>
235: </tr>
236: </table>
237: </FORM>
238:
239: </cfoutput>
240:
241: </body>
242: </html>

```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3:  <cfif not isDefined("FORM.userID")>
4:    <cflocation url="loginAdm.cfm" addtoken="no">
5:  </cfif>
6:
7:  <cfquery name="qryFindUser" datasource="#ap_dataSource#">
8:    select userID, password from security
9:    where security.userID = #FORM.userID#
10:  </cfquery>
11:
12:  <cfinclude template="include\clearOldFields.cfm">
13:  <cfset client.userName = "">
14:
15:  <!-- Save form values in case something is wrong -->
16:
17:  <cfif isDefined("form.btnShow")>
18:    <cfset client.lookupID = form.userID>
19:    <cfset client.detailID = -1>
20:    <cfset client.hasOldValues = true>
21:    <cfset client.old_username = form.edtUsername>
22:    <cfset client.old_fullname = form.edtFullname>
23:    <cfset client.old_password = form.edtPassword>
24:    <cfset client.old_checkPassword = form.edtCheckPassword>
25:    <cfset client.old_status = form.edtStatus>
26:    <cfset client.old_hint = form.edtHint>
27:    <cfset client.old_accessLevel = form.edtAccessLevel>
28:    <cfset client.old_displayRows = form.edtDisplayRows>
29:    <cfset client.old_email = form.edtEmail>
30:    <cflocation url="loginMaint.cfm?showAll=y&requestTimeout=5000" addToken="no">
31:  <cfelseif isDefined("form.btnHide")>
32:    <cfset client.lookupID = form.userID>
33:    <cfset client.detailID = -1>
34:    <cfset client.hasOldValues = true>
35:    <cfset client.old_username = form.edtUsername>
36:    <cfset client.old_fullname = form.edtFullname>
37:    <cfset client.old_password = form.edtPassword>
38:    <cfset client.old_checkPassword = form.edtCheckPassword>
39:    <cfset client.old_status = form.edtStatus>
40:    <cfset client.old_hint = form.edtHint>
41:    <cfset client.old_accessLevel = form.edtAccessLevel>
42:    <cfset client.old_displayRows = form.edtDisplayRows>
43:    <cfset client.old_email = form.edtEmail>
44:    <cflocation url="loginMaint.cfm" addToken="no">
45:  </cfif>
46:
47:  <cfif FORM.edtPassword is not FORM.edtCheckPassword>
48:    <cfset client.userName = "Passwords do not match">
49:    <cfset client.detailID = -1>

```



```

50: <cfset client.lookupID = form.userID>
51: <cfset client.hasOldValues = true>
52: <cfset client.old_username = form.edtUsername>
53: <cfset client.old_fullname = form.edtFullname>
54: <cfset client.old_password = ">
55: <cfset client.old_checkPassword = ">
56: <cfset client.old_status = form.edtStatus>
57: <cfset client.old_hint = form.edtHint>
58: <cfset client.old_accessLevel = form.edtAccessLevel>
59: <cfset client.old_displayRows = form.edtDisplayRows>
60: <cfset client.old_email = form.edtEmail>
61:
62: <cflocation url="loginMaint.cfm" addToken="no">
63: <cfelse>
64: <cfif len(trim(form.edtPassword)) is 0 and len(trim(form.edtCheckPassword)) is 0>
65:     <cfif qryFindUser.recordCount is 0>
66:         <cfset client.detailID = -1>
67:         <cfset client.lookupID = form.userID>
68:         <cfset client.hasOldValues = true>
69:         <cfset client.old_username = form.edtUsername>
70:         <cfset client.old_fullname = form.edtFullname>
71:         <cfset client.old_password = ">
72:         <cfset client.old_checkPassword = ">
73:         <cfset client.old_status = form.edtStatus>
74:         <cfset client.old_hint = form.edtHint>
75:         <cfset client.old_accessLevel = form.edtAccessLevel>
76:         <cfset client.old_displayRows = form.edtDisplayRows>
77:         <cfset client.old_email = form.edtEmail>
78:
79:         <cfset client.userName = "You must enter a password.">
80:         <cflocation url="loginMaint.cfm" addToken="no">
81:     </cfif>
82:     <!-- Same password as before -->
83:     <cfset cPassword = qryFindUser.password>
84:     <cfelse>
85:         <!-- Entered a new password -->
86:         <cfset cPassword = hash(form.edtPassword)>
87:     </cfif>
88: </cfif>
89:
90: <cfif isDefined("FORM.btnUpdate")>
91:     <cfset nDistributorID = listGetAt(form.edtControlOver,1,"|")>
92:     <cfset nEntityType = listGetAt(form.edtControlOver,2,"|")>
93:     <cfset nEntityID = listGetAt(form.edtControlOver,3,"|")>
94:     <cfif qryFindUser.recordCount is 0> <!-- Add this user -->
95:         <cfquery name="qryCheckDup" datasource="#ap_dataSource#">
96:             select userName from Security
97:             where userName = '#FORM.edtUserName#'
98:         </cfquery>

```

```

99:
100: <cfif qryCheckDup.recordCount gt 0>
101:   <cfset client.userName = "Sorry. That user name is already in use.">
102:   <cfset client.detailID = -1>
103:   <cfset client.lookupID = form.userID>
104:   <cfset client.hasOldValues = true>
105:   <cfset client.old_username = form.edtUsername>
106:   <cfset client.old_fullname = form.edtFullname>
107:   <cfset client.old_password = ">
108:   <cfset client.old_checkPassword = ">
109:   <cfset client.old_status = form.edtStatus>
110:   <cfset client.old_hint = form.edtHint>
111:   <cfset client.old_accessLevel = form.edtaccessLevel>
112:   <cfset client.old_displayRows = form.edtDisplayRows>
113:   <cfset client.old_email = form.edtEmail>
114:
115:   <cflocation url="loginMaint.cfm" addtoken="no">
116: </cfif>
117:
118: <cfset nDisplayRows = val(#form.edtDisplayRows#)>
119: <cfif nDisplayRows is 0>
120:   <cfset nDisplayRows = 10>
121: </cfif>
122:
123: <cfquery name="qryInsert" datasource="#ap_dataSource">
124:   insert into Security
125:     (userName, password, fullname, Status, Hint, entityType, email,
126:      displayRows, distributorID, accessLevel)
127:   values ('#FORM.edtUserName#', '#cPassword#', '#FORM.edtFullname#',
128:          '#FORM.edtStatus#', '#FORM.edtHint#',
129:          #nEntityID#, #nEntityType#, '#FORM.edtEmail#', #nDisplayRows#,
130:          #nDistributorID#, '#form.edtAccessLevel#')
131: </cfquery>
132: <cfelse>
133:   <cfquery name="qryCheckDup" datasource="#ap_dataSource">
134:     select userName from Security
135:     where userName = '#FORM.edtUserName#'
136:     and userID <> #form.userID#
137:   </cfquery>
138:
139:   <cfif qryCheckDup.recordCount gt 0>
140:     <cfset client.userName = "Sorry. That user name is already in use.">
141:     <cflocation url="loginMaint.cfm" addtoken="no">
142:   </cfif>
143:
144:   <cfset nDisplayRows = val(#form.edtDisplayRows#)>
145:   <cfif nDisplayRows is 0>
146:     <cfset nDisplayRows = 10>
147:   </cfif>

```

```
148: <cfif form.userID is client.userID>
149:   <cfset client.displayRows = nDisplayRows>
150: </cfif>
151:
152: <cfquery name="qryUpdate" datasource="#ap_dataSource#">
153:   update Security
154:   set userName      = '#form.edtUserName#',
155:     password        = '#cPassword#',
156:     fullName        = '#form.edtFullName#',
157:     status          = '#form.edtStatus#',
158:     hint            = '#form.edtHint#',
159:     entityID        = '#nEntityID#',
160:     entityType      = '#nEntityType#',
161:     email            = '#form.edtEmail#',
162:     displayRows     = '#nDisplayRows#',
163:     distributorID   = '#nDistributorID#',
164:     accessLevel     = '#form.edtAccessLevel#',
165:     where security.userID = #FORM.userID#
166: </cfquery>
167: </cfif>
168: <cflocation url="loginAdm.cfm" addtoken="no">
169: <cfelseif isDefined("FORM.btnDelete")>
170:   <cfquery name="qryDelete" datasource="#ap_dataSource#">
171:     delete from security
172:     where security.userID = #FORM.userID#
173:   </cfquery>
174:   <cflocation url="loginAdm.cfm" addtoken="no">
175: </cfif>
```

4.0 Transitional/EN

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN">
2:
3: <cfset client.gotopage = "messages.cfm">
4: <!--
5: <cfinclude template="include\securityTest.cfm">
6: -->
7:
8: <cfparam name="form.SortBy" default="priority,messageSent">
9:
10: <cfparam name="form.displayPage" default="New">
11:
12:
13: <cfif form.displayPage is "New">
14:   <cfquery name="qryMessages" datasource="#ap_dataSource#">
15:     select messages.*
16:     from messages, userMessages
17:     where userMessages.userID = #client.userID#
18:     and userMessages.messageID = messages.messageID
19:     and userMessages.messageRead is NULL
20:   </cfquery>
21:   <cfelseif form.displayPage is "Saved">
22:     <cfquery name="qryMessages" datasource="#ap_dataSource#">
23:       select messages.*
24:       from messages, userMessages
25:       where userMessages.userID = #client.userID#
26:       and userMessages.messageID = messages.messageID
27:       and userMessages.messageRead is not NULL
28:     </cfquery>
29:   <cfelseif form.displayPage is "AllMessages">
30:     <cfquery name="qryMessages" datasource="#ap_dataSource#">
31:       select messages.*
32:       from messages, userMessages
33:       where userMessages.userID = #client.userID#
34:       and userMessages.messageID = messages.messageID
35:     </cfquery>
36:   <cfelseif form.displayPage is "News">
37:
38:   </cfif>
39:
40:   <html>
41:   <head>
42:     <cfoutput>
43:       <title>#client.backOfficeName# Backoffice</title>
44:     </cfoutput>
45:     <link rel="stylesheet" href="style1.css" type="text/css">
46:   </head>
47:
48:   <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
49:     <cfinclude template="include\nocache.cfm">

```

```

50: <p><cfinclude template="include\header.cfm"></p>
51:
52:
53: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
54:   <tr bgcolor="#cccc99">
55:     <td colspan="4">
56:       <span class="hl"><b>User Messages</b></span><nbsp;<span><b>Create a Message</b></span></td>
57:     </tr>
58:   <tr bgcolor="#cccc99">
59:     <td colspan="4">
60:       <form action="messages.cfm" method="post">
61:         <cfoutput>
62:           <input type="hidden" name="sortBy" value="#form.sortBy#">
63:           </cfoutput>
64:
65:           <cfif form.displayPage is "New">
66:             <b>New Messages</b>
67:           <cfelse>
68:             <a href="javascript:document.forms[0].submit();" name="linkNew">[New Messages]</a>
69:           </cfif>
70:           <b><span><b>Saved Messages</b></span></b>
71:           <cfif form.displayPage is "Saved Messages">
72:             <b>Saved Messages</b>
73:           <cfelse>
74:             <a href="javascript:document.forms[0].submit();" name="linkSaved">[Saved Messages]</a>
75:           </cfif>
76:           <b><span><b>News</b></span></b>
77:           <cfif form.displayPage is "News">
78:             <b>News</b>
79:           <cfelse>
80:             <a href="messages.cfm?form.displayPage=News">[News]</a>
81:           </cfif>
82:         </form>
83:       </td>
84:     </tr>
85:   </tr>
86:
87:   <cfif qryMessages.recordCount gt 0>
88:     <tr bgcolor="#cccccc">
89:       <td>Sort by <a href="loginAdm.cfm?sortBy=loginName"><b>Login Name</b></a></td>
90:       <td>Sort by <a href="loginAdm.cfm?sortBy=fullName"><b>Full Name</b></a></td>
91:       <td><b></td>
92:     </tr>
93:   </cfif>
94:
95:   <CFIF qryMessages.recordCount is 0>
96:     <TR>
97:       <TD COLSPAN="3">

```

```
99: <cfif form.displayPage is "New">
100:     <i>You have no new messages.</i>
101: <cfelseif form.displayPage is "Saved">
102:     <i>You have no saved messages.</i>
103: <cfelseif form.displayPage is "News">
104:     <i>There are no news messages.</i>
105: </cfif>
106: </TD>
107: </TR>
108: </CFIF>
109:
110: <cfset lColor = True>
111: <cfloop query="qryMessages">
112:     <cfset lColor = not lColor>
113:     <tr <cfif lColor is TRUE>>bgcolor="eeeeee"</cfif>>
114:         <cfoutput>
115:             <td>#qryMessages.subject#</td>
116:             <td>#qryMessages.messageFrom#</td>
117:             <td><a href="loginMaint.cfm?UserID=#qryUsers.userID#">Edit</a></td>
118:         </cfoutput>
119:     </tr>
120: </cfloop>
121: </table></p>
122:
123: </body>
124: </html>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2: <cfset client.gotopage = "navAdm.cfm">
3:
4: <cfif client.currentEntityType lt #ap_securityMastDist# and client.lookupDistID is -1>
5:   <!-- We do not know what distributor we should be editing, so find out -->
6:   <cfset client.lookupDistID = -1>
7:   <cfset client.lookupAgencyID = -1>
8:   <cfset client.lookupID = -1>
9:   <cfset client.DetailID = -1>
10:  <cflocation url="distSelect.cfm" addToken="no">
11: </cfif>
12:
13: <cfif client.currentEntityType gte #ap_securityMastDist#
14:   <cfset client.lookupDistID = client.currentDistributorID>
15:   <cfelseif client.lookupDistID is -1>
16:     <cflocation url="messages.cfm" addToken="no">
17:   </cfif>
18:
19:   <cfset client.lookupID = -1>
20:   <cfset client.detailID = -1>
21:   <cfset client.imageType = -1>
22:   <cfset client.lookupAgencyID = -1>
23:
24:   <cflocation url="navMaint.cfm" addToken="no">
25:
26: <html>
27: <head>
28:   <cfoutput>
29:     <title>#client.backofficeName# Backoffice Navigation Administration</title>
30:   </cfoutput>
31:   <link rel="stylesheet" href="style1.css" type="text/css">
32: </head>
33:
34:
35: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
36: <cfinclude template="include\nocache.cfm">
37:
38: </body>
39: </html>
40:

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfset client.gotoPage = " navigationAdm.cfm">
4: <!--
5: <cfinclude template="include\securityTest.cfm">
6: -->
7:
8: <cfparam name="URL.sortBy" default="name">
9: <cfset client.lookupID = -1>
10: <cfset client.detailID = -1>
11:
12: <!-- Display rows -->
13: <cfparam name="nStartFrom" default="1">
14: <cfparam name="nToDisplay" default="#client.displayRows#">
15: <cfparam name="nEnd" default="#client.displayRows#">
16:
17:
18: <cfquery name="qryEditList" dataSource="#ap_dataSource#">
19:   select portals.portalID, portals.name, portals.dataPath
20:   from portals
21: </cfquery>
22:
23: <html>
24: <head>
25:   <cfoutput>
26:     <title>#client.backofficeName# Backoffice</title>
27:   </cfoutput>
28:   <link rel="stylesheet" href="style1.css" type="text/css">
29: </head>
30:
31:
32: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
33: <cfinclude template="include\nocache.cfm">
34: <p><cfinclude template="include\header.cfm"></p>
35:
36: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
37:   <tr bgcolor="#cccc99">
38:     <td colspan="4">
39:       <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">
40:         <tr>
41:           <td align="left">
42:             <span class="h2"><b>Portal Administration</b></span>
43:           </td>
44:           <td align="right">
45:             <cfif #nToDisplay# gte qryEditList.recordCount>
46:               <cfset cToDisplay = min(qryEditList.recordCount, #nToDisplay#)>
47:             </cfif>
48:             <cfif qryEditList.recordCount gte #nToDisplay#>
49:               <cfset cToDisplay = min(qryEditList.recordCount, #nEnd#)>

```



```

50: </cfif>
51: <cfset cStartFrom = min(qryEditList.recordCount, #nStartFrom#)>
52: <cfoutput>(Viewing records #cStartFrom# to #cToDisplay# out of #qryEditList.recordCount#)</cfoutput>
53: </td>
54: </tr>
55: </table>
56: </td>
57: </tr>
58: <tr bgcolor="#cccc99">
59: <td colspan="4">
60: <b>Add a portal</a>
61: </td>
62: </tr>
63:
64: <tr bgcolor="#cccccc">
65: <td>Sort by <a href="portalAdm.cfm?SortBy=name"><b>Name</b></a></td>
66: <td>Sort by <a href="portalAdm.cfm?SortBy=dataPath"><b>Data Path</b></a></td>
67: <td></td>
68: <td></td>
69: </tr>
70:
71:
72: <CFIF qryEditList.recordCount is 0>
73: <TR><TD COLSPAN="3"><I>There are no portals defined</I></TD></TR>
74: </CFIF>
75: <cfset lColor = True>
76: <form action="portalMaint.cfm" method="post">
77: <cfoutput query="qryEditList" startrow="#nStartFrom#" maxrows="#nToDisplay#">
78: <cfset lColor = not lColor>
79: <tr valign="center" <cfif _Color is TRUE>bgcolor="#ffffff"</cfif>>
80: <td>#qryEditList.name#</td>
81: <td>#qryEditList.dataPath#</td>
82: <td></td>
83: <td align="center"><input type="image" name="edit#qryEditList.distributorID#" src="#ap_commonImages#edit.gif" alt="Edit" border="0"></td>
84: </tr>
85: </cfoutput>
86: </form>
87: </table></p>
88:
89: <CFSET nPrevStart = nStartFrom-nToDisplay>
90: <CFSET nNextStart = nStartFrom+nToDisplay>
91: <CFSET nPrevEnd = #nPrevStart#+nToDisplay-1>
92: <CFSET nNextEnd = #nNextStart#+nToDisplay-1>
93: <cfif nPrevStart gte 1 or nNextStart lte qryEditList.recordCount>
94: <table border="0" align="center">
95: <tr>
96: <cfif nPrevStart gte 1>
97: <tc>

```

```

98: <form action="portalAdm.cfm?sortBy=#url#sortBy#" METHOD="POST">
99:   <input type="hidden" name="nStartFrom" value="#nPrevStart#">
100:   <input type="hidden" name="nToDisplay" value="#nToDisplay#">
101:   <input type="hidden" name="nEnd" value="#nPrevEnd#">
102:   <input type="submit" value="Previous #nToDisplay#">
103: </FORM>
104: </td>
105: </cfif>
106: <cfif nNextStart lte qryEditList.recordCount>
107:   <td>
108:     <form action="portalAdm.cfm?sortBy=#url#sortBy#" METHOD="POST">
109:       <input type="hidden" name="nStartFrom" value="#nNextStart#">
110:       <input type="hidden" name="nToDisplay" value="#nToDisplay#">
111:       <input type="hidden" name="nEnd" value="#nNextEnd#">
112:       <cfset nLeftToShow = min(nToDisplay, (qryEditList.recordcount - cToDisplay))>
113:       <input type="submit" value="Next #nLeftToShow#">
114:     </form>
115:   </td>
116: </cfif>
117: </tr>
118: </table>
119: </cfif>
120:
121: </body>
122: </html>
123:

```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfif client.currentEntityType gte #ap_securityMastDist#>
4:    <cfset client.lookupDistID = client.currentEntityID>
5:  </cfif>
6:
7:  <cfif not isDefined("client.lookupDistID") or client.lookupDistID is "-1">
8:    <cflocation url="distAdm.cfm" addToken="no">
9:  </cfif>
10:  <cfparam name="client.userMessage" default="">
11:
12:  <cfquery name="qryFindDist" datasource="#ap_dataSource#">
13:    select distributors.templateID, distributors.name
14:    from distributors
15:    where distributors.distributorID = #client.lookupDistID#
16:  </cfquery>
17:
18:  <cfif qryFindDist.recordCount gt 0>
19:    <cfset nDistributorID = client.lookupDistID>
20:  <cfelse>
21:    <cfset client.lookupID = -1>
22:    <cfset client.detailID = -1>
23:    <cfset client.userMessage = "">
24:    <cflocation url="distAdm.cfm" addToken="no">
25:  </cfif>
26:
27:  <cfinclude template="include\javaValidate.cfm">
28:
29:  <script language="JavaScript">
30:    <!--
31:    function validate(testform) {
32:      var results = "";
33:      var lResult = true;
34:
35:      if (!lResult) {
36:        window.alert(results);
37:      }
38:      return lResult;
39:    }
40:  -->
41:  </script>
42:
43:  <html>
44:  <head>
45:    <cfoutput>
46:    <title>#client.backofficeName# Backoffice Navigation Maintenance</title>
47:    </cfoutput>
48:    <link rel="stylesheet" href="style1.css" type="text/css">
49:

```

```

50: </head>
51:
52: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
53: <cfinclude template="include\nocache.cfm">
54:
55: <p><cfinclude template="include\header.cfm"></p>
56:
57: <cfoutput>
58:
59: <form action="navUpdate.cfm" method="post" onsubmit="return validate(this)">
60:   <input type="hidden" name="distributorID" value="#nDistributorID#">
61:   <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
62:     <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Navigation Bar Maintenance for #qryFindDist.name#</b></span>
63:       <cfif client.lookupDistID is -1>
64:         <b> (Create a navigation menu bar)
65:       </cfif>
66:     </td></tr>
67:
68:     <CFIF client.userName is not "">
69:       <tr bgcolor="eeeeee">
70:         <td colspan="5"><p><font color="red">#client.userName#</font></p></td>
71:       </tr>
72:       <tr bgcolor="eeeeee"><td colspan="5"><b><td colspan="5"></td></tr>
73:     </CFIF>
74:     <cfset client.userName = "">
75:
76:     <tr bgcolor="##eeeeee">
77:       <td colspan="5">Navigation Color:</td>
78:       <td colspan="4">
79:         <select name="edtNavColor">
80:           <option value="##330099">Red
81:           <option value="##330099">Blue
82:           <option value="##330099">Green
83:         </select>
84:       </td>
85:
86:     <tr bgcolor="eeeeee">
87:       <cfif qryFindDist.recordCount is 0>
88:         <td colspan="5">
89:           <input type="submit" name="btnUpdate" value="Add Template">
90:           <input type="reset" value="Reset Info">
91:         </td>
92:       <cfelse>
93:         <td colspan="5">
94:           <input type="submit" name="btnUpdate" value="Update Navigation">
95:           <input type="reset" value="Reset Info">
96:           <input type="submit" name="btnView" value="View Navigation">
97:         </td>
98:

```

```

99:         <td align="right">
100:             <input type="submit" name="btnDelete" value="Delete Navigation">
101:         </td>
102:     </tr>
103: </cfif>
104: </tr>
105: </table>
106: </form>
107: </cfoutput>
108:
109: <!-- If this community page has already been created, allow paragraph editing -->
110:
111: <cfif qryFindDist.recordCount gt 0>
112:     <script language="JavaScript">
113:         <!--
114:         function validateDetail(testform) {
115:             var results = "";
116:             var lResult = true;
117:
118:             if ((removeSpaces(testform.edtSortOrder.value) != "") && (!isNumber(testform.edtSortOrder.value))) {
119:                 results = results + " * " + testform.edtSortOrder.value + " is not a valid numeric sort order value.\r";
120:                 lResult = false;
121:             }
122:
123:             if (!lResult) {
124:                 window.alert(results);
125:             }
126:
127:             return lResult;
128:         }
129:     </script>
130:
131:     <cfquery name="qryDetail" dataSource="#ap_dataSource#">
132:         select navigation.*
133:         from navigation
134:         where navigation.distributorID = #client.lookupDistID#
135:         order by navigation.sortOrder
136:     </cfquery>
137:
138:
139:     <cfquery name="qryEdit" dataSource="#ap_dataSource#">
140:         select navigation.*
141:         from navigation
142:         where navigation.distributorID = #client.lookupDistID#
143:         and navigation.navItemID = #client.detailID#
144:     </cfquery>
145:
146:     <!-- Set default values -->
147:     <cfif isdefined("client.old_sortOrder")>

```

```

148:      <cfset nSortOrder = client.old_sortOrder>
149:      <cfelseif qryEdit.recordCount is 1>
150:      <cfset nSortOrder = qryEdit.sortOrder>
151:      <cfelseif qryDetail.recordCount gt 0>
152:      <cfquery name="qryMax" dataSource="#ap_dataSource#">
153:          select max(sortOrder) as maxOrder
154:          from navigation
155:          where navigation.distributorID = #client.lookupDistID#
156:      </cfquery>
157:      <cfset nSortOrder = qryMax.maxOrder + 1>
158:      <cfelse>
159:      <cfset nSortOrder = qryEdit.sortOrder>
160:      </cfif>
161:
162:      <cfif isDefined("client.old_menuText")>
163:      <cfset cMenuText = client.old_menuText>
164:      <cfelse>
165:      <cfset cMenuText = trim(qryEdit.menuText)>
166:      </cfif>
167:      <cfif isDefined("client.old_menuURL")>
168:      <cfset cMenuURL = client.old_menuURL>
169:      <cfelse>
170:      <cfset cMenuURL = trim(qryEdit.menuURL)>
171:      </cfif>
172:
173:      <form action="navUpdate.cfm" method="post" onSubmit="return validateDetail(this)">
174:      <cfoutput>
175:      <input type="hidden" name="distributorID" value="#client.lookupDistID#">
176:      <input type="hidden" name="navItemID" value="#client.detailID#">
177:      </cfoutput>
178:
179:      <cfif qryDetail.recordCount is 0>
180:      <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
181:      <tr><td colspan="4"><i><b>There are no navigation links defined.</b></i></td></tr>
182:      <tr><td colspan="4"><nbsp></td></tr>
183:      </table>
184:      <cfelse>
185:      <table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
186:      <tr valign="top" bgcolor="#cccccc">
187:      <td><b>Menu Text</b></td>
188:      <td><b>Menu URL</b></td>
189:      <td><b>Sort Order</b></td>
190:      <td><nbsp></td>
191:      <td><nbsp></td>
192:      </tr>
193:      <cfoutput query="qryDetail">
194:      <tr valign="top" bgcolor="#"><cfif qryDetail.navItemID is client.detailID>#ffffff<cfelse>#eeeeee</cfif>>
195:      <td>
196:      <cfif trim(qryDetail.menuText) is ""><nbsp></cfif>#qryDetail.menuText#

```

```

197:         </td>
198:     </td>
199:     <cfif trim(qryDetail.menuURL) is "">&nbsp;</cfif>#qryDetail.menuURL#
200: </td>
201: <td>#qryDetail.sortOrder#</td>
202: <td align="center">
203:     <input type="image" name="edit#qryDetail.navItemID#" src="#ap_commonImages#edit.gif" alt="Edit" border="0">
204: </td>
205: <td align="center">
206:     <cfif qryDetail.systemLink is "Y">
207:         &nbsp;<
208:     <cfelse>
209:         <input type="image" name="delete#qryDetail.navItemID#" src="#ap_commonImages#delete.gif" alt="Delete"
border="0">
210:     </cfif>
211: </td>
212: </tr>
213: </cfoutput>
214: </table>
215: </cfif>
216: <cfoutput>
217: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
218: <tr><td colspan="3">&nbsp;</td></tr>
219: <cfif client.detailID is -1>
220:     <tr bgcolor="##cccccc"><td colspan="3"><b>Add a navigation link</b></td></tr>
221: <cfelse>
222:     <tr bgcolor="##cccccc"><td colspan="3"><b>Edit this navigation link</b></td></tr>
223: </cfif>
224: <tr valign="top" bgcolor="##eeeeee">
225: <td><b>Menu Text</b></td>
226: <td><b>Menu URL</b></td>
227: <td><b>Order</b></td>
228: </tr>
229: <tr valign="top" bgcolor="##eeeeee">
230: </td>
231: <td>
232:     <cfif ucase(trim(qryEdit.menuText)) is "***SPECIALTY PAGES**">
233:         <input type="hidden" name="edtMenuText" value="#cMenuText#">
234:         #cMenuText#
235:     <cfelse>
236:         <input type="text" name="edtMenuText" value="#cMenuText#" size="25" maxlength="25">
237:     </cfif>
238: </td>
239: <td>
240:     <cfif qryEdit.systemLink is "Y">
241:         <input type="hidden" name="edtMenuURL" value="#cMenuURL#">
242:         #cMenuURL#
243:     <cfelse>
244:         <input type="text" name="edtMenuURL" value="#cMenuURL#" size="40" maxlength="120">

```

```
245:         </cfif>
246:     </td>
247:     <td><input type="text" name="edtSortOrder" value="#nSortOrder#" size="2" maxlength="2"></td>
248: </tr>
249:
250: <tr bgcolor="eeeeee">
251:     <td colspan="3">
252:         <cfif qryEdit.recordCount is 0>
253:             <input type="submit" name="btnUpdateDetail" value="Add Link">
254:             <input type="reset" value="Reset Info">
255:         <cfelse>
256:             <input type="submit" name="btnUpdateDetail" value="Update Link">
257:             <input type="reset" value="Reset Info">
258:             <input type="submit" name="btnCancelDetail" value="Cancel">
259:         </cfif>
260:     </td>
261: </tr>
262: </table>
263: </cfoutput>
264: </form>
265: </cfif>
266:
267: </body>
268: </html>
```



```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3:  <cfif not isDefined("form.distributorID")>
4:    <cfset client.lookupID = -1>
5:    <cfset client.detailID = -1>
6:    <cfset client.imageType = -1>
7:    <cfset client.userName = "">
8:    <cflocation url="messages.cfm" addtoken="no">
9:  </cfif>
10:
11:  <cfquery name="qryFindDist" datasource="#ap_dataSource#">
12:    select distributors.distributorID
13:    from distributors
14:    where distributors.distributorID = #form.distributorID#
15:  </cfquery>
16:
17:  <cfif qryFindDist.recordCount is 0>
18:    <cfset client.lookupID = -1>
19:    <cfset client.detailID = -1>
20:    <cfset client.imageType = -1>
21:    <cfset client.userName = "">
22:    <cflocation url="messages.cfm" addtoken="no">
23:  </cfif>
24:
25:  <cfinclude template="include\clearOldFields.cfm">
26:  <cfset client.userName = "">
27:
28:  <cfif isDefined("form.btnCancelDetail")> <!-- Cancel detail edit -->
29:    <cfset client.lookupID = #form.distributorID#>
30:    <cfset client.detailID = -1>
31:    <cfset client.imageType = -1>
32:    <cfset client.userName = "">
33:    <cflocation url="navMaint.cfm" addtoken="no">
34:
35:  <cfelseif isDefined("form.btnCancelDelete")> <!-- Cancel detail edit -->
36:    <cfset client.lookupID = #form.agencyID#>
37:    <cfset client.detailID = -1>
38:    <cfset client.imageType = -1>
39:    <cfset client.userName = "Deletion canceled.">
40:    <cflocation url="navMaint.cfm" addtoken="no">
41:
42:  <cfelseif isDefined("form.btnView")>
43:    <cflocation url="../navView.cfm?distributorID=#form.distributorID# addtoken="no">
44:
45:  <cfelseif isDefined("form.btnUpdateDetail")>
46:    <cfquery name="qryFindDetail" datasource="#ap_dataSource#">
47:      select navItemID
48:      from navigation
49:      where navigation.navItemID = #form.navItemID#

```

```

50: </cfquery>
51:
52: <cfif qryFindDetail.recordCount is 0>
53:   <cfset cMenuText = preserveSingleQuotes(form.edtMenuText)>
54:   <cfset cMenuURL = preserveSingleQuotes(form.edtMenuURL)>
55:   <cfset nSortOrder = val(form.edtSortOrder)>
56:
57:   <cftransaction>
58:     <cfquery name="qryInsert" dataSource="#ap_dataSource#">
59:       insert into navigation
60:         (distributorID, menuText, menuURL, sortOrder, systemLink)
61:       values
62:         (#form.distributorID#, '#cMenuText#', '#cMenuURL#', #nSortOrder#, 'N')
63:     </cfquery>
64:   </cftransaction>
65:
66:   <cfset client.lookupID = form.distributorID>
67:   <cfset client.detailID = -1>
68:
69:   <cflocation url="navMaint.cfm" addToken="no">
70:
71: <cfelse>
72:   <cfset cMenuText = preserveSingleQuotes(form.edtMenuText)>
73:   <cfset cMenuURL = preserveSingleQuotes(form.edtMenuURL)>
74:   <cfset nSortOrder = val(form.edtSortOrder)>
75:
76:   <cftransaction>
77:     <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
78:       update navigation
79:       set
80:         menuText = '#cMenuText#',
81:         menuURL = '#cMenuURL#',
82:         sortOrder = #nSortOrder#
83:       where navigation.navItemID = #form.navItemID#
84:     </cfquery>
85:   </cftransaction>
86:
87:   <cfset client.lookupID = form.distributorID>
88:   <cfset client.detailID = -1>
89:
90:   <cflocation url="navMaint.cfm" addToken="no">
91:
92: </cfif>
93:
94: <cfelseif isDefined("form.btnUpdate")>
95:   <cfset client.lookupID = form.distributorID>
96:   <cfset client.detailID = -1>
97:   <cfset client.userName = "There was an error while updating the navigation information.">
98:   <cftransaction>

```

```

99: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
100:   update distributors
101:     set navColor = '#form.edtNavColor#'
102:   where distributors.distributorID = #form.distributorID#
103: </cfquery>
104:
105: <cfset client.detailID = -1>
106: <cfset client.userName = "Navigation information was updated.">
107: </cftransaction>
108:
109: <cfif client.lookupID gt 0>
110:   <cflocation url="navMaint.cfm" addToken="no">
111: <cfelse>
112:   <cflocation url="messages.cfm" addToken="no">
113: </cfif>
114: </cfif>
115:
116: <cfset client.lookupID = -1>
117: <cfset client.detailID = -1>
118: <cfset client.imageType = -1>
119: <!-- Get ID number from edit -->
120: <cfloop collection="#form#" item="cName">
121:   <cfif ucCase(left(cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
122:     <cfset cValue = mid(cName#, 5, len(cName#)-6)>
123:     <cfset client.lookupID = form.distributorID>
124:     <cfset client.detailID = val(cValue)>
125:   </cfif>
126:
127:   <cfif client.lookupID gt -1 and client.detailID gt -1>
128:     <cflocation url="navMaint.cfm" addToken="no">
129:   </cfif>
130: </cfloop>
131:
132: <!-- Get ID number for delete detail item -->
133: <cfloop collection="#form#" item="cName">
134:   <cfif ucCase(left(cName#,6)) is "DELETE" and findNoCase(".X", #cName#,1) gt 0>
135:     <cfset cValue = mid(cName#, 7, len(cName#)-8)>
136:     <cfset client.lookupID = form.distributorID>
137:     <cfset client.detailID = val(cValue)>
138:     <cfset client.imageType = -1>
139:   </cfif>
140:
141:   <cfif client.lookupID gt -1 and client.lookupID gt -1>
142:     <cfset client.userName = "Unable to delete link.">
143:   </cftransaction>
144:   <cfquery name="qryDelete" dataSource="#ap_dataSource#">
145:     delete from navigation
146:     where navigation.navitemID = #client.detailID#
147:   </cfquery>

```

```
148:         <cfset client.detailID = -1>
149:         <cfset client.userName = "Navigation link deleted.">
150:         </cftransaction>
151:         <cflocation url="navMaint.cfm" addToken="no">
152:         </cfif>
153:         </cfloop>
154:
155:         <!--- If anything else, then go back to the admin page --->
156:         <cflocation url="messages.cfm" addToken="no">
157:
158:
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3: <cfset client.gotoPage = "portalAdm.cfm">
4: <!--
5: <cfinclude template="include\securityTest.cfm">
6: -->
7:
8: <cfparam name="URL.sortBy" default="portalName">
9: <cfset client.lookupID = -1>
10: <cfset client.detailID = -1>
11: <cfset client.lookupDistID = -1>
12: <cfset client.lookupAgencyID = -1>
13:
14:
15: <!-- Display rows -->
16: <cfparam name="nStartFrom" default="1">
17: <cfparam name="nToShow" default="#client.displayRows#">
18: <cfparam name="nEnd" default="#client.displayRows#">
19:
20:
21: <cfquery name="qryEditList" dataSource="#ap_dataSource#"
22: select portals.portalID, portals.name as portalName, portals.dataPath
23: from portals
24: join securityAccess on
25: securityAccess.entityType = #ap_securityPortal#
26: and securityAccess.entityID = portals.portalID
27: and securityAccess.hierarchyID like '#client.hierarchyID#',
28: order by #url.sortBy#
29: </cfquery>
30:
31: <html>
32: <head>
33: <cfoutput>
34: <title>#client.backofficeName# Backoffice</title>
35: </cfoutput>
36: <link rel="stylesheet" href="style1.css" type="text/css">
37: </head>
38:
39:
40: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
41: <cfinclude template="include\nocache.cfm">
42: <p><cfinclude template="include\header.cfm"></p>
43:
44: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
45: <tr bgcolor="#cccc99">
46: <td colspan="4">
47: <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">
48: <tr>
49: <td align="left">

```

```

50: <span class="h2"><b>Portal Administration</b></span>
51: </td>
52: <td align="right">
53: <cfif #ntoDisplay# gte qryEditList.recordCount>
54: <cfset cToDisplay = min(qryEditList.recordCount, #ntoDisplay#)>
55: </cfif>
56: <cfif qryEditList.recordCount gte #ntoDisplay#>
57: <cfset cToDisplay = min(qryEditList.recordCount, #nEnd#)>
58: </cfif>
59: <cfset cStartFrom = min(qryEditList.recordCount, #nStartFrom#)>
60: <cfoutput>{Viewing records #cstartFrom# to #cToDisplay# out of #qryEditList.recordCount#}</cfoutput>
61: </td>
62: </tr>
63: </table>
64: </td>
65: </tr>
66: <cfif trim(client.userName) is not "">
67: <tr bgcolor="#cccc99">
68: <td colspan="4" align="center">
69: <cfoutput><b><cfset client.userName#</b></cfoutput>
70: </td>
71: </tr>
72: </cfif>
73: <cfset client.userName = "">
74: <cfset client.lookupID = -1>
75: <cfset client.detailID = -1>
76:
77: <tr bgcolor="#cccc99">
78: <td colspan="4">
79: <b><cfset client.userName#</b></td>
80: </td>
81: </tr>
82:
83: <tr bgcolor="#cccccc">
84: <td>Sort by <a href="portalAdm.cfm?SortBy=portalName"><b>Name</b></a></td>
85: <td>Sort by <a href="portalAdm.cfm?SortBy=dataPath"><b>Data Path</b></a></td>
86: <td><b></td>
87: <td align="center">Portal Info</td>
88: </tr>
89:
90:
91: <CFIF qryEditList.recordCount is 0>
92: <TR><TD COLSPAN="3"><I>There are no portals defined</I></TD></TR>
93: </CFIF>
94: <cfset lColor = True>
95: <form action="portalMaint.cfm" method="post">
96: <cfoutput query="qryEditList" startrow="#nstartFrom#" maxrows="#ntoDisplay#">
97: <cfset lColor = not lColor>
98: <tr valign="center" <cfif lColor is TRUE>bgcolor="#eeeeee"</cfif>>

```

```

99:      <td>#qryEditList.portalName#</td>
100:      <td>#qryEditList.dataPath#</td>
101:      <td><b>nbsp;</td>
102:      <td align="center"><input type="image" name="edit#qryEditList.portalID#" src="#ap_commonImages#edit.gif" alt="Edit"
      border="0"></td>
103:      </tr>
104:      </cfoutput>
105:      </form>
106:      </table></p>
107:
108:      <cfoutput>
109:      <CFSET nPrevStart = nStartFrom-nToDisplay>
110:      <CFSET nNextStart = nStartFrom+nToDisplay>
111:      <CFSET nPrevEnd = #nPrevStart#+nToDisplay-1>
112:      <CFSET nNextEnd = #nNextStart#+nToDisplay-1>
113:      <cfif nPrevStart gte 1 or nNextStart lte qryEditList.recordCount>
114:      <table border="0" align="center">
115:      <tr>
116:      <cfif nPrevStart gte 1>
117:      <td>
118:      <form action="portalAdm.cfm?sortBy=#url.sortBy#&url.sortBy#" METHOD="POST">
119:      <input type="hidden" name="nStartFrom" value="#nPrevStart#">
120:      <input type="hidden" name="nToDisplay" value="#nToDisplay#">
121:      <input type="hidden" name="nEnd" value="#nPrevEnd#">
122:      <input type="submit" value="Previous #nToDisplay#">
123:      </FORM>
124:      </td>
125:      </cfif>
126:      <cfif nNextStart lte qryEditList.recordCount>
127:      <td>
128:      <form action="portalAdm.cfm?sortBy=#url.sortBy#&url.sortBy#" METHOD="POST">
129:      <input type="hidden" name="nStartFrom" value="#nNextStart#">
130:      <input type="hidden" name="nToDisplay" value="#nToDisplay#">
131:      <input type="hidden" name="nEnd" value="#nNextEnd#">
132:      <cfset nLeftToShow = min(nToDisplay, (qryEditList.recordcount - cToDisplay))>
133:      <input type="submit" value="Next #nLeftToShow#">
134:      </form>
135:      </td>
136:      </cfif>
137:      </tr>
138:      </table>
139:      </cfif>
140:      </cfoutput>
141:
142:      </body>
143:      </html>
144:

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3: <!-- Get ID number from edit -->
4: <cfloop collection="#form#" item="cName">
5:   <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
6:     <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
7:     <cfset client.lookupID = val(cValue)>
8:     <cfset client.detailID = -1>
9:     </cfif>
10:   </cfloop>
11:
12: <cfif not isDefined("client.lookupID")>
13:   <cflocation url="portalAdm.cfm" addToken="no">
14: </cfif>
15: <cfparam name="client.userName" default="">
16:
17: <cfquery name="qryFindPortal" datasource="#ap_dataSource#">
18:   select * from portals
19:   where portals.portalID = #client.lookupID#
20: </cfquery>
21:
22: <cfif qryFindPortal.recordCount gt 0>
23:   <cfset nPortalID = qryFindPortal.portalID>
24: <cfelse>
25:   <cfset nPortalID = -1>
26: </cfif>
27:
28:
29:
30: <script language="JavaScript">
31: <!--
32:   function validate(testform) {
33:     if (testform.edtPortalName.value == "") {
34:       window.alert("Please enter a name for the portal.");
35:       return false;
36:     }
37:
38:     if (testform.edtDataPath.value == "") {
39:       window.alert("Please enter a valid data path.");
40:       return false;
41:     }
42:
43:     if (testform.edtURL.value == "") {
44:       window.alert("Please enter the URL to reach the main WWW portal site.");
45:       return false;
46:     }
47:
48:     return true;
49:   }

```



```

50:  <!-->
51:  </script>
52:
53:  <html>
54:  <head>
55:    <cfoutput>
56:    <title>#client.backofficeName# Backoffice Portal Maintenance</title>
57:    </cfoutput>
58:    <link rel="stylesheet" href="style1.css" type="text/css">
59:  </head>
60:
61:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
62:  <cfinclude template="include\nocache.cfm">
63:
64:  <p><cfinclude template="include\header.cfm"></p>
65:
66:  <cfoutput>
67:
68:  <form action="portalUpdate.cfm" method="post" onSubmit="return validate(this)">
69:    <input type="hidden" name="portalID" value="#nportalID#">
70:
71:    <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
72:      <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Portal Maintenance</b></span>
73:        <cfif client.lookupID is -1>
74:          &nbsp;<b>? (Create a new portal)
75:        </cfif>
76:      </td></tr>
77:
78:      <CFIF client.userMessage is not "">
79:        <tr bgcolor="eeeeee">
80:          <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td>
81:        </tr>
82:        <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
83:      </CFIF>
84:      <cfset client.userMessage = "">
85:
86:      <tr bgcolor="eeeeee">
87:        <td width="15%">Portal Name:</td>
88:        <td colspan="4"><input type="text" name="edtPortalName" value="#qryFindPortal.Name#" size="60"></td>
89:      </tr>
90:      <tr bgcolor="eeeeee">
91:        <td width="15%">Data Path:</td>
92:        <td colspan="4"><input type="text" name="edtDataPath" value="#qryFindPortal.dataPath#" size="60"></td>
93:      </tr>
94:      <tr bgcolor="eeeeee">
95:        <td width="15%">WWW URL:</td>
96:        <td colspan="4"><input type="text" name="edtURL" value="#qryFindPortal.url#" size="60"></td>
97:      </tr>
98:

```

```
99: <tr bgcolor="eeeeee">
100: <td width="15%">Status:</td>
101: <td width="34%">
102: <select name="edtStatus">
103: <option value="Enabled" <cfif qryFindPortal.Status is "Enabled" or nPortalID is -1> selected</cfif>>Enabled
104: <option value="Disabled" <cfif qryFindPortal.Status is "Disabled"> selected</cfif>>Disabled
105: <option value="Admin Only" <cfif qryFindPortal.Status is "Admin Only"> selected</cfif>>Admin Only
106: </select>
107: </td>
108: <td width="2%">&nbsp;</td>
109: <td colspan="2">&nbsp;</td>
110: </tr>
111:
112: <tr bgcolor="eeeeee">
113: <td colspan="5">
114: <cfif qryFindPortal.recordCount is 0>
115: <input type="submit" name="btnUpdate" value="Add Portal">
116: <input type="reset" value="Reset Info">
117: <cfelse>
118: <input type="submit" name="btnUpdate" value="Update Portal Info">
119: <input type="reset" value="Reset Info">
120: <input type="submit" name="btnDelete" value="Delete Portal">
121: </cfif>
122: </td>
123: </tr>
124: </table>
125: </form>
126:
127: </cfoutput>
128:
129: </body>
130: </html>
```

-----  
 4.0 Transitional/EN

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN">
2:
3: <cfif not isDefined("form.portalID")>
4:   <cfset client.lookupID = -1>
5:   <cfset client.detailID = -1>
6:   <cfset client.userName = "">
7:   <cflocation url="portalAdm.cfm" addtoken="no">
8: </cfif>
9:
10: <cfquery name="qryFindPortal" datasource="#ap_dataSource#">
11:   select portalID, name
12:   from portals
13:   where portals.portalID = #form.portalID#
14: </cfquery>
15:
16: <cfinclude template="include\clearOldFields.cfm">
17: <cfset client.userName = "">
18:
19: <!--- Save form values in case something is wrong -->
20:
21: <cfif isDefined("form.btnUpdate")>
22:   <cfif qryFindPortal.recordCount is 0>
23:     <cfset client.lookupID = -1>
24:     <cfset client.detailID = -1>
25:     <cfset client.userName = "There was an error while creating the portal.">
26:     <cftransaction>
27:       <cfset cName = preservesingleQuotes(form.edtPortalName)>
28:       <cfset cPath = preservesingleQuotes(form.edtDataPath)>
29:       <cfset cURL = preservesingleQuotes(form.edtURL)>
30:
31:       <cfquery name="qryInsert" datasource="#ap_dataSource#">
32:         insert into portals
33:           (name, dataPath, URL, status)
34:         values
35:           ('#cName', '#cPath', '#cURL', '#form.edtStatus#')
36:       </cfquery>
37:
38:       <cfset client.userName = form.edtPortalName & " Portal was created.">
39:     </cftransaction>
40:
41:     <cflocation url="portalAdm.cfm" addtoken="no">
42:   <cfelse>
43:     <cfset client.lookupID = -1>
44:     <cfset client.detailID = -1>
45:     <cfset client.userName = "There was an error while updating the portal information.">
46:     <cftransaction>
47:       <cfset cName = preservesingleQuotes(form.edtPortalName)>
48:       <cfset cPath = preservesingleQuotes(form.edtDataPath)>
49:

```

```
50: <cfset cURL = preservesingleQuotes(form.edtURL)>
51:
52: <cfquery name="qryUpdate" datasource="#ap_dataSource#">
53:     update portals
54:     set name = '#cName#',
55:     dataPath = '#cPath#',
56:     URL = '#cURL#',
57:     status = '#form.edtStatus#'
58:     where portals.portalID = #form.portalID#
59: </cfquery>
60:
61: <cfset client.userName = #form.edtPortalName# & " portal was saved">
62: </cftransaction>
63: <cflocation url="portalAdm.cfm" addToken="no">
64: </cfif>
65: <cfelseif isDefined("form.btnDelete")>
66:     <cfset client.lookupID = -1>
67:     <cfset client.detailID = -1>
68:     <cfset client.userName = "Unable to delete #form.edtPortalName#">
69:     <cftransaction>
70:         <cfquery name="qryDelete" datasource="#ap_dataSource#">
71:             delete from portals
72:             where portals.portalID = #form.portalID#
73:         </cfquery>
74:         <cfset client.userName = #form.edtPortalName# & " portal was deleted">
75:         </cftransaction>
76:         <cflocation url="portalAdm.cfm" addToken="no">
77:         </cfif>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <cfset client.gotoPage = "propertyAdm.cfm">
4:
5: <!--
6: <cfinclude template="include\securityTest.cfm">
7: -->
8:
9: <cfparam name="URL.sortBy" default="propertyName">
10: <cfset client.lookupID = -1>
11: <cfset client.detailID = -1>
12: <cfset client.lookupDistID = -1>
13: <cfset client.lookupAgencyID = -1>
14:
15: <!-- Display Rows -->
16: <cfparam name="nStartFrom" default="1">
17: <cfparam name="ntoDisplay" default="#client.displayRows#">
18: <cfparam name="nEnd" default="#client.displayRows#">
19:
20:
21: <cfquery name="qryEditList" dataSource="#ap_dataSource#">
22:   select prop_main.prop_id,prop_main.name as propertyName, prop_main.address, prop_main.price,
23:     prop_main.mls_no, agents.lastName + ', ' + agents.firstName as agentName
24:   from prop_main
25:   join securityAccess on
26:     securityAccess.entityType = #ap_securityAgent#
27:   and securityAccess.entityID = prop_main.agent_id
28:   and securityAccess.hierarchyID like '#client.hierarchyID#%'
29:   left outer join agents
30:     on agents.agent_id = prop_main.agent_id
31:   order by #url.sortBy#
32: </cfquery>
33:
34: <html>
35: <head>
36:   <cfoutput>
37:     <title>#client.backofficeName# Property Admin</title>
38:   </cfoutput>
39:   <link rel="stylesheet" href="style1.css" type="text/css">
40: </head>
41:
42:
43: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
44: <cfinclude template="include\nocache.cfm">
45: <p><cfinclude template="include\header.cfm"></p>
46:
47: <cfif client.currentEntityType is not ap_securityAgent>
48:   <cfset nColumns = 6>
49: <cfelse>

```

```

50: <cfset nColumns = 5>
51: </cfif>
52:
53:
54: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
55: <tr bgcolor="#cccc99">
56: <cfoutput>
57: <td colspan="#nColumns#">
58: <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">
59: <tr>
60: <td align="left">
61: <span class="h2"><b>Property Administration</b></span>
62: </td>
63: <td align="right">
64: <cfif #nToDisplay# gte qryEditList.recordCount>
65: <cfset cToDisplay = min(qryEditList.recordCount, #nToDisplay#)>
66: </cfif>
67: <cfif qryEditList.recordCount gte #nToDisplay#>
68: <cfset cToDisplay = min(qryEditList.recordCount, #nEnd#)>
69: </cfif>
70: <cfset cStartFrom = min(qryEditList.recordCount, #nStartFrom#)>
71: <div>Viewing records #cStartFrom# to #cToDisplay# out of #qryEditList.recordCount#</div>
72: </td>
73: </tr>
74: </table>
75: </td>
76: </cfoutput>
77: </tr>
78:
79: <cfif trim(client.userName) is not "">
80: <tr bgcolor="#cccc99">
81: <cfoutput>
82: <td colspan="#nColumns#" align="center">
83: <b>#client.userName#</b>
84: </td>
85: </cfoutput>
86: </tr>
87: </cfif>
88: <cfset client.userName = "">
89: <cfset client.lookupID = -1>
90: <cfset client.detailID = -1>
91:
92:
93: <tr bgcolor="#cccc99">
94: <cfoutput>
95: <td colspan="#nColumns#">
96: <b>#client.userName#</b> <a href="propertyMaint.cfm">Add a property</a>
97: </td>
98: </cfoutput>

```

```

99: </tr>
100:
101: <tr bgcolor="#cccccc">
102:   <td>Sort by <a href="propertyAdm.cfm?SortBy=propertyName"><b>Name</b></a></td>
103:   <td>Sort by <a href="propertyAdm.cfm?SortBy=address"><b>Address</b></a></td>
104:   <td>Sort by <a href="propertyAdm.cfm?SortBy=price"><b>Price</b></a></td>
105:   <td>Sort by <a href="propertyAdm.cfm?SortBy=mls_no"><b>MLS Number</b></a></td>
106:   <cfif client.currentEntityType is not ap_securityAgent>
107:     <td>Sort by <a href="propertyAdm.cfm?SortBy=agentName"><b>Agent Name</b></a></td>
108:   </cfif>
109:   <td align="center">Property Info</td>
110: </tr>
111:
112:
113: <CFIF qryEditList.recordCount is 0>
114:   <TR>
115:     <cfoutput>
116:       <TD COLSPAN="#nColumns#"><I>There are no properties defined</I></TD>
117:     </cfoutput>
118:   </TR>
119: </CFIF>
120: <cfset lColor = True>
121: <form action="propertyChoice.cfm" method="post">
122:   <cfoutput query="qryEditList" startrow="#nstartFrom#" maxrows="#ntoDisplay#">
123:     <cfset lColor = not lColor>
124:     <tr valign="center" <cfif lColor is TRUE>bgcolor="#ffffff"</cfif>>
125:       <td>#qryEditList.propertyName#</td>
126:       <td>#qryEditList.address#</td>
127:       <td>#decimalFormat(qryEditList.price)#</td>
128:       <td>#qryEditList.mls_no#</td>
129:       <cfif client.currentEntityType is not ap_securityAgent>
130:         <td>#qryEditList.agentName#</td>
131:       </cfif>
132:       <td align="center"><input type="image" name="edit#qryEditList.prop_id#" src="#ap_commonImages#edit.gif" alt="Edit"
border="0"></td>
133:     </tr>
134:   </cfoutput>
135: </form>
136: </table></p>
137:
138: <CFSET nPrevStart = nStartFrom-nToDisplay>
139: <CFSET nNextStart = nStartFrom+nToDisplay>
140: <CFSET nPrevEnd = #nPrevStart#+nToDisplay-1>
141: <CFSET nNextEnd = #nNextStart#+nToDisplay-1>
142: <cfif nPrevStart gte 1 or nNextStart lte qryEditList.recordCount>
143:   <table border="0" align="center">
144:     <tr>
145:       <cfif nPrevStart gte 1>
146:         <td>

```

```

147: <form action="propertyAdm.cfm?sortBy=#url.sortBy# METHOD=#post#">
148:   <input type="hidden" name="nStartFrom" value="#nPrevStart#">
149:   <input type="hidden" name="nToDisplay" value="#nToDisplay#">
150:   <input type="hidden" name="nEnd" value="#nPrevEnd#">
151:   <input type="submit" value="Previous #nToDisplay#">
152:   </FORM>
153:   </td>
154: </cfcif>
155: <cfcif nNextStart lte qryEditList.recordCount>
156:   <tc>
157:     <form action="propertyAdm.cfm?sortBy=#url.sortBy# METHOD="POST">
158:       <input type="hidden" name="nStartFrom" value="#nNextStart#">
159:       <input type="hidden" name="nToDisplay" value="#nToDisplay#">
160:       <input type="hidden" name="nEnd" value="#nNextEnd#">
161:       <cfsort nLeftToShow = min(nToDisplay, (qryEditList.recordcount - cToDisplay))>
162:       <input type="submit" value="Next #nLeftToShow#">
163:     </form>
164:   </td>
165: </cfcif>
166: </tr>
167: </table>
168: </cfcif>
169:
170: </body>
171: </html>
172:

```



```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:  <html>
3:  <head>
4:    <title>Property Choice</title>
5:  </head>
6:  <body>
7:
8:
9:
10:  <cfset client.lookupDistID = -1>
11:
12:  <cfloop collection="#form#" item="cName">
13:    <cfif ucase(left(cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
14:      <cfset cValue = mid(cName#, 5, len(cName#)-6)>
15:      <cfset client.lookupID = val(cValue)>
16:      <cfset client.detailID = -1>
17:      <cfset client.userMessage = "">
18:      <cflocation url="propertyMaint.cfm" addToken="no">
19:      <cfelseif ucase(left(cName#,7)) is "OHTEDIT" and findNoCase(".X", #cName#,1) gt 0>
20:        <cfset cValue = mid(cName#, 8, len(cName#)-9)>
21:        <cfset client.lookupID = val(cValue)>
22:        <cfset client.detailID = -1>
23:        <cfset client.userMessage = "">
24:        <cflocation url="OHTMaint.cfm" addToken="no">
25:      </cfif>
26:    </cfloop>
27:
28:    <cfset client.lookupID = -1>
29:    <cfset client.detailID = -1>
30:    <cfset client.userMessage = "">
31:    <cflocation url="propertyAdm.cfm" addToken="no">
32:
33:  </body>
34:  </html>

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
2:
3:
4: <cfif not isdefined("client.lookupID")>
5:   <cflocation url="propertyAdm.cfm" addToken="no">
6: </cfif>
7:
8: <cfparam name="client.userName" default="">
9:
10: <cfparam name="url.displayPage" default="propInfo">
11:
12: <cfquery name="qryFindProperty" datasource="#ap_dataSource#">
13:   select prop_main.*, agents.lastName + ', ' + agents.firstName as agentName,
14:     agency.name as agencyName
15:   from prop_main
16:   left outer join agents on agents.agent_id = prop_main.agent_id
17:   left outer join agency on agency.agency_id = prop_main.agency_id
18:   where prop_main.prop_id = #client.lookupID#
19: </cfquery>
20:
21: <cfif qryFindProperty.recordCount gt 0>
22:   <cfset nPropID = qryFindProperty.prop_id>
23: <cfelse>
24:   <cfset nPropID = -1>
25: </cfif>
26:
27: <html>
28: <head>
29:   <cfoutput>
30:     <title>#client.backofficeName# Backoffice Property Maintenance</title>
31:   </cfoutput>
32:   <link rel="stylesheet" href="style1.css" type="text/css">
33: </head>
34:
35: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
36:   <cfinclude template="include\nocache.cfm">
37:
38:   <p><cfinclude template="include\header.cfm"></p>
39:
40:   <cfset url.displayPage = ucase(url.displayPage)>
41:
42:   <cfif qryFindProperty.recordCount is 1>
43:     <cfset nDistID = qryFindProperty.distributorID>
44:     <cfset client.currentDistributorID gt 0>
45:     <cfset nDistID = client.currentDistributorID>
46:     <cfset client.lookupDistID gt 0>
47:     <cfset nDistID = client.lookupDistID>
48:   <cfelse>
49:     <cfset nDistID = -1>

```

```
50: </cfif>
51:
52: <cfif nPropID is -1 and client.lookupDistID is -1 and client.currentEntityType lte #ap_securityPortal#>
53:   <!-- If adding a new property and we don't know the distributor, find it -->
54:   <cfinclude template="include\propDist.cfm">
55:   <cfelseif url.displayPage is "PROPINFO" and nDistID gt -1>
56:   <cfinclude template="include\propInfo.cfm">
57:   <cfelseif url.displayPage is "PROPIIMAGES" and nDistID gt -1>
58:   <cfinclude template="include\propImages.cfm">
59:   <cfelseif url.displayPage is "PROPROOMS" and nDistID gt -1>
60:   <cfinclude template="include\propRooms.cfm">
61:   <cfelseif url.displayPage is "PROPMISC" and nDistID gt -1>
62:   <cfinclude template="include\propMisc.cfm">
63:   <cfelse>
64:   <cflocation url="propertyAdm.cfm" addToken="no">
65:   </cfif>
66:
67: </body>
68: </html>
```

----- Save form values in case something is wrong -----  
 <!-- A change in the image type has been requested -->

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfif not isdefined("form.propertyID")>
4:    <cfset client.lookupID = -1>
5:    <cfset client.detailID = -1>
6:    <cfset client.imageType = -1>
7:    <cfset client.userName = "">
8:    <cflocation url="propertyAdm.cfm" addtoken="no">
9:  </cfif>
10:
11:  <cfquery name="qryFindProperty" datasource="#ap_dataSource#">
12:    select prop_id, name
13:    from prop_main
14:    where prop_main.prop_id = #form.propertyID#
15:  </cfquery>
16:
17:  <cfinclude template="include\clearOldFields.cfm">
18:  <cfset client.userName = "">
19:  <cfset client.imageType = -1>
20:
21:  <!-- Save form values in case something is wrong ----->
22:  <cfif isdefined("form.btnImageType")>
23:    <!-- A change in the image type has been requested -->
24:    <cfset client.lookupID = form.propertyID>
25:    <cfset client.detailID = form.propertyImageID>
26:    <cfset client.imageType = form.edtImageType>
27:
28:    <cfset client.old_sortOrder = form.edtSortOrder>
29:
30:    <cflocation url="propertyMaint.cfm?displayPage=propImages" addToken="no">
31:  </cfif>
32:
33:  <cfif isdefined("form.btnUpdate")>
34:    <cfif qryFindProperty.recordCount is 0>
35:      <cfset client.lookupID = -1>
36:      <cfset client.detailID = -1>
37:      <cfset client.userName = "There was an error while creating the property.">
38:      <cftransaction>
39:        <cfset cName      = preservesingleQuotes(form.edtName)>
40:        <cfset cAddress   = preservesingleQuotes(form.edtAddress)>
41:        <cfset cCity      = preservesingleQuotes(form.edtCity)>
42:        <cfset cShortDesc = trim(preservesingleQuotes(form.edtShortDesc))>
43:        <cfset cDesc      = trim(preservesingleQuotes(form.edtDesc))>
44:        <cfset nBedrooms  = val(form.edtBedrooms)>
45:        <cfset nBathrooms = val(form.edtBathrooms)>
46:        <cfset nLotSize   = val(form.edtLotSize)>
47:        <cfset nSqFeet    = val(form.edtSqFeet)>
48:        <cfset cPrice     = replace(form.edtPrice, ",", "", "ALL")>
49:        <cfset cPPrice    = replaceNoCase(cPrice, "$", "", "ALL")>

```

```

50: <cfset nPrice = val(cPrice)>
51: <cfset cSoldPrice = replaceNoCase(form.edtSoldPrice, "", "ALL")>
52: <cfset cSoldPrice = replaceNoCase(cSoldPrice, "$", "", "ALL")>
53: <cfset nSoldPrice = val(cSoldPrice)>
54: <cfset nAgencyID = listGetAt(form.edtAgentID,1,"|")>
55: <cfset nAgentID = listGetAt(form.edtAgentID,2,"|")>
56:
57:
58: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
59:     insert into prop_main
60:     (name, address, city, state, zip, county, cnty_id,
61:      agent_id, agency_id, distributorID, portalID, mls_no,
62:      status, beginDate, endDate, price, salesPrice,
63:      prop_type, lotType, homeType, lotSize, size,
64:      bedroom, bath, propdscrip, communityID, dscrip1)
65:     values
66:     ('#cName#, '#cAddress#, '#cCity#, '#form.edtState#, '#form.edtZipcode#,
67:      '#form.edtCounty#, '#form.edtCountry#, '#nAgentID#,
68:      '#nAgencyID#, '#form.edtDistributorID#, '#form.edtPortalID#,
69:      '#form.edtMLS#, '#form.edtStatus#, '#form.edtBeginDate#,
70:      '#form.edtEndDate#, '#nPrice#, '#nSoldPrice#, '#form.edtPropertyType#,
71:      '#form.edtLotType#, '#form.edtHomeType#, '#nLotSize#, '#nSqFeet#,
72:      '#nBedrooms#, '#nBathrooms#, '#cShortDesc#, '#form.edtCommunities#,
73:      '#cDesc#')
74: </cfquery>
75:
76: <cfquery name="qryLastID" dataSource="#ap_dataSource#">
77:     select max(prop_main.prop_id) as lastID
78:     from prop_main
79: </cfquery>
80:
81: <cfset client.lookupID = qryLastID.lastID>
82: <cfquery name="qryDelete" dataSource="#ap_dataSource#">
83:     delete from propSpecialty where propID = #qryLastID.lastID#
84: </cfquery>
85:
86: <cfloop list="#form.edtSpecialtyPages#" index="nItem">
87:     <cfquery name="qryInsert" dataSource="#ap_dataSource#">
88:         insert into propSpecialty
89:             (propID, specialtyPageID)
90:             values
91:             (#nLastID#, #listGetAt(form.edtSpecialtyPages,nItem)#)
92:     </cfquery>
93: </cfloop>
94:
95: <cfset reportType = 2>
96: <cfset reportID = qryLastID.lastID>
97: <cfset reportAction = "ADD">
98: <cfinclude template="include\reportUpdate.cfm">

```

```

99:
100:     <cfset client.userName = form.edtName & " added.">
101: </cftransaction>
102:
103: <cflocation url="propertyMaint.cfm?displayPage=propImages" addToken="no">
104:
105: <cfelse>
106: <cfset client.lookupID = -1>
107: <cfset client.detailID = -1>
108: <cfset client.userName = "There was an error while updating the property information.">
109: </cftransaction>
110:
111: <cfset cName = preserveSingleQuotes(form.edtName)>
112: <cfset cAddress = preserveSingleQuotes(form.edtAddress)>
113: <cfset cCity = preserveSingleQuotes(form.edtCity)>
114: <cfset cShortDesc = preserveSingleQuotes(form.edtShortDesc)>
115: <cfset cDesc = preserveSingleQuotes(form.edtDesc)>
116: <cfset nBedrooms = val(form.edtBedrooms)>
117: <cfset nBathrooms = val(form.edtBathrooms)>
118: <cfset nLotSize = val(form.edtLotSize)>
119: <cfset nsqFeet = val(form.edtsqFeet)>
120: <cfset cPrice = replaceNoCase(form.edtPrice, ",", "", "ALL")>
121: <cfset nPrice = val(cPrice)>
122: <cfset cSoldPrice = replaceNoCase(form.edtsoldPrice, ",", "", "ALL")>
123: <cfset cSoldPrice = replaceNoCase(cSoldPrice, "$", "", "ALL")>
124: <cfset nSoldPrice = val(cSoldPrice)>
125: <cfset nAgencyID = listGetAt(form.edtAgentID,1,"|")>
126: <cfset nAgentID = listGetAt(form.edtAgentID,2,"|")>
127:
128: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
update prop_main
set name = '#cName#',
address = '#cAddress#',
city = '#cCity#',
state = '#form.edtState#',
zip = '#form.edtZipcode#',
county = '#form.edtCounty#',
cntry_id = '#form.edtCountry#',
agent_id = '#nAgentID#',
agency_id = '#nAgencyID#',
distributorID = '#form.edtDistributorID#',
portalID = '#form.edtPortalID#',
mls_no = '#form.edtMLS#',
status = '#form.edtStatus#',
beginDate = '#form.edtBeginDate#',
endDate = '#form.edtEndDate#',
price = '#nPrice#',
salesPrice = '#nSoldPrice#',
prop_type = '#form.edtPropertyType#',

```

```

148: lotType = '#form.edtLotType#',
149: homeType = '#form.edtHomeType#',
150: lotSize = #nLotSize#,
151: size = #nSqFeet#,
152: bedroom = '#nBedrooms#',
153: bath = '#nBathrooms#',
154: propdscrip = '#cShortDesc#',
155: communityID = #form.edtCommunities#,
156: dscrip1 = '#cDesc#',
157: where prop_main.prop_id = #form.propertyID#
158: </cfquery>
159:
160: <cfquery name="qryDelete" dataSource="#ap_dataSource#">
161: delete from propSpecialty where propertyID = #form.propertyID#
162: </cfquery>
163:
164: <cfloop list="#form.edtSpecialtyPages#" index="nitem">
165: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
166: insert into propSpecialty
167: (propertyID, specialtyPageID)
168: values
169: (#form.propertyID#, #listGetAt(form.edtSpecialtyPages,nitem)#)
170: </cfquery>
171: </cfloop>
172:
173: <cfset reportType = 2>
174: <cfset reportID = form.propertyID>
175: <cfset reportAction = "EDIT">
176: <cfinclude template="include\reportUpdate.cfm">
177:
178: <cfset client.userName = form.edtName & " updated.">
179: </cftransaction>
180:
181: <cfset client.lookupID = form.propertyID>
182: <cflocation url="propertyMaint.cfm" addToken="no">
183: </cfif>
184:
185: <cfelseif isDefined("form.btnUpdateImages")>
186: <cfquery name="qryFindDetail" dataSource="#ap_dataSource#">
187: select propertyImageID
188: from propertyImages
189: where propertyImages.propertyImageID = #form.propertyImageID#
190: </cfquery>
191:
192: <cfif qryFindDetail.recordCount is 0>
193: <cfset nSortOrder = val(form.edtSortOrder)>
194:
195: <cfquery name="qryImageType" dataSource="#ap_dataSource#">
196: select imageType, isFormField, isApplet, isURL

```

```

197: from imageTypes
198: where imageTypes.imageType = #form.edtImageType#
199: </cfquery>
200:
201: <cfif qryImageType.isFormField is "Y">
202:   <cfif trim(form.edtImage) is "">
203:     <cfset cImage = form.originalImage>
204:     <cfset cUserImage = form.originalUserImage>
205:   <cfelse>
206:     <cfquery name="qryImagePath" dataSource="#app_dataSource#">
207:       select distributors.propertyImages
208:       from distributors
209:       where distributors.distributorID = #form.distributorID#
210:     </cfquery>
211:
212:     <!--- Upload the file to a unique name --->
213:     <cffile
214:       destination = "#qryImagePath.propertyImages#"
215:       action = "UPLOAD"
216:       nameconflict = "OVERWRITE"
217:       filefield = "edtImage"
218:     >
219:
220:     <cfset cImage = file.serverFile>
221:     <cfset cUserImage = file.serverFile>
222:
223:     <cfset cImagePath = file.serverDirectory & "\">
224:     <cfset cNewImage = "#cImagePath#trim(form.propertyID)#_file.serverFile#">
225:
226:     <cfif fileExists(cNewImage)>
227:       <cffile
228:         action = "DELETE"
229:         file="#cNewImage#"
230:       >
231:     </cfif>
232:
233:     <!--- Now rename the unique uploaded file to the new name --->
234:     <cffile
235:       action = "RENAME"
236:       source = "#file.serverDirectory#\#file.serverFile#"
237:       destination="#cNewImage#"
238:     >
239:
240:     <cfset cImage = cNewImage>
241:   </cfif>
242:   <cfelseif qryImageType.isURL is "Y">
243:     <cfset cImage = form.edtImage>
244:     <cfset cUserImage = form.edtImage>
245:   <cfelseif qryImageType.isApplet is "Y">

```



```

246: <cfset cImage = form.edtImage>
247: <cfset cUserImage = form.edtImage>
248: <cfelse>
249: <cfset cImage = form.edtImage>
250: <cfset cUserImage = form.edtImage>
251: </cfif>
252:
253:
254: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
255: insert into propertyImages
256: (propertyID, sortOrder, image, username,imageType)
257: values
258: (#form.propertyID#, #nSortOrder#,
259: '#cImage#', '#cUserImage#', #form.edtImageType#)
260: </cfquery>
261:
262: <cfset client.lookupID = form.propertyID>
263: <cfset client.detailID = -1>
264: <cfset client.imageType = form.edtImageType> <!--- Keep last inserted image type -->
265:
266: <cflocation url="propertyMaint.cfm?displayPage=propImages" addToken="no">
267:
268: <cfelse>
269: <cfset nSortOrder = val(form.edtSortOrder)>
270:
271: <cfquery name="qryImageType" dataSource="#ap_dataSource#">
272: select imageType, isFormField, isApplet, isURL
273: from imageTypes
274: where imageTypes.imageType = #form.edtImageType#
275: </cfquery>
276:
277: <cfif qryImageType.isFormField is "y">
278: <cfif isDefined("form.chkDeleteImage")>
279: <cfset cImage = "">
280: <cfset cUserImage = "">
281: <cfelseif trim(form.edtImage) is "">
282: <cfset cImage = form.originalImage>
283: <cfset cUserImage = form.originalUserImage>
284: <cfelse>
285: <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
286: select distributors.propertyImages
287: from distributors
288: where distributors.distributorID = #form.distributorID#
289: </cfquery>
290:
291: <!--- Upload the file to a unique name -->
292: <cfif
293: destination = "#qryImagePath.propertyImages#"
294: action = "UPLOAD"

```

```

295:     nameconflict = "OVERWRITE"
296:     filefield = "edImage"
297:
298:
299:     <cfset cImage = file.serverFile>
300:     <cfset cUserImage = file.serverFile>
301:
302:     <cfset cImagePath = file.serverDirectory & "\">
303:     <cfset cNewImage = "#cImagePath##trim(form.propertyID)#_file.serverFile#">
304:
305:     <cfif fileExists(cNewImage)>
306:         <cffile
307:             action = "DELETE"
308:             file="#cNewImage#"
309:         >
310:     </cfif>
311:
312:     <!--- Now rename the unique uploaded file to the new name ---->
313:     <cffile
314:         action = "RENAME"
315:         source = "#file.serverDirectory#\#file.serverFile#"
316:         destination="#cNewImage#"
317:     >
318:
319:     <cfset cImage = cNewImage>
320:     </cfif>
321:     <cfelseif qryImageType.isURL is "Y">
322:         <cfset cImage = form.edtImage>
323:         <cfset cUserImage = form.edtImage>
324:         <cfelseif qryImageType.isApplet is "Y">
325:             <cfset cImage = form.edtImage>
326:             <cfset cUserImage = form.edtImage>
327:         <cfelse>
328:             <cfset cImage = form.edtImage>
329:             <cfset cUserImage = form.edtImage>
330:         </cfif>
331:
332:     <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
333:         update propertyImages
334:         set
335:             sortOrder = #nsortOrder#,
336:             imageType = #form.edtImageType#,
337:             image = '#cImage#',
338:             userName = '#cUserImage#'
339:         where propertyImages.propertyImageID = #form.propertyImageID#
340:     </cfquery>
341:
342:     <cfif isDefined("form.chkDeleteImage")>
343:         <cfset cImage = form.originalImage>

```

```

344: <cfif fileExists(cImage)>
345:   <cffile
346:     action = "DELETE"
347:     file="#cImage#"
348:   >
349:   </cfif>
350: </cfif>
351:
352: <cfset client.lookupID = form.propertyID>
353: <cfset client.detailID = -1>
354: <cfset client.imageType = -1>
355:
356: <cflocation url="propertyMaint.cfm?displayPage=propImages" addToken="no">
357:
358: </cfif>
359:
360: <cfelseif isDefined("form.btnCancelRoom")> <!-- Cancel detail edit -->
361: <cfset client.lookupID = #form.propertyID#>
362: <cfset client.detailID = -1>
363: <cfset client.userMessage = "">
364: <cflocation url="propertyMaint.cfm?displayPage=propRooms" addToken="no">
365:
366: <cfelseif isDefined("form.btnCancelImages")> <!-- Cancel detail edit -->
367: <cfset client.lookupID = #form.propertyID#>
368: <cfset client.detailID = -1>
369: <cfset client.userMessage = "">
370: <cflocation url="propertyMaint.cfm?displayPage=propImages" addToken="no">
371:
372: <cfelseif isDefined("form.btnUpdateRoom")>
373: <cfquery name="qryFindDetail" dataSource="#ap_dataSource#">
374:   select roomDetailID
375:   from rooms
376:   where rooms.roomDetailID = #form.roomDetailID#
377: </cfquery>
378:
379: <cfif qryFindDetail.recordCount is 0>
380:   <cfset nSize = val(form.edtSize)>
381:   <cfset cFloor = preservesingleQuotes(form.edtFloor)>
382:   <cfset nSortOrder = val(form.edtSortOrder)>
383:
384: <cftransaction>
385:   <cfquery name="qryInsert" dataSource="#ap_dataSource#">
386:     insert into rooms
387:       (propertyID, roomID, size, floor, sortOrder)
388:     values
389:       (#form.propertyID#, #form.edtRoom#, #nSize#, 'cFloor', #nSortOrder#)
390:   </cfquery>
391: </cftransaction>
392:

```

```

393: <cfset client.lookupID = form.propertyID>
394: <cfset client.detailID = -1>
395:
396: <cflocation url="propertyMaint.cfm?displayPage=propRooms" addToken="no">
397:
398: <cfelse>
399:   <cfset nSize = val(form.edtSize)>
400:   <cfset cFloor = preservesSingleQuotes(form.edtFloor)>
401:   <cfset nSortOrder = val(form.edtSortOrder)>
402:
403: <cftransaction>
404:   <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
405:     update rooms
406:     set
407:       roomID = #form.edtRoom#,
408:       size = #nSize#,
409:       floor = '#cFloor#',
410:       sortOrder = #nSortOrder#
411:     where rooms.roomDetailID = #form.roomDetailID#
412:   </cfquery>
413: </cftransaction>
414:
415: <cfset client.lookupID = form.propertyID>
416: <cfset client.detailID = -1>
417:
418: <cflocation url="propertyMaint.cfm?displayPage=propRooms" addToken="no">
419: </cfif>
420:
421: <cfelseif isDefined("form.btnDelete")>
422:   <cfset client.lookupID = -1>
423:   <cfset client.detailID = -1>
424:   <cfset client.userName = "Unable to delete #form.edtName#">
425:   <cftransaction>
426:     <cfquery name="qryDelete" dataSource="#ap_dataSource#">
427:       delete from prop_main
428:       where prop_main.prop_id = #form.propertyID#
429:     </cfquery>
430:     <cfset client.userName = form.edtName & " deleted.">
431:   </cftransaction>
432:   <cflocation url="propertyAdm.cfm" addToken="no">
433:
434:
435: <cfelseif isDefined("btnSelectDist")>
436:   <cfset client.lookupID = form.propertyID>
437:   <cfset client.lookupDistID = form.edtDistributorID>
438:   <cflocation url="propertyMaint.cfm" addToken="no">
439: <cfelseif isDefined("btnCancelDist")>
440:   <cfset client.lookupID = -1>
441:   <cfset client.detailID = -1>

```

```

442: <cfset client.lookupDistID = -1>
443: <cfset client.lookupAgencyID = -1>
444: <cflocation url="propertyAdm.cfm" addToken="no">
445: </cfif>
446:
447: <cfset client.lookupID = -1>
448: <cfset client.detailID = -1>
449:
450: <!-- Get ID number from edit -->
451: <cfloop collection="#form#" item="cName">
452:   <cfif ucase(left(cName#8)) is "EDITROOM" and findNoCase(".X", #cName#,1) gt 0>
453:     <cfset cValue = mid(cName#, 9, len(cName#)-10)>
454:     <cfset client.lookupID = form.propertyID>
455:     <cfset client.detailID = val(cValue)>
456:   </cfif>
457:
458:   <cfif client.lookupID gt -1 and client.detailID gt -1>
459:     <cflocation url="propertyMaint.cfm?displayPage=propRooms" addToken="no">
460:   </cfif>
461: </cfloop>
462:
463: <!-- Get ID number from edit -->
464: <cfloop collection="#form#" item="cName">
465:   <cfif ucase(left(cName#9)) is "EDITIMAGE" and findNoCase(".X", #cName#,1) gt 0>
466:     <cfset cValue = mid(cName#, 10, len(cName#)-11)>
467:     <cfset client.lookupID = form.propertyID>
468:     <cfset client.detailID = val(cValue)>
469:   </cfif>
470:
471:   <cfif client.lookupID gt -1 and client.detailID gt -1>
472:     <cflocation url="propertyMaint.cfm?displayPage=propImages" addToken="no">
473:   </cfif>
474: </cfloop>
475:
476: <!-- Get ID number for delete detail item -->
477: <cfloop collection="#form#" item="cName">
478:   <cfif ucase(left(cName#10)) is "DELETEROOM" and findNoCase(".X", #cName#,1) gt 0>
479:     <cfset cValue = mid(cName#, 11, len(cName#)-12)>
480:     <cfset client.lookupID = form.propertyID>
481:     <cfset client.detailID = val(cValue)>
482:   </cfif>
483:
484:   <cfif client.lookupID gt -1 and client.detailID gt -1>
485:     <cfset client.userName = "Unable to delete room.">
486:     <cfquery name="qryDelete" dataSource="#ap_dataSource#">
487:       delete from rooms
488:       where rooms.roomDetailID = #client.detailID#
489:     </cfquery>
490:     <cfset client.detailID = -1>

```

```

491:         <cfset client.userMessage = "room deleted.">
492:         <cflocation url="propertyMaint.cfm?displayPage=propRooms" addToken="no">
493:     </cfif>
494: </cfloop>
495:
496:     <!--- Get ID number for delete detail item --->
497:     <cfloop collection="#form#" item="cName">
498:         <cfif ucase(left(#cName#,11)) is "DELETEIMAGE" and findNoCase(".X", #cName#,1) gt 0>
499:             <cfset cValue = mid(#cName#, 12, len(#cName#)-13)>
500:             <cfset client.lookupID = form.propertyID>
501:             <cfset client.detailID = val(cValue)>
502:         </cfif>
503:
504:         <cfif client.lookupID gt -1 and client.DetailID gt -1>
505:             <cfset client.userMessage = "Unable to delete image.">
506:             <cfquery name="qryDelete" dataSource="#ap_dataSource#">
507:                 delete from propertyImages
508:                 where propertyImages.propertyImageID = #client.detailID#
509:             </cfquery>
510:             <cfset client.detailID = -1>
511:             <cfset client.userMessage = "image deleted.">
512:             <cflocation url="propertyMaint.cfm?displayPage=propImages" addToken="no">
513:         </cfif>
514:     </cfloop>
515:
516:     <!--- If anything else, then go back to the admin page --->
517:     <cflocation url="propertyAdm.cfm" addToken="no">
518: 
```

-----  
 4.0 Transitional/EN\$  
 -----

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN$
2:  <cfset client.gotoPage = "resourceAdm.cfm">
3:
4:  <cfif client.currentEntityType lt #ap_securityMastDist# and client.lookupDistID is -1>
5:    <!-- We do not know what distributor we should be editing, so find out ---->
6:    <cfset client.lookupDistID = -1>
7:    <cfset client.lookupAgencyID = -1>
8:    <cfset client.lookupID = -1>
9:    <cfset client.DetailID = -1>
10:    <cflocation url="distSelect.cfm" addToken="no">
11:  </cfif>
12:
13:
14:  <cfif client.currentEntityType lt #ap_securityMastDist#>
15:    <cfquery name="qryDist" dataSource="#ap_dataSource#">
16:      select distributors.name as distName
17:      from distributors
18:      where distributors.distributorID = #client.lookupDistID#
19:    </cfquery>
20:    <cfset cDistName = qryDist.distName>
21:    <cfelseif client.currentEntityType gte #ap_securityMastDist#>
22:    <cfset client.lookupDistID = client.currentEntityID>
23:    <cfset cDistName = "">
24:  </cfif>
25:
26:  <cfparam name="URL.sortBy" default="groupName">
27:  <cfset client.lookupID = -1>
28:  <cfset client.detailID = -1>
29:
30:  <!-- Display rows ---->
31:  <cfparam name="nStartFrom" default="1">
32:  <cfparam name="nToDisplay" default="#client.displayRows#">
33:  <cfparam name="nEnd" default="#client.displayRows#">
34:
35:
36:  <cfquery name="qryEditList" dataSource="#ap_dataSource#">
37:    select resourceGroups.groupID, resourceGroups.name as groupName
38:    from resourceGroups
39:    join securityAccess on
40:      (securityAccess.entityType = #ap_securityMastDist# or securityAccess.entityType = #ap_securityDist#)
41:      and securityAccess.entityID = resourceGroups.distributorID
42:      and securityAccess.hierarchyID like '#client.hierarchyID#%'
43:      where resourceGroups.distributorID = #client.lookupDistID#
44:      order by #url.sortBy#
45:  </cfquery>
46:
47:  <html>
48:  <head>
49:    <cfoutput>

```

```

50: <title>#client.backofficeName# Backoffice Resource Groups</title>
51: </cfoutput>
52: <link rel="stylesheet" href="style1.css" type="text/css">
53: </head>
54:
55:
56: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
57: <cfinclude template="include\nocache.cfm">
58: <p><cfinclude template="include\header.cfm"></p>
59:
60: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
61: <tr bgcolor="#cccc99">
62: <td colspan="6">
63: <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">
64: <tr>
65: <td align="left">
66: <span class="h2">
67: <b>Resource Administration</b>
68: <cfif cDistName is not "">
69: <cfoutput>
70: <nbsp;#cDistName#>
71: </cfoutput>
72: </cfif>
73: </span>
74: </td>
75: <td align="right">
76: <cfif #nToDisplay# gte qryEditList.recordCount>
77: <cfset cToDisplay = min(qryEditList.recordCount, #nToDisplay#)>
78: </cfif>
79: <cfif qryEditList.recordCount gte #nToDisplay#>
80: <cfset cToDisplay = min(qryEditList.recordCount, #ToEnd#)>
81: </cfif>
82: <cfset cStartFrom = min(qryEditList.recordCount, #StartFrom#)>
83: <cfoutput>(Viewing records #cStartFrom# to #cToDisplay# out of #qryEditList.recordCount#)</cfoutput>
84: </td>
85: </tr>
86: </table>
87: </td>
88: </tr>
89:
90: <cfif trim(client.userName) is not "">
91: <tr bgcolor="#cccc99">
92: <td colspan="6" align="center">
93: <cfoutput><b>#client.userName#</b></cfoutput>
94: </td>
95: </tr>
96: </cfif>
97: <cfset client.userName = "">
98: <cfset client.lookupID = -1>

```



99: 100: 101: 102: 103: 104: 105: 106: 107: 108: 109: 110: 111: 112: 113: 114: 115: 116: 117: 118: 119: 120: 121: 122: 123: 124: 125: 126: 127: 128: 129: 130: 131: 132: 133: 134: 135: 136: 137: 138: 139: 140: 141: 142: 143: 144: 145: 146:

```
147: <form action="resourceAdm.cfm?sortBy=#url.sortBy# METHOD="POST">
148:   <input type="hidden" name="nStartFrom" value="#nNextStart#">
149:   <input type="hidden" name="nToDisplay" value="#nToDisplay#">
150:   <input type="hidden" name="nEnd" value="#nNextEnd#">
151:   <cfset nLeftToShow = min(nToDisplay, (qryEditList.recordcount - cToDisplay))>
152:   <input type="submit" value="Next #nLeftToShow#">
153:   </form>
154:   </td>
155: </cfif>
156: </tr>
157: </table>
158: </cfif>
159: </body>
160: </html>
161:
162:
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3: <html>
4: <head>
5: <title>Resource Choice</title>
6: </head>
7:
8: <body>
9:
10: <cfloop collection="#form#" item="cName">
11: <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".",X", #cName#,1) gt 0>
12: <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
13: <cfset client.lookupID = val(cValue)>
14: <cfset client.detailID = -1>
15: <cfset client.userMessage = "">
16: <cflocation url="resourceMaint.cfm" addToken="no">
17: </cfif>
18: </cfloop>
19:
20: <cfset client.lookupID = -1>
21: <cfset client.detailID = -1>
22: <cfset client.userMessage = "">
23: <cflocation url="resourceAdm.cfm" addToken="no">
24:
25: </body>
26: </html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <cfif client.lookupID is "-1">
4:    <cfset client.lookupID = -1>
5:    <cfset client.detailID = -1>
6:    <cfset client.userName = "">
7:    <cflocation url="resourceAdm.cfm" addtoken="no">
8:  </cfif>
9:
10:  <cfquery name="qryGetPage" dataSource="#ap_dataSource#">
11:    select groupID, name, distributorID
12:    from resourceGroups
13:    where resourceGroups.groupID = #client.lookupID#
14:  </cfquery>
15:
16:  <html>
17:  <head>
18:    <title>Confirm Deletion of Resource Group</title>
19:  </head>
20:
21:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
22:    <cfinclude template="include\nocache.cfm">
23:
24:    <p><cfinclude template="include\header.cfm"></p>
25:
26:    <cfoutput>
27:
28:    <cfset client.detailID = -1>
29:    <cfset client.userName = "">
30:    <cfset client.imageType = -1>
31:
32:    <cfquery name="qryFindLinks" dataSource="#ap_dataSource#">
33:      select linkID, description
34:      from resourceLinks
35:      where resourceLinks.groupID = #client.lookupID#
36:    </cfquery>
37:
38:    <form action="resourceUpdate.cfm" method="post">
39:      <input type="hidden" name="groupID" value="#client.lookupID#">
40:      <input type="hidden" name="edName" value="#qryGetPage.name#">
41:      <input type="hidden" name="distributorID" value="#qryGetPage.distributorID#">
42:      <!--
43:      <input type="hidden" name="url" value="#url.type#">
44:      -->
45:
46:      <b>#qryGetPage.name# Resource Group Deletion Confirmation</b>
47:      <br>
48:      <br>
49:      <cfif qryFindLinks.recordCount gt 0>

```



```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN"
2:
3:  <cfif client.currentEntityType lt #ap_securityMastDist#>
4:    <cfquery name="qryDist" datasource="#ap_dataSource#">
5:      select distributors.name as distName
6:      from distributors
7:      where distributors.distributorID = #client.lookupDistID#
8:    </cfquery>
9:    <cfset cDistName = qryDist.distName>
10:  <cfelseif client.currentEntityType gte #ap_securityMastDist#>
11:    <cfset client.lookupDistID = client.currentDistributorID>
12:    <cfset cDistName = "">
13:  </cfif>
14:
15:
16:  <!-- Get ID number from edit -->
17:  <cfloop collection="#form#" item="cName">
18:    <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
19:      <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
20:      <cfset client.lookupID = val(cValue)>
21:      <cfset client.detailID = -1>
22:    </cfif>
23:  </cfloop>
24:
25:  <!-- Get ID number from edit -->
26:  <cfloop collection="#form#" item="cName">
27:    <cfif ucase(left(#cName#,4)) is "VIEW" and findNoCase(".X", #cName#,1) gt 0>
28:      <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
29:      <cfset client.lookupID = -1>
30:      <cfset client.detailID = -1>
31:      <cfset client.userMessage = "">
32:      <cflocation url="resourceView.cfm?groupID=#cValue# addToken="no">
33:    </cfif>
34:  </cfloop>
35:
36:
37:  <cfif not isDefined("client.lookupID")>
38:    <cflocation url="resourceAdm.cfm" addToken="no">
39:  </cfif>
40:  <cfparam name="client.userMessage" default="">
41:  <cfparam name="client.imageType" default="-1">
42:
43:  <cfquery name="qryFindGroup" datasource="#ap_dataSource#">
44:    select * from resourceGroups
45:    where resourceGroups.groupID = #client.lookupID#
46:  </cfquery>
47:
48:
49:  <cfif qryFindGroup.recordCount gt 0>

```

```

50: <cfset nGroupID = qryFindGroup.groupID>
51: <cfset nDistributorID = qryFindgroup.distributorID>
52: <cfelse>
53: <cfset nGroupID = -1>
54: <cfif client.currentEntityType lte 3>
55: <cfset nDistributorID = -1>
56: <cfelse>
57: <cfset nDistributorID = client.lookupDistID>
58: </cfif>
59: </cfif>
60:
61:
62: <cfinclude template="include\javaValidate.cfm">
63:
64: <script language="JavaScript">
65: \!--
66: function validate(testform) {
67: var results = "";
68: var lResult = true;
69:
70: if (removeSpaces(testform.edtName.value) == "") {
71: results = results + "** Please enter a name for the resource group.\r";
72: lResult = false;
73: }
74:
75: if ((removeSpaces(testform.edtSortOrder.value) != "") && (!isNumber(testform.edtSortOrder.value))) {
76: results = results + "** " + testform.edtSortOrder.value + " is not a valid numeric sort order value.\r";
77: lResult = false;
78: }
79:
80: // Netscape does not recognize the value of select elements, but does know which item was selected
81: if ((testform.edtDistributorID.value == "-1") || (testform.edtDistributorID.selectedIndex == 0)) {
82: results = results + "** You must select a distributor for this resource group.\r";
83: lResult = false;
84: }
85:
86: if (!lResult) {
87: window.alert(results);
88: }
89: return lResult;
90: }
91: -->
92: </script>
93:
94: <html>
95: <head>
96: <cfoutput>
97: <title>#client.backofficeName# Backoffice Resource Maintenance</title>
98: </cfoutput>

```

```

99: <link rel="stylesheet" href="style1.css" type="text/css">
100: </head>
101:
102: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
103: <cfinclude template="include/nocache.cfm">
104:
105: <p><cfinclude template="include/header.cfm"></p>
106:
107: <cfoutput>
108:
109: <form action="resourceUpdate.cfm" method="post" onsubmit="return validate(this)">
110:   <input type="hidden" name="groupID" value="#hGroupID#">
111:   <input type="hidden" name="edtDistributorID" value="#client.lookupDistID#">
112:   <input type="hidden" name="distributorID" value="#client.lookupDistID#">
113:
114:   <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
115:     <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Resource Maintenance</b></span>
116:     <cfif client.lookupID is -1>
117:       &nbsp;<br>(Create a new resource group
118:       <cfif cDistName is not "">
119:         for #cDistName#
120:       </cfif>
121:     )
122:     </cfif>
123:   </td></tr>
124:
125:   <CFIF client.userMessage is not "">
126:     <tr bgcolor="ffffff">
127:       <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td>
128:     </tr>
129:     <tr bgcolor="ffffff"><td colspan="5">&nbsp;</td></tr>
130:   </CFIF>
131:   <cfset client.userMessage = "">
132:
133:   <tr bgcolor="##ffffff">
134:     <td width="15%"><b>Name:</b></td>
135:     <td width="34%"><input type="text" name="edtName" value="#qryFindGroup.name#" size="60" maxlength="45"></td>
136:     <td width="2%">&nbsp;</td>
137:     <td width="15%"><b>Sort Order:</b>
138:     <td width="34%"><input type="text" name="edtSortOrder" value="#qryFindGroup.sortOrder#" size="2" maxlength="2"></td>
139:   </tr>
140:
141:   <!--
142:   <cfif client.currentEntityType lte ap_securityPortal>
143:     <cfquery name="qryDist" datasource="#op_datasource#">
144:       select distributors.distributorID, distributors.name as distName
145:       from distributors
146:       join securityAccess on
147:         (securityAccess.entityType = #ap_securityMasterDist# or securityAccess.entityType = #ap_securityDist#)

```



```

148: and securityAccess.entityID = distributors.distributorID
149: and securityAccess.hierarchyID like '#client.hierarchyID#%'
150: order by distName
151: </cfquery>
152: <tr bgcolor="#eeeeee">
153:   <td width="15%">Distributor:</td>
154:   <td colspan="4">
155:     <select name="editDistributorID">
156:       <option value=""><cfif qryFindGroup.distributorID is 0 or trim(qryFindGroup.distributorID) is "">
157:         <cfloop query="qryDist">
158:           <option value="#qryDist.distributorID#"><cfif qryDist.distributorID is qryFindGroup.distributorID,
159:             selected</cfif>#qryDist.distName#
160:         </cfloop>
161:       </select>
162:     </tr>
163:   <else>
164:     <cfif qryFindGroup.recordCount is 0>
165:       <input type="hidden" name="editDistributorID" value="#client.lookupDistID#">
166:     <cfelse>
167:       <input type="hidden" name="editDistributorID" value="#qryFindGroup.distributorID#">
168:     </cfif>
169:   </cfif>
170: </td>
171: </tr>
172: <tr bgcolor="eeeeee">
173:   <cfif qryFindGroup.recordCount is 0>
174:     <td colspan="5">
175:       <input type="submit" name="btnUpdate" value="Add Resource Group">
176:       <input type="reset" value="Reset Info">
177:     </td>
178:   <cfelse>
179:     <td colspan="4">
180:       <input type="submit" name="btnUpdate" value="Update Resource Group">
181:       <input type="reset" value="Reset Info">
182:       <input type="submit" name="btnView" value="View Resource Group">
183:     </td>
184:     <td align="right">
185:       <input type="submit" name="btnDelete" value="Delete Resource Group">
186:     </td>
187:   </cfif>
188: </tr>
189: </table>
190: </form>
191: </cfoutput>
192:
193: <!-- If this resource group has already been created, allow link editing -->
194:

```

```

195: <cfif qryFindGroup.recordCount gt 0>
196: <script language="JavaScript">
197: <!--
198:   function validateDetail(testform) {
199:     var results = "";
200:     var lResult = true;
201:
202:     if ((removeSpaces(testform.edtSortOrder.value) != "") && (!isNumber(testform.edtSortOrder.value))) {
203:       results = results + " * " + testform.edtSortOrder.value + " is not a valid numeric sort order value.\r";
204:       lResult = false;
205:     }
206:
207:     if (!lResult) {
208:       window.alert(results);
209:     }
210:
211:     return lResult;
212:   }
213:   -->
214: </script>
215:
216: <cfquery name="qryDetail" datasource="#ap_dataSource#">
217:   select resourceLinks.*
218:   from resourceLinks
219:   where resourceLinks.groupID = #client.lookupID#
220:   order by resourceLinks.sortOrder
221: </cfquery>
222:
223: <cfquery name="qryEdit" datasource="#ap_dataSource#">
224:   select resourceLinks.*
225:   from resourceLinks
226:   where resourceLinks.groupID = #client.lookupID#
227:   and resourceLinks.linkID = #client.detailID#
228: </cfquery>
229:
230: <!-- Set default values -->
231: <cfif qryEdit.recordCount is 0> <!-- New record -->
232:   <cfif qryDetail.recordCount is 0>
233:     <cfset nSortOrder = "1">
234:   <cfelse>
235:     <cfquery name="qryMax" datasource="#ap_dataSource#">
236:       select max(sortOrder) as maxOrder
237:       from resourceLinks
238:       where resourceLinks.groupID = #client.lookupID#
239:     </cfquery>
240:     <cfset nSortOrder = qryMax.maxOrder+1>
241:   </cfif>
242: <cfelse> <!-- Existing record -->
243:   <cfset nSortOrder = qryEdit.sortOrder>

```

```

244: </cfif>
245: <cfset cURL = trim(qryEdit.URL)>
246: <cfset cDesc = trim(qryEdit.description)>
247:
248: <form action="resourceUpdate.cfm" method="post" enctype="multipart/form-data" onSubmit="return validateDetail(this)">
249:   <cfoutput>
250:     <input type="hidden" name="groupID" value="#client.lookupID#">
251:     <input type="hidden" name="distributorID" value="#client.lookupDistID#">
252:     <input type="hidden" name="linkID" value="#client.detailID#">
253:     <input type="hidden" name="originalImage" value="#qryEdit.image#">
254:     <input type="hidden" name="originalUserImage" value="#qryEdit.userName#">
255:   </cfoutput>
256:
257:   <cfif qryDetail.recordCount is 0>
258:     <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
259:       <tr><td colspan="6"><i><b>There are no links defined.</b></i></td></tr>
260:       <tr><td colspan="6"><b><nbsp;</b></td></tr>
261:     </table>
262:   </cfif>
263:   <table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
264:     <tr valign="top" bgcolor="#cccccc">
265:       <td><b>Description</b></td>
266:       <td><b>URL</b></td>
267:       <td><b>Image Name</b></td>
268:       <td><b>Order</b></td>
269:       <td><b><nbsp;</b></td>
270:     </tr>
271:     <cfoutput query="qryDetail">
272:       <tr valign="top" bgcolor="#<cfif qryDetail.linkID is client.detailID>#ffffff<cfelse>#eeeeee</cfif>">
273:         <td>
274:           <cfif trim(qryDetail.description) is ""><b></b></td>
275:         </td>
276:         <td>
277:           <cfif trim(qryDetail.URL) is ""><b></b></td>
278:         </td>
279:         <td>
280:           <cfif trim(qryDetail.userName) is ""><b></b></td>
281:         </td>
282:         <td>#qryDetail.sortOrder#</td>
283:         <td align="center">
284:           <input type="image" name="edit#qryDetail.linkID#" src="#ap_commonImages#edit.gif" alt="Edit" border="0">
285:           <hr>
286:           <input type="image" name="delete#qryDetail.linkID#" src="#ap_commonImages#delete.gif" alt="Delete" border="0">
287:         </td>
288:       </tr>
289:     </cfoutput>
290:   </table>
291: </cfif>
292: <cfoutput>

```

```

293: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
294: <tr><td colspan="5">&nbsp;</td></tr>
295: <cfif client.detailID is -1>
296: <tr bgcolor="#cccccc"><td colspan="5"><b>Add a link</b></td></tr>
297: <cfelse>
298: <tr bgcolor="#cccccc"><td colspan="5"><b>Edit this link</b></td></tr>
299: </cfif>
300: <tr valign="top" bgcolor="#eeeeee">
301: <td><b>Description</b></td>
302: <td><b>URL</b></td>
303: <td><b>Image</b></td>
304: <td><b>Order</b></td>
305: <td><b>Display Pages</b></td>
306: </tr>
307: <tr valign="top" bgcolor="#eeeeee">
308: <td><input type="text" name="edtDesc" value="#cDesc#" size="40" maxlength="120"></td>
309: <td><input type="text" name="edtURL" value="#cURL#" size="30" maxlength="120"></td>
310: <td><input type="File" name="edImage"></td>
311: <td><input type="text" name="edtSortOrder" value="#nSortOrder#" size="2" maxlength="2"></td>
312: <td>&nbsp;</td>
313: </tr>
314: <tr bgcolor="eeeeee">
315: <td colspan="5">
316: <cfif qryEdit.recordCount is 0>
317: <input type="submit" name="btnUpdateDetail" value="Add Link">
318: <input type="reset" value="Reset Info">
319: <cfelse>
320: <input type="submit" name="btnUpdateDetail" value="Update Link">
321: <input type="reset" value="Reset Info">
322: <input type="submit" name="btnCancelDetail" value="Cancel">
323: </cfif>
324: </td>
325: </tr>
326: </table>
327: </cfoutput>
328: </form>
329: </cfif>
330:
331: </body>
332: </html>
333:
334:

```

4.0 Transitional/TFEN

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/TFEN">
2:
3:  <cfif not isDefined("form.groupID")>
4:    <cfset client.lookupID = -1>
5:    <cfset client.detailID = -1>
6:    <cfset client.imageType = -1>
7:    <cfset client.userName = "">
8:    <cflocation url="resourceAdm.cfm" addtoken="no">
9:  </cfif>
10:
11:  <cfquery name="qryFindGroup" datasource="#ap_dataSource#">
12:    select groupID, name
13:    from resourceGroups
14:    where resourceGroups.groupID = #form.groupID#
15:  </cfquery>
16:
17:  <cfinclude template="include\clearOldFields.cfm">
18:  <cfset client.userName = "">
19:  <cfset client.imageType = -1>
20:
21:  <cfif isDefined("form.btnCancelDetail")> <!-- Cancel detail edit -->
22:    <cfset client.lookupID = #form.groupID#>
23:    <cfset client.detailID = -1>
24:    <cfset client.imageType = -1>
25:    <cfset client.userName = "">
26:    <cflocation url="resourceMaint.cfm" addtoken="no">
27:  <cfelseif isDefined("form.btnCancelDelete")> <!-- Cancel detail edit -->
28:    <cfset client.lookupID = #form.groupID#>
29:    <cfset client.detailID = -1>
30:    <cfset client.imageType = -1>
31:    <cfset client.userName = "Deletion canceled.">
32:    <cflocation url="resourceMaint.cfm" addtoken="no">
33:
34:  <cfelseif isDefined("form.btnView")>
35:    <cflocation url="resourceView.cfm?groupID=#form.groupID#> addtoken="no">
36:
37:  <cfelseif isDefined("form.btnUpdateDetail")>
38:    <cfquery name="qryFindDetail" datasource="#ap_dataSource#">
39:      select resourceLinks.linkID
40:      from resourceLinks
41:      where resourceLinks.linkID = #form.linkID#
42:    </cfquery>
43:
44:  <cfif qryFindDetail.recordCount is 0>
45:    <cfset cURL = preservesingleQuotes(form.edtURL)>
46:    <cfset cDesc = preservesingleQuotes(form.edtDesc)>
47:    <cfset nSortOrder = val(form.edtSortOrder)>
48:
49:

```

```

50: <cfif trim(form.edtImage) is ">
51:   <cfset cImage = form.originalImage>
52:   <cfset cUserImage = form.originalUserImage>
53: </cfelse>
54:   <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
55:     select distributors.resourceImages
56:     from distributors
57:     where distributors.distributorID = #form.distributorID#
58:   </cfquery>
59:   <!-- Upload the file to a unique name -->
60:   <cffile
61:     destination = "#qryImagePath.resourceImages#"
62:     action = "UPLOAD"
63:     nameConflict = "OVERWRITE"
64:     filefield = "edtImage"
65:   >
66:
67:   <cfset cImage = file.serverFile>
68:   <cfset cUserImage = file.serverFile>
69:
70:   <cfset cImagePath = file.serverDirectory & "\">
71:   <cfset cNewImage = "#cImagePath#trim(form.groupID)#_#file.serverFile#">
72:
73:   <cfif fileExists(cNewImage)>
74:     <cffile
75:       action = "DELETE"
76:       file="#cNewImage#"
77:     >
78:   </cfif>
79:
80:   <!-- Now rename the unique uploaded file to the new name -->
81:   <cffile
82:     action = "RENAME"
83:     source = "#file.serverDirectory#\#file.serverFile#"
84:     destination="#cNewImage#"
85:   >
86:
87:   <cfset cImage = cNewImage>
88: </cfif>
89:
90:
91:   <cfquery name="qryInsert" dataSource="#ap_dataSource#">
92:     insert into resourceLinks
93:       (groupID, description, URL, image, username, sortOrder)
94:     values
95:       (#form.groupID#, '#cDesc#', '#cURL#', '#cImage#', '#cUserImage#',
96:        #nSortOrder#)
97:   </cfquery>
98:

```

```

99: <cfset client.lookupID = form.groupID>
100: <cfset client.detailID = -1>
101:
102: <cflocation url="resourceMaint.cfm" addToken="no">
103:
104: <cfelse>
105: <cfset cURL = preservesSingleQuotes(form.edtURL)>
106: <cfset cDesc = preservesSingleQuotes(form.edtDesc)>
107: <cfset nSortOrder = val(form.edtSortOrder)>
108:
109: <cfif trim(form.edtImage) is "">
110: <cfset cImage = form.originalImage>
111: <cfset cUserImage = form.originalUserImage>
112: <cfelse>
113: <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
114:   select distributors.resourceImages
115:   from distributors
116:   where distributors.distributorID = #form.distributorID#
117: </cfquery>
118: <!--- Upload the file to a unique name -->
119: <cfif
120:   destination = "#qryImagePath.resourceImages#"
121:   action = "UPLOAD"
122:   nameConflict = "OVERWRITE"
123:   filefield = "edtImage"
124: >
125:
126: <cfset cImage = file.serverFile>
127: <cfset cUserImage = file.serverFile>
128:
129: <cfset cImagePath = file.serverDirectory & "\">
130: <cfset cNewImage = "#cImagePath#trim(form.groupID)#_file.serverFile#">
131:
132: <cfif fileExists(cNewImage)>
133:   <cfif
134:     action = "DELETE"
135:     file="#cNewImage#"
136:   >
137: </cfif>
138:
139: <!--- Now rename the unique uploaded file to the new name -->
140: <cfif
141:   action = "RENAME"
142:   source = "#file.serverDirectory#\#file.serverFile#"
143:   destination="#cNewImage#"
144: >
145:
146: <cfset cImage = cNewImage>
147: </cfif>

```

```

148:
149:
150:
151:
152:
153:
154:
155:
156:
157:
158:
159:
160:
161:
162:
163:
164:
165:
166:
167:
168:
169:
170:
171:
172:
173:
174:
175:
176:
177:
178:
179:
180:
181:
182:
183:
184:
185:
186:
187:
188:
189:
190:
191:
192:
193:
194:
195:
196:

```

```

<cfquery name="qryUpdate" dataSource="#ap_dataSource#">
update resourceLinks
set
    description = '#cDesc#',
    URL = '#cURL#',
    image = '#cImage#',
    userName = '#cUserName#',
    sortOrder = #nSortOrder#
where resourceLinks.linkID = #form.linkID#
</cfquery>

<cfset client.lookupID = form.groupID>
<cfset client.detailID = -1>
<cfset client.imageType = -1>

<cflocation url="resourceMaint.cfm" addToken="no">

</cfif>

<cfelseif isDefined("form.btnUpdate")>
<cfif qryFindGroup.recordCount is 0>
<cfset client.lookupID = -1>
<cfset client.detailID = -1>
<cfset client.userName = "There was an error while creating the resource group.">
<cftransaction>
    <cfset cName = preserveSingleQuotes(form.edtName)>
    <cfset nSortOrder = val(form.edtSortOrder)>

    <cfquery name="qryInsert" dataSource="#ap_dataSource#">
        insert into resourceGroups
            (distributorID, name, sortOrder)
        values
            (#form.edtDistributorID#, '#cName#', #nSortOrder#)
    </cfquery>

    <cfquery name="qryGetID" dataSource="#ap_dataSource#">
        select max(groupID) as lastID
        from resourceGroups
    </cfquery>
    <cfset nGroupID = qryGetID.lastID>
    <cfset client.lookupID = nGroupID>

    <cfset client.userName = "" & form.edtName & " resource group was created.">
    </cftransaction>

<cfif client.lookupID gt 0>
    <cflocation url="resourceMaint.cfm" addToken="no">
<cfelse>

```



```

197:     <cflocation url="resourceAdm.cfm" addToken="no">
198:   </cfif>
199:
200:   <cfelse>
201:     <cfset client.lookupID = form.GroupID>
202:     <cfset client.detailID = -1>
203:     <cfset client.userName = "There was an error while updating the resource group information.">
204:     <cftransaction>
205:       <cfset cName = preserveSingleQuotes(form.edtName)>
206:       <cfset nSortOrder = val(form.edtSortOrder)>
207:
208:       <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
209:         update resourceGroups
210:         set distributorID = #form.edtDistributorID#,
211:           name = '#cName#',
212:           sortOrder = #nSortOrder#
213:         where resourceGroups.groupID = #form.groupID#
214:       </cfquery>
215:
216:       <cfset client.detailID = -1>
217:       <cfset client.userName = "" & #form.edtName# & "" resource group was updated.">
218:       </cftransaction>
219:
220:     <cfif client.lookupID gt 0>
221:       <cflocation url="resourceMaint.cfm" addToken="no">
222:     <cfelse>
223:       <cflocation url="resourceAdm.cfm" addToken="no">
224:     </cfif>
225:   </cfif>
226:   <cfelseif isDefined("form.btnDelete")>
227:     <cflocation url="resourceDelete.cfm" addToken="no">
228:   <cfelseif isDefined("form.btnConfirmedDelete")>
229:     <cfset client.lookupID = -1>
230:     <cfset client.detailID = -1>
231:     <cfset client.userName = "Unable to delete #form.edtName#">
232:     <cftransaction>
233:       <cfif isDefined("form.moveGroup") and form.moveGroup gt 0>
234:         <!-- Move the links to a new group -->
235:         <cfquery name="qryMoveLinks" dataSource="#ap_dataSource#">
236:           update resourceLinks
237:           set resourceLinks.groupID = #form.moveGroup#
238:           where resourceLinks.groupID = #form.groupID#
239:         </cfquery>
240:
241:         <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
242:           select distributors.resourceImages
243:           from distributors
244:           where distributors.distributorID = #form.distributorID#
245:         </cfquery>

```

```

246: <cfset lstDirectory = "">
247: <cfdirectory
248:   name = "lstDirectory"
249:   action = "list"
250:   directory = "#qryImagePath.resourceImages#"
251:   filter="#form.groupID# *.*"
252: >
253:
254: <cfloop query="lstDirectory">
255:   <cfset coldName = #lstDirectory.name#>
256:   <cfset nAt = findNoCase("_", coldName)>
257:   <cfif nAt gt 0>
258:     <cfset cNewName = "#form.moveGroup#_#right(coldName, len(coldName)-nAt)#">
259:     <cfelse>
260:       <cfset cNewName = coldName>
261:     </cfif>
262:     <cffile
263:       action="rename"
264:       source="#qryImagePath.resourceImages##coldName#"
265:       destination="#qryImagePath.resourceImages##cNewName#"
266:     >
267:   </cfloop>
268:
269: </cfif>
270: <cfquery name="qryDelete" datasource="#ap_dataSource#">
271:   delete from resourceLinks
272:   where resourceLinks.groupID = #form.groupID#
273: </cfquery>
274: <cfquery name="qryDelete" datasource="#ap_dataSource#">
275:   delete from resourceGroups
276:   where resourceGroups.groupID = #form.groupID#
277: </cfquery>
278:
279: <cfquery name="qryImagePath" datasource="#ap_dataSource#">
280:   select distributors.resourceImages
281:   from distributors
282:   where distributors.distributorID = #form.distributorID#
283: </cfquery>
284: <cfset lstDirectory = "">
285: <cfdirectory
286:   name = "lstDirectory"
287:   action = "list"
288:   directory = "#qryImagePath.resourceImages#"
289:   filter="#form.groupID# *.*"
290: >
291:
292: <cfquery name="qryImagePath" datasource="#ap_dataSource#">
293:   select distributors.resourceImages
294:   from distributors

```

```

295: where distributors.distributorID=#form.distributorID# and distributors.distributorID#=#form.distributorID#
296: </cfquery>
297: <cfloop query="lstDirectory">
298:     <cffile
299:         action="delete"
300:         file="#gryImagePath.resourceImages#lstDirectory.name#"
301:     >
302: </cfloop>
303:
304:     <cfset client.userMessage = "" & #form.edtName# & " resource group was deleted">
305: </cftransaction>
306: <cflocation url="resourceAdm.cfm" addtoken="no">
307: </cfif>
308:
309: <cfset client.lookupID = -1>
310: <cfset client.detailID = -1>
311: <cfset client.imageType = -1>
312: <!-- Get ID number from edit -->
313: <cfloop collection="#form#" item="cName">
314:     <cfif ucase(left(#cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
315:         <cfset cValue = mid(#cName#, 5, len(#cName#)-6)>
316:         <cfset client.lookupID = form.GroupID>
317:         <cfset client.detailID = val(cValue)>
318:         <cfset client.imageType = -1>
319:     </cfif>
320:
321:     <cfif client.lookupID gt -1 and client.lookupID gt -1>
322:         <cflocation url="resourceMaint.cfm" addToken="no">
323:         </cfif>
324:     </cfloop>
325:
326: <!-- Get ID number for delete detail item -->
327: <cfloop collection="#form#" item="cName">
328:     <cfif ucase(left(#cName#,6)) is "DELETE" and findNoCase(".X", #cName#,1) gt 0>
329:         <cfset cValue = mid(#cName#, 7, len(#cName#)-8)>
330:         <cfset client.lookupID = form.GroupID>
331:         <cfset client.detailID = val(cValue)>
332:         <cfset client.imageType = -1>
333:     </cfif>
334:
335:     <cfif client.lookupID gt -1 and client.lookupID gt -1>
336:         <cfset client.userMessage = "Unable to delete link.">
337:         <cfquery name="gryDelete" dataSource="#ap_dataSource#">
338:             delete from resourceLinks
339:             where resourceLinks.linkID = #client.detailID#
340:         </cfquery>
341:         <cfset client.detailID = -1>
342:         <cfset client.userMessage = "link deleted.">
343:         <cflocation url="resourceMaint.cfm" addToken="no">

```

```
344:         </cfif>
345:     </cfloop>
346:
347:     <!-- If anything else, then go back to the admin page -->
348:     <cflocation url="resourceAdm.cfm" addToken="no">
349:
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN" >
2:
3: <cfparam name="cNavColor" default="#ap_defaultNavColor#">
4: <cfparam name="cMenuColor" default="#ap_defaultMenuColor#">
5:
6:
7: <!-- If a community is not passed, then exit -->
8: <cfif not isdefined("URL.groupID")>
9:   <cfllocation url="resourceMaint.cfm" addtoken="no">
10: <cfelse>
11:   <cfset nGroupID = URL.groupID>
12:   </cfif>
13:
14:   <cfquery name="qryPage" dataSource="#ap_dataSource#">
15:     select name
16:     from resourceGroups
17:     where resourceGroups.groupID = #nGroupID#
18:   </cfquery>
19:
20:   <cfquery name="qryDetail" dataSource="#ap_dataSource#">
21:     select *
22:     from resourceLinks
23:     where resourceLinks.groupID = #nGroupID#
24:     order by resourceLinks.sortOrder, resourceLinks.description
25:   </cfquery>
26:
27:
28: <html>
29: <head>
30:   <!--
31:   <title><cfoutput>#ap_agencyName# - #qryLinkType.manuTitle#</cfoutput></title>
32:   ---
33:   <title>Resource Links View</title>
34:   <link rel="stylesheet" href="style1.css" type="text/css">
35: </head>
36:
37: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
38:   <cfoutput>
39:
40:   <table width="760" border="0" cellpadding="0" cellspacing="0">
41:     <tr>
42:       <td align="right" valign="top" bgcolor="#cNavColor#" width="135">
43:         &nbsp;
44:       <!--
45:       <cfinclude template="navigation.cfm">
46:       ---
47:     </td>
48:     <td width="500" valign="top" align="center">
49:       <table border="0" width="480" cellspacing="2">

```

```

121 --- exclude "molecule" folder, "flu" ---

```

4.0 Transitional XEN" >

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML
2:
3:  <html>
4:  <head>
5:    <cfoutput>
6:    <title>#client.backofficeName# Verify Security Tree Recreation</title>
7:    </cfoutput>
8:    <link rel="stylesheet" href="style1.css" type="text/css">
9:  </head>
10:
11:  <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
12:  <cfinclude template="include/nocache.cfm">
13:  <p><cfinclude template="include/header.cfm"></p>
14:
15:
16:  <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
17:    <tr bgcolor="#cccc99">
18:      <td>
19:        <span class="h2"><b>Recreate Security Tree</b></span>
20:      </td>
21:    </tr>
22:
23:    <tr bgcolor="#cccccc">
24:      <td align="center">
25:        <span class="h2"><b> * * W A R N I N G * * </b></span>
26:      <br><br>
27:    </td>
28:  </tr>
29:  <tr bgcolor="#cccccc">
30:    <td>
31:    <p><b>Recreating the Security Access Tree can take several minutes and cause problems for other users logged into the
Back Office while the tree is generated.</b></p>
    <br>
32:    Are you sure you want to recreate the Security Access Tree?
33:    <br>
34:    <br>
35:    <br>
36:    <b><a href="createSecurityTree.cfm?requestTimeout=5000">No, just view the Security Tree</a></b>
37:    <br><br>
38:    <b><a href="createSecurityTree.cfm?requestTimeout=5000&generate=Yes">Yes, create the Security Tree</a></b>
39:    </td>
40:  </tr>
41:  </table></p>
42:
43:  </body>
44:  </html>

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html40/strict.dtd">
2:
3: <cfset client.userID = -1>
4: <cfset client.userName = "">
5: <cfset client.entityID = -1>
6: <cfset client.entityType = -1>
7: <cfset client.currentEntityID = -1>
8: <cfset client.currentEntityType = -1>
9: <cfset client.distributorID = -1>
10: <cfset client.backofficeName = "">
11: <cfset client.userMessage = "">
12:
13: <cfif isDefined("form.btnCancel")>
14:   <cflocation url="login.cfm" addToken="no">
15: </cfif>
16:
17: <cfquery name="qryFindInfo" dataSource="#ap_dataSource#">
18:   select * from security
19:   where security.email = '#form.edtEmail#'
20: </cfquery>
21:
22: <html>
23: <head>
24:   <title>Back Office Administration Forgot Password</title>
25:   <link rel="stylesheet" href="style1.css" type="text/css">
26: </head>
27:
28: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
29: <cfinclude template="include\nocache.cfm">
30:
31: <cfif qryFindInfo.recordCount ge 1>
32:   <cfif qryFindInfo.hint is not "">
33:     <cfmail subject="Back Office Information"
34:       from="Administrator"
35:       to="#form.edtEmail#"
36:     >
37:     Here is the information you requested from the Back Office:
38:
39:     Your password hint: #qryFindInfo.hint#
40:
41:     If you still have trouble logging in, please contact your administrator.
42:   </cfmail>
43:   <cfset client.userMessage = "An email with the requested information has been sent.">
44: <cfelse>
45:   <cfset client.userMessage = "You do not have a hint specified. Please contact your administrator to have your password
   changed.">
46:   </cfif>
47: <cfelse>
48:   <cfset client.userMessage = "The specified email address was not found.">

```



```
49: </cfif>
50: <cflocation url="login.cfm" addToken="no">
51:
52:
53: </body>
54: </html>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN">
2:
3: <cfset client.gotoPage = "specialtyAdm.cfm">
4: <cfif client.currentEntityType lt #ap_securityMastDist# and client.lookupDistID is -1>
5:   <!-- We do not know what distributor we should be editing, so find out -->
6:   <cfset client.lookupDistID = -1>
7:   <cfset client.lookupAgencyID = -1>
8:   <cfset client.lookupID = -1>
9:   <cfset client.DetailID = -1>
10:   <cflocation url="distSelect.cfm" addToken="no">
11: </cfif>
12:
13:
14: <cfif client.currentEntityType lt #ap_securityMastDist#>
15:   <cfquery name="qryDist" dataSource="#ap_dataSource#">
16:     select distributors.name as distName
17:     from distributors
18:     where distributors.distributorID = #client.lookupDistID#
19:   </cfquery>
20:   <cfset cDistName = qryDist.distName>
21:   <cfelseif client.currentEntityType gte #ap_securityMastDist#>
22:     <cfset client.lookupDistID = client.currentDistributorID>
23:     <cfset cDistName = "">
24:   </cfif>
25:
26:   <cfparam name="URL.sortBy" default="name">
27:   <cfset client.lookupID = -1>
28:   <cfset client.detailID = -1>
29:   <cfset client.imageType = -1>
30:   <cfset client.lookupAgencyID = -1>
31:
32:   <cfinclude template="include\clearOldFields.cfm">
33:
34:   <!-- Display rows -->
35:   <cfparam name="nStartFrom" default="1">
36:   <cfparam name="nToDisplay" default="#client.displayRows#">
37:   <cfparam name="nEnd" default="#client.displayRows#">
38:
39:
40:   <cfquery name="qryEditList" dataSource="#ap_dataSource#">
41:     select specialtyPages.specialtyPageID, specialtyPages.name
42:     from specialtyPages
43:     join securityAccess on
44:       (securityAccess.entityType = #ap_securityMastDist# or securityAccess.entityType = #ap_securityDist#
45:        and securityAccess.entityID = specialtyPages.distributorID
46:        and securityAccess.hierarchyID like '#client.hierarchyID#%'
47:        where specialtyPages.distributorID = #client.lookupDistID#
48:   </cfquery>
49:

```

[illegible]

```

99: </cfif>
100: <cfset client.userName = "">
101: <cfset client.lookupID = -1>
102: <cfset client.detailID = -1>
103:
104:
105: <tr bgcolor="#cccc99">
106:   <td colspan="4">
107:     <b><b>Add a Specialty Page</a>
108:   </td>
109: </tr>
110:
111: <tr bgcolor="#cccccc">
112:   <td>Sort by <a href="specialtyAdm.cfm?SortBy=name"><b>Name</b></a></td>
113:   <td><b></td>
114:   <td><b></td>
115:   <td><b></td>
116: </tr>
117:
118:
119: <CFIF qryEditList.recordCount is 0>
120:   <TR><TD COLSPAN="4"><I>There are no specialty pages defined</I></TD></TR>
121: </CFIF>
122: <cfset lColor = True>
123: <form action="specialtyMaint.cfm" method="post">
124:   <cfoutput query="qryEditList" startrow="#nstartFrom#" maxrows="#ntoDisplay#">
125:     <cfset lColor = not lColor>
126:     <tr valign="center" <cfif lColor is TRUE>bgcolor="#eeeeee"</cfif>>
127:       <td>#qryEditList.name#</td>
128:       <td><b></td>
129:       <td align="center"><input type="image" name="edit#qryEditList.specialtyPageID#" src="#ap_commonImages#edit.gif"
        alt="Edit" border="0"></td>
        <td align="center"><input type="image" name="view#qryEditList.specialtyPageID#" src="#ap_commonImages#view.gif"
        alt="View" border="0"></td>
      </tr>
    </cfoutput>
  </form>
</table></p>
<CFSET nPrevStart = nStartFrom-nToDisplay>
<CFSET nNextStart = nStartFrom+nToDisplay>
<CFSET nPrevEnd = #nPrevStart#+nToDisplay-1>
<CFSET nNextEnd = #nNextStart#+nToDisplay-1>
<cfif nPrevStart gte 1 or nNextStart lte qryEditList.recordCount>
  <table border="0" align="center">
    <tr>
    <cfif nPrevStart gte 1>
    <td>
    <form action="specialtyAdm.cfm?sortBy=url.sortBy#" METHOD="POST">

```

```
146: <input type="hidden" name="nStartFrom" value="#nStartFrom" sortBy="#url.sortBy#" METHOD="POST">
147: <input type="hidden" name="nToDisplay" value="#nToDisplay#">
148: <input type="hidden" name="nEnd" value="#nPrevEnd#">
149: <input type="submit" value="Previous #nToDisplay#">
150: </FORM>
151: </td>
152: </cfif>
153: <cfif nNextStart lte qryEditList.recordCount>
154: <td>
155: <form action="specialtyAdm.cfm?sortBy=#url.sortBy#" METHOD="POST">
156: <input type="hidden" name="nStartFrom" value="#nNextStart#">
157: <input type="hidden" name="nToDisplay" value="#nToDisplay#">
158: <input type="hidden" name="nEnd" value="#nNextEnd#">
159: <cfset nLeftToShow = min(nToDisplay, (qryEditList.recordcount - cToDisplay))>
160: <input type="submit" value="Next #nLeftToShow#">
161: </form>
162: </td>
163: </cfif>
164: </tr>
165: </table>
166: </cfif>
167:
168: </body>
169: </html>
170:
```

#### 4.0 Transitional/JEN"X

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <cfif client.currentEntityType lt #ap_securityMastDist#>
4:   <cfquery name="qryDist" dataSource="#ap_dataSource#">
5:     select distributors.name as distName
6:     from distributors
7:     where distributors.distributorID = #client.lookupDistID#
8:   </cfquery>
9:   <cfset cDistName = qryDist.distName>
10:  <cfelseif client.currentEntityType gte #ap_securityMastDist#>
11:    <cfset client.lookupDistID = client.currentDistributorID>
12:    <cfset cDistName = "">
13:  </cfif>
14:
15:  <!-- Get ID number from edit -->
16:  <cfloop collection="#form#" item="cName">
17:    <cfif ucase(left(cName#,4)) is "EDIT" and findNoCase(".",X", #cName#,1) gt 0>
18:      <cfset cValue = mid(cName#, 5, len(cName#)-6)>
19:      <cfset client.lookupID = val(cValue)>
20:      <cfset client.detailID = -1>
21:    </cfif>
22:  </cfloop>
23:
24:  <!-- Get ID number from edit -->
25:  <cfloop collection="#form#" item="cName">
26:    <cfif ucase(left(cName#,4)) is "VIEW" and findNoCase(".",X", #cName#,1) gt 0>
27:      <cfset cValue = mid(cName#, 5, len(cName#)-6)>
28:      <cfset client.lookupID = -1>
29:      <cfset client.detailID = -1>
30:      <cfset client.userName = "">
31:      <cflocation url="./specialtyPageView.cfm?specialtyPageID=#cValue#" addToken="no">
32:    </cfif>
33:  </cfloop>
34:
35:
36:  <cfif not isDefined("client.lookupID")>
37:    <cflocation url="specialtyAdm.cfm" addToken="no">
38:  </cfif>
39:  <cfparam name="client.userName" default="">
40:  <cfparam name="client.imageType" default="-1">
41:
42:  <cfquery name="qryFindSpecialty" dataSource="#ap_dataSource#">
43:    select * from specialtyPages
44:    where specialtyPages.specialtyPageID = #client.lookupID#
45:  </cfquery>
46:
47:  <cfquery name="qryPropertyTypes" dataSource="#ap_dataSource#">
48:    select propertyTypeID, propertyType
49:    from propertyTypeValues

```

where propertyTypeValues.distributorID = #testClient.lookupDistID# and order by propertyType

```

50: where propertyTypeValues.distributorID = #testClient.lookupDistID# and order by propertyType
51: order by propertyType
52: </cfquery>
53:
54:
55: <cfif qryFindSpecialty.recordCount gt 0>
56: <cfset nSpecialtyID = qryFindSpecialty.specialtyPageID>
57: <cfset nDistributorID = qryFindSpecialty.distributorID>
58: <cfelse>
59: <cfset nSpecialtyID = -1>
60: <cfif client.currentEntityType gte #ap_securityMastDist#>
61: <cfset nDistributorID = client.currentDistributorID>
62: <cfelseif client.lookupDistID is not -1>
63: <cfset nDistributorID = client.lookupDistID>
64: <cfelse>
65: <cflocation url="specialtyAdm.cfm" addToken="no">
66: </cfif>
67: </cfif>
68:
69:
70: <cfinclude template="include\javaValidate.cfm">
71:
72: <script language="JavaScript">
73: <!--
74: function validate(testform) {
75: var results = "";
76: var lResult = true;
77:
78: if (removeSpaces(testform.edtName.value) == "") {
79: results = results + " * Please enter a name for the specialty page.\r";
80: lResult = false;
81: }
82: if (!isValidDate(testform.edtBeginDate.value)) {
83: if (removeSpaces(testform.edtBeginDate.value) == "") {
84: results = results + " * Please enter a valid beginning date.\r";
85: }
86: else {
87: results = results + " * " + testform.edtBeginDate.value + " is not valid. Please enter a valid beginning date.\r";
88: }
89: lResult = false;
90: }
91:
92: if (!isValidDate(testform.edtEndDate.value)) {
93: if (removeSpaces(testform.edtEndDate.value) == "") {
94: results = results + " * Please enter a valid ending date.\r";
95: }
96: else {
97: results = results + " * " + testform.edtEndDate.value + " is not valid. Please enter a valid ending date.\r";
98:

```



```

99:     }
100:     lResult = false;
101: }
102:
103: if ((removeSpaces(testform.edtMenuSortOrder.value) != "") && (!isNumber(testform.edtMenuSortOrder.value))) {
104:     results = results + "<*>" + testform.edtMenuSortOrder.value + "<*>" is not a valid numeric menu sort order value.<br>";
105:     lResult = false;
106: }
107:
108: // Netscape does not recognize the value of select elements, but does know which item was selected
109: if ((testform.edtDistributorID.value == "-1") || (testform.edtDistributorID.selectedIndex == 0)) {
110:     results = results + "<*> You must select a distributor for this specialty page.<br>";
111:     lResult = false;
112: }
113:
114: if (!lResult) {
115:     window.alert(results);
116: }
117: return lResult;
118: }
119: </script>
120:
121: <html>
122: <head>
123: <cfoutput>
124: <title>#client.backofficeName# Backoffice Specialty Page Maintenance</title>
125: </cfoutput>
126: <link rel="stylesheet" href="style1.css" type="text/css">
127: </head>
128:
129: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
130: <cfinclude template="include\nocache.cfm">
131:
132: <p><cfinclude template="include\header.cfm"></p>
133:
134: <cfoutput>
135:
136: <form action="specialtyUpdate.cfm" method="post" onsubmit="return validate(this)">
137:   <input type="hidden" name="specialtyPageID" value="#nSpecialtyID#">
138:   <input type="hidden" name="edtDistributorID" value="#nDistributorID#">
139:   <input type="hidden" name="distributorID" value="#nDistributorID#">
140:   <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
141:     <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Specialty Page Maintenance</b></span>
142:     <cfif client.lookupID is -1>
143:       <nbsp><b>Create a new specialty page</b>
144:     <cfif cDistName is not "">
145:       for #cDistName#
146:     </cfif>
147:

```

```

148: )
149: </cfif>
150: </td></tr>
151:
152: <CFIF client.userMessage is not "">
153:   <tr bgcolor="eeeeee">
154:     <td colspan="5"><p>font color="red">#client.userMessage#</font></p></td>
155:   </tr>
156:   <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
157: </CFIF>
158: <cfset client.userMessage = "">
159:
160: <tr bgcolor="eeeeee">
161:   <td width="15%"><b>Name:</b></td>
162:   <td colspan="4"><input type="text" name="#qryFindSpecialty.name#" value="#qryFindSpecialty.name#" size="60"></td>
163: </tr>
164: <tr bgcolor="##eeeeee">
165:   <td width="15%"><b>Begin Date:</b></td>
166:   <td colspan="4"><input type="text" name="edtBeginDate" value="#dateFormat(qryFindSpecialty.beginDate,"mm/dd/yyyy")#"
size="10"><i>(MM/DD/YY or MM/DD/YYYY)</i></td>
167:   <td width="23%">&nbsp;</td>
168:   <td width="15%"><b>End Date:</b></td>
169:   <td colspan="4"><input type="text" name="edtEndDate" value="#dateFormat(qryFindSpecialty.endDate,"mm/dd/yyyy")#"
size="10"><i>(MM/DD/YY or MM/DD/YYYY)</i></td>
170: </tr>
171: <tr bgcolor="##eeeeee">
172:   <td width="15%">Menu Title:</td>
173:   <td colspan="4"><input type="text" name="edtMenuTitle" value="#qryFindSpecialty.menuTitle#" size="30"></td>
174:   <td width="23%">&nbsp;</td>
175:   <td width="15%">Menu Sort Order:</td>
176:   <td colspan="4"><input type="text" name="edtMenuSortOrder" value="#qryFindSpecialty.menuSortOrder#" size="2"></td>
177: </tr>
178: <tr bgcolor="##eeeeee">
179:   <td colspan="5">Classified Property Type:</td>
180:   <td colspan="5">
181:     <select name="edtClassPropType">
182:       <option value="0"><cfif client.lookupID is -1 or qryFindSpecialty.classPropertyType le 0> selected</cfif>>Not
Assigned
183:       <cfloop query="qryPropertyTypes">
184:         <option value="#qryPropertyTypes.propertyTypeID#" <cfif qryFindSpecialty.classPropertyType is
qryPropertyTypes.propertyTypeID> selected</cfif>>#qryPropertyTypes.propertyType#
185:       </cfloop>
186:     </select>
187:   </td>
188:   <td colspan="4">&nbsp;</td>
189:   <td colspan="5">Classified Region:</td>
190:   <td colspan="5">&nbsp;</td>
191: </tr>
192: <tr bgcolor="##eeeeee">

```

```

193: <td width="15%">Search Property Type:</td>
194: <td width="34%">
195: <select name="edtSearchPropType">
196: <option value="0"><cfif client.lookupID is -1 or qryFindSpecialty.searchPropertyType le 0> selected</cfif>>Not
Assigned
197: <cfloop query="qryPropertyTypes">
198: <option value="#qryPropertyTypes.propertyTypeID#" <cfif qryFindSpecialty.searchPropertyType is
qryPropertyTypes.propertyTypeID> selected</cfif>>#qryPropertyTypes.propertyTypeID#
199: </cfloop>
200: </select>
201: </td>
202: <td colspan="3">&nbsp;</td>
203: </tr>
204:
205: <!--
206: <cfif client.currentEntityType le 3>
207: <cfquery name="qryDist" datasource="#ep_datasource#">
208: select distributors.distributorID, distributors.name
209: from distributors
210: order by name
211: </cfquery>
212: <table border="1">
213: <td width="15%"><p>Distributor:</p></td>
214: <td colspan="3">
215: <select name="edtDistributorID">
216: <option value="1"><cfif distributorID le 0> selected</cfif>>Not Assigned
217: <cfloop query="qryDist">
218: <option value="#qryDist.distributorID#" <cfif qryFindSpecialty.distributorID is distributorID>
selected</cfif>>#qryDist.name#
219: </cfloop>
220: </select>
221: </td>
222: </tr>
223: <cfif ne>
224: <input type="hidden" name="edtDistributorID" value="#distributorID#">
225: </cfif>
226: -->
227:
228:
229: <tr bgcolor="#eeeeee">
230: <td width="15%">Description:</td>
231: <td colspan="4">
232: <textarea name="edtDesc" rows="5" cols="60" wrap="virtual">#trim(qryFindSpecialty.description)#</textarea>
233: </td>
234: </tr>
235:
236:
237: <tr bgcolor="eeeeee">
238: <cfif qryFindSpecialty.recordCount is 0>

```

```

239: <td colspan="5">
240: <input type="submit" name="btnUpdate" value="Add Specialty Page">
241: <input type="reset" value="Reset Info">
242: </td>
243: <cfelse>
244: <td colspan="4">
245: <input type="submit" name="btnUpdate" value="Update Specialty Page">
246: <input type="reset" value="Reset Info">
247: <input type="submit" name="btnView" value="View Specialty Page">
248: </td>
249: <td align="right">
250: <input type="submit" name="btnDelete" value="Delete Specialty Page">
251: </td>
252: </cfif>
253: </tr>
254: </table>
255: </form>
256: </cfoutput>
257:
258: <!-- If this specialty page has already been created, allow user to edit -->
259:
260: <cfif qryFindSpecialty.recordCount gt 0>
261: <script language="JavaScript">
262: <!--
263: function validateDetail(testform) {
264: var results = "";
265: var lResult = true;
266:
267: if ((removeSpaces(testform.edtSortOrder.value) != "") && (!isNumber(testform.edtSortOrder.value))) {
268: results = results + " * " + testform.edtSortOrder.value + " is not a valid numeric sort order value.\r";
269: lResult = false;
270: }
271:
272: if (!lResult) {
273: window.alert(results);
274: }
275:
276: return lResult;
277: }
278: -->
279: </script>
280:
281: <cfquery name="qryDetail" dataSource="#app_dataSource#">
282: select specialtyDetail.*, imageTypes.description as imageName
283: from specialtyDetail
284: left outer join imageTypes on imageTypes.imageType = specialtyDetail.imageType
285: where specialtyDetail.specialtyPageID = #client.lookupID#
286: order by specialtyDetail.sortOrder
287: </cfquery>

```

```

288: <cfquery name="qryEdit" dataSource="#ap_dataSource#">
289: select specialtyDetail.*,
290: imageTypes.isFormField, imageTypes.isApplet, imageTypes.isURL
291: from specialtyDetail
292: left outer join imageTypes on imageTypes.imageType = specialtyDetail.imageType
293: where specialtyDetail.specialtyPageID = #client.lookupID#
294: and specialtyDetail.specialtyDetailID = #client.detailID#
295: </cfquery>
296: <cfquery name="qryImageTypes" dataSource="#ap_dataSource#">
297: select imageType, description, isFormField, isApplet, isURL
298: from imageTypes
299: order by description
300: </cfquery>
301:
302:
303: <!-- Set default values -->
304: <cfif qryEdit.recordCount is 0> <!-- New Record -->
305: <cfif isDefined("client.old_sortOrder")>
306: <cfset nSortOrder = client.old_sortOrder>
307: <cfelse>
308: <cfset nSortOrder = "1">
309: </cfif>
310:
311: <cfquery name="qryDefault" dataSource="#ap_dataSource#">
312: select imageType from imageTypes
313: where imageTypes.description = 'Standard Photo'
314: </cfquery>
315: <cfif client.imageType gt -1>
316: <cfset nImageType = client.imageType>
317: <cfelseif qryDefault.recordCount gt 0>
318: <cfset nImageType = qryDefault.imageType>
319: <cfelse>
320: <cfset nImageType = 0>
321: </cfif>
322:
323: <cfelse> <!-- Existing Record -->
324: <cfif isDefined("client.old_sortOrder")>
325: <cfset nSortOrder = client.old_sortOrder>
326: <cfelse>
327: <cfset nSortOrder = qryEdit.sortOrder>
328: </cfif>
329:
330: <cfif client.imageType gt -1>
331: <cfset nImageType = client.imageType>
332: <cfelse>
333: <cfset nImageType = qryEdit.imageType>
334: </cfif>
335: </cfif>
336: <cfif isDefined("client.old_title")>

```

```

337:      <cfset cTitle = client.old_title>
338:    </cfset>
339:    <cfset cTitle = trim(qryEdit.title)>
340:  </cfif>
341:  <cfif isDefined("client.old_alignment")>
342:    <cfset cAlignment = client.old_alignment>
343:  </cfelse>
344:    <cfset cAlignment = trim(qryEdit.alignment)>
345:  </cfif>
346:  <cfif isDefined("client.old_desc")>
347:    <cfset cDesc = client.old_desc>
348:  </cfelse>
349:    <cfset cDesc = trim(qryEdit.text)>
350:  </cfif>
351:
352:
353:  <cfquery name="qryImageInfo" dataSource="#ap_dataSource#">
354:    select formTitle, isFormField, isApplet, isURL
355:    from imageTypes
356:    where imageTypes.imageType = #nImageType#
357:  </cfquery>
358:
359:  <form action="specialtyUpdate.cfm" method="post" enctype="multipart/form-data" onsubmit="return validateDetail(this)">
360:    <cfoutput>
361:      <input type="hidden" name="distributorID" value="#nDistributorID#">
362:      <input type="hidden" name="specialtyPageID" value="#client.lookupID#">
363:      <input type="hidden" name="specialtyDetailID" value="#client.detailID#">
364:      <input type="hidden" name="originalImage" value="#qryEdit.image#">
365:      <input type="hidden" name="originalUserImage" value="#qryEdit.userName#">
366:    </cfoutput>
367:
368:    <cfif qryDetail.recordCount is 0>
369:      <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
370:        <tr><td colspan="6"><i><b>There are no paragraphs defined.</b></i></td></tr>
371:        <tr><td colspan="6"><b><nbsp;</b></td></tr>
372:      </table>
373:    </cfelse>
374:    <table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
375:      <tr valign="top" bgcolor="#cccccc">
376:        <td><b>Image Type</b></td>
377:        <td><b>Title</b></td>
378:        <td><b>Text</b></td>
379:        <td><b>Image Name</b></td>
380:        <td><b>Alignment</b></td>
381:        <td><b>Order</b></td>
382:        <td><b><nbsp;</b></td>
383:      </tr>
384:      <cfoutput query="qryDetail">
385:        <tr valign="top" bgcolor="#<cfif qryDetail.specialtyDetailID is client.detailID>#ffffcc<cfelse>#eeeeee</cfif>">

```

```

386: <td>
387: <cfif trim(qryDetail.imageName) is "">&nbsp;</cfif>#qryDetail.imageName#
388: </td>
389: <td>
390: <cfif trim(qryDetail.title) is "">&nbsp;</cfif>#qryDetail.title#
391: </td>
392: <td>
393: <cfif trim(qryDetail.text) is "">&nbsp;</cfif>#qryDetail.text#
394: </td>
395: <td>
396: <cfif trim(qryDetail.userName) is "">&nbsp;</cfif>#qryDetail.userName#
397: </td>
398: <td>#qryDetail.alignment#</td>
399: <td>#qryDetail.sortOrder#</td>
400: <td align="center">
401: <input type="image" name="edit#qryDetail.specialtyDetailID#" src="#ap_commonImages#edit.gif" alt="Edit"
border="0">
402: <br>
403: <input type="image" name="delete#qryDetail.specialtyDetailID#" src="#ap_commonImages#delete.gif" alt="Delete"
border="0">
404: </td>
405: </tr>
406: </cfoutput>
407: </table>
408: </cfif>
409: <cfoutput>
410: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
411: <tr><td colspan="5">&nbsp;</td></tr>
412: <cfif client.detailID is -1>
413: <tr bgcolor="#cccccc"><td colspan="5"><b>Add a paragraph</b></td></tr>
414: <cfelse>
415: <tr bgcolor="#cccccc"><td colspan="5"><b>Edit this paragraph</b></td></tr>
416: </cfif>
417: <tr valign="top" bgcolor="#eeeeee">
418: <td><b>Image Type</b></td>
419: <td><b>Title</b></td>
420: <td><b>#qryImageInfo.formTitle#</b></td>
421: <td><b>Alignment</b></td>
422: <td><b>Order</b></td>
423: </tr>
424: <tr valign="top" bgcolor="#eeeeee">
425: <td>
426: <select name="edtImageType">
427: <cfloop query="qryImageTypes">
428: <option value="#qryImageTypes.imageType#"<cfif qryImageTypes.imageType is nImageType>
selected</cfif>#qryImageTypes.description#
</cfloop>
429: </select>
430: <cfif qryImageTypes.recordCount gt 1>
431:

```

```
432: <input type="submit" name="btnImageType" value="Change">
433: </cfif>
434: </td>
435: <td><input type="text" name="edTitle" value="#cTitle#"></td>
436: </td>
437: <cfif qryImageInfo.isFormField is "Y">
438: <input type="File" name="edImage"></td>
439: <cfelseif qryImageInfo.isApplet is "Y">
440: <input type="text" name="edImage">
441: <cfelseif qryImageInfo.isURL is "Y">
442: <input type="text" name="edImage">
443: <cfelse> <!-- The default if a new entry -->
444: <input type="File" name="edImage"></td>
445: </cfif>
446: </td>
447: <td>
448: <select name="edAlignment">
449: <option value="left"><cfif lcase(cAlignment) is "left"> selected</cfif><Left
450: <option value="middle"><cfif lcase(cAlignment) is "middle"> selected</cfif><Middle
451: <option value="right"><cfif lcase(cAlignment) is "right"> selected</cfif><Right
452: </select>
453: </td>
454: <td><input type="text" name="edSortOrder" value="#nSortOrder#" size="2"></td>
455: </tr>
456: <tr valign="top" bgcolor="#eeeeee">
457: <td colspan="5">
458: <b>Text:</b><br>
459: <textarea name="edtDesc" rows="5" cols="80" wrap="virtual">#trim(cDesc)#</textarea>
460: </td>
461: </tr>
462: <tr bgcolor="eeeeee">
463: <td colspan="5">
464: <cfif qryEdit.recordCount is 0>
465: <input type="submit" name="btnUpdateDetail" value="Add Paragraph">
466: <input type="reset" value="Reset Info">
467: <cfelse>
468: <input type="submit" name="btnUpdateDetail" value="Update Paragraph">
469: <input type="reset" value="Reset Info">
470: <input type="submit" name="btnCancelDetail" value="Cancel">
471: </cfif>
472: </td>
473: </tr>
474: </table>
475: </cfoutput>
476: </form>
477: </cfif>
478:
479:
480: </body>
```





11/29/2000 5:03:33 PM  
S:\FullImpact\FullImpact\admin\specialtyUpdate.cfm

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN" >
2:
3: <cfif not isDefined("form.specialtyPageID") >
4:   <cfset client.lookupID = -1>
5:   <cfset client.detailID = -1>
6:   <cfset client.imageType = -1>
7:   <cfset client.userName = "">
8:   <cflocation url="specialtyAdm.cfm" addtoken="no">
9: </cfif>
10:
11: <cfquery name="qryFindSpecialty" datasource="#ap_dataSource#">
12:   select specialtyPageID, name
13:   from specialtyPages
14:   where specialtyPageID = #form.specialtyPageID#
15: </cfquery>
16:
17: <cfinclude template="include\clearOldFields.cfm">
18: <cfset client.userName = "">
19: <cfset client.imageType = -1>
20:
21: <cfif isDefined("form.btnImageType") >
22:   <!-- A change in the image type has been requested -->
23:   <cfset client.lookupID = form.specialtyPageID>
24:   <cfset client.detailID = form.specialtyDetailID>
25:   <cfset client.imageType = form.edtImageType>
26:
27:   <cfset client.old_title = form.edtTitle>
28:   <cfset client.old_alignment = form.edtAlignment>
29:   <cfset client.old_sortOrder = form.edtSortOrder>
30:   <cfset client.old_desc = form.edtDesc>
31:
32:   <cflocation url="specialtyMaint.cfm" addToken="no">
33: </cfif>
34:
35:
36: <cfif isDefined("form.btnCancelDetail") > <!-- Cancel detail edit -->
37:   <cfset client.lookupID = #form.specialtyPageID#>
38:   <cfset client.detailID = -1>
39:   <cfset client.imageType = -1>
40:   <cfset client.userName = "">
41:   <cflocation url="specialtyMaint.cfm" addToken="no">
42: <cfelseif isDefined("form.btnCancelDelete") > <!-- Cancel detail edit -->
43:   <cfset client.lookupID = #form.specialtyPageID#>
44:   <cfset client.detailID = -1>
45:   <cfset client.imageType = -1>
46:   <cfset client.userName = "Deletion canceled.">
47:   <cflocation url="specialtyMaint.cfm" addToken="no">
48:
49: <cfelseif isDefined("form.btnView") >

```

```

50: <cflocation url="../specialtyPageView.cfm?specialtyPageID=#form.specialtyPageID#" addToken="no">
51:
52: <cfelseif isDefined("form.btnUpdateDetail")>
53: <cfquery name="qryFindDetail" dataSource="#ap_dataSource#">
54:   select specialtyDetailID
55:   from specialtyDetail
56:   where specialtyDetail.specialtyDetailID = #form.specialtyDetailID#
57: </cfquery>
58:
59: <cfif qryFindDetail.recordCount is 0>
60:   <cfset cTitle = preservesSingleQuotes(form.edtTitle)>
61:   <cfset cDesc = preservesSingleQuotes(form.edtDesc)>
62:   <cfset nSortOrder = val(form.edtSortOrder)>
63:
64:   <cfquery name="qryImageType" dataSource="#ap_dataSource#">
65:     select imageType, isFormField, isApplet, isURL
66:     from imageTypes
67:     where imageTypes.imageType = #form.edtImageType#
68:   </cfquery>
69:
70:   <cfif qryImageType.isFormField is "Y">
71:     <cfif trim(form.edtImage) is "">
72:       <cfset cImage = form.originalImage>
73:       <cfset cUserImage = form.originalUserImage>
74:     <cfelse>
75:       <cfquery name="qryImagePath" dataSource="#ap_dataSource#">
76:         select distributors.specialtyImages
77:         from distributors
78:         where distributors.distributorID = #form.distributorID#
79:       </cfquery>
80:       <!-- Upload the file to a unique name -->
81:       <cffile
82:         destination = "#qryImagePath.specialtyImages#"
83:         action = "UPLOAD"
84:         nameconflict = "OVERWRITE"
85:         fieldid = "edtImage"
86:       >
87:
88:       <cfset cImage = file.serverFile>
89:       <cfset cUserImage = file.serverFile>
90:
91:       <cfset cImagePath = file.serverDirectory & "\">
92:       <cfset cNewImage = "#cImagePath#trim(form.specialtyPageID)#_#file.serverFile#">
93:
94:       <cfif fileExists(cNewImage)>
95:         <cffile
96:           action = "DELETE"
97:           file="#cNewImage#"
98:         >

```

```

99:      </cfif>
100:
101:      <!-- Now rename the unique uploaded file to the new name -->
102:      <cffile
103:        action = "RENAME"
104:        source = "#file.serverDirectory#\#file.serverFile#"
105:        destination="#cNewImage#"
106:      >
107:
108:      <cfset cImage = cNewImage>
109:      </cfif>
110:      <cfelseif gryImageType.isURL is "Y">
111:        <cfset cImage = form.edtImage>
112:        <cfset cUserImage = form.edtImage>
113:        <cfelseif gryImageType.isApplet is "Y">
114:          <cfset cImage = form.edtImage>
115:          <cfset cUserImage = form.edtImage>
116:        <cfelse>
117:          <cfset cImage = form.edtImage>
118:          <cfset cUserImage = form.edtImage>
119:        </cfif>
120:
121:
122:      <cfquery name="qryInsert" dataSource="#ap_dataSource#">
123:        insert into specialtyDetail
124:          (specialtyPageID, sortOrder, title, image, userFilename, imageType,
125:           alignment, text)
126:        values
127:          (#form.specialtyPageID#, #nsSortOrder#, '#cTitle#',
128:           '#cImage#', '#cUserImage#', #form.edtImageType#, '#form.edtAlignmert#',
129:           '#cDesc#')
130:      </cfquery>
131:
132:      <cfset client.lookupID = form.specialtyPageID>
133:      <cfset client.detailID = -1>
134:      <cfset client.imageType = form.edtImageType> <!-- Keep last inserted image type -->
135:
136:      <cflocation url="specialtyMaint.cfm" addToken="no">
137:
138:    <cfelse>
139:      <cfset cTitle = preserveSingleQuotes(form.edtTitle)>
140:      <cfset cDesc = preserveSingleQuotes(form.edtDesc)>
141:      <cfset nsSortOrder = val(form.edtSortOrder)>
142:
143:      <cfquery name="qryImageType" dataSource="#ap_dataSource#">
144:        select imageType, isFormField, isApplet, isURL
145:        from imageTypes
146:        where imageTypes.imageType = #form.edtImageType#
147:      </cfquery>

```



```

197: <cfset cUserImage = form.edtImage>#form.edtImage#>
198: </cfif>
199:
200: <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
201:   update specialtyDetail
202: set
203:   sortOrder = #nSortOrder#,
204:   title = #cTitle#,
205:   imageType = #form.edtImageType#,
206:   alignment = '#form.edtAlignment#',
207:   image = '#cImage#',
208:   userFilename = '#cUserImage#',
209:   text = '#cDesc#'
210:   where specialtyDetail.specialtyDetailID = #form.specialtyDetailID#
211: </cfquery>
212:
213: <cfset client.lookupID = form.specialtyPageID>
214: <cfset client.detailID = -1>
215: <cfset client.imageType = -1>
216:
217: <cflocation url="specialtyMaint.cfm" addToken="no">
218:
219: </cfif>
220:
221: <cfelseif isDefined("form.btnUpdate")>
222: <cfif qryFindSpecialty.recordCount is 0>
223:   <cfset client.lookupID = -1>
224:   <cfset client.detailID = -1>
225:   <cfset client.userName = "There was an error while creating the specialty page.">
226:   <cftransaction>
227:     <cfset cName = preservesingleQuotes(form.edtName)>
228:     <cfset cMenuTitle = preservesingleQuotes(form.edtMenuTitle)>
229:     <cfset nMenuOrder = val(form.edtMenuSortOrder)>
230:     <cfset cDesc = preservesingleQuotes(form.edtDesc)>
231:
232:     <cfquery name="qryInsert" dataSource="#ap_dataSource#">
233:       insert into specialtyPages
234:         (distributorID, name, menuTitle, menuSortOrder, beginDate, endDate,
235:          searchPropertyType, classPropertyType, classRegion,
236:          description)
237:       values
238:         (#form.edtDistributorID#, '#cName#', '#cMenuTitle#', #nMenuOrder#,
239:          '#form.edtBeginDate#', '#form.edtEndDate#', #form.edtSearchPropType#,
240:          #form.edtClassPropType#, 0, '#cDesc#')
241:     </cfquery>
242:
243:     <cfquery name="qryGetID" dataSource="#ap_dataSource#">
244:       select max(specialtyPageID) as lastID
245:       from specialtyPages

```

```

246: </cfquery>
247: <cfset nDistID = qryGetID.lastID>
248: <cfset client.lookupID = nDistID>
249:
250: <cfset client.userName = "" & form.edtName & "" Specialty Page was created.">
251: </cftransaction>
252:
253: <cfif client.lookupID gt 0>
254:   <cflocation url="specialtyMaint.cfm" addToken="no">
255: <cfelse>
256:   <cflocation url="specialtyAdm.cfm" addToken="no">
257: </cfif>
258:
259: <cfelse>
260:   <cfset client.lookupID = form.specialtyPageID>
261:   <cfset client.detailID = -1>
262:   <cfset client.userName = "There was an error while updating the specialty page information.">
263:   </cftransaction>
264:   <cfset cName = preservesSingleQuotes(form.edtName)>
265:   <cfset cMenuTitle = preservesSingleQuotes(form.edtMenuTitle)>
266:   <cfset cMenuOrder = val(form.edtMenuSortOrder)>
267:   <cfset cDesc = preservesSingleQuotes(form.edtDesc)>
268:
269:   <cfquery name="qryUpdate" dataSource="#ap_dataSource#">
270:     update specialtyPages
271:     set distributorID = #form.edtDistributorID#,
272:       name = '#cName#',
273:       menuTitle = '#cMenuTitle#',
274:       menuSortOrder = #nMenuOrder#,
275:       beginDate = '#form.edtBeginDate#',
276:       endDate = '#form.edtEndDate#',
277:       searchPropertyType = #form.edtSearchPropType#,
278:       classPropertyType = #form.edtClassPropType#,
279:       classRegion = 0,
280:       description = '#cDesc#'
281:     where specialtyPages.specialtyPageID = #form.specialtyPageID#
282:   </cfquery>
283:
284:   <cfset client.detailID = -1>
285:   <cfset client.userName = "" & #form.edtName# & "" specialty page was updated.">
286:   </cftransaction>
287:
288:   <cfif client.lookupID gt 0>
289:     <cflocation url="specialtyMaint.cfm" addToken="no">
290:   <cfelse>
291:     <cflocation url="specialtyAdm.cfm" addToken="no">
292:   </cfif>
293: </cfif>
294: <cfelseif isDefined("form.btnDelete")>

```

```

295: <cflocation url="specialtyDelete.cfm" addToken="#form.edtName#">
296: <cfelseif isDefined("form.btnConfirmedDelete")>
297: <cfset client.lookupID = -1>
298: <cfset client.detailID = -1>
299: <cfset client.userName = "Unable to delete #form.edtName#">
300: <cftransaction>
301: <cfquery name="qryDelete" datasource="#ap_dataSource#">
302: delete from specialtyDetail
303: where specialtyDetail.specialtyPageID = #form.specialtyPageID#
304: </cfquery>
305: <cfquery name="qryDelete" datasource="#ap_dataSource#">
306: delete from specialtyPages
307: where specialtyPages.specialtyPageID = #form.specialtyPageID#
308: </cfquery>
309:
310: <cfquery name="qryImagePath" datasource="#ap_dataSource#">
311: select distributors.specialtyImages
312: from distributors
313: where distributors.distributorID = #form.distributorID#
314: </cfquery>
315: <cfset lstDirectory = "">
316: <cfdirectory
317: name = "lstDirectory"
318: action = "list"
319: directory = "#qryImagePath.specialtyImages#"
320: filter="#form.specialtyPageID# *.*"
321: >
322:
323: <cfloop query="lstDirectory">
324: <cfif
325: action="delete"
326: file="#qryImagePath.specialtyImages#lstDirectory.name#"
327: >
328: </cfloop>
329:
330: <cfset client.userName = "" & #form.edtName# & "' Specialty Page was deleted">
331: </cftransaction>
332: <cflocation url="specialtyAdm.cfm" addToken="no">
333: </cfif>
334:
335: <cfset client.lookupID = -1>
336: <cfset client.detailID = -1>
337: <cfset client.imageType = -1>
338: <!-- Get ID number from edit -->
339: <cfloop collection="#form#" item="cName">
340: <cfif ucase(left(cName#,4)) is "EDIT" and findNoCase(".X", #cName#,1) gt 0>
341: <cfset cValue = mid(cName#, 5, len(cName#)-6)>
342: <cfset client.lookupID = form.specialtyPageID>
343: <cfset client.detailID = val(cValue)>

```



```

344:     <cfset client.imageType = -1>
345:     </cfif>
346:
347:     <cfif client.lookupID gt -1 and client.lookupID gt -1>
348:         <cflocation url="specialtyMaint.cfm" addToken="no">
349:     </cfif>
350: </cfloop>
351:
352:     <!--- Get ID number for delete detail item -->
353:     <cfloop collection="#form#" item="cName">
354:         <cfif ucase(left(cName#,6)) is "DELETE" and findNoCase(".X", #cName#,1) gt 0>
355:             <cfset cValue = mid(cName#, 7, len(cName#)-8)>
356:             <cfset client.lookupID = form.specialtyPageID>
357:             <cfset client.detailID = val(cValue)>
358:             <cfset client.imageType = -1>
359:         </cfif>
360:
361:         <cfif client.lookupID gt -1 and client.lookupID gt -1>
362:             <cfset client.userMessage = "Unable to delete paragraph.">
363:             <cfquery name="qryDelete" dataSource="#ap_dataSource#">
364:                 delete from specialtyDetail
365:                 where specialtyDetail.specialtyDetailID = #client.detailID#
366:             </cfquery>
367:             <cfset client.detailID = -1>
368:             <cfset client.userMessage = "paragraph deleted.">
369:             <cflocation url="specialtyMaint.cfm" addToken="no">
370:         </cfif>
371:     </cfloop>
372:
373:     <!--- If anything else, then go back to the admin page -->
374:     <cflocation url="specialtyAdm.cfm" addToken="no">
375:

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <cfset client.gotoPage = "statsAdm.cfm">
4:
5: <!--
6: <cfinclude template="include\securityTest.cfm">
7: -->
8:
9: <cfparam name="URL.sortBy" default="name">
10: <cfset client.lookupID = -1>
11: <cfset client.detailID = -1>
12:
13: <!-- Display rows -->
14: <cfparam name="nStartFrom" default="1">
15: <cfparam name="ntoDisplay" default="#client.displayRows#">
16: <cfparam name="nEnd" default="#client.displayRows#">
17:
18: <cfparam name="form.edtFilterFrom" default="#dateFormat(now(), "mm/dd/yy")#">
19: <cfparam name="form.edtFilterTo" default="#dateFormat(now(), "mm/dd/yy")#">
20:
21: <cfparam name="form.edtFilterPage" default="-1|-1">
22:
23: <cfset nFilterType = listGetAt(form.edtFilterPage, 1, "|")>
24: <cfset nFilterID = listGetAt(form.edtFilterPage, 2, "|")>
25:
26: <cfinclude template="include\javaValidate.cfm">
27:
28: <script language="JavaScript">
29: <!--
30:     function validate(testform) {
31:         var results = "";
32:         var lResult = true;
33:
34:         if (!isValidDate(testform.edtFilterFrom.value)) {
35:             if (removeSpaces(testform.edtFilterFrom.value) == "") {
36:                 results = results + "** Please enter a valid beginning date.\r";
37:             }
38:         }
39:         results = results + "** " + testform.edtFilterFrom.value + " is not valid. Please enter a valid beginning
         date.\r";
40:     }
41:     lResult = false;
42: }
43:
44:
45: if (!isValidDate(testform.edtFilterTo.value)) {
46:     if (removeSpaces(testform.edtFilterTo.value) == "") {
47:         results = results + "** Please enter a valid ending date.\r";
48:     }

```

```

49:     else {
50:         results = results + " * " + testform.edtFilterTo.value + " is not valid. Please enter a valid ending date.\r";
51:     }
52:     lResult = false;
53: }
54:
55: if (!lResult) {
56:     window.alert(results);
57: }
58: return lResult;
59: }
60: ---
61: </script>
62:
63:
64:
65: <html>
66: <head>
67:     <cfoutput>
68:         <title>#client.backofficeName# Backoffice Stats</title>
69:     </cfoutput>
70:     <link rel="stylesheet" href="style1.css" type="text/css">
71: </head>
72:
73:
74: <body bgcolor="#ffffff" topmargin="0" leftmargin="0" marginheight="0" marginwidth="0">
75: <cfinclude template="include\nocache.cfm">
76: <p><cfinclude template="include\header.cfm"></p>
77:
78: <p><table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
79:     <tr bgcolor="#cccc99">
80:         <td colspan="5">
81:             <table border="0" cellpadding="0" cellspacing="0" align="left" width="100%">
82:                 <tr>
83:                     <td align="left">
84:                         <span class="h2"><b>Statistics</b></span>
85:                     </td>
86:                     </tr>
87:                 </table>
88:             </td>
89:             </tr>
90:
91: <cfif trim(client.userName) is not "">
92:     <tr bgcolor="#cccc99">
93:         <td colspan="5" align="center">
94:             <cfoutput><b>#client.userName#</b></cfoutput>
95:         </td>
96:     </tr>
97: </cfif>

```

```

98:
99: <cfset client.userName = ">
100: <cfset client.lookupID = -1>
101: <cfset client.detailID = -1>
102:
103: <tr bgcolor="#cccc99">
104:   <td colspan="5">
105:     <cfoutput>
106:       <form action="statsAdm.cfm" method="post" onsubmit="return validate(this)">
107:         <input type="text" name="edtFilterFrom" value="#form.edtFilterFrom#" size="8" maxlength="10">
108:         <input type="text" name="edtFilterTo" value="#form.edtFilterTo#" size="8" maxlength="10">
109:         <input type="submit" name="btnSubmit" value="Filter">
110:       </form>
111:     </td>
112:
113:     <select name="edtFilterPage">
114:       <option value="1|-1">All
115:       <option value="1|-1">Main Page
116:       <option value="2|-1">Properties
117:       <option value="3|-1">Agents
118:       <option value="4|-1">Agencies
119:       <option value="5|-1">Communities
120:       <option value="6|-1">Specialty Pages
121:       <option value="7|-1">Enhanced Agent Bios
122:       <option value="8|-1">Enhanced Agency Bios
123:       <option value="9|-1">Enhanced Property Views
124:     </select>
125:   </td>
126:   </td>
127:   </td>
128:   </td>
129: </tr>
130: </table>
131:
132: <cfset lstPages = "Main Page|Property|Agent|Agency|Community|Specialty Page|Enhanced Agent|Enhanced Agency|Enhanced
133:   Property">
134:
135: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
136:   <tr>
137:     <td colspan="2" align="left"><span class="h2"><b>Page Views</b></span></td>
138:   </tr>
139:   <tr>
140:     <td align="center" colspan="2">
141:       <cfquery name="qryView" dataSource="#ap_dataSource#">
142:         select count(distinct userIP) as viewCount
143:         from reporting
144:         where reporting.reportDate >= '#form.edtFilterFrom#'
145:         and reporting.reportDate <= '#form.edtFilterTo#'
146:         <cfif nFilterType is not "-1">

```

```

146:         and reporting.reportType = #nFilterType#
147:     </cfif>
148:     <cfif nFilterID is not "-1">
149:         and reporting.reportID = #nFilterType#
150:     </cfif>
151: </cfquery>
152: <cfoutput>
153: <b>Unique User Sessions:</b> #qryView.viewCount#<br>
154: </cfoutput>
155:
156: <cfquery name="qryView" dataSource="#ap_dataSource#">
157:     select count(userID) as viewCount
158:     from reporting
159:     where reporting.reportDate >= '#form.edtFilterFrom#'
160:     and reporting.reportDate <= '#form.edtFilterTo#'
161:     <cfif nFilterType is not "-1">
162:         and reporting.reportType = #nFilterType#
163:     </cfif>
164:     <cfif nFilterID is not "-1">
165:         and reporting.reportID = #nFilterType#
166:     </cfif>
167: </cfquery>
168: <cfoutput>
169: <b>Total Page Hits:</b> #qryView.viewCount#
170: </cfoutput>
171: </td>
172: </tr>
173:
174: <tr><td colspan="2"><b></td></tr>
175:
176: <tr>
177:     <td align="left" colspan="2"><span class="h2"><b>Top 10 Viewed Pages</b></span></td>
178: </tr>
179: <tr>
180:     <td width="5%"><b></td>
181:     <td>
182:         <!--
183:         <cfquery name="qryView" dataSource="#ap_dataSource#">
184:             select 'Main Page' as reportPage, reportID
185:             from reporting
186:             where reporting.action = 'VIEW'
187:             and reporting.reportType = 1
188:             and reporting.reportDate >= '#form.edtFilterFrom#'
189:             and reporting.reportDate <= '#form.edtFilterTo#'
190:             <cfif nFilterType is not "-1">
191:                 and reporting.reportType = #nFilterType#
192:             </cfif>
193:             <cfif nFilterID is not "-1">
194:                 and reporting.reportID = #nFilterType#

```

```

195:         </cfif>
196:     <cfloop from="2" to="#listLen(lstPages, '|')#" index="i">
197:         <cfif nFilterType is "-1" or nFilterType is 1>
198:             union select '#listGetAt(lstPages, i, '|')#' as reportPage, reportID
199:             from reporting
200:             where reporting.action = 'VIEW'
201:             and reporting.reportType = #i#
202:             and reporting.reportDate >= '#form.edtFilterFrom#'
203:             and reporting.reportDate <= '#form.edtFilterTo#'
204:         </cfif>
205:     </cfloop>
206:     <del by reportPage, reportID
207:
208:
209:     </cfquery>
210:
211:     <cfquery name="qryView" dataSource="#ap_dataSource#">
212:         select reportType, reportID
213:         from reporting
214:         where reporting.action = 'VIEW'
215:         and reporting.reportDate >= '#form.edtFilterFrom#'
216:         and reporting.reportDate <= '#form.edtFilterTo#'
217:     <cfif nFilterType is not "-1">
218:         and reporting.reportType = #nFilterType#
219:     </cfif>
220:     <cfif nFilterID is not "-1">
221:         and reporting.reportID = #nFilterType#
222:     </cfif>
223:     order by reportType, reportID
224: </cfquery>
225:
226:     <cfoutput query="qryView" maxrows="10" group="reportType">
227:         #listGetAt(lstPages, qryView.reportType, '|')#<br>
228:     </cfoutput>
229:     </td>
230: </tr>
231: </table>
232:
233: </body>
234: </html>
235:

```

```
1: .h2 { font-family: verdana, arial, helvetica, sans-serif; font-size: 12pt; }
2: .h1 { font-family: verdana, arial, helvetica, sans-serif; font-size: 14pt; }
3: a { font-family: verdana, arial, helvetica, sans-serif; font-size: 14pt; }
4: a:visited { font-family: verdana, arial, helvetica, sans-serif; font-size: 10pt; }
5: a:link { font-family: verdana, arial, helvetica, sans-serif; font-size: 10pt; }
6: a:active { font-family: verdana, arial, helvetica, sans-serif; font-size: 10pt; }
7: p, body, th, ul, td { font-family: verdana, arial, helvetica, sans-serif; font-size: 10pt; }
8: .help { font-family: verdana, arial, helvetica, sans-serif; font-size: 10pt; color: red; }
9: .title { font-family: verdana, arial, helvetica, sans-serif; font-size: 14pt; }
```

```
1: <cfparam name="lFormat" default="False">
2:
3:
4: <cfif lFormat is True>
5:   <cfoutput>#qryFormat.sideCode#</cfoutput>
6: <cfelse>
7:   &nbsp;
8: </cfif>
```



```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
2:
3:  <!-- If a Agency ID is not passed, then exit -->
4:  <cfif not isDefined("URL.agencyID")>
5:    <cflocation url="agencySearch.cfm" addtoken="no">
6:  </cfelse>
7:    <cfset nAgencyID = URL.agencyID>
8:  </cfif>
9:
10:   <cfquery name="qryAgency" dataSource="#ap_dataSource#">
11:     select agency.name, agency.mainImage, agency.description
12:   from agency
13:  where agency.agency_id = #url.agencyID#
14: </cfquery>
15:
16: <cfset nAgencyID = url.agencyID>
17:
18: <cfquery name="qryAgents" dataSource="#ap_dataSource#">
19:   select agents.agent_id, agents.firstName, agents.lastName, agents.extension,
20:   agents.webSite, agentBios.agentID as agentBioID
21: from agents
22: left outer join agentBios on agentBios.agentID = agents.agent_id
23: where agents.agency_id = #url.agencyID#
24: order by agents.lastName, agents.firstName, agents.extension
25: </cfquery>
26:
27: <html>
28: <head>
29:   <cfoutput>
30:     <title>Agency Agent List for #qryAgency.name#</title>
31:   </cfoutput>
32:   <link rel="stylesheet" href="style1.css" type="text/css">
33: </head>
34:
35: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
36: <cfoutput>
37:
38:   <cfset nEntityType = 4>
39:   <cfset nEntityID = 0>
40:
41:   <cfinclude template="pageFormat.cfm">
42:
43:   <cfinclude template="header_bannerad.cfm">
44:
45:   <table width="760" border="0" cellpadding="0" cellspacing="0">
46:     <tr>
47:       <td align="right" valign="top" bgcolor="#cNavBGColor#" width="135">
48:         <cfinclude template="navigation.cfm">
49:       </td>

```

```

50: <td width="500" valign="top" align="center" colspan="2">
51: <table border="0" width="480" cellspacing="2">
52: <tr bgcolor="#cMenuBGColor#" class="click_heading">
53: <td align="center"><b>#qryAgency.name#</b></td>
54: </tr>
55: <tr valign="top" bgcolor="#cccccc">
56: <td align="center">
57: <cfif fileExists("#qryAgency.mainImage#")>
58: 
59: </cfif>
60: </td>
61: </tr>
62: <tr valign="top" bgcolor="#cccccc">
63: <td align="center">
64: #trim(qryAgency.description)#
65: </td>
66: </tr>
67:
68: <tr bgcolor="#cMenuBGColor#">
69: <td align="center">Seatch Criteria goes here?</td>
70: </tr>
71:
72: <tr>
73: <td align="center">
74: "*" indicates agents with web sites | Underline indicates agents with biography pages
75: </td>
76: </tr>
77:
78: <tr><td><b>#</td></tr>
79:
80: <cfset lOpen = False>
81: <cfset nColumn = 1>
82: <cfset nMaxColumns = 2>
83: <cfloop query="qryAgents">
84: <cfif nColumn is 1>
85: <tr>
86: <cfset lOpen = True>
87: </cfif>
88: <td>
89: <cfif qryAgents.website is not "">*<b>#</cfif>
90: <cfif qryAgents.agentBioID is qryAgents.agent_id>
91: <a href="agentBioView.cfm?agentID=#qryAgents.agent_id#">
92: </cfif>
93: #trim(qryAgents.lastName)#, #trim(qryAgents.firstName)#<b>#<cfif>
94: <cfif qryAgents.extension is not "">
95: x #trim(qryAgents.extension)#
96: </cfif>
97: <cfif qryAgents.agentBioID is qryAgents.agent_id></a></cfif>
98: </td>

```

```

99:   <cfif nColumn is nMaxColumns>
100:     <cfset nColumn = 1>
101:   </tr>
102:   <cfelse>
103:     <cfset nColumn = nColumn + 1>
104:   </cfif>
105: </cfloop>
106: <cfloop from="#nColumn#" to="#nMaxColumns#" index="i">
107:   <td>&nbsp;</td>
108: </cfloop>
109:
110: <cfif lOpen is True></tr></cfif>
111:
112: <tr><td>&nbsp;</td></tr>
113:
114:   <cfinclude template="footer.cfm">
115:   </td>
116:   <td valign="top" width="1" bgcolor="#6666ff"></td>
118:   <td valign="top" width="4" bgcolor="#ffffff"></td>
120:   <td width="120" valign="top">
121:     <cfinclude template="120x65ads.cfm">
122:   </td>
123: </tr>
124: </table>
125: </cfoutput>
126: <!-- <cfinclude template="footer.cfm"> -->
127: </body>
128: </html>

```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN" >
2:
3: <cfparam name="cNavColor" default="#ap_defaultNavColor#">
4: <cfparam name="cMenuColor" default="#ap_defaultMenuColor#">
5:
6:
7: <!-- If a Agency ID is not passed, then exit -->
8: <cfif not isdefined("URL.agencyID")>
9:   <cflocation url="agencySearch.cfm" addtoken="no">
10: </cfif>
11: <cfset nAgencyID = URL.agencyID>
12: </cfif>
13:
14: <cfquery name="qryPage" dataSource="#ap_dataSource#">
15:   select agencyBios.*, agency.name as agencyName
16:   from agencyBios
17:   join agency on agency.agency_id = agencyBios.agencyID
18:   where agencyBios.agencyID = #nAgencyID#
19: </cfquery>
20:
21: <cfquery name="qryDetail" dataSource="#ap_dataSource#">
22:   select *
23:   from agencyBioDetail
24:   where agencyBioDetail.agencyID = #nAgencyID#
25:   order by agencyBioDetail.sortOrder, AgencyBioDetail.title
26: </cfquery>
27:
28:
29: <html>
30: <head>
31: <!--
32:   <title><cfoutput>#ap_agencyName# - #qryPropType.manTitle#</cfoutput></title>
33:   <!--
34:   <title>Agency Bio for #qryPage.agencyName#</title>
35:   <link rel="stylesheet" href="style1.css" type="text/css">
36: </head>
37:
38: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
39: <cfoutput>
40:
41: <table width="760" border="0" cellpadding="0" cellspacing="0">
42: <tr>
43:   <td align="right" valign="top" bgcolor="#cNavColor#" width="135">
44:     <nbsp;
45:     <!--
46:     <cfinclude template="navigation.cfm">
47:     <!--
48:   </td>
49:   <td width="500" valign="top" align="center">

```

```
50: <table border="0" width="480" cellpadding="2">
51: <tr>
52: <td bgcolor="#cMenuColor#" class="heading">#qryPage.agencyName#</td>
53: </tr>
54:
55: <cfloop query="qryDetail">
56: <tr><td align="#qryDetail.alignment#">
57: <cfif trim(qryDetail.image) is not "">
58: <cfif qryDetail.imageType is 1>
59: 
<cfif lcase(qryDetail.alignment) is "middle">
</td></tr> <!-- Force paragraph to a new row -->
<tr><td>
</cfif>
</cfif>
</cfif>
<cfif trim(qryDetail.title) is not "">
<h3>#trim(qryDetail.title)#</h3>
</cfif>
<cfif trim(qryDetail.text) is not "">
#paragraphFormat(trim(qryDetail.text))#
</td></tr>
</cfloop>
</table>
<td><b>#</td>
</tr>
</table>
</cfoutput>
<!-- <cfinclude template="footer.cfm"> -->
</body>
</html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
2:
3:  <cfparam name="cNavColor" default="#ap_defaultNavColor#">
4:  <cfparam name="cMenuColor" default="#ap_defaultMenuColor#">
5:
6:
7:  <!-- If a Agent ID is not passed, then exit -->
8:  <cfif not isdefined("URL.agentID")>
9:    <cflocation url="agentSearch.cfm" addtoken="no">
10:  </cfif>
11:  <cfset nAgentID = URL.agentID>
12:  </cfif>
13:
14:  <cfquery name="qryPage" datasource="#ap_dataSource#">
15:    select agentBios.*, agents.firstname + ' ' + agents.lastname as agentName
16:    from agentBios
17:    join agents on agents.agent_id = agentBios.agentID
18:    where agentBios.agentID = #nAgentID#
19:  </cfquery>
20:
21:  <cfquery name="qryDetail" datasource="#ap_dataSource#">
22:    select *
23:    from agentBioDetail
24:    where agentBioDetail.agentID = #nAgentID#
25:    order by agentBioDetail.sortOrder, AgentBioDetail.title
26:  </cfquery>
27:
28:
29:  <html>
30:  <head>
31:    <!--
32:    <title><cfoutput>#ap_agencyName# - #qryPropType.manifestTitle#</cfoutput><'title>
33:    -->
34:    <title>Agent Bio for #qryPage.agentName#</title>
35:    <link rel="stylesheet" href="style1.css" type="text/css">
36:  </head>
37:
38:  <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
39:  <cfoutput>
40:
41:  <table width="760" border="0" cellpadding="0" cellspacing="0">
42:  <tr>
43:    <td align="right" valign="top" bgcolor="#cNavColor#" width="135">
44:      &nbsp;
45:      <!--
46:      <cfinclude template="navigation.cfm">
47:      -->
48:    </td>
49:    <td width="500" valign="top" align="center">

```

```
50: <table border="0" width="480" cellpadding="2">
51: <tr>
52: <td bgcolor="#MenuColor#" class="heading">#qryPage.agentName#</td>
53: </tr>
54:
55: <cfloop query="qryDetail">
56: <tr><td align="#qryDetail.alignment#">
57: <cfif trim(qryDetail.image) is not "">
58: <cfif qryDetail.imageType is 1>
59: 
<cfif lcase(qryDetail.alignment) is "middle">
</td></tr> <!-- Force paragraph to a new row -->
<tr><td>
</cfif>
</cfif>
</cfif>
<cfif trim(qryDetail.title) is not "">
<h3>#trim(qryDetail.title)#</h3>
</cfif>
<cfif trim(qryDetail.text) is not "">
#paragraphFormat(trim(qryDetail.text))#
</cfif>
</td></tr>
</cfloop>
</table>
<td><b>sp</b></td>
</tr>
</table>
</cfoutput>
<!-- <cfinc./ids/footer.cfm"> -->
</body>
</html>
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN" >
2:
3:  <!-- If a Agent ID is not passed, then exit -->
4:  <cfif not isDefined("URL.agentID")>
5:    <cflocation url="agentSearch.cfm" addtoken="no">
6:  </cfelse>
7:    <cfset nAgentID = URL.agentID>
8:    </cfif>
9:
10:
11:    <cfquery name="qryAgent" dataSource="#ap_dataSource#">
12:      select agents.firstName, agents.lastName, agents.image_name, agents.bio,
13:      agents.specialty, agents.website, agents.email, agents.workPhone, agents.extension,
14:      agents.homePhone, agents.pub_home, agents.cellPhone, agents.faxPhone, agents.otherPhone,
15:      agents.agency_id, agency.name as agencyName, agency.email as agencyEmail
16:      from agents
17:      left outer join agency on agents.agency_id = agency.agency_id
18:      where agents.agent_id = #url.agentID#
19:    </cfquery>
20:
21:    <cfset nAgencyID = qryAgent.agency_id>
22:
23:    <cfset cAgentName = trim(trim(qryAgent.firstName) & ' ' & trim(qryAgent.lastName))>
24:
25:    <html>
26:    <head>
27:      <!--
28:      <title><cfoutput>#ap_agencyName# - #qryAgent.monTitle#</cfoutput></title>
29:      -->
30:      <cfoutput>
31:      <title>Agent View for #cAgentName#</title>
32:      </cfoutput>
33:      <link rel="stylesheet" href="style1.css" type="text/css">
34:    </head>
35:
36:    <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
37:      <cfoutput>
38:
39:      <cfset nEntityType = 4>
40:      <cfset nEntityID = 0>
41:
42:      <cfinclude template="pageFormat.cfm">
43:
44:      <cfinclude template="header_bannerad.cfm">
45:
46:      <table width="760" border="0" cellpadding="0" cellspacing="0">
47:        <tr>
48:          <td align="right" valign="top" bgcolor="#cNavBGColor#" width="135">
49:            <cfinclude template="navigation.cfm">

```



```

50: </td>
51: <td width="500" valign="top" align="center">
52: <table border="0" width="480" cellspacing="2">
53: <tr trim(qryAgent.agencyName) is not "">
54: <tr bgcolor="#cMenuBGColor#" class="click_heading">
55: <td align="center"><b>#qryAgent.agencyName#</b></td>
56: </tr>
57: </cfif>
58: <tr><td>&nbsp;</td></tr>
59: <tr>
60: <td bgcolor="#cMenuBGColor#" class="click_heading"><b>Agent</b> - #cAgentName# </td>
61: </tr>
62:
63: <tr><td>
64: <table border="0" cellspacing="3" cellpadding="3">
65: <tr>
66: <td valign="middle" align="center">
67: <cfif fileExists("#ap_fullAgentImages#getFileFromPath(qryAgent.image_name)#">
68: 
69: <cfelse if fileExists("#ap_fullCommonImages#noImage.jpg">
70: 
71: <cfelse>
72: <cfif trim(qryAgent.firstName) is not "">
73: <cfif lcase(right(qryAgent.firstName,1)) is "s">
74: <i>Sorry. #trim(qryAgent.firstName)#' image is currently not available.</i>
75: <cfelse>
76: <i>Sorry. #trim(qryAgent.firstName)#'s image is currently not available.</i>
77: </cfif>
78: <cfelse>
79: <i>Sorry. This agent's image is currently not available.</i>
80: </cfif>
81: </cfif>
82: </td>
83: <td valign="top">
84: <p>#qryAgent.bio#</p>
85: <cfif qryAgent.specialty is not "">
86: <b>Specialty:</b> #qryAgent.specialty#<br>
87: </cfif>
88: <cfif qryAgent.webSite is not "">
89: <b>Web Site:</b> #qryAgent.webSite#<br>
90: </cfif>
91: <cfif qryAgent.email is not "">
92: <b>Agent's Email:</b> <a href="mailto:#qryAgent.email#">#qryAgent.email#</a><br>
93: </cfif>
94: <cfif qryAgent.agencyEmail is not "">
95: <b>Agency's Email:</b> <a href="mailto:#qryAgent.agencyEmail#">#qryAgent.agencyEmail#</a><br>
96: </cfif>
97: <b>Office:</b> #qryAgent.workPhone#<br>
98: <cfif qryAgent.faxPhone is not "">

```

```

99:         <b>Fax:</b> #qryAgent.faxPhone#<br>
100:     </cfif>
101:     <cfif qryAgent.cellPhone is not "">
102:         <b>Cell:</b> #qryAgent.cellPhone#<br>
103:     </cfif>
104:     <cfif qryAgent.pub home is "y" and qryAgent.homePhone is not "">
105:         <b>Home:</b> #qryAgent.homePhone#<br>
106:     </cfif>
107:     </td>
108: </tr>
109: </table>
110: </td></tr>
111: <tr>
112:     <td><a href="agentListing.cfm?agentID=#url.agentID#">
113:         <cfif lcase(right(qryAgent.firstName,1)) is "s">
114:             #qryAgent.firstName# Listings</a></td>
115:         <cfelse>
116:             #qryAgent.firstName#'s Listings</a></td>
117:         </cfif>
118:     </tr>
119:
120: <tr><td>&nbsp;</td></tr>
121: <tr bgcolor="#cMenuBGColor#" class="click_heading">
122:     <td align="center">
123:         Back to Listings | Back to Agent Roster | Printable Page
124:     </td>
125: </tr>
126: <cfinclude template="footer.cfm">
127: </table>
128: </td>
129: <td valign="top" width="1" bgcolor="#6666ff"></td>
130: <td valign="top" width="4" bgcolor="#ffffff"></td>
131: <td width="120" valign="top">
132:     <cfinclude template="120x65ads.cfm">
133: </td>
134: </tr>
135: </table>
136:
137: </cfoutput>
138: </body>
139: </html>

```

```

1:  <!--
2:  Product:      Full Impact
3:  Version:      1.0
4:  History:
5:
6:  -->
7:
8:  <!-- Application Settings -->
9:  <cfapplication
10:     name="FullImpact"
11:     clientManagement="yes"
12:     clientStorage="clientStorage"
13:     sessionManagement="yes"
14:  >
15:
16:  <!-- Product Database Information -->
17:  <cfset ap_dataSource = "fullImpactAlpha">
18:
19:
20:  <!-- Path Information -->
21:  <cfset ap_rootPath = "c:\inetpub\multidimension\fullimpact\"> <!-- the root of the application -->
22:  <cfset ap_commonImages = "commonImages/"> <!-- Path from root of customer -->
23:  <cfset ap_fullCommonImages = "c:\inetpub\multidimension\fullimpact\commonImages\">
24:  <cfset ap_specialtyImages = "specialtyImages\">
25:  <cfset ap_agentImages = "agentImages/">
26:  <cfset ap_fullAgentImages = "c:\inetpub\multidimension\fullimpact\agentImages\">
27:  <cfset ap_agencyImages = "agencyImages/">
28:
29:  <!-- Product Defaults -->
30:  <cfset ap_defaultNavColor = "#330099"> <!-- Default navigation background color -->
31:  <cfset ap_defaultMenuColor = "#990000"> <!-- Default menu background color -->
32:
33:
34:  <!-- Error Handling -->
35:  <cfset ap_defaultEmailProblems = "jjunker@techmission.com"> <!-- Default email to send error messages -->
36:

```

```
1: <cfparam name="URL.PropertyType" DEFAULT="URL" >
2:
3: <cfquery name="qryCommunity" datasource="#ap_dataSource#">
4:   select communities.communityID, communities.name
5:   from communities
6:   where communities.distributorID = #ap_distributorID#
7: </cfquery>
8:
9: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
10:
11: <cfset nEntityType = 4> <!-- Property Main Page -->
12: <cfset nEntityID = 0> <!-- Property Pages -->
13: <cfinclude template="pageFormat.cfm">
14:
15: <cfinclude template="header_bannerad.cfm">
16:
17: <table width="760" border="0" cellpadding="0" cellspacing="0">
18:   <tr>
19:     <td align="center" valign="top" bgcolor="#cNavBGColor#" width="170">
20:       <cfinclude template="navigation.cfm">
21:     </td>
22:     <td width="500" valign="top" align="center">
23:       <table border="0" width="480" cellspacing="2">
24:         <tr>
25:           <td bgcolor="#cMenuBGColor#" class="heading">Community Search</td>
26:         </tr>
27:
28:         <cfif qryCommunity.recordCount is 0>
29:           <tr>
30:             <td>
31:               <i>There is no community information available.</i>
32:             </td>
33:           </tr>
34:         <cfelseif qryCommunity.recordCount is 1>
35:           <cflocation url="communityView.cfm?communityID=#qryCommunity.communityID#" addToken="no">
36:         <cfelse>
37:           <tr>
38:             <td>
39:               We have different communities to choose from, each with its own unique atmosphere.<br>
40:             <br>
41:             Please select a community to view:
42:
43:             <form action="communityView.cfm" method="post">
44:               <select name="communityID">
45:                 <cfoutput query="qryCommunity">
46:                   <option value="#qryCommunity.communityID#"#qryCommunity.name#
47:                 </cfoutput>
48:               </select>
49:             <input type="submit" value="Search" />

```

```
50:         <input type="submit" name="btnSelect" value="Select Community">
51:     </form>
52: </td>
53: </tr>
54: </cfinf>
55:
56: <cfinclude template="footer.cfm">
57: </table>
58: </td>
59: <td valign="top" width="1" bgcolor="#6666ff"></td>
60: <td valign="top" width="4" bgcolor="#ffffff"></td>
61: <td width="120" valign="top">
62:     <cfinclude template="120x65ads.cfm">
63: </td>
64: </tr>
65: </table>
66: </body>
67: </html>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/FEN">
2:
3: <!-- If a community ID is not passed, then exit -->
4: <cfif not isDefined("URL.communityID") and not isDefined("form.communityID")>
5:   <cflocation url="communitySearch.cfm" addtoken="no">
6: </cfelse>
7:   <cfif isDefined("url.communityID")>
8:     <cfset nCommunityID = URL.communityID>
9:     <cfelseif isDefined("form.communityID")>
10:       <cfset nCommunityID = form.communityID>
11:     </cfif>
12:   </cfif>
13:
14:   <cfquery name="qryPage" dataSource="#ap_dataSource#">
15:     select *
16:     from communities
17:     where communities.communityID = #nCommunityID#
18:   </cfquery>
19:
20:   <cfquery name="qryDetail" dataSource="#ap_dataSource#">
21:     select *
22:     from communityDetail
23:     where communityDetail.communityID = #nCommunityID#
24:     order by communityDetail.sortOrder, communityDetail.title
25:   </cfquery>
26:
27:
28: <html>
29: <head>
30: <!--
31:   <title><cfoutput>#ap_agencyName# - #qryDetail.type.nameTitle#</cfoutput></title>
32: -->
33:   <title>Community View</title>
34:   <link rel="stylesheet" href="style1.css" type="text/css">
35: </head>
36:
37: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
38:
39:   <cfset nEntityType = 4> <!-- Property Main Page = 5 -->
40:   <cfset nEntityID = 0> <!-- Property Pages = 0 -->
41:   <cfinclude template="pageFormat.cfm">
42:
43:   <cfinclude template="header_bannerad.cfm">
44:
45:   <cfoutput>
46:
47:   <table width="760" border="0" cellpadding="0" cellspacing="0">
48:     <tr>
49:       <td align="center" valign="top" bgcolor="#cNavBGColor#" width="170">

```

```

50: <cfinclude template="navigation.cfm">
51: </td>
52: <td width="500" valign="top" align="center">
53: <table border="0" width="480" cellspacing="2">
54: <tr>
55: <td bgcolor="#cMenuBGColor#" class="heading">#qryPage.Name#</td>
56: </tr>
57:
58: <cfloop query="qryDetail">
59: <tr><td align="#qryDetail.alignment#">
60: <cfif trim(qryDetail.image) is not "">
61: <cfif qryDetail.imageType is 1>
62: 
<cfif lcase(qryDetail.alignment) is "middle">
</td></tr> <!-- Force paragraph to a new row -->
<tr><td>
</cfif>
</cfif>
<cfif trim(qryDetail.title) is not "">
<h3>#trim(qryDetail.title)</h3>
</cfif>
<cfif trim(qryDetail.text) is not "">
#paragraphFormat(trim(qryDetail.text))#
</cfif>
</td></tr>
</cfloop>
<cfinclude template="footer.cfm">
</table>
</td>
<td valign="top" width="1" bgcolor="#6666ff"></td>
<td valign="top" width="4" bgcolor="#ffffff"></td>
<td width="120" valign="top">
<cfinclude template="120x65ads.cfm">
</td>
</tr>
</table>
</cfoutput>
</body>
</html>

```

```

1: <cfparam name="URL.PropertyType" DEFAULT="y">
2:
3: <cfparam name="form.minPrice" default="0">
4: <cfparam name="form.maxPrice" default="0">
5: <cfparam name="form.minBedrooms" default="0">
6: <cfparam name="form.minBathrooms" default="0">
7: <cfparam name="form.propertyTypeID" default="-1">
8: <cfparam name="form.specialtyPageID" default="-1">
9: <cfparam name="form.communityID" default="-1">
10: <cfparam name="form.regionID" default="-1">
11: <cfparam name="form.lotTypeID" default="-1">
12: <cfparam name="form.homeTypeID" default="-1">
13: <cfparam name="form.agentID" default="-1">
14: <cfparam name="form.propertySource" default="1">
15:
16: <cfparam name="form.sortOrder" default="prop_main.name">
17: <cfparam name="form.showPhotos" default="y">
18:
19: <cfset nMinPrice = val(form.minPrice)>
20: <cfset nMaxPrice = val(form.maxPrice)>
21: <cfset nMinBedrooms = val(form.minBedrooms)>
22: <cfset nMinBathrooms = val(form.minBathrooms)>
23:
24: <cfquery name="qryProps" dataSource="#ap_dataSource#">
25:   select prop_main.prop_id, prop_main.name, prop_main.city, prop_main.size,
26:     prop_main.price, prop_main.bedrooms, prop_main.bath, prop_main.mls_no,
27:     prop_main.communityID, prop_main.status, prop_main.findPropType,
28:     prop_main.description, prop_main.agency_id, prop_main.agent_id,
29:     agency.name as agencyName,
30:     agents.firstName + ' ' + agents.lastName as agentName, agents.workPhone as agentPhone,
31:     statusValues.status as statusValue,
32:     propertyTypeValues.propertyType as propertyTypeValue
33:   <cfif form.communityID gt -1>, communities.name as commName</cfif>
34:   <cfif form.regionID gt -1>, communities.regionID</cfif>
35:   from prop_main
36:   <cfif form.communityID gt -1 or form.regionID gt -1>
37:     join communities on communities.communityID = prop_main.communityID
38:   <cfif form.communityID gt -1>
39:     and prop_main.communityID = #form.communityID#
40:   </cfif>
41:   <cfif form.regionID is not -1>
42:     and communities.regionID = #form.regionID#
43:   </cfif>
44: </cfif>
45: <cfif form.specialtyPageID gt -1>
46:   join propSpecialty on propSpecialty.propertyID = prop_main.property_id
47:   and propSpecialty.specialtyPageID = #form.specialtyPageID#
48: </cfif>
49: join statusValues on statusValues.distributorID = #ap_distributorID#

```



```

50: and prop_main.status = statusValues.statusID#
51: and statusValues.propViewVisible = 'Y'
52: join propertyTypeValues on propertyTypeValues.propertyTypeID = prop_main.prop_type
53: <cfif form.propertyTypeID gt -1>
54:   and propertyTypeValues.propertyTypeID = #form.propertyTypeID#
55: </cfif>
56: left outer join agency on agency.agency_id = prop_main.agency_id
57: left outer join agents on agents.agent_id = prop_main.agent_id
58: where prop_main.distributorID = #ap.distributorID#
59: and prop_main.propertySource = #form.propertySource#
60: and prop_main.price >= #minPrice#
61: and prop_main.price <= #maxPrice#
62: and prop_main.bath >= #minBathrooms#
63: and prop_main.bedroom >= #minBedrooms#
64: <cfif form.agentID gt -1>
65:   and prop_main.agent_id = #form.agentID#
66: </cfif>
67: <cfif form.homeTypeID gt -1>
68:   and prop_main.homeType = '#form.homeTypeID#'
69: </cfif>
70: <cfif form.lotTypeID gt -1>
71:   and prop_main.lottype = '#form.lotTypeID#'
72: </cfif>
73: order by #form.sortOrder:#
74: </cfquery>
75:
76:
77:
78: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
79:
80: <cfset nEntityType = 4>
81: <cfset nEntityID = 0>
82: <cfinclude template="pageFormat.cfm">
83:
84: <cfinclude template="header_bannerad.cfm">
85:
86: <cfoutput>
87: <table width="790" border="0" cellpadding="0" cellspacing="0">
88: <tr>
89:   <td align="center" valign="top" bgcolor="#cNavBGColor#" width="170">
90:     <cfinclude template="navigation.cfm">
91:   </td>
92:   <td width="500" valign="top" align="center">
93:     <table border="0" width="480" cellspacing="2">
94:       <tr>
95:         <td bgcolor="#cMenuBGColor#" class="heading">Property Results</td>
96:       </tr>
97:       <tr bgcolor="#cccccc"><td>Sort Order Options:</td></tr>
98:

```

```

99: <tr bgcolor="#cccccc">
100: <td>
101: <form action="findPropertyResults.cfm" method="post">
102: <input type="hidden" name="minPrice" value="#nMinPrice#">
103: <input type="hidden" name="maxPrice" value="#nMaxPrice#">
104: <input type="hidden" name="minBedrooms" value="#nMinBedrooms#">
105: <input type="hidden" name="minBathrooms" value="#nMinBathrooms#">
106: <input type="hidden" name="propertyTypeID" value="#form.propertyTypeID#">
107: <input type="hidden" name="specialtyPageID" value="#form.specialtyPageID#">
108: <input type="hidden" name="communityID" value="#form.communityID#">
109: <input type="hidden" name="regionID" value="#form.regionID#">
110: <input type="hidden" name="lotTypeID" value="#form.lotTypeID#">
111: <input type="hidden" name="homeTypeID" value="#form.homeTypeID#">
112: <input type="hidden" name="agentID" value="#form.agentID#">
113: <input type="hidden" name="propertySource" value="#form.propertySource#">
114:
115: <select name="showPhotos">
116: <option value="y"><cfif form.showPhotos is "y"> selected</cfif>>With Photos
117: <option value="n"><cfif form.showPhotos is "n"> selected</cfif>>Without Photos
118: </select>
119: &nbsp;
120: Sort By:
121: <select name="sortOrder">
122: <option value="prop_main.name"><cfif form.sortOrder is "prop_main.name"> selected</cfif>>Property Name
123: <option value="prop_main.price"><cfif form.sortOrder is "prop_main.price"> selected</cfif>>Price
124: <option value="prop_main.bath"><cfif form.sortOrder is "prop_main.bath"> selected</cfif>>Bathrooms
125: <option value="prop_main.bedroom"><cfif form.sortOrder is "prop_main.bedroom"> selected</cfif>>Bedrooms
126: </select>
127: &nbsp;
128: <input type="submit" name="btnChange" value="Change">
129: </form>
130: </td>
131: </tr>
132: <tr bgcolor="#ffffff">
133: <td>
134: Search Criteria:
135: Search Results:
136: </td>
137: </tr>
138: <tr bgcolor="#ffffff"><td>&nbsp;</td></tr>
139:
140: <cfloop query="qryProps">
141: <tr bgcolor="#####" class="menu">
142: <td>
143: <b>#trim(qryProps.name) # - #qryProps.statusValue# - #qryProps.propertyTypeID#</b>
144: <cfif qryProps.mls_no is not "">
145: &nbsp;<b>-- (MLS##qryProps.mls_no#)</b>
146: </cfif>
147: </td>

```

```
148: </td>
149:
150: <tr><td>
151:   <table border="0" cellspacing="0" cellpadding="2" width="100%">
152:     <tr valign="top">
153:       <td width="50%" bgcolor="##eeeeee">
154:         <table border="0" cellspacing="0" cellpadding="0" width="100%">
155:           <tr>
156:             <td width="60%" align="center" valign="top">
157:               <cfif form.showPhotos is "y">
158:                 <cfset cFilename = "">
159:                 <cfif fileExists(cFilename)>
160:                   
161:                 <cfelse>
162:                   <i>Sorry, image is not available.</i>
163:                 </cfif>
164:               <cfelse>
165:                 <i>Images Suppressed.</i>
166:               </cfif>
167:             </td>
168:             <td width="40%" align="left" valign="top">
169:               #dollarFormat(qryProps.price)#<br>
170:               <cfif qryProps.city is not "">
171:                 #qryProps.city#<br>
172:               </cfif>
173:               <cfif qryProps.bedroom gt 0>
174:                 #qryProps.bedroom# bed<br>
175:               </cfif>
176:               <cfif qryProps.bath gt 0>
177:                 #qryProps.bath# bath<br>
178:               </cfif>
179:             </td>
180:           </tr>
181:         </table>
182:         &nbsp;
183:       </td>
184:       <td width="30%">
185:         #qryProps.dscreptn_1#
186:       </td>
187:     </tr>
188:     <td width="20%">
189:       <a href="agencyAgentList.cfm?agencyID=#qryProps.agency_id#">#ucase(qryProps.agencyName) #</a><br>
190:       <a href="agentView.cfm?agentID=#qryProps.agent_id#">#qryProps.agentName#</a><br>
191:       #qryProps.agentPhone#
192:     </td>
193:   </tr>
194: </table>
195: </td></tr>
196:
```

```
197:         <tr bgcolor="#cccccc">
198:             <td align="center">
199:                 <a href="propertyView.cfm?propertyID=#qryProps.prop_id#">See Details About This Property</a>
200:             <td align="center">
201:                 
202:             </td>
203:         </tr>
204:     </cfloop>
205:
206:     <cfinclude template="footer.cfm">
207: </table>
208: </td>
209: <td valign="top" width="1" bgcolor="#6666ff">
210: </td>
211: <td align="top" width="4" bgcolor="#ffffff">
212: </td>
213: <td align="top" width="120" valign="top">
214:     <cfinclude template="120x65ads.cfm">
215: </td>
216: </tr>
217: </table>
218: </cfoutput>
219: </body>
220: </html>
```

```

1: <cfparam name="lFormat" default="False">
2:
3: <cfif lFormat is True>
4:   <tr><td><b><cfif lFormat is True></td></tr>
5:   <tr>
6:     <td align="center">
7:       <cfoutput>#qryFormat.footerCode#</cfoutput>
8:     </td>
9:   </tr>
10:  </cfif>
11:
12: <cfoutput>
13: <cfif isDefined("nAgencyID")>
14:   <cfquery name="qryAgency" dataSource="#ap_dataSource#">
15:     select agency.name, agency.address, agency.city, agency.state, agency.zip,
16:     agency.phone, agency.fax, agency.email
17:     from agency where agency_id = #nAgencyID#
18:   </cfquery>
19:
20:   <tr><td><b><cfif lFormat is True></td></tr>
21:   <tr align="top">
22:     <td align="center">
23:       <b>#trim(qryAgency.name)#</b><br>
24:       #trim(qryAgency.address)#, #trim(qryAgency.city)#, #trim(qryAgency.state)# #trim(qryAgency.zip)#<br>
25:       Phone: #trim(qryAgency.phone)# Fax: #trim(qryAgency.fax)#<br>
26:       <cfif qryAgency.email is not "">
27:         <a href="mailto:#qryAgency.email#">#trim(qryAgency.email)#</a><br>
28:       </cfif>
29:     <br>
30:     Copyright #dateFormat(now(), "yyyy")#, #trim(qryAgency.name)#<br>
31:     </td>
32:   </tr>
33: </cfif>
34:   <tr align="top">
35:     <td align="center">
36:       <br><a href="http://www.yakalo.net"></a>
37:     </td>
38:   </tr>
39:
40: </cfoutput>
41:

```

```
1: <cfparam name="lFormat" default="False">
2:
3: <cfif lFormat is True>
4:   <table width="760" border="0" cellpadding="0" cellspacing="0">
5:     <tr>
6:       <td>
7:         <cfoutput>#qryFormat.headerCode#</cfoutput>
8:       </td>
9:     </tr>
10:   </table>
11: </cfelse>
12:   &nbsp;
13: </cfif>
```

```

1: <cfquery name="qryPropTypes" datasource="#ap_dataSource#">
2:   select * from propertyTypeValues
3:   where propertyTypeValues.distributorID = #ap_distributorID#
4:   order by propertyTypeValues.propertyType
5: </cfquery>
6:
7: <cfquery name="qryGetComm" datasource="#ap_dataSource#">
8:   SELECT communityID, name, region
9:   FROM Communities
10:  where communities.distributorID=#ap_distributorID#
11:  ORDER BY Communities.Region, Communities.name
12: </cfquery>
13:
14: <form action="findPropertyResults.cfm" method="post">
15:   <input type="hidden" name="propertySource" value="0">
16:   <table border="0" cellspacing="0" cellpadding="2" align="center" bgcolor="#cfcfcfc" size="8"></td>
17:     <tr><td align="right"> From: $</td><td align="text" value="100000" name="minPrice" size="8"></td>
18:     <td valign="top" align="right"> Min Bedrooms:</td>
19:     <td align="text" value="0" size="4" value="0"></td>
20:   </tr>
21:   <tr><td align="right">To: $</td><td align="text" value="300000" name="maxPrice" size="8"></td>
22:   <td align="right">Min Bathrooms:</td>
23:   <td align="text" value="0" size="4" value="0"></td>
24:   </tr>
25:   <tr>
26:     <td align="right">Property Type: </td>
27:     <td>
28:       <select name="propertyTypeID">
29:         <option value="-1" selected>All
30:         <cfoutput query="qryPropTypes">
31:           <option value="#qryPropTypes.propertyTypeID#"#qryPropTypes.propertyType#
32:         </cfoutput>
33:       </select>
34:     </td>
35:     <td colspan="2">&nbsp;</td>
36:   </tr>
37:   <tr>
38:     <td colspan="4" align="center"><input type="submit" value="Search"> <input type="reset" value="Reset"></td>
39:   </tr>
40: </table>
41: </form>
42:

```

```

1: <cfif not isDefined("qryFormat")>
2:   <cfset nEntityType = -1>
3:   <cfset nEntityID = 0>
4:   <cfinclude template="#ap_commonFiles#pageFormat.cfm">
5: </cfif>
6:
7: <cfif qryFormat.recordCount is 0>
8:   <cfset nFormatID = -1>
9: <cfelse>
10:   <cfset nFormatID = qryFormat.templateID>
11: </cfif>
12:
13: <cfquery name="qrySpecialty" datasource="#ap_dataSource#">
14:   select specialtyPageID, name, menuTitle, menuSortOrder, description
15:   from specialtyPages
16:   where specialtyPages.distributorID = #ap_distributorID#
17:   order by menuSortOrder, menuTitle
18: </cfquery>
19:
20: <cfquery name="qryNavigation" datasource="#ap_dataSource#">
21:   select menuText, menuURL, sortOrder
22:   from navigation
23:   where navigation.distributorID = #ap_distributorID#
24:   order by sortOrder
25: </cfquery>
26:
27: <cfquery name="qryTemplate" datasource="#ap_dataSource#">
28:   select templates.navButtonImage
29:   from templates
30:   where templates.templateID = #nFormatID#
31: </cfquery>
32:
33: <cfif qryNavigation.recordCount is 0>
34:   <cfoutput>
35:     <a href="propertySearch.cfm" class="nav">FIND A HOME<nbsp></a><br>
36:     <a href="realtorSearch.cfm" class="nav">FIND AN OFFICE<nbsp></a><br>
37:     <a href="communitySearch.cfm" class="nav">COMMUNITY INFO<nbsp></a><br>
38:     <a href="ohtListings.cfm" class="nav">ENHANCED LISTINGS<nbsp></a><br>
39:   </cfoutput>
40:   <cfoutput query="qrySpecialty">
41:     <a href="specialtyPageView.cfm?specialtyPageID=#qrySpecialty.specialtyPageID#
42:     class="nav">#ucase(qrySpecialty.menuTitle)<nbsp></a><br>
43:   </cfoutput>
44:   <cfoutput>
45:     <a href="index.cfm" class="nav">HOME<nbsp></a><br>
46:   </cfoutput>
47:   <cfif qryTemplate.recordCount is 0 or trim(qryTemplate.navButtonImage) is "">
48:     <cfset cBGButton = ">

```



```

49: <cfelse>
50: <cfset cBGButton = "background=" & chr(34) & "common/images/" & qryTemplate.navButtonImage & chr(34)>
51: </cfif>
52:
53: <table border="0" cellpadding="0" cellspacing="0" width="170">
54: <cfloop query="qryNavigation">
55: <tr class="nav">
56: <cfif ucase(trim(qryNavigation.menuText)) is "***SPECIALTY PAGES**">
57: <cfoutput query="qrySpecialty">
58: <td class="nav" width="170" height="35" align="center" #cBGButton#><a
href="specialtyPageView.cfm?specialtyPageID=#qrySpecialty.specialtyPageID#" class="nav"><font
color="#cNavTextColor#"#ucase(qrySpecialty.menuTitle)#</font></a><b></td>
</cfoutput>
59: <cfelseif trim(qryNavigation.menuText) is "">
60: <td class="nav"><b></td>
61: <td class="nav"><b></td>
62: <cfelseif trim(qryNavigation.menuText) is "<HR>">
63: <td class="nav"><hr></td>
64: <cfelse>
65: <cfoutput>
66: <td class="nav" width="170" height="35" align="center" #cBGButton#><a href="#qryNavigation.menuURL#"
class="nav"><font color="#cNavTextColor#"#trim(qryNavigation.menuText)#</font></a><b></td>
67: </cfoutput>
68: </cfif>
69: </tr>
70: </cfloop>
71: </table>
72: </cfif>
73:

```

```

1: <cfparam name="URL.PropertyType" DEFAULT="URL" />
2:
3: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
4:
5: <cfset nEntityType = 4> <!--- Property Main Page = 5 --->
6: <cfset nEntityID = 0> <!--- Property Pages = 0 --->
7: <cfinclude template="pageFormat.cfm">
8:
9: <cfinclude template="header_bannerad.cfm">
10:
11: <table width="760" border="0" cellpadding="0" cellspacing="0">
12: <tr>
13: <td align="center" valign="top" bgcolor="#cfcfcfcf" width="170">
14: <cfinclude template="navigation.cfm">
15: </td>
16: <td width="500" valign="top" align="center">
17: <table border="0" width="480" cellspacing="2">
18: <tr>
19: <td bgcolor="#cfcfcfcf" width="100%" class="heading">Enhanced Listings</td>
20: </tr>
21: <cfinclude template="footer.cfm">
22: </table>
23: </td>
24: <td align="top" width="1" bgcolor="#6666ff" width="1" height="1" border="1" alt="0"></td>
25: <td align="top" width="4" bgcolor="#ffffff" width="1" height="1" border="1" alt="0"></td>
26: <td width="120" valign="top">
27: <cfinclude template="120x65ads.cfm">
28: </td>
29: </tr>
30: </table>
31: </body>
32: </html>

```

```

1: <cfif ap_useFormats is True>
2: <cfquery name="qryFormat" dataSource="#ap_dataSource#" maxRows=1>
3:   select pageFormats.pageFormatID, pageFormats.navBGColor, pageFormats.navTextColor,
4:     pageFormats.menuBGColor, pageFormats.menuTextColor,
5:     pageFormats.headerBGColor, pageFormats.footerBGColor,
6:     pageFormats.adBGColor, pageFormats.searchBGColor,
7:     pageFormats.headerCode, pageFormats.sideCode,
8:     pageFormats.footerCode, pageFormats.templateID
9:   from pageFormats, formatAssignment
10:  where pageFormats.pageFormatID = formatAssignment.pageFormatID
11:  and pageFormats.distributorID = #ap_distributorID#
12:  and ((formatAssignment.entityTypeID = -1 and formatAssignment.entityID = 0)
13:    or (formatAssignment.entityTypeID = #nEntityTypeID# and formatAssignment.entityID = 0)
14:    or (formatAssignment.entityTypeID = #nEntityTypeID# and formatAssignment.entityID = #nEntityID#))
15:  order by formatAssignment.entityTypeID desc, formatAssignment.entityID desc
16: </cfquery>
17: <cfif qryFormat.recordCount is 0>
18:   <cfset lFormat = False>
19:   <cfset cNavBGColor = trim(ap_defaultNavBGColor)>
20:   <cfset cNavTextColor = trim(ap_defaultNavTextColor)>
21:   <cfset cMenuBGColor = trim(ap_defaultMenuBGColor)>
22:   <cfset cMenuTextColor = trim(ap_defaultMenuTextColor)>
23:   <cfset cHeaderBGColor = trim(ap_defaultHeaderBGColor)>
24:   <cfset cFooterBGColor = trim(ap_defaultFooterBGColor)>
25:   <cfset cAdBGColor = trim(ap_defaultAdBGColor)>
26:   <cfset cSearchBGColor = trim(ap_defaultSearchBGColor)>
27: </cfif>
28: <cfset lFormat = True>
29:   <cfset cNavBGColor = trim(qryFormat.navBGColor)>
30:   <cfset cNavTextColor = trim(qryFormat.navTextColor)>
31:   <cfset cMenuBGColor = trim(qryFormat.menuBGColor)>
32:   <cfset cMenuTextColor = trim(qryFormat.menuTextColor)>
33:   <cfset cHeaderBGColor = trim(qryFormat.headerBGColor)>
34:   <cfset cFooterBGColor = trim(qryFormat.footerBGColor)>
35:   <cfset cAdBGColor = trim(qryFormat.adBGColor)>
36:   <cfset cSearchBGColor = trim(qryFormat.searchBGColor)>
37: </cfif>
38: </cfelse>
39:   <cfset lFormat = False>
40:   <cfset cNavBGColor = trim(ap_defaultNavBGColor)>
41:   <cfset cNavTextColor = trim(ap_defaultNavTextColor)>
42:   <cfset cMenuBGColor = trim(ap_defaultMenuBGColor)>
43:   <cfset cMenuTextColor = trim(ap_defaultMenuTextColor)>
44:   <cfset cHeaderBGColor = trim(ap_defaultHeaderBGColor)>
45:   <cfset cFooterBGColor = trim(ap_defaultFooterBGColor)>
46:   <cfset cAdBGColor = trim(ap_defaultAdBGColor)>
47:   <cfset cSearchBGColor = trim(ap_defaultSearchBGColor)>
48: </cfif>
49:

```

```

1: <cfparam name="URL.PropertyType" DEFAULT="URL.PropertyType" marginwidth="4">
2:
3: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
4:
5: <cfset nEntityType = 4> <!--- Property Main Page = 5 --->
6: <cfset nEntityID = 0> <!--- Property Pages = 0 --->
7: <cfinclude template="pageFormat.cfm">
8:
9: <cfinclude template="header_bannerad.cfm">
10:
11: <table width="760" border="0" cellpadding="0" cellspacing="0">
12: <tr>
13: <td align="center" valign="top" bgcolor="#cNavBGColor#"><cfoutput>#cNavBGColor#</cfoutput> " width="170">
14: <cfinclude template="navigation.cfm">
15: </td>
16: <td width="500" valign="top" align="center">
17: <table border="0" width="480" cellspacing="2">
18: <tr>
19: <td bgcolor="#cMenuBGColor#"><cfoutput>#cMenuBGColor#</cfoutput> " class="heading">Find a Home</td>
20: </tr>
21: <tr>
22: <td>
23: <blockquote><p>Search our database of homes for sale in the area.</p></blockquote>
24: <p><cfinclude template="mlsSearchForm.cfm"></p>
25: </td>
26: </tr>
27: <tr>
28: <td><cfinclude template="footer.cfm">
29: </td>
30: <td align="top" width="1" bgcolor="#6666ff"></td>
31: <td align="top" width="4" bgcolor="#ffffff"></td>
32: <td width="120" valign="top">
33: <cfinclude template="120x65ads.cfm">
34: </td>
35: </tr>
36: </table>
37: </body>
38: </html>

```

```

1: <cfinclude template="javaValidate.cfm">
2:
3: <script language="JavaScript">
4: <!--
5:   function validate(testform) {
6:     var results = "";
7:     var lResult = true;
8:
9:     if (removeSpaces(testform.edtDesc.value) == "") {
10:       results = results + " * Please enter a description for this format page.\r";
11:       lResult = false;
12:     }
13:
14:     if (!lResult) {
15:       window.alert(results);
16:     }
17:     return lResult;
18:   }
19: -->
20: </script>
21:
22: <cfquery name="qryAssigned" dataSource="#ap_dataSource#">
23:   select convert(varchar,formatAssignment.entityTypeID)+'<convert(varchar,formatAssignment.entityID) as entityValue
24:   from formatAssignment
25:   where formatAssignment.pageFormatID = #client.lookupID#
26: </cfquery>
27: <cfset lstAssigned = valueList(qryAssigned.entityValue, ",")>
28:
29: <cfset lstPages = "Default, Main Page, Communities, Specialty Pages, Property View, Agency View, Resources">
30: <cfset lstPageValues = "-1, 1, 2, 3, 4, 5, 6, 7">
31:
32: <cfoutput>
33:
34: <form action="formatUpdate.cfm" method="post" onSubmit="return validate(this)">
35:   <input type="hidden" name="pageFormatID" value="#nPageFormatID#">
36:   <input type="hidden" name="distributorID" value="#nDistributorID#">
37:
38:   <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
39:     <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Page Format Maintenance</b></span>
40:       <cfif client.lookupID is -1>
41:         <nbsp><Create a new page format
42:         <cfif cDistName is not "">
43:           for #cDistName#
44:         </cfif>
45:       )
46:     </cfif>
47:   </td></tr>
48:
49:   <cfif client.lookupID gt 0>

```

```

50: <tr bgcolor="#cccccc99">
51:   <td colspan="5">
52:     <a href="formatMaint.cfm?displayPage=formatScheme">Color Scheme</a>
53:   </td>
54: </tr>
55: </cfif>
56:
57: <CFIF client.userMessage is not "">
58:   <tr bgcolor="eeeeee">
59:     <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td>
60:   </tr>
61:   <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
62: </CFIF>
63: <cfset client.userMessage = "">
64:
65:   <tr bgcolor="#eeeeee">
66:     <td width="15%"><b>Description:</b></td>
67:     <td colspan="4"><input type="text" name="edtDesc" value="#qryFindPage.description#" size="45" maxlength="45"></td>
68:   </tr>
69:
70:   <tr bgcolor="#eeeeee">
71:     <td width="15%">Page Assignment:</td>
72:     <td colspan="4">
73:       <select name="edtPages" multiple size="5">
74:         <cfloop from="1" to="#listLen(listPages, ",")#" index="i">
75:           <cfset cValue = listGetAt(listPageValues,i,"")>
76:           <cfset cFind = cValue & "|0">
77:           <option value="#cFind#">cfif listFind(listAssigned,trim(cFind),",") gt 0>
selected</cfif>>#listGetAt(listPages,i,"")#
       </cfloop>
       </select>
       </td>
       </tr>
       </td>
       <tr>
78:   <tr bgcolor="#eeeeee">
79:     <td colspan="5">&nbsp;</td>
80:   </tr>
81:
82:   <tr bgcolor="eeeeee">
83:     <td colspan="5">&nbsp;</td>
84:   </tr>
85:
86:   <tr bgcolor="#eeeeee">
87:     <td width="15%">Header Content:</td>
88:     <td colspan="4">
89:       <textarea name="edtHeader" rows="5" cols="60" wrap="virtual">#trim(qryFindPage.headerCode)#</textarea>
90:     </td>
91:   </tr>
92:
93:   <tr bgcolor="#eeeeee">
94:     <td width="15%">Side Content:</td>
95:     <td colspan="4">
96:       <textarea name="edtSide" rows="5" cols="60" wrap="virtual">#trim(qryFindPage.sideCode)#</textarea>
97:     </td>

```

```
98: </tr>
99: <tr bgcolor="#ffffff">
100: <td width="15%">Footer: Content:</td>
101: <td colspan="4">
102: <textarea name="editFooter" rows="5" cols="60" wrap="virtual">#trim(qryFindPage.footerCode)#</textarea>
103: </td>
104: </tr>
105:
106: <tr bgcolor="#ffffff">
107: <cfif qryFindPage.recordCount is 0>
108: <td colspan="5">
109: <input type="submit" name="btnUpdate" value="Add Page Format">
110: <input type="reset" value="Reset Info">
111: </td>
112: <cfelse>
113: <td colspan="4">
114: <input type="submit" name="btnUpdate" value="Update Page Format">
115: <input type="reset" value="Reset Info">
116: <input type="submit" name="btnView" value="View Page Format">
117: </td>
118: <td align="right">
119: <input type="submit" name="btnDelete" value="Delete Page Format">
120: </td>
121: </cfif>
122: </tr>
123: </table>
124: </form>
125:
126: </cfoutput>
```

```

1: <cfinclude template="javaValidate.cfm">
2:
3: <script language="JavaScript">
4: <!--
5:   function validate(testform) {
6:     var results = "";
7:     var lResult = true;
8:
9:     if (!isHex(removeSpaces(testform.edtNavBGColor.value))) {
10:       results = results + "** Please enter the navigation background color for this format page.\r";
11:       lResult = false;
12:     }
13:
14:     if (!isHex(removeSpaces(testform.edtNavTextColor.value))) {
15:       results = results + "** Please enter the navigation text color for this format page.\r";
16:       lResult = false;
17:     }
18:
19:     if (!isHex(removeSpaces(testform.edtMenuBGColor.value))) {
20:       results = results + "** Please enter the menu background color for this format page.\r";
21:       lResult = false;
22:     }
23:
24:     if (!isHex(removeSpaces(testform.edtMenuTextColor.value))) {
25:       results = results + "** Please enter the menu text color for this format page.\r";
26:       lResult = false;
27:     }
28:
29:     if (!isHex(removeSpaces(testform.edtHeaderBGColor.value))) {
30:       results = results + "** Please enter the header background color for this format page.\r";
31:       lResult = false;
32:     }
33:
34:     if (!isHex(removeSpaces(testform.edtFooterBGColor.value))) {
35:       results = results + "** Please enter the footer background color for this format page.\r";
36:       lResult = false;
37:     }
38:
39:     if (!isHex(removeSpaces(testform.edtAdBGColor.value))) {
40:       results = results + "** Please enter the ad space background color for this format page.\r";
41:       lResult = false;
42:     }
43:
44:     if (!lResult) {
45:       window.alert(results);
46:     }
47:
48:     return lResult;
49:   }

```



```

50:
51: function setValues(nTemplate, cNavBGColor, cNavTextColor, cMenuBGColor, cMenuTextColor) {
52:     var onform = document.forms.length;
53:     var theForm = document.forms[onform-1];
54:
55:     theForm.templateID.value = nTemplate;
56:     theForm.edtNavBGColor.value = cNavBGColor;
57:     theForm.edtNavTextColor.value = cNavTextColor;
58:     theForm.edtMenuBGColor.value = cMenuBGColor;
59:     theForm.edtMenuTextColor.value = cMenuTextColor;
60:
61:     return false;
62: }
63: -->
64: </script>
65:
66: <cfoutput>
67:
68: <!-- Get default template scheme info -->
69: <cfquery name="qryDefaultScheme" dataSource="#ap_dataSource#">
70:     select * from templates
71:     where templates.templateID = #qryFindPage.templateID#
72: </cfquery>
73:
74: <cfquery name="qrySchemes" dataSource="#ap_dataSource#">
75:     select templates.*
76:     from templates
77:     where templates.distributorID = 0
78:     or templates.distributorID = #nDistributorID#
79:     order by templates.sortOrder
80: </cfquery>
81:
82: <form action="formatUpdate.cfm" method="post" onsubmit="return validate(this)">
83:     <input type="hidden" name="pageFormatID" value="#nPageFormatID#">
84:     <input type="hidden" name="distributorID" value="#nDistributorID#">
85:     <input type="hidden" name="templateID" value="#qryFindPage.templateID#">
86:     <cfif qryDefaultScheme.recordCount is 1>
87:         <input type="hidden" name="defNavBGColor" value="#qryDefaultScheme.navBGColor#">
88:     </cfif>
89:
90:     <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
91:     <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Page Format Maintenance</b></span>
92:         <cfif client.lookupID is -1>
93:             <nbspesp>(Create a new page format
94:             <cfif cDistName is not "">
95:                 for #cDistName#
96:             </cfif>
97:         )
98:     </cfif>

```

```

99: </td></tr>
100:
101: <cfif client.lookupID gt 0>
102:   <tr bgcolor="#cccc99">
103:     <td colspan="5">
104:       <a href="formatMaint.cfm?displayPage=formatInfo">Format Content</a>
105:     </td>
106:   </tr>
107: </cfif>
108:
109: <CFIF client.userMessage is not "">
110:   <tr bgcolor="eeeeee">
111:     <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td>
112:   </tr>
113:   <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
114: </CFIF>
115: <cfset client.userMessage = "">
116:
117:   <tr bgcolor="##eeeeee">
118:     <td colspan="5" align="center"><b>Select the color and layout scheme you want for this format page.</b></td>
119:   </tr>
120:
121:   <tr bgcolor="##eeeeee">
122:     <td colspan="5">&nbsp;</td>
123:   </tr>
124:
125:   <tr bgcolor="##eeeeee">
126:     <td width="15%"><b>Nav Background Color:</b></td>
127:     <td width="34%"><input type="text" name="edtNavBGColor" value="#trim(qryFindPage.navBGColor)#"></td>
128:     <td width="28%">&nbsp;</td>
129:     <td width="15%"><b>Nav Text Color:</b></td>
130:     <td width="34%"><input type="text" name="edtNavTextColor" value="#trim(qryFindPage.navTextColor)#"></td>
131:   </tr>
132:
133:   <tr bgcolor="##eeeeee">
134:     <td colspan="5">&nbsp;</td>
135:   </tr>
136:
137:   <tr bgcolor="##eeeeee">
138:     <td width="15%"><b>Menu Background Color:</b></td>
139:     <td width="34%"><input type="text" name="edtMenuBGColor" value="#trim(qryFindPage.menuBGColor)#"></td>
140:     <td width="28%">&nbsp;</td>
141:     <td width="15%"><b>Menu Text Color:</b></td>
142:     <td width="34%"><input type="text" name="edtMenuTextColor" value="#trim(qryFindPage.menuTextColor)#"></td>
143:   </tr>
144:
145:   <tr bgcolor="##eeeeee">
146:     <td colspan="5">&nbsp;</td>
147:   </tr>

```

```

148: <tr bgcolor="#ffffff">
149: <td width="15%"><b>header Background Color:</b></td>
150: <td width="34%"><input type="text" name="edtHeaderBGColor" value="#trim(qryFindPage.headerBGColor)#"></td>
151: <td width="2%"><b></b></td>
152: <td width="15%"><b>Footer Background Color:</b></td>
153: <td width="34%"><input type="text" name="edtFooterBGColor" value="#trim(qryFindPage.footerBGColor)#"></td>
154: </tr>
155:
156:
157: <tr bgcolor="#ffffff">
158: <td colspan="5"><b></b></td>
159: </tr>
160:
161: <tr bgcolor="#ffffff">
162: <td width="15%"><b>Ad Space Background Color:</b></td>
163: <td width="34%"><input type="text" name="edtAdBGColor" value="#trim(qryFindPage.adBGColor)#"></td>
164: <td width="2%"><b></b></td>
165: <td width="15%"><b>Search Background Color:</b></td>
166: <td width="34%"><input type="text" name="edtSearchBGColor" value="#trim(qryFindPage.searchBGColor)#"></td>
167: </tr>
168:
169:
170: <tr bgcolor="#cccc99">
171: <td colspan="5"><b></b></td>
172: </tr>
173:
174: <tr bgcolor="#cccc99">
175: <td colspan="5"><b>qryFindPage.recordCount is 0</td>
176: <td colspan="5">
177: <input type="submit" name="btnUpdateScheme" value="Add Page Format">
178: <input type="reset" value="Reset Changes">
179: </td>
180: <td colspan="4"><b></b></td>
181: <td colspan="4">
182: <input type="submit" name="btnUpdateScheme" value="Update Page Format">
183: <input type="reset" value="Reset Changes">
184: <input type="submit" name="btnView" value="View Page Format">
185: </td>
186: <td align="right">
187: <input type="submit" name="btnDelete" value="Delete Page Format">
188: </td>
189: </td>
190: </tr>
191:
192: <tr bgcolor="#cccc99">
193: <td colspan="5"><b></b></td>
194: </tr>
195:
196: <td colspan="5"><b>qrySchemes.recordCount is 0</td>

```

```

197: <tr bgcolor="#ffffff">
198:   <td colspan="5"><i>There are no sample schemes available.</i></td>
199: </tr>
200: <cfelse>
201:   <tr bgcolor="#ffffff">
202:     <td colspan="5">
203:       Templates:
204:     </td>
205:   </tr>
206:
207:   <tr bgcolor="#ffffff">
208:     <td width="10%"><b><nbsp;</td>
209:     <td><b>Description</b></td>
210:     <td align="center"><b>Button Shape</b></td>
211:     <td align="center"><b>Navigation Colors</b></td>
212:     <td align="center"><b>Menu Colors</b></td>
213:   </tr>
214:
215:   <cfset lColor = True>
216:   <cfloop query="qrySchemes">
217:     <cfset lColor = not lColor>
218:     <tr <cfif lColor is TRUE>bgcolor="#ffffff"</cfif>>
219:       <td width="10%">
220:         <input type="button" name="btnSet" value="Set"
221:           onclick="return setValues('#qrySchemes.templateID#,
222:             '#trim(qrySchemes.navBGColor)#',
223:             '#trim(qrySchemes.navTextColor)#', '#trim(qrySchemes.menuBGColor)#',
224:             '#trim(qrySchemes.menuTextColor)#')">
225:       <cfif qryFindPage.templateID is qrySchemes.templateID><i>(currently)</i></cfif>
226:     </td>
227:     <td valign="top">#trim(qrySchemes.sampleText)</td>
228:     <cfif qrySchemes.navButtonImage is not "">
229:       <td align="center"></td>
230:     <cfelse>
231:       <td align="center"><i>Text Only</i></td>
232:     </cfif>
233:     <td align="center" bgcolor="#trim(qrySchemes.navBGColor)#"><font
      color="#trim(qrySchemes.navTextColor)#"><b>Navigation Text</b></font></td>
234:     <td align="center" bgcolor="#trim(qrySchemes.menuBGColor)#"><font color="#trim(qrySchemes.menuTextColor)#"><b>Menu
      Text</b></font></td>
235:   </tr>
236:   </cfloop>
237: </cfif>
238:
239: </table>
240: </form>
241:
242: </cfoutput>

```

```

1: <!-- Get security hierarchy -->
2: <cfparam name="client.cacheSecurity" default="true">
3:
4: <cfif not isDefined("client.entityID") or not isDefined("client.entityType")>
5:   <cflocation url="login.cfm" addToken="no">
6: </cfif>
7:
8: <cfparam name="lstSecurityFilter" default="-1">
9:
10: <cfif client.cacheSecurity is true>
11:   <cfset nCacheTime = createTimeSpan(0,0,30,0)>
12: <cfelse>
13:   <cfset nCacheTime = createTimeSpan(0,0,-30,0)>
14: </cfif>
15: <cfquery name="qrySecurity" dataSource="#ap_datasource#" cachedwithin="#nCacheTime#">
16:   select *
17:   from securityAccess
18:   where securityAccess.hierarchyID like
19:     (select hierarchyID from securityAccess where securityAccess.entityID = #client.entityID#
20:      and securityAccess.entityType = #client.entityType#) + '%'
21:   <cfif lstSecurityFilter is not "-1">
22:     and securityAccess.entityType in (#lstSecurityFilter#)
23:   </cfif>
24:   order by hierarchyID
25: </cfquery>
26:
27: <cfset client.cacheSecurity = true>
28:
29: <!--
30: <cfset lstSecurityList = quotedValueList(qrySecurity/.securityTest)>
31: ---
32:
33: <!--
34: <cfoutput query="qrySecurity">
35:   #entityID# #entityType# #name# #parentID# #parentType# #hierarchyID#<br>
36: </cfoutput>
37: ---

```

```

1:  <!-- Header -->
2:
3:  <cfif not isDefined("client.userID") or not isDefined("client.currentDistributorID")
4:  or not isDefined("client.hierarchyID")>
5:    <cflocation url="login.cfm" addToken="no">
6:  </cfif>
7:
8:  <table border="0" width="100%" cellpadding="2" cellspacing="0">
9:    <cfif isDefined("client.multiCustomer") and client.multiCustomer is True>
10:      <tr>
11:        <td bgcolor="#cccc99">
12:          <cfif not isDefined("lstSecurityFilter")>
13:            <cfset lstSecurityFilter = "#ap_securityYakalo#, #ap_securityMastDist#,
14:            #ap_securityDist#">
15:          </cfif>
16:        </td>
17:        <cfset lstSecurityFilter = "1,2,3,4,5,6,7,8">
18:      </tr>
19:    </cfif>
20:    <cfinclude template="getSecurityTree.cfm">
21:    <cfif grySecurity.recordCount gt 1>
22:      <table border="0" cellpadding="0" cellspacing="0" width="100%">
23:        <tr valign="top">
24:          <td width="40%">
25:            <form action="customerSwitch.cfm" method="post">
26:              Administrator: <select name="edtSite">
27:                <cfloop query="grySecurity">
28:                  <cfoutput>
29:                    <option value="#grySecurity.entityType#|#grySecurity.entityID#"><cfif grySecurity.entityID is
30:                      grySecurity.entityType is trim(client.currentEntityType)>selected</cfif><cfif>
31:                    <cfif client.entityType is 1>
32:                      <cfset nSpaceStart = 2>
33:                    </cfif>
34:                    <cfset nSpaceStart = 3>
35:                    </cfif>
36:                    <cfloop from="#nSpaceStart#" to="#grySecurity.entityType#" index="i">&nbsp;&nbsp;&nbsp;</cfloop>#grySecurity.name#
37:                  </cfoutput>
38:                </select>
39:                <input type="submit" name="btnSubmit" value="Change">
40:              </form>
41:            </td>
42:            <td bgcolor="#cccc99" class="hl" align="center"><cfoutput>#client.backOfficeName#</cfoutput> Back Office</td>
43:          </tr>
44:        </table>
45:      </cfif>
46:    </td>
47:  </tr>
48:  </cfif>

```

```

49: <cfset lstSecurityFilter = "1,2,3,4,5,6,7,8">
50: <cfinclude template="getSecurityTree.cfm">
51: <tr>
52:   <td bgcolor="#cccc99" class="hl" align="center"><cfoutput>#client.backOfficeName#</cfoutput>'s Back Office<br></td>
53: </tr>
54: </cfif>
55: </table>
56:
57: <cfoutput>
58: <table border="0" cellpadding="0" cellspacing="0" width="100%">
59: <!-- administrator Options are available only for Yakalo users -->
60: <cfif client.entityType is ap_securityYakalo>
61:   <tr bgcolor="#cccc99">
62:     <td><b>Administrator Options:</b></td>
63:     <td><b></td>
64: </tr>
65: <td><midot><a href="/customerAdm.cfm" onMouseOver="window.status='Maintains customer information'; return true"
66:   </td>
67: <td><midot><a href="/defaultAdm.cfm" onMouseOver="window.status='Maintain system default settings'; return true"
68:   <td><b></td>
69: <td><midot><a href="/statsAdm.cfm" onMouseOver="window.status='View statistics'; return true"
70:   <td><b></td>
71: <td><midot><a href="/securityAsk.cfm" onMouseOver="window.status='Regenerates the security access list table'; return
72:   true" onMouseOut="window.status=''">Recreate Security Tree</a></td>
73: </tr>
74: </cfif>
75:
76: <cfif client.currentEntityType lte ap_securityPortal>
77:   <tr bgcolor="#cccc99">
78:     <td><b>Portal Options:</b></td>
79:     <td><midot><a href="/portalAdm.cfm" onMouseOver="window.status='Maintain portal information'; return true"
80:     <td><b></td>
81:     <td><midot></td>
82:     <td><b></td>
83:     <td><midot></td>
84:   </tr>
85: </cfif>
86:
87:
88: <cfif client.currentEntityType lte ap_securityDist>
89:   <tr bgcolor="#cccc99">
90:     <td><b>Distributor Options:</b></td>
91:     <td><midot><a href="/resourceAdm.cfm" onMouseOver="window.status='Maintain resource groups and links'; return true"
onMouseOut="window.status=''">Resources</a></td>

```

```

92:         <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="communityAdm.cfm" onmouseover="Maintain community information"; return true"
onMouseout="window.status="">Communities</a></td>
93:         <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="distDefaultAdm.cfm" onmouseover="window.status='Maintain default settings'; return true"
onMouseout="window.status="">Defaults</a></td>
94:         <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="navMaint.cfm" onmouseover="window.status='Maintain main WWW navigation links'; return true"
onMouseout="window.status="">Navigation</a></td>
95:         <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="specialtyAdm.cfm" onmouseover="window.status='Maintain specialty pages'; return true"
onMouseout="window.status="">Specialty Pages</a></td>
96:         <cfif client.currentEntityType is ap_securityYakalo or client.currentEntityType is ap_securityPortal>
97:         <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="distAdm.cfm" onmouseover="window.status='Distributor Administration'; return true"
onMouseout="window.status="">Distributor Admin</a></td>
98:         <cfelse>
99:         <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
100:        </cfif>
101:    </tr>
102:    <tr bgcolor="##cccc99">
103:        <cfif client.currentDistributorID gt 0>
104:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
105:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="formatAdm.cfm" onmouseover="window.status='Maintain format pages'; return true"
onMouseout="window.status="">Format Pages</a></td>
106:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="homePageAdm.cfm" onmouseover="window.status='Maintain customized home page'; return true"
onMouseout="window.status="">Home Page</a></td>
107:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
108:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
109:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
110:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
111:        <cfelse>
112:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
113:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="formatAdm.cfm" onmouseover="window.status='Maintain format pages'; return true"
onMouseout="window.status="">Format Pages</a></td>
114:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="homePageAdm.cfm" onmouseover="window.status='Maintain customized home page'; return true"
onMouseout="window.status="">Home Page</a></td>
115:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
116:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
117:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
118:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</td>
119:        </cfif>
120:    </tr>
121:    </cfif>
122:
123:    <cfif client.currentEntityType lte ap_securityAgency>
124:    <tr bgcolor="##cccc99">
125:        <td><b>Agency Options</b></td>
126:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="agencyAdm.cfm" onmouseover="window.status='Maintain agency information'; return true"
onMouseout="window.status="">Agency Admin</a></td>
127:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="AgencyBioAdm.cfm" onmouseover="window.status='Maintain enhanced agency listings'; return true"
onMouseout="window.status="">Agency Bio</a></td>
128:        <td>&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<a href="defaultMaint.cfm?type=rooms" onmouseover="window.status='Maintain room names'; return true"
onMouseout="window.status="">Rooms</a></td>

```



```

129:         <td>&nbsp;</td>
130:         <td>&nbsp;</td>
131:         <td>&nbsp;</td>
132:     </tr>
133: </cfif>
134:
135: <cfif client.currentEntityType lte ap_securityAgent>
136:     <tr bgcolor="#cccc99">
137:         <td><b>Agent Options:</b></td>
138:         <td>&nbsp;<b>Agent Options:</b></td>
139:         <td>&nbsp;<b>Agent Options:</b></td>
140:         <td>&nbsp;<b>Agent Options:</b></td>
141:         <td>&nbsp;<b>Agent Options:</b></td>
142:         <td>&nbsp;<b>Agent Options:</b></td>
143:         <td>&nbsp;<b>Agent Options:</b></td>
144:     </tr>
145: </cfif>
146:
147: <tr bgcolor="#cccc99">
148:     <td><b>User Options:</b></td>
149:     <td>&nbsp;<b>User Options:</b></td>
150:     <td>&nbsp;<b>User Options:</b></td>
151:     <td>&nbsp;<b>User Options:</b></td>
152:     <td>&nbsp;<b>User Options:</b></td>
153:     <td>&nbsp;<b>User Options:</b></td>
154:     <td>&nbsp;<b>User Options:</b></td>
155:     <td>&nbsp;<b>User Options:</b></td>
156:     <td>&nbsp;<b>User Options:</b></td>
157:     <td>&nbsp;<b>User Options:</b></td>
158:     <td>&nbsp;<b>User Options:</b></td>
159:     <td>&nbsp;<b>User Options:</b></td>
160:     <td>&nbsp;<b>User Options:</b></td>
161:     <td>&nbsp;<b>User Options:</b></td>
162:     <td>&nbsp;<b>User Options:</b></td>
163:     <td>&nbsp;<b>User Options:</b></td>
164:     <td>&nbsp;<b>User Options:</b></td>
165:     <td>&nbsp;<b>User Options:</b></td>
166:     <td>&nbsp;<b>User Options:</b></td>
167:     <td>&nbsp;<b>User Options:</b></td>
168:     <td>&nbsp;<b>User Options:</b></td>

```

```

1: <script language="JavaScript">
2: <!--
3: function removesSpaces(string) {
4:   var temp = "";
5:   string = '' + string;
6:   splitstring = string.split(" ");
7:   for(i = 0; i < splitstring.length; i++)
8:     temp += splitstring[i];
9:   return temp;
10: }
11:
12:
13: function isValidEmail(email) {
14:   var lsAT;
15:   var lsDOT;
16:
17:   lsAT = email.indexOf("@");
18:   lsDOT = email.indexOf(".");
19:
20:   if (lsAT == -1 || lsDOT == -1 || email.indexOf(" ") != -1 || lsAT + 1 >= lsDOT ) {
21:     return false;
22:   }
23:   return true;
24: }
25:
26:
27: function isValidDate(dateStr) {
28:
29:   var err=0
30:   var psj=0;
31:
32:   if (dateStr.length != 8 && dateStr.length != 10) return false
33:
34:   b = dateStr.substring(0, 2) // month,
35:   c = dateStr.substring(2, 3) // '/'
36:   d = dateStr.substring(3, 5) // day
37:   e = dateStr.substring(5, 6) // '/'
38:   if (dateStr.length == 8) f = dateStr.substring(6, 8) // 2-digit year
39:   if (dateStr.length == 10) f = dateStr.substring(6,10) // 4-digit year
40:
41:   //basic error checking
42:   if (b<1 || b>12) return false
43:   if (c != '/') return false
44:   if (d<1 || d>31) return false
45:   if (e != '/') return false
46:   if (f<0 || f>9999) return false
47:
48:   //advanced error checking
49:

```

```

50: // months with 30 days
51: if (b==4 || b==6 || b==9 || b==11){
52:     if (d==31) return false
53: }
54:
55: // february, leap year
56: if (b==2){
57:     // feb
58:     var g=parseInt(f/4)
59:     if (isNaN(g)) {
60:         return false
61:     }
62:
63:     if (d>29) return false
64:     if (d==29 && ((f/4)!=parseInt(f/4))) return false
65: }
66:
67: return true;
68: }
69:
70:
71: function isNumber(xValue)
72: {
73:     var l
74:     var word = xValue
75:     //
76:     // Run through each letter in the "word"
77:     //
78:     for (var j = 0; j < word.length; j++)
79:     {
80:         // Set the next letter
81:         l = word.charAt(j)
82:         // See if it doesn't equal 0, 1, 2, 3...
83:         if (l != "0" && l != "1" && l != "2" && l != "3" && l != "4" &&
84:             l != "5" && l != "6" && l != "7" && l != "8" && l != "9")
85:             return false
86:     }
87:     return true
88: }
89:
90: function isHex(xValue)
91: {
92:     var l
93:     var word = xValue
94:     //
95:     // Run through each letter in the "word"
96:     //
97:     word = xValue.toUpperCase();
98:

```

```

99: if (word.length == 0 || word == "#")
100:     return false;
101:
102: for (var j = 0; j < word.length; j++)
103: {
104:     // Get the next letter
105:     l = word.charAt(j)
106:     // See if it doesn't equal 0, 1, 2, 3...
107:     if (l == "#" && j > 0)
108:         return false
109:     if (l != "0" && l != "1" && l != "2" && l != "3" && l != "4" &&
110:         l != "5" && l != "6" && l != "7" && l != "8" && l != "9" &&
111:         l != "A" && l != "B" && l != "C" && l != "D" && l != "E" && l != "F" && l != "#")
112:         return false
113: }
114:     return true
115: }
116:
117:
118: function isFloat(xValue)
119: {
120:     var l
121:     var word = xValue
122:     var lDecimal
123:
124:     lDecimal = false
125:     // Run through each letter in the "word"
126:     //
127:     for (var j = 0; j < word.length; j++)
128:     {
129:         // Get the next letter
130:         l = word.charAt(j)
131:
132:         // Check for multiple decimal point
133:         if (l == ".") {
134:             if (lDecimal)
135:                 return false
136:             lDecimal = true
137:         }
138:     }
139:
140:     // See if it doesn't equal 0, 1, 2, 3...
141:     if (l != "0" && l != "1" && l != "2" && l != "3" && l != "4" &&
142:         l != "5" && l != "6" && l != "7" && l != "8" && l != "9" && l != ".")
143:         return false
144:     }
145:     return true
146: }
147:

```

[illegible]

```

1:  <!-- Generate application.cfm for a distributed application -->
2:
3:  <cfif isDefined("nCreateDistID")>
4:    <cfquery name="qryDist" dataSource="#ap_dataSource#">
5:      select distributors.*
6:      from distributors
7:      where distributors.distributorID = #nCreateDistID#
8:    </cfquery>
9:
10:    <cfset cCurrentPath = expandPath(".")>
11:    <cfset cTemplateFile = #cCurrentPath# & "include\templateApplication.cfm">
12:    <cfset cTemplate = "">
13:
14:    <cfif qryDist.recordCount is 1>
15:      <cfif action="read"
16:        variable = "cTemplate"
17:        file = "#cTemplateFile#"
18:      >
19:
20:        <cfset cTemplate = replaceNoCase(cTemplate,
21:          "<<COMMON_IMAGES>>", #qryDist.commonImages#)>
22:        <cfset cTemplate = replaceNoCase(cTemplate,
23:          "<<PROPERTY_IMAGES>>", #qryDist.propertyImages#)>
24:        <cfset cTemplate = replaceNoCase(cTemplate,
25:          "<<AGENT_IMAGES>>", #qryDist.agentImages#)>
26:        <cfset cTemplate = replaceNoCase(cTemplate,
27:          "<<AGENCY_IMAGES>>", #qryDist.agencyImages#)>
28:        <cfset cTemplate = replaceNoCase(cTemplate,
29:          "<<COMMUNITY_IMAGES>>", #qryDist.communityImages#)>
30:        <cfset cTemplate = replaceNoCase(cTemplate,
31:          "<<SPECIALTY_IMAGES>>", #qryDist.specialtyImages#)>
32:        <cfset cTemplate = replaceNoCase(cTemplate,
33:          "<<ENHAGENCY_IMAGES>>", #qryDist.enhAgencyImages#)>
34:        <cfset cTemplate = replaceNoCase(cTemplate,
35:          "<<ENHAGENT_IMAGES>>", #qryDist.enhAgentImages#)>

```

```

1: <cfparam name="nUpdateID" default="-1">
2: <cfparam name="nUpdateType" default="-1">
3: <cfparam name="cUpdateAction" default="CREATE">
4:
5: <cfset cUpdateAction = ucase(cUpdateAction)>
6: <cfif cUpdateAction is "DELETE">
7:   <cfset cUpdateAction = "UPDATE">
8: </cfif>
9:
10: <cfif cUpdateAction is "UPDATE">
11:
12:   <!--- Mark the parent as dirty -->
13:   <cfquery name="qryParent" dataSource="#ap_dataSource#">
14:     select entityID, entityType, hierarchyID
15:     from securityAccess
16:     where securityAccess.entityID = #nUpdateID#
17:   <cfif nUpdateType is #ap_securityMastAgency#>
18:     and (securityAccess.entityType = #ap_securityMastAgency# or
19:         securityAccess.entityType = #ap_securityAgency#)
20:   <cfelse>
21:     and securityAccess.entityType = #nUpdateType#
22:   </cfif>
23: </cfquery>
24:
25:   <!--- Mark my childer as dirty -->
26:   <cfquery name="qryDirty" dataSource="#ap_dataSource#">
27:     update securityAccess
28:     set dirty='Y'
29:     where securityAccess.hierarchyID like '#qryParent.hierarchyID#%'
30:   </cfquery>
31: </cfif>
32:
33:
34:   <!--- New Security Creation Routines -->
35:   <cfif cUpdateAction is "CREATE">
36:     <cfquery name="qryDelete" dataSource="#ap_dataSource#">
37:       truncate table securityAccess
38:     </cfquery>
39:   </cfif>
40:
41:   <!--- Yakalo Administrator -->
42:
43:   <cfif cUpdateAction is "CREATE">
44:     <cfquery name="qryInsert" dataSource="#ap_dataSource#">
45:       insert into SecurityAccess
46:         (entityID, entityType, name, parentID, parentType, distributorID, portalID, hierarchyID)
47:         values
48:         (#ap_securityYakalo#, #ap_securityYakalo#, 'Yakalo Solutions Administrator', 0, 0, 0, 0,
         '#ap_securityYakalo#.#ap_securityYakalo#.')

```

```

49: </cfquery>
50: </cfif>
51:
52: <!-- Portals -->
53: <cfif cUpdateAction is "CREATE">
54:   <cfquery name="qryInsert" dataSource="#ap_dataSource#">
55:     insert into SecurityAccess
56:       (entityID, entityType, name, parentID, parentType, distributorID, portalID, hierarchyID)
57:     select portals.portalID as entityID, #ap_securityPortal# as entityType, portals.name,
58:       #ap_securityYakalo# as parentID, #ap_securityYakalo# as parentType, 0 as distributorID,
59:       portals.portalID as portalID,
60:       p.hierarchyID + '#ap_securityPortal#' + convert(varchar,portals.portalID) + '.' as hierarchyID
61:     from portals
62:     join securityAccess p on p.entityID = #ap_securityYakalo#
63:     and p.entityType = #ap_securityYakalo#
64:   </cfquery>
65: </cfif>
66:
67:
68: <!-- Master Distributors -->
69: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
70:   insert into SecurityAccess
71:     (entityID, entityType, name, parentID, parentType, distributorID, portalID, hierarchyID)
72:   select distributors.distributorID as entityID, #ap_securityMastDist# as entityType, distributors.name,
73:     distributors.portalID as parentID, #ap_securityPortal# as parentType,
74:     distributors.distributorID, p.portalID as portalID,
75:     p.hierarchyID + '#ap_securityMastDist#' + convert(varchar,distributors.distributorID) + '.' as hierarchyID
76:   from distributors
77:   join securityAccess p on p.entityID = distributors.portalID
78:   and p.entityType = #ap_securityPortal#
79: <cfif cUpdateAction is "UPDATE">
80:   join securityAccess c on c.entityID = distributors.distributorID and
81:     (c.entityType = #ap_securityMastDist# or c.entityType = #ap_securityDist#)
82:   and c.dirty = 'Y'
83: </cfif>
84:   where distributors.parentID = 0
85: <cfif cUpdateAction is "ADD" and nUpdateType is #ap_securityMastDist#>
86:   and distributors.distributorID = #nUpdateID#
87: <cfelseif cUpdateAction is "ADD">
88:   and distributors.distributorID = -1
89: </cfif>
90:
91: </cfquery>
92:
93:
94: <!-- Distributors -->
95: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
96:   insert into SecurityAccess
97:     (entityID, entityType, name, parentID, parentType, distributorID, portalID, hierarchyID)

```



```

98: select distributors.distributorID as entityID, #ap_securityMastDist# as entityType, distributors.name,
99: distributors.parentID as parentID, #ap_securityMastDist# as parentType,
100: distributors.distributorID, p.portalID as portalID,
101: p.hierarchyID+ '#ap_securityDist#' + convert(varchar,distributors.distributorID) + '.' as hierarchyID
102: from distributors
103: join securityAccess p on p.entityID = distributors.parentID
104: and p.entityType = #ap_securityMastDist#
105: <cfif cUpdateAction is "UPDATE">
106: join securityAccess c on c.entityID = distributors.distributorID and
107: (c.entityType = #ap_securityMastDist# or c.entityType = #ap_securityDist#)
108: and c.dirty = 'Y',
109: </cfif>
110: where distributors.parentID > 0
111: <cfif cUpdateAction is "ADD" and nUpdateType is #ap_securityMastDist#>
112: and distributors.distributorID = #nUpdateID#
113: <cfelseif cUpdateAction is "ADD">
114: and distributors.distributorID = -1
115: </cfif>
116: </cfquery>
117:
118: <!--- Create 'Unaffiliated Agents' agency for all distributors ---->
119: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
120: insert into SecurityAccess
121: (entityID, entityType, name, parentID, distributorID, portalID, hierarchyID)
122: select distributors.distributorID as entityID, #ap_securityNoAgency# as entityType,
123: 'Unaffiliated Agents' as name,
124: distributors.distributorID as parentID,
125: p.entityType as parentType,
126: distributors.distributorID, p.portalID,
127: p.hierarchyID+ '#ap_securityNoAgency#' + convert(varchar,distributors.distributorID) + '.' as hierarchyID
128: from distributors
129: join securityAccess p on p.entityID = distributors.distributorID
130: and (p.entityType = #ap_securityMastDist# or p.entityType = #ap_securityDist#)
131: <cfif cUpdateAction is "UPDATE">
132: join securityAccess c on c.entityID = distributors.distributorID and
133: c.entityType = #ap_securityNoAgency#
134: and c.dirty = 'Y',
135: </cfif>
136: <cfif cUpdateAction is "ADD" and nUpdateType is #ap_securityMastDist#>
137: and distributors.distributorID = #nUpdateID#
138: <cfelseif cUpdateAction is "ADD">
139: and distributors.distributorID = -1
140: </cfif>
141:
142: </cfquery>
143:
144: <!--- Agencies * * * ---->
145:
146:

```

```

147:
148:
149: <!-- Master Agencies w/ Distributors -->
150: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
151:   insert into SecurityAccess
152:     (entityID, entityType, name, parentID, parentType, distributorID, portalID, hierarchyID)
153:   select agency_id as entityID, #ap_securityMastAgency# as entityType, agency.name,
154:     agency.distributorID as parentID, p.entityType as parentType,
155:     agency.distributorID as distributorID, p.portalID,
156:     p.hierarchyID+ '#ap_securityMastAgency#'+convert(varchar,agency.agency_id)+'.' as hierarchyID
157:   from agency
158:   join securityAccess p on p.entityID = agency.distributorID
159:   and (p.entityType = #ap_securityMastDist# or p.entityType = #ap_securityDist#)
160:   <cfif cUpdateAction is "UPDATE">
161:     join securityAccess c on c.entityID = agency.agency_id and
162:       (c.entityType = #ap_securityMastAgency# or c.entityType = #ap_securityAgency#)
163:     and c.dirty = 'Y'
164:   </cfif>
165:   where agency.parentAgency = 0
166:   and agency.distributorID > 0
167:   <cfif cUpdateAction is "ADD" and nUpdateType is #ap_securityMastAgency#>
168:     and agency.agency_id = #nUpdateID#
169:   <cfelseif cUpdateAction is "ADD">
170:     and agency.agency_id = -1
171:   </cfif>
172: </cfquery>

173:
174: <!-- Master Agencies w/o Distributors -->
175: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
176:   insert into SecurityAccess
177:     (entityID, entityType, name, parentID, parentType, distributorID, portalID, hierarchyID)
178:   select agency_id as entityID, #ap_securityMastAgency# as entityType, agency.name,
179:     #ap_securityYakalo# as parentID, #ap_securityYakalo# as parentType, agency.distributorID,
180:     p.portalID,
181:     p.hierarchyID+ '#ap_securityMastAgency#'+convert(varchar,agency.agency_id)+'.' as hierarchyID
182:   from agency
183:   join securityAccess p on p.entityID = agency.distributorID
184:   and p.entityType = #ap_securityYakalo#
185:   <cfif cUpdateAction is "UPDATE">
186:     join securityAccess c on c.entityID = agency.agency_id and
187:       (c.entityType = #ap_securityMastAgency# or c.entityType = #ap_securityAgency#)
188:     and c.dirty = 'Y'
189:   </cfif>
190:   where agency.parentAgency = 0
191:   and agency.distributorID = 0
192:   <cfif cUpdateAction is "ADD" and nUpdateType is #ap_securityMastAgency#>
193:     and agency.agency_id = #nUpdateID#
194:   <cfelseif cUpdateAction is "ADD">
195:     and agency.agency_id = -1

```

```

196: </cfif>
197: </cfquery>
198:
199: <!-- Agencies w/ Master Agency and w/Distributor-->
200: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
201: insert into SecurityAccess
202: (entityID, entityType, name, parentID, parentType, distributorID, portalID, hierarchyID)
203: select agency_id as entityID, #ap_securityAgency# as entityType, agency.name,
204: agency.parentAgency as parentID, p.entityType as parentType,
205: agency.distributorID, p.portalID,
206: p.hierarchyID+'#ap_securityAgency#'+convert(varchar,agency.agency_id)+'.' as hierarchyID
207: from agency
208: join securityAccess p on p.entityID = agency.parentAgency
209: and p.entityType = #ap_securityMastAgency#
210: <cfif cUpdateAction is "UPDATE">
211: join securityAccess c on c.entityID = agency.agency_id and
212: (c.entityType = #ap_securityAgency# or c.entityType = #ap_securityMastAgency#)
213: and c.dirty = 'Y'
214: </cfif>
215: where agency.parentAgency > 0
216: and agency.distributorID > 0
217: <cfif cUpdateAction is "ADD" and nUpdateType is #ap_securityMastAgency#>
218: and agency.agency_id = #nUpdateID#
219: <cfelseif cUpdateAction is "ADD">
220: and agency.agency_id = -1
221: </cfif>
222: </cfquery>
223:
224: <!-- Agencies w/Master Agency and w/o Distributor-->
225: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
226: insert into SecurityAccess
227: (entityID, entityType, name, parentID, parentType, distributorID, portalID, hierarchyID)
228: select agency_id as entityID, #ap_securityAgency# as entityType, agency.name,
229: #ap_securityYakalo# as parentID, p.entityType as parentType,
230: agency.distributorID, p.portalID,
231: p.hierarchyID+'#ap_securityAgency#'+convert(varchar,agency.agency_id)+'.' as hierarchyID
232: from agency
233: join securityAccess p on p.entityID = #ap_securityYakalo#
234: and p.entityType = #ap_securityYakalo#
235: <cfif cUpdateAction is "UPDATE">
236: join securityAccess c on c.entityID = agency.agency_id and
237: (c.entityType = #ap_securityAgency# or c.entityType = #ap_securityMastAgency#)
238: and c.dirty = 'Y'
239: </cfif>
240: where agency.parentAgency > 0
241: and agency.distributorID = 0
242: <cfif cUpdateAction is "ADD" and nUpdateType is #ap_securityMastAgency#>
243: and agency.agency_id = #nUpdateID#
244: <cfelseif cUpdateAction is "ADD">

```

```

245:         and agency.agency_id = -1
246:     </cfif>
247:
248: </cfquery>
249:
250:
251: <!-- * * * Agents * * * -->
252:
253: <!-- Agent with Agency -->
254: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
255:     insert into SecurityAccess
256:     (entityID, entityType, name, parentID, parentType, distributorID, portalID, hierarchyID)
257:     select agents.agent_id as entityID, #ap_securityAgent# as entityType,
258:     agents.firstName + ' ' + agents.lastName as name,
259:     agents.agency_id as parentID,
260:     p.entityType as parentType,
261:     agents.distributorID, p.portalID,
262:     p.hierarchyID+'#ap_securityAgent#.'+convert(varchar,agents.agent_id)+'.' as hierarchyID
263:     from agents
264:
265:     join securityAccess p on p.entityID = agents.agency_id
266:     and (p.entityType = #ap_securityMastAgency# or p.entityType = #ap_securityAgency#)
267: <cfif cUpdateAction is "UPDATE">
268:     join securityAccess c on c.entityID = agents.agent_id and c.entityType = #ap_securityAgent# and c.dirty = 'Y'
269: </cfif>
270:     where agents.agency_id > 0
271:     and agents.distributorID > 0
272: <cfif cUpdateAction is "ADD" and nUpdateType is #ap_securityAgent#>
273:     and agents.agent_id = #nUpdateID#
274: <cfelse if cUpdateAction is "ADD">
275:     and agents.agent_id = -1
276: </cfif>
277: </cfquery>
278:
279:
280: <!-- Unaffiliated Agents -->
281: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
282:     insert into SecurityAccess
283:     (entityID, entityType, name, parentID, parentType, distributorID, portalID, hierarchyID)
284:     select agents.agent_id as entityID, #ap_securityAgent# as entityType,
285:     agents.firstName + ' ' + agents.lastName as name,
286:     agents.distributorID as parentID, #ap_securityNoAgency#,
287:     agents.distributorID, p.portalID,
288:     p.hierarchyID+'#ap_securityAgent#.'+convert(varchar,agents.agent_id)+'.' as hierarchyID
289:     from agents
290:     join securityAccess p on p.entityID = agents.distributorID
291:     and p.entityType = #ap_securityNoAgency#
292: <cfif cUpdateAction is "UPDATE">
293:     join securityAccess c on c.entityID = agents.agent_id and c.entityType = #ap_securityAgent# and c.dirty = 'Y'

```

```
294: </cfif>
295: where agents.agency_id = 0
296: and agents.distributorID > 0
297: <cfif cUpdateAction is "ADD" and nUpdateType is #ap_securityAgent#>
298:   and agents.agent_id = #nUpdateID#
299: <cfelseif cUpdateAction is "ADD">
300:   and agents.agent_id = -1
301: </cfif>
302: </cfquery>
303:
304:
305: <cfif cUpdateAction is "UPDATE">
306:   <cfquery name="qryClean" dataSource="#ap_dataSource#">
307:     delete from securityAccess
308:     where securityAccess.dirty = 'Y'
309:   </cfquery>
310: </cfif>
311:
312:
```

```
1: <cfquery name="qryTruncate" dataSource="#ap_dataSource#">
2:   delete from securityAccess
3: </cfquery>
4:
5:
6:
7: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
8:   select entityType from entityTypes
9:   where entityTypes.description = 'Yakalo Administrator'
10: </cfquery>
11: <cfset nYakaloID = qryGetEntityID.entityTypeID>
12:
13: <cfquery name="qryGetYakalo" dataSource="#ap_dataSource#">
14:   select userID from security
15:   where security.userName = 'Yakalo.adm'
16: </cfquery>
17: <cfset nYakUserID = qryGetEntityID.entityTypeID>
18:
19:
20: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
21:   select entityType from entityTypes
22:   where entityTypes.description = 'Portal'
23: </cfquery>
24: <cfset nPortalID = qryGetEntityID.entityTypeID>
25:
26:
27: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
28:   select entityType from entityTypes
29:   where entityTypes.description = 'Master Distributor'
30: </cfquery>
31: <cfset nMastDistID = qryGetEntityID.entityTypeID>
32:
33: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
34:   select entityType from entityTypes
35:   where entityTypes.description = 'Distributor'
36: </cfquery>
37: <cfset nDistID = qryGetEntityID.entityTypeID>
38:
39: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
40:   select entityType from entityTypes
41:   where entityTypes.description = 'Master Agency'
42: </cfquery>
43: <cfset nMastAgency_id = qryGetEntityID.entityTypeID>
44:
45: <cfquery name="qryGetEntityID" dataSource="#ap_dataSource#">
46:   select entityType from entityTypes
47:   where entityTypes.description = 'Agency'
48: </cfquery>
49: <cfset nAgency_id = qryGetEntityID.entityTypeID>
```

```

50:         <cfquery name="qryGetEntityID" datasource="#ap_dataSource#">
51:             select entityID from entityTypes
52:             where entityTypes.description = 'Agent'
53:         </cfquery>
54:         <cfset nagent_id = qryGetEntityID.entityTypeID>
55:
56:
57:
58:         <!-- Make securityAccess table -->
59:         <cfquery name="qryInsert" datasource="#ap_dataSource#">
60:             insert into securityAccess
61:             (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
62:             values
63:             (#nYakUserID#, #nYakaloID#, 'Yakalo Solutions Administrator', 0, 0, '#nYakaloID#', 0)
64:         </cfquery>
65:
66:
67:         <cfquery name="qryPortal" datasource="#ap_dataSource#">
68:             select portals.portalID, portals.name
69:             from portals
70:         </cfquery>
71:         <cfloop query="qryPortal">
72:             <cfquery name="qryInsert" datasource="#ap_dataSource#">
73:                 insert into securityAccess
74:                 (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID, portalID)
75:                 values
76:                 (#qryPortal.portalID#, #nPortalID#, '#qryPortal.name#', #nYakUserID#, #nYakaloID#,
77:                 '#nYakaloID#.#nPortalID#.#qryPortal.portalID#', 0, #qryPortal.portalID#)
78:             </cfquery>
79:         </cfloop>
80:
81:         <!-- Master Distributors
82:             Parents are portals
83:         -->
84:         <cfquery name="qryDist" datasource="#ap_dataSource#">
85:             select distributors.distributorID, distributors.name, distributors.portalID
86:             from distributors
87:             where distributors.parentID = 0
88:         </cfquery>
89:
90:         <cfloop query="qryDist">
91:             <cfquery name="qryFindParent" datasource="#ap_dataSource#">
92:                 select * from securityAccess
93:                 where securityAccess.entityID = #qryDist.portalID#
94:                 and securityAccess.entityType = #nPortalID#
95:             </cfquery>
96:
97:             <cfquery name="qryInsert" datasource="#ap_dataSource#">

```

```

98: insert into securityAccess
99: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
100: values
101: (#qryDist.distributorID#, #nMastDistID#, 'qryDist.name', #qryDist.portalID#, #qryFindParent.entityType#,
102: #qryFindParent.hierarchyID#, #nMastDistID#, #qryDist.distributorID#, #qryDist.distributorID#)
103: </cfquery>
104: </cfloop>
105:
106: <!-- Distributors
107: Patent: are Master Distributors
108: -->
109:
110: <cfquery name="qryDist" datasource="#ap_dataSource#">
111: select distributors.distributorID, distributors.name, parentID from distributors
112: where distributors.parentID > 0
113: </cfquery>
114:
115: <cfloop query="qryDist">
116: <cfquery name="qryFindParent" datasource="#ap_dataSource#">
117: select * from securityAccess
118: where securityAccess.entityID = #qryDist.parentID#
119: and securityAccess.entityType = #nMastDistID#
120: </cfquery>
121:
122: <cfquery name="qryInsert" datasource="#ap_dataSource#">
123: insert into securityAccess
124: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
125: values
126: (#qryDist.distributorID#, #nDistID#, 'qryDist.name', #qryDist.parentID#, #qryFindParent.entityType#,
127: #qryFindParent.hierarchyID#, #nDistID#, #qryDist.distributorID#, #qryDist.distributorID#)
128: </cfquery>
129: </cfloop>
130:
131: <!-- agencies -->
132: <cfquery name="qryAgency" datasource="#ap_dataSource#">
133: select agency.agency_id, agency.name, agency.distributorID from agency
134: where agency.parentAgency = 0 and agency.distributorid > 0
135: </cfquery>
136:
137: <cfloop query="qryAgency">
138: <cfquery name="qryFindParent" datasource="#ap_dataSource#">
139: select * from securityAccess
140: where securityAccess.entityID = #qryAgency.distributorID#
141: and (securityAccess.entityType = #nMastDistID# or securityAccess.entityType=#nDistID#)
142: </cfquery>
143:
144: <cfquery name="qryInsert" datasource="#ap_dataSource#">

```



```

145: insert into securityAccess
146: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
147: values
148: (#qryAgency.agency_id#, #nMastagency_id#, 'qryAgency.name#', #qryAgency.distributorID#, #qryFindParent.entityType#,
149: #qryFindParent.hierarchyID#, #nMastagency_id#, #qryAgency.agency_id#, #qryAgency.distributorID#)
150: </cfquery>
151: </cfloop>
152:
153: <cfquery name="qryAgency" datasource="#ap_dataSource#">
154: select agency.agency_id, agency.name, agency.distributorID, agency.parentAgency
155: from agency
156: where agency.parentAgency > 0 and distributorID > 0
157: </cfquery>
158:
159: <cfloop query="qryAgency">
160: <cfquery name="qryFindParent" datasource="#ap_dataSource#">
161: select * from securityAccess
162: where securityAccess.entityID = #qryAgency.parentAgency#
163: and securityAccess.entityType = #nMastagency_id#
164: </cfquery>
165:
166: <cfquery name="qryInsert" datasource="#ap_dataSource#">
167: insert into securityAccess
168: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
169: values
170: (#qryAgency.agency_id#, #nagency_id#, 'qryAgency.name#', #qryAgency.parentAgency#, #qryFindParent.entityType#,
171: #qryFindParent.hierarchyID#, #nagency_id#, #qryAgency.agency_id#, #qryAgency.distributorID#)
172: </cfquery>
173: </cfloop>
174:
175: <cfquery name="qryAgency" datasource="#ap_dataSource#">
176: select agency.agency_id, agency.name, agency.distributorID, agency.parentAgency
177: from agency
178: where agency.parentAgency = 0 and agency.distributorID = 0
179: </cfquery>
180:
181: <cfloop query="qryAgency">
182: <cfquery name="qryFindParent" datasource="#ap_dataSource#">
183: select * from securityAccess
184: where securityAccess.entityID = #nuserId#
185: and securityAccess.entityType = #nkaloid#
186: </cfquery>
187:
188: <cfquery name="qryInsert" datasource="#ap_dataSource#">
189: insert into securityAccess
190: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
191: values
192: (#qryAgency.agency_id#, #nagency_id#, 'qryAgency.name#', #qryFindParent.entityID#, #nkaloid#,

```

```

192: '#qryFindParent.hierarchyID#. #nagency_id#. #qryAgency.agent_id#', #qryAgency.distributorID#)
193: </cfquery>
194: </cfloop>
195:
196: <cfquery name="qryAgency" datasource="#ap_datasource#">
197:   select agency.agent_id, agency.name, agency.distributorID, agency.parentAgency
198:   from agency
199:   where agency.parentAgency > 0 and agency.distributorID = 0
200: </cfquery>
201:
202: <cfloop query="qryAgency">
203:   <cfquery name="qryFindParent" datasource="#ap_datasource#">
204:     select * from securityAccess
205:     where securityAccess.entityID = #qryAgency.parentAgency#
206:     and securityAccess.entityType = #nMastagency_id#
207:   </cfquery>
208:
209:   <cfquery name="qryInsert" datasource="#ap_datasource#">
210:     insert into securityAccess
211:     (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
212:     values
213:     (#qryAgency.agent_id#, #nagency_id#, '#qryAgency.name#', #qryAgency.parentAgency#, #qryFindParent.entityType#,
214:     '#qryFindParent.hierarchyID#. #nagency_id#. #qryAgency.agent_id#', #qryAgency.distributorID#)
215:   </cfquery>
216: </cfloop>
217:
218: <!-- Agents -->
219: <cfquery name="qryAgents" datasource="#ap_datasource#">
220:   select agents.agent_id, agents.firstname + ' ' + agents.lastname as name, agents.agency_id, agents.distributorID
221:   from agents
222:   where agency_id > 0
223: </cfquery>
224:
225: <cfloop query="qryAgents">
226:   <cfquery name="qryFindParent" datasource="#ap_datasource#">
227:     select * from securityAccess
228:     where securityAccess.entityID = #qryAgents.agency_id#
229:     and (securityAccess.entityType = #nMastagency_id# or securityAccess.entityType=#nagency_id#)
230:   </cfquery>
231:
232:   <cfif qryFindParent.recordCount gt 0>
233:     <cfquery name="qryInsert" datasource="#ap_datasource#">
234:       insert into securityAccess
235:       (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
236:       values
237:       (#qryAgents.agent_id#, #nagent_id#, '#qryAgents.name#', #qryAgents.agency_id#, #qryFindParent.entityType#,
       '#qryFindParent.hierarchyID#. #nagent_id#. #qryAgents.agent_id#', #qryAgents.distributorID#)

```

```
238: </cfquery>
239: <cfelse>
240: <cfquery name="qryFindParent" dataSource="#ap_dataSource#">
241:   select * from securityAccess
242:   where securityAccess.entityID = #nYakUserID#
243:   and securityAccess.entityType = #nYakaloID#
244: </cfquery>
245:
246: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
247:   insert into securityAccess
248:     (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
249:     values
250:     (#qryAgents.agent_id#, #nagent_id#, 'qryAgents.name', #qryFindParent.entityID#, #nYakaloID#,
251:      #qryFindParent.hierarchyID#, #nagent_id#, #qryAgents.agent_id#, #qryAgents.distributorID#)
252: </cfquery>
253: </cfif>
254: </cfloop>
255:
256: <cfquery name="qryAgents" dataSource="#ap_dataSource#">
257:   select agents.agent_id, agents.firstname + ' ' + agents.lastname as name, agents.agency_id, agents.distributorID
258:   from agents
259:   where agents.agency_id = 0
260:   and agents.distributorID > 0
261: </cfquery>
262:
263: <cfloop query="qryAgents">
264:   <cfquery name="qryFindParent" dataSource="#ap_dataSource#">
265:     select * from securityAccess
266:     where securityAccess.entityID = #qryAgents.distributorid#
267:     and (securityAccess.entityType = #nMastDistID# or securityAccess.entityType=#nDistID#)
268:   </cfquery>
269:
270:   <cfquery name="qryInsert" dataSource="#ap_dataSource#">
271:     insert into securityAccess
272:       (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
273:       values
274:       (#qryAgents.agent_id#, #nagent_id#, 'qryAgents.name', #qryAgents.distributorID#, #qryFindParent.entityType#,
275:        #qryFindParent.hierarchyID#, #nagent_id#, #qryAgents.agent_id#, #qryAgents.distributorID#)
276:   </cfquery>
277: </cfloop>
```

```

1:  <!-- Create style sheet -->
2:
3:  <cfquery name="qryGetPath" dataSource="#ap_dataSource#">
4:    select dataPath
5:    from distributors
6:    where distributors.distributorID = #form.distributorID#
7:  </cfquery>
8:
9:  <cfif qryGetPath.recordCount is 1>
10:    <cfset cPath = qryGetPath.dataPath>
11:    <cfset cFile = cPath & "clientStyle.css">
12:
13:    <cfset cContent = "">
14:
15:    <cfset cContent = cContent & "a { font-family: verdana, arial, helvetica,sans-serif; color:#form.edtNavBGColor#;
font-size: 9pt; }">
16:    <cfset cContent = cContent & "a.nav { font-family: arial, verdana, helvetica,sans-serif; color:#form.edtNavTextColor#;
font-size: 9pt; font-weight: bold; }">
17:    <cfset cContent = cContent & "a.menu { font-family: arial, verdana, helvetica,sans-serif; color:#form.edtMenuTextColor#;
font-size: 9pt; font-weight: bold; }">
18:    <cfset cContent = cContent & "a.nav:hover { text-decoration: underline; font-family: arial, verdana, helvetica,sans-serif;
color:#ffff00; font-size: 9pt; font-weight: bold; }">
19:    <cfset cContent = cContent & ".heading { font-family: verdana, arial, helvetica,sans-serif; font-size: 10pt; font-weight:
bold; color: #ffffff; }">
20:    <cfset cContent = cContent & "a:hover { text-decoration: underline; font-family: verdana, arial, helvetica,sans-serif;
color:#990000; }">
21:    <cfset cContent = cContent & "p, body, th, ul, td { font-family: verdana, arial, helvetica,sans-serif; font-size: 9pt; }">
22:    <!-- menu background color -->
23:    <cfset cContent = cContent & ".click_heading { font-family: verdana, arial, helvetica,sans-serif; font-size: 10pt;
font-weight: bold; color: #form.edtMenuTextColor#; }">
24:
25:    <cfset cContent = cContent & ".td { font-family: verdana, arial, helvetica,sans-serif; font-size: 9pt; }">
26:
27:    <cffile action="write"
28:      file="#cFile#"
29:      output="#cContent#"
30:    >
31:  </cfif>

```

```
1:  <CFHEADER NAME="cache-control" VALUE="no-cache, no-store, must-revalidate">
2:  <!-- On HTTP version 1.1 servers, stops the browser and/or
3:  proxy from caching the document. Also forces form elements to be
4:  re-examined. -->
5:  <CFHEADER NAME="Pragma" VALUE="no-cache">
6:  <!-- On HTTP version 1.0 servers, stops the browser and/or
7:  proxy from caching the document. Does not work on 1.1
8:  servers -->
9:  <CFHEADER NAME="Expires" VALUE="#Now()#">
```

```

1:      <cfoutput>
2:
3:
4:      <cfquery name="qryGetDists" dataSource="#ap_dataSource#">
5:      select distributors.distributorID, distributors.name as distName
6:      from distributors
7:      join securityAccess on
8:      (securityAccess.entityType = #ap_securityMastDist# or securityAccess.entityType = #ap_securityDist#)
9:      and securityAccess.entityID = distributors.distributorID
10:     and securityAccess.hierarchyID like '#client.hierarchyID#%'
11:     order by distName
12:   </cfquery>
13:
14:   <cfif qryGetDists.recordCount is 0>
15:     <cfset client.userName = "There are no distributors in which to create a property.">
16:     <cflocation url="propertyAdm.cfm" addToken="no">
17:   </cfif>
18:
19:   <cfif qryGetDists.recordCount is 1>
20:     <cfset client.lookupDistID = qryGetDists.distributorID>
21:     <cfset client.lookupID = nPropID>
22:     <cflocation url="propertyMaint.cfm" addToken="no">
23:   </cfif>
24:
25:   <form action="propertyUpdate.cfm" method="post">
26:     <input type="hidden" name="propertyID" value="#nPropID#">
27:
28:     <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
29:       <tr bgcolor="cccc99">
30:         <td>
31:           <span class="h2"><b>Property Maintenance</b></span>
32:         </td>
33:       </tr>
34:
35:       <tr bgcolor="#eeeeee"><td>
36:         Some property information is dependent on a specific distributor's information.<br>
37:         <br>
38:         Please select the distributor for this new property.
39:       </td></tr>
40:
41:       <tr bgcolor="#eeeeee">
42:         <td align="center">
43:           Distributor:
44:           <select name="edtDistributorID">
45:             <cfloop query="qryGetDists">
46:               <option value="#qryGetDists.distributorID#">#qryGetDists.distName#
47:             </cfloop>
48:           </select>
49:         </td>

```

```
50: </tr>
51:
52: <tr bgcolor="#ffffff">
53: <td>
54: <input type="submit" name="btnSelectDist" value="Select Distributor">
55: <input type="submit" name="btnCancelDist" value="Cancel">
56: </td>
57: </tr>
58: </table>
59: </form>
60:
61: </cfoutput>
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <html>
4: <head>
5:   <title><cfoutput>Realty Objects - #ap_distributorName# - Property View</cfoutput></title>
6:   <link rel="stylesheet" href="clientStyle.css" type="text/css">
7: </head>
8:
9: <cfinclude template="#ap_commonFiles#propertyView.cfm">
10:
```



```

1: <cfparam name="client.userMessage" defaultMessage="default#">
2: <cfparam name="client.imageType" default="-1">
3:
4: <cfinclude template="javaValidate.cfm">
5:
6: <script language="JavaScript">
7: <!--
8:   function validateDetail(testform) {
9:     var results = "";
10:    var lResult = true;
11:
12:    if ((removeSpaces(testform.edtSortOrder.value) != "") && (!isNumber(testform.edtSortOrder.value))) {
13:      results = results + " * " + testform.edtSortOrder.value + " is not a valid numeric sort order value.\r";
14:      lResult = false;
15:    }
16:
17:    if (!lResult) {
18:      window.alert(results);
19:    }
20:
21:    return lResult;
22:  }
23: <!-->
24: </script>
25:
26: <cfquery name="qryDetail" dataSource="#ap_dataSource#">
27:   select propertyImages.*, imageTypes.description as imageName
28:   from propertyImages
29:   left outer join imageTypes on imageTypes.imageType = propertyImages.imageType
30:   where propertyImages.propertyID = #client.lookupID#
31:   order by propertyImages.sortOrder
32: </cfquery>
33:
34: <cfquery name="qryEdit" dataSource="#ap_dataSource#">
35:   select propertyImages.*, imageTypes.description as imageName
36:   from propertyImages
37:   left outer join imageTypes on imageTypes.imageType = propertyImages.imageType
38:   where propertyImages.propertyID = #client.lookupID#
39:   and propertyImages.propertyImageID = #client.detailID#
40: </cfquery>
41:
42: <cfquery name="qryImageTypes" dataSource="#ap_dataSource#">
43:   select imageType, description, isFormField, isApplet, isURL
44:   from imageTypes
45:   order by description
46: </cfquery>
47:
48: <!-- Set default values -->
49: <cfif qryEdit.recordCount is 0> <!-- New record -->

```

```

50: <cfif isDefined("client.old_sortOrder")><table border="1">
51:   <cfset nSortOrder = client.old_sortOrder>
52:   <cfelse>
53:     <cfset nSortOrder = "1">
54:   </cfif>
55:
56:   <cfquery name="qryDefault" dataSource="#ap_dataSource#">
57:     select imageUrl from imageTypes
58:     where imageTypes.description = 'Standard Photo'
59:   </cfquery>
60:   <cfif client.imageType gt -1>
61:     <cfset nImageType = client.imageType>
62:     <cfelseif qryDefault.recordCount gt 0>
63:       <cfset nImageType = qryDefault.imageType>
64:     <cfelse>
65:       <cfset nImageType = 0>
66:     </cfif>
67:
68:   <cfelse> <!-- Existing record -->
69:     <cfif isDefined("client.old_sortOrder")>
70:       <cfset nSortOrder = client.old_sortOrder>
71:     <cfelse>
72:       <cfset nSortOrder = qryEdit.sortOrder>
73:     </cfif>
74:
75:     <cfif client.imageType gt -1>
76:       <cfset nImageType = client.imageType>
77:     <cfelse>
78:       <cfset nImageType = qryEdit.imageType>
79:     </cfif>
80:   </cfif>
81:
82:   <cfquery name="qryImageInfo" dataSource="#ap_dataSource#">
83:     select formTitle, isFormField, isApplet, isURL
84:     from imageTypes
85:     where imageTypes.imageType = #nImageType#
86:   </cfquery>
87:
88:   <cfoutput>
89:
90:   <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
91:   <tr bgcolor="cccc99"><td colspan="5"><b>Property Rooms</b></span></td></tr>
92:   </td></tr>
93:
94:   <cfif client.lookupID gt 0>
95:     <tr bgcolor="##cccc99">
96:       <td colspan="5">
97:         <a href="propertyMaint.cfm?displayPage=propInfo">Property Info</a>
98:         <b>| <del>nbsp</del></a> <a href="propertyMaint.cfm?displayPage=propRooms">Rooms</a>

```

```

99:         </td>
100:     </tr>
101: </cfif>
102:
103: <CFIF client.userMessage is not "">
104:     <tr bgcolor="eeeeee">
105:         <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td>
106:     </tr>
107:     <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
108: </CFIF>
109: <cfset client.userMessage = "">
110: </table>
111: </cfoutput>
112:
113: <form action="propertyUpdate.cfm" method="post" enctype="multipart/form-data" onsubmit="return validateDetail(this)">
114:     <cfoutput>
115:         <input type="hidden" name="distributorID" value="#nDistID#">
116:         <input type="hidden" name="propertyID" value="#client.lookupID#">
117:         <input type="hidden" name="propertyImageID" value="#client.detailID#">
118:         <input type="hidden" name="originalImage" value="#qryEdit.image#">
119:         <input type="hidden" name="originalUserImage" value="#qryEdit.userName#">
120:     </cfoutput>
121:
122:     <cfif qryDetail.recordCount is 0>
123:         <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
124:             <tr><td colspan="4"><i><b>There are no images for this property.</b></i></td></tr>
125:             <tr><td colspan="4">&nbsp;</td></tr>
126:         </table>
127:     </cfelse>
128:     <table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
129:         <tr valign="top" bgcolor="#cccccc">
130:             <td><b>Image Type</b></td>
131:             <td><b>Image Name</b></td>
132:             <td><b>Order</b></td>
133:             <td>&nbsp;</td>
134:         </tr>
135:         <cfoutput query="qryDetail">
136:             <tr valign="top" bgcolor=""><cfif qryDetail.propertyImageID is client.detailID>#ffcc<cfelse>#eeeeee</cfif>">
137:                 <td>
138:                     <cfif trim(qryDetail.imageName) is "">&nbsp;</cfif>#qryDetail.imageName#
139:                 </td>
140:                 <td>
141:                     <cfif trim(qryDetail.userName) is "">&nbsp;</cfif>#qryDetail.userName#
142:                 </td>
143:                 <td>#qryDetail.sortOrder#</td>
144:                 <td align="center">
145:                     <input type="image" name="editImage#qryDetail.propertyImageID#" src="#ap_commonImages#edit.gif" alt="Edit"
border="0">
146:                 <hr>

```

```

147:         <input type="image" name="deleteImage#qryDetailImageID#" src="#ap_commonImages#delete.gif" alt="Delete"
border="0">
148:         </td>
149:     </tr>
150: </cfoutput>
151: </table>
152: </cfif>
153: <cfoutput>
154: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
155: <tr><td colspan="3"><b><br></td></tr>
156: <cfif client.detailID is -1>
157:   <tr bgcolor="#cccccc"><td colspan="3"><b>Add an image</b></td></tr>
158: <cfelse>
159:   <tr bgcolor="#cccccc"><td colspan="3"><b>Edit this image</b></td></tr>
160: </cfif>
161: <tr valign="top" bgcolor="#eeeeee">
162:   <td width="30%"><b>Image Type</b></td>
163:   <td width="50%"><b>#qryImageInfo.formatTitle#</b></td>
164:   <td width="10%"><b>Order</b></td>
165: </tr>
166: <tr valign="top" bgcolor="#eeeeee">
167:   <td width="30%">
168:     <select name="editImageType">
169:       <cfloop query="qryImageTypes">
170:         <option value="#qryImageTypes.imageType#"><cfif qryImageTypes.imageType is nImageType>
selected</cfif><#qryImageTypes.description#
        </cfloop>
        </select>
171:       <cfif qryImageTypes.recordCount gt 1>
172:         <input type="submit" name="btnImageType" value="Change">
173:       </cfif>
174:     </td>
175:   <td width="50%">
176:     <cfif qryImageInfo.isFormField is "Y">
177:       <input type="File" name="editImage" size="45">
178:       <cfif qryEdit.userName is not "">
179:         <br>
180:         <cfset cFilename = getFileFromPath(qryEdit.userName)>
181:         <cfset cFilename = replace(cFilename, "#qryEdit.propertyID#", "")>
182:         <i>Currently: #cFilename#</i><br>
183:         <input type="checkbox" name="chkDeleteImage"> Delete Image
184:       </cfif>
185:     </td>
186:   <td width="10%">
187:     <cfif qryImageInfo.isApplet is "Y">
188:       <input type="text" name="editImage" value="#qryDetail.image#" size="45" maxlength="120">
189:     <cfelseif qryImageInfo.isURL is "Y">
190:       <input type="text" name="editImage" value="#qryDetail.image#" size="45" maxlength="120">
191:     <cfelse> <!-- The default if a new entry -->
192:       <input type="File" name="editImage" size="45">
193:

```

```
194:         </cfif>
195:     </td>
196:     <td width="10%"><input type="text" name="editSortOrder" value="#nSortOrder#" size="2"></td>
197: </tr>
198:
199: <tr bgcolor="eeeeee"><td colspan="3">&nbsp;</td></tr>
200:
201: <tr bgcolor="eeeeee">
202:     <td colspan="3">
203:         <cfif qryEdit.recordCount is 0>
204:             <input type="submit" name="btnUpdateImages" value="Add Image">
205:             <input type="reset" value="Reset Info">
206:         <cfelse>
207:             <input type="submit" name="btnUpdateImages" value="Update Image">
208:             <input type="reset" value="Reset Info">
209:             <input type="submit" name="btnCancelImages" value="Cancel">
210:         </cfif>
211:     </td>
212: </tr>
213: </table>
214: </cfoutput>
215: </form>
216:
```

```

1: <cfinclude template="javaValidate.cfm">
2:
3: <script language="JavaScript">
4: </--
5:
6: function validate(testform) {
7:     var results = "";
8:     var lResult = true;
9:
10:    if (removeSpaces(testform.edtName.value) == "") {
11:        results = results + "** Please enter the property's name.\r";
12:        lResult = false;
13:    }
14:    if (removeSpaces(testform.edtAddress.value) == "") {
15:        results = results + "** Please enter the property's address.\r";
16:        lResult = false;
17:    }
18:    if (removeSpaces(testform.edtCity.value) == "") {
19:        results = results + "** Please enter the property's city.\r";
20:        lResult = false;
21:    }
22:    if (removeSpaces(testform.edtState.value) == "") {
23:        results = results + "** Please enter the property's state.\r";
24:        lResult = false;
25:    }
26:    if (removeSpaces(testform.edtZipcode.value) == "") {
27:        results = results + "** Please enter the property's zipcode.\r";
28:        lResult = false;
29:    }
30:    if (removeSpaces(testform.edtBedrooms.value) == "") {
31:        results = results + "** Please enter the number of bedrooms.\r";
32:        lResult = false;
33:    }
34:    if (removeSpaces(testform.edtBathrooms.value) == "") {
35:        results = results + "** Please enter the number of bathrooms.\r";
36:        lResult = false;
37:    }
38:
39:    if (!isValidDate(testform.edtBeginDate.value)) {
40:        results = results + "** " + testform.edtBeginDate.value + " is not valid. Please enter a valid beginning date.\r";
41:        lResult = false;
42:    }
43:
44:    if (!isValidDate(testform.edtEndDate.value)) {
45:        results = results + "** " + testform.edtEndDate.value + " is not valid. Please enter a valid ending date.\r";
46:        lResult = false;
47:    }
48:
49:    if (removeSpaces(testform.edtShortDesc.value) == "") {

```

```

50: results = results + "** Please enter a short description for this property.\r";
51: lResult = false;
52: }
53:
54: if (testform.edtAgentID.value == "-1|-1" || removeSpaces(testform.edtAgentID.value) == "") {
55: results = results + "** Please select the property's agent.\r";
56: lResult = false;
57: }
58:
59: var cID = removeSpaces(testform.edtAgentID.value);
60: if (cID.substr(0,cID.length-2,cID.length) == "|0" || removeSpaces(testform.edtAgentID.value) == "") {
61: results = results + "** You must select an agent, not an agency.\r";
62: lResult = false;
63: }
64:
65:
66: if (testform.edtDistributorID.value == "-1" || removeSpaces(testform.edtDistributorID.value) == "") {
67: results = results + "** Please select the property's distributor.\r";
68: lResult = false;
69: }
70: if (testform.edtPortalID.value == "-1" || removeSpaces(testform.edtPortalID.value) == "") {
71: results = results + "** Please select the property's portal.\r";
72: lResult = false;
73: }
74:
75: if (!lResult) {
76: window.alert(results);
77: }
78: return lResult;
79: }
80: -->
81: </script>
82:
83: <cfset client.detailID = -1>
84:
85: <cfoutput>
86:
87: <cfquery name="qryCommunities" dataSource="#ap_dataSource#">
88: select communities.communityID, communities.name
89: from communities
90: where communities.distributorID = #nDistID#
91: order by communities.name
92: </cfquery>
93:
94: <cfquery name="qrySpecialtyPages" dataSource="#ap_dataSource#">
95: select specialtyPages.specialtyPageID, specialtyPages.name
96: from specialtyPages
97: where specialtyPages.distributorID = #nDistID#
98: order by specialtyPages.name

```

```

99: </cfquery>
100:
101: <cfquery name="qryPropSpecial" dataSource="#ap_dataSource#">
102:   select propSpecialty.specialtyPageID
103:   from propSpecialty
104:   where propSpecialty.propertyID = #client.lookupID#
105: </cfquery>
106: <cfset lstSpecialtyPages = valueList(qryPropSpecial.specialtyPageID)>
107:
108: <cfquery name="qryHomeTypes" dataSource="#ap_dataSource#">
109:   select homeTypeID, homeType
110:   from homeTypeValues
111:   where homeTypeValues.distributorID = #nDistID#
112:   order by homeType
113: </cfquery>
114: <cfquery name="qryLotTypes" dataSource="#ap_dataSource#">
115:   select lotTypeID, lotType
116:   from lotTypeValues
117:   where lotTypeValues.distributorID = #nDistID#
118:   order by lotType
119: </cfquery>
120: <cfquery name="qryPropertyTypes" dataSource="#ap_dataSource#">
121:   select propertyTypeID, propertyType
122:   from propertyTypeValues
123:   where propertyTypeValues.distributorID = #nDistID#
124:   order by propertyType
125: </cfquery>
126: <cfquery name="qryStatus" dataSource="#ap_dataSource#">
127:   select statusID, status
128:   from statusValues
129:   where statusValues.distributorID = #nDistID#
130:   order by status
131: </cfquery>
132:
133: <cfquery name="qryDist" dataSource="#ap_dataSource#">
134:   select distributors.name as distName, distributors.portalID, portals.name as portalName
135:   from distributors
136:   join portals on portals.portalID = distributors.portalID
137:   where distributors.distributorID = #nDistID#
138: </cfquery>
139:
140: <form action="propertyUpdate.cfm" method="post" onsubmit="return validate(this)">
141:   <input type="hidden" name="propertyID" value="#nPropID#">
142:   <input type="hidden" name="edtDistributorID" value="#nDistID#">
143:   <input type="hidden" name="edtPortalID" value="#qryDist.portalID#">
144:
145:   <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
146:     <tr bgcolor="cccc99"><td colspan="5"><span class="h2"><b>Property Maintenance</b></span>
147:       <cfif client.lookupID is -1>

```



```

148:      <nbsp> (Create a new Property)
149:    </cfif>
150:  </td></tr>
151:
152:  <cfif client.lookupID gt 0>
153:    <tr bgcolor="#cccc99">
154:      <td colspan="5">
155:        <a href="propertyMaint.cfm?displayPage=propImages">Property Images</a>
156:      <nbsp> | <nbsp> <a href="propertyMaint.cfm?displayPage=propRooms">Rooms</a>
157:    </td>
158:  </tr>
159:  </cfif>
160:
161:  <CFIF client.userMessage is not "">
162:    <tr bgcolor="eeeeee">
163:      <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td>
164:    </tr>
165:    <tr bgcolor="eeeeee"><td colspan="5"><td></td></tr>
166:  </CFIF>
167:  <cfset client.userMessage = "">
168:
169:  <tr bgcolor="#eeeeee">
170:    <td width="15%"><b>Property Title:</b></td>
171:    <td width="34%"><input type="text" name="propertyName" value="#qryFindProperty.Name#" size="30"></td>
172:    <td width="2%"><td></td>
173:    <td width="15%"><b>Status:</b></td>
174:    <td width="34%">
175:      <select name="editStatus">
176:        <option value="0"><cfif client.lookupID is -1 or qryFindProperty.status le 0> selected</cfif>>Not Assigned
177:        <cfloop query="qryStatus">
178:          <option value="#qryStatus.statusID#" <cfif qryFindProperty.status is qryStatus.statusID>
            selected</cfif>>#qryStatus.status#
          </cfloop>
179:        </select>
180:      </td>
181:    </tr>
182:
183:  <tr bgcolor="#eeeeee">
184:    <td width="15%"><b>Address:</b></td>
185:    <td width="34%"><input type="text" name="editAddress" value="#qryFindProperty.address#" size="30"></td>
186:    <td width="2%"><td></td>
187:    <td width="15%"><b>City:</b></td>
188:    <td width="34%"><input type="text" name="editCity" value="#qryFindProperty.city#" size="30"></td>
189:  </tr>
190:  <tr bgcolor="eeeeee">
191:    <td width="15%"><b>State:</b></td>
192:    <td width="34%"><input type="text" name="editState" value="#qryFindProperty.State#" size="2"></td>
193:    <td width="2%"><td></td>
194:    <td width="15%"><b>Zipcode:</b></td>
195:    <td width="34%"><input type="text" name="editZipcode" value="#qryFindProperty.Zipcode#" size="10"></td>

```

```

196: <td width="34%"><input type="text" name="#edtZipCode#" value="#qryFindProperty.zip#" size="10"></td>
197: </tr>
198: <tr bgcolor="#eeeeee">
199: <td width="15%">County:</td>
200: <td width="34%"><input type="text" name="edtCounty" value="#qryFindProperty.county#"></td>
201: <td width="2%">&nbsp;</td>
202: <td width="15%">County:</td>
203: <td width="34%"><input type="text" name="edtCountry" value="#qryFindProperty.centry_id#"></td>
204: </tr>
205: <tr bgcolor="#eeeeee">
206: <td width="15%">Property Type:</td>
207: <td width="34%">
208: <select name="edtPropertyType">
209: <option value="0"><cfif client.lookupID is -1 or qryFindProperty.prop_type le 0> selected</cfif>>Not Assigned
210: <cfloop query="qryPropertyTypes">
211: <option value="#qryPropertyTypes.propertyTypeID#" <cfif qryFindProperty.prop_type is
qryPropertyTypes.propertyTypeID> selected</cfif>>#qryPropertyTypes.propertyType#
212: </cfloop>
213: </select>
214: </td>
215: <td width="2%">&nbsp;</td>
216: <td width="15%">MLS Number:</td>
217: <td width="34%"><input type="text" name="edtMLS" value="#qryFindProperty.mls_no#"></td>
218: </tr>
219: <tr bgcolor="#eeeeee">
220: <td width="15%"><b>Bedrooms:</b></td>
221: <td width="34%"><input type="text" name="edtBedrooms" value="#qryFindProperty.bedroom#" size="3"></td>
222: <td width="2%">&nbsp;</td>
223: <td width="15%"><b>Bathrooms:</b></td>
224: <td width="34%"><input type="text" name="edtBathrooms" value="#qryFindProperty.bath#" size="3"></td>
225: </tr>
226: <tr bgcolor="#eeeeee">
227: <td width="15%"><b>Begin Date:</b></td>
228: <td width="34%"><input type="text" name="edtBeginDate" value="#dateFormat(qryFindProperty.beginDate, "mm/dd/yyyy")#"
size="10"><i>(MM/DD/YY or MM/DD/YYYY)</i></td>
229: <td width="2%">&nbsp;</td>
230: <td width="15%"><b>End Date:</b></td>
231: <td width="34%"><input type="text" name="edtEndDate" value="#dateFormat(qryFindProperty.endDate, "mm/dd/yyyy")#"
size="10"><i>(MM/DD/YY or MM/DD/YYYY)</i></td>
232: </tr>
233: <tr bgcolor="#eeeeee">
234: <td width="15%"><b>Current Price:</b></td>
235: <td width="34%"><input type="text" name="edtPrice" value="#decimalFormat(qryFindProperty.price)#" size="20"></td>
236: <td width="2%">&nbsp;</td>
237: <td width="15%"><b>Sold Price:</b></td>
238: <td width="34%"><input type="text" name="edtSoldPrice" value="#decimalFormat(qryFindProperty.salesPrice)#"
size="20"></td>
239: </tr>
240: <tr bgcolor="#eeeeee">

```



```

286: </tr>
287:
288: <tr bgcolor="#ffffff">
289:   <td width="15%">Community:</td>
290:   <td colspan="4">
291:     <input type="hidden" name="edtCommunities" value="">
292:     <cfif qryCommunities.recordCount gt 0>
293:       <select name="edtCommunities">
294:         <option value="0"> <cfif client.lookupID is -1 or qryFindProperty.communityID le 0> selected</cfif>>Not Assigned
295:         <cfloop query="qryCommunities">
296:           <option value="#qryCommunities.communityID#"> <cfif qryFindProperty.communityID is qryCommunities.communityID>
selected</cfif>>#qryCommunities.name#
297:         </cfloop>
298:       </select>
299:     <cfelse>
300:       <input type="hidden" name="edtCommunities" value="0">
301:       No Communities Defined
302:     </cfif>
303:   </td>
304: </tr>
305:
306: <tr bgcolor="#ffffff">
307:   <td width="15%"><b>Agent:</b></td>
308:   <td width="34%">
309:     <cfif client.currentEntityType lt ap_securityAgent> <!-- Only if not the agent -->
310:     <cfquery name="qryAgents" dataSource="#ap_dataSource#">
311:       select agents.agent_id, agents.agency_id,
312:         agents.lastname + ', ' + agents.firstname as agentName,
313:         agency.agency_id, agency.name as agencyName
314:     from agents
315:     join agency on agency.agency_id = agents.agency_id
316:     where agents.distributorID = #nDiscID#
317:     order by agencyName, agentName
318:   </cfquery>
319:   <select name="edtAgentID">
320:     <option value="-1|-1"> <cfif client.lookupID is -1 or qryFindProperty.agent_id is -1 or
trim(qryFindProperty.agent_id) is ""> selected</cfif>>Not Assigned
321:     <cfset nOldAgency = -1>
322:     <cfloop query="qryAgents">
323:       <cfif nOldAgency is not qryAgents.agency_id>
324:         <option value="#qryAgents.agency_id|0"> <cfif qryAgents.agent_id is qryFindProperty.agent_id and
qryAgents.agency_id is 0> selected</cfif>>#qryAgents.agencyName#
325:         <cfset nOldAgency = qryAgents.agency_id>
326:       </cfif>
327:       <option value="#qryAgents.agency_id#"> <cfif qryAgents.agent_id#"> <cfif qryAgents.agent_id is qryFindProperty.agent_id
and qryAgents.agency_id is qryFindProperty.agency_id> selected</cfif>>#qryAgents.agencyName#
328:     </cfloop>
329:   </select>
330:   <cfelse>

```

```

331: <cfif trim(qryFindProperty.agentName) is "">
332:     Not Assigned
333: </cfelse>
334:     #qryFindProperty.agentName#
335: </cfif>
336: <input type="hidden" name="edtAgentID" value="#qryFindProperty.agent_id#">
337: </cfif>
338: </td>
339: <td colspan="3">&nbsp;</td>
340: </tr>
341:
342: <tr bgcolor="#eeeeee">
343: <td width="15%">Description:</td>
344: <td colspan="4">
345:     <textarea name="edtDesc" rows="5" cols="60" wrap="virtual">#trim(qryFindProperty.dscrptn_l)#</textarea>
346: </td>
347: </tr>
348:
349: <cfif client.currentEntityType lte ap_securityPortal>
350:     <tr bgcolor="#eeeeee">
351: <td width="15%">Portal:</td>
352: <td width="34%">#qryDist.portalName#</td>
353: <td width="2%">&nbsp;</td>
354: <td width="15%">Distributor:</td>
355: <td width="34%">#qryDist.distName#</td>
356: </tr>
357: <cfelseif client.currentEntityType lte ap_securityDist>
358:     <tr bgcolor="#eeeeee">
359: <td width="15%">Distributor:</td>
360: <td colspan="4">#qryDist.distName#</td>
361: </tr>
362: </cfif>
363:
364: <tr bgcolor="#eeeeee">
365: <td colspan="5">
366:     <cfif qryFindProperty.recordCount is 0>
367:         <input type="submit" name="btnUpdate" value="Add Property">
368:         <input type="reset" value="Reset Info">
369:     </cfelse>
370:         <input type="submit" name="btnUpdate" value="Update Property Info">
371:         <input type="reset" value="Reset Info">
372:         <input type="submit" name="btnDelete" value="Delete Property">
373:     </cfif>
374: </td>
375: </tr>
376: </table>
377: </form>
378:
379: </cfoutput>

```

```

1: <cfinclude template="javaValidate.cfm">
2:
3: <script language="JavaScript">
4: </--
5:
6: function validateDetail(testform) {
7:   var results = "";
8:   var lResult = true;
9:
10:  if ((removeSpaces(testform.edtSize.value) != "") && (!isFloat(testform.edtSize.value))) {
11:    results = results + "** Please enter a numeric size.\r";
12:    lResult = false;
13:  }
14:
15:  if ((removeSpaces(testform.edtSortOrder.value) == "") || (!isNumber(testform.edtSortOrder.value))) {
16:    results = results + "** Please enter a numeric sort order.\r";
17:    lResult = false;
18:  }
19:
20:  if (!lResult) {
21:    window.alert(results);
22:  }
23:  return lResult;
24: }
25: -->
26: </script>
27:
28: <cfoutput>
29:
30: <cfquery name="qryDetail" dataSource="#ap_dataSource#">
31:   select rooms.roomDetailID, rooms.roomID, rooms.size, rooms.floor, rooms.sortOrder,
32:     roomValues.room as roomName
33:   from rooms
34:   join roomValues on roomValues.roomID = rooms.roomID
35:   where rooms.propertyID = #propID#
36:   order by rooms.sortOrder
37: </cfquery>
38:
39: <cfquery name="qryRooms" dataSource="#ap_dataSource#">
40:   select roomID, room as roomName
41:   from roomValues
42:   where roomValues.distributorID = #qryFindProperty.distributorID#
43:   and roomValues.agencyID = #qryFindProperty.agency_id#
44:   order by roomName
45: </cfquery>
46:
47: <cfquery name="qryEdit" dataSource="#ap_dataSource#">
48:   select rooms.roomDetailID, rooms.roomID, rooms.size, rooms.floor, rooms.sortOrder,
49:     roomValues.room as roomName

```

```

50: from rooms
51: join roomValues on roomValues.roomID = rooms.roomID
52: where rooms.propertyID = #nPropID#
53: and rooms.roomDetailID = #client.detailID#
54: </cfquery>
55:
56: <cfif qryEdit.recordCount gt 0>
57:   <cfset nSortOrder = qryEdit.sortOrder>
58: <cfelseif qryDetail.recordCount gt 0>
59:   <cfquery name="qryMax" dataSource="#ap_dataSource#">
60:     select max(sortOrder) as maxOrder
61:     from rooms
62:     where rooms.propertyID = #nPropID#
63:   </cfquery>
64:   <cfset nSortOrder = qryMax.maxOrder+1>
65: <cfelse>
66:   <cfset nSortOrder = 1>
67: </cfif>
68:
69: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
70:   <tr bgcolor="cccc99"><td colspan="5"><b>Property Rooms</b></span>
71:   </td></tr>
72:
73:   <cfif client.lookupID gt 0>
74:     <tr bgcolor="##cccc99">
75:       <td colspan="5">
76:         <a href="propertyMaint.cfm?displayPage=propInfo">Property Info</a>
77:         &nbsp;
78:       </td>
79:     </tr>
80:   </cfif>
81:
82:   <CFIF client.userMessage is not "">
83:     <tr bgcolor="eeeeee">
84:       <td colspan="5"><p><font color="red">#client.userMessage#</font></p></td>
85:     </tr>
86:     <tr bgcolor="eeeeee"><td colspan="5">&nbsp;</td></tr>
87:   </CFIF>
88:   <cfset client.userMessage = "">
89: </table>
90:
91: </cfoutput>
92:
93: <form action="propertyUpdate.cfm" method="post" onSubmit="return validateDetail(this)">
94:   <cfoutput>
95:     <input type="hidden" name="propertyID" value="#nPropID#">
96:     <input type="hidden" name="roomDetailID" value="#client.detailID#">
97:   </cfoutput>
98:

```

```

99: <cfif qryDetail.recordCount is 0>
100: <table border="0" cellpadding="1" cellspacing="1" align="center" width="90%">
101: <tr><td colspan="6"><i><b>There are no rooms assigned.</b></i></td></tr>
102: <tr><td colspan="6"><b><nbsp;</b></td></tr>
103: </table>
104: <cfelse>
105: <table border="1" cellpadding="1" cellspacing="0" align="center" width="90%">
106: <tr valign="top" bgcolor="#cccccc">
107: <td><b>Room</b></td>
108: <td><b>Size</b></td>
109: <td><b>Floor</b></td>
110: <td><b>Sort Order</b></td>
111: <td><b><nbsp;</b></td>
112: <td><b><nbsp;</b></td>
113: </tr>
114: <cfoutput query="qryDetail">
115: <tr valign="top" bgcolor=""><cfif qryDetail.roomDetailID is client.detailID>#ffffcc<cfelse>#eeeeee</cfif>">
116: <td>
117: <cfif trim(qryDetail.roomName) is ""><b><nbsp;</b></cfif>#qryDetail.roomName#
118: </td>
119: <td>
120: <cfif trim(qryDetail.size) is ""><b><nbsp;</b></cfif>#qryDetail.size#
121: </td>
122: <td>
123: <cfif trim(qryDetail.floor) is ""><b><nbsp;</b></cfif>#qryDetail.floor#
124: </td>
125: <td>
126: <cfif trim(qryDetail.sortOrder) is ""><b><nbsp;</b></cfif>#qryDetail.sortOrder#
127: </td>
128: <td align="center">
129: <input type="image" name="editroom#qryDetail.roomDetailID#" src="#ap_commonImages#edit.gif" alt="Edit"
border="0">
</td>
130: <td align="center">
131: <input type="image" name="deleteroom#qryDetail.roomDetailID#" src="#ap_commonImages#delete.gif" alt="Delete"
border="0">
</td>
132: </tr>
133: </cfoutput>
134: </table>
135: </cfoutput>
136: </table>
137: </cfif>
138:
139: <cfif qryRooms.recordCount gt 0>
140: <cfoutput>
141: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
142: <tr><td colspan="4"><b><nbsp;</b></td></tr>
143: <cfif client.detailID is -1>
144: <tr bgcolor="#cccccc"><td colspan="4"><b>Add a room</b></td></tr>
145: <cfelse>

```



```

146: <tr bgcolor="#cccccc"><td colspan="4"><b>Edit this room</b></td></tr>
147: </cfif>
148: <tr valign="top" bgcolor="#eeeeee">
149: <td><b>Room</b></td>
150: <td><b>Size</b></td>
151: <td><b>Floor</b></td>
152: <td align="center"><b>Sort Order</b></td>
153: </tr>
154: <tr valign="top" bgcolor="#eeeeee">
155: <td>
156: <select name="editRoom">
157: <cfloop query="qryRooms">
158: <option value="#qryRooms.roomID#"><cfif qryEdit.roomID is qryRooms.roomID> selected</cfif>>#qryRooms.roomName#
159: </cfloop>
160: </select>
161: </td>
162: <td><input type="text" name="editSize" value="#qryEdit.size#"></td>
163: <td><input type="text" name="editFloor" value="#qryEdit.floor#" size="15" maxlength="20"></td>
164: <td align="center"><input type="text" name="editSortOrder" value="#nSortOrder#" size="2" maxlength="2"></td>
165: </tr>
166: <tr bgcolor="eeeeee">
167: <td colspan="5">
168: <cfif qryEdit.recordCount is 0>
169: <input type="submit" name="btnUpdateRoom" value="Add Room">
170: <input type="reset" value="Reset Info">
171: </cfif>
172: <input type="submit" name="btnUpdateRoom" value="Update Room">
173: <input type="reset" value="Reset Info">
174: <input type="submit" name="btnCancelRoom" value="Cancel">
175: </cfif>
176: </td>
177: </tr>
178: </table>
179: </cfoutput>
180: </cfelse>
181: <table border="0" cellpadding="1" cellspacing="0" align="center" width="90%">
182: <tr>
183: <td colspan="5" align="center">
184: <i>There are no rooms defined. Use the 'Rooms' option under the Agency menu to define rooms.</i>
185: </td>
186: </tr>
187: </table>
188: </cfif>
189: </form>
190:
191:

```

```

1:  <!--
2:  Reporting Updater
3:
4:  ObjectTypes: 1 - Main Page
5:                2 - Property View
6:                3 - Agent View
7:                4 - Agency View
8:                5 - Community
9:                6 - Specialty Page View
10:               7 - Enhanced Agent Bio
11:               8 - Enhanced Agency Bio
12:               9 - Enhanced Property (OUT)
13:
14:  -->
15:  <cfif isDefined("reportType") and isDefined("reportID")>
16:    <cfparam name="reportAction" default="VIEW">
17:
18:    <cfquery name="qryReport" dataSource="#ap_dataSource#">
19:      insert into reporting
20:        (reportID, reportType, action, userID, browser)
21:      values
22:        (#reportID#, #reportType#, '#reportAction#', '#cgi.remote_addr#', '#cgi.http_user_agent#')
23:    </cfquery>
24:  </cfif>

```

```

1: <!--
2:   Product:   Full Impact
3:   Version:   1.0
4:   History:
5:
6:   -->
7:
8: <!-- Application Settings -->
9: <cfapplication
10:   name="FullImpact"
11:   clientManagement="yes"
12:   clientStorage="clientStorage"
13:   sessionManagement="yes"
14: >
15:
16: <!-- Product Database Information -->
17: <cfset ap_dataSource = "fullImpactAlpha">
18:
19:
20: <!-- Path Information -->
21: <cfset ap_rootPath = "c:\inetpub\multidimension\fullimpact\"> <!-- The root of the application -->
22: <cfset ap_commonImages = "commonImages/"> <!-- Path from root of customer -->
23: <cfset ap_fullCommonImages = "<<COMMONIMAGES>>">
24: <cfset ap_specialtyImages = "specialtyImages\">
25: <cfset ap_agentImages = "agentImages/">
26: <cfset ap_fullAgentImages = "c:\inetpub\multidimension\fullimpact\agentImages\">
27: <cfset ap_agencyImages = "agencyImages/">
28:
29:
30: <cfset ap_commonImages = "<<COMMON IMAGES>>">
31: <cfset ap_agencyImages = "<<AGENCY_IMAGES>>">
32: <cfset ap_agentImages = "<<AGENT_IMAGES>>">
33: <cfset ap_propertyImages = "<<PROPERTY_IMAGES>>">
34: <cfset ap_communityImages = "<<COMMUNITY_IMAGES>>">
35: <cfset ap_specialtyImages = "<<SPECIALTY_IMAGES>>">
36: <cfset ap_enhAgencyImages = "<<ENHAGENCY_IMAGES>>">
37: <cfset ap_enhAgentImages = "<<ENHAGENT_IMAGES>>">
38:
39:
40: <!-- Product Defaults -->
41: <cfset ap_defaultNavColor = "#330099"> <!-- Default navigation background color -->
42: <cfset ap_defaultMenuColor = "#990000"> <!-- Default menu background color -->
43:
44:
45: <!-- Error Handling -->
46: <cfset ap_defaultEmailProblems = "jjunker@techmission.com"> <!-- Default email to send error messages -->
47:

```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
2:
3: <html>
4: <head>
5:   <title><cfoutput>Realty Objects - #ap_distributorName# - Agency Agent List</cfoutput></title>
6:   <link rel="stylesheet" href="clientstyle.css" type="text/css">
7: </head>
8:
9: <cfinclude template="#ap_commonFiles#agencyAgentList.cfm">
10:
```

```
1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3:  <html>
4:  <head>
5:    <title><cfoutput>Realty Objects - #ap_distributorName# - Agent View</cfoutput></title>
6:    <link rel="stylesheet" href="clientStyle.css" type="text/css">
7:  </head>
8:
9:  <cfinclude template="#ap_commonFiles#agentView.cfm">
10:
```

```
1: <!-- Generated Application.cfm -->
2: <!-- Application Settings -->
3: <cfapplication
4:     name="FullImpact"
5:     clientManagement="yes"
6:     clientStorage="clientStorage"
7:     sessionManagement="yes"
8: >
9:
10: <cfset ap_dataSource="fullImpactAlpha">
11:
12:
13: <!-- Distributor Information -->
14: <cfset ap_distributorName = "Yakalo Solution Full Impact Demo">
15: <cfset ap_distributorID = 5>
16:
17:
18:
19: <!-- Path Information -->
20: <cfset ap_commonFiles = "..\..\..\common">
21:
22: <cfset ap_fullAgentImages = "">
23: <cfset ap_fullCommonImages = "">
24:
25: <!-- Path Information -->
26: <cfset ap_rootPath = "c:\inetpub\multidimension\fullimpact\clients\yakalo\demo"> <!-- The root of the application -->
27: <cfset ap_commonImages = "images/">
28: <cfset ap_specialtyImages = "c:\inetpub\multidimension\fullimpact\clients\yakalo\demo\images\specialty">
29: <cfset ap_communityImages = "c:\inetpub\multidimension\fullimpact\clients\yakalo\demo\images\community">
30: <cfset ap_agentBioImages = "c:\inetpub\multidimension\fullimpact\clients\yakalo\demo\images\enhAgent">
31: <cfset ap_agencyBioImages = "c:\inetpub\multidimension\fullimpact\clients\yakalo\demo\images\enhAgency">
32: <cfset ap_resourceImages = "c:\inetpub\multidimension\fullimpact\clients\yakalo\demo\images\resources">
33: <cfset ap_homePageImages = "c:\inetpub\multidimension\fullimpact\clients\yakalo\demo\images\homePage">
34: <cfset ap_propertyImages = "c:\inetpub\multidimension\fullimpact\clients\yakalo\demo\images\property">
35: <cfset ap_agentImages = "c:\inetpub\multidimension\fullimpact\clients\yakalo\demo\images\agent">
36:
37: <!-- Use page formats or not? -->
38: <cfset ap_useFormats = true>
39:
40: <!-- Default colors if page formats are not used -->
41: <cfset ap_defaultNavBarColor = "##0066CC">
42: <cfset ap_defaultNavBarTextColor = "##FFFFFF">
43: <cfset ap_defaultMenuBGColor = "##0066CC">
44: <cfset ap_defaultMenuTextColor = "##FFFFFF">
45: <cfset ap_defaultHeaderBGColor = "##0066CC">
46: <cfset ap_defaultFooterBGColor = "##FFFFFF">
47: <cfset ap_defaultAdBGColor = "##FFFFFF">
48: <cfset ap_defaultSearchBGColor = "##FFFFFF">
49:
```

```
1: a { font-family: verdana, arial, helvetica,sans-serif; color:#990000; font-size: 9pt; }a.nav { font-family: arial, verdana,
helvetica,sans-serif; color:#FFFFFF; font-size: 9pt; font-weight: bold; }a.menu { font-family: arial, verdana,
helvetica,sans-serif; color:#FFFFFF; font-size: 9pt; font-weight: bold; }a.nav:hover { text-decoration: underline;
font-family: arial, verdana, helvetica,sans-serif; color:#fff000; font-size: 9pt; font-weight: bold; }.heading { font-family:
verdana, arial, helvetica,sans-serif; font-size: 10pt; font-weight: bold; color: #ffffff; }a:hover { text-decoration:
underline; font-family: verdana, arial, helvetica,sans-serif; color:#990000; }p, body, th, ul, td { font-family: verdana,
arial, helvetica,sans-serif; font-size: 9pt; }.click_heading { font-family: verdana, arial, helvetica,sans-serif; font-size:
10pt; font-weight: bold; color: #FFFFFF; }.td { font-family: verdana, arial, helvetica,sans-serif; font-size: 9pt; }
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <html>
4: <head>
5: <title><cfoutput>Realty Objects - #ap_distributorName# - Community Search:</cfoutput></title>
6: <link rel="stylesheet" href="clientStyle.css" type="text/css">
7: </head>
8:
9: <cfinclude template="#ap_commonFiles#communitySearch.cfm">
```



```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
2:
3: <html>
4: <head>
5:   <title><cfoutput>Realty Objects - #ap_distributorName# - Community View</cfoutput></title>
6:   <link rel="stylesheet" href="clientStyle.css" type="text/css">
7: </head>
8:
9: <cfinclude template="#ap_commonFiles#communityView.cfm">
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <html>
4: <head>
5:   <title><cfoutput>Realty Objects - #ap_distributorName# - Property Search Results</cfoutput></title>
6:   <link rel="stylesheet" href="clientStyle.css" type="text/css">
7: </head>
8:
9: <cfinclude template="#ap_commonFiles#findPropertyResults.cfm">
10:
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html40/strict.dtd">
2:
3:  <html>
4:  <head>
5:    <title><cfoutput>Realty Objects - #ap_distributorName#</cfoutput></title>
6:    <link rel="stylesheet" href="clientstyle.css" type="text/css">
7:  </head>
8:
9:  <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
10:
11:  <cfset nEntityType = 1> <!-- Main Page = 1 -->
12:  <cfset nEntityID = 0> <!-- Main Page = 0 -->
13:
14:  <cfinclude template="#ap_commonFiles#pageFormat.cfm">
15:
16:  <cfinclude template="#ap_commonFiles#header_bannerad.cfm">
17:
18:
19:  <table width="760" border="0" cellpadding="0" cellspacing="0">
20:    <tr>
21:      <td align="center" valign="top" bgcolor="#cfcfcfcf" width="170">
22:        <cfinclude template="#ap_commonFiles#navigation.cfm">
23:      </td>
24:      <td width="500" valign="top" align="center">
25:        <table border="0" width="480" cellspacing="2">
26:          <tr>
27:            <td class="click_heading" bgcolor="#cfcfcfcf" width="50%">
28:              <a href="#propertySearch.cfm" class="menu">Find a Home</a>
29:            </td>
30:            <td class="click_heading" bgcolor="#cfcfcfcf" width="50%">
31:              <a href="#realtorSearch.cfm" class="menu">Find an Office/Agent</a>
32:            </td>
33:          </tr>
34:        </table>
35:      <td width="50%" valign="top"><p>Search our database of homes for sale in the area.</p><p><enbsp></p></td>
36:      <td width="50%" valign="top"><p>Search for the right Real Estate agent by either Company, Name, Specialty or
        Location.</p><p><enbsp></p></td>
37:    </tr>
38:  </table>
39:  <td class="click_heading" bgcolor="#cfcfcfcf" width="50%">
40:    <a href="#communitySearch.cfm" class="menu">Community Info</a>
41:  </td>
42:  <td class="click_heading" bgcolor="#cfcfcfcf" width="50%">
43:    <a href="#enhancedListings.cfm" class="menu">Enhanced Listings</a>
44:  </td>
45: </tr>
46: <tr>
47:   <td width="50%" valign="top"><p>Find information about your new community.</p><p><enbsp></p></td>
48:   <td width="50%" valign="top"><p>View online home tours of properties.</p><p><enbsp></p></td>

```

```
49: </tr>
50: <cfset nColumn = 1>
51: <cfoutput query="qrySpecialty">
52:   <cfif nColumn is 1>
53:     <tr>
54:       <cfset cDesc1 = qrySpecialty.description>
55:       <cfelse>
56:       <cfset cDesc2 = qrySpecialty.description>
57:       </cfif>
58:       <td class="click_heading" bgcolor="#cMenuBGColor#" width="50%">
59:         <a href="#specialtyPageView.cfm?specialtyPageID=#qrySpecialty.specialtyPageID#"
          class="menu">#qrySpecialty.menuTitle#</a></td>
60:       <cfif nColumn is 2>
61:         </tr>
62:       <tr>
63:         <td width="50%" valign="top"><p>#cDesc1#</p><p><enbsp></p></td>
64:         <td width="50%" valign="top"><p>#cDesc2#</p><p><enbsp></p></td>
65:       </tr>
66:       </cfif>
67:       <cfif nColumn is 1>
68:         <cfset nColumn = 2>
69:       <cfelse>
70:         <cfset nColumn = 1>
71:       </cfif>
72:     </cfoutput>
73:     <cfif nColumn is 2>
74:       <td width="50%"><enbsp></td>
75:       </td>
76:     <tr>
77:       <td width="50%" valign="top"><p><cfoutput>#cDesc1#</cfoutput></p></td>
78:       <td width="50%" valign="top"><enbsp></p></td>
79:     </tr>
80:   </cfif>
81:
82: </table>
83: <table border="0" width="480" cellspacing="2">
84:   <cfinclude template="#ap_commonFiles#footer.cfm">
85: </table>
86:
87: </td>
88: <td valign="top" width="1" bgcolor="#6666ff"></td>
89: <td valign="top" width="4" bgcolor="#ffffff"></td>
90: <td width="120" valign="top">
91:   <cfinclude template="#ap_commonFiles#120x65ads.cfm">
92: </td>
93: </tr>
94: </table>
95:
96:
```

97:       </body>  
98:       </html>  
99:

-----

```
1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
2:
3:  <html>
4:  <head>
5:    <title><cfoutput>Realty Objects - #ap_distributorName# - Enhanced Listings</cfoutput></title>
6:    <link rel="stylesheet" href="clientStyle.css" type="text/css">
7:  </head>
8:
9:  <cfinclude template="#ap_commonFiles#ohListings.cfm">
```

```
1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" "http://www.w3.org/TR/REC-html40/loose.dtd">
2:
3:  <html>
4:  <head>
5:    <title><cfoutput>Realty Objects - #ap_distributorName# - Find a property</cfoutput></title>
6:    <link rel="stylesheet" href="clientStyle.css" type="text/css">
7:  </head>
8:
9:  <cfinclude template="#ap_commonFiles#propertySearch.cfm">
10:
```

```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN" >
2:
3: <html>
4: <head>
5:   <title><cfoutput>Realty Objects - #ap_distributorName# - Property View</cfoutput></title>
6:   <link rel="stylesheet" href="clientStyle.css" type="text/css">
7: </head>
8:
9: <cfinclude template="#ap_commonFiles#propertyView.cfm">
10:
```



```
1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
2:
3: <html>
4: <head>
5:   <title><cfoutput>Realty Objects - #ap_distributorName# - Find an Office/Agent</cfoutput></title>
6:   <link rel="stylesheet" href="clientStyle.css" type="text/css">
7: </head>
8:
9: <cfinclude template="#ap_commonFiles#realtorSearch.cfm">
```

```

1:  <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN">
2:
3:  <!-- If a Agency ID is not passed, then exit -->
4:  <cfif not isDefined("URL.propertyID")>
5:    <cflocation url="propertySearch.cfm" addToken="no">
6:  <cfelse>
7:    <cfset nPropertyID = URL.propertyID>
8:  </cfif>
9:
10:
11:  <cfquery name="qryProperty" dataSource="#ap_dataSource#">
12:    select prop_main.prop_id, prop_main.name, prop_main.address, prop_main.city,
13:    prop_main.state, prop_main.zip, prop_main.price, prop_main.size, prop_main.dscrptn_s,
14:    prop_main.mls_no, prop_main.bedroom, prop_main.bath, prop_main.lotSize,
15:    prop_main.agency_id, prop_main.garage,
16:    statusValues.status, homeTypeValues.homeType, prop_main.agent_id,
17:    agents.firstName, agents.lastName, agents.image_name as agentImage,
18:    agents.website as agentWebSite, agents.email as agentEmail,
19:    agency.name as agencyName, agency.mainImage as agencyImage
20:  from prop_main
21:  join statusValues on statusValues.statusID = prop_main.status
22:  join homeTypeValues on homeTypeValues.homeTypeID = prop_main.homeType
23:  left outer join agents on agents.agent_id = prop_main.agent_id
24:  left outer join agency on agency.agency_id = prop_main.agency_id
25:  where prop_main.prop_id = #url.propertyID#
26: </cfquery>
27:
28:
29:  <cfquery name="qryRooms" dataSource="#ap_dataSource#">
30:    select rooms.roomID, rooms.size, rooms.floor,
31:    roomValues.room, roomValues.sortOrder
32:  from rooms
33:  join roomValues on roomValues.roomID = rooms.roomID
34:  where rooms.propertyID = #url.propertyID#
35:  order by roomValues.sortOrder, roomValues.room
36: </cfquery>
37:
38:  <cfif qryProperty.recordCount is 0>
39:    <cflocation url="propertySearch.cfm" addToken="no">
40:  </cfif>
41:
42:  <cfset nAgencyID = qryProperty.agency_id>
43:
44:  <cfset reportID = url.propertyID>
45:  <cfset reportType = 2>
46:  <cfinclude template="reportUpdate.cfm">
47:
48:  <html>
49:  <head>

```

```

50: <cfoutput>
51: <title>Property Listing for #qryProperty.name#</title>
52: </cfoutput>
53: <link rel="stylesheet" href="style1.css" type="text/css">
54: </head>
55:
56: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
57: <cfoutput>
58:
59: <cfset nEntityType = 4> <!-- Main Page = 1 -->
60: <cfset nEntityID = 0> <!-- Main Page = 0 -->
61: <cfinclude template="pageFormat.cfm">
62:
63: <cfinclude template="header_bannerad.cfm">
64:
65: <table width="760" border="0" cellpadding="0" cellspacing="0">
66: <tr>
67: <td align="right" valign="top" bgcolor="#cNavBGColor#" width="135">
68: <cfinclude template="navigation.cfm">
69: </td>
70: <td width="500" valign="top" align="center">
71: <table border="0" width="480" cellspacing="2">
72: <tr bgcolor="#cccccc">
73: <td align="center">
74: Back to Listings | Printable Page | Add to KEEPERS
75: </td>
76: </tr>
77: <tr><td><b></td></tr>
78:
79: <tr bgcolor="#cccccc">
80: <td align="center">
81: <b>
82: #qryProperty.name# - #qryProperty.status#
83: <cfif ucase(trim(qryProperty.homeType)) is not "NONE">
84: <b> - <b> #trim(qryProperty.homeType)#
85: </cfif>
86: <cfif trim(qryProperty.mls_no) is not "">
87: <b> - <b> (MLS##trim(qryProperty.mls_no))
88: </cfif>
89: </b>
90: </td>
91: </tr>
92:
93: <cfquery name="qryMainImage" dataSource="#ap_dataSource#">
94: select propertyImages.*
95: from propertyImages
96: join imageTypes on imageTypes.imageType = propertyImages.imageType
97: and imageTypes.description = 'Standard Photo'
98: where propertyImages.propertyID = #qryProperty.prop_id#

```

```

99:         order by propertyImages.sortOrder# # # # #
100:     </cfquery>
101:
102:     <cfif qryMainImage.recordCount gt 0>
103:         <cfif fileExists("#qryMainImage.image#")>
104:             <tr>
105:                 <td align="center">
106:                     
107:                 </td>
108:             </tr>
109:         </cfif>
110:         </cfif>
111:         <!-- Insert multiple images here -->
112:
113:     <tr><td>&nbsp;</td></tr>
114:
115:     <tr><td align="center">View Map</td></tr>
116:
117:     <tr><td>&nbsp;</td></tr>
118:     <tr valign="top">
119:         <td align="center">
120:             <b>
121:                 #trim(qryProperty.address)#<br>
122:                 #trim(qryProperty.city)#, #qryProperty.state# #qryProperty.zip#
123:             </b>
124:         </td>
125:     </tr>
126:     <tr valign="top">
127:         <td align="center">
128:             <p>#qryProperty.dscrptn_s#</p>
129:         </td>
130:     </tr>
131:
132:     <tr><td>
133:         <table border="0" cellspacing="2" cellpadding="2" width="100%">
134:             <tr bgcolor="#cMenuBGColor#" class="click_heading">
135:                 <td width="50%">Property Details</td>
136:                 <td width="50%">Room Sizes</td>
137:             </tr>
138:             <tr bgcolor="#cccccc">
139:                 <td width="50%" valign="top">
140:                     #qryProperty.size# Sq. Ft.<br>
141:                     #qryProperty.bedroom# bedroom<cfif qryProperty.bedroom is not 1>s</cfif><br>
142:                     #qryProperty.bath# bathroom<cfif qryProperty.bath is not 1>s</cfif><br>
143:                     <cfif qryProperty.garage gt 0>
144:                         #qryProperty.garage# car garage<br>
145:                     </cfif>
146:                     <br>
147:                 </td>

```



```
197:         </td></tr>
198:     </td></tr>
199:
200:     <cfinclude template="footer.cfm">
201:     </table>
202:     </td>
203:     <td valign="top" width="1" bgcolor="##6666ff"></td>
205:     <td valign="top" width="4" bgcolor="##ffffff"></td>
207:     <td width="120" valign="top">
208:         <cfinclude template="120x65ads.cfm">
209:     </td>
210:     </tr>
211: </table>
212: </cfoutput>
213: </body>
214: </html>
```

```

1: <cfquery name="qrySpecialty" dataSource="#ap_dataSource#">
2:   select distinct specialty
3:   from agents
4:   where specialty <> ''
5:   and agents.distributorID = #ap_distributorID#
6: </cfquery>
7:
8: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
9:
10:  <cfset nEntityType = 4>
11:  <cfset nEntityID = 0>
12:  <cfinclude template="pageFormat.cfm">
13:
14:  <cfinclude template="header_bannerad.cfm">
15:
16:  <table width="760" border="0" cellpadding="0" cellspacing="0">
17:    <tr>
18:      <td align="center" valign="top" bgcolor="#cNavBGColor"><cfoutput>#cNavBGColor</cfoutput> width="170">
19:      <cfinclude template="navigation.cfm">
20:    </td>
21:    <td width="500" valign="top" align="center">
22:      <table border="0" width="480" cellspacing="2">
23:        <tr>
24:          <td bgcolor="#cMenuBGColor"><cfoutput>#cMenuBGColor</cfoutput> class="heading">Find an Office/Agent</td>
25:        </tr>
26:        <tr>
27:          <td>
28:            <blockquote><p>Search for the right real estate agent by either Company, Name, or Specialty.</p></blockquote>
29:            <form action="findAgentResult.cfm" method="post">
30:              <table border="0" cellspacing="0" cellpadding="2" align="center"
31:                bgcolor="#cSearchBGColor"><cfoutput>#cSearchBGColor</cfoutput>#>
32:                <tr><td>Agent Name: </td>
33:                <td><input type="text" value="" name="agentFullName" size="15"></td></tr>
34:                <tr><td>Agency Name: </td>
35:                <td><input type="text" value="" name="agencyName" size="15"></td></tr>
36:                <tr>
37:                  <td><input type="button" value="Search" value="" name="recordCount" value="0">
38:                </td>
39:                <td><input type="button" value="Specialty" value="" name="specialty" value="Specialty">
40:                </td>
41:                <td><input type="button" value="Any Specialty" value="" name="anySpecialty" value="Any Specialty">
42:                </td>
43:                <td><input type="button" value="Specialty" value="" name="specialty" value="Specialty">
44:                </td>
45:                <td><input type="button" value="Any Specialty" value="" name="anySpecialty" value="Any Specialty">
46:                </td>
47:                <td><input type="button" value="Specialty" value="" name="specialty" value="Specialty">
48:                </td>

```

```
49:         <tr>
50:         <td>
51:             <b>nbsp;</td><td colspan="2" align="center"><input type="submit" value="search"> <input type="reset"
52:             value="Reset">
53:         </td>
54:     </table>
55:     </form>
56: </td>
57: </tr>
58: <cfinclude template="footer.cfm">
59: </table>
60: </td>
61: <td valign="top" width="1" bgcolor="#6666ff"></td>
62: <td valign="top" width="4" bgcolor="#ffffff"></td>
63: <td width="120" valign="top">
64:     <cfinclude template="120x65ads.cfm">
65: </td>
66: </tr>
67: </table>
68: </body>
69: </html>
```



```
1: <!---
2:   Reporting Updater
3:
4:   ObjectTypes: 1 - Main Page
5:                 2 - Property View
6:                 3 - Agent View
7:                 4 - Agency View
8:                 5 - Community
9:                 6 - Specialty Page View
10:                7 - Enhanced Agen Bio
11:                8 - Enhanced Agency Bio
12:                9 - Enhanced Property (OHT)
13:
14: -->
15: <cfif isDefined("reportType") and isDefined("reportID")>
16:   <cfparam name="reportAction" default="VIEW">
17:
18:   <cfquery name="qryReport" dataSource="#ap_dataSource#">
19:     insert into reporting
20:       (reportID, reportType, action, userID, browser)
21:     values
22:       (#reportID#, #reportType#, '#reportAction#', '#cgi.remote_addr#', '#cgi.http_user_agent#')
23:   </cfquery>
24: </cfif>
```

```

1: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional/EN" >
2:
3: <cfparam name="cNavColor" default="#ap_defaultNavColor#">
4: <cfparam name="cMenuColor" default="#ap_defaultMenuColor#">
5:
6:
7: <!-- If a community ID is not passed, then exit -->
8: <cfif not isDefined("URL.specialtyPageID")>
9:   <cflocation url="specialtyPageSearch.cfm" addtoken="no">
10: <cfelse>
11:   <cfset nSpecialtyPageID = URL.specialtyPageID>
12: </cfif>
13:
14: <cfquery name="qryPage" dataSource="#ap_dataSource#">
15:   select *
16:   from specialtyPages
17:   where specialtyPages.specialtyPageID = #nSpecialtyPageID#
18: </cfquery>
19:
20: <cfquery name="qryDetail" dataSource="#ap_dataSource#">
21:   select *
22:   from specialtyDetail
23:   where specialtyDetail.specialtyPageID = #nSpecialtyPageID#
24:   order by specialtyDetail.sortOrder, specialtyDetail.title
25: </cfquery>
26:
27:
28: <html>
29: <head>
30: <!--
31: <title><cfoutput>#ap_agencyName# - #qryPropType.mainTitle#</cfoutput></title>
32: ---
33: <title>Specialty Page View</title>
34: <link rel="stylesheet" href="style1.css" type="text/css">
35: </head>
36:
37: <body bgcolor="#ffffff" topmargin="2" leftmargin="4" marginheight="2" marginwidth="4">
38: <cfoutput>
39:
40: <table width="760" border="0" cellpadding="0" cellspacing="0">
41: <tr>
42:   <td align="right" valign="top" bgcolor="#cNavColor#" width="135">
43:     &nbsp;
44:     <!--
45:     <cfinclude template="navigation.cfm">
46:     ---
47:   </td>
48:   <td width="500" valign="top" align="center">
49:     <table border="0" width="480" cellspacing="2">

```

```

50: <tr>
51:   <td bgcolor="#cMenuColor#" class="heading">#qryPage.Name#</td>
52: </tr>
53:
54: <cfloop query="qryDetail">
55:   <tr><td align="#qryDetail.alignment#">
56:     <cfif trim(qryDetail.image) is not "">
57:       <cfif qryDetail.imageType is 1>
58:         
           <cfif lcase(qryDetail.alignment) is "middle">
             </td></tr> <!-- Force paragraph to a new row -->
             <tr><td>
               </cfif>
             </cfif>
           </cfif>
           <cfif trim(qryDetail.title) is not "">
             <h3>#trim(qryDetail.title)#</h3>
           </cfif>
           <cfif trim(qryDetail.text) is not "">
             #paragraphFormat(trim(qryDetail.text))#
           </cfif>
         </td></tr>
       </cfloop>
     </table>
   </td><td>
   </tr>
</table>
</cfoutput>
<!-- <cfinclude template="footer.cfm"> -->
</body>
</html>

```

```
1: <cfif client.userID is -1>
2:   <cflocation url="login.cfm" addtoken="no">
3: </cfif>
```

```
1:  <!-- Delete old field values -->
2:  <cfset deleted = deleteClientVariable("hasOldValues")>
3:  <cfloop index="xField" list="#getClientVariablesList()#">
4:    <cfif left(xField,4) is "old">
5:      <cfset deleted = deleteClientVariable("#xField#")>
6:    </cfif>
7:  </cfloop>
```

```
1:      <cfquery name="qryTruncate" datasource="#ap_datasource#">
2:      delete from securityAccess
3:      </cfquery>
4:
5:
6:
7:      <cfquery name="qryGetEntityID" datasource="#ap_datasource#">
8:      select entityType from entityTypees
9:      where entityTypees.description = 'Yakalo Administrator'
10:     </cfquery>
11:     <cfset nYakaloID = qryGetEntityID.entityTypeID>
12:
13:     <cfquery name="qryGetYakalo" datasource="#ap_datasource#">
14:     select userID from security
15:     where security.userName = 'Yakalo.adm'
16:     </cfquery>
17:     <cfset nYakUserID = qryGetEntityID.entityTypeID>
18:
19:
20:     <cfquery name="qryGetEntityID" datasource="#ap_datasource#">
21:     select entityType from entityTypees
22:     where entityTypees.description = 'Portal'
23:     </cfquery>
24:     <cfset nPortalID = qryGetEntityID.entityTypeID>
25:
26:
27:     <cfquery name="qryGetEntityID" datasource="#ap_datasource#">
28:     select entityType from entityTypees
29:     where entityTypees.description = 'Master Distributor'
30:     </cfquery>
31:     <cfset nMastDistID = qryGetEntityID.entityTypeID>
32:
33:     <cfquery name="qryGetEntityID" datasource="#ap_datasource#">
34:     select entityType from entityTypees
35:     where entityTypees.description = 'Distributor'
36:     </cfquery>
37:     <cfset nDistID = qryGetEntityID.entityTypeID>
38:
39:     <cfquery name="qryGetEntityID" datasource="#ap_datasource#">
40:     select entityType from entityTypees
41:     where entityTypees.description = 'Master Agency'
42:     </cfquery>
43:     <cfset nMastagency_id = qryGetEntityID.entityTypeID>
44:
45:     <cfquery name="qryGetEntityID" datasource="#ap_datasource#">
46:     select entityType from entityTypees
47:     where entityTypees.description = 'Agency'
48:     </cfquery>
49:     <cfset nagency_id = qryGetEntityID.entityTypeID>
```

```

50:         <cfquery name="qryGetEntityID" datasource="#ap_dataSource#">
51:             select entityID from entityTypes
52:             where entityTypes.description = 'Agent'
53:         </cfquery>
54:         <cfset nagent_id = qryGetEntityID.entityType>
55:
56:
57:         <!--- Make securityAccess table -->
58:         <cfquery name="qryInsert" datasource="#ap_dataSource#">
59:             insert into securityAccess
60:             (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
61:             values
62:             (#nyakUserID#, #nyakaloID#, 'Yakalo Solutions Administrator', 0, 0, '#nyakaloID#', 0)
63:         </cfquery>
64:
65:
66:         <!---
67:         <cfquery name="qryPortal" datasource="#ap_dataSource#">
68:             select portals.portalID, portals.name
69:             from portals
70:         </cfquery>
71:         <cfloop query="qryPortal">
72:             <cfquery name="qryInsert" datasource="#ap_dataSource#">
73:                 insert into securityAccess
74:                 (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID, portalID)
75:                 values
76:                 (#nyakUserID#, #nyakaloID#, #portalID#, '#qryPortal.name#', #nyakUserID#, #nyakaloID#,
77:                 '#nyakaloID#.#nyakaloID#.#qryPortal.portalID#', 0, #qryPortal.portalID#)
78:             </cfquery>
79:         </cfloop>
80:         <!---
81:         <!--- Master Distributors
82:         Parents are portals
83:         -->
84:         <cfquery name="qryDist" datasource="thufirREDev">
85:             select distributors.distributorID, distributors.name
86:             from distributors
87:             where distributors.parentID = 0
88:         </cfquery>
89:
90:         <cfloop query="qryDist">
91:             <cfquery name="qryInsert" datasource="#ap_dataSource#">
92:                 ere entityType.description
93:                 (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
94:                 values
95:                 (#qryDist.distributorID#, #nMastDistID#, '#qryDist.name#', #nyakUserID#, #nyakaloID#,
96:                 '#nyakaloID#.#nMastDistID#.#qryDist.distributorID#', #qryDist.distributorID#)
97:             </cfquery>

```

```

97: </cfloop>
98:
99:
100: <!-- Distributors
101: Parents are Master Distributors
102: -->
103:
104: <cfquery name="qryDist" datasource="ThufirREDev">
105: select distributors.distributorID, distributors.name, parentID from distributors
106: where distributors.parentID > 0
107: </cfquery>
108:
109: <cfloop query="qryDist">
110: <cfquery name="qryFindParent" datasource="#ap_dataSource#">
111: select * from securityAccess
112: where securityAccess.entityID = #qryDist.parentID#
113: and securityAccess.entityType = #nMastDistID#
114: </cfquery>
115:
116: <cfquery name="qryInsert" datasource="#ap_dataSource#">
117: insert into securityAccess
118: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
119: values
120: (#qryDist.distributorID#, #nDistID#, '#qryDist.name#', #qryDist.parentID#, #qryFindParent.entityType#,
121: '#qryFindParent.hierarchyID#.#nDistID#.#qryDist.distributorID#', #qryDist.distributorID#)
122: </cfquery>
123: </cfloop>
124:
125: <!-- agencies -->
126: <cfquery name="qryAgency" datasource="ThufirREDev">
127: select agency.agency_id, agency.name, agency.distributorID from agency
128: where agency.parentAgency = 0 and agency.distributorid > 0
129: </cfquery>
130:
131: <cfloop query="qryAgency">
132: <cfquery name="qryFindParent" datasource="#ap_dataSource#">
133: select * from securityAccess
134: where securityAccess.entityID = #qryAgency.distributorID#
135: and (securityAccess.entityType = #nMastDistID# or securityAccess.entityType=#nDistID#)
136: </cfquery>
137:
138: <cfquery name="qryInsert" datasource="#ap_dataSource#">
139: insert into securityAccess
140: (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
141: values
142: (#qryAgency.agency_id#, #nMastAgency_id#, '#qryAgency.name#', #qryAgency.distributorID#, #qryFindParent.entityType#,
143: '#qryFindParent.hierarchyID#.#nMastAgency_id#.#qryAgency.agency_id#', #qryAgency.distributorID#)
144: </cfquery>

```



```

144: </cfloop>
145:
146:
147: <cfquery name="qryAgency" datasource="ThufirREDev">
148:   select agency.agency_id, agency.name, agency.distributorID, agency.parentAgency
149:   from agency
150:   where agency.parentAgency > 0 and distributorID > 0
151: </cfquery>
152:
153: <cfloop query="qryAgency">
154:   <cfquery name="qryFindParent" datasource="#ap_dataSource#">
155:     select * from securityAccess
156:     where securityAccess.entityID = #qryAgency.parentAgency#
157:     and securityAccess.entityType = #nMastagency_id#
158:   </cfquery>
159:
160:   <cfquery name="qryInsert" datasource="#ap_dataSource#">
161:     insert into securityAccess
162:     (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
163:     values
164:     (#qryAgency.agency_id#, #nagency_id#, '#qryAgency.name#', #qryAgency.parentAgency#, #qryFindParent.entityType#,
165:      '#qryFindParent.hierarchyID#.#nagency_id#.#qryAgency.agency_id#', #qryAgency.distributorID#)
166:   </cfquery>
167: </cfloop>
168:
169: <cfquery name="qryAgency" datasource="ThufirREDev">
170:   select agency.agency_id, agency.name, agency.distributorID, agency.parentAgency
171:   from agency
172:   where agency.parentAgency = 0 and agency.distributorID = 0
173: </cfquery>
174:
175: <cfloop query="qryAgency">
176:   <cfquery name="qryFindParent" datasource="#ap_dataSource#">
177:     select * from securityAccess
178:     where securityAccess.entityID = #nYakUserID#
179:     and securityAccess.entityType = #nYakaloID#
180:   </cfquery>
181:
182:   <cfquery name="qryInsert" datasource="#ap_dataSource#">
183:     insert into securityAccess
184:     (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
185:     values
186:     (#qryAgency.agency_id#, #nagency_id#, '#qryAgency.name#', #qryFindParent.entityID#, #nYakaloID#,
187:      '#qryFindParent.hierarchyID#.#nagency_id#.#qryAgency.agency_id#', #qryAgency.distributorID#)
188:   </cfquery>
189: </cfloop>
190:
191: <cfquery name="qryAgency" datasource="ThufirREDev">

```

```

191: select agency.agency_id, agency.name, |agency_id is distributor_id, agency.parentAgency
192: from agency
193: where agency.parentAgency > 0 and agency.distributorID = 0
194: </cfquery>
195:
196: <cfloop query="qryAgency">
197:   <cfquery name="qryFindParent" dataSource="#ap_dataSource#">
198:     select * from securityAccess
199:     where securityAccess.entityID = #qryAgency.parentAgency#
200:     and securityAccess.entityType = #nMastagency_id#
201:   </cfquery>
202:
203:   <cfquery name="qryInsert" dataSource="#ap_dataSource#">
204:     insert into securityAccess
205:     (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
206:     values
207:     (#qryAgency.agency_id#, #nagency_id#, 'qryAgency.name', #qryAgency.parentAgency#, #qryFindParent.entityType#,
208:      '#qryFindParent.hierarchyID#.#nagency_id#.#qryAgency.agency_id#', #qryAgency.distributorID#)
209:   </cfquery>
210: </cfloop>
211:
212: <!--- Agents --->
213: <cfquery name="qryAgents" dataSource="ThufirREDev">
214:   select agents.agent_id, agents.firstname + ' ' + agents.lastname as name, agents.agency_id, agents.distributorID
215:   from agents
216:   where agency_id > 0
217: </cfquery>
218:
219: <cfloop query="qryAgents">
220:   <cfquery name="qryFindParent" dataSource="#ap_dataSource#">
221:     select * from securityAccess
222:     where securityAccess.entityID = #qryAgents.agency_id#
223:     and (securityAccess.entityType = #nMastagency_id# or securityAccess.entityType=#nagency_id#)
224:   </cfquery>
225:
226:   <cfif qryFindParent.recordCount gt 0>
227:     <cfquery name="qryInsert" dataSource="#ap_dataSource#">
228:       insert into securityAccess
229:       (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
230:       values
231:       (#qryAgents.agent_id#, #nagent_id#, '#qryAgents.name', #qryAgents.agency_id#, #qryFindParent.entityType#,
232:        '#qryFindParent.hierarchyID#.#nagent_id#.#qryAgents.agent_id#', #qryAgents.distributorID#)
233:     </cfquery>
234:   <cfelse>
235:     <cfquery name="qryFindParent" dataSource="#ap_dataSource#">
236:       select * from securityAccess
237:       where securityAccess.entityID = #nYakUserID#
238:       and securityAccess.entityType = #nYakaloID#

```

```

238: </cfquery>
239:
240: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
241:   insert into securityAccess
242:     (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
243:     values
244:     (#qryAgents.agent_id#, #nagent_id#, '#qryAgents.name#', #qryFindParent.entityID#, #nYakaloID#,
      '#qryFindParent.hierarchyID#.#nagent_id#.#qryAgents.agent_id#', #qryAgents.distributorID#)
245:   </cfquery>
246: </cfif>
247: </cfloop>
248:
249: <cfquery name="qryAgents" dataSource="ThufirREDev">
250:   select agents.agent_id, agents.firstname + ' ' + agents.lastname as name, agents.agency_id, agents.distributorID
251:   from agents
252:   where agents.agency_id = 0
253:   and agents.distributorID > 0
254: </cfquery>
255:
256: <cfloop query="qryAgents">
257:   <cfquery name="qryFindParent" dataSource="#ap_dataSource#">
258:     select * from securityAccess
259:     where securityAccess.entityID = #qryAgents.distributorid#
260:     and (securityAccess.entityType = #nMastDistID# or securityAccess.entityType=#nDistID#)
261:   </cfquery>
262:
263:   <cfquery name="qryInsert" dataSource="#ap_dataSource#">
264:     insert into securityAccess
265:       (entityID, entityType, name, parentID, parentType, hierarchyID, distributorID)
266:       values
267:       (#qryAgents.agent_id#, #nagent_id#, '#qryAgents.name#', #qryAgents.distributorID#, #qryFindParent.entityType#,
        '#qryFindParent.hierarchyID#.#nagent_id#.#qryAgents.agent_id#', #qryAgents.distributorID#)
268:   </cfquery>
269: </cfloop>
270:

```

```

1: <cfparam name="updateSecurityID" default="#updateSecurityID#">
2: <cfparam name="updateSecurityType" default="#updateSecurityType#">
3: <cfparam name="securityAction" default="EDIT">
4:
5: <cfset securityAction = ucase(securityAction)>
6:
7: <cfif nUpdateType is ap_securityYakalo>
8:   <cfinclude template="makeSecurityTree.cfm">
9: <cfelseif nUpdateType is ap_securityPortal>
10:   <cfinclude template="makeSecurityTree.cfm">
11: <cfelseif nUpdateType is ap_securityMastDist>
12:   <cfinclude template="makeSecurityTree.cfm">
13: <cfelseif nUpdateType is ap_securityDist>
14:   <cfinclude template="makeSecurityTree.cfm">
15: <cfelse>
16:
17:   <!--- Mark dirty records of parent and all children --->
18:   <cfquery name="qryParent" dataSource="#ap_dataSource#">
19:     select entityID, entityType, hierarchyID
20:     from securityAccess
21:     where securityAccess.entityID = #nUpdateID#
22:     and securityAccess.entityType = #nUpdateType#
23:   </cfquery>
24:
25:   <cfquery name="qryDirty" dataSource="#ap_dataSource#">
26:     update securityAccess
27:     set dirty='Y'
28:     where securityAccess.hierarchyID like '#qryParent.hierarchyID#%'
29:   </cfquery>
30:
31:
32:   <!--- Update Agents --->
33:   <cfquery name="qryInsert" dataSource="#ap_dataSource#">
34:     update securityAccess
35:     set name = p.name,
36:         parentID = s.entityID,
37:         parentType = s.entityType,
38:         hierarchyID = s.hierarchyID+entityType + '.' + entityID
39:     from
40:         agents p
41:     join securityAccess s on agents.agency_id = s.entityID
42:     and (s.entityType = ap_securityMastAgency or s.entityType = ap_securityAgency)
43:     where
44:         securityAccess.dirty = 'Y'
45:         and securityAccess.entityType = #ap_securityAgent#
46:         and p.agent_id = securityAccess.entityID
47:         and p.agency_id > 0
48:         and p.distributorID > 0
49:   </cfquery>

```

```

50:
51:
52: </cfif>
53:
54:
55:
56: <!-- * Agencies * -->
57:
58: <!-- Master Agencies w/ Distributors -->
59: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
60:   insert into SecurityAccess
61:     (entityID, entityType, name, parentID, parentType, distributorID, hierarchyID)
62:   select agency_id as entityID, #ap_securityMastAgency# as entityType, agency.name,
63:     agency.distributorID,
64:     agency.distributorID as parentID,
65:     p.entityType as parentType, p.hierarchyID+'#ap_securityMastAgency#'+convert(varchar,agency.agency_id)+'.' as hierarchyID
66:   from agency
67:   join securityAccess p on p.entityID = agency.distributorID
68:     and (p.entityType = #ap_securityMastDist# or p.entityType = #ap_securityDist#)
69:   where agency.parentAgency = 0
70:   and agency.distributorID > 0
71: </cfquery>
72:
73: <!-- Master Agencies w/ Distributors -->
74: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
75:   insert into SecurityAccess
76:     (entityID, entityType, name, parentID, parentType, distributorID, hierarchyID)
77:   select agency_id as entityID, #ap_securityMastAgency# as entityType, agency.name,
78:     agency.distributorID, #ap_securityYakalo# as parentID, #ap_securityYakalo# as parentType,
79:     p.hierarchyID+'#ap_securityMastAgency#'+convert(varchar,agency.agency_id)+'.' as hierarchyID
80:   from agency
81:   join securityAccess p on p.entityID = agency.distributorID
82:     and p.entityType = #ap_securityYakalo#
83:   where agency.parentAgency = 0
84:   and agency.distributorID = 0
85: </cfquery>
86:
87: <!-- Agencies w/ Master Agency and w/Distributor -->
88: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
89:   insert into SecurityAccess
90:     (entityID, entityType, name, parentID, parentType, distributorID, hierarchyID)
91:   select agency_id as entityID, #ap_securityAgency# as entityType, agency.name,
92:     agency.distributorID,
93:     agency.parentAgency as parentID,
94:     p.entityType as parentType, p.hierarchyID+'#ap_securityAgency#'+convert(varchar,agency.agency_id)+'.' as hierarchyID
95:   from agency
96:   join securityAccess p on p.entityID = agency.parentAgency
97:     and p.entityType = #ap_securityAgency#
98:   where agency.parentAgency > 0

```

```

99: and agency.distributorID > 0
100: </cfquery>
101:
102: <!-- Agencies w/Master Agency and w/o Distributor-->
103: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
104: insert into SecurityAccess
105: (entityID, entityType, name, parentID, parentType, distributorID, hierarchyID)
106: select agency_id as entityID, #ap_securityAgency# as entityType, agency.name,
107: agency.distributorID, #ap_securityYakalo# as parentID,
108: p.entityType as parentType, p.hierarchyID+'#ap_securityAgency#'+convert(varchar,agency.agency_id)+'.' as hierarchyID
109: from agency
110: join securityAccess p on p.entityID = #ap_securityYakalo#
111: and p.entityType = #ap_securityYakalo#
112: where agency.parentAgency > 0
113: and agency.distributorID = 0
114: </cfquery>
115:
116:
117:
118: <!-- Agent w/No Agency * * * -->
119:
120: <!-- Agent w/No Agency -->
121: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
122: insert into SecurityAccess
123: (entityID, entityType, name, parentID, parentType, distributorID, hierarchyID)
124: select agents.agent_id as entityID, #ap_securityAgent# as entityType,
125: agents.firstName + ' ' + agents.lastName as name,
126: agents.distributorID, agents.agency_id as parentID,
127: p.entityType as parentType, p.hierarchyID+'#ap_securityAgent#'+convert(varchar,agents.agent_id)+'.' as hierarchyID
128: from agents
129: join securityAccess p on p.entityID = agents.agency_id
130: and (p.entityType = #ap_securityMastAgency# or p.entityType = #ap_securityAgency#)
131: where agents.agency_id > 0
132: and agents.distributorID > 0
133: </cfquery>
134:
135: <!-- Unaffiliated Agents -->
136: <cfquery name="qryInsert" dataSource="#ap_dataSource#">
137: insert into SecurityAccess
138: (entityID, entityType, name, parentID, parentType, distributorID, hierarchyID)
139: select agents.agent_id as entityID, #ap_securityAgent# as entityType,
140: agents.firstName + ' ' + agents.lastName as name,
141: agents.distributorID, agents.agency_id as parentID,
142: p.entityType as parentType, p.hierarchyID+'#ap_securityAgent#'+convert(varchar,agents.agent_id)+'.' as hierarchyID
143: from agents
144: join securityAccess p on p.entityID = agents.distributorID
145: and (p.entityType = #ap_securityNoAgency#)
146: where agents.agency_id = 0
147: and agents.distributorID > 0

```

</cfquery>

148:  
149:  
150:

148:  
149:  
150: